METRIC

A-A-52572A
July 31, 2003
A-A-52572

JANUARY 30, 1998

COMMERCIAL ITEM DESCRIPTION

CUTTERS; PAPER, GUILLOTINE: FLOOR MODEL, ELECTRIC-MOTOR-DRIVEN

The General Services Administration has authorized the use of this Commercial Item Description (CID) for all federal agencies. The original issue of this CID replaced MIL-C-43141.

1. SCOPE

1.1 Scope. This commercial item description covers electric-motor-driven paper cutters for cutting, squaring, and trimming stacks of paper by a guillotine action of the cutting blade.

2. CLASSIFICATION

2.1 Size. The paper cutters shall conform to the following sizes, for the throat width, as specified (see 6.3). See Table I, following page.

Beneficial comments, recommendations, additions, deletions, clarifications etc., and any other data which may improve this document should be sent to: ENGINEER RESEARCH AND DEVELOPMENT CENTER, CORPS OF ENGINEERS, U.S. ARMY TOPOGRAPHIC ENGINEERING CENTER, ATTN CEERD-TS, 7701 TELEGRAPH ROAD, ALEXANDRIA, VA 22315-3864.

AMSC N/A FSC 3610

Distribution Statement A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:13Z
Check the source to verify that this is the current version before use.

Table I. Cutter Sizes

Size 1 - 463.55 mm (18.25 inch) minimum - 508.0 mm (20.00 inch) maximum	Size 5 - 1473.2 mm (58.00 inch) minimum - 1625.6 mm (64.00 inch) maximum
Size 2 - 584.2 mm (23.00 inch) minimum - 685.8 mm (27.00 inch) maximum	Size 6 - 1651.0 mm (65.00 inch) minimum - 2260.6 mm (89.00 inch) maximum
Size 3 - 774.7 mm (30.50 inch) minimum - 1143.0 mm (45.00 inch) maximum	Size 7 - 2286.0 mm (90.00 inch) minimum - 2819.4 mm (111.00 inch) maximum
Size 4 - 1181.1 mm (46.50 inch) minimum - 1447.8 mm (57.00 inch) maximum	

2.2 Class. The paper cutters shall conform to the following classes, for operating power, as specified (see 6.3).

Class A - 115-volt, alternating current
Class B - 208-volt, alternating current
Class C - 220-volt, alternating current

2.3 Grade. The paper cutters shall conform to the following grades, for operating power, as specified (see 6.3).

Grade 1 - 50 Hertz, (cycle per second)
Grade 2 - 60 Hertz, (cycle per second)

3. SALIENT CHARACTERISTICS

3.1 Description. Each paper cutter shall consist of a base and frame, a cutting table, a knife bar and cutting knife, cutting sticks, a paper clamp, back and side gauges, and safety guards and locks.

3.2 Fungus and moisture resistance. Materials selected for fabrication of the paper cutters shall be fungus-inert (see 7.8.1) or shall be treated with a commercially accepted, moisture and fungus-proofing compound. Electrical circuitry and components susceptible to fungus and moisture damage shall be hermetically sealed or otherwise coated for protection.

3.3 Identification of materials and finishes. The contractor shall identify and document the specific material and material finish or treatment of all components and sub-components.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:13Z
Check the source to verify that this is the current version before use.

3.4 Treatment and painting. Unless otherwise specified (see 7.3), or unless the material is inherently corrosion resistant, the paper cutters shall be treated and painted for corrosion protection using the contractor's standard practice.

3.5 Capacities and dimensions. Capacities and dimensions for the paper cutters shall be as specified in table II.

TABLE II. Capacities, dimensions, and weights.

Capacity, dimension, and weight	Size						
	1	2	3	4	5	6	7
Throat width:							
Minimum mm	463.55	584.20	774.70	1181.10	1473.20	1651.00	2286.00
(inches)	(18.25)	(23.00)	(30.50)	(46.500)	(58.00)	(65.00)	(90.00)
Maximum mm	508.00	685.80	1143.00	1447.80	1625.60	2260.60	2819.4
(inches)	(20.00)	(27.00)	(45.00)	(57.00)	(64.00)	(89.00)	(111.00)
Clearance under clamp (pile height):							
Maximum mm	76.20	101.60	152.40	177.80	177.80	177.80	203.20
(inches)	(3.00)	(4.00)	(6.00)	(7.00)	(7.00)	(7.00)	(8.00)
Back gauge from knife Far limit:							
Minimum mm	463.55	584.20	774.70	1181.10	1473.20	1651.00	2286.00
(inches)	(18.25)	(23.00)	(30.50)	(46.50)	(58.00)	(65.00)	(90.00)
Back gauge from knife; Near limit:							
Maximum mm	12.70	19.05	19.05	19.05	19.05	19.05	25.40
(inches)	(.50)	(.75)	(.75)	(.75)	(.75)	(.75)	(1.00)
Back gauge indicator increment:							
Maximum mm	1.588	1.588	1.588	1.588	1.588	1.588	1.588
(inches)	(.0625)	(.0625)	(.0625)	(.0625)	(.0625)	(.0625)	(.0625)
Front of table to knife:							
Minimum mm	311.15	469.90	457.20	533.40	482.60	533.40	635.00
(inches)	(12.25)	(18.50)	(18.00)	(21.00)	(19.00)	(21.00)	(25.00)
Maximum mm	406.40	476.25	508.00	635.00	635.00	736.60	762.00
(inches)	(16.00)	(18.75)	(20.00)	(25.00)	(25.00)	(29.00)	(30.00)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:13Z
Check the source to verify that this is the current version before use.

TABLE II. Capacities, dimensions, and weights. (continued)

Capacity, dimension, and weight	Size						
	1	2	3	4	5	6	7
rule graduations:							
mm	-	1.588	1.588	1.588	1.588	1.588	1.588
(inches)	-	(.0625)	(.0625)	(.0625)	(.0625)	(.0625)	(.0625)
Height of tabletop:							
Minimum mm	863.60	863.60	863.60	952.50	939.80	939.80	939.80
(inches)	(34.00)	(34.00)	(34.00)	(37.50)	(37.00)	(37.00)	(37.00)
Maximum mm	914.40	939.80	952.50	990.60	1016.00	1016.00	1016.00
(inches)	(36.00)	(37.00)	(37.50)	(39.00)	(40.00)	(40.00)	(40.00)
Width, floor space:							
Maximum mm	914.40	1498.60	3124.20	3454.40	3581.40	3733.80	4394.20
(inches)	(36.00)	(59.00)	(123.00)	(136.00)	(141.00)	(147.00)	(173.00)
Depth, floor space:							
Maximum mm	1270.00	1600.20	2489.20	3098.80	3251.20	3810.00	4394.20
(inches)	(50.00)	(63.00)	(98.00)	(122.00)	(128.00)	(150.00)	(173.00)
Weight:							
Maximum Kg.	410.50	907.18	4535.90	4535.90	6350.30	6803.90	9979.00
(pounds)	(905)	(2,000)	(10,000)	(10,000)	(14,000)	(15,000)	(22,000)

3.6 Base and frame. The base and frame shall be of material and construction capable of supporting the assembled paper cutter, and shall assure a rigid and firm structure for all operating parts. Mounting holes shall be provided to permit bolting of the assembly to a supporting surface.

3.7 Cutting table. The cutting table shall have a smooth and plane surface with not more than a ± 0.076 mm (0.003 inch) variation in a 304.80 mm (12.00 inch) distance, and not more than a ± 0.127 mm (0.005 inch) variation overall. When specified (see 7.3), indication rule graduations shall be provided on the working surface in front of the knife. A recess shall be provided on the surface for holding the cutting stick (see 3.10), and shall extend the full width of the surface beneath the edge of the cutting knife. The recess shall be slightly off-center from the cutting knife edge to extend the serviceable life of the cutting stick. The surface shall have an illuminated working area and, when specified (see 7.3), shall include an illuminated cut-line indicator.

3.8 Knife bar. The knife bar shall solidly seat the cutting knife and shall have adjusting and leveling devices to permit adjustment of the cutting knife edge to the cutting stick when the bottom of the cutting stroke has been reached, and to ensure correct contact of the cutting blade.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:13Z
Check the source to verify that this is the current version before use.

3.9 Cutting knife. Each paper cutter shall be supplied with not less than two cutting knives. One cutting knife shall be solidly seated and bolted in the knife bar, and remaining cutting knives shall be maintained as spares. The cutting edge of the knife shall produce clean, sharp cut edges. Storage safety and edge guards shall be provided with each cutting knife for use in removal, replacement, and storage (see 3.13). Not less than two separate settings shall be provided on the cutting knife to compensate for wear.

3.10 Cutting sticks. Not less than 36 cutting sticks shall be provided with each paper cutter. The cutting sticks shall be of hardwood or plastic fabrication and shall fit snugly within the recess provided on the surface of the cutting table.

3.11 Paper clamp. The paper clamp shall be capable of exerting sufficient pressure on the paper stock to ensure accuracy during the cutting operation. A gauge shall be provided to indicate clamp adjustment and pressure amount. A detachable sole plate capable of covering the width of the clamping surface shall be provided with the paper clamp.

3.12 Gauges.

3.12.1 Back gauge. The back gauge may be manually operated, power, or motor-driven and shall maintain the setting when adjusted to any distance from the cutting knife within the range specified in table I. An illuminated dial for measuring the distance between the back gauge and the cutting knife shall be provided, and shall have an accuracy of 0.254 mm (0.01 inch). The location of the dial shall be readable from the operator's position. A locking device shall be provided to secure the back gauge setting against movement during the cutting operation. A means for adjusting, controlling, and locking the back gauge shall be located on the front of the paper cutter.

3.12.2 Side gauges. Right and left side gauges shall be fixed to the cutting table and be spaced to comply with the applicable throat widths specified in table I. Height of the side gauges shall not be less than the applicable pile heights specified in table I. The working plane of the side gauges shall be square with the cutting table and the cutting knife edge.

3.13 Safety. All moving or sharp parts presenting a hazard to personnel shall be fully enclosed or guarded. Each paper cutter shall be provided with a safety lock to hold the knife in the "up" position at the conclusion of each cutting stroke. Release of the safety lock shall require the simultaneous use of both hands by the operator to start the cutting stroke. A built-in, non-repeat device shall be provided to limit each cutting operation to one stroke. An overload safety device shall be provided to limit or disengage power when the knife strikes a hard foreign object on the downward stroke. Protective devices shall not impair operating functions. Safety markings and labels shall be provided identifying any potential hazards to personnel and comply with the requirements of ANSI Z535.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:13Z
Check the source to verify that this is the current version before use.

3.14 Electrical requirements. All electrical equipment and wiring shall conform to NFPA No. 70, National Electrical Code. Operators shall not access to components with voltages exceeding 30V.

3.14.1 Motors. Electric motors shall conform to NEMA Standard MG-1, Motors and Generators.

3.15 Maintainability. All major assemblies and installed attachments shall be accessible for maintenance, repair, and replacement without removal of other major assemblies and installed attachments. Covers and plates that must be removed for component adjustment, repair, replacement, or maintenance shall be equipped with quick-disconnect fastenings.

3.16 Interchangeability. All parts having the same part number shall be functionally and dimensionally interchangeable (see 7.8.2).

3.17 Human factors engineering. The paper cutters shall conform to the design requirements of ASTM F 1166. Special emphasis shall be given but not limited to: Significance and Use (4), Control/Display Integration (5), Visual Displays (6), Controls (21), Labeling (27), Anthropometry (30), Design for Maintainability (33), and Hazard and Safety (51) sections of ASTM F 1166, as applicable. The design shall foster effective performance of operating procedures, an effective personnel safety and health environment, and minimize factors that contribute to increased operator error. The design shall incorporate protection from toxic, electrical, thermal, mechanical, and other potential hazards.

3.18 Noise limits. Steady-state noise produced by the paper cutters shall conform to SAE J1074. If procedures for noise suppression have been pursued and documented to the satisfaction of the procuring activity and written permission to exceed 85 dB(A) is obtained, hazard signs shall conform to ANSI Z 535.2, and shall state “HEARING PROTECTION REQUIRED WITHIN (specify) FEET.” The signs shall be legible from the distance specified on the signs.

3.19 Instruction plates. Special or important procedures to be followed in operating and servicing the paper cutter shall be placed on instruction plates to include all applicable warnings and cautions, and may include diagrams. The plates shall be placed in a protected, readily visible area on a non-working surface, shall be permanently attached, and shall remain legible for the life expectancy of the paper cutter.

3.20 Lubrication. All components requiring lubrication shall be lubricated and provided with suitable means of lubrication prior to delivery. Fittings shall be self-sealing and located to facilitate access using standard lubricating equipment.

3.20.1 Pressure-release device. A pressure-release device shall be provided where the use of pressure lubricating equipment could damage grease seals or other parts.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:13Z
Check the source to verify that this is the current version before use.

3.21 Identification marking. Each paper cutter shall have identification plates attached by metal fasteners in a conspicuous, protected location. The location of the plates shall not interfere with the operation and maintenance of the paper cutter. The paper cutter shall be identified by manufacturer's name and part number, serial number, and contract number.

3.22 Inch-pound products. Products manufactured to inch-pound dimensions will be considered on an equal basis with those manufactured using metric units, provided they fall within specified tolerances and all other requirements of this commercial item description are met. The contracting officer has the option of accepting or rejecting the product.

4. REGULATORY REQUIREMENTS

4.1 Recovered materials. The offerer/contractor is encouraged to use recovered materials (see 7.8.3) to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR).

5. QUALITY ASSURANCE PROVISIONS

5.1 Product conformance. The products provided shall meet the salient characteristics of this CID, conform to the producer’s own drawings, specifications, standards, and quality assurance practices, and be the same product offered for sale in the commercial marketplace. The government reserves the right to require proof of such conformance.

5.2 Market acceptability. The products offered shall be of the latest model of the standard product of the supplier, and shall have been used in the field for at least one year by commercial organizations.

5.3 Examinations. Each paper cutter shall be examined for compliance with the requirements specified in 3.2 through 3.22. Any modification necessary following failure to meet the specified requirements shall receive particular attention for adequacy and suitability. This element of inspection shall encompass all examinations of performance and dimensional requirements. Non-compliance to any specified requirement or the presence of one or more defects shall constitute cause for rejection.

6. PACKAGING

6.1 Preservation, packing, and marking shall be as specified in the contract or order.

7. NOTES

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:13Z
Check the source to verify that this is the current version before use.

7.1 Intended use. The paper cutters are intended to be used for cutting, squaring, and trimming stacks of paper for printing of maps, forms, and miscellaneous documents in both fixed-sites and mobile van environments.

7.2 When this Commercial Item Description is used for procurement, the product conformance clause should appear in the solicitation.

7.3 Ordering data. Procurement documents should specify the following:

a. Title, number, and date of this CID.

b. Size of paper cutter required (see 2.1).

c. Class of electric power required (see 2.2).

d. Grade of electric power required (see 2.3).

e. When treatment and painting shall be other than standard practice (see 3.4).

f. Indication rule graduations required (see 3.7)

g. Illuminated cut-line indicator required (see 3.7).

h. Level of preservation and packing required.

7.4 Data requirements. The contracting officer should include, in the contract or order, any data requirements, such as maintenance and operation manuals, instructional materials, and technical publications to be furnished with each paper cutter.

7.5 Provisioning. The contracting officer should include, in the contract or order, provisioning requirements for repair parts, maintenance tools (including any special tools), as necessary; and instructions regarding shipment of the paper cutters.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:13Z
Check the source to verify that this is the current version before use.

7.6 Part Identification Number (PIN). The following part identification numbering procedure is for government purposes and does not constitute a requirement for the contractor.
This example describes a part numbering system for CID A-A-52572.

AA52572-1A1

- Grade: 1 or 2
- Class: A, B, or C
- Size: 1 - 7

7.7 Source of documents.

7.7.1 Copies of ANSI specifications are available from the American National Standards Institute, 1430 Broadway, New York, NY 10018.

7.7.2 Copies of ASTM specifications are available from the American Society for Testing and Materials, 1916 Race Street, Philadelphia PA 19103.

7.7.3 Copies of NEMA specifications are available from the National Electrical Manufacturers Association, 2101 L Street NW, Washington, DC 20037.

7.7.4 Copies of NFPA specifications are available from the National Fire Protection Association, Batterymarch Park, Quincy, MA 02269.

7.7.5 Copies of SAE specifications are available from the Society of Automotive Engineers, Inc., 400 Commonwealth Drive, Warrendale, PA 15096-0001.

7.8 Definitions. For the purposes of this CID, the following definitions apply.

7.8.1 Fungus-inert. A fungus inert material is a material that is not a nutrient to fungi.

7.8.2 Interchangeable parts. Interchangeable parts are defined as two or more parts possessing functional and physical characteristics equivalent in performance and durability. These parts are capable of being exchanged one for the other without alteration of the parts; of mating or adjoining parts, except for adjustment; and without selection for fit or performance.

7.8.3 Recovered materials. Recovered materials are those that have been collected from solid waste and reprocessed to become a source of raw materials, as distinguished from virgin raw materials.

7.9 National Stock Number (NSN). The NSN 3610-01-236-9998 has been used in the past to procure a Size 3, Class C, Grade 2 Cutter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:13Z
Check the source to verify that this is the current version before use.

7.10 Subject term (key words) listing.
Paper cutter

Custodians:
Army - CE3
DLA-GS

Preparing activity:
Army - CE3
(Project 3610-0430)

Review activity:
ARMY-CR

Civilian coordinating agency:
GSA-FSS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:13Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7, and send to preparing activity.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER	2. DOCUMENT DATE *(YYYYMMDD)*
	A-A-52572A	**20030731**

3. DOCUMENT TITLE
CUTTERS; PAPER, GUILLOTINE: FLOOR MODEL, ELECTRIC-MOTOR-DRIVEN

4. NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed)*

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME *(Last, First, Middle Initial)*	b. ORGANIZATION	
c. ADDRESS *(Include Zip Code)*	d. TELEPHONE *(Include Area Code)* (1) Commercial (2) DSN *(If applicable)*	7. DATE SUBMITTED *(YYYYMMDD)*

8. PREPARING ACTIVITY

a. NAME	b. TELEPHONE (*Include Area Code*)	
U.S. ARMY TOPOGRAPHIC ENGINEERING CENTER	(1) Commercial (703) 428-6862	(2) DSN 328-6862
c. ADDRESS (*Include Zip Code*) ATTN: CEERD-TS-T 7701 TELEGRAPH ROAD ALEXANDRIA, VA 22315-3864	**IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT:** **Defense Standardization Program Office (DLSC-LM)** **8725 John J. Kingman Road, Suite 2533** **Fort Belvoir, Virginia 22060-6221** **Telephone (703) 767-6888 DSN 427-6888**	

DD Form 1426, FEB 1999 (EG) PREVIOUS EDITIONS OBSOLETE

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:13Z
Check the source to verify that this is the current version before use.