INCH-POUND
MIL-C-87217
AMENDMENT 4
23 February 1994
SUPERSEDING
AMENDMENT 3
29 October 1991

MILITARY SPECIFICATION

CAPACITORS, FIXED, SUPERMETALLIZED PLASTIC FILM DIELECTRIC, DIRECT CURRENT FOR LOW ENERGY, HIGH IMPEDANCE APPLICATIONS, HERMETICALLY SEALED IN METAL CASES, HIGH RELIABILITY, GENERAL SPECIFICATION FOR

This amendment forms a part of MIL-C-87217, dated 11 March 1985, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

* Bottom of page, delete and substitute the following:

"

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Air Force Material Command, 645 LOG/LGME, Gentile Station, 1060 Hamilton Street, Dayton, OH 45444-5400 by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

"

PAGE 2

* STANDARDS, MILITARY: Delete "MIL-STD-105" and its title.

* STANDARDS, MILITARY: Add "MIL-STD-45662 - Calibration Systems Requirement."

3.2, delete and substitute the following:

"3.2 Qualification. Capacitors furnished under this specification shall be products which are qualified for listing on the applicable qualified products list at the time set for opening of bids (see 4.4 and 6.3). In addition, the manufacturer shall obtain certification from the qualifying activity that the reliability assurance requirements of 4.1.1 have been met and are being maintained. Authorized distributors which are approved to MIL-STD-790 distributor requirements by the qualified product list (QPL) manufacturers are listed in the QPL."

PAGE 4

3.16.1, lines 7 through 10: Delete "The "JAN" or "J" shall be placed immediately before the part number except that if such location would place a hardship on the manufacturer in connection with such marking, the "JAN" or "J" may be located on the first line above or below the part number."

PAGE 5

4.1.1b: Delete in its entirety.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T12:20Z
Check the source to verify that this is the current version before use.

* Following 4.1.1 add:

* "4.1.2 Test equipment and inspection facilities. Test and measuring equipment and inspection facilities of sufficient accuracy, and quality and quantity to permit performance of the required inspection shall be established and maintained by the contractor. The establishment and maintainance of a calibration system to control the accuracy of the measuring and test equipment shall be in accordance with MIL-STD-45662."

4.4.1, line 2: Delete "MIL-C-87217" and substitute "MIL-C-83421".

PAGE 6

4.5c: Delete in its entirety.

* 4.6.1.2.1, delete and substitute the following:

"4.6.1.2.1 Sampling plan. Subgroups 1, 2, 3, and 4 tests shall be performed on each capacitor offered for inspection. Subgroup 6 test shall be performed on an inspection lot basis. Statistical sampling inspection shall be performed on an inspection lot basis. A sample of 13 parts shall then be randomly selected. If one or more defects are found, the lot shall be rescreened and defects removed. A new sample of 13 parts shall then randomly be selected. If one or more defects are found in this second sample, the lot shall be rejected and shall not be supplied to this specification."

PAGE 7

* TABLE I, Subgroup 6, delete all references to AQL's and substitute "13 samples, 0 defects".

PAGE 10

6.1, delete and substitute:

"6.1 Intended use. Capacitors covered by this specification are primarily intended for use in low-energy, high impedance applications such as integrators, RC timing circuits, precision filters, and other applications where the ac component of voltage is not significant. Styles covered by this specification are available in tight tolerances and exhibit excellent capacitance stability over long life, as well as high insulation resistance and low loss factor. These capacitors can exhibit momentary breakdown in low energy applications. To insure clearing of breakdown, the circuit in which capacitors of 0.1 μF and greater capacitance are intended for use shall be capable of providing at least 100 microjoules of energy. Applications for these capacitors shall be limited to circuits that can provide the minimum energy and that are insensitive to momentary breakdown/clearing actions."

PAGE 13

Checklist, Item c.1, lines 1 and 2, delete and substitute:

"1. Capacitor shall have (must be verified) and describe, design by part number indicating the following with the necessary tolerance defined:"

Checklist, Item e. Traceability plan, add: "1/".

Checklist, add the following at end:

"1/ Traceability shall be applicable to MIL-C-83421 raw materials."

PAGE 14

B20, delete and substitute:

"B20. APPLICABLE DOCUMENTS. This section is not applicable to this appendix."

B20.1: Delete in its entirety.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T12:20Z
Check the source to verify that this is the current version before use.

* End of document, DD Form 1426 address, delete and substitute the following:

"645 LOG/LGME
Gentile Station
1060 Hamilton Street
Dayton, OH 45444-5400".

The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

CONCLUDING MATERIAL

Custodians:
Army - ER
Navy - EC
Air Force - 85
NASA - NA

Review activities:
Army - AR, MI
Navy - AS, CG, MC, OS, SH
Air Force - 17, 19
DLA - ES

Preparing activity:
Air Force - 85

Agent:
DLA - ES

(Project 5910-1885)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T12:20Z
Check the source to verify that this is the current version before use.