
THE REQUIREMENTS FOR ACQUIRING THE PRODUCT(S) DESCRIBED HEREIN SHALL CONSIST OF THIS SPECIFICATION SHEET AND THE ISSUE OF THE FOLLOWING SPECIFICATION LISTED IN THAT ISSUE OF THE DODISS SPECIFIED IN THE SOLICITATION: MIL-0-87114, MIL-F-18240

THIS SPECIFICATION IS APPROVED FOR USE BY ALL DEPARTMENTS AND AGENCIES OF THE DEPARTMENT OF DEFENSE.

Form Approved
OMB No. 0704-0188



DASH NO DIA	THREAD	øD MAX MIN	øA MAX MIN	øB MIN	H MAX MIN	M MAX REF	R RAD MAX MIN	T MAX	Y	d	e	b	2/ ULTIMATE TENSILE LBS/MIN	DOUBLE SHEAR LBS/MIN	DRIVER SIZE
04	.1120-40UNC-3A	.1120 .1095	.219 .205	.195	.080 .070	.250	.010 .015	.090	.005	.0045	.018	.0040	760	1,480	1
06	.1380-32UNC-3A	.1380 .1355	.270 .256	.242	.097 .087	.312		.111					1,120	2,240	2
08	.1640-32UNC-3A	.1635 .1610	.322 .308	.289	.115 .105	.437	.020 .010	.127					1,740	3,170	2
3	.1900-32UNF-3A	.1895 .1870	.373 .357	.331	.133 .122	.406		.145	.006				2,420	4,250	2
4	.2500-28UNF-3A	.2495 .2470	.492 .473	.424	.175 .162	.469		.192	.008			.0030	4,420	7,360	3
5	.3125-24UNF-3A	.3120 .3095	.615 .594	.518	.218 .203	.531		.287	.009	.0060	.024		7,100	11,500	4
6	.3750-24UNF-3A	.3745 .3720	.740 .718	.611	.281 .266	.641	.025	.266	.010			.0025	10,790	16,560	4
7	.4375-20UNF-3A	.4370 .4345	.863 .838	.706	.304 .288	.656							14,600	22,500	4
8	.5000-20UNF-3A	.4995 .4970	.987 .958	.801	.348 .327	.781	.030 .020					.0020	19,810	29,400	4

1/ CHAMFER LENGTH FROM END TO FIRST COMPLETE THREAD NOT TO EXCEED 2 THREAD PITCHES INCLUDING CHAMFER.

2/ BASED ON 125 KSI ULTIMATE TENSILE STRENGTH AND STRESS AREA = $3.1416 (E/2 - 3H/16)^2$ SEE FED-STD-H28/1.

© DENOTES CHANGE(S)

INCH-POUND

PREPARING ACTIVITY: DLA-IS
CUSTODIANS: ARMY-AV NAVY-AS
AIR FORCE-99 DLA-
REVIEW:
USER:
PROJECT NUMBER 5306-1618

MILITARY SPECIFICATION SHEET

TITLE
BOLT, SELF-LOCKING
75 KSI Fsu, 125 KSI Ftu
PAN HEAD, CROSS RECESSED

SPECIFICATION SHEET NUMBER
MS21096 5 DEC 94 REV C

SUPERSEDING
MS21096 B 14 OCT 94

AMSC-N/A FSC-5306

DISTRIBUTION STATEMENT
A. Approved for public release; distribution is unlimited.

DD Form 672, MAY 88 PREVIOUS EDITIONS ARE OBSOLETE

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:27Z
Check the source to verify that this is the current version before use.

THIS SPECIFICATION IS APPROVED FOR USE BY ALL DEPARTMENTS AND AGENCIES OF THE DEPARTMENT OF DEFENSE.

THE REQUIREMENTS FOR ACQUIRING THE PRODUCT(S) DESCRIBED HEREIN SHALL CONSIST OF THIS SPECIFICATION SHEET AND THE ISSUE OF THE FOLLOWING SPECIFICATION LISTED IN THAT ISSUE OF THE DODISS SPECIFIED IN THE SOLICITATION: MIL-B-87114, MIL-F-18240

Form Approved
OMB No. 0704-0188

LENGTH DASH NO	GRIP G ±.010	LENGTH +.031 -.015								
		.1120-40	.1380-32	.1640-32	.1900-32	.2500-28	.3125-24	.3750-24	.4375-20	.5000-20
001	.062	.312	.375	.500						
002	.125	.375	.437	.562						
003	.187	.437	.500	.625	.593					
004	.250	.500	.562	.687	.656	.719				
006	.375	.625	.687	.812	.741	.844	.906	1.016		
008	.500	.750	.812	.937	.906	.969	1.031	1.141	1.156	1.281
010	.625	.875	.937	1.062	1.031	1.094	1.156	1.266	1.281	1.406
012	.750	1.000	1.062	1.187	1.156	1.219	1.281	1.391	1.406	1.531
014	.875	1.125	1.187	1.312	1.281	1.344	1.406	1.516	1.531	1.656
016	1.000	1.250	1.312	1.437	1.406	1.469	1.531	1.641	1.656	1.781
018	1.125	1.375	1.437	1.562	1.531	1.594	1.656	1.766	1.781	1.906
020	1.250	1.500	1.562	1.687	1.656	1.719	1.781	1.891	1.906	2.031
022	1.375	1.625	1.687	1.812	1.781	1.844	1.906	2.016	2.031	2.156
024	1.500	1.750	1.812	1.937	1.906	1.969	2.031	2.141	2.156	2.281
026	1.625	1.875	1.937	2.062	2.031	2.094	2.156	2.266	2.281	2.406
028	1.750	2.000	2.062	2.187	2.156	2.219	2.281	2.391	2.406	2.531
030	1.875		2.187	2.312	2.281	2.344	2.406	2.616	2.531	2.656
032	2.000		2.312	2.437	2.406	2.469	2.531	2.641	2.656	2.781
034	2.125		2.437	2.562	2.531	2.594	2.656	2.766	2.781	2.906
036	2.250		2.562	2.687	2.656	2.719	2.781	2.891	2.906	3.031
038	2.375		2.687	2.812	2.781	2.844	2.906	3.016	3.031	3.156
040	2.500		2.312	2.937	2.906	2.969	3.031	3.141	3.156	3.281
042	2.625				3.031	3.094	3.156	3.266	3.281	3.406
044	2.750				3.156	3.219	3.281	3.391	3.406	3.531
046	2.875				3.281	3.344	3.406	3.516	3.531	3.656
048	3.000				3.406	3.469	3.531	3.641	3.656	3.781
050	3.125				3.531	3.594	3.656	3.766	3.781	3.906
052	3.250									4.031
054	3.375									4.156
056	3.500									4.281
058	3.625									4.406
060	3.750									4.531
062	3.875									4.656
064	4.000									4.781
066	4.125									4.906

PREPARING ACTIVITY: DLA-IS
CUSTODIANS: ARMY-AV NAVY- AS
AIR FORCE- 99 DLA-
REVIEW:
USER.
PROJECT NUMBER: 5306-1818

MILITARY SPECIFICATION SHEET

TITLE
BOLT, SELF-LOCKING
75 KSI Fsu, 125 KSI Ftu
PAN HEAD, CROSS RECESSED

SPECIFICATION SHEET NUMBER
MS21096 5 DEC 94 REV C

SUPERSEDING
MS21096 B 14 OCT 94

AMSC- N/A FSC -5306

DISTRIBUTION STATEMENT:
A. Approved for public release; distribution is unlimited.

DD Form 672, MAY 88 PREVIOUS EDITIONS ARE OBSOLETE

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:27Z
Check the source to verify that this is the current version before use.

THE REQUIREMENTS FOR ACQUIRING THE PRODUCT(S) DESCRIBED HEREIN SHALL CONSIST OF THIS SPECIFICATION SHEET AND THE ISSUE OF THE FOLLOWING SPECIFICATION LISTED IN THAT ISSUE OF THE DODISS SPECIFIED IN THE SOLICITATION: MIL-B-87114, MIL-F-18240

THIS SPECIFICATION IS APPROVED FOR USE BY ALL DEPARTMENTS AND AGENCIES OF THE DEPARTMENT OF DEFENSE.

Form Approved
OMB No 0704-0188

© REQUIREMENTS:

© 1. MATERIAL: ALLOY STEEL, 4340 (UNS G43400) IN ACCORDANCE WITH MIL-S-5000 OR 8740 (UNS G87400) IN ACCORDANCE WITH AMS 6322.

2. THREADS: THREADS SHALL BE CLASS 3A IN ACCORDANCE WITH FED-STD-H28/2. ACCEPTABILITY OF SCREW THREADS SHALL BE IN ACCORDANCE WITH FED-STD-H28/20, SYSTEM 22.

3. DIMENSIONING AND TOLERANCING: DIMENSIONING AND TOLERANCING SHALL BE IN ACCORDANCE WITH ANSI Y14.5M.

4. PROTECTIVE COATING: CADMIUM PLATED IN ACCORDANCE WITH QQ-P-416, TYPE II, CLASS 3.

5. LOCKING ELEMENT: IN ACCORDANCE WITH SPECIFICATION MIL-F-18240. THE LOCKING ELEMENT AREA, WITH LOCKING ELEMENT INCORPORATED MUST PASS THRU A RING GAGE EQUAL TO MAXIMUM MAJOR THREAD DIAMETER +.003" FREE OR WITH FINGER PRESSURE.


6. SURFACE TEXTURE: SURFACE TEXTURE, UNLESS OTHERWISE SPECIFIED, SHALL BE 125 MICROINCHES EXCEPT UPSET HEAD IN ACCORDANCE WITH ANSI/ASME B46.1.

7. TOLERANCE: UNLESS OTHERWISE SPECIFIED, TOLERANCES SHALL BE FOR LINEAR DIMENSIONS ±.010, ANGULAR DIMENSIONS ±5°.

8. HARDNESS: PARTS SHALL BE WITHIN ROCKWELL HARDNESS RANGE OF C-26 TO C-32.

9. PART NUMBER: THE PART NUMBER SHALL CONSIST OF THE BASIC MS NUMBER FROM TABLE.

EXAMPLE: MS21096-4008



MS21096-4008 INDICATES - BOLT, SELF-LOCKING, .250-28 UNF-3A, GRIP .500.

NOTES:

1. ALL DIMENSIONS ARE IN INCHES.
2. DESIGN AND USAGE LIMITATIONS: SEE MS15981.
3. REVISION LETTERS ARE NOT USED TO DENOTE CHANGES DUE TO THE EXTENSIVENESS OF THE CHANGES.
© 4. IN THE EVENT OF A CONFLICT BETWEEN THE TEXT OF THIS DOCUMENT AND THE REFERENCES CITED HEREIN, THE TEXT OF THIS DOCUMENT SHALL TAKE PRECEDENCE.
© 5. UNLESS OTHERWISE SPECIFIED, ISSUE OF REFERENCED DOCUMENTS ARE THOSE IN EFFECT AT THE TIME OF SOLICITATION.
6. AS AND AMS ARE SAE PUBLICATIONS.
7. GRIP LENGTH IS MEASURED FROM THE UNDERSIDE OF HEAD TO END OF FULL CYLINDRICAL PORTION OF SHANK.
8. UNASSIGNED DASH NUMBERS SHALL NOT BE USED EXCEPT THOSE DASH NUMBERS INCLUDED BY THE FOLLOWING CODING NOTE: DASH NUMBERS INDICATE PREFERRED GRIP LENGTHS IN .125 INCREMENTS FOR LENGTHS LONGER THAN .250 INCHES. INTERMEDIATE GRIP LENGTHS BETWEEN THESE LENGTHS LISTED, MAY BE SPECIFIED IN .062 INCREMENTS BY INTERMEDIATE DASH NUMBERS. LENGTH AND GRIP OF A BOLT WITH AN ODD NUMBER FOR THE DASH NUMBER WILL BE .062 GREATER THAN SHOWN FOR THE BOLT WITH THE PRECEDING EVEN DASH NUMBER.
© 9. PROCUREMENT SPECIFICATION: MIL-B-87114 EXCEPT AS NOTED TENSILE LOADS AS TABULATED HEREIN. FATIGUE STRENGTH AND COLD WORKING OF HEAD TO SHANK FILLET ARE NOT APPLICABLE. RECESS TORQUE VALUES ARE NOT APPLICABLE FOR SCREWS WITH MS9006 RECESSES.

PREPARING ACTIVITY: DLA-IS CUSTODIANS: ARMY-AV NAVY-AS AIR FORCE-99 . DLA- REVIEW: USER: PROJECT NUMBER: 5306-1818	MILITARY SPECIFICATION SHEET TITLE BOLT, SELF-LOCKING 75 KSI Fsu, 125 KSI Fbr PAN HEAD, CROSS RECESSED	SPECIFICATION SHEET NUMBER MS21096 5 DEC 94 REV C SUPERSEDING MS21096 B 14 OCT 94 AMSC-N/A FSC-5110
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.		Page 3 of 3

DD Form 672, MAY 88 PREVIOUS EDITIONS ARE OBSOLETE

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:27Z
Check the source to verify that this is the current version before use.