PART NUMBER	PACKAGING
MS36426-1	5 gal pail
MS36426-2	55 gal drum

FED. SUP CLASS
6850

REVIEWER: GL MD MI MR PS
USER: MO SM

SAFETY PRECAUTIONS: DANGER! HAZARDOUS LIQUID. CAUSES SEVERE BURNS. RAPIDLY ABSORBED THROUGH SKIN.

Do not ingest. Vapor irritating to eyes. Avoid breathing vapor, use protective mask. Do not get in eyes, on skin, on clothing; in case of contact, immediately flush skin or eyes with plenty of water for at least 15 minutes; for eyes get medical attention. Remove and wash contaminated clothing before reuse.

INTENDED USE: For use in cleaning either copper or aluminum-alloy aircraft oil coolers.

MATERIAL: Single-phase liquid. Ready to use.

REQUIREMENTS: Qualification required. The compound shall be free of abrasives, silicates (except ethyl silicate as a corrosion preventative), inorganic acids, cyanides, inert fillers, or undissolved material and shall be equal to or superior in effectiveness to the control formula. Minimum flash point, 80 degrees Fahrenheit. Maximum pour point, minus 20 degrees Fahrenheit.

CONTROL FORMULA
(For information. Does not necessarily indicate composition, either compound or quantity, of the qualified product)

Ingredient	Percent by Weight
95 percent ethyl alcohol	10
Cresol USP	10
Methylene Chloride	70
Potassium oleate	8
Wetting agent (polyethyleneglycol monalkylaryl ether specification MIL-D-16791)	2

DIRECTIONS FOR USE: The oil cooler shall be cleaned in a washing machine that has a tumbling and surging action caused by pressure and vacuum. The regulators shall be so hooked up that the cleaning compound will circulate in the opposite direction to that of the flow of oil when the regulators are installed on the plane. The oil cooler shall be flushed with any standard petroleum solvent to remove residual oil and sludge. The oil cooler should not be immersed in the cleaning compound. The cooler shall then be flushed with the cleaning compound to remove the carbon deposits, engine oil, gums, lead deposits, and foreign contamination. The cooler shall then be rinsed with a standard petroleum solvent. If the oil cooler is not to be brightened, it shall be filled with a suitable preservative oil and drained prior to use or storage; other wise, no preservative should be applied.

NOTES:
1. Referenced documents shall be of the issue in effect on date of invitations for bid.
2. Safety Precaution given is based on compounds of the Control Formula.

APPROVED 12 March 1965 REVISED

This standard has been approved by the Munitions Command, Department of the Army and is mandatory for use by that activity. All other military activities are required to employ this standard when suitable.

P.A. MU	TITLE	MILITARY STANDARD
Other Cust	CLEANING COMPOUND, SOLVENT oil-cooler	MS36426(MU)
Procurement Specification MIL-C-6864	SUPERSEDES:	SHEET 1 OF 1

DD FORM 672

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T17:40Z
Check the source to verify that this is the current version before use.