MIL-H-3586D
26 February 1981
SUPERSEDING
MIL-H-3586C
25 May 1976

MILITARY SPECIFICATION

HOLDFAST ASSEMBLY: CHAIN TYPE

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers a holdfast assembly to be used with fixed and floating bridges.

2. APPLICABLE DOCUMENTS

2.1 Issues of documents. The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

QQ-S-781	- Strapping, Steel, and Seals.
RR-C-271	- Chains and Attachments, Welded and Weldless.
PPP-B-601	- Boxes, Wood, Cleated-Plywood.
PPP-B-621	- Boxes, Wood, Nailed and Lock-Corner.

MILITARY

MIL-P-52258	- Pickets, Steel.

FSC 5420

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Mobility Equipment Research and Development Command, ATTN: DRDME-DS, Fort Belvoir, VA 22060 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T18:33Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	- Marking for Shipment and Storage.
MIL-STD-130	- Identification Marking of US Military Property.
MIL-STD-1188	- Commercial Packaging of Supplies and Equipment

(Copies of specifications and standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Description. The holdfast assembly shall consist of a length of steel chain and nine steel pickets.

3.2 First article (first-produced holdfast assemblies). The contractor shall furnish one or more holdfast assemblies (see 6.2) for examination within the time frame specified (see 6.2) to prove that his production methods will produce holdfast assemblies that comply with the requirements of this specification. Examination shall be as specified in Section 4 and shall be subject to surveillance and approval by the Government (see 6.3).

3.3 Material. Material shall be as specified herein. Materials not specified shall be selected by the contractor and shall be subject to all provisions of this specification (see 6.4).

3.4 Chain. The steel chain shall consist of 12 links in accordance with RR-C-271, type I, grade C, class 6, size 3/4 inch. The nominal inside dimensions of each link shall be 6 inches by 1-1/2 inches.

3.5 Pickets. The steel pickets shall be in accordance with MIL-P-52258, type II.

3.6 Identification marking. The holdfast assemblies shall be identified in accordance with MIL-STD-130.

3.7 Workmanship. The holdfast assembly shall be free from grease, rust, dirt, and other foreign matter.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection

Source: https://assist.dla.mil -- Downloaded: 20261O-16T18:33Z
Check the source to verify that this is the current version before use.

requirements specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Component and material inspection. The contractor is responsible for insuring that components and materials used are manufactured, examined, and tested in accordance with referenced specifications and standards, as applicable.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

(a) First-produced holdfast assemblies inspection (see 4.3).
(b) Quality conformance inspection (see 4.4).
(c) Inspection of packaging (see 4.6).

4.3 First-produced holdfast assemblies inspection.

4.3.1 Examination. The first-produced holdfast assemblies selected from the first ten produced holdfast assemblies shall be examined as specified in 4.5.1. Presence of one or more defects shall be cause for rejection.

4.4 Quality conformance inspection.

4.4.1 Sampling. Sampling for examination shall be in accordance with MIL-STD-105.

4.4.2 Examination. Samples selected in accordance with 4.4.1 shall be examined for the major and minor defects specified in 4.5.1. AQL shall be 2.5 percent defective for major defects and 4.0 percent defective for the minor defect.

4.5 Inspection procedure.

4.5.1 Examination. The holdfast assembly shall be examined as specified herein for the following defects:

Major

101. Components missing or not as specified.
102. Identification marking missing, incomplete or not legible.

Minor

201. Workmanship not as specified.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T18:33Z
Check the source to verify that this is the current version before use.

4.6 Inspection of packaging.

4.6.1 Quality conformance inspection of pack.

4.6.1.1 Unit of product. For the purpose of inspection, a completed pack prepared for shipment shall be considered a unit of product.

4.6.1.2 Sampling. Sampling for examination shall be in accordance with MIL-STD-105.

4.6.1.3 Examination. Samples selected in accordance with 4.6.1.2 shall be examined for the following defects. AQL shall be 2.5 percent defective.

103.	Materials or containers not as specified for level A or B.
104.	Blocking, bracing, and anchoring not adequate to prevent movement for level A or B.
105.	Strapping not as specified for level A.
106.	Marking missing, illegible, incorrect, or incomplete for level A, B, or commercial.

5. PACKAGING

5.1 Packing. Packing shall be level A or B, or commercial, as specified (see 6.2).

5.1.1 Level A. Each holdfast assembly shall be packed in a close-fitting box conforming to PPP-B-621, class 2, style optional or PPP-B-601, overseas type, style optional. Blocking, bracing, and anchoring shall be provided to prevent movement. Box closure and strapping shall be in accordance with the appendix to the applicable box specification. Strapping shall conform to QQ-S-781, class 1, type I or IV, size as applicable. Unless otherwise specified (see 6.2), strapping shall be finish B. When specified (see 6.2), strapping shall be finish A.

5.1.2 Level B. Level B packing shall be as specified in 5.1.1 for level A, except boxes shall be domestic type or class, as applicable. Box closure and strapping shall be in accordance with the appendix to the applicable box specification.

5.1.3 Commercial. Commercial packing shall be in accordance with MIL-STD-1188.

5.2 Marking.

5.2.1 Military. Military marking shall be in accordance with MIL-STD-129.

5.2.2 Commercial. Commercial marking shall be in accordance with MIL-STD-1188.

Source: https://assist.dla.mil -- Downloaded: 202610-16T18:33Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Intended use. The holdfast assembly is intended for use in mooring various types of floating bridges and in providing ground anchorage in the erection of some of the fixed bridges.

6.2 Ordering data. Acquisition documents should specify the following:

(a) Title, number, and date of this specification.
(b) Time frame required for submission of first-produced model, and number of holdfast assemblies required (see 3.2).
(c) Degree of packing required (see 5.1).
(d) When strapping shall be other than as specified (see 5.1.1).

6.3 First-produced holdfast assemblies. Any changes or deviations of production holdfast assemblies from the approved first-produced holdfast assemblies during production will be subject to the approval of the contracting officer. Approval of the first-produced holdfast assemblies will not relieve the contractor of his obligation to furnish holdfast assemblies conforming to this specification.

6.4 Recycled material. It is encouraged that recycled material be used when practical as long as it meets the requirements of the specification (see 3.3).

Custodians:
Army - ME
Navy - MC

Preparing activity:
Army - ME

Project 5420-0137

Source: https://assist.dla.mil -- Downloaded: 202610-16T18:33Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-H-3586D Holdfast Assembly: Chain Type

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1 OCT 76 1426

EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 202640-16T18:33Z
Check the source to verify that this is the current version before use.

)LD

EPARTMENT OF THE ARMY

OFFICIAL BUSINESS
NALTY FOR PRIVATE USE $300

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY CARD

FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
USA Mobility Equipment R&D Command
ATTN: DRDME-DS
Ft. Belvoir, VA 22060

LD

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T18:33Z
Check the source to verify that this is the current version before use.