MILITARY SPECIFICATION SHEET

INSIGNIA, BRANCH OF SERVICE, OFFICERS, SPECIAL FORCES

This specification is approved for use by all Departments and Agencies of the Department of Defense. The complete requirements for procuring the item(s) described herein shall consist of this document and the issue in effect of Specification MIL-I-3575.



DASH NOS.
-1: REGULAR
-2: SUBDUED

MATERIAL:
-1: RED BRASS
-2: RED BRASS OR ALUMINUM

DIMENSIONS (INCHES):
HEIGHT: 3/4 (REF)
THICKNESS (AT THICKEST POINT): .080 ± .005

FINISH:
-1: GOLD PLATED MIRROR-LIKE POLISHED
-2: DULL, FLAT BLACK ENAMEL OR ANODIZED AND DYED, AS APPLICABLE

NOTES:

1. ATTACHING DEVICE SHALL BE PRONG AND CLUTCH TYPE. PRONGS SHALL BE LOCATED ON THE CENTER LINE OF EITHER ARROW 1-1/4 ± 1/64 INCH ON CENTERS.

2. THE DASH NO. 1 INSIGNIA IS AUTHORIZED TO BE MANUFACTURED FROM ALUMINUM FOR COMMERCIAL SALE ONLY. THE INSIGNIA SHALL BE ANODIZED AND DYED TO MATCH THE FINISH ON THE STANDARD SAMPLE.

Custodian:
Army - IH

Preparing activity:
Army - IH

Review activity:
DLA - CT

(Project No. 8455 - A288)

AMSC N/A

FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T18:29Z
Check the source to verify that this is the current version before use.