METRIC

A-A-59370A
05 April 2013.
SUPERSEDING
A-A-59370
20 July 2000

COMMERCIAL ITEM DESCRIPTION

AMMONIUM HYDROXIDE, TECHNICAL

The General Service Administration has authorized the use of this commercial item description by all federal agencies.

1. SCOPE. This commercial item description covers four types of technical grades ammonium hydroxide. The intended uses for the ammonium hydroxide are as a cleaning agent, an accelerator in vulcanization, and as a dry diazo print developer for white print machines.

2. CLASSIFICATION. The ammonium hydroxide, technical, shall conform to the following types as specified (see 7.2):

Types. Type I - 26° Baumé (27 to 30 percent as ammonia (NH_3))
Type II - 21° Baumé (19 to 21 percent as NH_3)
Type III - 16° Baumé (9 to 10 percent as NH_3)
Type IV - 14° Baumé (6 to 7 percent as NH_3)

3. SALIENT CHARACTERISTICS.

3.1 Appearance. Ammonium hydroxide shall be a colorless, transparent, aqueous solution of NH_3 and water, visually free from foreign matter.

3.2 Residue after ignition. The residue after ignition shall be 0.03 percent by weight maximum. Testing shall be in accordance with the American Chemical Society (ACS) Reagent Chemicals specification for Ammonium Hydroxide, ACS.

3.3 Specific gravity. The specific gravity at 60°/60° F should not exceed a maximum of 0.904 - Type I, 0.929 - Type II, 0.963 - Type III, and 0.974 - Type IV, Ammonium Hydroxide, when tested in accordance with ASTM D1122.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data that may improve this document should be sent to: STDZNMGT@dla.mil or Defense Logistics Agency - Aviation, ATTN: DLA Aviation-VEB, 8000 Jefferson Davis Highway, Richmond, VA 23297-5616. Since contact information can change, you may want to verify the currency of this address information using the ASSIST database at https://assist.dla.mil.

FSC 6810

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:12Z
Check the source to verify that this is the current version before use.

3.4 Assay. Testing for assay shall be in accordance with the Ammonium Hydroxide, ACS specification outlined in the ACS Reagent Chemicals.

3.5 Nonvolatile matter. The nonvolatile matter should not exceed 0.05 percent by weight. To determine the nonvolatile matter, retrieve approximately 25 ml of the specimen, weighed to the nearest 0.1 g, into a tared evaporating dish weighed to the nearest mg. Evaporate to dryness on a steam bath. Dry the residue to constant weight at 105° C. Cool to room temperature in a desicccator and weigh to the nearest mg. Calculate the percent by weight nonvolatile matter as: Percent nonvolatile matter = (100 (A - B))/W, where A = weight of dish and residue in grams, B = weight of dish in grams, and W = weight of specimen in grams.

4. REGULATORY REQUIREMENTS.

The manufacturer shall prepare and submit Material Safety Data Sheets (MSDS) and Hazardous Warning Labels (HWL) meeting the requirements of FED-STD-313 and the Code of Federal Regulations (CFR), Section 29 CFR 1910.1200

5. QUALITY ASSURANCE PROVISIONS.

5.1 Product conformance. The products provided shall meet the salient characteristics of this commercial item description, conform to the producer's own drawings, specifications, standards, and quality assurance practices, and be the same product offered for sale in the commercial market. The company must be able to show test data or laboratory results of meeting the salient characteristics of technical grade Ammonium Hydrozide. The government reserves the right to require proof of such conformance.

6. PACKAGING

6.1 Packaging. Preservation, packing, and marking shall be as specified in the contract or order (see 7.1).

6.2 Precautionary marking. Each unit container shall be durably and legibly marked to show the following special information:

Warning! Poison! Corrosive!
Liquid causes burns
Vapor extremely irritating

Avoid breathing vapor. Avoid contact with eyes, skin, and clothing. In case of contact, immediately flush skin or eyes with plenty of water for at least 15 minutes; for eyes, get medical attention. HANDLING & STORAGE: Use care in opening this container as a portion of the contents may blow out violently due to the pressure of the ammonia gas; safety goggles or a face shield must be worn. Place a cloth over the cap or stopper before removal. It is also advisable to cool container before opening, especially during warm seasons. Keep well closed and in cool place.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:12Z
Check the source to verify that this is the current version before use.

7. NOTES.

7.1 Ordering data. Acquisition document must specify the following:

a. Title, number, and date of this document.
b. Part identification number.
c. Quantity and size of container required.
d. Packaging and special marking (see 6.1 and 6.2)

7.2 Part identification number (PIN). The following part identification number procedure is for government purposes and does not constitute a requirement for the contractor.

A-A-59370 - X - X - Quantity

CID Number

Quantity: A - 16 ounces; B - 32 ounces; C - 80 ounces; D - 128 ounces

Type I - Ammonium Hydroxide, Technical (26° Baumé)
II - Ammonium Hydroxide, Technical (21° Baumé)
III - Ammonium Hydroxide, Technical (16° Baumé)
IV - Ammonium Hydroxide, Technical (14° Baumé)

7.3 National stock numbers (NSNs). The following is a list of assigned NSNs, which correspond to this CID. This list may not be indicative of all possible NSNs associated with this document.

NSN	TYPE
6810-00-584-3793	I (16 Ounces)
6810-00-222-9643	I (80 Ounces)
6810-00-817-9929	I (128 Ounces)
6810-00-527-2476	III (32 Ounces)

7.4 Sources of referenced documents. Copies of referenced documents are available from:

Federal documents:
Defense Automated Printing Service (DAPS)
Building 4D, NPM-DODSSP
700 Robbins Avenue
Philadelphia, PA 19111-5094

American Society for Testing and Materials (ASMT) documents:
American Society for Testing Materials
100 Barr Harbor Drive
West Conshohocken, PA 19428-2959

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:12Z
Check the source to verify that this is the current version before use.

ACS documents:
American Chemical Society
1155 16th Street, NW
Washington, DC 20036

CFR documents:
US Government Printing Office
Superintendent of Documents
Washington, DC 20402-9328

CIVIL AGENCY COORDINATING ACTIVITY:
GSA/FAS

Preparing Activity:
DLA-GS3

(Project 6810-2013-027)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:12Z
Check the source to verify that this is the current version before use.