INCH POUND
A-A-59377A
August 15, 2000
SUPERSEDING
A-A-59377
01 February 1999

COMMERCIAL ITEM DESCRIPTION

COUPLING ASSEMBLY, QUICK-DISCONNECT, SEXLESS TYPE

The General Services Administration has authorized the use of this Commercial Item Description for all federal agencies.

1. SCOPE. This Commercial Item Description (CID) covers the performance requirements for the quick-disconnect coupling assemblies, sexless type. The quick-disconnect, sexless couplings are used to provide a positive seal disconnect between components of an aircraft fuel servicing system.

2. CLASSIFICATION. The coupling assemblies shall be of the following classes, as specified (see 7.1):

2.1 Class.

Class A - Valved (dry break)
Class B - Valveless (wet break)

3. SALIENT CHARACTERISTICS

3.1 Materials. The materials selected for construction are the responsibility of the contractor. The materials shall be of sufficient durability to meet the operational and environmental requirements as specified herein. Materials used in the manufacture of the coupling assembly shall be resistant to all fluids as specified. The material shall have no adverse effect on the health of personnel when used for its intended purpose. Whenever feasible, toxic chemicals, hazardous substances or ozone depleting chemicals (ODC) shall not be used.

3.1.1 Deterioration prevention and control. The coupling assembly shall be fabricated from compatible materials, inherently corrosion resistant or treated to provide protection against the various forms of corrosion and deterioration to which the material is susceptible.

3.1.2 Dissimilar metals. Dissimilar metals shall not be used in intimate contact with each other unless protected against galvanic corrosion.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data that may improve this document should be sent to: U.S. Army Tank-automotive and Armaments Command, ATTN: AMSTA-TR-E/IE, Warren, MI 48397-5000

FSC 4730

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:12Z
Check the source to verify that this is the current version before use.

3.1.3 Cleaning, treatment, and painting. Unless otherwise specified (see 7.3), all surfaces of the coupling, normally painted internally and externally shall be cleaned, treated, and painted in accordance with the manufacturer's standard commercial practice. Unless otherwise specified, the coupling assembly color shall be a non-vivid and lusterless shade of tan, except the valve lever, bumper and dust cap, if used, shall be a non-vivid and lusterless shade of black.

3.2 Physical characteristics.

3.2.1 Valved coupling assembly (Class A). The valve shall prevent leakage in the closed position when the end cap is removed or when connected. The valve shall also be prevented from inadvertent opening or closing. When the valve is open, a means shall be provided to prevent sexless connection or disconnection. The valve device shall be large enough to allow ease of operation by personnel wearing arctic mittens. The valve control shall be labeled with a double-ended arrow showing direction of operation at each end to indicate the functional result (i.e., open, close, etc.). One person shall be capable of connecting or disconnecting the sexless end connection by hand.

3.2.2 Valveless coupling assembly (Class B). The mating parts of the valveless coupling assembly shall provide a positive lock by engaging and sealing against any leakage during operation. One person shall be capable of connecting or disconnecting the sexless end connection by hand.

3.2.3 Weight. The weight of a valved or valveless coupling assembly, with the sexless end connection and without an adapter end connection, shall be no more than four (4) pounds for a two-inch coupling or six (6) pounds for a three-inch coupling.

3.2.4 Adapter end connections. Camlock connections shall conform to the requirements of A-A-59326. Hose connections shall be reusable and sized to mate with 2.00- or 3.00-inch standard collapsible or noncollapsible hose conforming to MIL-PRF-370, type A (collapsible), B (noncollapsible) or D (noncollapsible, low temperature).

3.3 Dust protection. The internal surfaces of the coupling assembly, when connected or disconnected and covered, shall not be contaminated by blowing dust, sand, and other foreign particles when tested in accordance with MIL-STD-810, method 510.1.

3.4 Interface.

3.4.1 Fuel. The coupling assembly shall be compatible with fuel conforming to MIL-DTL-5624, grade JP-8.

3.4.2 Existing couplings. The couplings shall interface with existing sexless, quick-disconnect couplings (see 7.6).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:12Z
Check the source to verify that this is the current version before use.

3.5 Safety. The coupling assembly shall incorporate safety features that will ensure personnel safety, minimize human error in the field, and prevent accidental spills. The coupling assembly shall ensure electrical continuity during fuel operations by incorporating a dedicated contact. The device shall be easily operable in any operating environment including quick shut-off capability while the system is pressurized and flowing. The valve-operating device shall be conveniently located; however, it shall also prevent inadvertent valve openings or closings by locking in the fully open and fully closed position.

3.6 Static control. To control static electricity during fueling operation, an electrical continuity device shall be incorporated in the coupling assembly. This device shall provide continuity contact between mating sexless surfaces without the use of external conductors. Provisions shall also be made to achieve intimate contact between hose bonding conductor and sexless coupling assembly when assembling the hose to the sexless coupling assembly. Static control devices shall also provide control of static electricity with all existing sexless connectors.

3.7 Identification marking. Identification markings shall be permanent, legible, and shall include the manufacturer's identification code and the manufacturer's part number. The part or identification number (PIN) and the national stock number (NSN) shall be required if specified in the contract (see 7.3).

4. REGULATORY REQUIREMENTS. The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR).

5. PRODUCT CONFORMANCE PROVISIONS

5.1 Product conformance. The products provided shall meet the salient characteristics of this CID, conform to the producer's own drawings, specifications, standards, and quality assurance practices, and be the same product offered for sale in the commercial marketplace. The Government reserves the right to require proof of such conformance (see 7.3).

5.2 Market acceptability. The following market acceptability criteria are necessary to document the quality of the product to be provided under this CID.

5.2.1 The manufacturer of the item must have been producing a product meeting the requirements of this CID for at least 2 years.

5.2.2 The company must have sold at least 1000 units meeting this CID in the commercial market place over the past 2 years.

6. PACKAGING

6.1 Packaging. Preservation, packing, and marking shall be as specified in the contract or order (see 7.3).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:12Z
Check the source to verify that this is the current version before use.

7. NOTES

7.1 Part or Identification Number (PIN). The following part or identification numbering procedure is for government purposes and does not constitute a requirement for the contractor.

This example describes a part numbering system for specification CID A-A-59377A.

AA59377 – A 2

Example of reference part number:
AA59377 – A2

Class: A – Valved (dry break)
B – Valveless (wet break)

Size: 2 – two-inch connection
3 – three-inch connection

7.2 Addresses for obtaining copies of referenced documents.

7.2.1 The Code of Federal Regulations (CFR) may be obtained from the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.

7.2.2 Military specifications and standards are available from Defense Automated Printing Service, Building 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.

MIL-PRF-370	- Hose and Hose Assemblies, Nonmetallic: Elastomeric, Liquid Fuel
MIL-DTL-5624	- Turbine Fuel, Aviation, Grades JP-4, JP-5, and JP-5/JP-8 ST
MIL-STD-810	- Environmental Engineering Considerations and Laboratory Tests

7.2.3 Federal specifications are available from the Defense Automated Printing Service, Building 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.

A-A-59326	- Coupling Halves, Quick-Disconnect, Cam-Locking Type

7.3 Ordering data. Acquisition documents will specify the following:

a. CID document number, revision, and CID PIN.
b. Coupling assembly class required (see 2.1).
c. When cleaning, treatment, and painting are required (see 3.1.3).
d. Top coat, if required, and color (see 3.1.3).
e. If PIN and NSN are required for identification (see 3.7).
f. Product conformance provisions (see 5.1).
g. Packaging requirements (see 6.1).

7.4 Products known to meet this CID. Companies whose products are known to meet some or all of the requirements of this CID are listed below. Competition is not limited to these companies; however, any new products must meet the requirements of this CID.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:12Z
Check the source to verify that this is the current version before use.

Aeroquip Corporation
Engineered Systems Group
Coupling Products Division
2500 W. Argyle
Jackson, Michigan 49202-1967
517-787-8121

Carter Ground Fueling Co.
671 W. 17th Street
Costa Mesa, CA 92627
949-548-3421
516-789-4704

7.5 Key words.

Coupling assembly
Drybreak
Quick-disconnect
Sexless
Wetbreak

7.6 Existing couplings. Existing couplings have been manufactured in accordance with MIL-C-53071, Coupling Assemblies, Quick-Disconnect, Sexless Type, which has been superseded by this document.

MILITARY INTERESTS:

Custodians:
Army – AT
Navy – SH
Air Force – 99

Review Activity:
DLA – CC

CIVIL AGENCY COORDINATING ACTIVITY:
GSA-FSS

Preparing Activity:
Army – AT

(Project 4730-2109)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:12Z
Check the source to verify that this is the current version before use.