INCH-POUND
A-A-59377B
13 June 2016
SUPERSEDING
A-A-59377A
15 August 2000

COMMERCIAL ITEM DESCRIPTION

COUPLING ASSEMBLY, QUICK-DISCONNECT, SEXLESS TYPE

The General Services Administration has authorized the use of this Commercial Item Description for all federal agencies.

1. SCOPE. This Commercial Item Description (CID) covers the performance requirements for the quick-disconnect coupling assemblies, sexless type. The quick-disconnect, sexless couplings are used to provide a positive seal disconnect between components of an aircraft fuel servicing system.

2. CLASSIFICATION. The coupling assemblies shall be of the following classes, as specified (see 7.1):

2.1 Class.

Class A - Valved (dry break)
Class B - Valveless (wet break)

3. SALIENT CHARACTERISTICS

3.1 Materials. The materials selected for construction are the responsibility of the contractor. The materials shall be of sufficient durability to meet the operational and environmental requirements as specified herein. Materials used in the manufacture of the coupling assembly shall be resistant to all fluids as specified. The material shall have no adverse effect on the health of personnel when used for its intended purpose. Whenever feasible, toxic chemicals, hazardous substances or ozone depleting chemicals (ODC) shall not be used.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data that may improve this document should be sent to U.S. Army RDECOM, Tank Automotive Research, Development and Engineering Center,
ATTN: RDTA-EN/STND/TRANS MS #268, 6501 E. 11 Mile Road, Warren, MI 48397-5000 or sent by email to usarmy.detroit.rdecom.mbx.tardec-standardization@mail.mil. Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at https://assist.dla.mil.

AMSC N/A FSC 4730

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:12Z
Check the source to verify that this is the current version before use.

3.1.1 Deterioration prevention and control. The coupling assembly shall be fabricated from compatible materials, inherently corrosion resistant or treated to provide protection against the various forms of corrosion and deterioration to which the material is susceptible.

3.1.2 Dissimilar metals. Dissimilar metals shall not be used in intimate contact with each other unless protected against galvanic corrosion.

3.1.3 Cleaning, treatment, and painting. Unless otherwise specified (see 7.3), all surfaces of the coupling, normally painted internally and externally shall be cleaned, treated, and painted in accordance with the manufacturer's standard commercial practice. Unless otherwise specified, the coupling assembly color shall be a non-vivid and lusterless shade of tan, except the valve lever, bumper and dust cap, if used, shall be a non-vivid and lusterless shade of black.

3.2 Physical characteristics.

3.2.1 Valved coupling assembly (Class A). The valve shall prevent leakage in the closed position when the end cap is removed or when connected. The valve shall also be prevented from inadvertent opening or closing. When the valve is open, a means shall be provided to prevent sexless connection or disconnection. The valve device shall be large enough to allow ease of operation by personnel wearing arctic mittens. The valve control shall be labeled with a double-ended arrow showing direction of operation at each end to indicate the functional result (i.e., open, close, etc.). One person shall be capable of connecting or disconnecting the sexless end connection by hand.

3.2.2 Valveless coupling assembly (Class B). The mating parts of the valveless coupling assembly shall provide a positive lock by engaging and sealing against any leakage during operation. One person shall be capable of connecting or disconnecting the sexless end connection by hand.

3.2.3 Weight. The weight of a valved or valveless coupling assembly, with the sexless end connection and without an adapter end connection, shall be no more than four (4) pounds for a two-inch coupling or six (6) pounds for a three-inch coupling.

3.2.4 Adapter end connections. Camlock connections shall conform to the requirements of A-A-59326. Hose connections shall be reusable and sized to mate with 2.00- or 3.00-inch standard collapsible or noncollapsible hose conforming to MIL-PRF-370, type A (collapsible), B (noncollapsible) or D (noncollapsible, low temperature).

3.3 Dust protection. The internal surfaces of the coupling assembly, when connected or disconnected and covered, shall not be contaminated by blowing dust, sand, and other foreign particles when tested in accordance with MIL-STD-810, method 510.6.

3.4 Interface.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:12Z
Check the source to verify that this is the current version before use.

3.4.1 Fuel. The coupling assembly shall be compatible with fuel conforming to MIL-DTL-83133, Turbine Fuel, Aviation, Kerosene Type, JP-8 (NATO F-34), NATO F-35, and JP-8+100 (NATO F-37).

3.4.2 Interface Dimensions: The coupling assembly shall conform to the dimensions in drawing 12563976, 2" Unisex Coupling Interface with Lanyard and Cap.

3.5 Safety. The coupling assembly shall incorporate safety features that will ensure personnel safety, minimize human error in the field, and prevent accidental spills. The coupling assembly shall ensure electrical continuity during fuel operations by incorporating a dedicated contact. The device shall be easily operable in any operating environment including quick shut-off capability while the system is pressurized and flowing. The valve-operating device shall be conveniently located; however, it shall also prevent inadvertent valve openings or closings by locking in the fully open and fully closed position.

3.6 Static control. To control static electricity during fueling operation, an electrical continuity device shall be incorporated in the coupling assembly. This device shall provide continuity contact between mating sexless surfaces without the use of external conductors. Provisions shall also be made to achieve intimate contact between hose bonding conductor and sexless coupling assembly when assembling the hose to the sexless coupling assembly.

3.7 Identification marking. Identification markings shall be permanent, legible, and shall include the manufacturer's identification code and the manufacturer's part number. The part or identification number (PIN) and the national stock number (NSN) shall be required if specified in the contract (see 7.3).

3.8 Swiveling Torque. The torque required to start or to sustain a 360 degree rotation in either direction shall not be greater than 240 inch-pounds while the coupling assembly has an internal pressure of 0 to 100 psig.

3.9 Internal Pressure. Two couplings mated together shall be able to withstand hydrostatic pressures up to 300 psig for no less than 1 minute, with valves open or closed. The mated coupling shall than be able to withstand 10 psig of internal pressure for no less than 1 minute. No damage or leaks shall be present after being subjected to these parameters.

4. REGULATORY REQUIREMENTS. The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR).

5. PRODUCT CONFORMANCE PROVISIONS

5.1 Product conformance. The products provided shall meet the salient characteristics of this CID, conform to the producer's own drawings, specifications, standards, and quality assurance practices, and be the same product offered for sale in the commercial marketplace. The Government reserves the right to require proof of such conformance (see 7.3).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:12Z
Check the source to verify that this is the current version before use.

5.2 Market acceptability. The company must have sold units meeting this CID in the commercial market place over the past 5 years.

6. PACKAGING

6.1 Packaging. Preservation, packing, and marking shall be as specified in the contract or order (see 7.3).

7. NOTES

7.1 Part or Identification Number (PIN). The following part or identification numbering procedure is for government purposes and does not constitute a requirement for the contractor.

This example describes a part numbering system for specification CID A-A-59377B.

AA59377 - A 2 Example of reference part number:
AA59377 - A2

Class: A - Valved (dry break)
B - Valveless (wet break)
Size: 2 - two-inch connection
3 - three-inch connection

7.2 Addresses for obtaining copies of referenced documents.

7.2.1 Military specifications and standards are available from https://assist.dla.mil/quicksearch/ or from the Standardization Document Order Desk, 700 Robbins Avenue, Building 4D, Philadelphia, PA 19111-5094.)
.

MIL-PRF-370 - Hose and Hose Assemblies, Nonmetallic: Elastomeric, Liquid Fuel
MIL-DTL-83133 - Turbine Fuel, Aviation, Kerosene Type, JP-8 (NATO F-34), NATO F-35, and JP-8+100 (NATO F-37)
MIL-STD-810 - Environmental Engineering Considerations and Laboratory Tests

7.2.2 Federal specifications are available from https://assist.dla.mil/quicksearch/ or from the Standardization Document Order Desk, 700 Robbins Avenue, Building 4D, Philadelphia, PA 19111-5094.

A-A-59326 - Coupling Halves, Quick-Disconnect, Cam-Locking Type

7.3 Ordering data. Acquisition documents will specify the following:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:12Z
Check the source to verify that this is the current version before use.

a. CID document number, revision, and CID PIN.
b. Coupling assembly class required (see 2.1).
c. When cleaning, treatment, and painting are required (see 3.1.3).
d. Top coat, if required, and color (see 3.1.3).
e. If PIN and NSN are required for identification (see 3.7).
f. Product conformance provisions (see 5.1).
g. Packaging requirements (see 6.1).

7.4 Products known to meet this CID. Companies whose products are known to meet some or all of the requirements of this CID are listed below. Competition is not limited to these companies; however, any new products must meet the requirements of this CID.

Aeroquip Corporation
Engineered Systems Group
Coupling Products Division
2500 W. Argyle
Jackson, Michigan 49202-1967
517-787-8121
Contact by email at: http://www.eaton.com/.

Carter Ground Fueling Co.
671 W. 17th Street
Costa Mesa, CA 92627
949-764-2200
516-789-4704
Contact by email at: http://www.cla-cal.com/.

Cla-Val
1701 Placentia Avenue
Costa Mesa, CA 92627-4475
800-942-6326
Contact by email at: http://www.zycon.com/.

7.5 Key words.

Drybreak
Wetbreak

7.6 Changes from previous issue. The margins of this Commercial Item Description (CID) are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:12Z
Check the source to verify that this is the current version before use.

evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the previous issue.

MILITARY INTERESTS:

Custodians:
Army - AT
Navy - SH
Air Force - 99

Review activities:
DLA - CC

CIVIL AGENCY COORDINATING ACTIVITY:
GSA-FAS

Preparing activity:
Army - AT

(Project 4730-2016-028)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:12Z
Check the source to verify that this is the current version before use.