INCH-POUND
A-A-59379
19 March 1999
SUPERSEDING
MIL-V-58039E
26 March 1984

COMMERCIAL ITEM DESCRIPTION

VALVES, GATE, RISING STEM, DOUBLE ACTING, LIGHTWEIGHT

The General Services Administration has authorized the use of this Commercial Item Description (CID) by all federal agencies.

1. SCOPE. This CID covers double acting, rising stem, gate valves for use with liquid petroleum supply systems.

2. CLASSIFICATION.

2.1 Type. Valves shall be classified into three types as follows (see 7.2):

Type I -3 inch, round Truck Trailer Manufacturer's Association (TTMA) flange ends.
Type II -4 inch, round TTMA flange ends.
Type III -6 inch, round TTMA flange ends.

3. SALIENT CHARACTERISTICS.

3.1 Description. The valves shall be lightweight, and have a double-acting, rising stem connected to a wedge-shaped double-disk and actuated by manual handwheel.

3.2 Interface. The valves shall have bolt circle and flange dimensions in accordance with TTMA RP No. 28 or as shown in table I to allow proper interface with other system components.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may improve this document should be addressed to: U.S. Army Tank-automotive and Armaments Command, ATTN: AMSTA-TR-D/210, Warren, MI 48397-5000

AMSC N/A FSC 4820

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:12Z
Check the source to verify that this is the current version before use.

TABLE I. Valve flange dimensions

Size	O. D. 1/	Bolt circle diameter	Bolt hole diameter	Number of bolts
3 inch	5.625	4.875	0.438	8
4 inch	6.750	5.875	0.438	8
6 inch	9.000	8.125	0.438	12

NOTE: Manufacturer's standard tolerance shall apply.
1/ O.D. = Outside Diameter.

3.3 Materials. The materials selected for construction are the responsibility of the contractor. The materials shall be of sufficient durability to meet all requirements specified herein. Valves shall be constructed of corrosion resistant material suitable for fuel service.

3.4 Valve body. The valve body shall have an area of flow passage, when fully opened, not less than that of a circle having a diameter equal to the valve nominal pipe size.

3.5 Valve performance. When subjected to a hydrostatic pressure of 300 pounds per square inch gage (psig) for type I and II or 225 psig for type III for a period of not less than one minute, there shall be no leakage nor visible distortion or evidence of cracks.

3.6 End flanges. The end flanges (inlet and outlet) shall be integral with the valve body and shall meet all requirements of a TTMA flange.

3.7 Bonnet. The bonnet shall be constructed to contain the stuffing box assembly, and shall provide adequate clearance for the disks when the valve is fully opened. The bonnet shall be removable from the valve body to allow access to the stuffing box assembly for repair. A replaceable means of sealing the bonnet to valve body interface shall be provided.

3.8 Stuffing box. The stuffing box or condensation chamber shall be self-adjusting and shall consist of a packing nut, packing gland, and gland spring. All components shall be of corrosion resisting materials.

3.9 Packing. Packing shall be the contractors standard product.

3.10 Rising stem. The rising stem shall be of a corrosion resistant material and may be of one or two piece construction with a double acting feature for fast closing. The stem shall include a retaining mechanism which prevents the stem and its components from being expelled from the valve under pressure.

3.11 Double disk. The disk shall be of the double disk type with a self-aligning feature to assure a positive leak-proof closure. The disks shall be of a corrosion resistant material to ensure continued operation. Disks shall be loosely keyed together to facilitate removal. The disk shall not jam and internal parts shall not be damaged when a force of 2.5 foot-pounds of torque is applied to the handwheel to close the valve and the same torque is applied to open the valve.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:12Z
Check the source to verify that this is the current version before use.

3.12 Seat ring. The seat ring shall be of a corrosion resistant material. The finish of the seat rings and the double disks shall be such that smooth close contact between the components shall prevent leakage but not bind or gall one another during opening and closing.

3.13 Handwheel. The handwheel shall be the contractors standard handwheel securely fastened to the rising stem. The handwheel shall have direction of rotation, for opening and closing, indicated.

3.14 Finish. Before assembly the valve components shall be anodized with a color as specified (see 7.3). The coating shall be of a thickness to allow assembly and valve operation without interference.

4. REGULATORY REQUIREMENTS.

4.1 Recovered materials. The offeror/contractor is encouraged to use recovered materials to the maximum extent practical, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR).

5. QUALITY ASSURANCE PROVISIONS.

5.1 Product conformance. The products provided shall meet the salient characteristics of this CID, conform to the producer's own drawings, specifications, standards, and quality assurance practices, and be the same product offered for sale in the commercial market. The Government reserves the right to require proof of such conformance.

5.2 Market acceptability. The product offered shall be of the latest model of the standard product of the supplier that have been used in the field for at least one year by commercial users.

5.3 Examinations. Each valve examined shall be inspected for compliance with the requirements specified in 3.1 through 3.14. Nonconformance to any specified requirement, or the presence of one or more defects shall constitute cause for rejection.

6. PACKAGING.

6.1 Preservation, packing, and marking shall be as specified in the contract or purchase order. (see 7.2)

7. NOTES.

7.1 Part identification number (PIN). The following part identification numbering procedure is for Government purposes and does not constitute a requirement for the contractor.

This example describes a part numbering system for CID A-A-59379

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:12Z
Check the source to verify that this is the current version before use.

AA59379-1
└── 1 - Type I
2 - Type II
3 - Type III

7.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number, and date of this CID.
b. Type of valve required (see 2.1).
c. Color of finish required (see 3.14).
d. Level of preservation and packing required (see 6.1).

7.3 Data requirements. The contracting officer should include, in the contract or order, any data requirements, such as instructional materials or technical publications to be furnished with the valves.

7.4 Provisioning. The contracting officer should include, in the contract or order, provisioning requirements for repair parts (overpack if required) and maintenance tools (including special tools), as necessary, and instructions regarding packaging and shipment of the valves.

7.5 Sources of documents. TTMA RP No. 28 is available from the Truck Trailer Manufacturers Association (TTMA), 1020 Princess Street, Alexandria, VA 22314.

7.6 Sources of supply. Manufacturers whose products meet some or all of the requirements of this CID are listed below; however, competition is not limited to these companies.

Milwaukee Valve Co. Inc.
2375 S Burrell St
Milwaukee, WI 53207-1519

Morrison Bros. Co.
24th E Elm St
PO Box 238
Dubuque, IA 52004

Marine and Valve Supply
13115 Braton Rd Unit A
Whittier, CA 90605

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:12Z
Check the source to verify that this is the current version before use.

7.7 Subject term (key word) listing.

Bonnet
Double disk
Valve body

Custodians:
Army - AT
Navy - MC

Preparing Activity:
Army - AT

(Project 4820-0821)

Review Activity:
Navy - YD2

Civilian Coordinating Agency
GSA - FSS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:12Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter must be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER A-A-59379	2. DOCUMENT DATE (YYMMDD) 990319

3. DOCUMENT TITLE
VALVES, GATE, RISING STEM, DOUBLE ACTING, LIGHTWEIGHT

4. NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed)*

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) DSN (If applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME USA TACOM, AMSTA-TR-D/210 (Fuel and Water Handling)	b. TELEPHONE (Including Area Code) (1) Commercial (810)574-7744 (2) DSN 786-7744
c. ADDRESS (Include Zip Code) US Army Tank-automotive and Armaments Command Attn: AMSTA-TR-D/210 Warren, MI 48397-5000	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 681-9340 DSN 761-9340

DD Form 1426, Oct 89 *Previous editions obsolete*

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:12Z
Check the source to verify that this is the current version before use.