X-K-001274A(GSA-FSS)
April 24, 1969
SUPERSEDING
Int. Fed. Spec. X-K-001274
June 22, 1967

INTERIM FEDERAL SPECIFICATION

KIT, CLASSIFIED DOCUMENT DESTRUCTOR, DRUM TYPE

This Interim Federal Specification was developed by Standardization Division, Federal Supply Service, General Services Administration, Washington, D.C. 20406, based upon currently available technical information. It is recommended that Federal agencies use this document in procurement and forward any recommendations for changes to the preparing activity at the address shown above.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers a chemical loaded, document destructor kit which is designed to meet the protection criteria for classified material set forth in Executive Order 10501, as amended, "Safeguarding Official Information in the Interest of the Defense of the United States." The kit is considered an expendable item for use in emergency conditions.

1.2 Classification. The document destructor kit specified herein shall be of one type and size and shall be capable of destroying paper product, of the type normally found in office files, in the amount that can be placed in the open core of the kit's fiberboard liner, an estimated weight of 100 to 120 pounds. Destruction of the paper product shall be complete and accomplished within 25 minutes after the kit has been ignited.

2. APPLICABLE DOCUMENTS

2.1 Specifications and standards. The following specifications and standards, of the issues in effect on the date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

Federal Specifications:

QQ-S-781	- Steel, Strapping, Flat.
TT-C-490	- Cleaning Methods and Pretreatment of Ferrous Surfaces for Organic Coatings.
TT-E-516	- Enamel, Lusterless, Quick-Drying, Styrenated, Alkyd Type.
TT-P-320	- Pigment, Aluminum; Powder and Paste, for Paint.
UU-P-268	- Paper, Kraft, Untreated, Wrapping.
JJJ-S-791	- Sugar, Refined or Brown; Cane or Beet.
MMM-A-00185	- Adhesive, Rubber (For Paper Bonding).
PPP-C-843	- Cushioning Material, Cellulosic.

Federal Standards:

Fed. Std. No. 123 - Marking for Domestic Shipment (Civilian agencies)
Fed. Std. No. 595 - Colors.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:37Z
Check the source to verify that this is the current version before use.

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20402.)

(Single copies of this specification and other product specifications required by activities outside the Federal Government for bidding purposes are available without charge at the General Services Administration Regional Offices in Boston, New York, Washington, D.C., Atlanta, Chicago, Kansas City, Mo., Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, Wash.)

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Specifications:

JAN-C-178 - Charcoal (For Use in Munitions).
MIL-S-322 - Sodium Nitrate.
MIL-R-3390 - Wire, Steel.
MIL-A-5092 - Adhesive, Rubber Base, General Purpose.

Military Standard :

MIL-STD-129 - Marking for Shipment and Storage.

(Copies of Military Specifications and Standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following document forms a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

INTERSTATE COMMERCE COMMISSION:

49 CFR 71-90 - Interstate Commerce Commission Rules and Regulations for Transportation of Explosives and Other Dangerous Articles.

(Application for copies should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20402)

3. REQUIREMENTS

3.1 Preproduction sample. Before regular production is commenced, two complete, sample kits, including all components shall be made ready and submitted to the contracting officer or his authorized representative for examination and test as specified in section 4 to determine compliance with this specification. Approval of the preproduction samples authorizes the commencement of production, but does not relieve the supplier of responsibility for compliance with all requirements of this specification. Production units shall not vary from the approved preproduction samples in design, construction, material, or workmanship.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:37Z
Check the source to verify that this is the current version before use.

3.2 Parts. Parts used in the construction of the kit shall be as shown in the detail drawings (see 6.2) identified hereunder:

Part Name	Drawing Number	Quantity
Destructor Kit Assembly	352-100A	1
55 Gal. Drum, Open Head	352-200A	1
Liner	352-300A	1
Screen, Assembly & Detail	352-301A	1
Retaining Band Assembly	352-302A	1
Charge Ring	352-303A	1
Disk, Paper	352-304A	1
Insert Assembly	352-305A	2

3.3 Material. Material used in the kit shall be as described herein and as shown in the detail drawings. Material not definitely specified shall be of good commercial quality suitable for the purpose intended.

3.3.1 Sodium nitrate. The sodium nitrate for the destruction charge shall conform to the following specification:

Component	Shipping	Limit
$NaNO_3$	99.2%	Min.
$NaNO_2$	.03	Max.
NaCL	.22	"
Na_2SO_4	.40	"
SiO_2	.004	"
CaO	.03	"
MgO	.002	"
AL_2O_3	.001	"
Mn	.0001	"
Cu	.0001	"
Hot Water Insolubles	.01	"
Fe_2O_3	.003	"
Total M. O. akly, as Na_2CO_3	.20	"
H_2O	.10	"
Total N	16.35	Min.

To insure free-flow and to minimize dusting, the sodium nitrate shall be prilled-processed in the form of small, hard spherical pellets.

3.3.2 Material for the ignition charge. The ignition charge shall consist of the following material:

Component	Specification	Quantity
Sodium nitrate	MIL-S-322, Grade A, Class 1	2 pounds
Sugar	JJJ-S-791, Type (A)	2 pounds
Charcoal	JAN-C-178, Class D	8 ounces

3.4 Construction.

3.4.1 Assembly. Assembly of component parts of the kit shall be in accordance with this specification and as shown in Drawing No. 352-100A. Assembly of kits shall be performed in a dehumidified room, below 40 percent R. H., and at a temperature of 70 to 80 degrees Fahrenheit.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:37Z
Check the source to verify that this is the current version before use.

3.4.2 Liner and insert assembly. The liner for the kit shall be predried for 24 hours in a low humidity, heated room. It shall then be placed in the interior of the drum so that it fits around the raised portion of the drum botton. A ring of rubberized horsehair as shown in Drawing No. 352-305A shall be inserted with the paper side down to the bottom of the annulus to preclude the displacement of sodium nitrate loaded in the annulus.

3.4.3 Destructor charge. The destructor charge shall consist of the sodium nitrate specified in 3.3.1. The sodium nitrate shall be thoroughly dried prior to insertion into the kit and shall consist of approximately 200 pounds of the chemical, but not less than 180 pounds of chemical shall be used. The charge shall be poured into the annulus formed between the liner and the drum to a height that will allow insertion of the ignition mix, paper separation ring, and horsehair retainer as shown in Drawing No. 352-100A. The proper level shall be determined after shaking the drum to insure that the sodium nitrate charge is properly settled and evenly distributed to the level indicated on Drawing No. 352-100A. The kraft paper separation ring shall then be placed in the annulus of the sodium nitrate charge.

3.4.4 Ignition charge. The components for the ignition charge as specified in 3.3.2 shall be thoroughly mixed together in a blending machine to assure that an intimate mixture results. The ignition charge shall then be poured into a high density polyethelene plastic tube, sealed and then tied to form a ring as depicted in Drawing No. 352-303A. The charge ring shall be placed evenly around the annulus. The space remaining between the ignition charge and the top of the drum shall be filled with a ring of rubberized horsehair with the paper side down.

3.4.5 Closure. The cover screen with its tie-down wires attached to the retaining band shall be placed inside of the drum. The lid, with operating instructions affixed to its inside surface, shall be fitted over the drum with the sealer gasket in place. Extreme care shall be exercised to insure that the lid is properly fitted and that the gasket creates a positive water proof seal. The lid shall be held in place by a closure ring secured by a screwbolt and nut, firmly tightened.

3.5 Pretreatment and finish. All metal surfaces of the kit shall be pre-treated as indicated in Drawing No. 352-200A. The interior surfaces shall then be painted with a pigmented aluminum specified in TT-P-320. The exterior surfaces shall be painted with a lusterless enamel specified in TT-E-516. The color of the enamel used for the exterior surfaces shall be green, color No. 34079, of Fed. Std. No. 595.

(Sample panels of the standard color of finish are obtainable without charge, from the Business Service Center, Federal Supply Service, General Services Administration, Washington, D.C. 20407, or from the Business Service Center of the nearest General Services Administration Regional Office.)

3.6 Special markings. In addition to the markings specified in section 5 of this specification, each kit shall be marked in accordance with the Code of Federal Regulations 49 CFR 71-90, and as indicated in Drawing No. 352-100A.

3.7 Instruction sheet. An instruction sheet containing the information listed hereunder shall be placed on the inside surface of the drum lid as shown in Drawing Number 352-100A.

"CAUTION: THIS DOCUMENT DESTRUCTOR IS TO BE IGNITED OUT OF DOORS.

"OPERATION INSTRUCTIONS FOR DOCUMENT DESTRUCTOR KIT

"1. Remove retaining band and wire screen from inside core of kit.
2. Unfold screen.
3. Place retaining band, with eyelets pointing toward top of drum, around outside circumference of the drum just below the second rib of the drum. Secure retaining band by passing one end through the loop on the other end and bending it back 180°.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:37Z
Check the source to verify that this is the current version before use.

"OPERATION INSTRUCTIONS FOR
DOCUMENT DESTRUCTOR KIT (cont'd)

4. Remove rubberized horsehair at the top of the kit to expose the plastic tube containing the charge mix.

5. Lift up one end of the igniter ring so that it is exposed and near the top of the drum. Break open the plastic tube at this point to expose the powdered charge mix.

6. Place the paper material to be burned in the core of the kit until it is full, flush with the top of the drum. The load of paper material should be tightly packed. DO NOT PLACE LARGE METAL OBJECTS IN THIS KIT.

7. Place wire screen on top of the drum and bend the corners down. Fasten the 16 tie-down wires securely to the eight eyelets on the retaining band.

8. Ignite charge mix by direct application of flame. A match, lit cigarette, propane torch, or similar igniters are suitable for this purpose. Wait a few seconds to insure that ignition has occurred.

9. Evacuate the burn area or retire a safe distance of 100 feet."

3.8 Workmanship. The destructor kit shall be constructed, assembled, and finished in a workmanlike manner. The instruction sheet specified in 3.7 shall be firmly attached to the inside surface of the drum lid. All markings shall be neat and legible.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.1.1 Component and material inspection. In accordance with 4.1, the supplier is responsible for insuring that components and materials used are manufactured, tested, and inspected in accordance with the requirements of referenced subsidiary specifications and standards to the extent specified, or, if none, in accordance with this specification.

4.2 Preproduction Samples. In accordance with 3.1, the inspection specified in 4.5.1 and the tests specified in 4.5.2 and 4.5.3 shall be accomplished on two preproduction samples prior to the start of regular production to determine compliance with the requirements of this specification. The supplier shall provide an adequate facility and all material necessary for the performance of all inspections and tests.

4.3 Sampling for inspection and acceptance.

4.3.1 Production lot. A production lot shall consist of kits produced from the same type materials from one supplier and assembled under essentially the same production line methods and conditions during a 30 day period. Each lot shall be identified by the manufacturer's prefix initials preceeding a serial number and year of manufacturer.

EXAMPLE: XYX 1-68.

4.3.2 Lot inspection. Ten percent of each production lot shall be inspected for proper construction, presence of all materials, and quality of workmanship. This 10 percent inspection may be made prior to actual closure of the kits; but the lid, instruction sheet, sealer gasket, locking ring, screwbolt, and other hardware shall be with the inspected units and included in the inspection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:37Z
Check the source to verify that this is the current version before use.

4.3.3 Lot testing. Two kits selected at random from each lot shall be tested as specified in 4.5.2 and 4.5.3.

4.4 Rejection.

4.4.1 If any of the kits are not properly made in accordance with this specification, or if materials are not as specified, or if not of good workmanship, the lot shall be rejected; but may be reworked to over come the objection and resubmitted prior to testing in 4.5.2 and 4.5.3.

4.4.2 Kits subjected to the performance test in 4.5.2 shall be rejected if after the drop, or roll, or leak test, the metal drum has been damaged to the point that affects operation or preparation for operation of the kit; or the ignition mix has burst from it polyethelene container; or if the ignition mix container becomes dislodged from its position in the annulus atop the sodium nitrate charge; or if displacement of sodium nitrate into the open core of the kit exceeds two pounds; or if the fiberboard liner is deformed or extensively damaged; or if the kit leaked.

4.4.3 Kits subjected to the paper burning test in 4.5.3 shall be rejected if they fail to completely destroy the charge of paper within the time specified in 1.2; if the metal drum fails to be intact and contain the residue left from burning; if the wire screen and retaining band fail to remain in place. Failure of the cover screen or retaining band to remain in place shall be attributed to component failure and not from improper installation to constitute rejection.

4.4.4 Rejection of kits in performance test and paper burning test shall result in rejection of the entire lot. The lot may be reworked and resubmitted; however, such resubmitted lots shall be inspected and tested to the extent determined appropriate by the Government inspector to insure that deficiencies previously noted have been corrected.

4.5 Inspections and tests.

4.5.1 Inspection of samples. Samples shall be inspected for proper construction, presence of all materials and components, and quality of workmanship.

4.5.2 Performance test. The sample kits shall be complete, closed, and fully prepared for delivery. Each sample kit shall be placed on its side and permitted to drop from a height of four feet onto a concrete or equally hard surface. The kit shall then be rolled on the ground for a distance of not less than 100 yards. Upon completion of the roll, the kit shall be immersed in tap water of approximately the same temperature as the kit for a period of 5 minutes. At completion of this testing, the kit shall be opened and inspected.

The metal drum shall not be damaged nor deformed in a manner which might affect operation or preparation for operation of the kit. Dents in the drum or marks on its finish resulting from the tests shall not constitute rejection.

The ignition mix shall be contained in the polyethelene tube; the ring shall be contained in the annulus between the rubberized horsehair and the kraft paper rings and on top of the sodium nitrate charge.

The sodium nitrate charge shall be contained in the annulus between the fiberboard liner and the drum. There shall be no leakage of chemical into the center of the kit. The presence of less than two (2) pounds of chemical in the open core of the kit shall not constitute rejection.

The fiberboard liner shall be in place and not deformed. Marks and scratches on the liner caused by shifting of the wire screen or retaining band shall not constitute rejection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:37Z
Check the source to verify that this is the current version before use.

The inner contents of the kit shall be dry and there shall be no evidence of leakage.

4.5.3 Paper burning test. The sample kits, on being found acceptable in all criteria in 4.5.2 shall be tested to determine burning capability.

The kit shall be charged with paper product in an amount that completely fills the inner core; this charge shall be tightly packed in the kit and no less than 100 pounds of paper product shall be used.

The charged kit shall be prepared and ignited in accordance with printed instructions furnished with the kit. Ignition shall occur on the first or second attempt.

Complete burning destruction of the charged paper shall result within the time limitations specified 1.2; the metal drum shall be intact and containing the residue left from burning; the screen shall be intact and remain affixed to the retaining band around the drum.

Failure of one or more tie-down wires on the cover screen shall not constitute rejection so long as the cover screen does not lift free of the kit during operation or displace in a manner to permit ejection of the paper product being burned.

5. PREPARATION FOR DELIVERY

5.1 Kits. The kit shall not require any further packaging or packing.

5.2 Marking. Each kit shall be marked in accordance with the procurement documents and the markings applied as specified in Fed. Std. No. 123 and MIL-STD-129, as applicable.

6. NOTES

6.1 Ordering data. Purchaser should select the permitted options offered herein, and include the following information in procurement documents.

(a) Title, number, and date of this specification.

(b) Number of preproduction samples required (see 3.1).

(c) Marking required (see 5.2).

6.2 Specification drawings. The detail specification drawings for the kits are available for examination or will be furnished at a cost of $7.00 per set upon request to the General Services Administration Business Service Center, 7th and D Streets, S.W., Washington, D.C. 20407. Certified check or postal money order shall be made payable to "General Services Administration, Region 3".

GSA DC 69- 13515

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:37Z
Check the source to verify that this is the current version before use.