MIL-HDBK-265A (NAVY)
22 September 1986
SUPERSEDING
MIL-HDBK-265 (NAVY)
15 January 1981

MILITARY HANDBOOK

STANDARD GENERAL PURPOSE ELECTRONIC TEST EQUIPMENT SUPPORT ITEMS

AMSC N/A FSC 6625

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

DEPARTMENT OF THE NAVY
SPACE AND NAVAL WARFARE SYSTEMS COMMAND
WASHINGTON, DC 20363-5100

MIL-HDBK-265A(NAVY)

Standard General Purpose Electronic Test Equipment Support Items

1. This Military Handbook is approved for use by the Department of the Navy and is available for use by all Departments and Agencies of the Department of Defense.

2. Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, Space And Naval Warfare Systems Command, Attn: SPAWAR 003-121, Washington, DC 20363-5100 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

CONTENTS

		Page
Paragraph 1.	SCOPE	1
2.	REFERENCED DOCUMENTS	1
2.1	Government documents	1
3.	DEFINITIONS	2
4.	GENERAL REQUIREMENTS	2
4.1	Limitations	2
4.2	Selection of GAI	3
5.	DETAILED REQUIREMENTS	3
5.1	Guidance for use	3
6.	NOTES	4
6.1	Listing inquiries	4
6.2	Environmental classes	4
6.3	Navy item control numbers (NICN)	4
6.4	Changes	4
6.5	Manufacturer's name and federal supply code	5

APPENDIXES

Appendix	A-Reference Equipment to Standard Equipment	7
	B-Reference NIIN to Standard Equipment	39
	C-Standard Equipment to Reference Equipment	71
	D-Standard Equipment to Specifications	91
	E-Noun Name to Standard Equipment	129
	F-NAVSEA SCAT Code to Standard Equipment	167
	G-Federal Supply Code to Manufacturer's Name	175
	H-Manufacturer's Name to Federal Supply Code	179

Source: https://assist.dla.mil -- Downloaded: 202640-26T13:40Z
Check the source to verify that this is the current version before use.

STANDARD GENERAL PURPOSE ELECTRONIC TEST EQUIPMENT SUPPORT ITEMS

1. SCOPE

This handbook identifies standard and substitute standard General Purpose Electronic Test Equipment Support Items (GSI) which have been determined to be suitable for Navy use, and for which the Space and Naval Warfare Systems Command (SPAWAR) exercises material support responsibility by management of item entry. It should be used for guidance purposes in planning and support documents which specify GSI requirements (e.g. prime equipment technical manuals and Operational Logistics Support Summaries).

2. REFERENCED DOCUMENTS

2.1 Government documents

2.1.1 Specifications and standards. Unless otherwise specified the following specifications and standards of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation form a part of this handbook to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-T-28800	Test Equipment For Use With Electrical And Electronic Equipment, General Specification For

STANDARDS

MILITARY

MIL-STD-1364	Standard General Purpose Electronic Test Equipment
MIL-STD-1387	Procedures For Submission Of Application For Approval Of Non-Standard General Purpose Electronic Test Equipment (GPETE)

(Copies of specifications and standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.1.2 Other Government documents. The following other Government document forms a part of this standard to the extent specified herein.

DEPARTMENT OF DEFENSE

DOD H4-2 Federal Supply Code for Manufacturers, Code to Name

(Application for copies should be addressed to the Commanding Officer, Naval Publications and Forms Center, 5801 Tabor Avenue, Philadelphia, PA 19120.)

Source: https://assist.dla.mil -- Downloaded: 202610-26T13:40Z
Check the source to verify that this is the current version before use.

3. DEFINITIONS

3.1 General purpose electronic test equipment (GPETE). Electronic test equipment capable of generating, modifying, or measuring a range of electronic functions to test two or more systems or equipments of basically different design.

3.2 GPETE support item (GSI). The complement of equipment, supplemental to GPETE, which is necessary to facilitate a complete test measurement capability. This includes GPETE auxiliary items, GPETE accessories, GPETE plug-ins, and GPETE ancillary equipment.

3.2.1 Standard GSI. Support equipment listed herein as preferred for procurement.

3.2.2 Nonstandard GSI. Items of GSI not listed herein as preferred for procurement.

3.2.3 GPETE auxiliary item (GAI). A general purpose component or device used in support of a test measurement setup employing GPETE. (Examples: ratio transformers, portable directional couplers, DC power supplies, and so forth.)

3.2.4 GPETE accessory (GA). An individual support item used to complete or augment the operational capability of a specific item of GPETE or group of GPETE. (Examples: oscilloscope probes, multimeter test probes, noise sources, and so forth.)

3.2.5 GPETE plug-ins (GP-I). A removable assembly intended to complete or augment the operational capability of a specific item of GPETE. (Examples: oscilloscope preamplifier plug-ins, heterodyne frequency extender plug-ins, digital word generator plug-ins, and so forth.)

3.2.6 GPETE ancillary equipment (GAE). A self-contained unit intended to augment the operational capability of a specific item of GPETE or group of GPETE. (Examples: self-contained transfer oscillators, self-contained modulators, self-contained tracking generators, and so forth.)

3.3 GPETE master group (GMG). A code that identifies instrument measurement requirements within a generic family of equipment.

4. GENERAL REQUIREMENTS

4.1 Limitations. This handbook is limited in application to standard and reference GAI only. The other GSI categories (GA, GP-I, and GAE) are considered unique to specific items of GPETE and are not subject to entry management other than that exercised through MIL-STD-1364 procedures.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

4.2 Selection of GAI. Contents of this handbook include items of GAI generally found in Navy inventory and newer GAI planned for procurement. Naval activities and contractors initiating requirements for GAI may select standard GSI using one or more of the following appendixes:

a. Appendix A. Reference Equipment to Standard Equipment. This appendix lists model numbers of GAI generally found in the Navy inventory referenced to the standard GAI preferred for procurement. National Stock Number (NSN) and status information are also provided.

b. Appendix B. Reference NIIN to Standard Equipment. This appendix lists NSNs (by NIIN) of GAI generally found in the Navy inventory referenced to the standard equipment preferred for procurement. Model number and status information are also provided.

c. Appendix C. Standard Equipment to Reference Equipment. This appendix lists model numbers of standard GAI referenced to model numbers of GAI generally found in the Navy inventory.

d. Appendix D. Standard Equipment to Specifications. This appendix lists technical information on all standard GAI.

e. Appendix E. Noun Name to Standard Equipment. This appendix lists standard GSI for individual noun name groups and can be used to identify standard equipment on the basis of functional requirements. Individual equipment specifications are included.

f. Appendix F. NAVSEA SCAT Code to Standard Equipments. Certain documents cite the NAVSEA SCAT Code to identify the family group of a particular GAI. This appendix identifies the standard GAI for each NAVSEA SCAT Code.

g. Appendix G. Federal Supply Code to Manufacturer's Name. This appendix identifies manufacturers associated with the FSCMs used in this publication.

h. Appendix H. Manufacturer's Name to Federal Supply Code. This appendix identifies FSCMs for manufacturers of GAI listed in this publication.

5. DETAILED REQUIREMENTS

5.1 Guidance for use. Appendixes A and B provide status and guidance information for items managed as GSI. Users should interpret and apply the notes contained therein as indicated in 5.1.1 and 5.1.2. Models designated UNDER REVIEW have been discontinued and are being reviewed for replacement. No replacements have been identified at the time of printing. Contact NESEA Code 2261 for guidance.

5.1.1 Equipment status:

a. STD. Item is identified as standard GAI.

b. REPL. Item is replaced for procurement purposes by the standard model cited.

c. GA. GPETE accessory. GA items are not identified to standards.

d. 1387. No direct standard replacement available. Submit requirements via MIL-STD-1387 for guidance.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

5.1.2 Equipment notes:

a. Note 1. Reference equipment is classified obsolete.
b. Note 2. Reference equipment is classified obsolescent.

6. NOTES

6.1 Listing inquiries. The Navy need for GAI is a function of the specific test and measurement capabilities required to maintain and repair weapon systems and ancillary subsystems. Accordingly, the listing of standard electronic test instruments in this document was developed on the basis of extensive evaluation and testing in consideration of current and projected GAI requirements. Manufacturers' inquiries relative to products which can lead to significant operational improvements and economy are welcome. Inquiries should be addressed to: Space and Naval Warfare Systems Command, Test and Monitoring Systems Group (TAMS), Washington, DC 20363-5100. Provide full descriptive information, including test data (MIL-T-28800 applies), technical manual, and support availability. Also indicate reason(s) why the product(s) should be listed, with supporting evidence showing known or projected specific Navy measurement requirements. These should be identified to particular weapon systems and, where possible, user activity.

6.1.1 Discontinued items. Certain GAI items listed as standard in the previous issue have been discontinued with no replacement selected at time of publication. The various appendixes note these items as under review. User inquiries may be directed to the Space and Naval Warfare Systems Command address noted in 6.1.

6.2 Environmental classes. Approximate severity of usage capabilities of standard equipment is indicated on the technical information sheets of Appendixes D and E, based upon requirements in MIL-T-28800 where applicable.

6.3 Navy item control numbers (NICNs). When NSNs were not assigned by time of issue, NICNs are shown.

6.4 CHANGES. REVISIONS TO THIS DOCUMENT WILL BE REGULARLY SCHEDULED. INTERIM GUIDANCE TO ADDITIONS AND DELETIONS OF STANDARD GAI IS PROVIDED IN THE GAI STATUS LIST WITH REFERENCE PRICES, ISSUED QUARTERLY BY THE NAVAL ELECTRONIC SYSTEMS ENGINEERING ACTIVITY, ST. INIGOES, MD 20684-0010. DIRECT INQUIRIES TO CODE 2261.

6.4.1 Symbols. Symbols are not used in this revision to identify changes from the previous issue due to the extensiveness of the changes.

Source: https://assist.dla.mil -- Downloaded: 202610-26T13:40Z
Check the source to verify that this is the current version before use.

6.5 Manufacturer's name and federal supply code. Appendixes G and H cross reference manufacturer's name and federal supply code and are applicable to products as specified in DoD H4-2 referenced herein.

6.6 Subject term (key word) listing.

Electronic test equipment, support items, standard general equipment
General purpose electronic test equipment (GPETE)
General purpose electronic test equipment accessory (GA)
General purpose electronic test equipment ancillary equipment (GAE)
General purpose electronic test equipment auxiliary (GAI)
General purpose electronic test equipment master group (GMG)
General purpose electronic test equipment plug-ins (GP-I)
General purpose electronic test equipment support item (GSI)
Nonstandard general purpose electronic test equipment
Standard general purpose electronic test equipment
Substitute standard general purpose electronic test equipment

Preparing activity:
Navy-EC
(Project No. 6625-N842)

Review activities:
Navy - AS, MC, SH, SA

User activities:
Navy - OS, CG, YD

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX A

REFERENCE EQUIPMENT TO STANDARD EQUIPMENT

REFERENCE EQUIPMENT					STANDARD EQUIPMENT		
MODEL	FSCM	NSN	STATUS	NOTES	MODEL	FSCM	NSN
A-90	89536	1H6625-00-506-0533	GA		N/A		
AAT-1	11242	NSNL	GA		N/A		
ABC100-0.2M	85604	1H6130-00-601-6301	REPL		6443B	28480	1H6130-00-163-6201
AC-03N	00929	9N5985-00-485-4879	REPL		210A-3	93459	1H6625-LL-HHE-4111
AC-10N	00929	7Z6625-00-813-6847	REPL		2-20	93459	1H6625-01-017-1276
AC-16K	28480	NSNL	GA		N/A		
AC-16Q	28480	NSNL	GA		N/A		
AC-20N	00929	1H6625-00-813-6853	REPL		N9412-20	09992	1H5985-01-203-5192
AC-60A	28480	1H5950-00-294-4883	GA		N/A		
ACD-1	11242	NSNL	GA		N/A		
AD-06N	00929	NSNL	REPL		8491A-006	28480	9N5895-00-230-1827
AD-10N	00929	9N5985-00-445-6952	REPL		8491A-010	28480	9N5985-00-865-0108
AD-30N	00929	1H6625-00-445-6954	REPL		2-30	93459	1H6625-01-014-3463
AD-40N	00929	NSNL	REPL		2-40	93459	1H6625-01-014-3464
AE-10N	00929	1H5905-00-792-4543	REPL		8491A-010	28480	9N5985-00-865-0108
AF-117-69-34	93459	NSNL	REPL		AF-117A-69-34	93459	9N6625-01-063-9297
AF-117A-69-34	93459	9N6625-01-063-9297	STD		AF-117A-69-34	93459	9N6625-01-063-9297
AH-C32	00929	9N5985-00-763-8796	REPL		8491A-006	28480	9N5895-00-230-1827
AJ-210N	00929	1H5985-00-201-5055	REPL		AU-65AMN	12457	1H6625-01-040-9528
AMN-1	11242	NSNL	GA		N/A		
AN/UPA-1	MIL	NSNL	GA	1	N/A		
AN/UPA-1A	MIL	NSNL	GA	1	N/A		
AN/UPA-1B	MIL	NSNL	GA	1	N/A		
AN/UPM-85	MIL	&&6625-00-678-5639	1387	1	N/A		
AN/URM-111	MIL	8R6625-00-792-9956	GA	1	N/A		
AN/URM-111A	MIL	NSNL	GA	1	N/A		
AN/USM-119	MIL	NSNL	GA		N/A		
AN/USM-119A	MIL	1H6625-00-773-6102	GA		N/A		
AT-200-SR	12598	9N5985-00-525-5074	REPL		355C	28480	1H5985-00-993-1377
AT-201-SR	12598	NSNL	REPL		355D	28480	9N5985-00-957-1860
ATA-1	11242	NSNL	GA		N/A		
ATN-1	11242	NSNL	GA		N/A		
ATP-1	11242	NSNL	GA		N/A		

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX A

REFERENCE EQUIPMENT TO STANDARD EQUIPMENT

REFERENCE EQUIPMENT				STANDARD EQUIPMENT		
MODEL	FSCM	NSN	STATUS NOTES	MODEL	FSCM	NSN
AU-10	12457	9N5985-00-881-0262	REPL	2-3414-30	09992	9N5985-00-999-8095
AU-10A	12457	9N5985-00-881-0262	REPL	2-3414-30	09992	9N5985-00-999-8095
AU-65AMN	12457	1H6625-01-040-9528	STD	AU-65AMN	12457	1H6625-01-040-9528
AU-65A5-NCM	12457	1H6625-01-040-9528	REPL	AU-65AMN	12457	1H6625-01-040-9528
AV-50	01113	1H6625-00-975-9941	REPL	432-D	80138	9N5985-00-087-2547
AV-75	01113	1H6625-00-987-3441	REPL	442-D	80138	9N5905-00-313-9064
A40A10	89536	1H6625-00-427-5149	GA	N/A		
A40A20	89536	1H6625-00-427-5160	GA	N/A		
A400 BC	16786	1H6625-01-142-5447	STD	A400 BC	16786	1H6625-01-142-5447
A404-7	12868	1H6625-00-733-5914	REPL	RT-30A	88869	1H6625-LL-HHE-4050
A420D	11332	1H6625-01-021-6645	GA	N/A		
A4240C	11332	1H6625-01-095-8844	GA	N/A		
A6302	80009	NSNL	GA	N/A		
A80	89536	NSNL	GA	N/A		
B-1576	91161	1H5985-00-792-9928	STD	B-1576	91161	1H5985-00-792-9928
BA-C-110C	00341	1H6625-01-030-5505	STD	BA-C-110C	00341	1H6625-01-030-5505
BHK-500-0.4M	85604	7Z6625-01-031-8855	STD	BHK-500-0.4M	85604	7Z6625-01-031-8855
BP-60F	23934	NSNL	REPL	5015V	98095	1H6625-01-224-0215
BPA-60E	23934	NSNL	REPL	5015V	98095	1H6625-01-224-0215
B4063	00929	NSNL	REPL	UF-0050	00929	9N5985-00-572-6267
C-12	80009	NSNL	REPL	C-30BP	80009	7G6720-01-095-2205
C-30	80009	1H6720-00-907-3600	REPL	C-30BP	80009	7G6720-01-095-2205
C-30A	80009	NSNL	REPL	C-30BP	80009	7G6720-01-095-2205
C-30B	80009	7Z6625-01-145-2809	REPL	C-30BP	80009	7G6720-01-095-2205
C-30BP	80009	7G6720-01-095-2205	STD	C-30BP	80009	7G6720-01-095-2205
C-59AP	80009	1H6720-00-262-4198	STD	C-59AP	80009	1H6720-00-262-4198
CB-B12	00929	1H5985-01-065-8225	REPL	3000-10	99899	9N5985-00-816-4287
CB-B13	00929	1H6625-01-065-5289	REPL	3041-10	99899	1H5985-01-039-5404
CB-B14	00929	1H6625-01-065-5290	REPL	3042B-10	99899	9N5985-00-465-8112
CB-B15	00929	1H6625-01-065-5291	REPL	3043B-10	99899	1H6625-01-065-5289
CB-B16	00929	1H6625-01-065-5292	REPL	3004-10	99899	9N5985-00-788-6962
CDA	14655	9Y6625-00-982-5256	REPL	UNDER REVIEW		
CDA-2	14655	9Y6625-00-982-5256	REPL	UNDER REVIEW		

Source: https://assist.dla.mil -- Downloaded: 20260-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX A

REFERENCE EQUIPMENT TO STANDARD EQUIPMENT

REFERENCE EQUIPMENT MODEL	FSCM	NSN	STATUS	NOTES	STANDARD EQUIPMENT MODEL	FSCM	NSN
CDA-5	14655	NSNL	REPL		UNDER REVIEW		
CDB	14655	NSNL	REPL		UNDER REVIEW		
CDB-3	14655	9Y6625-00-649-4284	REPL		UNDER REVIEW		
CDB-5	14655	2R6625-00-519-2055	REPL		UNDER REVIEW		
CDC	14655	9N6625-00-865-6142	REPL		UNDER REVIEW		
CDC-3	14655	9N6625-00-865-6142	REPL		UNDER REVIEW		
CDC-5	14655	1H6625-00-519-2054	REPL		UNDER REVIEW		
CN-1000/G	MIL	1H6625-00-215-4931	REPL		850-CT2W	83332	NSNL
CN-16/U	MIL	NSNL	REPL		W5MT3A	13850	9N5950-00-987-5601
CN-16A/U	MIL	NSNL	REPL		W5MT3A	13850	9N5950-00-987-5601
CN-16B/U	MIL	NSNL	REPL		W5MT3A	13850	9N5950-00-987-5601
CN-30/U	MIL	NSNL	REPL		8491A-010	28480	9N5985-00-865-0108
CN-30A/U	MIL	9N5985-00-250-3481	REPL		8491A-010	28480	9N5985-00-865-0108
CN-30B/U	MIL	NSNL	REPL		8491A-010	28480	9N5985-00-865-0108
CN-39A/U	MIL	NSNL	REPL		8491A-020	28480	1H4935-01-031-2694
CN-39B/U	MIL	NSNL	REPL		8491A-020	28480	1H4935-01-031-2694
CN-45/UP	MIL	1H5985-00-240-3974	GA		N/A		
CN-476/U	MIL	NSNL	REPL		M602	57646	NSNL
CN-608A/U	MIL	NSNL	REPL		0874-9577	82316	&&5840-00-868-1287
CN-87/U	MIL	9N5985-00-781-2903	REPL		8491A-020	28480	1H4935-01-031-2694
CN-87A/U	MIL	9N5985-00-781-2903	REPL		8491A-020	28480	1H4935-01-031-2694
CN-87B/U	MIL	9N5985-00-781-2903	REPL		8491A-020	28480	1H4935-01-031-2694
CR-133-N	12598	NSNL	REPL		423A	28480	9N6625-00-880-4978
CRT-3	12678	NSNL	REPL		RT-20A	88869	1H5950-01-067-3203
CR9	47904	&&6720-00-467-0974	REPL	1	C-30BP	80009	7G6720-01-095-2205
CV-2343/U	MIL	NSNL	REPL		10514A	28480	9N5985-00-087-4714
CW-541B/USM-117	MIL	NSNL	GA		N/A		
CX20PS	14135	9N5985-00-145-3514	STD		CX20PS	14135	9N5985-00-145-3514
CX90S	31791	NSNL	REPL		CX20PS	14135	9N5985-00-145-3514
CY-245/U	MIL	1H6625-00-301-4738	GA		N/A		
CY-669/U	MIL	1H6625-00-649-2737	GA		N/A		
C1580	80103	1H6625-01-067-3275	REPL		TCR-300S-3-1	89022	1H6625-LL-MHE-4110
C20PS	14135	1H4931-00-921-7357	STD		C20PS	14135	1H4931-00-921-7357

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX A

REFERENCE EQUIPMENT TO STANDARD EQUIPMENT

REFERENCE EQUIPMENT				STANDARD EQUIPMENT		
MODEL	FSCM NSN	STATUS	NOTES	MODEL	FSCM	NSN
C4479	91161 1H6625-LL-HHE-2821	1387		N/A		
C60-S	31791 NSNL	REPL		C20PS	14135	1H4931-00-921-7357
DA-115/U	MIL 1H4931-00-346-8264	1387		N/A		
DA-140/AP	MIL NSNL	REPL		8201	70998	1H6625-00-994-6797
DA-145/U	MIL 7G5985-00-539-6126	REPL		WF-0025	00929	7G5985-00-539-6126
DA-146/U	MIL 9N5985-00-538-7328	REPL		WF-0055	00929	9N5985-00-538-7328
DA-148/U	MIL 9N5985-00-538-7329	REPL		WF-0050	00929	9N5985-00-572-6267
DA-177/U	MIL 1H5985-00-587-6905	REPL		8404	70998	1H6625-01-150-1897
DA-177A/U	MIL 1H6625-00-994-6797	1387		N/A		
DA-242/U	MIL 1H5985-00-792-9928	REPL		B-1576	91161	1H5985-00-792-9928
DA-242A/U	MIL 1H5985-00-792-9928	REPL		B-1576	91161	1H5985-00-792-9928
DA-274/U	MIL NSNL	REPL		8404	70998	1H6625-01-150-1897
DA-296A/GRM-50	MIL 1H6625-00-762-3872	1387		N/A		
DA-366/U	MIL 1H6625-00-078-4324	REPL		371BNM	99899	1H6625-00-970-3685
DA-371/U	MIL NSNL	REPL		8135	70998	9N6625-00-773-7311
DA-412/U	MIL 1H6625-00-907-8347	REPL		8404	70998	1H6625-01-150-1897
DA-412A/U	MIL 1H6625-00-930-1810	REPL		8404	70998	1H6625-01-150-1897
DA-412B/U	MIL 1H5985-01-060-3476	REPL		8404	70998	1H6625-01-150-1897
DA-412C/U	MIL 1H6625-LL-HHE-2821	REPL		8404	70998	1H6625-01-150-1897
DA-43/U	MIL 1H6625-00-538-1164	1387		N/A		
DA-484/URT	MIL NSNL	REPL		DPTC-25KFM	91161	1H5985-01-152-4077
DA-507/URT	MIL NSNL	REPL		DPTC-50KFM	91161	1H5985-01-152-4078
DA-64/UP	MIL 1H6625-00-376-1634	1387		N/A		
DA-64B/UP	MIL 1H6625-00-642-8911	1387		N/A		
DA-88/U	MIL 1H6625-00-209-6841	REPL		8404	70998	1H6625-01-150-1897
DA-88A/U	MIL NSNL	REPL		8404	70998	1H6625-01-150-1897
DA-91/U	MIL 1H5985-01-060-3476	1387		N/A		
DA-91A/U	MIL 1H6625-01-065-5341	REPL		8404	70998	1H6625-01-150-1897
DA52-3	05591 NSNL	GA		N/A		
DBGS385-1000	01220 1H6625-00-762-9285	1387		N/A		
DBGS385-1000	52542 1H6625-00-762-9285	1387		N/A		
DB655	11837 1H6625-00-756-1507	1387		N/A		
DB655-639A	11837 1H6625-00-756-1507	1387		N/A		

Source: https://assist.dla.mil -- Downloaded: 202610-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX A

REFERENCE EQUIPMENT TO STANDARD EQUIPMENT

REFERENCE EQUIPMENT MODEL	FSCM	NSN	STATUS	NOTES	STANDARD EQUIPMENT MODEL	FSCM	NSN
DC-122	12598	NSNL	REPL		3040B-20	99899	1H5985-00-067-6750
DCR150-10A	49956	1H6130-01-040-9810	REPL		DCR150-12B	49956	7Z6625-01-136-3178
DCR150-12B	49956	7Z6625-01-136-3178	STD		DCR150-12B	49956	7Z6625-01-136-3178
DCR40-20A	49956	1R6625-00-841-8917	REPL		DCR40-25B	49956	1H6130-01-040-9808
DCR40-25B	49956	1H6130-01-040-9808	STD		DCR40-25B	49956	1H6130-01-040-9808
DCR600-75B	49956	7Z6625-01-033-7479	REPL		BHK-500-0.4M	85604	7Z6625-01-031-8855
DPTC-25KFM	91161	1H5985-01-152-4077	STD		DPTC-25KFM	91161	1H5985-01-152-4077
DPTC-50KFM	91161	1H5985-01-152-4078	STD		DPTC-50KFM	91161	1H5985-01-152-4078
DV411-10K	11837	1H6625-00-624-8791	1387		N/A		
D44C15	06424	1H6625-00-291-0956	REPL		C20PS	14135	1H4931-00-921-7357
D44C15	56232	1H6625-00-291-0956	1387		N/A		
D44L15	06424	1H6625-00-841-5020	REPL		L20PS	14135	906625-00-738-2716
D44S15	06424	1H5985-00-104-5981	REPL		S11PS	14135	9N5985-00-439-3536
D44X15	06424	NSNL	REPL		CX20PS	14135	9N5985-00-145-3514
EJ-201V	83008	NSNL	REPL		P6161	80089	9N5950-00-645-1807
EJ-401V	83008	NSNL	REPL		P6161	80089	9N5950-00-645-1807
EN/DEBB-1	F6130	NSNL	GA		N/A		
E1010VA	83008	NSNL	REPL		W10MT3A	13850	9S6120-00-054-7794
E103	88869	1H6625-00-490-8844	1387		N/A		
FCR100	49956	NSNL	REPL		153B/403SD-001	25965	7G6625-01-197-9866
FP-5	08098	NSNL	GA		N/A		
FR30-150-LM	11920	NSNL	REPL		5015V	98095	1H6625-01-224-0215
F1403N	93459	1H6625-01-018-0932	1387		N/A		
F5150N1	80009	NSNL	GA		N/A		
G-101	77327	9N5985-00-921-3697	STD		G-101	77327	9N5985-00-921-3697
GA810K	26512	NSNL	REPL		432-D	80138	9N5985-00-087-2547
GIL-360-1	00341	NSNL	GA		N/A		
GM-318-C4	60674	9N6625-01-036-2020	STD		GM-318-C4	60674	9N6625-01-036-2020
GM-318-C4	95712	9N6625-01-036-2020	REPL		GM-318-C4	60674	9N6625-01-036-2020
G281A	28480	9N5985-00-772-6676	STD		G281A	28480	9N5985-00-772-6676
G347A	28480	1H6625-00-887-7783	GA		N/A		
G375A	28480	&&5985-00-596-5378	REPL		G-101	77327	9N5985-00-921-3697
G382A	28480	9N5985-00-771-8421	REPL		G-101	77327	9N5985-00-921-3697

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX A

REFERENCE EQUIPMENT TO STANDARD EQUIPMENT

REFERENCE EQUIPMENT					STANDARD EQUIPMENT		
MODEL	FSCM	NSN	STATUS	NOTES	MODEL	FSCM	NSN
G485B	28480	NSNL	REPL		314	00443	1H6625-01-039-5259
H-2190	49673	NSNL	GA	1	N/A		
H-4065B	00929	1H6625-01-067-3271	REPL		WE-0035	00929	1H6625-01-067-3271
HL-160A	12110	1H6625-01-065-5307	REPL		C20PS	14135	1H4931-00-921-7357
HR40-5B	09206	1H6130-00-835-2608	1387		N/A		
HR40-5B	52542	1H6130-00-835-2608	1387		N/A		
HV300-1	89022	NSNL	REPL		TCR-300S-3-1	89022	1H6625-LL-MHE-4110
HV300-1.5M	89022	NSNL	REPL		TCR-300S-3-1	89022	1H6625-LL-MHE-4110
HX292B	28480	NSNL	GA		N/A		
H281A	28480	9N5985-00-295-9824	GA		N/A		
H638A	00929	NSNL	REPL		BA-C-110C	00341	1H6625-01-030-5505
H752C	28480	8A5985-00-729-6971	REPL		574-10	00443	1H6625-LL-MHE-8018
H752D	28480	9N5985-00-814-4721	REPL		574-20	00443	1H6625-LL-MHE-8019
H810B	28480	NSNL	GA		N/A		
IV-1-2M	83008	1H5950-01-036-1977	REPL		P6161	80089	9N5950-00-645-1807
JN192W	00341	1H6625-00-907-8347	1387		N/A		
JQE-150-1	85604	NSNL	REPL		DCR150-12B	49956	7Z6625-01-136-3178
JQE-150-15M	85604	1H6625-01-034-2216	REPL		DCR150-12B	49956	7Z6625-01-136-3178
JQE-150-3.5M	85604	NSNL	REPL		DCR150-12B	49956	7Z6625-01-136-3178
JQE-36-3M	85604	1H6130-00-471-1735	STD		JQE-36-3M	85604	1H6130-00-471-1735
J281A	28480	9N5985-00-606-9161	STD		J281A	28480	9N5985-00-606-9161
J347A	28480	1H6625-00-445-6928	GA		N/A		
J382A	28480	7G6625-00-679-0627	STD		J382A	28480	7G6625-00-679-0627
KS60-10M	85604	NSNL	REPL		6266B	28480	9G6130-00-137-0167
KU110L1	14135	1H5985-01-039-2317	1387		N/A		
K362A	28480	9N5985-00-488-7434	STD		K362A	28480	9N5985-00-488-7434
K382A	28480	9N5985-00-822-8666	STD		K382A	28480	9N5985-00-822-8666
K420D	11332	1H6625-01-018-1207	GA		N/A		
K422A	28480	1H6625-00-874-7733	STD		K422A	28480	1H6625-00-874-7733
K422A-001	28480	9V6625-00-495-7898	REPL		K422A	28480	1H6625-00-874-7733
K4240C	11332	1H6625-01-095-8843	GA		N/A		
K486A	28480	8A6625-00-880-1217	GA		N/A		
K752C	28480	9I5985-00-913-9842	STD		K752C	28480	9I5985-00-913-9842

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX A

REFERENCE EQUIPMENT TO STANDARD EQUIPMENT

REFERENCE EQUIPMENT					STANDARD EQUIPMENT		
MODEL	FSCM	NSN	STATUS	NOTES	MODEL	FSCM	NSN
L-141B	12110	1H6625-01-065-5308	REPL		L20PS	14135	906625-00-738-2716
LA-60N	00929	9N5915-00-725-6051	STD		LA-60N	00929	9N5915-00-725-6051
LL141B	12110	NSNL	1387		N/A		
LP-415A-FM	80103	NSNL	REPL		LQ-415	80103	1H6625-01-178-9497
LQ-415	80103	1H6625-01-178-9497	STD		LQ-415	80103	1H6625-01-178-9497
LT-6000	01341	NSNL	REPL		LA-60N	00929	9N5915-00-725-6051
L15S	31791	NSNL	REPL		L20PS	14135	906625-00-738-2716
L20PS	14135	906625-00-738-2716	STD		L20PS	14135	906625-00-738-2716
L24PS	14135	1H6625-00-841-5020	1387		N/A		
M-1012A	12678	1H6625-01-206-2974	REPL		M-1012A	88869	1H6625-01-206-2974
M-1012A	88869	1H6625-01-206-2974	STD		M-1012A	88869	1H6625-01-206-2974
M-1012A-AC	88869	7Z6625-LL-HHE-8011	REPL		M-1012A	88869	1H6625-01-206-2974
M-255	14140	NSNL	GA		N/A		
M-50	98202	NSNL	GA	1	N/A		
MA-648A	96341	9N5985-00-111-5020	REPL		UNDER REVIEW		
MA-8F208	96341	1H6625-00-392-0521	REPL		UNDER REVIEW		
MC-5001B	32421	1H6625-01-010-0736	GA		N/A		
MC-501A	32421	1H6625-01-010-0486	GA		N/A		
MK-704/USM-118	MIL	NSNL	GA		N/A		
MK-704/USM-118A	MIL	NSNL	GA		N/A		
MK-827/USM-118	MIL	NSNL	GA		N/A		
MK-827/USM-118A	MIL	NSNL	GA		N/A		
MK-828/USM-118A	MIL	NSNL	GA		N/A		
MV-828A/G	85711	NSNL	GA		N/A		
MX-1258/U	MIL	9Y6625-00-301-0815	GA		N/A		
MX-1545/USM-37	MIL	NSNL	GA		N/A		
MX-2012/U	MIL	1H6625-00-506-4359	GA		N/A		
MX-2144/U	MIL	NSNL	GA	1	N/A		
MX-2144A/U	MIL	NSNL	GA	1	N/A		
MX-2144B/U	MIL	NSNL	GA	1	N/A		
M2G3	13850	9N5950-00-877-4863	STD		M2G3	13850	9N5950-00-877-4863
M5	13850	9N5950-00-504-9090	STD		M5	13850	9N5950-00-504-9090
M5C-160-8	52542	&A6625-LL-HHE-2884	1387		N/A		

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX A

REFERENCE EQUIPMENT TO STANDARD EQUIPMENT

REFERENCE EQUIPMENT					STANDARD EQUIPMENT		
MODEL	FSCM	NSN	STATUS	NOTES	MODEL	FSCM	NSN
M546	57646	NSNL	REPL		M602	57646	NSNL
M602	57646	NSNL	STD		M602	57646	NSNL
N-6284-A	77327	NSNL	GA		N/A		
NHA4017C/1	03950	1H6625-01-095-8844	GA		N/A		
N157B	00929	1H6625-01-037-9435	REPL		L20PS	14135	9D6625-00-738-2716
N301-0-2	95924	NSNL	GA	1	N/A		
N420C	11332	&&6625-00-923-8947	GA		N/A		
N423	11332	NSNL	GA		N/A		
N443	11332	1H6625-01-194-4013	GA		N/A		
N9412-20	09992	1H5985-01-203-5192	STD		N9412-20	09992	1H5985-01-203-5192
OD-1119 A/B B/T E	96341	1H5895-01-066-6943	1387		N/A		
OD8F208	96341	1H6625-00-392-0521	1387		N/A		
OD8F248	96341	NSNL	1387		N/A		
PC92350007-1	38597	1H6625-00-585-4915	REPL		240C	12697	1H6625-00-585-4915
PDA-6	01113	1H6625-01-040-0304	GA		N/A		
PGF	01113	1H5935-01-040-0305	GA		N/A		
P281B	28480	9N5985-00-136-8330	STD		P281B	28480	9N5985-00-136-8330
P347A	28480	1H6625-00-691-6597	GA		N/A		
P382A	28480	6G6625-00-752-3222	STD		P382A	28480	6G6625-00-752-3222
P424A	28480	1R6625-00-980-9302	STD		P424A	28480	1R6625-00-980-9302
P486A	28480	6G6625-00-404-0409	GA		N/A		
P487B	28480	9N6625-00-618-9192	GA	1	N/A		
P6006	80009	1H6625-00-077-7187	GA		N/A		
P6008	80009	NSNL	GA		N/A		
P6009	80009	NSNL	GA		N/A		
P6016	80009	1H6625-00-816-9321	GA		N/A		
P6021	80009	1H6625-00-172-6612	GA		N/A		
P6028	80009	NSNL	GA		N/A		
P6046	80009	1H6625-00-372-5237	GA		N/A		
P6053B	80009	NSNL	GA		N/A		
P6062A	80009	NSNL	GA		N/A		
P6075A	80009	NSNL	GA		N/A		
P6106	80009	&&6625-01-112-5768	GA		N/A		

Source: https://assist.dla.mil -- Downloaded: 202610-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX A

REFERENCE EQUIPMENT TO STANDARD EQUIPMENT

REFERENCE EQUIPMENT				STANDARD EQUIPMENT		
MODEL	FSCM	NSN	STATUS NOTES	MODEL	FSCM	NSN
P6161	80089	9N5950-00-645-1807	STD	P6161	80089	9N5950-00-645-1807
P6411A	80089	NSNL	REPL	P6161	80089	9N5950-00-645-1807
QH-2-30	12457	NSNL	REPL	QHB-2-30	12457	1R5985-00-991-1013
QHB-2-30	12457	1R5985-00-991-1013	STD	QHB-2-30	12457	1R5985-00-991-1013
QR36-15A	49956	1H6625-00-294-4917	REPL	DCR40-25B	49956	1H6130-01-040-9808
R-1011AA	94990	&&6625-LL-HHE-2886	REPL	R-1011B	94990	1H6625-01-205-1224
R-1011B	94990	1H6625-01-205-1224	STD	R-1011B	94990	1H6625-01-205-1224
RAM-230A	09449	9N5985-00-104-3568	REPL	102AC46-1E	01456	1H6625-00-178-0008
RB-503C-S1177	07342	1H6625-00-733-5914	REPL	RT-30A	88869	1H6625-LL-HHE-4050
RB-503T	07342	9N6625-00-174-6625	REPL	RT-30A	88869	1H6625-LL-HHE-4050
RDA	14655	9N6625-00-935-1331	REPL	240C	12697	1H6625-00-585-4915
RDB	14655	1H6625-00-302-8319	REPL	240C	12697	1H6625-00-585-4915
RDC	14655	1H6625-00-296-1665	REPL	1433-9724	24655	1H6625-00-0 -3571
RE40-5M	89022	7Z6625-01-036-2030	REPL	6266B	28480	9G6130-00-137-0167
RFB-552-50	14140	1H5905-00-882-6496	REPL	432-D	80138	9N5985-00-[illegible]7-2547
RT-2	12678	1H6625-00-859-5184	REPL	RT-20A	88869	1H5950-01-067-3203
RT-20A	12678	1H5950-01-067-3203	REPL	RT-20A	88869	1H5950-01-067-3203
RT-20A	88869	1H5950-01-067-3203	STD	RT-20A	88869	1H5950-01-067-3203
RT-30	12678	1H5950-01-067-3204	REPL	RT-30A	88869	1H6625-LL-HHE-4050
RT-30A	12678	1H6625-LL-HHE-4050	REPL	RT-30A	88869	1H6625-LL-HHE-4050
RT-30A	88869	1H6625-LL-HHE-4050	STD	RT-30A	88869	1H6625-LL-HHE-4050
RT-6M	88869	NSNL	1387	N/A		
RT-7	12678	1H6625-00-733-5914	REPL	RT-30A	88869	1H6625-LL-HHE-4050
RT-8	12678	1H6625-00-999-0866	REPL	M-1012A	88869	1H6625-01-206-2974
RT-9	12678	1H6625-00-675-4983	REPL	M-1012A	88869	1H6625-01-206-2974
R362A	28480	9N5915-00-488-7437	STD	R362A	28480	9N5915-00-488-7437
R382A	28480	1H5985-00-822-7874	STD	R382A	28480	1H5985-00-822-7874
R422A	28480	1R6625-00-981-9518	STD	R422A	28480	1R6625-00-981-9518
R486A	28480	9N6625-00-931-8812	GA	N/A		
R752C	28480	9N4931-00-777-1373	STD	R752C	28480	9N4931-00-777-1373
S-175	11787	NSNL	REPL	S281A	28480	1R4920-01-029-4624
S-347A	28480	7Z6625-00-859-5170	GA	N/A		
S-501C/979	11332	1H6625-01-019-8685	GA	N/A		

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX A

REFERENCE EQUIPMENT TO STANDARD EQUIPMENT

REFERENCE EQUIPMENT MODEL	FSCM	NSN	STATUS	NOTES	STANDARD EQUIPMENT MODEL	FSCM	NSN
SA-78	23042	NSNL	REPL		442-D	80138	9N5905-00-313-9064
SC-58	88869	1H6625-00-733-5914	REPL		RT-30A	88869	1H6625-LL-HHE-4050
SCR-300-2	89022	NSNL	REPL		TCR-300S-3-1	89022	1H6625-LL-HHE-4110
SCR-300-3	89022	1H6625-01-039-2258	REPL		TCR-300S-3-1	89022	1H6625-LL-HHE-4110
SL-140	12110	1H6625-01-065-8182	REPL		S11!	14135	9N5985-00-439-3536
SL-36-2M	96762	1H6130-01-041-3336	REPL		~SB	28480	9G6130-00-137-0167
SM-160-2AM	85604	NSNL	REPL		DCR150-12B	49956	7Z6625-01-136-3178
SM-160-2M	85604	NSNL	REPL		DCR150-12B	49956	7Z6625-01-136-3178
SPN-Z1	82199	7Z6625-LL-HHE-4184	GA		N/A		
SPX-3031	12678	1H5950-01-040-0282	REPL		SPX-3031	88869	1H5950-01-040-0282
SPX-3031	88869	1H5950-01-040-0282	STD		SPX-3031	88869	1H5950-01-040-0282
ST-100	12678	9N5950-00-679-6862	REPL		ST-100	88869	9N5950-00-679-6862
ST-100	88869	9N5950-00-679-6862	STD		ST-100	88869	9N5950-00-679-6862
ST-100A	12678	9N5950-00-679-5019	REPL		ST-100	88869	9N5950-00-679-6862
ST-100A	88869	9N5950-00-679-5019	REPL		ST-100	88869	9N5950-00-679-6862
ST-200A	12678	NSNL	REPL		SPX-3031	88869	1H5950-01-040-0282
ST-200F	12678	1H5950-00-294-4896	REPL		SPX-3031	88869	1H5950-01-040-0282
ST-213	12678	6G6625-00-916-3122	REPL		SPX-3031	88869	1H5950-01-040-0282
ST-248A	12678	NSNL	REPL		SPX-3031	88869	1H5950-01-040-0282
S10P	14135	NSNL	REPL		S11PS	14135	9N5985-00-439-3536
S102LCI	14135	NSNL	REPL		S11PS	14135	9N5985-00-439-3536
S11PS	14135	9N5985-00-439-3536	STD		S11PS	14135	9N5985-00-439-3536
S1303-A1	94990	NSNL	REPL		R-1011B	94990	1H6625-01-205-1224
S281A	28480	1R4920-01-029-4624	STD		S281A	28480	1R4920-01-029-4624
S30S	31791	&A6130-01-040-9811	REPL		S11PS	14135	9N5985-00-439-3536
S382C	28480	9N6625-00-179-8448	STD		S382C	28480	9N6625-00-179-8448
S4420-30	77327	NSNL	REPL		3043B-30	99899	9N5985-00-450-8802
S485A	28480	7Z6625-00-288-0179	REPL		214	00443	1H6625-00-395-0779
S501B	00929	1H6625-00-535-9532	STD		S501B	00929	1H6625-00-535-9532
S910A	28480	1H6625-00-953-9128	1387	2	N/A		
T-2098	12598	1H5985-01-060-3476	REPL		8404	70998	1H6625-01-150-1897
TCR-300S-3-1	89022	1H6625-LL-HHE-4110	STD		TCR-300S-3-1	89022	1H6625-LL-HHE-4110
TD-1159/U	80009	NSNL	1387				NSNL

Source: https://assist.dla.mil -- Downloaded: 202640-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX A

REFERENCE EQUIPMENT TO STANDARD EQUIPMENT

REFERENCE EQUIPMENT					STANDARD EQUIPMENT		
MODEL	FSCM	NSN	STATUS	NOTES	MODEL	FSCM	NSN
TDR-29011	87864	9N5985-00-062-6919	STD		TDR-29011	87864	9N5985-00-062-6919
TDR-29061-1	87864	NSNL	REPL		TDR-29011	87864	9N5985-00-062-6919
TM-1	82199	9N6625-00-717-6560	GA	1	N/A		
TM503	80009	1H6625-00-373-7528	GA		N/A		
TO-36-5M	89022	1H6625-01-065-8251	REPL		6266B	28480	9G6130-00-137-0167
TRB50	04423	9Y6625-00-494-5622	GA		N/A		
TS-234/UP	64959	NSNL	1387				NSNL
TS-235/UP	64959	NSNL	1387				NSNL
TSTP27	25647	1H6625-01-136-8476	GA		N/A		
TV795G	17870	NSNL	REPL		850-CT2W	83332	NSNL
UC1M	58474	NSNL	REPL		W5MT3A	13850	9N5950-00-987-5601
UC1MB	58474	NSNL	REPL		W5MT3A	13850	9N5950-00-987-5601
UHR-220	88865	1H6625-00-296-1412	REPL		BHK-500-0.4M	85604	7Z6625-01-031-8855
U6608	77327	NSNL	GA		N/A		
VT2NE	44655	1H5950-01-036-1982	REPL		W5MT3A	13850	9N5950-00-987-5601
VT8GC	44655	NSNL	REPL		W5MT3A	13850	9N5950-00-987-5601
V420D	11332	NSNL	GA		N/A		
V4420-20	77327	NSNL	REPL		3040B-20	99899	1H5985-00-067-6750
V637	99899	9N6625-01-031-1981	STD		V637	99899	9N6625-01-031-1981
WE-0035	00929	1H6625-01-067-3271	STD		WE-0035	00929	1H6625-01-067-3271
WF-0025	00929	7G5985-00-539-6126	STD		WF-0025	00929	7G5985-00-539-6126
WF-0050	00929	9N5985-00-572-6267	STD		WF-0050	00929	9N5985-00-572-6267
WF-0055	00929	9N5985-00-538-7328	STD		WF-0055	00929	9N5985-00-538-7328
WG301A	49671	1H6625-00-932-7260	GA		N/A		
WG301A	79089	1H6625-00-932-7260	GA	2	N/A		
WG301A	86684	1H6625-00-932-7260	GA		N/A		
WR-102	09449	1H6625-01-117-8746	REPL		102AC46-1E	01456	1H6625-00-178-0008
W10G3M	13850	9G6120-00-033-3776	STD		W10G3M	13850	9G6120-00-033-3776
W10HG3M	13850	1H6120-00-032-1173	STD		W10HG3M	13850	1H6120-00-032-1173
W10HMT3	13850	&A6625-00-143-0784	REPL		W10MT3A	13850	9S6120-00-054-7794
W10MT	13850	NSNL	REPL		W10MT3A	13850	9S6120-00-054-7794
W10MT3	13850	9G6120-00-682-2557	REPL		W10MT3A	13850	9S6120-00-054-7794
W10MT3A	13850	9S6120-00-054-7794	STD		W10MT3A	13850	9S6120-00-054-7794

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX A

REFERENCE EQUIPMENT TO STANDARD EQUIPMENT

REFERENCE EQUIPMENT					STANDARD EQUIPMENT		
MODEL	FSCM	NSN	STATUS	NOTES	MODEL	FSCM	NSN
W2MT	13850	NSNL	REPL		W5MT3A	13850	9N5950-00-987-5601
W2MT3	13850	NSNL	REPL		W5MT3A	13850	9N5950-00-987-5601
W30HG3M	13850	1H5950-00-294-4872	1387		N/A		
W40-NC	06351	7Z6625-00-148-8098	REPL		102AC46-1E	01456	1H6625-00-178-0008
W40-NCM	06351	NSNL	REPL		102AC46-1E	01456	1H6625-00-178-0008
W5G3M	13850	9G6120-00-879-3698	STD		W5G3M	13850	9G6120-00-879-3698
W5MT	13850	7Z5950-00-688-5722	REPL		W5MT3A	13850	9N5950-00-987-5601
W5MT3	13850	9N5950-00-617-9242	REPL		W5MT3A	13850	9N5950-00-987-5601
W5MT3A	13850	9N5950-00-987-5601	STD		W5MT3A	13850	9N5950-00-987-5601
W8MT3VM	13850	NSNL	REPL		W10MT3A	13850	9S6120-00-054-7794
XA-0640	00929	7Z5961-00-940-0449	GA	1	N/A		
XB1000	00929	1H6625-00-876-3100	REPL		423A	28480	9N6625-00-880-4978
XD-3A	04423	1H6625-00-876-3106	REPL	2	423A	28480	9N6625-00-880-4978
XL-140	12110	1H6625-01-065-8183	REPL		CX20PS	14135	9N5985-00-145-3514
X101-S8	77327	1H6625-00-961-0790	REPL		X382A	28480	1H6625-00-602-2089
X164A	00929	1H6625-00-993-9085	REPL		X382A	28480	1H6625-00-602-2089
X281A	28480	9N5985-00-892-0732	STD		X281A	28480	9N5985-00-892-0732
X301A	13047	1H5985-01-069-2318	STD		X301A	13047	1H5985-01-069-2318
X382A	28480	1H6625-00-602-2089	STD		X382A	28480	1H6625-00-602-2089
X420C	11332	NSNL	GA		N/A		
X420D	11332	NSNL	GA		N/A		
X4240C	11332	1H6625-01-095-8845	GA		N/A		
X4420-A-10	77327	1H5985-01-048-3901	REPL		3045C-10	99899	1R5985-00-604-8604
X485A	28480	9N5985-00-442-6083	GA		N/A		
X487B	28480	7Z6625-00-656-2454	GA	1	N/A		
X501B	00929	NSNL	REPL		X301A	13047	1H5985-01-069-2318
X501C	00929	1H6625-00-198-5812	REPL		X301A	13047	1H5985-01-069-2318
X601B	00929	7Z5985-00-103-9682	REPL		X281A	28480	9N5985-00-892-0732
X610C	00929	1H5985-00-364-3668	REPL		X752C	28480	9N5985-00-646-9472
X752C	28480	9N5985-00-646-9472	STD		X752C	28480	9N5985-00-646-9472
X910B	28480	NSNL	REPL		X301A	13047	1H5985-01-069-2318
010-0037-00	80009	1H6625-00-816-9321	GA		N/A		
010-0076-00	80009	1H6625-00-148-8099	GA		N/A		

Source: https://assist.dla.mil -- Downloaded: 202610-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX A

REFERENCE EQUIPMENT TO STANDARD EQUIPMENT

REFERENCE EQUIPMENT					STANDARD EQUIPMENT		
MODEL	FSCM	NSN	STATUS	NOTES	MODEL	FSCM	NSN
010-0127-00	80009	1H6625-00-077-7187	GA		N/A		
010-0172-00	80009	1H6625-00-922-9296	GA		N/A		
010-0175-01	80009	1H6625-00-185-6110	GA		N/A		
010-0177-01	80009	1H6625-00-498-2232	GA		N/A		
010-0197-00	80009	1H6625-00-311-6869	GA		N/A		
010-0213-00	80009	1H6625-00-372-5237	GA		N/A		
010-0264-01	80009	1H6625-01-033-4728	GA		N/A		
010-6053-03	80009	1H6625-01-039-5234	GA		N/A		
010-6053-13	80009	NSNL	GA		N/A		
010-6056-03	80009	NSNL	GA		N/A		
010-6101-02	80009	1H6625-00-463-5241	GA		N/A		
010-6106-03	80009	NSNL	GA		N/A		
011-0074-00	03950	NSNL	GA		N/A		
0111T25SR	06049	&&5950-01-023-9857	REPL		P6161	80089	9N5950-00-645-1807
012-0180-00	80009	1H6625-01-017-1238	GA		N/A		
013-0180-00	80009	NSNL	GA		N/A		
015-0057-02	80009	1H6625-01-010-1751	GA		N/A		
015-0135-01	80009	1H6625-01-067-0772	GA		N/A		
015-0140-13	80009	NSNL	GA		N/A		
015-05140-03	80009	NSNL	GA		N/A		
07006	12678	&&6625-00-992-3037	GA	1	N/A		
07048	00752	1H6625-00-992-3036	GA		N/A		
07048	12678	NSNL	GA	1	N/A		
07048T	00752	NSNL	GA		N/A		
07048T	12678	NSNL	GA		N/A		
0732	55026	1H6625-00-368-9223	GA		N/A		
0874-9099	24655	1H5935-00-370-8549	REPL		0874-9099	82316	1H5935-00-370-8549
0874-9099	82316	1H5935-00-370-8549	STD		0874-9099	82316	1H5935-00-370-8549
0874-957	82316	NSNL	REPL		0874-9577	82316	&&5840-00-868-1287
0874-9577	24655	&&5840-00-868-1287	REPL		0874-9577	82316	&&5840-00-868-1287
0874-9577	82316	&&5840-00-868-1287	STD		0874-9577	82316	&&5840-00-868-1287
1-10	93459	&&6625-00-192-0838	REPL		8491A-010	28480	9N5985-00-865-0108
1-20	93459	9N5985-00-222-9037	REPL		8491A-020	28480	1H4935-01-031-2694

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX A

REFERENCE EQUIPMENT TO STANDARD EQUIPMENT

REFERENCE EQUIPMENT					STANDARD EQUIPMENT		
MODEL	FSCM	NSN	STATUS	NOTES	MODEL	FSCM	NSN
1-3	93459	&&5985-00-498-5838	REPL		8491A-003	28480	9N5985-00-167-0544
1-6	93459	7Z5985-00-498-8414	REPL		8491A-006	28480	9N5895-00-230-1827
1/432D	80138	9N5985-00-252-8026	STD		1/432D	80138	9N5985-00-252-8026
100-564	28569	NSNL	GA		N/A		
100Q	24655	NSNL	REPL	1	1571-9831	13850	9G6110-00-087-4771
10000A02	30669	1H6625-01-017-9126	GA		N/A		
10002B	28480	1H6625-00-389-7007	GA		N/A		
10004A	28480	NSNL	GA		N/A		
10007A	28480	1H6625-01-017-1239	GA		N/A		
10007B	28480	1H6625-01-049-8460	GA		N/A		
1001	03782	7Z6625-LL-HHE-2878	REPL		423A	28480	9N6625-00-880-4978
1001	82199	NSNL	GA		N/A		
1001-M4	82199	7Z6625-00-866-0168	GA		N/A		
10014A	28480	1H6625-00-385-1156	GA		N/A		
1006A	28480	NSNL	GA		N/A		
10100C	28480	1H6625-00-106-7452	GA		N/A		
10125	19136	NSNL	1387		N/A		
102AC46-1E	01456	1H6625-00-178-0008	STD		102AC46-1E	01456	1H6625-00-178-0008
1027A	28481	1H6625-00-074-1291	GA		N/A		
10382656	00000	NSNL	REPL		BHK-500-0.4M	85604	7Z6625-01-031-8855
10457A	28480	&&5935-00-239-9553	GA		N/A		
10503A	28480	NSNL	GA		N/A		
10514A	28480	9N5985-00-087-4714	STD		10514A	28480	9N5985-00-087-4714
10519400	MIL	NSNL	GA		N/A		
10519453	MIL	1H6130-00-445-6933	GA		N/A		
10526T	28480	&&6625-00-170-6196	GA		N/A		
10528A	28480	1H4470-00-307-0437	GA		N/A		
10529A	28480	1H6625-00-490-7298	GA		N/A		
10536A	28480	1H6625-00-354-9730	GA		N/A		
10590A	28480	NSNL	GA		N/A		
10658140	18876	7Z5985-00-087-4714	REPL		10514A	28480	9N5985-00-087-4714
1081-0000-00	26805	1H5935-01-016-6059	GA		N/A		
108146-690	13973	1H6625-00-716-4031	GA		N/A		

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX A

REFERENCE EQUIPMENT TO STANDARD EQUIPMENT

REFERENCE EQUIPMENT					STANDARD EQUIPMENT		
MODEL	FSCM	NSN	STATUS	NOTES	MODEL	FSCM	NSN
108476-690	13973	1H6625-00-811-2435	GA		N/A		
10850B	50423	1H6625-01-040-9511	GA		N/A		
108573-690	13973	1H6625-01-037-9437	GA		N/A		
1091	06481	1H6625-00-910-2583	1387		N/A		
1091	31922	1H6625-00-910-2583	1387		N/A		
11-6403-00	96795	NSNL	GA		N/A		
1100-A	77327	NSNL	REPL		8491A-003	28480	9N5985-00-167-0544
11000	30669	1H6625-00-385-1157	GA		N/A		
110000	76526	1H6625-00-072-5590	1387		N/A		
11004A	28480	1H6625-00-567-5837	GA		N/A		
11005A	28480	7Z6625-LL-HHE-4086	GA		N/A		
11010	18778	NSNL	GA		N/A		
11027A	28480	1H6625-00-074-3703	GA		N/A		
11036A	28480	NSNL	GA		N/A		
11040A	28480	1H6625-00-628-6514	GA		N/A		
11042A	28480	NSNL	GA		N/A		
11044A	28480	1H6625-00-511-5383	GA	2	N/A		
11045A	28480	1H6625-00-995-7464	GA		N/A		
1106	80009	1H6130-01-018-1226	GA		N/A		
1106-A	77327	1H6130-01-018-1226	GA		N/A		
1108A	28480	1H6625-00-464-7743	GA		N/A		
1117B	28480	1H6625-00-932-2016	GA		N/A		
1120A	28480	7Z6625-00-150-6965	GA		N/A		
1123A	28480	NSNL	GA		N/A		
1124147	MIL	NSNL	REPL		10514A	28480	9N5985-00-087-4714
11290180	17773	NSNL	REPL		1425-4	93459	1H6930-01-140-4985
11473A	28480	NSNL	GA		N/A		
11500A	28480	9G5995-00-685-4683	GA		N/A		
11504A	28480	1H5982-00-088-6001	GA		N/A		
1156	77327	1H5985-00-288-0171	1387		N/A		
116	14856	NSNL	GA		N/A		
116B	58474	NSNL	REPL		W10MI3A	13850	9S6120-00-054-7794
11652A	28480	7Z6625-00-186-7685	GA		N/A		

Source: https://assist.dla.mil -- Downloaded: 202640-26T13:40Z
Check the source to verify that this is the currentversion before use.

APPENDIX A

REFERENCE EQUIPMENT TO STANDARD EQUIPMENT

REFERENCE EQUIPMENT					STANDARD EQUIPMENT		
MODEL	FSCM	NSN	STATUS	NOTES	MODEL	FSCM	NSN
11664A	28480	NSNL	GA		N/A		
11665B	28480	NSNL	GA		N/A		
11679A	28480	9N6625-01-055-6973	GA		N/A		
11679B	28480	NSNL	GA		N/A		
11692D	28480	9N5985-01-024-3832	STD		11692D	28480	9N5985-01-024-3832
1201B	24655	7Z6625-00-753-2109	GA	1	N/A		
1201C	24655	7Z6625-00-902-9745	GA	2	N/A		
1224-4	93459	NSNL	REPL		1425-4	93459	1H6930-01-140-4985
1228020P4	31637	1H5985-00-813-5433	1387		N/A		
1241	24655	NSNL	GA		N/A		
1267-9702	24655	1H6625-01-039-6571	REPL		TCR-300S-3-1	89022	1H6625-LL-HHE-4110
1290015P3	31637	1H6625-00-813-6847	GA		N/A		
1290015P4	31637	1H6625-00-813-6853	GA		N/A		
1290015P4	94117	NSNL	REPL		N9412-20	09992	1H5985-01-203-5192
1290019A1	31637	NSNL	GA		N/A		
1293021P2	31637	1H6625-00-023-5705	GA		N/A		
1293021P2	94117	NSNL	GA		N/A		
12989REVD	13327	1H6625-00-976-3868	1387		N/A		
1325	11837	1H6625-00-395-0785	GA		N/A		
13371	12598	1H5985-01-060-3476	1387		N/A		
134	80009	1H6525-01-010-1751	GA		N/A		
134303-1	45413	1H6625-00-463-5241	GA		N/A		
1346-9700	24655	7Z6625-01-009-6118	REPL		850-CT2W	83332	NSNL
1353	73386	1H6625-01-160-5093	REPL		1412-9410	24655	1H6625-00-465-6861
137617-1	45413	1H6625-00-463-5241	GA		N/A		
141043-2	49956	1H6625-00-922-9296	GA		N/A		
1412-9410	24655	1H6625-00-465-6861	STD		1412-9410	24655	1H6625-00-465-6861
1419-A	24655	1H6625-00-953-7537	REPL		1412-9410	24655	1H6625-00-465-6861
1419-B	24655	NSNL	REPL		1412-9410	24655	1H6625-00-465-6861
1419-9701	24655	1H6625-00-953-7537	REPL		1412-9410	24655	1H6625-00-465-6861
1419-9702	24655	1H6625-00-124-9382	REPL		1412-9410	24655	1H6625-00-465-6861
1423-9801	24655	7Z6625-00-775-1753	REPL		1412-9410	24655	1H6625-00-465-6861
1425-4	93459	1H6930-01-140-4985	STD		1425-4	93459	1H6930-01-140-4985

Source: https://assist.dla.mil -- Downloaded: 202610-26T13:40Z
Check the source to verify that this is the currentversion before use.

APPENDIX A

REFERENCE EQUIPMENT TO STANDARD EQUIPMENT

REFERENCE EQUIPMENT				STANDARD EQUIPMENT		
MODEL	FSCM	NSN	STATUS NOTES	MODEL	FSCM	NSN
1432-J	24655	NSNL	REPL	1433-9704	24655	9N6625-00-173-5441
1432-K	24655	1H6625-00-437-9157	REPL	1433-9722	24655	1H6625-00-947-7534
1432-L	24655	1H6625-00-975-1359	REPL	1433-9706	24655	&&6625-00-235-6308
1432-M	24655	7Z6625-00-553-7652	REPL	1433-9714	24655	1H6625-00-463-4011
1432-N	24655	NSNL	REPL	1433-9722	24655	1H6625-00-947-7534
1432-P	24655	1H6625-00-585-3152	REPL	1433-9726	24655	1H6625-00-140-8183
1432-T	24655	1H6625-00-840-4256	REPL	1433-9729	24655	1H6625-01-205-0820
1432-X	24655	1H6625-00-476-6838	REPL	1433-9722	24655	1H6625-00-947-7534
1432-9716	24655	NSNL	REPL	1433-9726	24655	1H6625-00-140-8183
1432-9720	24655	NSNL	REPL	1433-9729	24655	1H6625-01-205-0820
1432-9724	24655	NSNL	REPL	1433-9722	24655	1H6625-00-947-7534
1433-B	24655	1H6625-00-031-3521	REPL	1433-9724	24655	1H6625-00-031-3521
1433-G	24655	NSNL	REPL	1433-9731	24655	1H6625-00-480-0950
1433-J	24655	9N6625-00-173-5441	REPL	1433-9704	24655	9N6625-00-173-5441
1433-K	24655	1H6625-00-437-9157	REPL	1433-9722	24655	1H6625-00-947-7534
1433-L	24655	NSNL	REPL	1433-9706	24655	&&6625-00-235-6308
1433-M	24655	1H6625-00-463-4011	REPL	1433-9714	24655	1H6625-00-463-4011
1433-N	24655	1H6625-00-947-7534	REPL	1433-9722	24655	1H6625-00-947-7534
1433-P	24655	1H6625-00-228-9918	REPL	1433-9726	24655	1H6625-00-140-8183
1433-T	24655	1H6625-00-840-4256	REPL	1433-9729	24655	1H6625-01-205-0820
1433-U	24655	NSNL	REPL	1433-9729	24655	1H6625-01-205-0820
1433-W	24655	1H6625-00-102-9646	REPL	1433-9729	24655	1H6625-01-205-0820
1433-X	24655	1H6625-00-947-7534	REPL	1433-9722	24655	1H6625-00-947-7534
1433-Z	24655	1H6625-00-140-8183	REPL	1433-9726	24655	1H6625-00-140-8183
1433-9700	24655	NSNL	REPL	1433-9729	24655	1H6625-01-205-0820
1433-9704	24655	9N6625-00-173-5441	STD	1433-9704	24655	9N6625-00-173-5441
1433-9706	24655	&&6625-00-235-6308	STD	1433-9706	24655	&&6625-00-235-6308
1433-9710	24655	1H6625-00-840-4256	REPL	1433-9729	24655	1H6625-01-205-0820
1433-9712	24655	1H6625-00-947-7534	REPL	1433-9722	24655	1H6625-00-947-7534
1433-9714	24655	1H6625-00-463-4011	STD	1433-9714	24655	1H6625-00-463-4011
1433-9716	24655	NSNL	REPL	1433-9726	24655	1H6625-00-140-8183
1433-9718	24655	NSNL	1387	N/A		
1433-9720	24655	1H6625-00-102-9646	REPL	1433-9729	24655	1H6625-01-205-0820

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX A

REFERENCE EQUIPMENT TO STANDARD EQUIPMENT

REFERENCE EQUIPMENT					STANDARD EQUIPMENT		
MODEL	FSCM	NSN	STATUS	NOTES	MODEL	FSCM	NSN
1433-9722	24655	1H6625-00-947-7534	STD		1433-9722	24655	1H6625-00-947-7534
1433-9724	24655	1H6625-00-031-3521	STD		1433-9724	24655	1H6625-00-031-3521
1433-9726	24655	1H6625-00-140-8183	STD		1433-9726	24655	1H6625-00-140-8183
1433-9729	24655	1H6625-01-205-0820	STD		1433-9729	24655	1H6625-01-205-0820
1433-9731	24655	1H6625-00-480-0950	STD		1433-9731	24655	1H6625-00-480-0950
1434-G	24655	1H6625-00-067-9025	REPL		1433-9731	24655	1H6625-00-480-0950
1434-9707	24655	1H6625-00-067-9025	REPL		1433-9731	24655	1H6625-00-480-0950
1450-TBR	24655	NSNL	REPL		850-CT2W	83332	NSNL
1454-A	24655	1H6625-00-602-2087	REPL		UNDER REVIEW		
1454-9701	24655	NSNL	REPL		UNDER REVIEW		
1455-A	24655	1H6625-00-123-7458	REPL		UNDER REVIEW		
1455-B	24655	NSNL	REPL		UNDER REVIEW		
1455-9706	24655	6B4920-01-021-8513	REPL		UNDER REVIEW		
1480	99899	NSNL	GA		N/A		
1490-B	24655	1H6625-00-251-1158	REPL		1491-9704	24655	1H6625-00-251-1158
1490-D	24655	NSNL	1387		N/A		
1490-F	24655	1H6625-00-483-6777	REPL	1	1491-9704	24655	1H6625-00-251-1158
1491-D	24655	1H6625-00-251-1158	REPL		1491-9704	24655	1H6625-00-251-1158
1491-9704	24655	1H6625-00-251-1158	STD		1491-9704	24655	1H6625-00-251-1158
150S	49956	NSNL	REPL		1571-9831	13850	9G6110-00-087-4771
1506A	93459	9V6625-00-261-5033	STD		1506A	93459	9V6625-00-261-5033
153B/403SD-001	25965	7G6625-01-197-9866	STD		153B/403SD-001	25965	7G6625-01-197-9866
153B/403V	25965	7Z6625-01-136-3250	REPL		153B/403SD-001	25965	7G6625-01-197-9866
153B/403VTE	03950	7Z6625-01-136-3250	REPL		153B/403SD-001	25965	7G6625-01-197-9866
1570-ALS-15	13850	1H6110-00-895-2699	REPL		1571-9831	13850	9G6110-00-087-4771
1571-AL	13850	9G6110-00-087-4771	REPL		1571-9831	13850	9G6110-00-087-4771
1571-AL	24655	NSNL	REPL		1571-9831	13850	9G6110-00-087-4771
1571-9831	13850	9G6110-00-087-4771	STD		1571-9831	13850	9G6110-00-087-4771
158-100	93953	1H6130-00-660-8590	1387		N/A		
1581-AL	24655	NSNL	REPL		1571-9831	13850	9G6110-00-087-4771
1591-9700	13850	NSNL	GA		N/A		
1591-9700 LHA	03950	1H6625-01-040-2313	GA		N/A		
16-25	88113	NSNL	REPL		6296A	28480	1H6130-01-067-3777

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX A

REFERENCE EQUIPMENT TO STANDARD EQUIPMENT

REFERENCE EQUIPMENT					STANDARD EQUIPMENT		
MODEL	FSCM	NSN	STATUS	NOTES	MODEL	FSCM	NSN
160-100D	54778	NSNL	REPL		8135	70998	9N6625-00-773-7311
160A	80009	&&6625-00-792-4612	GA		N/A		
160B-150FN	54778	1H6625-01-065-8227	REPL		8135	70998	9N6625-00-773-7311
160B-600FN	54778	NSNL	REPL		8404	70998	1H6625-01-150-1897
162-B	77327	1H6625-01-017-1281	REPL		AU-65AMN	12457	1H6625-01-040-9528
175-0113-00	80009	NSNL	GA		N/A		
178-B	77327	1H6625-01-003-6118	REPL		J382A	28480	7G6625-00-679-0627
180A-470	54778	NSNL	GA		N/A		
189-100	93953	1H6625-00-773-6102	GA		N/A		
19K1	98732	1H6625-00-920-9927	1387		N/A		
195-B	77327	7Z6625-00-679-5386	REPL		X382A	28480	1H6625-00-602-2089
196A	28480	&&6720-00-863-2353	REPL	2	C-30BP	80009	7G6720-01-095-2205
197A	28480	&&6720-00-831-7888	REPL		197B	28480	&&6720-01-104-3402
197B	28480	&&6720-01-104-3402	STD		197B	28480	&&6720-01-104-3402
2-10	93459	1H6625-01-017-1278	STD		2-10	93459	1H6625-01-017-1278
2-20	93459	1H6625-01-017-1276	STD		2-20	93459	1H6625-01-017-1276
2-3	93459	1H6625-01-020-6032	STD		2-3	93459	1H6625-01-020-6032
2-30	93459	1H6625-01-014-3463	STD		2-30	93459	1H6625-01-014-3463
2-3414-30	09992	9N5985-00-999-8095	STD		2-3414-30	09992	9N5985-00-999-8095
2-40	93459	1H6625-01-014-3464	STD		2-40	93459	1H6625-01-014-3464
2-50	93459	1H6625-01-014-3465	1387		N/A		
2-6	93459	1H6625-01-017-1277	STD		2-6	93459	1H6625-01-017-1277
2001-6113-00	16179	9N5985-01-064-2513	STD		2001-6113-00	16179	9N5985-01-064-2513
2002-6113-00	16179	9N5985-00-192-0138	STD		2002-6113-00	16179	9N5985-00-192-0138
20020J	16179	NSNL	REPL		2002-6113-00	16179	9N5985-00-192-0138
20020P	16179	NSNL	REPL		2001-6113-00	16179	9N5985-01-064-2513
2028906-0701	06845	1H6625-00-886-1962	GA		N/A		
205A1	90101	7Z6625-00-984-4731	1387	1	N/A		
205A1-2	90101	NSNL	1387	1	N/A		
205B1	90101	7Z6625-00-077-7191	1387	1	N/A		
205B1-2	90101	7Z6625-00-919-5008	1387	1	N/A		
2088792-1	06845	1H5905-00-882-6496	1387		N/A		
2088792-1	27914	1H5905-00-882-6496	1387		N/A		

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX A

REFERENCE EQUIPMENT TO STANDARD EQUIPMENT

REFERENCE EQUIPMENT				STANDARD EQUIPMENT		
MODEL	FSCM	NSN	STATUS NOTES	MODEL	FSCM	NSN
21A	76526	1H6625-00-072-5590	REPL	JQE-36-3M	85604	1H6130-00-471-1735
210-20	93459	7Z6625-00-633-0231	REPL	8491A-020	28480	1H4935-01-031-2694
210-3	93459	7Z5985-01-096-6835	REPL	8491A-003	28480	9N5985-00-167-0544
210-6	93459	7Z5985-00-615-3102	REPL	8491A-006	28480	9N5895-00-230-1827
210A-3	93459	1H6625-LL-HHE-4111	STD	210A-3	93459	1H6625-LL-HHE-4111
21090	16179	1H5935-01-016-6060	GA	N/A		
214	00443	1H6625-00-395-0779	STD	214	00443	1H6625-00-395-0779
215709	50040	1H6625-00-993-9085	REPL	X382A	28480	1H6625-00-602-2089
217B-T3	58474	NSNL	REPL	W10HG3M	13850	1H6120-00-032-1173
22523	00213	1H6625-01-015-7661	1387	N/A		
22523ET	00213	NSNL	GA	N/A		
22749	99899	NSNL	REPL	613-M	77327	1H6625-00-973-1151
2328	15305	1H6625-00-078-4324	REPL	4375G	99899	1H6625-LL-HHE-8020
24-6-34	93459	1H6625-LL-HHE-8021	STD	24-6-34	93459	1H6625-LL-HHE-8021
240C	12697	1H6625-00-585-4915	STD	240C	12697	1H6625-00-585-4915
248	06424	NSNL	REPL	G281A	28480	9N5985-00-772-6676
253	77327	7Z6625-00-796-3157	GA	N/A		
2613-1104	12855	NSNL	1387	N/A		
270A-30	54778	NSNL	GA	N/A		
270A-470	54778	7Z6625-00-072-7153	GA	N/A		
271A-30	54778	7Z6625-00-530-2636	GA	N/A		
2901	27834	NSNL	REPL	371BNM	99899	1H6625-00-970-3685
292-6	34078	NSNL	REPL	4M-6	93459	1H6625-01-015-2356
3PNT51B	83008	NSNL	REPL	W5MI3A	13850	9N5950-00-987-5601
3PN1010	83008	NSNL	REPL	W10MI3A	13850	9S6120-00-054-7794
3PN501B	83008	NSNL	REPL	W5MI3A	13850	9N5950-00-987-5601
30-N	00929	NSNL	REPL	2-30	93459	1H6625-01-014-3463
30-0	80138	7Z5985-00-831-5991	REPL	355C	28480	1H5985-00-993-1377
300	80138	NSNL	REPL	432-D	80138	9N5985-00-087-2547
3000-10	99899	9N5985-00-816-4287	STD	3000-10	99899	9N5985-00-816-4287
3000-20	99899	NSNL	REPL	3040B-20	99899	1H5985-00-067-6750
3001-10	99899	NSNL	REPL	3041-10	99899	1H5985-01-039-5404
3002-10	99899	NSNL	REPL	3042B-10	99899	9N5985-00-465-8112

Source: https://assist.dla.mil -- Downloaded: 202610-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX A

REFERENCE EQUIPMENT TO STANDARD EQUIPMENT

REFERENCE EQUIPMENT				STANDARD EQUIPMENT		
MODEL	FSCM	NSN	STATUS NOTES	MODEL	FSCM	NSN
3002-20	99899	9N5985-00-578-5747	STD	3002-20	99899	9N5985-00-578-5747
3003-10	99899	1H6625-01-065-5289	REPL	3043B-10	99899	1H6625-01-065-5289
3003-20	99899	9N5985-00-882-8654	STD	3003-20	99899	9N5985-00-882-8654
3004-10	99899	9N5985-00-788-6962	STD	3004-10	99899	9N5985-00-788-6962
3004-20	99899	9N5985-00-714-3247	STD	3004-20	99899	9N5985-00-714-3247
3020A	99899	7Z5985-00-442-3051	REPL	778D	28480	9N5985-00-239-3215
30372	00443	1H6625-01-069-2232	1387	N/A		
3040-20	99899	1H6625-00-981-3248	REPL	3040B-20	99899	1H5985-00-067-6750
3040B-20	99899	1H5985-00-067-6750	STD	3040B-20	99899	1H5985-00-067-6750
3041-10	99899	1H5985-01-039-5404	STD	3041-10	99899	1H5985-01-039-5404
3041-20	99899	1R5985-00-757-0549	STD	3041-20	99899	1R5985-00-757-0549
3042B-10	99899	9N5985-00-465-8112	STD	3042B-10	99899	9N5985-00-465-8112
3043B-10	99899	1H6625-01-065-5289	STD	3043B-10	99899	1H6625-01-065-5289
3043B-30	99899	9N5985-00-450-8802	STD	3043B-30	99899	9N5985-00-450-8802
3045B-10	99899	1R5895-00-967-4501	REPL	3045C-10	99899	1R5985-00-604-8604
3045C-10	99899	1R5985-00-604-8604	STD	3045C-10	99899	1R5985-00-604-8604
3060-20	99899	9N5985-00-492-7921	STD	3060-20	99899	9N5985-00-492-7921
310	80138	7Z5985-00-081-0163	REPL	442-D	80138	9N5905-00-313-9064
310-2	21900	1H6625-00-649-2737	1387	N/A		
3103R	88865	NSNL	1387	N/A		
3108	15305	NSNL	REPL	102AC46-1E	01456	1H6625-00-178-0008
3122	99899	1H5895-01-079-0537	STD	3122	99899	1H5895-01-079-0537
314	00443	1H6625-01-039-5259	STD	314	00443	1H6625-01-039-5259
3143575	MIL	1H6625-00-943-2881	GA	N/A		
316C4	95712	1H5985-00-087-6646	REPL	GM-318-C4	60674	9N6625-01-036-2020
318C4	95712	NSNL	REPL	GM-318-C4	60674	9N6625-01-036-2020
319-2-000	00607	1H5990-01-040-0193	GA	N/A		
319-3-000	00607	1H6625-01-040-0194	GA	N/A		
319-5-000	00607	1H5995-01-039-5216	GA	N/A		
32-0	80138	1H6625-00-977-9051	REPL	452-C	80138	9Y5985-00-712-8388
3202	88865	1H4931-00-178-1052	STD	3202	88865	1H4931-00-178-1052
3202B-10	99899	9N5985-00-412-2986	STD	3202B-10	99899	9N5985-00-412-2986
32115258	93346	1H6625-00-930-6836	GA	N/A		

Source: https://assist.dla.mil -- Downloaded: 202640-26T13:40Z
Check the source to verify that this is the currentversion before use.

APPENDIX A

REFERENCE EQUIPMENT TO STANDARD EQUIPMENT

REFERENCE EQUIPMENT					STANDARD EQUIPMENT		
MODEL	FSCM	NSN	STATUS	NOTES	MODEL	FSCM	NSN
3222-16	99899	1H5985-01-081-7855	STD		3222-16	99899	1H5985-01-081-7855
3292-1	99899	1R5985-01-059-3436	1387		N/A		
33B4	06424	NSNL	GA		N/A		
33C2	06424	NSNL	REPL		314	00443	1H6625-01-039-5259
33X4	06424	NSNL	GA		N/A		
330B	88865	NSNL	REPL		3750	88865	1H6625-00-001-2376
33000D-H21	28480	1H6625-01-079-0232	1387		N/A		
335	88865	NSNL	REPL		3750	88865	1H6625-00-001-2376
34B1	06424	1H5840-00-242-2653	REPL		UNDER REVIEW		
34C1	06424	NSNL	REPL	2	314	00443	1H6625-01-039-5259
34X1	99899	NSNL	1387		N/A		
342C554H02	79500	NSNL	REPL		371BNM	99899	1H6625-00-970-3685
342C554H02	97942	NSNL	REPL		371BNM	99899	1H6625-00-970-3685
343A	28480	1H6625-00-793-1344	GA		N/A		
345B	28480	7Z6625-00-793-1345	GA	1	N/A		
346B	28480	1H6625-00-886-1962	GA		N/A		
349A	28480	1H6625-00-886-1962	GA		N/A		
35-3078	72598	1H6625-00-301-4738	GA		N/A		
350B	28480	1H6625-00-838-2826	REPL		850-CI2W	83332	NSNL
350D	28480	1H6625-00-215-4931	1387		850-CI2W	83332	NSNL
354-C	77327	NSNL	REPL		X281A	28480	9N5985-00-892-0732
355A	28480	1H5985-00-285-6455	REPL		355C	28480	1H5985-00-993-1377
355B	28480	NSNL	REPL		355D	28480	9N5985-00-957-1860
355C	28480	1H5985-00-993-1377	STD		355C	28480	1H5985-00-993-1377
355C-C08	28480	NSNL	REPL		355C	28480	1H5985-00-993-1377
355C-001	28480	1H6625-01-003-6092	REPL		355C	28480	1H5985-00-993-1377
355D	28480	9N5985-00-957-1860	STD		355D	28480	9N5985-00-957-1860
355D-C08	28480	NSNL	REPL		355D	28480	9N5985-00-957-1860
355D-001	28480	1H6625-01-008-2051	REPL		355D	28480	9N5985-00-957-1860
356-A	77327	NSNL	REPL		J281A	28480	9N5985-00-605-9161
360A	28480	9N5915-00-503-1787	STD		360A	28480	9N5915-00-503-1787
360B	28480	9N5915-00-686-8922	STD		360B	28480	9N5915-00-686-8922
360C	28480	9N5915-00-503-0533	STD		360C	28480	9N5915-00-503-0533

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX A

REFERENCE EQUIPMENT TO STANDARD EQUIPMENT

REFERENCE EQUIPMENT					STANDARD EQUIPMENT		
MODEL	FSCM	NSN	STATUS	NOTES	MODEL	FSCM	NSN
360D	28480	9N5915-00-804-5302	STD		360D	28480	9N5915-00-804-5302
368NM	99899	1H6625-00-150-7079	1387		N/A		
370-20	00443	1H5985-01-008-2195	1387		N/A		
370BNM	99899	NSNL	REPL		1425-4	93459	1H6930-01-140-4985
371BNM	99899	1H6625-00-970-3685	STD		371BNM	99899	1H6625-00-970-3685
371NM	99899	1H5985-00-784-9045	REPL		371BNM	99899	1H6625-00-970-3685
3744A	28480	7Z6625-01-138-0293	GA		N/A		
375BNM	99899	NSNL	1387		N/A		
375NM	99899	1H6625-00-368-7198	REPL		1425-4	93459	1H6930-01-140-4985
3750	88865	1H6625-00-001-2376	STD		3750	88865	1H6625-00-001-2376
3750A	28480	7Z6625-00-047-9555	REPL		442-D	80138	9N5905-00-[illegible]3-9064
376BNF	99899	9N5985-00-241-3518	STD		376BNF	99899	9N5985-00-241-3518
376NF	99899	NSNL	REPL		376BNF	99899	9N5985-00-241-3518
394A	28480	1H5985-00-919-8548	REPL		0874-9577	82316	&&5840-00-868-1287
4M-10	93459	9N5985-00-258-0123	STD		4M-10	93459	9N5985-00-258-0123
4M-3	93459	1H6625-LL-HHE-1799	STD		4M-3	93459	1H6625-LL-HHE-1799
4M-3-6-10	93459	9N6625-01-026-2335	STD		4M-3-6-10	93459	9N6625-01-026-2335
4M-6	93459	1H6625-01-015-2356	STD		4M-6	93459	1H6625-01-015-2356
4002B-30	99899	1H5985-01-015-7687	1387		N/A		
4016-10	99899	NSNL	REPL		4016D-10	99899	9N5985-01-041-8132
4016B-10	99899	9N5985-01-041-8132	REPL		4016D-10	99899	9N5985-01-041-8132
4016D-10	99899	9N5985-01-041-8132	STD		4016D-10	99899	9N5985-01-041-8132
404-M05	22424	1H6625-00-368-7198	1387		N/A		
4055-10	99899	9N6625-00-261-7749	STD		4055-10	99899	9N6625-00-261-7749
4055-20	99899	1H5985-01-100-1668	STD		4055-20	99899	1H5985-01-100-1668
4055-30	99899	1H5985-01-096-6705	STD		4055-30	99899	1H5985-01-096-6705
407D	89536	NSNL	REPL		BHK-500-0.4M	85604	7Z6625-01-031-8855
407655	80006	1H5915-00-310-1476	STD		407655	80006	1H5915-00-310-1476
41227	65092	1H6625-01-057-9035	GA		N/A		
415B-45AN	28480	NSNL	GA		N/A		
415D-45A	28480	NSNL	GA		N/A		
417A	28480	NSNL	GA	1	N/A		
420A	28480	NSNL	REPL		423A	28480	9N6625-00-880-4978

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX A

REFERENCE EQUIPMENT TO STANDARD EQUIPMENT

REFERENCE EQUIPMENT					STANDARD EQUIPMENT		
MODEL	FSCM	NSN	STATUS	NOTES	MODEL	FSCM	NSN
420B	28480	NSNL	REPL		423A	28480	9N6625-00-880-4978
42213	12110	1H6625-01-065-5308	GA		N/A		
4222-16	99899	7Z5985-01-135-0012	REPL		3222-16	99899	1H5985-01-081-7855
423A	28480	9N6625-00-880-4978	STD		423A	28480	9N6625-00-880-4978
423A001	28480	NSNL	1387		N/A		
432-D	80138	9N5985-00-087-2547	STD		432-D	80138	9N5985-00-087-2547
432-D-J	80138	NSNL	REPL		432-D	80138	9N5985-00-087-2547
4375G	99899	1H6625-LL-HHE-8020	STD		4375G	99899	1H6625-LL-HHE-8020
440A	28480	1H6625-00-970-3695	REPL		UNDER REVIEW		
440B	11332	1H6625-01-018-1206	GA		N/A		
440B1	11332	1H6625-01-018-1208	GA		N/A		
442-C	80138	NSNL	REPL		442-D	80138	9N5905-00-313-9064
442-D	80138	9N5905-00-313-9064	STD		442-D	80138	9N5905-00-313-9064
442-D-J	80138	NSNL	REPL		442-D	80138	9N5905-00-313-9064
4436A	28480	NSNL	1387		N/A		
4437A	28480	1H6625-01-163-6679	1387		850-CI2W	83332	NSNL
444A	28480	NSNL	GA		N/A		
447B	28480	1H6625-00-433-2395	GA		N/A		
45X1-10	99899	1H5985-00-310-1475	REPL		X752C	28480	9N5985-00-646-9472
451-B	80138	NSNL	REPL		452-C	80138	9Y5985-00-712-8388
452-C	80138	9Y5985-00-712-8388	STD		452-C	80138	9Y5985-00-712-8388
452A	28480	7Z6625-00-678-0904	GA	1	N/A		
4520-2	15305	1H6625-LL-HHE-8012	REPL		4375G	99899	1H6625-LL-HHE-8020
453-1	18778	1H6625-00-296-1644	REPL		C-30BP	80009	7G6720-01-095-2205
453A	28480	7Z6625-00-628-6514	1387	2	N/A		
454A	28480	7Z6625-00-799-8655	1387	1	N/A		
455A	28480	NSNL	GA		N/A		
456A	28480	1H6625-00-076-0806	GA		N/A		
459A	28480	1H6625-00-511-5383	GA	1	N/A		
4600-789PC21	43689	NSNL	1387		N/A		
4609	99899	1H5985-01-025-3902	STD		4609	99899	1H5985-01-025-3902
464-A	80138	NSNL	REPL		355D	28480	9N5985-00-957-1860
47C2	31966	NSNL	1387		N/A		

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX A

REFERENCE EQUIPMENT TO STANDARD EQUIPMENT

REFERENCE EQUIPMENT					STANDARD EQUIPMENT		
MODEL	FSCM	NSN	STATUS	NOTES	MODEL	FSCM	NSN
477B	28480	NSNL	GA	1	N/A		
4779-10	99899	1H6625-01-018-0934	REPL		4M-10	93459	9N5985-00-258-0123
4779-3	99899	1H6625-01-015-2357	REPL		4M-3	93459	1H6625-LL-HHE-1799
4779-3-6-10	99899	7Z6625-00-115-9200	REPL		4M-3-6-10	93459	9N6625-01-026-2335
4779-6	99899	1H6625-01-015-2356	REPL		4M-6	93459	1H6625-01-015-2356
478A	28480	7Z6625-01-886-1955	GA		N/A		
478W	02039	1H6625-00-897-3406	GA		N/A		
480	99899	NSNL	GA		N/A		
5-B000-75	94375	1H5985-01-039-5402	1387		N/A		
50-10	93459	9N5985-00-655-7589	REPL		8491A-010	28480	9N5985-00-865-0108
50-20	93459	9N5985-00-626-4370	REPL		8491A-020	28480	1H4935-01-031-2694
50-3	93459	9N5985-00-965-6318	REPL		8491A-003	28480	9N5985-00-167-0544
50-30	93459	9N5985-00-777-1382	REPL		2-30	93459	1H6625-01-014-3463
50-40	93459	7Z4931-00-777-1381	REPL		2-40	93459	1H6625-01-014-3464
50-6	93459	9N5985-00-615-3104	REPL		8491A-006	28480	9N5895-00-230-1827
50B	12996	1H6625-00-562-4506	REPL		850-CT2W	83332	NSNL
500-B	83008	9N5950-00-933-7423	REPL		W10MT3A	13850	9S6120-00-054-7794
5015	98095	1H6130-00-990-8659	REPL		5015V	98095	1H6625-01-224-0215
5015T	98095	9G6130-00-062-9873	REPL		5015V	98095	1H6625-01-224-0215
5015V	98095	1H6625-01-224-0215	STD		5015V	98095	1H6625-01-224-0215
513	99899	1H6625-00-376-5076	REPL	2	314	00443	1H6625-01-039-5259
530-10	93459	NSNL	REPL		8491A-010	28480	9N5985-00-865-0108
530-20	93459	7Z5985-00-777-1379	REPL		8491A-020	28480	1H4935-01-031-2694
530-3	93459	7Z6625-00-713-9252	REPL		8491A-003	28480	9N5985-00-167-0544
530-6	93459	7Z5985-00-816-8717	REPL		8491A-006	28480	9N5895-00-230-1827
530A-10	93459	NSNL	REPL		8491A-010	28480	9N5985-00-865-0108
530A-20	93459	7Z5985-00-839-4405	REPL		8491A-020	28480	1H4935-01-031-2694
530A-3	93459	NSNL	REPL		8491A-003	28480	9N5985-00-167-0544
530A-6	93459	7Z5985-00-840-3418	REPL		8491A-006	28480	9N5895-00-230-1827
534114-2	96214	1H6625-00-498-2232	GA		N/A		
535MN	93459	NSNL	REPL		1425-4	93459	1H6930-01-140-4985
54-C1	06424	NSNL	REPL		G281A	28480	9N5985-00-772-6676
540	99899	7Z5985-00-777-6750	GA	1	N/A		

Source: https://assist.dla.mil -- Downloaded: 202640-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX A

REFERENCE EQUIPMENT TO STANDARD EQUIPMENT

REFERENCE EQUIPMENT					STANDARD EQUIPMENT		
MODEL	FSCM	NSN	STATUS	NOTES	MODEL	FSCM	NSN
541	99899	7Z6625-00-781-8043	GA	1	N/A		
546A	28480	NSNL	GA		N/A		
548A	28480	NSNL	GA		N/A		
553-10	93459	1H5985-01-065-8185	REPL		8491A-010	28480	9N5985-00-865-0108
553-20	93459	1H6625-01-067-0480	REPL		8491A-020	28480	1H4935-01-031-2694
560-B	99899	7Z6625-00-710-7270	GA	1	N/A		
562807-000	56232	1H6625-00-943-2881	GA		N/A		
574-10	00443	1H6625-LL-HHE-8018	STD		574-10	00443	1H6625-LL-HHE-8018
574-20	00443	1H6625-LL-HHE-8019	STD		574-20	00443	1H6625-LL-HHE-8019
576R747H03	97942	1H6625-00-813-6847	1387		N/A		
5779-10	99899	NSNL	REPL		2-10	93459	1H6625-01-017-1278
5779-20	99899	NSNL	REPL		2-20	93459	1H6625-01-017-1276
5779-3	99899	NSNL	REPL		2-3	93459	1H6625-01-020-6032
5779-6	99899	NSNL	REPL		2-6	93459	1H6625-01-017-1277
578-BS5	24655	9N5850-00-201-4268	REPL		ST-100	88869	9N5950-00-679-6862
597C24	94033	1H6625-00-643-2682	GA		N/A		
6015	80009	1H6625-00-922-9296	GA		N/A		
602540	07239	7Z6625-00-818-7643	1387		N/A		
606A34	28480	1H6625-00-976-3868	1387		N/A		
606A34C	28480	NSNL	1387		N/A		
6112A	28480	1H6625-01-040-2581	REPL		5015V	98095	1H6625-01-224-0215
613-M	77327	1H6625-00-973-1151	STD		613-M	77327	1H6625-00-973-1151
613A	99899	7Z5985-00-906-3287	REPL		G281A	28480	9N5985-00-772-6676
614A	99899	1H5985-00-330-9882	REPL		S281A	28480	1R4920-01-029-4624
616	99899	9N6625-00-424-5066	STD		616	99899	9N6625-00-424-5066
617912	06424	NSNL	GA		N/A		
617912	99899	NSNL	GA		N/A		
6205B	28480	1H6625-00-437-4861	REPL		5015V	98095	1H6625-01-224-0215
6206B	28480	1H6625-00-823-5359	REPL		5015V	98095	1H6625-01-224-0215
6207B	28480	1H6130-00-496-8652	REPL		UNDER REVIEW		
6209B	28480	6A6625-00-886-1955	REPL		BHK-500-0.4M	85604	7Z6625-01-031-8855
6216A	28480	1H6130-00-489-9167	REPL		JQE-36-3M	85604	1H6130-00-471-1735
6255A	28480	NSNL	REPL		5015V	98095	1H6625-01-224-0215

Source: https://assist.dla.mil -- Downloaded: 202610-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX A

REFERENCE EQUIPMENT TO STANDARD EQUIPMENT

REFERENCE EQUIPMENT					STANDARD EQUIPMENT		
MODEL	FSCM	NSN	STATUS	NOTES	MODEL	FSCM	NSN
6259B-026	28480	1H6130-01-040-9811	1387		N/A		
6265A	28480	1H6130-00-766-8543	REPL		6266B	28480	9G6130-00-137-0167
6266B	28480	9G6130-00-137-0167	STD		6266B	28480	9G6130-00-137-0167
627	93459	1H6625-01-065-8270	GA		N/A		
6274B	28480	7Z6130-00-160-0827	STD		6274B	28480	7Z6130-00-160-0827
6294A	28480	&&6130-01-062-6739	STD		6294A	28480	&&6130-01-062-6739
6296A	28480	1H6130-01-067-3777	STD		6296A	28480	1H6130-01-067-3777
6299A	28480	4G6130-00-406-5695	STD		6299A	28480	4G6130-00-406-5695
6302-HC	77327	NSNL	GA		N/A		
638	99899	9N6625-01-031-1980	STD		638	99899	9N6625-01-031-1980
640	99899	1R5985-00-729-1297	STD		640	99899	1R5985-00-729-1297
642	99899	NSNL	1387		N/A		
643	50423	NSNL	GA	1	N/A		
643	99899	7Z5985-00-448-0580	REPL		BA-C-110C	00341	1H6625-01-030-5505
6439B	28480	7Z6130-00-814-2106	REPL		6274B	28480	7Z6130-00-160-0827
6443B	28480	1H6130-00-163-6201	STD		6443B	28480	1H6130-00-163-6201
6522A	28480	1H6130-00-915-1930	REPL		UNDER REVIEW		
6525A	28480	&&6625-00-165-3837	1387		N/A		
6602	03782	NSNL	GA		N/A		
6602A	03782	NSNL	GA		N/A		
665	80138	NSNL	1387		850-CT2W	83332	NSNL
67	70998	&&6625-00-708-8582	REPL		8404	70998	1H6625-01-150-1897
6835	70998	7Z6625-00-973-2189	REPL		8404	70998	1H6625-01-150-1897
6855	83008	NSNL	REPL		W5RT3A	13850	9N5950-00-987-5601
7008	00752	1H6625-00-916-3209	GA		N/A		
704-50	01365	1H6625-00-907-8347	REPL		8404	70998	1H6625-01-150-1897
704-69	99899	7Z5985-00-172-6258	REPL		AF-117A-69-34	93459	9N6625-01-063-9297
70412	06049	9N5950-00-138-5219	REPL		P6161	80089	9N5950-00-645-1807
705-99	99899	9V6625-00-530-2601	REPL		AF-117A-69-34	93459	9N6625-01-063-9297
7091	12678	1H6625-00-925-0180	GA		N/A		
710	16055	7Z6625-00-072-5406	REPL		850-CT2W	83332	NSNL
712	99899	1H6625-00-288-0183	REPL		AF-117A-69-34	93459	9N6625-01-063-9297
712B	28480	1H6130-00-635-7991	REPL		BHK-500-0.4M	85604	7Z6625-01-031-8855

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX A

REFERENCE EQUIPMENT TO STANDARD EQUIPMENT

REFERENCE EQUIPMENT					STANDARD EQUIPMENT		
MODEL	FSCM	NSN	STATUS	NOTES	MODEL	FSCM	NSN
712C	28480	6G6130-00-116-7423	REPL		BHK-500-0.4M	85604	7Z6625-01-031-8855
716A	28480	1H6130-00-065-3211	1387	1	N/A		
72050-502	20193	NSNL	GA		N/A		
721A	28480	1H6130-00-445-6933	REPL		5015V	98095	1H6625-01-224-0215
722 MDQ	24655	1H6625-00-411-9628	1387		N/A		
724AR	28480	1H6625-00-713-3734	1387		N/A		
724BR	28480	1H6625-00-844-9134	1387		N/A		
757C-10	99899	7Z5985-00-483-4400	REPL		8491A-010	28480	9N5985-00-865-0108
757C-3	99899	7Z5985-00-222-0465	REPL		8491A-003	28480	9N5985-00-167-0544
757C-40	99899	1H6625-01-017-1279	1387		N/A		
757C-6	99899	7Z5985-00-118-7985	REPL		8491A-006	28480	9N5895-00-230-1827
765-6	99899	1H6625-01-039-5260	1387		24-6-34	93459	1H6625-LL-HHE-8021
772011-2	96214	1H6625-00-943-2881	GA		N/A		
776D	28480	NSNL	REPL		778D	28480	9N5985-00-239-3215
778D	28480	9N5985-00-239-3215	STD		778D	28480	9N5985-00-239-3215
779D	28480	7Z5985-00-490-2834	REPL		11692D	28480	9N5985-01-024-3832
7904453	77327	1H6625-00-215-4931	1387		UNDER REVIEW		
7907234	18876	1H6625-00-585-4915	REPL		240C	12697	1H6625-00-585-4915
7907319	00000	1H6625-00-251-1158	REPL		1491-9704	24655	1H6625-00-251-1158
7907413	18876	1H6625-00-602-2089	REPL		X382A	28480	1H6625-00-602-2089
7907413	19200	1H6625-00-602-2089	REPL		X382A	28480	1H6625-00-602-2089
7909033	18876	1H6625-00-602-2089	REPL		X382A	28480	1H6625-00-602-2089
7911092	18876	1H6625-00-071-6219	1387		N/A		
7911468	19200	1H4931-00-921-7357	REPL		C20PS	14135	1H4931-00-921-7357
796FM	99899	1H6625-00-287-5067	1387		N/A		
80F15	89536	1H6625-00-482-4123	GA		N/A		
80HRF	89536	1H6625-01-015-7423	GA		N/A		
80K-40	89536	NSNL	GA		N/A		
80M	70998	9Y5840-00-669-8675	STD		80M	70998	9Y5840-00-669-8675
80N-5	89536	NSNL	GA	1	N/A		
80RF-1	89536	7Z6625-00-373-7613	GA		N/A		
801197	00929	1H6625-00-777-6748	GA		N/A		
8037	04423	1H5895-01-039-5460	GA		N/A		

Source: https://assist.dla.mil -- Downloaded: 202610-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX A

REFERENCE EQUIPMENT TO STANDARD EQUIPMENT

REFERENCE EQUIPMENT					STANDARD EQUIPMENT		
MODEL	FSCM	NSN	STATUS	NOTES	MODEL	FSCM	NSN
806B	28480	7Z6625-00-284-7494	GA		N/A		
8085	70998	9N5985-00-477-8165	STD		8085	70998	9N5985-00-477-8165
809B	28480	1H6625-00-304-7213	GA		N/A		
809BL	28480	NSNL	GA		N/A		
809BPL	28480	NSNL	GA		N/A		
809C	28480	1H6625-00-097-6666	GA		N/A		
81	11332	1H6625-00-815-8333	GA		N/A		
8100-25	25284	7G6625-01-154-3807	1387		N/A		
811152	70998	1H6625-00-930-1810	1387		N/A		
8135	70998	9N6625-00-773-7311	STD		8135	70998	9N6625-00-773-7311
816A	28480	7Z6625-00-495-9930	GA		N/A		
8160	70998	1H5821-00-433-5584	REPL		8164	70998	1H5985-01-024-8193
8164	70998	1H5985-01-024-8193	STD		8164	70998	1H5985-01-024-8193
817-B	54294	&&6625-01-042-3326	REPL		1433-9729	24655	1H6625-01-205-0820
82A	70998	9Y6625-00-177-1639	REPL		8404	70998	1H6625-01-150-1897
82C	70998	9N5985-00-071-1401	REPL		8404	70998	1H6625-01-150-1897
82RF	89536	1H6625-01-040-9511	GA		N/A		
8201	70998	1H6625-00-994-6797	STD		8201	70998	1H6625-00-994-6797
8230	70998	1H6625-00-905-0051	REPL		8404	70998	1H6625-01-150-1897
8401	70998	1H6625-01-032-4371	REPL		8404	70998	1H6625-01-150-1897
8401SPECIAL	70998	1H6625-00-930-1810	REPL		8404	70998	1H6625-01-150-1897
8404	70998	1H6625-01-150-1897	STD		8404	70998	1H6625-01-150-1897
8470A	28480	1H6625-00-424-4334	STD		8470A	28480	1H6625-00-424-4334
8470A-012	28480	9N6625-00-222-9771	REPL		423A	28480	9N6625-00-880-4978
8470B	28480	9N6625-01-048-7045	REPL	1	8470A	28480	1H6625-00-424-4334
8470B-012	28480	NSNL	REPL	1	423A	28480	9N6625-00-880-4978
8472A-001	28480	1H6625-00-291-1039	STD		8472A-001	28480	1H6625-00-291-1039
8478B	28480	1H6625-00-811-2435	GA		N/A		
8478B-H27	28480	1H6625-01-067-0413	GA		N/A		
8478B-011-H27	28480	1H6625-01-067-0413	GA		N/A		
8481A	28480	NSNL	GA		N/A		
8482A	28480	NSNL	GA		N/A		
8482B	28480	NSNL	GA		N/A		

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX A

REFERENCE EQUIPMENT TO STANDARD EQUIPMENT

REFERENCE EQUIPMENT					STANDARD EQUIPMENT		
MODEL	FSCM	NSN	STATUS	NOTES	MODEL	FSCM	NSN
8484A	28480	1H6625-01-028-2882	GA		N/A		
8485A	28480	NSNL	GA		N/A		
8491A-003	28480	9N5985-00-167-0544	STD		8491A-003	28480	9N5985-00-167-0544
8491A-006	28480	9N5895-00-230-1827	STD		8491A-006	28480	9N5895-00-230-1827
8491A-010	28480	9N5985-00-865-0108	STD		8491A-010	28480	9N5985-00-865-0108
8491A-020	28480	1H4935-01-031-2694	STD		8491A-020	28480	1H4935-01-031-2694
8491A-030	28480	1H5985-00-230-1828	REPL		2-30	93459	1H6625-01-014-3463
8491A-040	28480	1H5985-01-039-5258	REPL		2-40	93459	1H6625-01-014-3464
850-CT2W	83332	NSNL	STD	1	850-CT2W	83332	NSNL
8616453	18876	1H6625-00-585-3152	REPL		1433-9726	24655	1H6625-00-140-8183
8721A	28480	NSNL	GA		N/A		
8731	70998	1H6625-01-037-9747	1387		N/A		
8732	70998	1H6625-01-037-9747	1387		N/A		
8736	70998	1H5985-01-039-5401	1387		N/A		
874-GA	24655	NSNL	REPL		0874-9577	82316	&A5840-00-868-1287
874-GAL	24655	7Z5985-00-623-0255	REPL		0874-9577	82316	&A5840-00-868-1287
880	28480	1H6130-00-065-3212	1387		N/A		
8890	70998	1H6625-00-772-2592	REPL		B-1576	91161	1H5985-00-792-9928
8890-300	70998	1H6625-01-145-2810	REPL		B-1576	91161	1H5985-00-792-9928
8894	70998	7Z5985-01-166-3721	REPL		B-1576	91161	1H5985-00-792-9928
8894-010	70998	NSNL	REPL		B-1576	91161	1H5985-00-792-9928
8894-300	70998	7Z5985-01-196-7882	REPL		B-1576	91161	1H5985-00-792-9928
900-9703	82316	1H5935-01-039-5228	1387		N/A		
900-9801	82316	1H5935-01-039-5257	1387		N/A		
900-9803	82316	1H5935-01-039-5227	1387		N/A		
90513-10	12678	NSNL	REPL		8491A-010	28480	9N5985-00-865-0108
90513-3	12678	NSNL	REPL		8491A-003	28480	9N5985-00-167-0544
90513-6	12678	NSNL	REPL		8491A-006	28480	9N5895-00-230-1827
9063646	18876	1H6625-00-777-6748	GA		N/A		
91-24A	04901	1H6625-01-037-9437	GA		N/A		
91092-22	06049	NSNL	REPL		P6161	80089	9N5950-00-645-1807
9113325	18876	1H6625-00-511-5383	GA		N/A		
9157430	18876	NSNL	GA		N/A		

Source: https://assist.dla.mil -- Downloaded: 202640-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX A

REFERENCE EQUIPMENT TO STANDARD EQUIPMENT

REFERENCE EQUIPMENT				STANDARD EQUIPMENT		
MODEL	FSCM	NSN	STATUS NOTES	MODEL	FSCM	NSN
9157607	18876	1H5985-00-919-8548	REPL	0874-9577	82316	&&5840-00-868-1287
920NA	98521	7Z6625-00-970-3682	REPL	UNDER REVIEW		
9211-1303	28480	1H6625-01-136-3174	GA	N/A		
922582-1	06481	7Z6130-00-814-2106	REPL	6266B	28480	9G6130-00-137-0167
926	93459	1H6625-00-488-9403	GA	N/A		
9700-0025	30669	NSNL	GA	N/A		
973-20	93459	1H6625-00-118-6729	STD	973-20	93459	1H6625-00-118-6729
973P-20	93459	1H6625-00-294-4871	REPL	973-20	93459	1H6625-00-118-6729
98-00224	14031	1H6625-01-039-1277	GA	N/A		
9975610	18876	1H5985-00-712-8388	REPL	452-C	80138	9Y5985-00-712-8388

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX B

REFERENCE NIIN TO STANDARD EQUIPMENT

REFERENCE EQUIPMENT NSN	MODEL	FSCM	STATUS	NOTES	STANDARD EQUIPMENT MODEL	FSCM	NSN
NSNL	AAT-1	11242	GA		N/A		
NSNL	AC-16K	28480	GA		N/A		
NSNL	AC-16Q	28480	GA		N/A		
NSNL	ACD-1	11242	GA		N/A		
NSNL	AD-06N	00929	REPL		8491A-006	28480	9N5895-00-230-1827
NSNL	AD-40N	00929	REPL		2-40	93459	1H6625-01-014-3464
NSNL	AF-117-69-34	93459	REPL		AF-117A-69-34	93459	9N6625-01-063-9297
NSNL	AMN-1	11242	GA		N/A		
NSNL	AN/UPA-1	MIL	GA	1	N/A		
NSNL	AN/UPA-1A	MIL	GA	1	N/A		
NSNL	AN/UPA-1B	MIL	GA	1	N/A		
NSNL	AN/URM-111A	MIL	GA	1	N/A		
NSNL	AN/USM-119	MIL	GA		N/A		
NSNL	AT-201-SR	12598	REPL		355D	28480	9N5985-00-957-1860
NSNL	ATA-1	11242	GA		N/A		
NSNL	ATN-1	11242	GA		N/A		
NSNL	ATP-1	11242	GA		N/A		
NSNL	A6302	80009	GA		N/A		
NSNL	A80	89536	GA		N/A		
NSNL	BP-60F	23934	REPL		5015V	98095	1H6625-01-224-0215
NSNL	BPA-60E	23934	REPL		5015V	98095	1H6625-01-224-0215
NSNL	B4063	00929	REPL		WF-0050	00929	9N5985-00-572-6267
NSNL	C-12	80009	REPL		C-30BP	80009	7G6720-01-095-2205
NSNL	C-30A	80009	REPL		C-30BP	80009	7G6720-01-095-2205
NSNL	CDA-5	14655	REPL		UNDER REVIEW		
NSNL	CDB	14655	REPL		UNDER REVIEW		
NSNL	CN-16/U	MIL	REPL		W5MT3A	13850	9N5950-00-987-5601
NSNL	CN-16A/U	MIL	REPL		W5MT3A	13850	9N5950-00-987-5601
NSNL	CN-16B/U	MIL	REPL		W5MT3A	13850	9N5950-00-987-5601
NSNL	CN-30/U	MIL	REPL		8491A-010	28480	9N5985-00-865-0108
NSNL	CN-30B/U	MIL	REPL		8491A-010	28480	9N5985-00-865-0108
NSNL	CN-39A/U	MIL	REPL		8491A-020	28480	1H4935-01-031-2694
NSNL	CN-39B/U	MIL	REPL		8491A-020	28480	1H4935-01-031-2694

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX B

REFERENCE NIIN TO STANDARD EQUIPMENT

REFERENCE EQUIPMENT NSN	MODEL	FSCM	STATUS	NOTES	STANDARD EQUIPMENT MODEL	FSCM	NSN
NSNL	CN-476/U	MIL	REPL		M602	57646	NSNL
NSNL	CN-608A/U	MIL	REPL		0874-9577	82316	5840-00-868-1287
NSNL	CR-133-N	12598	REPL		423A	28480	9N6625-00-880-497
NSNL	CRT-3	12678	REPL		RT-20A	88869	1H5950-01-067-3203
NSNL	CV-2343/U	MIL	REPL		10514A	28480	9N5985-00-087-4714
NSNL	CW-541B/USM-117	MIL	GA		N/A		
NSNL	CX90S	31791	REPL		CX20PS	14135	9N5985-00-145-3514
NSNL	C60-S	31791	REPL		C20PS	14135	1H4931-00-921-7357
NSNL	DA-140/AP	MIL	REPL		8201	70998	1H6625-00-994-6797
NSNL	DA-274/U	MIL	REPL		8404	70998	1H6625-01-150-1897
NSNL	DA-371/U	MIL	REPL		8135	70998	9N6625-00-773-7311
NSNL	DA-484/URT	MIL	REPL		DPTC-25KFM	91161	1H5985-01-152-4077
NSNL	DA-507/UBT	MIL	REPL		DPTC-50KFM	91161	1H5985-01-152-4078
NSNL	DA-88A/U	MIL	REPL		8404	70998	1H6625-01-150-1897
NSNL	DA52-3	05591	GA		N/A		
NSNL	DC-122	12598	REPL		3040B-20	99899	1H5985-00-067-6750
NSNL	D44X15	06424	REPL		CX20PS	14135	9N5985-00-145-3514
NSNL	EJ-201V	83008	REPL		P6161	80089	9N5950-00-645-1807
NSNL	EJ-401V	83008	REPL		P6161	80089	9N5950-00-645-1807
NSNL	EN/DEBB-1	F6130	GA		N/A		
NSNL	E1010VA	83008	REPL		W10MT3A	13850	9S6120-00-054-7794
NSNL	FCR100	49956	REPL		153B/403SD-001	25965	7G6625-01-197-9866
NSNL	FP-5	08098	GA		N/A		
NSNL	FR30-150-LM	11920	REPL		5015V	98095	1H6625-01-224-0215
NSNL	F5150N1	80009	GA		N/A		
NSNL	GA810K	26512	REPL		432-D	80138	9N5985-00-087-2547
NSNL	GIL-360-1	00341	GA		N/A		
NSNL	G485B	28480	REPL		314	00443	1H6625-01-039-5259
NSNL	H-2190	49673	GA	1	N/A		
NSNL	HV300-1	89022	REPL		TCR-300S-3-1	89022	1H6625-LL-HHE-4110
NSNL	HV300-1.5M	89022	REPL		TCR-300S-3-1	89022	1H6625-LL-HHE-4110
NSNL	HX292B	28480	GA		N/A		
NSNL	H638A	00929	REPL		BA-C-110C	00341	1H6625-01-030-5505

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX B

REFERENCE NIIN TO STANDARD EQUIPMENT

REFERENCE EQUIPMENT NSN	MODEL	FSCM	STATUS	NOTES	STANDARD EQUIPMENT MODEL	FSCM	NSN
NSNL	H810B	28480	GA		N/A		
NSNL	JQE-150-1	85604	REPL		DCR150-12B	49956	7Z6625-01-136-3178
NSNL	JQE-150-3.5M	85604	REPL		DCR150-12B	49956	7Z6625-01-136-3178
NSNL	KS60-10M	85604	REPL		6266B	28480	9G6130-00-137-0167
NSNL	LL141B	12110	1387		N/A		
NSNL	LP-415A-FM	80103	REPL		LQ-415	80103	1H6625-01-178-9497
NSNL	LT-6000	01341	REPL		LA-60N	00929	9N5915-00-725-6051
NSNL	L15S	31791	REPL		L20PS	14135	9Q6625-00-738-2716
NSNL	M-255	14140	GA		N/A		
NSNL	M-50	98202	GA	1	N/A		
NSNL	MK-704/USM-118	MIL	GA		N/A		
NSNL	MK-704/USM-118A	MIL	GA		N/A		
NSNL	MK-827/USM-118	MIL	GA		N/A		
NSNL	MK-827/USM-118A	MIL	GA		N/A		
NSNL	MK-828/USM-118A	MIL	GA		N/A		
NSNL	MV-828A/G	85711	GA		N/A		
NSNL	MX-1545/USM-37	MIL	GA		N/A		
NSNL	MX-2144/U	MIL	GA	1	N/A		
NSNL	MX-2144A/U	MIL	GA	1	N/A		
NSNL	MX-2144B/U	MIL	GA	1	N/A		
NSNL	M546	57646	REPL		M602	57646	NSNL
NSNL	M602	57646	STD		M602	57646	NSNL
NSNL	N-6284-A	77327	GA		N/A		
NSNL	N301-0-2	95924	GA	1	N/A		
NSNL	N423	11332	GA		N/A		
NSNL	OD8F248	96341	1387		N/A		
NSNL	P6008	80009	GA		N/A		
NSNL	P6009	80009	GA		N/A		
NSNL	P6028	80009	GA		N/A		
NSNL	P6053B	80009	GA		N/A		
NSNL	P6062A	80009	GA		N/A		
NSNL	P6075A	80009	GA		N/A		
NSNL	P6411A	80089	REPL		P6161	80089	9N5950-00-645-1807

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX B

REFERENCE NIIN TO STANDARD EQUIPMENT

REFERENCE EQUIPMENT NSN	MODEL	FSCM	STATUS	NOTES	STANDARD EQUIPMENT MODEL	FSCM	NSN
NSNL	QH-2-30	12457	REPL		QHB-2-30	12457	1R5985-00-991-1013
NSNL	RT-6M	88869	1387		N/A		
NSNL	S-175	11787	REPL		S281A	28480	1R4920-01-029-4624
NSNL	SA-78	23042	REPL		442-D	80138	9N5905-00-313-9064
NSNL	SCR-300-2	89022	REPL		TCR-300S-3-1	89022	1H6625-LL-HHE-4110
NSNL	SM-160-2AM	85604	REPL		DCR150-12B	49956	7Z6625-01-136-3178
NSNL	SM-160-2M	85604	REPL		DCR150-12B	49956	7Z6625-01-136-3178
NSNL	ST-200A	12678	REPL		SPX-3031	88869	1H5950-01-040-0282
NSNL	ST-248A	12678	REPL		SPX-3031	88869	1H5950-01-040-0282
NSNL	S10P	14135	REPL		S11PS	14135	9N5985-00-439-3536
NSNL	S102LCI	14135	REPL		S11PS	14135	9N5985-00-439-3536
NSNL	S1303-A1	94990	REPL		R-1011B	94990	1H6625-01-205-1224
NSNL	S4420-30	77327	REPL		3043B-30	99899	9N5985-00-450-8802
NSNL	TD-1159/U	80009	1387				NSNL
NSNL	TDR-29061-1	87864	REPL		TDR-29011	87864	9N5985-00-062-6919
NSNL	TS-234/UP	64959	1387				NSNL
NSNL	TS-235/UP	64959	1387				NSNL
NSNL	TV795G	17870	REPL		850-CT2W	83332	NSNL
NSNL	UC1M	58474	REPL		W5MT3A	13850	9N5950-00-987-5601
NSNL	UC1MB	58474	REPL		W5MT3A	13850	9N5950-00-987-5601
NSNL	U6608	77327	GA		N/A		
NSNL	VT8GC	44655	REPL		W5MT3A	13850	9N5950-00-987-5601
NSNL	V420D	11332	GA		N/A		
NSNL	V4420-20	77327	REPL		3040B-20	99899	1H5985-00-067-6750
NSNL	W10MT	13850	REPL		W10MT3A	13850	9S6120-00-054-7794
NSNL	W2MT	13850	REPL		W5MT3A	13850	9N5950-00-987-5601
NSNL	W2MT3	13850	REPL		W5MT3A	13850	9N5950-00-987-5601
NSNL	W40-NCM	06351	REPL		102AC46-1E	01456	1H6625-00-178-0008
NSNL	W8MT3VM	13850	REPL		W10MT3A	13850	9S6120-00-054-7794
NSNL	X420C	11332	GA		N/A		
NSNL	X420D	11332	GA		N/A		
NSNL	X501B	00929	REPL		X301A	13047	1H5985-01-069-2318
NSNL	X910B	28480	REPL		X301A	13047	1H5985-01-069-2318

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX B

REFERENCE NIIN TO STANDARD EQUIPMENT

REFERENCE EQUIPMENT NSN	MODEL	FSCM	STATUS	NOTES	STANDARD EQUIPMENT MODEL	FSCM	NSN
NSNL	010-6053-13	80009	GA		N/A		
NSNL	010-6056-03	80009	GA		N/A		
NSNL	010-6106-03	80009	GA		N/A		
NSNL	011-0074-00	03950	GA		N/A		
NSNL	013-0180-00	80009	GA		N/A		
NSNL	015-0140-13	80009	GA		N/A		
NSNL	015-05140-03	80009	GA		N/A		
NSNL	07048	12678	GA	1	N/A		
NSNL	07048T	00752	GA		N/A		
NSNL	07048T	12678	GA		N/A		
NSNL	0874-957	82316	REPL		0874-9577	82316	&&5840-00-868-1287
NSNL	100-564	28569	GA		N/A		
NSNL	100Q	24655	REPL	1	1571-9831	13850	9G6110-00-087-4771
NSNL	10004A	28480	GA		N/A		
NSNL	1001	82199	GA		N/A		
NSNL	1006A	28480	GA		N/A		
NSNL	10125	19136	1387		N/A		
NSNL	10382656	00000	REPL		BHK-500-0.4M	85604	7Z6625-01-031-8855
NSNL	10503A	28480	GA		N/A		
NSNL	10519400	MIL	GA		N/A		
NSNL	10590A	28480	GA		N/A		
NSNL	11-6403-00	96795	GA		N/A		
NSNL	1100-A	77327	REPL		8491A-003	28480	9N5985-00-167-0544
NSNL	11010	18778	GA		N/A		
NSNL	11036A	28480	GA		N/A		
NSNL	11042A	28480	GA		N/A		
NSNL	1123A	28480	GA		N/A		
NSNL	1124147	MIL	REPL		10514A	28480	9N5985-00-087-4714
NSNL	11290180	17773	REPL		1425-4	93459	1H6930-01-140-4985
NSNL	11473A	28480	GA		N/A		
NSNL	116	14856	GA		N/A		
NSNL	116B	58474	REPL		W10MT3A	13850	9S6120-00-054-7794
NSNL	11664A	28480	GA		N/A		

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX B

REFERENCE NIIN TO STANDARD EQUIPMENT

REFERENCE EQUIPMENT NSN	MODEL	FSCM	STATUS	NOTES	STANDARD EQUIPMENT MODEL	FSCM	NSN
NSNL	11665B	28480	GA		N/A		
NSNL	11679B	28480	GA		N/A		
NSNL	1224-4	93459	REPL		1425-4	93459	1H6930-01-140-4985
NSNL	1241	24655	GA		N/A		
NSNL	1290015P4	94117	REPL		N9412-20	09992	1H5985-01-203-5192
NSNL	1290019A1	31637	GA		N/A		
NSNL	1293021P2	94117	GA		N/A		
NSNL	1419-B	24655	REPL		1412-9410	24655	1H6625-00-465-6861
NSNL	1432-J	24655	REPL		1433-9704	24655	9N6625-00-173-5441
NSNL	1432-N	24655	REPL		1433-9722	24655	1H6625-00-947-7534
NSNL	1432-9716	24655	REPL		1433-9726	24655	1H6625-00-140-8183
NSNL	1432-9720	24655	REPL		1433-9729	24655	1H6625-01-205-0820
NSNL	1432-9724	24655	REPL		1433-9722	24655	1H6625-00-947-7534
NSNL	1433-G	24655	REPL		1433-9731	24655	1H6625-00-480-0950
NSNL	1433-L	24655	REPL		1433-9706	24655	&&6625-00-235-6308
NSNL	1433-U	24655	REPL		1433-9729	24655	1H6625-01-205-0820
NSNL	1433-9700	24655	REPL		1433-9729	24655	1H6625-01-205-0820
NSNL	1433-9716	24655	REPL		1433-9726	24655	1H6625-00-140-8183
NSNL	1433-9718	24655	1387		N/A		
NSNL	1450-TBR	24655	REPL		850-CT2W	83332	NSNL
NSNL	1454-9701	24655	REPL		UNDER REVIEW		
NSNL	1455-B	24655	REPL		UNDER REVIEW		
NSNL	1480	99899	GA		N/A		
NSNL	1490-D	24655	1387		N/A		
NSNL	150S	49956	REPL		1571-9831	13850	9G6110-00-087-4771
NSNL	1571-AL	24655	REPL		1571-9831	13850	9G6110-00-087-4771
NSNL	1581-AL	24655	REPL		1571-9831	13850	9G6110-00-087-4771
NSNL	1591-9700	13850	GA		N/A		
NSNL	16-25	88113	REPL		6296A	28480	1H6130-01-067-3777
NSNL	160-100D	54778	REPL		8135	70998	9N6625-00-773-7311
NSNL	160B-600FN	54778	REPL		8404	70998	1H6625-01-150-1897
NSNL	175-0113-00	80009	GA		N/A		
NSNL	180A-470	54778	GA		N/A		

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX B

REFERENCE NIIN TO STANDARD EQUIPMENT

NSN	REFERENCE EQUIPMENT MODEL	FSCM	STATUS	NOTES	STANDARD EQUIPMENT MODEL	FSCM	NSN
NSNL	20020J	16179	REPL		2002-6113-00	16179	9N5985-00-192-0138
NSNL	20020P	16179	REPL		2001-6113-00	16179	9N5985-01-064-2513
NSNL	205A1-2	90101	1387	1	N/A		
NSNL	217B-T3	58474	REPL		W10HG3M	13850	1H6120-00-032-1173
NSNL	22523ET	00213	GA		N/A		
NSNL	22749	99899	REPL		613-M	77327	1H6625-00-973-1151
NSNL	248	06424	REPL		G281A	28480	9N5985-00-772-6676
NSNL	2613-1104	12855	1387		N/A		
NSNL	270A-30	54778	GA		N/A		
NSNL	2901	27834	REPL		371BNM	99899	1H6625-00-970-3685
NSNL	292-6	34078	REPL		4M-6	93459	1H6625-01-015-2356
NSNL	3PNT51B	83008	REPL		W5MT3A	13850	9N5950-00-987-5601
NSNL	3PN1010	83008	REPL		W10MT3A	13850	9S6120-00-054-7794
NSNL	3PN501B	83008	REPL		W5MT3A	13850	9N5950-00-987-5601
NSNL	30-N	00929	REPL		2-30	93459	1H6625-01-014-3463
NSNL	300	80138	REPL		432-D	80138	9N5985-00-087-2547
NSNL	3000-20	99899	REPL		3040B-20	99899	1H5985-00-067-6750
NSNL	3001-10	99899	REPL		3041-10	99899	1H5985-01-039-5404
NSNL	3002-10	99899	REPL		3042B-10	99899	9N5985-00-465-8112
NSNL	3103R	88865	1387		N/A		
NSNL	3108	15305	REPL		102AC46-1E	01456	1H6625-00-178-0008
NSNL	318C4	95712	REPL		GM-318-C4	60674	9N6625-01-036-2020
NSNL	33B4	06424	GA		N/A		
NSNL	33C2	06424	REPL		314	00443	1H6625-01-039-5259
NSNL	33X4	06424	GA		N/A		
NSNL	330B	88865	REPL		3750	88865	1H6625-00-001-2376
NSNL	335	88865	REPL		3750	88865	1H6625-00-001-2376
NSNL	34C1	06424	REPL	2	314	00443	1H6625-01-039-5259
NSNL	34X1	99899	1387		N/A		
NSNL	342C554H02	79500	REPL		371BNM	99899	1H6625-00-970-3685
NSNL	342C554H02	97942	REPL		371BNM	99899	1H6625-00-970-3685
NSNL	354-C	77327	REPL		X281A	28480	9N5985-00-892-0732
NSNL	355B	28480	REPL		355D	28480	9N5985-00-957-1860

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX B

REFERENCE NIIN TO STANDARD EQUIPMENT

NSN	REFERENCE EQUIPMENT MODEL	FSCM	STATUS	NOTES	STANDARD EQUIPMENT MODEL	FSCM	NSN
NSNL	355C-C08	28480	REPL		355C	28480	1H5985-00-993-1377
NSNL	355D-C08	28480	REPL		355D	28480	9N5985-00-957-1860
NSNL	356-A	77327	REPL		J281A	28480	9N5985-00-606-9161
NSNL	370BNM	99899	REPL		1425-4	93459	1H6930-01-140-4985
NSNL	375BNM	99899	1387		N/A		
NSNL	376NF	99899	REPL		376BNF	99899	9N5985-00-241-3518
NSNL	4016-10	99899	REPL		4016D-10	99899	9N5985-01-041-8132
NSNL	407D	89536	REPL		BHK-500-0.4M	85604	7Z6625-01-031-8855
NSNL	415B-45AN	28480	GA		N/A		
NSNL	415D-45A	28480	GA		N/A		
NSNL	417A	28480	GA	1	N/A		
NSNL	420A	28480	REPL		423A	28480	9N6625-00-880-4978
NSNL	420B	28480	REPL		423A	28480	9N6625-00-880-4978
NSNL	423A001	28480	1387		N/A		
NSNL	432-D-J	80138	REPL		432-D	80138	9N5985-00-087-2547
NSNL	442-C	80138	REPL		442-D	80138	9N5905-00-313-9064
NSNL	442-D-J	80138	REPL		442-D	80138	9N5905-00-313-9064
NSNL	4436A	28480	1387		N/A		
NSNL	444A	28480	GA		N/A		
NSNL	451-B	80138	REPL		452-C	80138	9Y5985-00-712-8388
NSNL	455A	28480	GA		N/A		
NSNL	4600-789PC21	43689	1387		N/A		
NSNL	464-A	80138	REPL		355D	28480	9N5985-00-957-1860
NSNL	47C2	31966	1387		N/A		
NSNL	477B	28480	GA	1	N/A		
NSNL	480	99899	GA		N/A		
NSNL	530-10	93459	REPL		8491A-010	28480	9N5985-00-865-0108
NSNL	530A-10	93459	REPL		8491A-010	28480	9N5985-00-865-0108
NSNL	530A-3	93459	REPL		8491A-003	28480	9N5985-00-167-0544
NSNL	535MN	93459	REPL		1425-4	93459	1H6930-01-140-4985
NSNL	54-C1	06424	REPL		G281A	28480	9N5985-00-772-6676
NSNL	546A	28480	GA		N/A		
NSNL	548A	28480	GA		N/A		

Source: https://assist.dla.mil -- Downloaded: 202610-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX B

REFERENCE NIIN TO STANDARD EQUIPMENT

REFERENCE EQUIPMENT NSN	MODEL	FSCM	STATUS	NOTES	STANDARD EQUIPMENT MODEL	FSCM	NSN
NSNL	5779-10	99899	REPL		2-10	93459	1H6625-01-017-1278
NSNL	5779-20	99899	REPL		2-20	93459	1H6625-01-017-1276
NSNL	5779-3	99899	REPL		2-3	93459	1H6625-01-020-6032
NSNL	5779-6	99899	REPL		2-6	93459	1H6625-01-017-1277
NSNL	606A34C	28480	1387		N/A		
NSNL	617912	06424	GA		N/A		
NSNL	617912	99899	GA		N/A		
NSNL	6255A	28480	REPL		5015V	98095	1H6625-01-224-0215
NSNL	6302-HC	77327	GA		N/A		
NSNL	642	99899	1387		N/A		
NSNL	643	50423	GA	1	N/A		
NSNL	6602	03782	GA		N/A		
NSNL	6602A	03782	GA		N/A		
NSNL	665	80138	1387		850-CT2W	83332	NSNL
NSNL	6855	83008	REPL		W5MT3A	13850	9N5950-00-987-5601
NSNL	72050-502	20193	GA		N/A		
NSNL	776D	28480	REPL		778D	28480	9N5985-00-239-3215
NSNL	80K-40	89536	GA		N/A		
NSNL	80N-5	89536	GA	1	N/A		
NSNL	809BL	28480	GA		N/A		
NSNL	809BPL	28480	GA		N/A		
NSNL	8470B-012	28480	REPL	1	423A	28480	9N6625-00-880-4978
NSNL	8481A	28480	GA		N/A		
NSNL	8482A	28480	GA		N/A		
NSNL	8482B	28480	GA		N/A		
NSNL	8485A	28480	GA		N/A		
NSNL	850-CT2W	83332	STD	1	850-CT2W	83332	NSNL
NSNL	8721A	28480	GA		N/A		
NSNL	874-GA	24655	REPL		0874-9577	82316	&&5840-00-868-1287
NSNL	8894-010	70998	REPL		B-1576	91161	1H5985-00-792-9928
NSNL	90513-10	12678	REPL		8491A-010	28480	9N5985-00-865-0108
NSNL	90513-3	12678	REPL		8491A-003	28480	9N5985-00-167-0544
NSNL	90513-6	12678	REPL		8491A-006	28480	9N5895-00-230-1827

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX B

REFERENCE NIIN TO STANDARD EQUIPMENT

REFERENCE EQUIPMENT NSN	MODEL	FSCM	STATUS	NOTES	STANDARD EQUIPMENT MODEL	FSCM	NSN
NSNL	91092-22	06049	REPL		P6161	80089	9N5950-00-645-1807
NSNL	9157430	18876	GA		N/A		
NSNL	9700-0025	30669	GA		N/A		
1H6625-LL-MHE-1799	4M-3	93459	STD		4M-3	93459	1H6625-LL-MHE-1799
1H6625-LL-MHE-2821	C4479	91161	1387		N/A		
1H6625-LL-MHE-2821	DA-412C/U	MIL	REPL		8404	70998	1H6625-01-150-1897
7Z6625-LL-MHE-2878	1001	03782	REPL		423A	28480	9N6625-00-880-4978
&&6625-LL-MHE-2884	M5C-160-8	52542	1387		N/A		
&&6625-LL-MHE-2886	R-1011AA	94990	REPL		R-1011B	94990	1H6625-01-205-1224
1H6625-LL-MHE-4050	RT-30A	12678	REPL		RT-30A	88869	1H6625-LL-MHE-4050
1H6625-LL-MHE-4050	RT-30A	88869	STD		RT-30A	88869	1H6625-LL-MHE-4050
7Z6625-LL-MHE-4086	11005A	28480	GA		N/A		
1H6625-LL-MHE-4110	TCR-300S-3-1	89022	STD		TCR-300S-3-1	89022	1H6625-LL-MHE-4110
1H6625-LL-MHE-4111	210A-3	93459	STD		210A-3	93459	1H6625-LL-MHE-4111
7Z6625-LL-MHE-4184	SPN-Z1	82199	GA		N/A		
7Z6625-LL-MHE-8011	M-1012A-AC	88869	REPL		M-1012A	88869	1H6625-01-206-2974
1H6625-LL-MHE-8012	4520-2	15305	REPL		4375G	99899	1H6625-LL-MHE-8020
1H6625-LL-MHE-8018	574-10	00443	STD		574-10	00443	1H6625-LL-MHE-8018
1H6625-LL-MHE-8019	574-20	00443	STD		574-20	00443	1H6625-LL-MHE-8019
1H6625-LL-MHE-8020	4375G	99899	STD		4375G	99899	1H6625-LL-MHE-8020
1H6625-LL-MHE-8021	24-6-34	93459	STD		24-6-34	93459	1H6625-LL-MHE-8021
1H6625-00-001-2376	3750	88865	STD		3750	88865	1H6625-00-001-2376
1H6625-00-023-5705	1293021P2	31637	GA		N/A		
1H6625-00-031-3521	1433-B	24655	REPL		1433-9724	24655	1H6625-00-031-3521
1H6625-00-031-3521	1433-9724	24655	STD		1433-9724	24655	1H6625-00-031-3521
1H6120-00-032-1173	W10HG3M	13850	STD		W10HG3M	13850	1H6120-00-032-1173
9G6120-00-033-3776	W10G3M	13850	STD		W10G3M	13850	9G6120-00-033-3776
7Z6625-00-047-9555	3750A	28480	REPL		442-D	80138	9N5905-00-313-9064
9S6120-00-054-7794	W10MT3A	13850	STD		W10MT3A	13850	9S6120-00-054-7794
9N5985-00-062-6919	TDR-29011	87864	STD		TDR-29011	87864	9N5985-00-062-6919
9G6130-00-062-9873	5015T	98095	REPL		5015V	98095	1H6625-01-224-0215
1H6130-00-065-3211	716A	28480	1387	1	N/A		
1H6130-00-065-3212	880	28480	1387		N/A		

Source: https://assist.dla.mil -- Downloaded: 202610-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX B

REFERENCE NIIN TO STANDARD EQUIPMENT

REFERENCE EQUIPMENT NSN	MODEL	FSCM	STATUS	NOTES	STANDARD EQUIPMENT MODEL	FSCM	NSN
1H5985-00-067-6750	3040B-20	99899	STD		3040B-20	99899	1H5985-00-067-6750
1H6625-00-067-9025	1434-G	24655	REPL		1433-9731	24655	1H6625-00-480-0950
1H6625-00-067-9025	1434-9707	24655	REPL		1433-9731	24655	1H6625-00-480-0950
9N5985-00-071-1401	82C	70998	REPL		8404	70998	1H6625-01-150-1897
1H6625-00-071-6219	7911092	18876	1387		N/A		
7Z6625-00-072-5406	710	16055	REPL		850-CT2W	83332	NSNL
1H6625-00-072-5590	110000	76526	1387		N/A		
1H6625-00-072-5590	21A	76526	REPL		JQE-36-3M	85604	1H6130-00-471-1735
7Z6625-00-072-7153	270A-470	54778	GA		N/A		
1H6625-00-074-1291	1027A	28481	GA		N/A		
1H6625-00-074-3703	11027A	28480	GA		N/A		
1H6625-00-076-0806	456A	28480	GA		N/A		
1H6625-00-077-7187	P6006	80009	GA		N/A		
1H6625-00-077-7187	010-0127-00	80009	GA		N/A		
7Z6625-00-077-7191	205B1	90101	1387	1	N/A		
1H6625-00-078-4324	DA-366/U	MIL	REPL		371BNM	99899	1H6625-00-970-3685
1H6625-00-078-4324	2328	15305	REPL		4375G	99899	1H6625-LL-MHE-8020
7Z5985-00-081-0163	310	80138	REPL		442-D	80138	9N5905-00-313-9064
9N5985-00-087-2547	432-D	80138	STD		432-D	80138	9N5985-00-087-2547
9N5985-00-087-4714	10514A	28480	STD		10514A	28480	9N5985-00-087-4714
7Z5985-00-087-4714	10658140	18876	REPL		10514A	28480	9N5985-00-087-4714
9G6110-00-087-4771	1571-AL	13850	REPL		1571-9831	13850	9G6110-00-087-4771
9G6110-00-087-4771	1571-9831	13850	STD		1571-9831	13850	9G6110-00-087-4771
1H5985-00-087-6646	316C4	95712	REPL		GM-318-C4	60674	9N6625-01-036-2020
1H5982-00-088-6001	11504A	28480	GA		N/A		
1H6625-00-097-6666	809C	28480	GA		N/A		
1H6625-00-102-9646	1433-W	24655	REPL		1433-9729	24655	1H6625-01-205-0820
1H6625-00-102-9646	1433-9720	24655	REPL		1433-9729	24655	1H6625-01-205-0820
7Z5985-00-103-9682	X601B	00929	REPL		X281A	28480	9N5985-00-892-0732
9N5985-00-104-3568	RAM-230A	09449	REPL		102AC46-1E	01456	1H6625-00-178-0008
1H5985-00-104-5981	D44S15	06424	REPL		S11PS	14135	9N5985-00-439-3536
1H6625-00-106-7452	10100C	28480	GA		N/A		
9N5985-00-111-5020	MA-648A	96341	REPL		UNDER REVIEW		

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX B

REFERENCE NIIN TO STANDARD EQUIPMENT

REFERENCE EQUIPMENT NSN	MODEL	FSCM	STATUS	NOTES	STANDARD EQUIPMENT MODEL	FSCM	NSN
7Z6625-00-115-9200	4779-3-6-10	99899	REPL		4M-3-6-10	93459	9N6625-01-026-2335
6G6130-00-116-7423	712C	28480	REPL		BHK-500-0.4M	85604	7Z6625-01-031-8855
1H6625-00-118-6729	973-20	93459	STD		973-20	93459	1H6625-00-118-6729
7Z5985-00-118-7985	757C-6	99899	REPL		8491A-006	28480	9N5895-00-230-1827
1H6625-00-123-7458	1455-A	24655	REPL		UNDER REVIEW		
1H6625-00-124-9382	1419-9702	24655	REPL		1412-9410	24655	1H6625-00-465-6861
9N5985-00-136-8330	P281B	28480	STD		P281B	28480	9N5985-00-136-8330
9G6130-00-137-0167	6266B	28480	STD		6266B	28480	9G6130-00-137-0167
9N5950-00-138-5219	70412	06049	REPL		P6161	80089	9N5950-00-645-1807
1H6625-00-140-8183	1433-Z	24655	REPL		1433-9726	24655	1H6625-00-140-8183
1H6625-00-140-8183	1433-9726	24655	STD		1433-9726	24655	1H6625-00-140-8183
&&6625-00-143-0784	W10HMT3	13850	REPL		W10MT3A	13850	9S6120-00-054-7794
9N5985-00-145-3514	CX20PS	14135	STD		CX20PS	14135	9N5985-00-145-3514
7Z6625-00-148-8098	W40-NC	06351	REPL		102AC46-1E	01456	1H6625-00-178-0008
1H6625-00-148-8099	010-0076-00	80009	GA		N/A		
7Z6625-00-150-6965	1120A	28480	GA		N/A		
1H6625-00-150-7079	368NM	99899	1387		N/A		
7Z6130-00-160-0827	6274B	28480	STD		6274B	28480	7Z6130-00-160-0827
1H6130-00-163-6201	6443B	28480	STD		6443B	28480	1H6130-00-163-6201
&&6625-00-165-3837	6525A	28480	1387		N/A		
9N5985-00-167-0544	8491A-003	28480	STD		8491A-003	28480	9N5985-00-167-0544
&&6625-00-170-6196	10526T	28480	GA		N/A		
7Z5985-00-172-6258	704-69	99899	REPL		AF-117A-69-34	93459	9N6625-01-063-9297
1H6625-00-172-6612	P6021	80009	GA		N/A		
9N6625-00-173-5441	1433-J	24655	REPL		1433-9704	24655	9N6625-00-173-5441
9N6625-00-173-5441	1433-9704	24655	STD		1433-9704	24655	9N6625-00-173-5441
9N6625-00-174-6625	RB-503T	07342	REPL		RT-30A	88869	1H6625-LL-HHE-4050
9Y6625-00-177-1639	82A	70998	REPL		8404	70998	1H6625-01-150-1897
1H6625-00-178-0008	102AC46-1E	01456	STD		102AC46-1E	01456	1H6625-00-178-0008
1H4931-00-178-1052	3202	88865	STD		3202	88865	1H4931-00-178-1052
9N6625-00-179-8448	S382C	28480	STD		S382C	28480	9N6625-00-179-8448
1H6625-00-185-6110	010-0175-01	80009	GA		N/A		
7Z6625-00-186-7685	11652A	28480	GA		N/A		

Source: https://assist.dla.mil -- Downloaded: 202610-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX B

REFERENCE NIIN TO STANDARD EQUIPMENT

REFERENCE EQUIPMENT NSN	MODEL	FSCM	STATUS	NOTES	STANDARD EQUIPMENT MODEL	FSCM	NSN
9N5985-00-192-0138	2002-6113-00	16179	STD		2002-6113-00	16179	9N5985-00-192-0138
&&6625-00-192-0838	1-10	93459	REPL		8491A-010	28480	9N5985-00-865-0108
1H6625-00-198-5812	X501C	00929	REPL		X301A	13047	1H5985-01-069-2318
9N5850-00-201-4268	578-BS5	24655	REPL		ST-100	88869	9N5950-00-679-6862
1H5985-00-201-5055	AJ-210N	00929	REPL		AU-65AMN	12457	1H6625-01-040-9528
1H6625-00-209-6841	DA-88/U	MIL	REPL		8404	70998	1H6625-01-150-1897
1H6625-00-215-4931	CN-1000/G	MIL	REPL		850-CT2W	83332	NSNL
1H6625-00-215-4931	350D	28480	1387		850-CT2W	83332	NSNL
1H6625-00-215-4931	7904453	77327	1387		UNDER REVIEW		
7Z5985-00-222-0465	757C-3	99899	REPL		8491A-003	28480	9N5985-00-167-0544
9N5985-00-222-9037	1-20	93459	REPL		8491A-020	28480	1H4935-01-031-2694
9N6625-00-222-9771	8470A-012	28480	REPL		423A	28480	9N6625-00-880-4978
1H6625-00-228-9918	1433-P	24655	REPL		1433-9726	24655	1H6625-00-140-8183
9N5895-00-230-1827	8491A-006	28480	STD		8491A-006	28480	9N5895-00-230-1827
1H5985-00-230-1828	8491A-030	28480	REPL		2-30	93459	1H6625-01-014-3463
&&6625-00-235-6308	1433-9706	24655	STD		1433-9706	24655	&&6625-00-235-6308
9N5985-00-239-3215	778D	28480	STD		778D	28480	9N5985-00-239-3215
&&5935-00-239-9553	10457A	28480	GA		N/A		
1H5985-00-240-3974	CN-45/UP	MIL	GA		N/A		
9N5985-00-241-3518	376BNF	99899	STD		376BNF	99899	9N5985-00-241-3518
1H5840-00-242-2653	34B1	06424	REPL		UNDER REVIEW		
9N5985-00-250-3481	CN-30A/U	MIL	REPL		8491A-010	28480	9N5985-00-865-0108
1H6625-00-251-1158	1490-B	24655	REPL		1491-9704	24655	1H6625-00-251-1158
1H6625-00-251-1158	1491-D	24655	REPL		1491-9704	24655	1H6625-00-251-1158
1H6625-00-251-1158	1491-9704	24655	STD		1491-9704	24655	1H6625-00-251-1158
1H6625-00-251-1158	7907319	00000	REPL		1491-9704	24655	1H6625-00-251-1158
9N5985-00-252-8026	1/432D	80138	STD		1/432D	80138	9N5985-00-252-8026
9N5985-00-258-0123	4M-10	93459	STD		4M-10	93459	9N5985-00-258-0123
9V6625-00-261-5033	1506A	93459	STD		1506A	93459	9V6625-00-261-5033
9N6625-00-261-7749	4055-10	99899	STD		4055-10	99899	9N6625-00-261-7749
1H6720-00-262-4198	C-59AP	80009	STD		C-59AP	80009	1H6720-00-262-4198
7Z6625-00-284-7494	806B	28480	GA		N/A		
1H5985-00-285-6455	355A	28480	REPL		355C	28480	1H5985-00-993-1377

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX B

REFERENCE NIIN TO STANDARD EQUIPMENT

REFERENCE EQUIPMENT NSN	MODEL	FSCM	STATUS NOTES	STANDARD EQUIPMENT MODEL	FSCM	NSN
1H6625-00-287-5067	796FM	99899	1387	N/A		
1H5985-00-288-0171	1156	77327	1387	N/A		
7Z6625-00-288-0179	S485A	28480	REPL	214	00443	1H6625-00-395-0779
1H6625-00-288-0183	712	99899	REPL	AF-117A-69-34	93459	9N6625-01-063-9297
1H6625-00-291-0956	D44C15	06424	REPL	C20PS	14135	1H4931-00-921-7357
1H6625-00-291-0956	D44C15	56232	1387	N/A		
1H6625-00-291-1039	8472A-001	28480	STD	8472A-001	28480	1H6625-00-291-1039
1H6625-00-294-4871	973P-20	93459	REPL	973-20	93459	1H6625-00-118-6729
1H5950-00-294-4872	W30HG3M	13850	1387	N/A		
1H5950-00-294-4883	AC-60A	28480	GA	N/A		
1H5950-00-294-4896	ST-200F	12678	REPL	SPX-3031	88869	1H5950-01-040-0282
1H6625-00-294-4917	QR36-15A	49956	REPL	DCR40-25B	49956	1H6130-01-040-9808
9N5985-00-295-9824	H281A	28480	GA	N/A		
1H6625-00-296-1412	UHR-220	88865	REPL	BHK-500-0.4M	85604	7Z6625-01-031-8855
1H6625-00-296-1644	453-1	18778	REPL	C-30BP	80009	7G6720-01-095-2205
1H6625-00-296-1665	RDC	14655	REPL	1433-9724	24655	1H6625-00-031-3521
9Y6625-00-301-0815	MX-1258/U	MIL	GA	N/A		
1H6625-00-301-4738	CY-245/U	MIL	GA	N/A		
1H6625-00-301-4738	35-3078	72598	GA	N/A		
1H6625-00-302-8319	RDB	14655	REPL	240C	12697	1H6625-00-585-4915
1H6625-00-304-7213	809B	28480	GA	N/A		
1H4470-00-307-0437	10528A	28480	GA	N/A		
1H5985-00-310-1475	45X1-10	99899	REPL	X752C	28480	9N5985-00-646-9472
1H5915-00-310-1476	407655	80006	STD	407655	80006	1H5915-00-310-1476
1H6625-00-311-6869	010-0197-00	80009	GA	N/A		
9N5905-00-313-9064	442-D	80138	STD	442-D	80138	9N5905-00-313-9064
1H5985-00-330-9882	614A	99899	REPL	S281A	28480	1R4920-01-029-4624
1H4931-00-346-8264	DA-115/U	MIL	1387	N/A		
1H6625-00-354-9730	10536A	28480	GA	N/A		
1H5985-00-364-3668	X610C	00929	REPL	X752C	28480	9N5985-00-646-9472
1H6625-00-368-7198	375NM	99899	REPL	1425-4	93459	1H6930-01-140-4985
1H6625-00-368-7198	404-M05	22424	1387	N/A		
1H6625-00-368-9223	0732	55026	GA	N/A		

Source: https://assist.dla.mil -- Downloaded: 202610-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX B

REFERENCE NIIN TO STANDARD EQUIPMENT

REFERENCE EQUIPMENT NSN	MODEL	FSCM	STATUS	NOTES	STANDARD EQUIPMENT MODEL	FSCM	NSN
1H5935-00-370-8549	0874-9099	24655	REPL		0874-9099	82316	1H5935-00-370-8549
1H5935-00-370-8549	0874-9099	82316	STD		0874-9099	82316	1H5935-00-370-8549
1H6625-00-372-5237	P6046	80009	GA		N/A		
1H6625-00-372-5237	010-0213-00	80009	GA		N/A		
1H6625-00-373-7528	TM503	80009	GA		N/A		
7Z6625-00-373-7613	80RF-1	89536	GA		N/A		
1H6625-00-376-1634	DA-64/UP	MIL	1387		N/A		
1H6625-00-376-5076	513	99899	REPL	2	314	00443	1H6625-01-039-5259
1H6625-00-385-1156	10014A	28480	GA		N/A		
1H6625-00-385-1157	11000	30669	GA		N/A		
1H6625-00-389-7007	10002B	28480	GA		N/A		
1H6625-00-392-0521	MA-8F208	96341	REPL		UNDER REVIEW		
1H6625-00-392-0521	OD8F208	96341	1387		N/A		
1H6625-00-395-0779	214	00443	STD		214	00443	1H6625-00-395-0779
1H6625-00-395-0785	1325	11837	GA		N/A		
6G6625-00-404-0409	P486A	28480	GA		N/A		
4G6130-00-406-5695	6299A	28480	STD		6299A	28480	4G6130-00-406-5695
1H6625-00-411-9628	722 MDQ	24655	1387		N/A		
9N5985-00-412-2986	3202B-10	99899	STD		3202B-10	99899	9N5985-00-412-2986
1H6625-00-424-4334	8470A	28480	STD		8470A	28480	1H6625-00-424-4334
9N6625-00-424-5066	616	99899	STD		616	99899	9N6625-00-424-5066
1H6625-00-427-5149	A40A10	89536	GA		N/A		
1H6625-00-427-5160	A40A20	89536	GA		N/A		
1H6625-00-433-2395	447B	28480	GA		N/A		
1H5821-00-433-5584	8160	70998	REPL		8164	70998	1H5985-01-024-8193
1H6625-00-437-4861	6205B	28480	REPL		5015V	98095	1H6625-01-224-0215
1H6625-00-437-9157	1432-K	24655	REPL		1433-9722	24655	1H6625-00-947-7534
1H6625-00-437-9157	1433-K	24655	REPL		1433-9722	24655	1H6625-00-947-7534
9N5985-00-439-3536	S11PS	14135	STD		S11PS	14135	9N5985-00-439-3536
7Z5985-00-442-3051	3020A	99899	REPL		778D	28480	9N5985-00-239-3215
9N5985-00-442-6083	X486A	28480	GA		N/A		
1H6625-00-445-6928	J347A	28480	GA		N/A		
1H6130-00-445-6933	10519453	MIL	GA		N/A		

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX B

REFERENCE NIIN TO STANDARD EQUIPMENT

REFERENCE EQUIPMENT NSN	MODEL	FSCM	STATUS	NOTES	STANDARD EQUIPMENT MODEL	FSCM	NSN
1H6130-00-445-6933	721A	28480	REPL		5015V	98095	1H6625-01-224-0215
9N5985-00-445-6952	AD-10N	00929	REPL		8491A-010	28480	9N5985-00-865-0108
1H6625-00-445-6954	AD-30N	00929	REPL		2-30	93459	1H6625-01-014-3463
7Z5985-00-448-0580	643	99899	REPL		BA-C-110C	00341	1H6625-01-030-5505
9N5985-00-450-8802	3043B-30	99899	STD		3043B-30	99899	9N5985-00-450-8802
1H6625-00-463-4011	1433-M	24655	REPL		1433-9714	24655	1H6625-00-463-4011
1H6625-00-463-4011	1433-9714	24655	STD		1433-9714	24655	1H6625-00-463-4011
1H6625-00-463-5241	010-6101-02	80009	GA		N/A		
1H6625-00-463-5241	134303-1	45413	GA		N/A		
1H6625-00-463-5241	137617-1	45413	GA		N/A		
1H6625-00-464-7743	1108A	28480	GA		N/A		
1H6625-00-465-6861	1412-9410	24655	STD		1412-9410	24655	1H6625-00-465-6861
9N5985-00-465-8112	3042B-10	99899	STD		3042B-10	99899	9N5985-00-465-8112
6A6720-00-467-0974	CR9	47904	REPL	1	C-30BP	80009	7Q6720-01-095-2205
1H6130-00-471-1735	JQE-36-3M	85604	STD		JQE-36-3M	85604	1H6130-00-471-1735
1H6625-00-476-6838	1432-X	24655	REPL		1433-9722	24655	1H6625-00-947-7534
9N5985-00-477-8165	8085	70998	STD		8085	70998	9N5985-00-477-8165
1H6625-00-480-0950	1433-9731	24655	STD		1433-9731	24655	1H6625-00-480-0950
1H6625-00-482-4123	80F15	89536	GA		N/A		
7Z5985-00-483-4400	757C-10	99899	REPL		8491A-010	28480	9N5985-00-865-0108
1H6625-00-483-6777	1490-F	24655	REPL	1	1491-9704	24655	1H6625-00-251-1158
9N5985-00-485-4879	AC-03N	00929	REPL		210A-3	93459	1H6625-LL-MHE-4111
9N5985-00-488-7434	K362A	28480	STD		K362A	28480	9N5985-00-488-7434
9N5915-00-488-7437	R362A	28480	STD		R362A	28480	9N5915-00-488-7437
1H6625-00-488-9403	926	93459	GA		N/A		
1H6130-00-489-9167	6216A	28480	REPL		JQE-36-3M	85604	1H6130-00-471-1735
7Z5985-00-490-2834	779D	28480	REPL		11692D	28480	9N5985-01-024-3832
1H6625-00-490-7298	10529A	28480	GA		N/A		
1H6625-00-490-8844	E103	88869	1387		N/A		
9N5985-00-492-7921	3060-20	99899	STD		3060-20	99899	9N5985-00-492-7921
9Y6625-00-494-5622	TRB50	04423	GA		N/A		
9V6625-00-495-7898	K422A-001	28480	REPL		K422A	28480	1H6625-00-874-7733
7Z6625-00-495-9930	816A	28480	GA		N/A		

Source: https://assist.dla.mil -- Downloaded: 202640-26T13:40Z
Check the source to verify that this is the currentversion before use.

APPENDIX B

REFERENCE NIIN TO STANDARD EQUIPMENT

REFERENCE EQUIPMENT NSN	MODEL	FSCM	STATUS	NOTES	STANDARD EQUIPMENT MODEL	FSCM	NSN
1H6130-00-496-8652	6207B	28480	REPL		UNDER REVIEW		
1H6625-00-498-2232	010-0177-01	80009	GA		N/A		
1H6625-00-498-2232	534114-2	96214	GA		N/A		
AA5985-00-498-5838	1-3	93459	REPL		8491A-003	28480	9N5985-00-167-0544
7Z5985-00-498-8414	1-6	93459	REPL		8491A-006	28480	9N5895-00-230-1827
9N5915-00-503-0533	360C	28480	STD		360C	28480	9N5915-00-503-0533
9N5915-00-503-1787	360A	28480	STD		360A	28480	9N5915-00-503-1787
9N5950-00-504-9090	M5	13850	STD		M5	13850	9N5950-00-504-9090
1H6625-00-506-0533	A-90	89536	GA		N/A		
1H6625-00-506-4359	MX-2012/U	MIL	GA		N/A		
1H6625-00-511-5383	11044A	28480	GA	2	N/A		
1H6625-00-511-5383	459A	28480	GA	1	N/A		
1H6625-00-511-5383	9113325	18876	GA		N/A		
1H6625-00-519-2054	CDC-5	14655	REPL		UNDER REVIEW		
2R6625-00-519-2055	CDB-5	14655	REPL		UNDER REVIEW		
9N5985-00-525-5074	AT-200-SR	12598	REPL		355C	28480	1H5985-00-993-1377
9V6625-00-530-2601	705-99	99899	REPL		AF-117A-69-34	93459	9N6625-01-063-9297
7Z6625-00-530-2636	271A-30	54778	GA		N/A		
1H6625-00-535-9532	S501B	00929	STD		S501B	00929	1H6625-00-535-9532
1H6625-00-538-1164	DA-43/U	MIL	1387		N/A		
9N5985-00-538-7328	DA-146/U	MIL	REPL		WF-0055	00929	9N5985-00-538-7328
9N5985-00-538-7328	WF-0055	00929	STD		WF-0055	00929	9N5985-00-538-7328
9N5985-00-538-7329	DA-148/U	MIL	REPL		WF-0050	00929	9N5985-00-572-6267
7G5985-00-539-6126	DA-145/U	MIL	REPL		WF-0025	00929	7G5985-00-539-6126
7G5985-00-539-6126	WF-0025	00929	STD		WF-0025	00929	7G5985-00-539-6126
7Z6625-00-553-7652	1432-M	24655	REPL		1433-9714	24655	1H6625-00-463-4011
1H6625-00-562-4506	50B	12996	REPL		850-CT2W	83332	NSNL
1H6625-00-567-5837	11004A	28480	GA		N/A		
9N5985-00-572-6267	WF-0050	00929	STD		WF-0050	00929	9N5985-00-572-6267
9N5985-00-578-5747	3002-20	99899	STD		3002-20	99899	9N5985-00-578-5747
1H6625-00-585-3152	1432-P	24655	REPL		1433-9726	24655	1H6625-00-140-8183
1H6625-00-585-3152	8616453	18876	REPL		1433-9726	24655	1H6625-00-140-8183
1H6625-00-585-4915	PC92350007-1	38597	REPL		240C	12697	1H6625-00-585-4915

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX B

REFERENCE NIIN TO STANDARD EQUIPMENT

REFERENCE EQUIPMENT NSN	MODEL	FSCM	STATUS	NOTES	STANDARD EQUIPMENT MODEL	FSCM	NSN
1H6625-00-585-4915	240C	12697	STD		240C	12697	1H6625-00-585-4915
1H6625-00-585-4915	7907234	18876	REPL		240C	12697	1H6625-00-585-4915
1H5985-00-587-6905	DA-177/U	MIL	REPL		8404	70998	1H6625-01-150-1897
&&5985-00-596-5378	G375A	28480	REPL		G-101	77327	9N5985-00-921-3697
1H6130-00-601-6301	ABC100-0.2M	85604	REPL		6443B	28480	1H6130-00-163-6201
1H6625-00-602-2087	1454-A	24655	REPL		UNDER REVIEW		
1H6625-00-602-2089	X382A	28480	STD		X382A	28480	1H6625-00-602-2089
1H6625-00-602-2089	7907413	18876	REPL		X382A	28480	1H6625-00-602-2089
1H6625-00-602-2089	7907413	19200	REPL		X382A	28480	1H6625-00-602-2089
1H6625-00-602-2089	7909033	18876	REPL		X382A	28480	1H6625-00-602-2089
1R5985-00-604-8604	3045C-10	99899	STD		3045C-10	99899	1R5985-00-604-8604
9N5985-00-606-9161	J281A	28480	STD		J281A	28480	9N5985-00-606-9161
7Z5985-00-615-3102	210-6	93459	REPL		8491A-006	28480	9N5895-00-230-1827
9N5985-00-615-3104	50-6	93459	REPL		8491A-006	28480	9N5895-00-230-1827
9N5950-00-617-9242	W5MT3	13850	REPL		W5MT3A	13850	9N5950-00-987-5601
9N6625-00-618-9192	P487B	28480	GA	1	N/A		
7Z5985-00-623-0255	874-GAL	24655	REPL		0874-9577	82316	&&5840-00-868-1287
1H6625-00-624-8791	DV411-10K	11837	1387		N/A		
9N5985-00-626-4370	50-20	93459	REPL		8491A-020	28480	1H4935-01-031-2694
1H6625-00-628-6514	11040A	28480	GA		N/A		
7Z6625-00-628-6514	453A	28480	1387	2	N/A		
7Z6625-00-633-0231	210-20	93459	REPL		8491A-020	28480	1H4935-01-031-2694
1H6130-00-635-7991	712B	28480	REPL		BHK-500-0.4M	85604	7Z6625-01-031-8855
1H6625-00-642-8911	DA-64B/UP	MIL	1387		N/A		
1H6625-00-643-2682	597C24	94033	GA		N/A		
9N5950-00-645-1807	P6161	80089	STD		P6161	80089	9N5950-00-645-1807
9N5985-00-646-9472	X752C	28480	STD		X752C	28480	9N5985-00-646-9472
1H6625-00-649-2737	CY-669/U	MIL	GA		N/A		
1H6625-00-649-2737	310-2	21900	1387		N/A		
9Y6625-00-649-4284	CDB-3	14655	REPL		UNDER REVIEW		
9N5985-00-655-7589	50-10	93459	REPL		8491A-010	28480	9N5985-00-865-0108
7Z6625-00-656-2454	X487B	28480	GA	1	N/A		
1H6130-00-660-8590	158-100	93953	1387		N/A		

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX B

REFERENCE NIIN TO STANDARD EQUIPMENT

REFERENCE EQUIPMENT NSN	MODEL	FSCM	STATUS	NOTES	STANDARD EQUIPMENT MODEL	FSCM	NSN
9Y5840-00-669-8675	80M	70998	STD		80M	70998	9Y5840-00-669-8675
1H6625-00-675-4983	RT-9	12678	REPL		M-1012A	88869	1H6625-01-206-2974
7Z6625-00-678-0904	452A	28480	GA	1	N/A		
&&6625-00-678-5639	AN/UPM-85	MIL	1387	1	N/A		
7G6625-00-679-0627	J382A	28480	STD		J382A	28480	7G6625-00-679-0627
9N5950-00-679-5019	ST-100A	12678	REPL		ST-100	88869	9N5950-00-679-6862
9N5950-00-679-5019	ST-100A	88869	REPL		ST-100	88869	9N5950-00-679-6862
7Z6625-00-679-5386	195-B	77327	REPL		X382A	28480	1H6625-00-602-2089
9N5950-00-679-6862	ST-100	12678	REPL		ST-100	88869	9N5950-00-679-6862
9N5950-00-679-6862	ST-100	88869	STD		ST-100	88869	9N5950-00-679-6862
9G6120-00-682-2557	W10MT3	13850	REPL		W10MT3A	13850	9S6120-00-054-7794
9G5995-00-686-4683	11500A	28480	GA		N/A		
9N5915-00-686-8922	360B	28480	STD		360B	28480	9N5915-00-686-8922
7Z5950-00-688-5722	W5MT	13850	REPL		W5MT3A	13850	9N5950-00-987-5601
1H6625-00-691-6597	P347A	28480	GA		N/A		
&&6625-00-708-8582	67	70998	REPL		8404	70998	1H6625-01-150-1897
7Z6625-00-710-7270	560-B	99899	GA	1	N/A		
9Y5985-00-712-8388	452-C	80138	STD		452-C	80138	9Y5985-00-712-8388
1H5985-00-712-8388	9975610	18876	REPL		452-C	80138	9Y5985-00-712-8388
1H6625-00-713-3734	724AR	28480	1387		N/A		
7Z6625-00-713-9252	530-3	93459	REPL		8491A-003	28480	9N5985-00-167-0544
9N5985-00-714-3247	3004-20	99899	STD		3004-20	99899	9N5985-00-714-3247
1H6625-00-716-4031	108146-690	13973	GA		N/A		
9N6625-00-717-6560	TM-1	82199	GA	1	N/A		
9N5915-00-725-6051	LA-60N	00929	STD		LA-60N	00929	9N5915-00-725-6051
1R5985-00-729-1297	640	99899	STD		640	99899	1R5985-00-729-1297
&&5985-00-729-6971	H752C	28480	REPL		574-10	00443	1H6625-LL-HHE-8018
1H6625-00-733-5914	A404-7	12868	REPL		RT-30A	88869	1H6625-LL-HHE-4050
1H6625-00-733-5914	RB-503C-S1177	07342	REPL		RT-30A	88869	1H6625-LL-HHE-4050
1H6625-00-733-5914	RT-7	12678	REPL		RT-30A	88869	1H6625-LL-HHE-4050
1H6625-00-733-5914	SC-58	88869	REPL		RT-30A	88869	1H6625-LL-HHE-4050
9Q6625-00-738-2716	L20PS	14135	STD		L20PS	14135	9Q6625-00-738-2716
6G6625-00-752-3222	P382A	28480	STD		P382A	28480	6G6625-00-752-3222

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX B

REFERENCE NIIN TO STANDARD EQUIPMENT

REFERENCE EQUIPMENT NSN	MODEL	FSCM	STATUS	NOTES	STANDARD EQUIPMENT MODEL	FSCM	NSN
7Z6625-00-753-2109	1201B	24655	GA	1	N/A		
1H6625-00-756-1507	DB655	11837	1387		N/A		
1H6625-00-756-1507	DB655-639A	11837	1387		N/A		
1R5985-00-757-0549	3041-20	99899	STD		3041-20	99899	1R5985-00-757-0549
1H6625-00-762-3872	DA-296A/GRM-50	MIL	1387		N/A		
1H6625-00-762-9285	DBGS385-1000	01220	1387		N/A		
1H6625-00-762-9285	DBGS385-1000	52542	1387		N/A		
9N5985-00-763-8796	AH-C32	00929	REPL		8491A-006	28480	9N5895-00-230-1827
1H6130-00-766-8543	6265A	28480	REPL		6266B	28480	9G6130-00-137-0167
9N5985-00-771-8421	G382A	28480	REPL		G-101	77327	9N5985-00-921-3697
1H6625-00-772-2592	8890	70998	REPL		B-1576	91161	1H5985-00-792-9928
9N5985-00-772-6676	G281A	28480	STD		G281A	28480	9N5985-00-772-6676
1H6625-00-773-6102	AN/USM-119A	MIL	GA		N/A		
1H6625-00-773-6102	189-100	93953	GA		N/A		
9N6625-00-773-7311	8135	70998	STD		8135	70998	9N6625-00-773-7311
7Z6625-00-775-1753	1423-9801	24655	REPL		1412-9410	24655	1H6625-00-465-6861
9N4931-00-777-1373	R752C	28480	STD		R752C	28480	9N4931-00-777-1373
7Z5985-00-777-1379	530-20	93459	REPL		8491A-020	28480	1H4935-01-031-2694
7Z4931-00-777-1381	50-40	93459	REPL		2-40	93459	1H6625-01-014-3464
9N5985-00-777-1382	50-30	93459	REPL		2-30	93459	1H6625-01-014-3463
1H6625-00-777-6748	801197	00929	GA		N/A		
1H6625-00-777-6748	9063646	18876	GA		N/A		
7Z5985-00-777-6750	540	99899	GA	1	N/A		
9N5985-00-781-2903	CN-87/U	MIL	REPL		8491A-020	28480	1H4935-01-031-2694
9N5985-00-781-2903	CN-87A/U	MIL	REPL		8491A-020	28480	1H4935-01-031-2694
9N5985-00-781-2903	CN-87B/U	MIL	REPL		8491A-020	28480	1H4935-01-031-2694
7Z6625-00-781-8043	541	99899	GA	1	N/A		
1H5985-00-784-9045	371NM	99899	REPL		371BNM	99899	1H6625-00-970-3685
9N5985-00-788-6962	3004-10	99899	STD		3004-10	99899	9N5985-00-788-6962
1H5905-00-792-4543	AE-10N	00929	REPL		8491A-010	28480	9N5985-00-865-0108
&&6625-00-792-4612	160A	80009	GA		N/A		
1H5985-00-792-9928	B-1576	91161	STD		B-1576	91161	1H5985-00-792-9928
1H5985-00-792-9928	DA-242/U	MIL	REPL		B-1576	91161	1H5985-00-792-9928

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX B

REFERENCE NIIN TO STANDARD EQUIPMENT

REFERENCE EQUIPMENT NSN	MODEL	FSCM	STATUS	NOTES	STANDARD EQUIPMENT MODEL	FSCM	NSN
1H5985-00-792-9928	DA-242A/U	MIL	REPL		B-1576	91161	1H5985-00-792-9928
8R6625-00-792-9956	AN/URM-111	MIL	GA	1	N/A		
1H6625-00-793-1344	343A	28480	GA		N/A		
7Z6625-00-793-1345	345B	28480	GA	1	N/A		
7Z6625-00-796-3157	253	77327	GA		N/A		
7Z6625-00-799-8655	454A	28480	1387	1	N/A		
9N5915-00-804-5302	360D	28480	STD		360D	28480	9N5915-00-804-5302
1H6625-00-811-2435	108476-690	13973	GA		N/A		
1H6625-00-811-2435	8478B	28480	GA		N/A		
1H5985-00-813-5433	1228020P4	31637	1387		N/A		
7Z6625-00-813-6847	AC-10N	00929	REPL		2-20	93459	1H6625-01-017-1276
1H6625-00-813-6847	1290015P3	31637	GA		N/A		
1H6625-00-813-6847	576R747H03	97942	1387		N/A		
1H6625-00-813-6853	AC-20N	00929	REPL		N9412-20	09992	1H5985-01-203-5192
1H6625-00-813-6853	1290015P4	31637	GA		N/A		
7Z6130-00-814-2106	6439B	28480	REPL		6274B	28480	7Z6130-00-160-0827
7Z6130-00-814-2106	922582-1	06481	REPL		6266B	28480	9G6130-00-137-0167
9N5985-00-814-4721	H752D	28480	REPL		574-20	00443	1H6625-LL-HHE-8019
1H6625-00-815-8333	81	11332	GA		N/A		
9N5985-00-816-4287	3000-10	99899	STD		3000-10	99899	9N5985-00-816-4287
7Z5985-00-816-8717	530-6	93459	REPL		8491A-006	28480	9N5895-00-230-1827
1H6625-00-816-9321	P6016	80009	GA		N/A		
1H6625-00-816-9321	010-0037-00	80009	GA		N/A		
7Z6625-00-818-7643	602540	07239	1387		N/A		
1H5985-00-822-7874	R382A	28480	STD		R382A	28480	1H5985-00-822-7874
9N5985-00-822-8666	K382A	28480	STD		K382A	28480	9N5985-00-822-8666
1H6625-00-823-5359	6206B	28480	REPL		5015V	98095	1H6625-01-224-0215
7Z5985-00-831-5991	30-0	80138	REPL		355C	28480	1H5985-00-993-1377
&&6720-00-831-7888	197A	28480	REPL		197B	28480	&&6720-01-104-3402
1H6130-00-835-2608	HR40-5B	09206	1387		N/A		
1H6130-00-835-2608	HR40-5B	52542	1387		N/A		
1H6625-00-838-2826	350B	28480	REPL		850-CT2W	83332	NSNL
7Z5985-00-839-4405	530A-20	93459	REPL		8491A-020	28480	1H4935-01-031-2694

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX B

REFERENCE NIIN TO STANDARD EQUIPMENT

REFERENCE EQUIPMENT NSN	MODEL	FSCM	STATUS	NOTES	STANDARD EQUIPMENT MODEL	FSCM	NSN
7Z5985-00-840-3418	530A-6	93459	REPL		8491A-006	28480	9N5895-00-230-1827
1H6625-00-840-4256	1432-T	24655	REPL		1433-9729	24655	1H6625-01-205-0820
1H6625-00-840-4256	1433-T	24655	REPL		1433-9729	24655	1H6625-01-205-0820
1H6625-00-840-4256	1433-9710	24655	REPL		1433-9729	24655	1H6625-01-205-0820
1H6625-00-841-5020	D44L15	06424	REPL		L20PS	14135	906625-00-736-2716
1H6625-00-841-5020	L24PS	14135	1387		N/A		
1R6625-00-841-8917	DCR40-20A	49956	REPL		DCR40-25B	49956	1H6130-01-040-9808
1H6625-00-844-9134	724BR	28480	1387		N/A		
7Z6625-00-859-5170	S-347A	28480	GA		N/A		
1H6625-00-859-5184	RT-2	12678	REPL		RT-20A	88869	1H5950-01-067-3203
&&6720-00-863-2353	196A	28480	REPL	2	C-30BP	80009	7Q6720-01-095-2205
9N5985-00-865-0108	8491A-010	28480	STD		8491A-010	28480	9N5985-00-865-0108
9N6625-00-865-6142	CDC	14655	REPL		UNDER REVIEW		
9N6625-00-865-6142	CDC-3	14655	REPL		UNDER REVIEW		
7Z6625-00-866-0168	1001-M4	82199	GA		N/A		
&&5840-00-868-1287	0874-9577	24655	REPL		0874-9577	82316	&&5840-00-868-1287
&&5840-00-868-1287	0874-9577	82316	STD		0874-9577	82316	&&5840-00-868-1287
1H6625-00-874-7733	K422A	28480	STD		K422A	28480	1H6625-00-874-7733
1H6625-00-876-3100	XB1000	00929	REPL		423A	28480	9N6625-00-880-4978
1H6625-00-876-3106	XD-3A	04423	REPL	2	423A	28480	9N6625-00-880-4978
9N5950-00-877-4863	M2G3	13850	STD		M2G3	13850	9N5950-00-877-4863
9G6120-00-879-3698	U5G3M	13850	STD		U5G3M	13850	9G6120-00-879-3698
&&6625-00-880-1217	K486A	28480	GA		N/A		
9N6625-00-880-4978	423A	28480	STD		423A	28480	9N6625-00-880-4978
9N5985-00-881-0262	AU-10	12457	REPL		2-3414-30	09992	9N5985-00-999-8095
9N5985-00-881-0262	AU-10A	12457	REPL		2-3414-30	09992	9N5985-00-999-8095
1H5905-00-882-6496	RFB-552-50	14140	REPL		432-D	80138	9N5985-00-087-2547
1H5905-00-882-6496	2088792-1	06845	1387		N/A		
1H5905-00-882-6496	2088792-1	27914	1387		N/A		
9N5985-00-882-8654	3003-20	99899	STD		3003-20	99899	9N5985-00-882-8654
&&6625-00-886-1955	6209B	28480	REPL		BHK-500-0.4M	85604	7Z6625-01-031-8855
1H6625-00-886-1962	2028906-0701	06845	GA		N/A		
1H6625-00-886-1962	346B	28480	GA		N/A		

Source: https://assist.dla.mil -- Downloaded: 202640-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX B

REFERENCE NIIN TO STANDARD EQUIPMENT

REFERENCE EQUIPMENT NSN	MODEL	FSCM	STATUS	NOTES	STANDARD EQUIPMENT MODEL	FSCM	NSN
1H6625-00-886-1962	349A	28480	GA		N/A		
1H6625-00-887-7783	G347A	28480	GA		N/A		
9N5985-00-892-0732	X281A	28480	STD		X281A	28480	9N5985-00-892-0732
1H6110-00-895-2699	1570-ALS-15	13850	REPL		1571-9831	13850	9G6110-00-087-4771
1H6625-00-897-3406	478W	02039	GA		N/A		
7Z6625-00-902-9745	1201C	24655	GA	2	N/A		
1H6525-00-905-0051	8230	70998	REPL		8404	70998	1H6625-01-150-1897
7Z5985-00-906-3287	613A	99899	REPL		G281A	28480	9N5985-00-772-6676
1H6720-00-907-3600	C-30	80009	REPL		C-30BP	80009	7G6720-01-095-2205
1H6625-00-907-8347	DA-412/U	MIL	REPL		8404	70998	1H6625-01-150-1897
1H6625-00-907-8347	JN192W	00341	1387		N/A		
1H6625-00-907-8347	704-50	01365	REPL		8404	70998	1H6625-01-150-1897
1H6625-00-910-2583	1091	06481	1387		N/A		
1H6625-00-910-2583	1091	31922	1387		N/A		
9I5985-00-913-9842	K752C	28480	STD		K752C	28480	9I5985-00-913-9842
1H6130-00-915-1930	6522A	28480	REPL		UNDER REVIEW		
6G6625-00-916-3122	ST-213	12678	REPL		SPX-3031	88869	1H5950-01-040-0282
1H6625-00-916-3209	7008	00752	GA		N/A		
7Z6625-00-919-5008	205B1-2	90101	1387	1	N/A		
1H5985-00-919-8548	394A	28480	REPL		0874-9577	82316	&&5840-00-868-1287
1H5985-00-919-8548	9157607	18876	REPL		0874-9577	82316	&&5840-00-868-1287
1H6625-00-920-9927	19K1	98732	1387		N/A		
9N5985-00-921-3697	G-101	77327	STD		G-101	77327	9N5985-00-921-3697
1H4931-00-921-7357	C20PS	14135	STD		C20PS	14135	1H4931-00-921-7357
1H4931-00-921-7357	7911468	19200	REPL		C20PS	14135	1H4931-00-921-7357
1H6625-00-922-9296	010-0172-00	80009	GA		N/A		
1H6625-00-922-9296	141043-2	49956	GA		N/A		
1H6625-00-922-9296	6015	80009	GA		N/A		
&&6625-00-923-8947	N420C	11332	GA		N/A		
1H6625-00-925-0180	7091	12678	GA		N/A		
1H6625-00-930-1810	DA-412A/U	MIL	REPL		8404	70998	1H6625-01-150-1897
1H6625-00-930-1810	811152	70998	1387		N/A		
1H6625-00-930-1810	8401SPECIAL	70998	REPL		8404	70998	1H6625-01-150-1897

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX B

REFERENCE NIIN TO STANDARD EQUIPMENT

REFERENCE EQUIPMENT NSN	MODEL	FSCM	STATUS	NOTES	STANDARD EQUIPMENT MODEL	FSCM	NSN
1H6625-00-930-6836	32115258	93346	GA		N/A		
9N6625-00-931-8812	R486A	28480	GA		N/A		
1H6625-00-932-2016	1117B	28480	GA		N/A		
1H6625-00-932-7260	WG301A	49671	GA		N/A		
1H6625-00-932-7260	WG301A	79089	GA	2	N/A		
1H6625-00-932-7260	WG301A	86684	GA		N/A		
9N5950-00-933-7423	500-B	83008	REPL		W10MI3A	13850	9S6120-00-054-7794
9N6625-00-935-1331	RDA	14655	REPL		240C	12697	1H6625-00-585-4915
7Z5961-00-940-0449	XA-0640	00929	GA	1	N/A		
1H6625-00-943-2881	3143575	MIL	GA		N/A		
1H6625-00-943-2881	562807-000	56232	GA		N/A		
1H6625-00-943-2881	772011-2	96214	GA		N/A		
1H6625-00-947-7534	1433-N	24655	REPL		1433-9722	24655	1H6625-00-947-7534
1H6625-00-947-7534	1433-X	24655	REPL		1433-9722	24655	1H6625-00-947-7534
1H6625-00-947-7534	1433-9712	24655	REPL		1433-9722	24655	1H6625-00-947-7534
1H6625-00-947-7534	1433-9722	24655	STD		1433-9722	24655	1H6625-00-947-7534
1H6625-00-953-7537	1419-A	24655	REPL		1412-9410	24655	1H6625-00-465-6861
1H6625-00-953-7537	1419-9701	24655	REPL		1412-9410	24655	1H6625-00-465-6861
1H6625-00-953-9128	S910A	28480	1387	2	N/A		
9N5985-00-957-1860	355D	28480	STD		355D	28480	9N5985-00-957-1860
1H6625-00-961-0790	X101-S8	77327	REPL		X382A	28480	1H6625-00-602-2089
9N5985-00-965-6318	50-3	93459	REPL		8491A-003	28480	9N5985-00-167-0544
1R5895-00-967-4501	3045B-10	99899	REPL		3045C-10	99899	1R5985-00-604-8604
7Z6625-00-970-3682	920NA	98521	REPL		UNDER REVIEW		
1H6625-00-970-3685	371BNM	99899	STD		371BNM	99899	1H6625-00-970-3685
1H6625-00-970-3695	440A	28480	REPL		UNDER REVIEW		
1H6625-00-973-1151	613-M	77327	STD		613-M	77327	1H6625-00-973-1151
7Z6625-00-973-2189	6835	70998	REPL		8404	70998	1H6625-01-150-1897
1H6625-00-975-1359	1432-L	24655	REPL		1433-9706	24655	&&6625-00-235-6308
&&6625-00-975-9941	AV-50	01113	REPL		432-D	80138	9N5985-00-087-2547
1H6625-00-976-3868	12989REVD	13327	1387		N/A		
1H6625-00-976-3868	606A34	28480	1387		N/A		
1H6625-00-977-9051	32-0	80138	REPL		452-C	80138	9Y5985-00-712-8388

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX B

REFERENCE NIIN TO STANDARD EQUIPMENT

REFERENCE EQUIPMENT NSN	MODEL	FSCM	STATUS	NOTES	STANDARD EQUIPMENT MODEL	FSCM	NSN
1R6625-00-980-9302	P424A	28480	STD		P424A	28480	1R6625-00-980-9302
1H6625-00-981-3248	3040-20	99899	REPL		3040B-20	99899	1H5985-00-067-6750
1R6625-00-981-9518	R422A	28480	STD		R422A	28480	1R6625-00-981-9518
9Y6625-00-982-5256	CDA	14655	REPL		UNDER REVIEW		
9Y6625-00-982-5256	CDA-2	14655	REPL		UNDER REVIEW		
7Z6625-00-984-4731	205A1	90101	1387	1	N/A		
1H6625-00-987-3441	AV-75	01113	REPL		442-D	80138	9N5905-00-313-9064
9N5950-00-987-5601	W5MI3A	13850	STD		W5MI3A	13850	9N5950-00-987-5601
1H6130-00-990-8659	5015	98095	REPL		5015V	98095	1H6625-01-224-0215
1R5985-00-991-1013	QHB-2-30	12457	STD		QHB-2-30	12457	1R5985-00-991-1013
1H6625-00-992-3036	07048	00752	GA		N/A		
6A6625-00-992-3037	07006	12678	GA	1	N/A		
1H5985-00-993-1377	355C	28480	STD		355C	28480	1H5985-00-993-1377
1H6625-00-993-9085	X164A	00929	REPL		X382A	28480	1H6625-00-602-2089
1H6625-00-993-9085	215709	50040	REPL		X382A	28480	1H6625-00-602-2089
1H6625-00-994-6797	DA-177A/U	MIL	1387		N/A		
1H6625-00-994-6797	8201	70998	STD		8201	70998	1H6625-00-994-6797
1H6625-00-995-7464	11045A	28480	GA		N/A		
1H6625-00-999-0866	RT-8	12678	REPL		M-1012A	88869	1H6625-01-206-2974
9N5985-00-999-8095	2-3414-30	09992	STD		2-3414-30	09992	9N5985-00-999-8095
1H6625-01-003-6092	355C-001	28480	REPL		355C	28480	1H5985-00-993-1377
1H6625-01-003-6118	178-B	77327	REPL		J382A	28480	7G6625-00-679-0627
1H6625-01-008-2051	355D-001	28480	REPL		355D	28480	9N5985-00-957-1860
1H5985-01-008-2195	370-20	00443	1387		N/A		
7Z6625-01-009-6118	1346-9700	24655	REPL		850-CT2W	83332	NSNL
1H6625-01-010-0486	MC-601A	32421	GA		N/A		
1H6625-01-010-0736	MC-50018	32421	GA		N/A		
1H6625-01-010-1751	015-0057-02	80009	GA		N/A		
1H6625-01-010-1751	134	80009	GA		N/A		
1H6625-01-014-3463	2-30	93459	STD		2-30	93459	1H6625-01-014-3463
1H6625-01-014-3464	2-40	93459	STD		2-40	93459	1H6625-01-014-3464
1H6625-01-014-3465	2-50	93459	1387		N/A		
1H6625-01-015-2356	4M-6	93459	STD		4M-6	93459	1H6625-01-015-2356

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX B

REFERENCE NIIN TO STANDARD EQUIPMENT

REFERENCE EQUIPMENT NSN	MODEL	FSCM	STATUS	NOTES	STANDARD EQUIPMENT MODEL	FSCM	NSN
1H6625-01-015-2356	4779-6	99899	REPL		4M-6	93459	1H6625-01-015-2356
1H6625-01-015-2357	4779-3	99899	REPL		4M-3	93459	1H6625-LL-HHE-1799
1H6625-01-015-7423	80HRF	89536	GA		N/A		
1H6625-01-015-7661	22523	00213	1387		N/A		
1H5985-01-015-7687	4002B-30	99899	1387		N/A		
1H5935-01-016-6059	1081-0000-00	26805	GA		N/A		
1H5935-01-016-6060	21090	16179	GA		N/A		
1H6625-01-017-1238	012-0180-00	80009	GA		N/A		
1H6625-01-017-1239	10007A	28480	GA		N/A		
1H6625-01-017-1276	2-20	93459	STD		2-20	93459	1H6625-01-017-1276
1H6625-01-017-1277	2-6	93459	STD		2-6	93459	1H6625-01-017-1277
1H6625-01-017-1278	2-10	93459	STD		2-10	93459	1H6625-01-017-1278
1H6625-01-017-1279	757C-40	99899	1387		N/A		
1H6625-01-017-1281	162-B	77327	REPL		AU-65AMN	12457	1H6625-01-040-9528
1H6625-01-017-9126	10000A02	30669	GA		N/A		
1H6625-01-018-0932	F1403N	93459	1387		N/A		
1H6625-01-018-0934	4779-10	99899	REPL		4M-10	93459	9N5985-00-258-0123
1H6625-01-018-1206	440B	11332	GA		N/A		
1H6625-01-018-1207	K420D	11332	GA		N/A		
1H6625-01-018-1208	440B1	11332	GA		N/A		
1H6130-01-018-1226	1106	80009	GA		N/A		
1H6130-01-018-1226	1106-A	77327	GA		N/A		
1H6625-01-019-8685	S-501C/979	11332	GA		N/A		
1H6625-01-020-6032	2-3	93459	STD		2-3	93459	1H6625-01-020-6032
1H6625-01-021-6645	A420D	11332	GA		N/A		
6R4920-01-021-8513	1455-9706	24655	REPL		UNDER REVIEW		
&&5950-01-023-9857	0111T25SR	06049	REPL		P6161	80089	9N5950-00-645-1807
9N5985-01-024-3832	11692D	28480	STD		11692D	28480	9N5985-01-024-3832
1H5985-01-024-8193	8164	70998	STD		8164	70998	1H5985-01-024-8193
1H5985-01-025-3902	4609	99899	STD		4609	99899	1H5985-01-025-3902
9N6625-01-026-2335	4M-3-6-10	93459	STD		4M-3-6-10	93459	9N6625-01-026-2335
1H6625-01-028-2882	8484A	28480	GA		N/A		
1R4920-01-029-4624	S281A	28480	STD		S281A	28480	1R4920-01-029-4624

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX B

REFERENCE NIIN TO STANDARD EQUIPMENT

REFERENCE EQUIPMENT NSN	MODEL	FSCM	STATUS	NOTES	STANDARD EQUIPMENT MODEL	FSCM	NSN
1H6625-01-030-5505	BA-C-110C	00341	STD		BA-C-110C	00341	1H6625-01-030-5505
9N6625-01-031-1980	638	99899	STD		638	99899	9N6625-01-031-1980
9N6625-01-031-1981	V637	99899	STD		V637	99899	9N6625-01-031-1981
1H4935-01-031-2694	8491A-020	28480	STD		8491A-020	28480	1H4935-01-031-2694
7Z6625-01-031-8855	BHK-500-0.4M	85604	STD		BHK-500-0.4M	85604	7Z6625-01-031-8855
1H6625-01-032-4371	8401	70998	REPL		8404	70998	1H6625-01-150-1897
1H6625-01-033-4728	010-0264-01	80009	GA		N/A		
7Z6625-01-033-7479	DCR600-75B	49956	REPL		BHK-500-0.4M	85604	7Z6625-01-031-8855
1H6625-01-034-2216	JQE-150-15M	85604	REPL		DCR150-12B	49956	7Z6625-01-136-3178
1H5950-01-036-1977	IV-1-2M	83008	REPL		P6161	80089	9N5950-00-645-1807
1H5950-01-036-1982	VT2NE	44655	REPL		W5MT3A	13850	9N5950-00-987-5601
9N6625-01-036-2020	GM-318-C4	60674	STD		GM-318-C4	60674	9N6625-01-036-2020
9N6625-01-036-2020	GM-318-C4	95712	REPL		GM-318-C4	60674	9N6625-01-036-2020
7Z6625-01-036-2030	RE40-5M	89022	REPL		6266B	28480	9G6130-00-137-0167
1H6625-01-037-9435	N157B	00929	REPL		L20PS	14135	9Q6625-00-738-2716
1H6625-01-037-9437	108573-690	13973	GA		N/A		
1H6625-01-037-9437	91-24A	04901	GA		N/A		
1H6625-01-037-9747	8731	70998	1387		N/A		
1H6625-01-037-9747	8732	70998	1387		N/A		
1H6625-01-039-1277	98-00224	14031	GA		N/A		
1H6625-01-039-2258	SCR-300-3	89022	REPL		TCR-300S-3-1	89022	1H6625-LL-MME-4110
1H5985-01-039-2317	KU110L1	14135	1387		N/A		
1H5995-01-039-5216	319-5-000	00607	GA		N/A		
1H5935-01-039-5227	900-9803	82316	1387		N/A		
1H5935-01-039-5228	900-9703	82316	1387		N/A		
1H6625-01-039-5234	010-6053-03	80009	GA		N/A		
1H5935-01-039-5257	900-9801	82316	1387		N/A		
1H5985-01-039-5258	8491A-040	28480	REPL		2-40	93459	1H6625-01-014-3464
1H6625-01-039-5259	314	00443	STD		314	00443	1H6625-01-039-5259
1H6625-01-039-5260	765-6	99899	1387		24-6-34	93459	1H6625-LL-MME-8021
1H5985-01-039-5401	8736	70998	1387		N/A		
1H5985-01-039-5402	5-8000-75	94375	1387		N/A		
1H5985-01-039-5404	3041-10	99899	STD		3041-10	99899	1H5985-01-039-5404

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX B

REFERENCE NIIN TO STANDARD EQUIPMENT

REFERENCE EQUIPMENT NSN	MODEL	FSCM	STATUS	NOTES	STANDARD EQUIPMENT MODEL	FSCM	NSN
1H5895-01-039-5460	8037	04423	GA		N/A		
1H6625-01-039-6571	1267-9702	24655	REPL		TCR-300S-3-1	89022	1H6625-LL-MHE-4110
1H5990-01-040-0193	319-2-000	00607	GA		N/A		
1H6625-01-040-0194	319-3-000	00607	GA		N/A		
1H5950-01-040-0282	SPX-3031	12678	REPL		SPX-3031	88869	1H5950-01-040-0282
1H5950-01-040-0282	SPX-3031	88869	STD		SPX-3031	88869	1H5950-01-040-0282
1H6625-01-040-0304	PDA-6	01113	GA		N/A		
1H5935-01-040-0305	PGT	01113	GA		N/A		
1H6625-01-040-2313	1591-9700 LHA	03950	GA		N/A		
1H6625-01-040-2581	6112A	28480	REPL		5015V	98095	1H6625-01-224-0215
1H6625-01-040-9511	10850B	50423	GA		N/A		
1H6625-01-040-9511	82RF	89536	GA		N/A		
1H6625-01-040-9528	AU-65AMN	12457	STD		AU-65AMN	12457	1H6625-01-040-9528
1H6625-01-040-9528	AU-65A5-NCM	12457	REPL		AU-65AMN	12457	1H6625-01-040-9528
1H6130-01-040-9808	DCR40-25B	49956	STD		DCR40-25B	49956	1H6130-01-040-9808
1H6130-01-040-9810	DCR150-10A	49956	REPL		DCR150-12B	49956	7Z6625-01-136-3178
&&6130-01-040-9811	S30S	31791	REPL		S11PS	14135	9N5985-00-439-3536
1H6130-01-040-9811	6259B-026	28480	1387		N/A		
1H6130-01-041-3336	SL-36-2M	96762	REPL		6266B	28480	9G6130-00-137-0167
9N5985-01-041-8132	4016B-10	99899	REPL		4016D-10	99899	9N5985-01-041-8132
9N5985-01-041-8132	4016D-10	99899	STD		4016D-10	99899	9N5985-01-041-8132
&&6625-01-042-3326	817-B	54294	REPL		1433-9729	24655	1H6625-01-205-0820
9N6625-01-046-7045	8470B	28480	REPL	1	8470A	28480	1H6625-00-424-4334
1H5985-01-048-3901	X4420-A-10	77327	REPL		3045C-10	99899	1R5985-00-604-8604
1H6625-01-049-8460	10007B	28480	GA		N/A		
9N6625-01-055-6973	11679A	28480	GA		N/A		
1H6625-01-057-9035	41227	65092	GA		N/A		
1R5985-01-059-3436	3292-1	99899	1387		N/A		
1H5985-01-060-3476	DA-412B/U	MIL	REPL		8404	70998	1H6625-01-150-1897
1H5985-01-060-3476	DA-91/U	MIL	1387		N/A		
1H5985-01-060-3476	T-2098	12598	REPL		8404	70998	1H6625-01-150-1897
1H5985-01-060-3476	13371	12598	1387		N/A		
&&6130-01-062-6739	6294A	28480	STD		6294A	28480	&&6130-01-062-6739

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX B

REFERENCE NIIN TO STANDARD EQUIPMENT

REFERENCE EQUIPMENT NSN	MODEL	FSCM	STATUS	NOTES	STANDARD EQUIPMENT MODEL	FSCM	NSN
9N6625-01-063-9297	AF-117A-69-34	93459	STD		AF-117A-69-34	93459	9N6625-01-063-9297
9N5985-01-064-2513	2001-6113-00	16179	STD		2001-6113-00	16179	9N5985-01-064-2513
1H6625-01-065-5289	CB-B13	00929	REPL		3041-10	99899	1H5985-01-039-5404
1H6625-01-065-5289	3003-10	99899	REPL		3043B-10	99899	1H6625-01-065-5289
1H6625-01-065-5289	3043B-10	99899	STD		3043B-10	99899	1H6625-01-065-5289
1H6625-01-065-5290	CB-B14	00929	REPL		3042B-10	99899	9N5985-00-465-8112
1H6625-01-065-5291	CB-B15	00929	REPL		3043B-10	99899	1H6625-01-065-5289
1H6625-01-065-5292	CB-B16	00929	REPL		3004-10	99899	9N5985-00-788-6962
1H6625-01-065-5307	HL-160A	12110	REPL		C20PS	14135	1H4931-00-921-7357
1H6625-01-065-5308	L-141B	12110	REPL		L20PS	14135	906625-00-738-2716
1H6625-01-065-5308	42213	12110	GA		N/A		
1H6625-01-065-5341	DA-91A/U	MIL	REPL		8404	70998	1H6625-01-150-1897
1H6625-01-065-8182	SL-140	12110	REPL		S11PS	14135	9N5985-00-439-3536
1H6625-01-065-8183	XL-140	12110	REPL		CX20PS	14135	9N5985-00-145-3514
1H5985-01-065-8185	553-10	93459	REPL		8491A-010	28480	9N5985-00-865-0108
1H5985-01-065-8225	CB-B12	00929	REPL		3000-10	99899	9N5985-00-816-4287
1H6625-01-065-8227	160B-150FN	54778	REPL		8135	70998	9N6625-00-773-7311
1H6625-01-065-8251	TO-36-5M	89022	REPL		6266B	28480	9G6130-00-137-0167
1H6625-01-065-8270	627	93459	GA		N/A		
1H5895-01-066-6943	OD-1119 A/B B/T E	96341	1387		N/A		
1H6625-01-067-0413	8478B-H27	28480	GA		N/A		
1H6625-01-067-0413	8478B-011-H27	28480	GA		N/A		
1H6625-01-067-0480	553-20	93459	REPL		8491A-020	28480	1H4935-01-031-2694
1H6625-01-067-0772	015-0135-01	80009	GA		N/A		
1H5950-01-067-3203	RT-20A	12678	REPL		RT-20A	88869	1H5950-01-067-3203
1H5950-01-067-3203	RT-20A	88869	STD		RT-20A	88869	1H5950-01-067-3203
1H5950-01-067-3204	RT-30	12678	REPL		RT-30A	88869	1H6625-LL-HHE-4050
1H6625-01-067-3271	H-4065B	00929	REPL		WE-0035	00929	1H6625-01-067-3271
1H6625-01-067-3271	WE-0035	00929	STD		WE-0035	00929	1H6625-01-067-3271
1H6625-01-067-3275	C1580	80103	REPL		TCB-300S-3-1	89022	1H6625-LL-HHE-4110
1H6130-01-067-3777	6296A	28480	STD		6296A	28480	1H6130-01-067-3777
1H6625-01-069-2232	30372	00443	1387		N/A		
1H5985-01-069-2318	X301A	13047	STD		X301A	13047	1H5985-01-069-2318

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX B

REFERENCE NIIN TO STANDARD EQUIPMENT

REFERENCE EQUIPMENT NSN	MODEL	FSCM	STATUS	NOTES	STANDARD EQUIPMENT MODEL	FSCM	NSN
1H6625-01-079-0232	33000D-H21	28480	1387		N/A		
1H5895-01-079-0537	3122	99899	STD		3122	99899	1H5895-01-079-0537
1H5985-01-081-7855	3222-16	99899	STD		3222-16	99899	1H5985-01-081-7855
7G6720-01-095-2205	C-30BP	80009	STD		C-30BP	80009	7G6720-01-095-2205
1H6625-01-095-8843	K4240C	11332	GA		N/A		
1H6625-01-095-8844	A4240C	11332	GA		N/A		
1H6625-01-095-8844	NHA4017C/1	03950	GA		N/A		
1H6625-01-095-8845	X4240C	11332	GA		N/A		
1H5985-01-096-6705	4055-30	99899	STD		4055-30	99899	1H5985-01-096-6705
7Z5985-01-096-6835	210-3	93459	REPL		8491A-003	28480	9N5985-00-167-0544
1H5985-01-100-1668	4055-20	99899	STD		4055-20	99899	1H5985-01-100-1668
&&6720-01-104-3402	197B	28480	STD		197B	28480	&&6720-01-104-3402
&&6625-01-112-5768	P6106	80009	GA		N/A		
1H6625-01-117-8746	UR-102	09449	REPL		102AC46-1E	01456	1H6625-00-178-0008
7Z5985-01-135-0012	4222-16	99899	REPL		3222-16	99899	1H5985-01-081-7855
1H6625-01-136-3174	9211-1303	28480	GA		N/A		
7Z6625-01-136-3178	DCR150-12B	49956	STD		DCR150-12B	49956	7Z6625-01-136-3178
7Z6625-01-136-3250	153B/403V	25965	REPL		153B/403SD-001	25965	7G6625-01-197-9866
7Z6625-01-136-3250	153B/403VTE	03950	REPL		153B/403SD-001	25965	7G6625-01-197-9866
1H6625-01-136-8476	TSTP27	25647	GA		N/A		
7Z6625-01-138-0293	3744A	28480	GA		N/A		
1H6930-01-140-4985	1425-4	93459	STD		1425-4	93459	1H6930-01-140-4985
1H6625-01-142-5447	A400 BC	16786	STD		A400 BC	16786	1H6625-01-142-5447
7Z6625-01-145-2809	C-30B	80009	REPL		C-30BP	80009	7G6720-01-095-2205
1H6625-01-145-2810	8890-300	70998	REPL		B-1576	91161	1H5985-00-792-9928
1H6625-01-150-1897	8404	70998	STD		8404	70998	1H6625-01-150-1897
1H5985-01-152-4077	DPTC-25KFM	91161	STD		DPTC-25KFM	91161	1H5985-01-152-4077
1H5985-01-152-4078	DPTC-50KFM	91161	STD		DPTC-50KFM	91161	1H5985-01-152-4078
7G6625-01-154-3807	8100-25	25284	1387		N/A		
1H6625-01-160-5093	1353	73386	REPL		1412-9410	24655	1H6625-00-465-6861
1H6625-01-163-6679	4437A	28480	1387		850-CT2W	83332	NSNL
7Z5985-01-166-3721	8894	70998	REPL		B-1576	91161	1H5985-00-792-9928
1H6625-01-178-9497	LQ-415	80103	STD		LQ-415	80103	1H6625-01-178-9497

Source: https://assist.dla.mil -- Downloaded: 202610-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX B

REFERENCE NIIN TO STANDARD EQUIPMENT

REFERENCE EQUIPMENT NSN	MODEL	FSCM	STATUS NOTES	STANDARD EQUIPMENT MODEL	FSCM	NSN
1H6625-01-194-4013	N443	11332	GA	N/A		
7Z5985-01-196-7882	8894-300	70998	REPL	B-1576	91161	1H5985-00-792-9928
7G6625-01-197-9866	153B/403SD-001	25965	STD	153B/403SD-001	25965	7G6625-01-197-9866
1H5985-01-203-5192	N9412-20	09992	STD	N9412-20	09992	1H5985-01-203-5192
1H6625-01-205-0820	1433-9729	24655	STD	1433-9729	24655	1H6625-01-205-0820
1H6625-01-205-1224	R-1011B	94990	STD	R-1011B	94990	1H6625-01-205-1224
1H6625-01-206-2974	M-1012A	12678	REPL	M-1012A	88869	1H6625-01-206-2974
1H6625-01-206-2974	M-1012A	88869	STD	M-1012A	88869	1H6625-01-206-2974
1H6625-01-224-0215	5015V	98095	STD	5015V	98095	1H6625-01-224-0215
7Z6625-01-886-1955	478A	28480	GA	N/A		

Source: https://assist.dla.mil -- Downloaded: 202610-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX C

STANDARD EQUIPMENT TO REFERENCE EQUIPMENT

STANDARD EQUIPMENT	FSCM	GMG	REFERENCE EQUIPMENT	FSCM
AF-117A-69-34	93459	AT4GN	AF-117-69-34	93459
		AT4GN	AF-117A-69-34	93459
		AT4GN	704-69	99899
		AT4GN	705-99	99899
		AT4GN	712	99899
AU-65AMN	12457	AT6MN	AJ-210N	00929
		AT6MN	AU-65AMN	12457
		AT6MN	AU-65A5-NCM	12457
		AT6MN	162-B	77327
A400 BC	16786	FL1EJ	A400 BC	16786
B-1576	91161	DL1EY	B-1576	91161
		DL1EY	DA-242/U	MIL
		DL1EY	DA-242A/U	MIL
		DL1EY	8890	70998
		DL1EY	8890-300	70998
		DL1EY	8894	70998
		DL1EY	8894-010	70998
		DL1EY	8894-300	70998
BA-C-110C	00341	HN1FN	BA-C-110C	00341
		HN1FN	H638A	00929
		HN1FN	643	99899
BHK-500-0.4M	85604	PS1VN	BHK-500-0.4M	85604
		PS1VN	DCR600-75B	49956
		PS1VN	UHR-220	88865
		PS1VN	10382656	00000
		PS1VN	407D	89536
		PS1VN	6209B	28480
		PS1VN	712B	28480
		PS1VN	712C	28480
C-30BP	80009	CS1NN	C-12	80009
		CS1NN	C-30	80009
		CS1NN	C-30A	80009
		CS1NN	C-30B	80009

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX C

STANDARD EQUIPMENT TO REFERENCE EQUIPMENT

STANDARD EQUIPMENT	FSCM	GMG	REFERENCE EQUIPMENT	FSCM
C-30BP - CONTINUED		CS1NN	C-30BP	80009
		CS1NN	CR9	47904
		CS1NN	196A	28480
		CS1NN	453-1	18778
C-59AP	80009	CS1AA	C-59AP	80009
CX20PS	14135	SR1YN	CX20PS	14135
		SR1YN	CX90S	31791
		SR1YN	D44X15	06424
		SR1YN	XL-140	12110
C20PS	14135	SR1TN	C20PS	14135
		SR1TN	C60-S	31791
		SR1TN	D44C15	06424
		SR1TN	HL-160A	12110
		SR1TN	7911468	19200
DCR150-12B	49956	PS1MN	DCR150-10A	49956
		PS1MN	DCR150-12B	49956
		PS1MN	JQE-150-1	85604
		PS1MN	JQE-150-15M	85604
		PS1MN	JQE-150-3.5M	85604
		PS1MN	SM-160-2AM	85604
		PS1MN	SM-160-2M	85604
DCR40-25B	49956	PS1BN	DCR40-20A	49956
		PS1BN	DCR40-25B	49956
		PS1BN	QR36-15A	49956
DPTC-25KFM	91161	DL1AA	DA-484/URT	MIL
		DL1AA	DPTC-25KFM	91161
DPTC-50KFM	91161	DL1AN	DA-507/URT	MIL
		DL1AN	DPTC-50KFM	91161
G-101	77327	AI7NN	G-101	77327
		AI7NN	G375A	28480
		AI7NN	G382A	28480
GM-318-C4	60674	DC1WN	GM-318-C4	60674
		DC1WN	GM-318-C4	95712

Source: https://assist.dla.mil -- Downloaded: 202640-26T13:40Z
Check the source to verify that this is the currenversion before use.

APPENDIX C

STANDARD EQUIPMENT TO REFERENCE EQUIPMENT

STANDARD EQUIPMENT	FSCM	GMG	REFERENCE EQUIPMENT	FSCM
GM-318-C4 - CONTINUED		DC1WN	316C4	95712
		DC1WN	318C4	95712
G281A	28480	AD3FN	G281A	28480
		AD3FN	248	06424
		AD3FN	54-C1	06424
		AD3FN	613A	99899
JQE-36-3M	85604	PS1AN	JQE-36-3M	85604
		PS1AN	PP-4105/U	MIL
		PS1AN	21A	76526
		PS1AN	6216A	28480
J281A	28480	AD3MN	J281A	28480
		AD3MN	356-A	77327
J382A	28480	AT7AA	J382A	28480
		AT7AA	178-B	77327
K362A	28480	FL1JN	K362A	28480
K382A	28480	AT7AI	K382A	28480
K422A	28480	DE3NN	K422A	28480
		DE3NN	K422A-001	28480
K752C	28480	DC2AM	K752C	28480
LA-60N	00929	FL2YN	LA-60N	00929
		FL2YN	LT-6000	01341
LQ-415	80103	PS1RN	LP-415A-FM	80103
		PS1RN	LQ-415	80103
L20PS	14135	SR1FN	D44L15	06424
		SR1FN	L-141B	12110
		SR1FN	L15S	31791
		SR1FN	L20PS	14135
		SR1FN	N157B	00929
M-1012A	88869	TR4JN	M-1012A	12678
		TR4JN	M-1012A	88869
		TR4JN	M-1012A-AC	88869
		TR4JN	RT-8	12678
		TR4JN	RT-9	12678

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX C

STANDARD EQUIPMENT TO REFERENCE EQUIPMENT

STANDARD EQUIPMENT	FSCM	GMG	REFERENCE EQUIPMENT	FSCM
M2G3	13850	TR1MN	M2G3	13850
M5	13850	TR1FN	M5	13850
M602	57646	AT4KN	CN-476/U	MIL
		AT4KN	M546	57646
		AT4KN	M602	57646
N9412-20	09992	AT1NB	AC-20N	00929
		AT1NB	N9412-20	09992
		AT1NB	1290015P4	94117
P281B	28480	AD3UN	P281B	28480
P382A	28480	AT7AM	P382A	28480
P424A	28480	DE3AN	P424A	28480
P6161	80089	TR3AN	EJ-201V	83008
		TR3AN	EJ-401V	83008
		TR3AN	IV-1-2M	83008
		TR3AN	P6161	80089
		TR3AN	P6411A	80089
		TR3AN	0111T25SR	06049
		TR3AN	70412	06049
		TR3AN	91092-22	06049
QHB-2-30	12457	CQ1NN	QH-2-30	12457
		CQ1NN	QHB-2-30	12457
R-1011B	94990	PS1BY	R-1011AA	94990
		PS1BY	R-1011B	94990
		PS1BY	S1303-A1	94990
RT-20A	88869	TR4TJ	CRT-3	12678
		TR4TJ	RT-2	12678
		TR4TJ	RT-20A	12678
		TR4TJ	RT-20A	88869
RT-30A	88869	TR4TT	A404-7	12868
		TR4TT	RB-503C-S1177	07342
		TR4TT	RB-503T	07342
		TR4TT	RT-30	12678
		TR4TT	RT-30A	12678

Source: https://assist.dla.mil -- Downloaded: 202640-26T13:40Z
Check the source to verify that this is the currenversion before use.

APPENDIX C

STANDARD EQUIPMENT TO REFERENCE EQUIPMENT

STANDARD EQUIPMENT	FSCM	GMG	REFERENCE EQUIPMENT	FSCM
RT-30A - CONTINUED		TR4TT	RT-30A	88869
		TR4TT	RT-7	12678
		TR4TT	SC-58	88869
		TR4TT	TF-384/U	MIL
R362A	28480	FL2WG	R362A	28480
R382A	28480	AT7AY	R382A	28480
R422A	28480	DE3YN	R422A	28480
R752C	28480	DC2AI	R752C	28480
SPX-3031	88869	TR3YN	SPX-3031	12678
		TR3YN	SPX-3031	88869
		TR3YN	SI-200A	12678
		TR3YN	SI-200F	12678
		TR3YN	SI-213	12678
		TR3YN	SI-248A	12678
SI-100	88869	TR3NN	SI-100	12678
		TR3NN	ST-100	88869
		TR3NN	SI-100A	12678
		TR3NN	ST-100A	88869
		TR3NN	578-BS5	24655
S11PS	14135	SR1MN	D44S15	06424
		SR1MN	SL-140	12110
		SR1MN	S10P	14135
		SR1MN	S102LCI	14135
		SR1MN	S11PS	14135
		SR1MN	S30S	31791
S281A	28480	AD3CN	S-175	11787
		AD3CN	S281A	28480
		AD3CN	614A	99899
S382C	28480	AT7NA	S382C	28480
S501B	00929	TM2JN	S501B	00929
TCR-300S-3-1	89022	PS1TN	C1580	80103
		PS1TN	HV300-1	89022
		PS1TN	HV300-1.5M	89022

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX C

STANDARD EQUIPMENT TO REFERENCE EQUIPMENT

STANDARD EQUIPMENT	FSCM	GMG	REFERENCE EQUIPMENT	FSCM
TCR-300S-3-1 - CONTINUED		PS1TN	SCR-300-2	89022
		PS1TN	SCR-300-3	89022
		PS1TN	TCR-300S-3-1	89022
		PS1TN	1267-9702	24655
TDR-29011	87864	AD3JN	TDR-29011	87864
		AD3JN	TDR-29061-1	87864
UNDER REVIEW		CP1U3	CDA	14655
			CDA-2	14655
			CDA-5	14655
		CP1U2	CDB	14655
			CDB-3	14655
			CDB-5	14655
		CP1U1	CDC	14655
			CDC-3	14655
			CDC-5	14655
		TM2UR	MA-648A	96341
		ML1UR	MA-8F208	96341
			MX-8712/U	MIL
			1454-A	24655
			1454-9701	24655
			1455-A	24655
			1455-B	24655
		DR3UR	1455-9706	24655
			34B1	06424
		DE4UR	440A	28480
		PS1UR	6207B	28480
		PS1UR	6522A	28480
			920NA	98521
V637	99899	HN1YN	V637	99899
WE-0035	00929	DL2FN	H-4065B	00929
		DL2FN	WE-0035	00929
WF-0025	00929	DL2AN	DA-145/U	MIL
		DL2AN	WF-0025	00929

Source: https://assist.dla.mil -- Downloaded: 202610-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX C

STANDARD EQUIPMENT TO REFERENCE EQUIPMENT

STANDARD EQUIPMENT	FSCM	GMG	REFERENCE EQUIPMENT	FSCM
WF-0050	00929	DL2MN	B4063	00929
		DL2MN	DA-148/U	MIL
		DL2MN	TS-231/AP	MIL
		DL2MN	TS-231A/AP	MIL
		DL2MN	TS-231B/AP	MIL
		DL2MN	WF-0050	00929
WF-0055	00929	DL2YN	DA-146/U	MIL
		DL2YN	WF-0055	00929
W10G3M	13850	TR1TT	W10G3M	13850
W10HG3M	13850	TR1YN	W10HG3M	13850
		TR1YN	217B-T3	58474
W10MT3A	13850	TR1AN	E1010VA	83008
		TR1AN	TF-455/U	MIL
		TR1AN	W10HMT3	13850
		TR1AN	W10MT	13850
		TR1AN	W10MT3	13850
		TR1AN	W10MT3A	13850
		TR1AN	W8MT3VM	13850
		TR1AN	116B	58474
		TR1AN	3PN1010	83008
		TR1AN	500-B	83008
W5G3M	13850	TR1TJ	W5G3M	13850
W5MT3A	13850	TR1AA	CN-16/U	MIL
		TR1AA	CN-16A/U	MIL
		TR1AA	CN-16B/U	MIL
		TR1AA	UC1M	58474
		TR1AA	UC1MB	58474
		TR1AA	VT2NE	44655
		TR1AA	VT8GC	44655
		TR1AA	W2MT	13850
		TR1AA	W2MT3	13850
		TR1AA	W5MT	13850
		TR1AA	W5MT3	13850

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX C

STANDARD EQUIPMENT TO REFERENCE EQUIPMENT

STANDARD EQUIPMENT	FSCM	GMG	REFERENCE EQUIPMENT	FSCM
W5MT3A - CONTINUED		TR1AA	W5MT3A	13850
		TR1AA	3PNT51B	83008
		TR1AA	3PN501B	83008
		TR1AA	6855	83008
X281A	28480	AD3IN	UG-1053/U	MIL
		AD3IN	X281A	28480
		AD3IN	X601B	00929
		AD3IN	354-C	77327
X301A	13047	TM2IN	X301A	13047
		TM2IN	X501B	00929
		TM2IN	X501C	00929
		TM2IN	X910B	28480
X382A	28480	AT7AF	X101-68	77327
		AT7AF	X164A	00929
		AT7AF	X382A	28480
		AT7AF	195-B	77327
		AT7AF	215709	50040
		AT7AF	7907413	18876
		AT7AF	7907413	19200
		AT7AF	7909033	18876
X752C	28480	DC2AF	X610C	00929
		DC2AF	X752C	28480
		DC2AF	45X1-10	99899
0874-9099	82316	AD1NN	0874-9099	24655
		AD1NN	0874-9099	82316
0874-9577	82316	AT6IN	CN-608A/U	MIL
		AT6IN	0874-957	82316
		AT6IN	0874-9577	24655
		AT6IN	0874-9577	82316
		AT6IN	394A	28480
		AT6IN	874-GA	24655
		AT6IN	874-GAL	24655
		AT6IN	9157607	18876

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX C

STANDARD EQUIPMENT TO REFERENCE EQUIPMENT

STANDARD EQUIPMENT	FSCM	GMG	REFERENCE EQUIPMENT	FSCM
1/432D	80138	AT4DN	1/432D	80138
102AC46-1E	01456	AD3QN	RAM-230A	09449
		AD3QN	WR-102	09449
		AD3QN	W40-NC	06351
		AD3QN	W40-NCM	06351
		AD3QN	102AC46-1E	01456
		AD3QN	3108	15305
10514A	28480	MX1NN	CV-2343/U	MIL
		MX1NN	10514A	28480
		MX1NN	10658140	18876
		MX1NN	1124147	MIL
11692D	28480	DC1NN	11692D	28480
		DC1NN	779D	28480
1412-9410	24655	CP1MN	TS-671/U	MIL
		CP1MN	1353	73386
		CP1MN	1412-9410	24655
		CP1MN	1419-A	24655
		CP1MN	1419-B	24655
		CP1MN	1419-9701	24655
		CP1MN	1419-9702	24655
		CP1MN	1423-9801	24655
1425-4	93459	TM1MN	11290180	17773
		TM1MN	1224-4	93459
		TM1MN	1425-4	93459
		TM1MN	370BNM	99899
		TM1MN	375NM	99899
		TM1MN	535MN	93459
1433-9704	24655	RE1GF	1432-J	24655
		RE1GF	1433-J	24655
		RE1GF	1433-9704	24655
1433-9706	24655	RE1KJ	1432-L	24655
		RE1KJ	1433-L	24655
		RE1KJ	1433-9706	24655

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX C

STANDARD EQUIPMENT TO REFERENCE EQUIPMENT

STANDARD EQUIPMENT	FSCM	GMG	REFERENCE EQUIPMENT	FSCM
1433-9714	24655	RE1GM	1432-M	24655
		RE1GM	1433-M	24655
		RE1GM	1433-9714	24655
1433-9722	24655	RE1DN	MX-3993/U	MIL
		RE1DN	1432-K	24655
		RE1DN	1432-N	24655
		RE1DN	1432-X	24655
		RE1DN	1432-9724	24655
		RE1DN	1433-K	24655
		RE1DN	1433-N	24655
		RE1DN	1433-X	24655
		RE1DN	1433-9712	24655
		RE1DN	1433-9722	24655
1433-9724	24655	RE1GY	RDC	14655
		RE1GY	TS-672/U	MIL
		RE1GY	1433-B	24655
		RE1GY	1433-9724	24655
1433-9726	24655	RE1KT	1432-P	24655
		RE1KT	1432-9716	24655
		RE1KT	1433-P	24655
		RE1KT	1433-Z	24655
		RE1KT	1433-9716	24655
		RE1KT	1433-9726	24655
		RE1KT	8616453	18876
1433-9729	24655	RE1AN	1432-T	24655
		RE1AN	1432-9720	24655
		RE1AN	1433-T	24655
		RE1AN	1433-U	24655
		RE1AN	1433-W	24655
		RE1AN	1433-9700	24655
		RE1AN	1433-9710	24655
		RE1AN	1433-9720	24655
		RE1AN	1433-9729	24655

Source: https://assist.dla.mil -- Downloaded: 202610-26T13:40Z
Check the source to verify that this is the currentversion before use.

APPENDIX C

STANDARD EQUIPMENT TO REFERENCE EQUIPMENT

STANDARD EQUIPMENT	FSCM	GMG	REFERENCE EQUIPMENT	FSCM
1433-9729 - CONTINUED		RE1AN	817-B	54294
1433-9731	24655	RE1DY	1433-G	24655
		RE1DY	1433-9731	24655
		RE1DY	1434-G	24655
		RE1DY	1434-9707	24655
1491-9704	24655	LN1NN	1490-B	24655
		LN1NN	1490-F	24655
		LN1NN	1491-D	24655
		LN1NN	1491-9704	24655
		LN1NN	7907319	00000
1506A	93459	DP1NN	1506A	93459
153B/403SD-001	25965	CF1NN	FCR100	49956
		CF1NN	153B/403SD-001	25965
		CF1NN	153B/403V	25965
		CF1NN	153B/403VIE	03950
1571-9831	13850	RACAA	100Q	24655
		RACAA	150S	49956
		RACAA	1570-ALS-15	13850
		RACAA	1571-AL	13850
		RACAA	1571-AL	24655
		RACAA	1571-9831	13850
		RACAA	1581-AL	24655
197B	28480	CS1AB	197A	28480
		CS1AB	197B	28480
2-10	93459	AT1JN	2-10	93459
		AT1JN	5779-10	99899
2-20	93459	AT1NY	AC-10N	00929
		AT1NY	2-20	93459
		AT1NY	5779-20	99899
2-3	93459	AT1AM	2-3	93459
		AT1AM	5779-3	99899
2-30	93459	AT1SN	AD-30N	00929
		AT1SN	2-30	93459

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX C

STANDARD EQUIPMENT TO REFERENCE EQUIPMENT

STANDARD EQUIPMENT	FSCM	GMG	REFERENCE EQUIPMENT	FSCM
2-30 - *CONTINUED*		AT1SN	30-N	00929
		AT1SN	50-30	93459
		AT1SN	8491A-030	28480
2-3414-30	09992	AT6FN	AU-10	12457
		AT6FN	AU-10A	12457
		AT6FN	2-3414-30	09992
2-40	93459	AT1WN	AD-40N	00929
		AT1WN	2-40	93459
		AT1WN	50-40	93459
		AT1WN	8491A-040	28480
2-6	93459	AT1EY	2-6	93459
		AT1EY	5779-6	99899
2001-6113-00	16179	TM1TJ	2001-6113-00	16179
		TM1TJ	20020P	16179
2002-6113-00	16179	TM1TT	2002-6113-00	16179
		TM1TT	20020J	16179
210A-3	93459	AT1AB	AC-03N	00929
		AT1AB	210A-3	93459
214	00443	DE5AA	S485A	28480
		DE5AA	214	00443
24-6-34	93459	AT1AC	24-6-34	93459
240C	12697	RE1GT	PC92350007-1	38597
		RE1GT	RDA	14655
		RE1GT	RDB	14655
		RE1GT	240C	12697
		RE1GT	7907234	18876
3000-10	99899	DC1AA	CB-B12	00929
		DC1AA	3000-10	99899
3002-20	99899	DC1JM	3002-20	99899
3003-20	99899	DC1JQ	3003-20	99899
3004-10	99899	DC1AM	CB-B16	00929
		DC1AM	3004-10	99899
3004-20	99899	DC1JT	3004-20	99899

Source: https://assist.dla.mil -- Downloaded: 202640-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX C

STANDARD EQUIPMENT TO REFERENCE EQUIPMENT

STANDARD EQUIPMENT	FSCM	GMG	REFERENCE EQUIPMENT	FSCM
3040B-20	99899	DC1JC	DC-122	12598
		DC1JC	V4420-20	77327
		DC1JC	3000-20	99899
		DC1JC	3040-20	99899
		DC1JC	3040B-20	99899
3041-10	99899	DC1AC	CB-B13	00929
		DC1AC	3001-10	99899
		DC1AC	3041-10	99899
3041-20	99899	DC1JF	3041-20	99899
3042B-10	99899	DC1AF	CB-B14	00929
		DC1AF	3002-10	99899
		DC1AF	3042B-10	99899
3043B-10	99899	DC1AJ	CB-B15	00929
		DC1AJ	3003-10	99899
		DC1AJ	3043B-10	99899
3043B-30	99899	DC1SA	S4420-30	77327
		DC1SA	3043B-30	99899
3045C-10	99899	DC1AT	X4420-A-10	77327
		DC1AT	3045B-10	99899
		DC1AT	3045C-10	99899
3060-20	99899	DC1JA	3060-20	99899
3122	99899	DE1NN	3122	99899
314	00443	DE5AB	G485B	28480
		DE5AB	314	00443
		DE5AB	33C2	06424
		DE5AB	34C1	06424
		DE5AB	513	99899
3202	88865	FL4TN	3202	88865
3202B-10	99899	DC1AQ	3202B-10	99899
3222-16	99899	DC1EN	3222-16	99899
		DC1EN	4222-16	99899
355C	28480	AT4AN	AT-200-SR	12598
		AT4AN	30-0	80138

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX C

STANDARD EQUIPMENT TO REFERENCE EQUIPMENT

STANDARD EQUIPMENT	FSCM	GMG	REFERENCE EQUIPMENT	FSCM
355C - CONTINUED		AT4AN	355A	28480
		AT4AN	355C	28480
		AT4AN	355C-C08	28480
		AT4AN	355C-001	28480
355D	28480	AT4UN	AT-201-SR	12598
		AT4UN	355B	28480
		AT4UN	355D	28480
		AT4UN	355D-C08	28480
		AT4UN	355D-001	28480
		AT4UN	464-A	80138
360A	28480	FL2AN	360A	28480
360B	28480	FL2FN	360B	28480
360C	28480	FL2MN	360C	28480
360D	28480	FL2TN	360D	28480
371BNM	99899	TM1YN	DA-366/U	MIL
		TM1YN	2901	27834
		TM1YN	342C554H02	79500
		TM1YN	342C554H02	97942
		TM1YN	371BNM	99899
		TM1YN	371NM	99899
3750	88865	FL4JN	330B	88865
		FL4JN	335	88865
		FL4JN	3750	88865
376BNF	99899	TM1FN	376BNF	99899
		TM1FN	376NF	99899
4M-10	93459	AT1JY	4M-10	93459
		AT1JY	4779-10	99899
4M-3	93459	AT1AT	4M-3	93459
		AT1AT	4779-3	99899
4M-3-6-10	93459	AT2NN	4M-3-6-10	93459
		AT2NN	4779-3-6-10	99899
4M-6	93459	AT1EN	292-6	34078
		AT1EN	4M-6	93459

Source: https://assist.dla.mil -- Downloaded: 202640-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX C

STANDARD EQUIPMENT TO REFERENCE EQUIPMENT

STANDARD EQUIPMENT	FSCM	GMG	REFERENCE EQUIPMENT	FSCM
4M-6 - CONTINUED		AT1EN	4779-6	99899
4016D-10	99899	DC1AY	4016-10	99899
		DC1AY	4016B-10	99899
		DC1AY	4016D-10	99899
4055-10	99899	DC1AW	4055-10	99899
4055-20	99899	DC1JW	4055-20	99899
4055-30	99899	DC1SN	4055-30	99899
407655	80006	FL3NN	407655	80006
423A	28480	DE2AA	CR-133-N	12598
		DE2AA	XB1000	00929
		DE2AA	XD-3A	04423
		DE2AA	1001	03782
		DE2AA	420A	28480
		DE2AA	420B	28480
		DE2AA	423A	28480
		DE2AA	8470A-012	28480
		DE2AA	8470B-012	28480
432-D	80138	AT4NA	AV-50	01113
		AT4NA	GA810K	26512
		AT4NA	RFB-552-50	14140
		AT4NA	300	80138
		AT4NA	432-D	80138
		AT4NA	432-D-J	80138
4375G	99899	TM1WP	2328	15305
		TM1WP	4375G	99899
		TM1WP	4520-2	15305
442-D	80138	AT4NN	AV-75	01113
		AT4NN	SA-78	23042
		AT4NN	310	80138
		AT4NN	3750A	28480
		AT4NN	442-C	80138
		AT4NN	442-D	80138
		AT4NN	442-D-J	80138

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX C

STANDARD EQUIPMENT TO REFERENCE EQUIPMENT

STANDARD EQUIPMENT	FSCM	GMQ	REFERENCE EQUIPMENT	FSCM
452-C	80138	AI4NY	32-0	80138
		AI4NY	451-B	80138
		AI4NY	452-C	80138
		AI4NY	9975610	18876
4609	99899	AD3YN	4609	99899
5015V	98095	PS1DN	BP-60F	23934
		PS1DN	BPA-60E	23934
		PS1DN	FR30-150-LM	11920
		PS1DN	5015	98095
		PS1DN	5015I	98095
		PS1DN	5015V	98095
		PS1DN	6112A	28480
		PS1DN	6205B	28480
		PS1DN	6206B	28480
		PS1DN	6255A	28480
		PS1DN	721A	28480
574-10	00443	DC2AA	H752C	28480
		DC2AA	574-10	00443
574-20	00443	DC2NN	H752D	28480
		DC2NN	574-20	00443
613-M	77327	DE2AN	22749	99899
		DE2AN	613-M	77327
616	99899	AD3AN	616	99899
6266B	28480	PS1BA	KS60-10M	85504
		PS1BA	RE40-5M	89022
		PS1BA	SL-36-2M	96762
		PS1BA	TO-36-5M	89022
		PS1BA	6265A	28480
		PS1BA	6266B	28480
		PS1BA	922582-1	06481
6274B	28480	PS1FY	6274B	28480
		PS1FY	6439B	28480
6294A	28480	PS1FA	6294A	28480

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX C

STANDARD EQUIPMENT TO REFERENCE EQUIPMENT

STANDARD EQUIPMENT	FSCM	GMG	REFERENCE EQUIPMENT	FSCM
6296A	28480	PS1FN	16-25	88113
		PS1FN	6296A	28480
6299A	28480	PS1HN	6299A	28480
638	99899	HN1IN	638	99899
640	99899	HN1MN	640	99899
6443B	28480	PS1KN	ABC100-0.2M	85604
		PS1KN	6443B	28480
778D	28480	DC1JJ	3020A	99899
		DC1JJ	776D	28480
		DC1JJ	778D	28480
80M	70998	TM1SA	80M	70998
8085	70998	DL1NN	8085	70998
8135	70998	DL1SN	DA-371/U	MIL
		DL1SN	160-100D	54778
		DL1SN	160B-150FN	54778
		DL1SN	8135	70998
8164	70998	DL1EA	8160	70998
		DL1EA	8164	70998
8201	70998	DL1EN	DA-140/AP	MIL
		DL1EN	8201	70998
8404	70998	DL1JN	DA-177/U	MIL
		DL1JN	DA-274/U	MIL
		DL1JN	DA-412/U	MIL
		DL1JN	DA-412A/U	MIL
		DL1JN	DA-412B/U	MIL
		DL1JN	DA-412C/U	MIL
		DL1JN	DA-88/U	MIL
		DL1JN	DA-88A/U	MIL
		DL1JN	DA-91A/U	MIL
		DL1JN	T-2098	12598
		DL1JN	160B-600FN	54778
		DL1JN	67	70998
		DL1JN	6835	70998

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX C

STANDARD EQUIPMENT TO REFERENCE EQUIPMENT

STANDARD EQUIPMENT	FSCM	GMG	REFERENCE EQUIPMENT	FSCM
8404 - CONTINUED		DL1JN	704-50	01365
		DL1JN	82A	70998
		DL1JN	82C	70998
		DL1JN	8230	70998
		DL1JN	8401	70998
		DL1JN	8401SPECIAL	70998
		DL1JN	8404	70998
8470A	28480	DE2YN	8470A	28480
		DE2YN	8470B	28480
8472A-001	28480	DE2NN	8472A-001	28480
8491A-003	28480	AT1AF	1-3	93459
		AT1AF	1100-A	77327
		AT1AF	210-3	93459
		AT1AF	50-3	93459
		AT1AF	530-3	93459
		AT1AF	530A-3	93459
		AT1AF	757C-3	99899
		AT1AF	8491A-003	28480
		AT1AF	90513-3	12678
8491A-006	28480	AT1EA	AD-06N	00929
		AT1EA	AH-C32	00929
		AT1EA	1-6	93459
		AT1EA	210-6	93459
		AT1EA	50-6	93459
		AT1EA	530-6	93459
		AT1EA	530A-6	93459
		AT1EA	757C-6	99899
		AT1EA	8491A-006	28480
		AT1EA	90513-6	12678
8491A-010	28480	AT1JA	AD-10N	00929
		AT1JA	AE-10N	00929
		AT1JA	CN-30/U	MIL
		AT1JA	CN-30A/U	MIL

Source: https://assist.dla.mil -- Downloaded: 202610-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX C

STANDARD EQUIPMENT TO REFERENCE EQUIPMENT

STANDARD EQUIPMENT	FSCM	CMG	REFERENCE EQUIPMENT	FSCM
8491A-010 - CONTINUED		AT1JA	CN-30B/U	MIL
		AT1JA	1-10	93459
		AT1JA	50-10	93459
		AT1JA	530-10	93459
		AT1JA	530A-10	93459
		AT1JA	553-10	93459
		AT1JA	757C-10	99899
		AT1JA	8491A-010	28480
		AT1JA	90513-10	12678
8491A-020	28480	AT1NN	CN-39A/U	MIL
		AT1NN	CN-39B/U	MIL
		AT1NN	CN-87/U	MIL
		AT1NN	CN-87A/U	MIL
		AT1NN	CN-87B/U	MIL
		AT1NN	1-20	93459
		AT1NN	210-20	93459
		AT1NN	50-20	93459
		AT1NN	530-20	93459
		AT1NN	553-20	93459
		AT1NN	8491A-020	28480
850-CT2W	83332	AT4RQ	CN-1000/G	MIL
		AT4RQ	IV795G	17870
		AT4RQ	1346-9700	24655
		AT4RQ	1450-TBR	24655
		AT4RQ	350B	28480
		AT4RQ	50B	12996
		AT4RQ	710	16055
		AT4RQ	850-CT2W	83332
973-20	93459	AT6AN	973-20	93459
		AT6AN	973P-20	93459

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX D

STANDARD EQUIPMENT TO SPECIFICATIONS

STANDARD EQUIPMENT	FSCM	ICP/NSN	NOUN NAME	GMG	SCAI
AF-117A-69-34	93459	9N6625-01-063-9297	ATTENUATOR,STEP	AT4GN	4898
SPECIFICATIONS: ATTENUATION:0-69 DB IN 1 DB STEPS FREQUENCY RANGE:DC-18 GHZ IMPEDANCE:50 OHM NOM POWER:2W AVG;200W PEAK VSWR:1.6 MAX CONNECTOR:N (M-F) DIMENSIONS:(INCHES)3.2L X 4W X 3.3H APPROX WEIGHT:(OUNCES)27 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
AU-65AMN	12457	1H6625-01-040-9528	ATTENUATOR,VARIABLE,COAXIAL	AT6MN	NONE
SPECIFICATIONS: ATTENUATION:80 DB MAX FREQUENCY RANGE:0.3-8 GHZ VSWR:1.5 AT 50 OHM NOM POWER:10W AVG INSERTION LOSS:0.7 DB CONNECTOR:N (M-F) DIMENSIONS:(INCHES)8.3L X 1W X 2.1H APPROX WEIGHT:(OUNCES)25 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
A400 BC	16786	1H6625-01-142-5447	FILTER,BANDPASS	FL1EJ	4705
SPECIFICATIONS: PASSBAND:4-6 GHZ INSERTION LOSS:(PASSBAND) <2 DB REJECTION:STOPBAND >30 DB IMPEDANCE:50 OHM NOM VSWR:1.5 MAX CONNECTOR:N (F) DIMENSIONS:(INCHES)2.3L X 1.3W X 4.1H APPROX WEIGHT:(OUNCES) 6 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
B-1576	91161	1H5985-00-792-9928	DUMMY LOAD,COAXIAL	DL1EY	4658
SPECIFICATIONS: FREQUENCY RANGE:DC-1 GHZ POWER RATING:200W NOM,5 KW PEAK IMPEDANCE:50 OHM NOM VSWR:1.15 MAX CONNECTOR:LC (F) DIMENSIONS:(INCHES) 25L X 6.3W X 11.25H APPROX WEIGHT:(POUNDS)33 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
BA-C-110C	00341	1H6625-01-030-5505	HORN,STANDARD GAIN	HN1FN	4008
SPECIFICATIONS: FREQUENCY RANGE:3.95-5.85 GHZ GAIN:LOW END 15 DB;HIGH END 18 DB BEAM WIDTH:20-30 DEGREES OVER BAND IN BOTH PLANES VSWR:1.15 MAX WAVEGUIDE:(INCHES)1.87 X 2 APPROX,WR137 FLANGE:UG-344/U,BRASS (COVER) DIMENSIONS:(INCHES)10.3L X 4.8W X 6.3H APPROX WEIGHT:(POUNDS)2.3 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX D

STANDARD EQUIPMENT TO SPECIFICATIONS

STANDARD EQUIPMENT	FSCM	ICP/NSN	NOUN NAME	GMG	SCAT
BHK-500-0.4M	85604	7Z6625-01-031-8855	POWER SUPPLY,DIRECT VOLTAGE	PS1VN	4114
SPECIFICATIONS: OUTPUT:0-500V;0-0.4A LOAD EFFECT:VOLTS,0.01% OR 0.001V;AMPS,100 UA SOURCE EFFECT:VOLTS 0.01%,AMPS <100.0 MA DRIFT:VOLTS,0.01% OR 0.002V;AMPS,0.01% RIPPLE:VOLTS,0.001V RMS;AMPS,100 UA FEATURES:CONSTANT VOLTS AND CURRENT;REMOTE SENSING DIMENSIONS:(INCHES)16.3L X 19W X 5.2H APPROX WEIGHT:(POUNDS)46 APPROX					
THIS EQUIPMENT IS CLASSIFIED AS TYPE III, CLASS 5, STYLE E, AND COLOR R FOR NAVY USE IN ACCORDANCE WITH MIL-T-28800 AS APPLICABLE.					
C-30BP	80009	7G6720-01-095-2205	CAMERA,OSCILLOSCOPE	CS1NN	NONE
SPECIFICATIONS: LENS SIZE:56 MM LENS APERTURE(SPEED):F/1.9 F STOP RANGE:F/1.9 TO F/16 FIELD OF VIEW:7 X 9 CM OR 8 X 10 CM W/OPTION 01 SHUTTER SPEED:1/125 TO 1 SECOND,BULB & TIME,X SYNC MAGNIFICATION:0.7-1.5 CONTINUOUSLY VARIABLE FOCUS:SPLIT-IMAGE FOCUS PLATE FILM:POLAROID PACK FILM DIMENSIONS:(INCHES)5.1H X 7.5W X 10.4D APPROX WEIGHT:(POUNDS)4.8 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
C-59AP	80009	1H6720-00-262-4198	CAMERA,OSCILLOSCOPE	CS1AA	NONE
SPECIFICATIONS: LENS SIZE:56 MM LENS APPERATURE(SPEED)F/2.8 F STOP RANGE:F/2.8 TO F/16 FIELD OF VIEW:10.2 X 12.7 CM SHUTTER SPEED:1/125 TO 1 SECOND,BULB & TIME,X SYNC POWER:15V FROM SOME SCOPES,OR AA SIZE BATTERIES FOCUS:FOCUS PLATE FILM:POLAROID PACK FILM DIMENSIONS:(INCHES)11.5H X 7.6W X 10.7D APPROX WEIGHT:(POUNDS)7 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
CX20PS	14135	9N5985-00-145-3514	ISOLATOR,COAXIAL	SR1YN	4800
SPECIFICATIONS: FREQUENCY RANGE:7-11 GHZ VSWR:1.25 MAX CONNECTOR:N (F-F) ISOLATION:15 DB MIN INSERTION LOSS:1 DB MAX DIMENSIONS:(INCHES)5.11 X 1.8W APPROX WEIGHT:(OUNCES)16 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX D

STANDARD EQUIPMENT TO SPECIFICATIONS

STANDARD EQUIPMENT	FSCM	ICP/NSN	NOUN NAME	GMG	SCAT
C20PS	14135	1H4931-00-921-7357	ISOLATOR,COAXIAL	SR1TN	4797
SPECIFICATIONS: FREQUENCY RANGE:4-8 GHZ VSWR:1.20 MAX CONNECTOR:N (F-F) ISOLATION:15 DB MIN INSERTION LOSS:1 DB MAX DIMENSIONS:(INCHES)6.7L X 2.1W APPROX WEIGHT:(OUNCES)24 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
DCR150-12B	49956	7Z6625-01-136-3178	POWER SUPPLY,DIRECT VOLTAGE	PS1BN	4051
SPECIFICATIONS: OUTPUT:0-150V,0-12A LOAD EFFECT:VOLTS,0.01%+0.004V;AMPS,0.25% SOURCE EFFECT:VOLTS,0.01%+0.004V;AMPS,0.25% DRIFT:VOLTS,0.1%;AMPS,0.15% RIPPLE:VOLTS,0.3V;AMPS,0.024A FEATURES:CONSTANT VOLTS AND CURRENT;REMOTE SENSING DIMENSIONS:(INCHES)21L X 18W X 7.8H APPROX WEIGHT:(POUNDS)90 APPROX					
THIS EQUIPMENT IS CLASSIFIED AS TYPE III, CLASS 5, STYLE E, AND COLOR R FOR NAVY USE IN ACCORDANCE WITH MIL-T-28800 AS APPLICABLE.					
DCR40-25B	49956	1H6130-01-040-9808	POWER SUPPLY,DIRECT VOLTAGE	PS1BN	4792
SPECIFICATIONS: OUTPUT:0-40V;0-25A LOAD EFFECT:VOLTS,0.01%+0.004V;AMPS,0.25% SOURCE EFFECT:VOLTS,0.01%+0.004V;AMPS,0.25% DRIFT:VOLTS,0.1%;AMPS,0.15% RIPPLE:VOLTS,0.09V;AMPS,0.056A FEATURES:CONSTANT VOLTS AND CURRENT;REMOTE SENSING DIMENSIONS:(INCHES)18L X 17W X 5.8H APPROX WEIGHT:(POUNDS)70 APPROX					
THIS EQUIPMENT IS CLASSIFIED AS TYPE III, CLASS 5, STYLE E, AND COLOR R FOR NAVY USE IN ACCORDANCE WITH MIL-T-28800 AS APPLICABLE.					
DPTC-25KFM	91161	1H5985-01-152-4077	DUMMY LOAD,COAXIAL	DL1AA	NONE
SPECIFICATIONS: FREQUENCY RANGE:DC-110 MHZ POWER RATING:25 KW CONTINUOUS IMPEDANCE:50 OHM NOM VSWR:1.15 MAX CONNECTOR:3-1/8 EIA DIMENSIONS:(INCHES)17L X 17W X 65H APPROX WEIGHT:(POUNDS)100 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
DPTC-50KFM	91161	1H5985-01-152-4078	DUMMY LOAD,COAXIAL	DL1AN	NONE
SPECIFICATIONS: FREQUENCY RANGE:DC-110 MHZ POWER RATING:55 KW CONTINUOUS IMPEDANCE:50 OHM NOM VSWR:1.15 MAX CONNECTOR:3-1/8 EIA DIMENSIONS:(INCHES)21L X 21W X 71H APPROX WEIGHT:(POUNDS)120 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX D

STANDARD EQUIPMENT TO SPECIFICATIONS

STANDARD EQUIPMENT	FSCM	ICP/NSN	NOUN NAME	GMG	SCAT
G-101	77327	9N5985-00-921-3697	ATTENUATOR,VARIABLE,WAVEGUIDE	AT7NN	4671
SPECIFICATIONS:	ATTENUATION:0-60 DB FREQUENCY RANGE:3.95-5.85 GHZ VSWR:1.15 AT 50 OHM NOM POWER:15W MAX FLANGE:UG-407/U,ALUMINUM (COVER) WAVEGUIDE:WR187 DIMENSIONS:(INCHES)19L X 7W X 6.3H APPROX WEIGHT:(POUNDS)11 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
GM-318-C4	60674	9N6625-01-036-2020	COUPLER,DIRECTIONAL,COAXIAL	DC1WN	4696
SPECIFICATIONS:	COUPLING:40 DB FREQUENCY RANGE:25 MHZ-8 GHZ DIRECTIVITY:20 DB POWER:1W MAX VSWR:PRI LINE 1.3,SEC LINE 1.45 CONNECTOR:C (F) DIMENSIONS:(INCHES)3.1L X 1.3W X 2.4H APPROX WEIGHT:(OUNCES)14 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
G281A	28480	9N5985-00-772-6676	ADAPTER,WAVEGUIDE TO COAXIAL	AD3FN	4861
SPECIFICATIONS:	FREQUENCY RANGE:3.95-5.85 GHZ VSWR:1.25 MAX WAVEGUIDE:WR187 FLANGE:UG-407/U,ALUMINUM (COVER) CONNECTOR:N (F) DIMENSIONS:(INCHES)3.8L X 2W X 1H APPROX WEIGHT:(POUNDS)0.5 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
JQE-36-3M	85604	1H6130-00-471-1735	POWER SUPPLY,DIRECT VOLTAGE	PS1AN	NONE
SPECIFICATIONS:	OUTPUT:0-36V;0-3A LOAD EFFECT:VOLTS,0.005% OR 200 UV;AMPS,0.01% SOURCE EFFECT:VOLTS,0.0005%;AMPS,0.005% DRIFT:VOLTS,0.01% OR 0.001V;AMPS,0.02% RIPPLE:VOLTS,200 UV RMS;AMPS,0.02% FEATURES:MODULAR;CONSTANT VOLTS & CURRENT;METERED DIMENSIONS:(INCHES)18L X 4W X 4.8H APPROX WEIGHT:(POUNDS)19 APPROX				
THIS EQUIPMENT IS CLASSIFIED AS TYPE III, CLASS 5, STYLE E, AND COLOR R FOR NAVY USE IN ACCORDANCE WITH MIL-T-28800 AS APPLICABLE.					
J281A	28480	9N5985-00-606-9161	ADAPTER,WAVEGUIDE TO COAXIAL	AD3MN	4610
SPECIFICATIONS:	FREQUENCY RANGE:5.3-8.2 GHZ VSWR:1.25 (1.3:5.3 AT 5.3 GHZ) WAVEGUIDE:WR137 FLANGE:UG-344/U,BRASS (COVER) CONNECTOR:N (F) DIMENSIONS:(INCHES)2L X 1.5W X 0.75H APPROX WEIGHT:(POUNDS)1 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX D

STANDARD EQUIPMENT TO SPECIFICATIONS

STANDARD EQUIPMENT	FSCM	ICP/NSN	NOUN NAME	GMG	SCAT
J382A	28480	7G6625-00-679-0627	ATTENUATOR,VARIABLE,WAVEGUIDE	AT7AA	NONE
SPECIFICATIONS: ATTENUATION:0-50 DB FREQUENCY RANGE:5.3-8.2 GHZ VSWR:1.15 AT 50 OHM NOM POWER:10W MAX FLANGE:UG-441/U,ALUMINUM (COVER) WAVEGUIDE:WR137 DIMENSIONS:(INCHES)25L X 6.2W X 8H APPROX WEIGHT:(POUNDS)17 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
K362A	28480	9N5985-00-488-7434	FILTER,BANDPASS	FL1JN	4728
SPECIFICATIONS: PASSBAND:18-26.5 GHZ;STOPBAND:31-80 GHZ INSERTION LOSS:(PASSBAND)<1 DB REJECTION:(STOPBAND)>40 DB IMPEDANCE:50 OHM NOM VSWR:1.5 MAX WAVEGUIDE:WR42;FLANGE UG-595/U,BRASS (COVER) DIMENSIONS:(INCHES)2.5L X 0.5W X 0.3H APPROX WEIGHT:(OUNCES)5.3 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
K382A	28480	9N5985-00-822-8666	ATTENUATOR,VARIABLE,WAVEGUIDE	AT7AT	4675
SPECIFICATIONS: ATTENUATION:0-50 DB FREQUENCY RANGE:18-26.5 GHZ VSWR:1.15 AT 50 OHM NOM POWER:2W MAX FLANGE:UG-597/U,ALUMINUM (COVER) WAVEGUIDE:WR42 DIMENSIONS:(INCHES)7.8L X 4.8W X 6H APPROX WEIGHT:(POUNDS)6 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
K422A	28480	1H6625-00-874-7733	DETECTOR,RF,FIXED,WAVEGUIDE	DE3NN	4966
SPECIFICATIONS: FREQUENCY RANGE:18-26.5 GHZ FREQUENCY RESPONSE:+/-2 DB WAVEGUIDE:WR42 VSWR:2.5 MAX POWER:100 MW MAX FLANGE:UG-595/U,BRASS (COVER) DIMENSIONS:(INCHES)2L X 0.5W X 0.3H APPROX WEIGHT:(POUNDS)1 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
K752C	28480	915985-00-913-9842	COUPLER,DIRECTIONAL,WAVEGUIDE	DC2AM	4907
SPECIFICATIONS: COUPLING:10 DB NOM FREQUENCY RANGE:18-26.5 GHZ DIRECTIVITY:40 DB MIN POWER:5W MAX FLANGE:UG-595/U,BRASS (COVER) WAVEGUIDE:WR42 DIMENSIONS:(INCHES)10L X 0.5W X 0.3H APPROX WEIGHT:(POUNDS)1 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX D

STANDARD EQUIPMENT TO SPECIFICATIONS

STANDARD EQUIPMENT	FSCM	ICP/NSN	NOUN NAME	GMG	SCAT
LA-60N	00929	9N5915-00-725-6051	FILTER,LOWPASS	FL2YN	4003
SPECIFICATIONS:	CUT-OFF FREQUENCY:6000 MHZ INSERTION LOSS:0.2 DB BELOW 6000 MHZ REJECTION:25 DB,7200 MHZ INCR TO 55 DB,9000 MHZ IMPEDANCE:50 OHM NOM VSWR:1.4 MAX CONNECTOR:N (M-F) DIMENSIONS:(INCHES)3.2L X 1 DIA APPROX WEIGHT:(OUNCES)3 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
LQ-415	80103	1H6625-01-178-9497	POWER SUPPLY,DIRECT VOLTAGE	PS1RN	NONE
SPECIFICATIONS:	OUTPUT:0-250V;0-0.08A LOAD EFFECT:0.005% + 0.5 MV SOURCE EFFECT:0.005% + 0.5 MV DRIFT:VOLTS,0.2% RIPPLE:VOLTS,300 UV RMS,1MV P-P FEATURES:SERIES/PARALLEL OPERATION;REMOTE SENSING DIMENSIONS:(INCHES)10L X 5.2W X 4.2H APPROX WEIGHT:(POUNDS)9 APPROX				
THIS EQUIPMENT IS CLASSIFIED AS TYPE III, CLASS 5, STYLE E, AND COLOR R FOR NAVY USE IN ACCORDANCE WITH MIL-T-28800 AS APPLICABLE.					
L20PS	14135	9O6625-00-738-2716	ISOLATOR,COAXIAL	SR1FN	4798
SPECIFICATIONS:	FREQUENCY RANGE:1-2 GHZ VSWR:1.25 MAX CONNECTOR:N (F-F) ISOLATION:10 DB INSERTION:1.5 DB DIMENSIONS:(INCHES)7.4L X 2.1W APPROX WEIGHT:(OUNCES)36 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
M-1012A	88869	1H6625-01-206-2974	TRANSFORMER,RATIO	TR4JN	4643
SPECIFICATIONS:	FREQUENCY RANGE:30-1000 HZ RESOLUTION:0.00001 % ACCURACY:+/-(0.0001%+[0.00005%]),30-400 HZ INPUT VOLTAGE:2.5 X FREQUENCY WITH 350V MAX SERIES OUTPUT IMP:RS-5 OHM,LS-350 UV INPUT IMP:2.5 X INPUT FREQ,220K OHMS TYPICALLY DIMENSIONS:(INCHES)17W X 5.875H X 16.875D APPROX WEIGHT:(POUNDS)26 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
M2G3	13850	9N5950-00-877-4863	TRANSFORMER,AUTO	TR1MN	4652
SPECIFICATIONS:	INPUT:120-208-240 VAC,400 HZ,THREE PHASE RATED CURRENT:2.4 AMPERES,3.1 AMPERES MAX KVA RATING:1.30 KVA (MAX LOAD CURRENT X INPUT VAC) OUTPUT VOLTAGE RATING:0-240 VAC OVERVOLTAGE:17% PERMITTED ON 120/208 VAC INPUT MOUNTING:OPEN,WYE CONNECTION DIMENSIONS:(INCHES)3.69H X 3.5W X 8.25D APPROX WEIGHT:(POUNDS)5 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					

Source: https://assist.dla.mil -- Downloaded: 202610-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX D

STANDARD EQUIPMENT TO SPECIFICATIONS

STANDARD EQUIPMENT	FSCM	ICP/NSN	NOUN NAME	QMG	SCAT
M5	13850	9N5950-00-504-9090	TRANSFORMER,AUTO	TR1FN	4655
SPECIFICATIONS: INPUT:120 VAC,400 HZ,SINGLE PHASE RATED CURRECT:6.0 AMPERES,7.8 AMPERES MAX KVA RATING:0.94 KVA (MAX LOAD CURRENT X INPUT VAC) OUTPUT VOLTAGE RATING:0-140 VAC MOUNTING:OPEN DIMENSIONS:(INCHES)4.94H X 4.5W X 2.69D APPRX WEIGHT:(POUNDS)3 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
M602	57646		ATTENUATOR,STEP	AT4KN	NONE
SPECIFICATIONS: ATTENUATION:100 DB MAX FREQUENCY RANGE:DC-500 MHZ IMPEDANCE:90 OHMS NOM POWER:0.5W AVG INSERTION LOSS:<1 DB AT 150 MHZ & <4 DB AT 400 MHZ CONNECTOR:BNC (F-F) DIMENSIONS:(INCHES)11L X 2W X 2H APPROX WEIGHT:(POUNDS)1.5 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
M9412-2C	09992	1H5985-01-203-5192	ATTENUATOR,FIXED,COAXIAL	AT1NB	NONE
SPECIFICATIONS: ATTENUATION:20 DB +/- 2.0 DB TO 18 GHZ FREQUENCY RANGE:DC-18.0 GHZ IMPEDANCE:50 OHMS NOM POWER:2W AVG;3 KW PEAK VSWR:2.0 MAX CONNECTOR:N (M-F) DIMENSIONS:(INCHES)2.42L X 0.82 DIA APPROX WEIGHT:(OUNCES)5.0 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
P281B	28480	9N5985-00-136-8330	ADAPTER,WAVEGUIDE TO COAXIAL	AD3WN	4609
SPECIFICATIONS: FREQUENCY RANGE:12.4-18 GHZ VSWR:1.25 MAX WAVEGUIDE:WR62 FLANGE:UG-419/U,BRASS (COVER) CONNECTOR:APC-7 (F),ORDER OPT 013 FOR TYPE N (F) DIMENSIONS:(INCHES)2.5L X 0.7W X 0.4H APPROX WEIGHT:(POUNDS)0.2 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
P382A	28480	6G6625-00-752-3222	ATTENUATOR,VARIABLE,WAVEGUIDE	AT7AM	4673
SPECIFICATIONS: ATTENUATION:0-50 DB FREQUENCY RANGE:12.4-18 GHZ VSWR:1.15 AT 50 OHM NOM POWER:5W MAX FLANGE:UG-419/U,COPPER ALLOY (COVER) WAVEGUIDE:WR62 DIMENSIONS:(INCHES)12.5L X 4.8W X 7.8H APPROX WEIGHT:(POUNDS)8 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX D

STANDARD EQUIPMENT TO SPECIFICATIONS

STANDARD EQUIPMENT	FSCM	ICP/NSN	NOUN NAME	GMG	SCAI
P424A	28480	1R6625-00-980-9302	DETECTOR,RF,FIXED,WAVEGUIDE	DE3AN	NONE
SPECIFICATIONS: FREQUENCY RANGE:12.4-18 GHZ FREQUENCY RESPONSE:+/-0.5 DB WAVEGUIDE:WR62 VSWR:1.5 MAX POWER:100 MW MAX FLANGE:UG-419/U,BRASS (COVER) DIMENSIONS:(INCHES)1L X 0.7W X 0.4H APPROX WEIGHT:(POUNDS)0.5 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
P6161	80089	9N5950-00-645-1807	TRANSFORMER,ISOLATION	TR3AN	4796
SPECIFICATIONS: INPUT:105/115/125 VAC,50-60 HZ OUTPUT:115 VAC VOLT-AMPS CAPACITY:250 VA RMS TEST VOLTAGE:1500V DIMENSIONS:(INCHES)5.5L X 3.8W X 4.7H APPROX WEIGHT:(POUNDS)14 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
QHB-2-30	12457	1R5985-00-991-1013	COUPLER,HYBRID,QUADRATURE	CQ1NN	4870
SPECIFICATIONS: FREQUENCY:CENTER 30 MHZ,BANDWIDTH 10% IMPEDANCE:50 OHM NOM POWER:1W AVG VSWR:1.3:1,AMPLITUDE BALANCE:0.6 DB INSERTION LOSS:0.3 DB MAX ISOLATION:25 DB MIN,COUPLING:-3 DB PHASE QUADRATURE:90 DEG +/-3 DEG CONNECTOR:BNC (F) DIMENSIONS:(INCHES)2.25L X 1.7 W X 0.60H APPROX WEIGHT:(OUNCES)1.5 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
R-1011B	94990	1H6625-01-205-1224	POWER SUPPLY,DIRECT VOLTAGE	PS1BY	NONE
SPECIFICATIONS: OUTPUT:1-40 IN 2 RANGES:0-40A IN 3 RANGES LOAD EFFECT:VOLTS,0.1% OF FULL SCALE SOURCE EFFECTS:VOLTS,0.1% OF FULL SCALE DRIFT:VOLTS,0.1% RIPPLE:VOLTS,0.02V RMS FEATURES:SHORT PROTECTION;RFI/EMI PROTECTED,220-240 VAC,50-60 HZ AVAILABLE THRU SHORTING BARS DIMENSIONS:(INCHES)20D X 16W X 8H APPROX WEIGHT:(POUNDS)75 APPROX					
THIS EQUIPMENT IS CLASSIFIED AS TYPE III, CLASS 5, STYLE E, AND COLOR R FOR NAVY USE IN ACCORDANCE WITH MIL-T-28800 AS APPLICABLE.					

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX D

STANDARD EQUIPMENT TO SPECIFICATIONS

STANDARD EQUIPMENT	FSCM	ICP/NSN	NOUN NAME	GMG	SCAT
RT-20A	88869	1H5950-01-067-3203	TRANSFORMER,RATIO	TR4TJ	4649
SPECIFICATIONS:	FREQUENCY RANGE:50 HZ TO 10 KHZ RESOLUTION:INTERPOLATING POTENTIOMETER PROVIDING A VARIATION OF 1 PPM ACCURACY:+/-(.001%+.0001%/RATIO)@50-3000 HZ,+/-(.0 1%+.0001%/RATIO)@3000/10000 HZ INPUT VOLTAGE:0.35 X FREQ IN HZ TO 350 VRMS MAX SERIES OUTPUT IMP:RS=3.0 OHMS,LS=75 MICRO HENRIES INPUT IMP:45K OHMS,DEPENDENT ON FREQUENCY DIMENSIONS(INCHES)17W X 5.25H X 16.875D APPROX WEIGHT(POUNDS)16 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
RT-30A	88869	1H6625-LL-HHE-4050	TRANSFORMER,RATIO	TR4TT	4650
SPECIFICATIONS:	FREQUENCY RANGE:50 HZ TO 10 KHZ RESOLUTION:INTERPOLATING POTENTIOMETER PROVIDING CONTINUOUS READINGS TO SEVEN PLACES ACCURACY:0.0001/RATIO % AT 400 HZ INPUT VOLTAGE:0.35 X FREQ OR 350V,WHATEVER IS LESS SERIES OUTPUT IMPEDANCE:RS-4,LS-200 UH INPUT IMP:(AT 20V,400 HZ) 150K OHM MIN. DIMENSIONS:(INCHES)19W X 5.25H X 6.5D APPROX WEIGHT:(POUNDS)11 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
R362A	28480	5N5915-00-488-7437	FILTER,LOWPASS	FL2WG	4729
SPECIFICATIONS:	PASSBAND:26.5-40 GHZ;STOPBAND:47-120 GHZ INSERTION LOSS:(PASSBAND)<2 DB REJECTION:(STOPBAND)>35 DB IMPEDANCE:50 OHM NOM VSWR:1.8 MAX WAVEGUIDE:WR28;FLANGE UG-599/U,BRASS (COVER) DIMENSIONS:(INCHES)1.7L X 0.4W X 0.2H APPROX WEIGHT:(OUNCES)4 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
R362A	28480	1H5985-00-822-7874	ATTENUATOR,VARIABLE,WAVEGUIDE	AT7AY	4677
SPECIFICATIONS:	ATTENUATION:0-50 DB FREQUENCY RANGE:26.5-40 GHZ VSWR:1.15 AT 50 OHM NOM POWER:1W MAX FLANGE:UG-599/U,COPPER ALLOY (COVER) WAVEGUIDE:WR28 DIMENSIONS:(INCHES)6.4L X 8W X 6.1H APPROX WEIGHT:(POUNDS)6 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX D

STANDARD EQUIPMENT TO SPECIFICATIONS

STANDARD EQUIPMENT	FSCM	ICP/NSN	NOUN NAME	GMG	SCAT
R422A	28480	1R6625-00-981-9518	DETECTOR,RF,FIXED,WAVEGUIDE	DE3YN	4965
SPECIFICATIONS: FREQUENCY RANGE:26.5-40 GHZ FREQUENCY RESPONSE:+/-2 DB WAVEGUIDE:WR28 VSWR:3 MAX POWER:100 MW MAX FLANGE:UG-599/U,BRASS (COVER) DIMENSIONS:(INCHES)2L X 0.4W X 0.2H APPROX WEIGHT:(POUNDS)1 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
R752C	28480	9N4931-00-777-1373	COUPLER,DIRECTIONAL,WAVEGUIDE	DC2AT	4909
SPECIFICATIONS: COUPLING:10 DB NOM FREQUENCY RANGE:26.5-40 GHZ DIRECTIVITY:40 DB MIN POWER:5W MAX FLANGE:UG-599/U,BRASS (COVER) WAVEGUIDE:WR28 DIMENSIONS:(INCHES)8.6L X 0.4W X 0.2H APPROX WEIGHT:(POUNDS)1 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
SPX-3031	88869	1H5950-01-040-0282	TRANSFORMER,ISOLATION	TR3YN	4660
SPECIFICATIONS: FREQUENCY RANGE:50 HZ-10 KHZ TURNS RATIO:1:1 DC RESISTANCE:10 OHM APPROX INPUT IMPEDANCE:>250K OHM AT 400 HZ INPUT VOLTAGE:350V MAX CONNECTOR:FOUR BINDING POSTS DIMENSIONS:(INCHES)3.5L X 4.4W X 4.3H APPROX WEIGHT:(POUNDS)2.5 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
ST-100	88869	9N5950-00-679-6862	TRANSFORMER,ISOLATION	TR3NN	4659
SPECIFICATIONS: FREQUENCY RANGE:20-5000 HZ TURNS RATIO:4:1 DC RESISTANCE:100 OHM-LOW SIDE;2.7K OHM-HIGH SIDE INPUT IMPEDANCE:>15K OHM AT 400 HZ INPUT VOLTAGE:115V RMS AT 60 HZ CONNECTOR:FOUR BINDING POSTS DIMENSIONS:(INCHES)3.5L X 4.4W X 4.3H APPROX WEIGHT:(POUNDS)2.5 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
S11PS	14135	9N5985-00-439-3536	ISOLATOR,COAXIAL	SR1MN	4799
SPECIFICATIONS: FREQUENCY RANGE:2-4 GHZ VSWR:1.15 MAX CONNECTOR:N (F-F) ISOLATION:20 DB MIN INSERTION LOSS:0.7 DB MAX DIMENSIONS:(INCHES)6.9L X 2.1W APPROX WEIGHT:(OUNCES)38 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX D

STANDARD EQUIPMENT TO SPECIFICATIONS

STANDARD EQUIPMENT	FSCM	ICP/NSN	NOUN NAME	GMG	SCAT
S281A	28480	1R4920-01-029-4624	ADAPTER,WAVEGUIDE TO COAXIAL	AD3CN	4860
SPECIFICATIONS: FREQUENCY RANGE:2.6-3.95 GHZ VSWR:1.25 MAX WAVEGUIDE:WR284 FLANGE::UG-584/U,ALUMINUM (COVER) CONNECTOR:N (F) DIMENSIONS:(INCHES)5.5L X 3.0W X 1.5H APPROX WEIGHT:(POUNDS)1.2 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
S382C	28480	9N6625-00-179-8448	ATTENUATOR,VARIABLE,WAVEGUIDE	AT7NA	4670
SPECIFICATIONS: ATTENUATION:0-60 DB FREQUENCY RANGE:2.6-3.95 GHZ VSWR:1.2,2.6-3 GHZ & 1.15,3-3.95 GHZ;AT 50 OHM NOM POWER:10W MAX FLANGE:UG-584/U,ALUMINUM (COVER) WAVEGUIDE:WR284 DIMENSIONS:(INCHES)25.3L X 8W X 6H APPROX WEIGHT:(POUNDS)22 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
S501B	00929	1H6625-00-535-9532	TERMINATION,WAVEGUIDE	TM2JN	NONE
SPECIFICATIONS: FREQUENCY RANGE:2.6-3.95 GHZ POWER:5W AVG VSWR:1.025 MAX WAVEGUIDE:WR284,RG48 FLANGE:UG-53/U (COVER) DIMENSIONS:(INCHES)9.9L X 3W X 1.5H APPROX WEIGHT:(POUNDS)3.5 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
TCR-300S-3-1	89022	1H6625-LL-HHE-4110	POWER SUPPLY,DIRECT VOLTAGE	PS1TN	4129
SPECIFICATIONS: OUTPUT:0-300V; 0-3A LOAD EFFECT:VOLTS,0.1%;AMPS,0.1% SOURCE EFFECTS:VOLTS,0.1%;AMPS,0.1% DRIFT:VOLTS,0.05%;AMPS,0.05% RIPPLE;VOLTS,0.25V;AMPS,0.003A RMS FEATURES:CONSTANT VOLTS & CURRENT,REMOTE SENSING DIMSNSIONS:(INCHES)21L X 19W X 3.5H APPROX WEIGHT:(POUNDS)64 APPROX					
THIS EQUIPMENT IS CLASSIFIED AS TYPE III, CLASS 5, STYLE E, AND COLOR R FOR NAVY USE IN ACCORDANCE WITH MIL-T-28800 AS APPLICABLE.					
TDR-29C:1	87864	9N5985-00-062-6919	ADAPTER,WAVEGUIDE TO COAXIAL	AD3JN	4862
SPECIFICATIONS: FREQUENCY RANGE:3.5-8.2 GHZ VSWR:1.20 MAX WAVEGUIDE:WR350;MFG NUMBER DR-29 FLANGE:UG-1550/U,ALUMINUM (COVER) CONNECTOR:N (F) DIMENSIONS:(INCHES)5.2L X 1.5W X 0.7H APPROX WEIGHT:(POUNDS)1 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX D

STANDARD EQUIPMENT TO SPECIFICATIONS

STANDARD EQUIPMENT	FSCM	ICP/NSN	NOUN NAME	GMG	SCAT
UNDER REVIEW			DIVIDER,VOLTAGE,DECADE	DR3UR	4678
SPECIFICATIONS: RATIO:0.00001-1.00000, 5 DIALS, 10 PPM STEPS INPUT IMPEDANCE:10K OHM, +/-150 PPM VOLTAGE RATING:230V MAX FREQUENCY RESPONSE:DC-690 KHZ DEPENDENT ON VOLTAGE ABSOLUTE LINEARITY:+/-0.03 TO +/-20 PPM OF INPUT CONNECTORS:BINDING POSTS DIMENSIONS:(INCHES)17.3L X 3.5W X 6H APPROX WEIGHT:(POUNDS)7.8 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
UNDER REVIEW			DETECTOR,RF,TUNABLE,COAXIAL	DE4UR	4943
SPECIFICATIONS: FREQUENCY RANGE:2.4-12.4 GHZ CONNECTOR:N (M) DETECTORS:1N21,1N21 OR 821 SERIES BARRETTER DIMENSIONS:(INCHES)4.5L X 1W X 8H APPROX WEIGHT:(POUNDS)1 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
UNDER REVIEW			POWER SUPPLY,DIRECT VOLTAGE	PS1UR	NONE
SPECIFICATIONS: OUTPUT:0-160V,0.2A LOAD EFFECT:VOLTS 0.02%+0.002V,AMPS 200 UA SOURCE EFFECT:VOLTS 0.02%+0.002V,AMPS 200 UA DRIFT:VOLTS 0.1%+0.005V,AMPS 0.1%+750 UA RIPPLE:VOLTS 500 UV, AMPS 200 UA RMS FEATURES:CONSTANT VOLTS AND CURRENT,REMOTE SENSING DIMENSIONS:(INCHES)8.5L X 12.5W X 3.5H APPROX WEIGHT:(POUNDS)10 APPROX					
THIS EQUIPMENT IS CLASSIFIED AS TYPE III, CLASS 5, STYLE E, AND COLOR R FOR NAVY USE IN ACCORDANCE WITH MIL-T-28800 AS APPLICABLE.					
UNDER REVIEW			POWER SUPPLY,DIRECT VOLTAGE	PS1UR	NONE
SPECIFICATIONS: OUTPUT:0-2 KV,0-0.1A LOAD EFFECT:VOLTS,0.005% OR 0.02V,2% OR 0.001 AMP SOURCE EFFECT:VOLTS,0.005% OR 0.02V:AMPS,0.001A DRIFT:VOLTS,0.036%+0.003V:AMPS,0.25%+0.00025A RIPPLE:VOLTS,0.001V AMPS,0.001A RMS FEATURES:CONSTANT VOLTS AND CURRENT, SHORT PROOF DIMENSIONS(INCHES)17.9L X 16.8W X 5H APPROX WEIGHT:(POUNDS)63 APPROX					
THIS EQUIPMENT IS CLASSIFIED AS TYPE III, CLASS 5, STYLE E, AND COLOR R FOR NAVY USE IN ACCORDANCE WITH MIL-T-28800 AS APPLICABLE.					
UNDER REVIEW			CAPACITOR,DECADE	CP1U3	4644
SPECIFICATIONS: RANGE:0.0001-0.011 MFD IN 0.0001 MFD STEPS ACCURACY:+/-2% VOLTAGE:600 VDC MAX,200 VAC MAX RANGE SELECTOR:TWO ROTARY SWITCHES CONNECTOR:BINDING POSTS DIMENSIONS:(INCHES)3.6L X 5W X 3H APPROX WEIGHT:(POUNDS)1 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX D

STANDARD EQUIPMENT TO SPECIFICATIONS

STANDARD EQUIPMENT	FSCM	ICP/NSN	NOUN NAME	GMG	SCAI
UNDER REVIEW			CAPACITOR,DECADE	CP1U2	4646
SPECIFICATIONS: RANGE:0.01-1.1 MFD IN 0.01 MFD STEPS ACCURACY:+/-3% VOLTAGE:600 VDC MAX,220 VAC MAX RANGE SELECTOR:TWO ROTARY SWITCHES CONNECTOR:BINDING POSTS DIMENSIONS:(INCHES)3.6L X 5W X 3H APPROX WEIGHT:(POUNDS)2 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
UNDER REVIEW			CAPACITOR,DECADE	CP1U1	4647
SPECIFICATIONS: RANGE:1-10 MFD IN 1 MFD STEPS ACCURACY:+/-3% VOLTAGE:600 VDC MAX,220 VAC MAX RANGE SELECTOR:ONE ROTARY SWITCH CONNECTOR:BINDING POSTS DIMENSIONS:(INCHES)3.6L X 5W X 3H APPROX WEIGHT:(POUNDS)3 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
UNDER REVIEW			TERMINATION,WAVEGUIDE	TM2UR	NONE
SPECIFICATIONS: FREQUENCY RANGE:8.5-9.6 GHZ POWER RATING:4W MAX VSWR:1.1 MAX WAVEGUIDE:RG-52/U,WR90 FLANGE:UG-39/U,BRASS(COVER) DIMENSIONS:(INCHES)1.53L X 1W X 0.5H APPROX WEIGHT:(POUNDS)2 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
UNDER REVIEW			MODULATOR,WAVEGUIDE	ML1UR	NONE
SPECIFICATIONS: FREQUENCY RANGE:8.2-10.6 GHZ VSWR:1.30 MAX WAVEGUIDE:WR90,FLANGE UG-39/U,BRASS (COVER) ATTENUATION:25 DB MAX INSERTION:1 DB MODULATION SPEED:0.2 KHZ DIMENSIONS:(INCHES)3.5L X 1W X 0.5H APPROX WEIGHT:(OUNCES)6 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
V637	99899	9N6625-01-031-1981	HORN,STANDARD GAIN	HN1YN	4012
SPECIFICATIONS: FREQUENCY RANGE:26.5-40 GHZ GAIN:(MID FREQ VARIATION)1.5 DB/COMPLETE BAND BEAM WIDTH:28 DEGREES APPROX,EQUAL IN E&H PLANES VSWR:1.15 MAX WAVEGUIDE:(INCHES)0.36 X 0.22 APPROX,WR28 FLANGE:UG-599/U,BRASS (COVER) DIMENSIONS:(INCHES)1.8L X 0.78W X 1H APPROX WEIGHT:(POUNDS)0.1 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX D

STANDARD EQUIPMENT TO SPECIFICATIONS

STANDARD EQUIPMENT	FSCM	ICP/NSN	NOUN NAME	GMG	SCAT
WE-0035	00929	1H6625-01-067-3271	DUMMY LOAD,WAVEGUIDE	DL2FN	4002
SPECIFICATIONS:	FREQUENCY RANGE:3.95-5.85 GHZ POWER RATING:800W AVG;5250 KW PEAK (INDEPENDENT PEAK POWER RATING ASSUMES NEGLIGIBLE AVG POWER) VSWR:1.1 MAX WAVEGUIDE:RG-95/U,WR187 FLANGE:UG-407/U,ALUMINUM (COVER) DIMENSIONS:(INCHES)7.8L X 5.3W X 5.3H APPROX WEIGHT:(POUNDS)5 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
WF-0025	00929	7G5985-00-539-6126	DUMMY LOAD,WAVEGUIDE	DL2AN	NONE
SPECIFICATIONS:	FREQUENCY RANGE:2.6-3.95 GHZ POWER RATING:4.5 KW AVG;3200 KW PEAK VSWR:1.1 MAX WAVEGUIDE:RG-75/U;WR284 FLANGE:UG-584/U,ALUMINUM (COVER) DIMENSIONS:(INCHES)14L X 4.9W X 6.4H APPROX WEIGHT:(POUNDS)11.5 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
WF-0050	00929	9N5985-00-572-6267	DUMMY LOAD,WAVEGUIDE	DL2MN	4599
SPECIFICATIONS:	FREQUENCY RANGE:7.05-10 GHZ POWER RATING:600W AVG;460 KW PEAK VSWR:1.1 MAX WAVEGUIDE:RG-68/U;WR112 FLANGE:UG-138/U,ALUMINUM (COVER) DIMENSIONS:(INCHES)6.3L X 2.5W X 3.1H APPROX WEIGHT:(POUNDS)2.8 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
WF-0055	00929	9N5985-00-538-7328	DUMMY LOAD,WAVEGUIDE	DL2YN	4600
SPECIFICATIONS:	FREQUENCY RANGE:8.2-12.4 GHZ POWER RATING:500W AVG;290 KW PEAK VSWR:1.1 MAX WAVEGUIDE:RG-67/U;WR90 FLANGE:UG-135/U,ALUMINUM (COVER) DIMENSIONS:(INCHES)5.7L X 2.8W X 2.8H APPROX WEIGHT:(POUNDS)1.3 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
W10G3M	13850	9G6120-00-033-3776	TRANSFORMER,AUTO	TR1TT	NONE
SPECIFICATIONS:	INPUT:208-240 VAC,50-60 HZ,THREE PHASE RATED CURRENT:10.0 AMPERES,13.0 AMPERES MAX KVA RATING:5.40 KVA (MAX LOAD CURRENT X INPUT VAC) OUTPUT VOLTAGE RATING:0-240 VAC MOUNTING:OPEN,WYE CONNECTION DIMENSIONS:(INCHES)9.69H X 7.13 X 14.19 APPROX WEIGHT:(POUNDS)43 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					

Source: https://assist.dla.mil -- Downloaded: 202640-26T13:40Z
Check the source to verify that this is the currenversion before use.

APPENDIX D

STANDARD EQUIPMENT TO SPECIFICATIONS

STANDARD EQUIPMENT	FSCM	ICP/NSN	NOUN NAME	GMG	SCAT
W10HG3M	13850	1H6120-00-032-1173	TRANSFORMER,AUTO	TR1YN	4648
SPECIFICATIONS: INPUT:480 VAC,50-60 HZ,THREE PHASE RATED CURRENT:4.0 AMPERES,5.2 AMPERES MAX KVA RATING:4.32 KVA (MAX LOAD CURRENT X INPUT VAC) OUTPUT VOLTAGE RATING:0-480 VAC MOUNTED:ENCLOSED,WYE CONNECTION DIMENSIONS:(INCHES)9.69H X 7.13W X 14.19D APPROX WEIGHT:(POUNDS)42 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
W10MT3A	13850	9S6120-00-054-7794	TRANSFORMER,AUTO	TR1AN	4656
SPECIFICATIONS: INPUT:120 VAC,50-60 HZ,SINGLE PHASE RATED CURRENT:10.0 AMPERES OUTPUT VOLTAGE RATING:0-140 VAC MAX METER RANGE:(FULL SCALE)AMPERES 2&10,VOLTS 150 MOUNTING:ENCLOSED DIMENSIONS:(INCHES)11.94H X 8.63W X 5.38D APPROX WEIGHT:(POUNDS)18 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
W5G3M	13850	9G6120-00-879-3698	TRANSFORMER,AUTO	TR1TJ	NONE
SPECIFICATIONS: INPUT:208 VAC,50-60 HZ,THREE PHASE RATED CURRENT:5.0 AMPERES,6.5 AMPERES MAX KVA RATING:2.70 KVA (MAX LOAD CURRENT X INPUT VAC) OUTPUT VOLTAGE RATING:2-240 VAC MOUNTING:ENCLOSED,WYE CONNECTION DIMENSIONS:(INCHES)6.75H X 5.13W X 12.25D APPROX WEIGHT:(POUNDS)22 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
W5MT3A	13850	9N5950-00-987-5601	TRANSFORMER,AUTO	TR1AA	4653
SPECIFICATIONS: INPUT:120 VAC,50-60 HZ,SINGLE PHASE RATED CURRENT:5.0 AMPERES OUTPUT VOLTAGE RATING:0-140 VAC MAX METER RANGE:(FULL SCALE) AMPERES 1&5,VOLTS 150 MOUNTING:ENCLOSED DIMENSIONS:(INCHES)9.5H X 6.75W X 5.25D APPROX WEIGHT:(POUNDS)11 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
X281A	28480	9N5985-00-892-0732	ADAPTER,WAVEGUIDE TO COAXIAL	AD3TN	4605
SPECIFICATIONS: FREQUENCY RANGE:8.2-12.4 GHZ VSWR:1.25 MAX WAVEGUIDE:WR90 FLANGE:UG-135/U,ALUMINUM (COVER) CONNECTOR:N (F) DIMENSIONS:(INCHES)1.8L X 1W X 0.5H APPROX WEIGHT:(POUNDS)1 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX D

STANDARD EQUIPMENT TO SPECIFICATIONS

STANDARD EQUIPMENT	FSCM	ICP/NSN	NOUN NAME	GMG	SCAT
X301A	13047	1H5985-01-069-2318	TERMINATION,WAVEGUIDE	TM2TN	4892
SPECIFICATIONS: FREQUENCY RANGE:8.2-12.4 GHZ POWER:2W AVG;1 KW PEAK VSWR:1.02 MAX WAVEGUIDE:WR90 FLANGE:UG-39/U,BRASS (COVER) DIMENSIONS:(INCHES)5L X 1W X 0.5H APPROX WEIGHT:(POUNDS)0.7 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
X382A	28480	1H6625-00-602-2089	ATTENUATOR,VARIABLE,WAVEGUIDE	AT7AF	4901
SPECIFICATIONS: ATTENUATION:0-50 DB FREQUENCY RANGE:8.2-12.4 GHZ VSWR:1.15 AT 50 OHM NOM POWER:10W MAX FLANGE:UG-135/U,ALUMINUM (COVER) WAVEGUIDE:WR90 DIMENSIONS:(INCHES)15.5L X 4.7W X 7.5H APPROX WEIGHT:(POUNDS)8 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
X752C	28480	9N5985-00-646-9472	COUPLER,DIRECTIONAL,WAVEGUIDE	DC2AF	4905
SPECIFICATIONS: COUPLING:10 DB NOM FREQUENCY RANGE:8.2-12.4 GHZ DIRECTIVITY:40 DB MIN POWER:10W MAX FLANGE:UG-135/U,ALUMINUM (COVER) WAVEGUIDE:WR90 DIMENSIONS:(INCHES)15.6L X 1W X 0.5H APPROX WEIGHT:(POUNDS)3 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
0874-9099	82316	1H5935-00-370-8549	ADAPTER,COAXIAL,SET	AD1NN	4604
SPECIFICATIONS: IMPEDANCE:50 OHM NOM ALL CONNECTORS ADAPT TO TYPE GR874 CONNECTOR,1 EA OF TYPE C (M-F),HN (M-F),SMA (M-F),TNC (M-F0,1 TEE (3 X GR874),1 RIGHT ANGLE LINE SECTION (2 X GR874) AND 1 GR874-A3 50 OHM CABLE TERMINATED W/GR 874 1 END,OTHER END W/BANANA PLUG DIMENSIONS:(INCHES)CASE 7L X 18.5W X 4H APPROX WEIGHT:(POUNDS)4.5 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
0874-9577	82316	&A5840-00-868-1287	ATTENUATOR,VARIABLE,COAXIAL	AT6TN	4697
SPECIFICATIONS: ATTENUATION:120 DB MAX FREQUENCY RANGE:100 MHZ-4 GHZ VSWR:<1.03,1 GHZ & 1.12,1-4 GHZ;AT 50 OHM NOM POWER:300W AVG INSERTION LOSS:30.4 DB CONNECTOR:GR874 (SEXLESS) DIMENSIONS:(INCHES)36L INCLUDING CABLE,APPROX WEIGHT:(POUNDS)1.3 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					

Source: https://assist.dla.mil -- Downloaded: 202640-26T13:40Z
Check the source to verify that this is the currentversion before use.

APPENDIX D

STANDARD EQUIPMENT TO SPECIFICATIONS

STANDARD EQUIPMENT	FSCM	ICP/NSN	NOUN NAME	GMG	SCAT
1/432D	80138	9N5985-00-252-8026	ATTENUATOR,STEP	AT4DN	NONE
SPECIFICATIONS: ATTENUATION:0-22.1 DB IN 0.1 DB STEPS FREQUENCY RANGE:DC-0.5 GHZ IMPEDANCE:50 OHM NOM POWER:1W MAX VSWR:1.2 MAX CONNECTOR:BNC (F-F) DIMENSIONS:(INCHES)2L X 9.8W X 2H APPROX WEIGHT:(POUNDS)3 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
102AC46-1E	01456	1H6625-00-178-0008	ADAPTER,WAVEGUIDE TO COAXIAL	AD3QN	4606
SPECIFICATIONS: FREQUENCY RANGE:7-11 GHZ VSWR:1.25 MAX WAVEGUIDE:WR102 FLANGE:RG-320/U,ALUMINUM (COVER) CONNECTOR:N (F) DIMENSIONS:(INCHES)1L X 1.2W APPROX WEIGHT:(POUNDS)0.3 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
10514A	28480	9N5985-00-087-4714	MIXER,BALANCED,DOUBLE	MX1NN	NONE
SPECIFICATIONS: FREQUENCY RANGE:0.2-500 MHZ CONNECTOR:BNC (F) IMPEDANCE:50 OHM NOM INPUT LEVEL:0.0040A MAX INPUT POWER:0.005W MAX DIMENSIONS:(INCHES)2L X 3W APPROX WEIGHT:(POUNDS)1 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
11692D	28480	9N5985-01-024-3832	COUPLER,DIRECTIONAL,COAXIAL	DC1NN	4695
SPECIFICATIONS: COUPLING:22 DB FREQUENCY RANGE:2-18 GHZ DIRECTIVITY:30 DB POWER:50W AVG;250W PEAK VSWR:PRI LINE,1.3;SEC LINE,1.4 CONNECTOR:N (F) DIMENSIONS:(INCHES)16L X 1W X 5.3H APPROX WEIGHT:(POUNDS)6 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
1412-9410	24655	1H6625-00-465-6861	CAPACITOR,DECADE	CP1MN	4624
SPECIFICATIONS: RANGE:50 PF TO 1.11115 MFD IN 100 PF STEPS ACCURACY:+/-(0.5%+5 PF) AT 1 KHZ VOLTAGE:500V (DC OR PEAK)UP TO 35 KHZ RANGE SELECTOR:FIVE ROTARY SWITCHES CONNECTOR:FOUR BINDING POSTS DIMENSIONS:(INCHES) 17.25W X 3.5H X 6.0D APPROX WEIGHT:(POUNDS) 8.5 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX D

STANDARD EQUIPMENT TO SPECIFICATIONS

STANDARD EQUIPMENT	FSCM	ICP/NSN	NOUN NAME	GMG	SCAT
1425-4	93459	1H6930-01-140-4985	TERMINATION,COAXIAL	TM1MN	NONE
SPECIFICATIONS: FREQUENCY RANGE:DC-12.4 GHZ POWER:10W AVG;10 KW PEAK IMPEDANCE:50 OHM NOM VSWR:1.3 MAX CONNECTOR:N (M),FOR N (F) ORDER MODEL 1425-3 DIMENSIONS:(INCHES) 3.3L X 1 DIA APPROX WEIGHT:(OUNCHES) 4 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
1433-9704	24655	9N6625-00-173-5441	RESISTOR,DECADE	RE1GF	4639
SPECIFICATIONS: RANGE:0-11,110 OHM;1 OHM INCR;4 DECADES ACCURACY:+/-0.01%+0.002 OHM MAX CURRENT:0.023-0.8A DEPENDENT ON RESISTANCE ZERO RESISTANCE:0.001 OHM PER DECADE RESISTOR TYPE:WIRE WOUND CONNECTORS:BINDING POSTS DIMENSIONS:(INCHES) 3.5H X 12.3W X 5D APPROX WEIGHT:(POUNDS)5.5 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
1433-9706	24655	&&6625-00-235-6308	RESISTOR,DECADE	RE1KJ	NONE
SPECIFICATIONS: RANGE:0-111,100 OHM;10 OHM INCR;4 DECADES ACCURACY:+/-0.01%+0.002 OHM MAX CURRENT:0.007-0.25A DEPENDENT ON RESISTANCE ZERO RESISTANCE:0.001 OHM PER DECADE RESISTOR TYPE:WIRE WOUND CONNECTORS:BINDING POSTS DIMENSIONS:(INCHES) 3.5H X 12.3W X 5D APPROX WEIGHT:(POUNDS)4.8 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
1433-9714	24655	1H6625-00-463-4011	RESISTOR,DECADE	RE1GM	4634
SPECIFICATIONS: RANGE:0-111,110 OHM;1 OHM INCR;5 DECADES ACCURACY:+/-0.01%+0.002 OHM MAX CURRENT:0.007-0.8A DEPENDENT ON RESISTRANCE ZERO RESISTANCE:0.001 OHM PER DECADE RESISTOR TYPE:WIRE WOUND CONNECTORS:BINDING POSTS DIMENSIONS:(INCHES) 3.5H X 14.8W X 5D APPROX WEIGHT:(POUNDS)6.5 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
1433-9722	24655	1H6625-00-947-7534	RESISTOR,DECADE	RE1DN	4630
SPECIFICATIONS: RANGE:0-111,111 OHM;0.1 OHM INCR;6 DECADES ACCURACY:+/-0.01%+0.002 OHM MAX CURRENT:0.007-1.6A DEPENDENT ON RESISTANCE ZERO RESISTANCE:0.001 OHM PER DECADE RESISTOR TYPE:WIRE WOUND CONNECTORS:BINDING POSTS DIMENSIONS:(INCHES) 3.5H X 17.3W X 5D APPROX WEIGHT:(POUNDS)8.5 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX D

STANDARD EQUIPMENT TO SPECIFICATIONS

STANDARD EQUIPMENT	FSCM	ICP/NSN	NOUN NAME	GMG	SCAT
1433-9724	24655	1H6625-00-031-3521	RESISTOR,DECADE	RE1GY	4636
SPECIFICATIONS: RANGE:0-1,111,110 OHM;1 OHM INCR;6 DECADES ACCURACY:+/-0.01%+0.002 OHM MAX CURRENT:0.0023-0.8A DEPENDENT ON RESISTANCE ZERO RESISTANCE:0.001 OHM PER DECADE RESISTOR TYPE:WIRE WOUND CONNECTORS:BINDING POSTS DIMENSIONS:(INCHES) 3.5H X 17.3W X 5D APPROX WEIGHT:(POUNDS)8.5 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
1433-9726	24655	1H6625-00-140-8183	RESISTOR,DECADE	RE1KT	4637
SPECIFICATIONS: RANGE:0-11,111,110 OHM;10 OHM INCR;6 DECADES ACCURACY:+/-0.01%+0.002 OHM MAX CURRENT:0.0007-0.25A DEPENDENT ON RESISTANCE ZERO RESISTANCE:0.001 OHM PER DECADE RESISTOR TYPE:WIRE WOUND CONNECTORS:BINDING POSTS DIMENSIONS:(INCHES) 3.5H X 17.3W X 5D APPROX WEIGHT:(POUNDS)7 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
1433-9729	24655	1H6625-01-205-0820	RESISTOR,DECADE	RE1AN	NONE
SPECIFICATIONS: RANGE:0:111,111.1 OHM;0.01 OHM INCR;7 DECADES ACCURACY:+/-0.01%+0.002 OHM MAX CURRENT:0.007-4A DEPENDENT ON FREQUENCY ZERO RESISTANCE:0.001 OHM PER DECADE RESISTOR TYPE:WIRE WOUND CONNECTIONS:BINDING POSTS DIMENSIONS:(INCHES) 5.3 H X 17.3W X 5D APPROX WEIGHT:(POUNDS) 8.8 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
1433-9731	24655	1H6625-00-480-0950	RESISTOR,DECADE	RE1DY	NONE
SPECIFICATIONS: RANGE:0-1,111,111 OHM;0.1 OHM INCR;7 DECADES ACCURACY:+/-0.01%+0.002 OHM MAX CURRENT:0.0023-4A DEPENDENT ON RESISTANCE ZERO RESISTANCE:0.001 OHM PER DECADE RESISTOR TYPE:WIRE WOUND CONNECTORS:BINDING POSTS DIMENSIONS:(INCHES) 5.3H X 17.3W X 5D APPROX WEIGHT:(POUNDS)10.3 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
1491-9704	24655	1H6625-00-251-1158	INDUCTOR,DECADE	LN1NN	NONE
SPECIFICATIONS: RANGE:0-11.1H IN 0.001H STEPS ZERO INDUCTANCE:1 UH APPROX VOLTAGE:500V RMS RANGE SELECTOR:FIVE ROTARY SWITCHES CONNECTOR:THREE BINDING POSTS DIMENSIONS:(INCHES)7L X 17W X 9H APPROX WEIGHT:(POUNDS)23 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX D

STANDARD EQUIPMENT TO SPECIFICATIONS

STANDARD EQUIPMENT	FSCM	ICP/NSN	NOUN NAME	GMG	SCAT
1506A	93459	9V6625-00-261-5033	DIVIDER,POWER	DP1NN	4679
SPECIFICATIONS: FREQUENCY RANGE:DC-18 GHZ VSWR:1.25,DC-10 GHZ;1.35,10-18 GHZ POWER:1W AVG;1 KW PEAK CONNECTOR:N (M-F) INSERTION LOSS:6 DB NOM OUTPUT PHASE DIFFERENCE:0 DEGREES NOM DIMENSIONS:(INCHES)1.6L X 1.8W APPROX WEIGHT:(OUNCES)5 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
153B/403SD-001	25965	7G6625-01-197-9866	CONVERTER,FREQUENCY,AC	CF1NN	4084
SPECIFICATIONS: OUTPUT:150 VA,0-130V LINE-NEUTRAL,45 HZ TO 10 KHZ INPUT:0.5 KVA,117V OR 230V,3 PHASE, 47-63 HZ PHASE ANGLE:120 DEGREES +/-1 DEGREE C FREQUENCY TEMP COEFF:+/-0.02% DEGREE C DIMENSIONS:(INCHES) 19L X16.5W X 5.3H APPROX WEIGHT:(POUNDS)70 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
1571-9831	13850	9G6110-00-087-4771	REGULATOR,LINE	RACAA	4802
SPECIFICATIONS: INPUT:115 VAC +/-10%;57-63 HZ OUTPUT:103-127 VAC VARIABLE,CURRENT 50A KVA RATING:5.8 CORRECTION RATE:2.5 HZ +1.5 HZ/V,GIVEN IN HZ OF THE LINE FREQUENCY REGULATION:+/-0.25% DIMENSIONS:(INCHES)7H X 19W X 12D APPROX WEIGHT:(POUNDS)53 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
197B	28480	6A6720-01-104-3402	CAMERA,OSCILLOSCOPE	CS1AB	NONE
SPECIFICATIONS: LENS SIZE:75 MM LENS APERATURE(SPEED):F/1.9 F STOP RANGE:F/1.9 TO F/16 FIELD OF VIEW:REDUCTION RATIO CONTROL SHUTTER SPEED:1/30-4 SEC BULB & TIME,SYNC CONTACTS POWER:SELECT SWITCH 115/230 VAC +/-10%,48-66 HZ FOCUS:SPLIT IMAGE,ADJUSTABLE WITH LOCK FILM:POLAROID PACK BACK DIMENSIONS:(INCHES)10.5H X 7.6W X 14D APPROX WEIGHT:(POUNDS)10 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
2-10	93459	1H6625-01-017-1278	ATTENUATOR,FIXED,COAXIAL	AT1JN	4916
SPECIFICATIONS: ATTENUATION:10 DB +/-0.5 DB FREQUENCY RANGE:DC-18 GHZ IMPEDANCE:50 OHM NOM POWER:5W AVG;1 KW PEAK VSWR:1.15,DC-4 GHZ;INCR TO 1.40,12.4-18 GHZ CONNECTOR:N (M-F) DIMENSIONS:(INCHES)2.3L X 0.8 DIA APPROX WEIGHT:(OUNCES)2.6 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					

Source: https://assist.dla.mil -- Downloaded: 202640-26T13:40Z
Check the source to verify that this is the currentversion before use.

APPENDIX D

STANDARD EQUIPMENT TO SPECIFICATIONS

STANDARD EQUIPMENT	FSCM	ICP/NSN	NOUN NAME	GMG	SCAT
2-20	93459	1H6625-01-017-1276	ATTENUATOR,FIXED,COAXIAL	AT1NY	4917
SPECIFICATIONS: ATTENUATION:20 DB +/-0.5 DB FREQUENCY RANGE:DC-18 GHZ IMPEDANCE:50 OHM NOM POWER:5W AVG;1 KW PEAK VSWR:1.15,DC-4 GHZ;INCR TO 1.40,12.4-18 GHZ CONNECTOR:N (M-F) DIMENSIONS:(INCHES)2.3L X 0.8 DIA APPROX WEIGHT:(OUNCES)2.6 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
2-3	93459	1H6625-01-020-6032	ATTENUATOR,FIXED,COAXIAL	AT1AM	4924
SPECIFICATIONS: ATTENUATION:3 DB +/-0.3 DB FREQUENCY RANGE:DC-18 GHZ IMPEDANCE:50 OHM NOM POWER:5W AVG;1 KW PEAK VSWR:1.15,DC-4 GHZ;INCR TO 1.40,12.4-18 GHZ CONNECTOR:N (M-F) DIMENSIONS:(INCHES)2.3L X 0.8 DIA APPROX WEIGHT:(OUNCES)2.6 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
2-30	93459	1H6625-01-014-3463	ATTENUATOR,FIXED,COAXIAL	AT1SN	4918
SPECIFICATIONS: ATTENUATION:30 DB +/-1 DB FREQUENCY RANGE:DC-18 GHZ IMPEDANCE:50 OHM NOM POWER:5W AVG,1 KW PEAK VSWR:1.15,DC-4 GHZ,INCR TO 1.40,12.4-18 GHZ CONNECTOR:N (M-F) DIMENSIONS:(INCHES)2.3L X 0.8 DIA APPROX WEIGHT:(OUNCES)2.6 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
2-3414-30	09992	9N5985-00-999-8095	ATTENUATOR,VARIABLE,COAXIAL	AT6FN	4895
SPECIFICATIONS: ATTENUATION:30 DB MAX FREQUENCY RANGE:0.8-2.5 GHZ VSWR:1.5 AT 50 OHM NOM POWER:10W AVG INSERTION LOSS:0.2 DB CONNECTOR:N (F-F) DIMENSIONS:(INCHES)5D X 1H APPROX WEIGHT:(POUNDS)1.8 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
2-40	93459	1H6625-01-014-3464	ATTENUATOR,FIXED,COAXIAL	AT1WN	4919
SPECIFICATIONS: ATTENUATION:40 DB +/-1 DB FREQUENCY RANGE:DC-18 GHZ IMPEDANCE:50 OHM NOM POWER:5W AVG;1 KW PEAK VSWR:1.15,DC-4 GHZ;INCR TO 1.40,12.4-18 GHZ CONNECTOR:N (M-F) DIMENSIONS:(INCHES)2.7L X 0.8 DIA APPROX WEIGHT:(OUNCES)3.6 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					

Source: https://assist.dla.mil -- Downloaded: 202610-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX D

STANDARD EQUIPMENT TO SPECIFICATIONS

STANDARD EQUIPMENT	FSCM	ICP/NSN	NOUN NAME	GMG	SCAT
2-6	93459	1H6625-01-017-1277	ATTENUATOR,FIXED,COAXIAL	AT1EY	4915
SPECIFICATIONS: ATTENUATION:6 DB +/-0.3 DB FREQUENCY RANGE:DC-18 GHZ IMPEDANCE:50 OHM NOM POWER:5W AVG;1 KW PEAK VSWR:1.15,DC-4 GHZ;INCR TO 1.40,12.4-18 GHZ CONNECTOR:N (M-F) DIMENSIONS:(INCHES)2.3L X 0.8 DIA APPROX WEIGHT:(OUNCES)2.6 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
2001-6113-00	16179	9N5985-01-064-2513	TERMINATION,COAXIAL	TM1TJ	4950
SPECIFICATIONS: FREQUENCY RANGE:DC-18 GHZ POWER:0.5W AVG IMPEDANCE:50 OHMS NOM VSWR:1.3 MAX CONNECTOR:OSM PLUG DIMENSIONS:(INCHES) 0.61 X 0.3 DIA (APPROX) WEIGHT:(OUNCHES) 0.1 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
2002-6113-00	16179	9N5985-00-192-0138	TERMINATION,COAXIAL	TM1TT	4944
SPECIFICATIONS: FREQUENCY RANGE:DC-18 GHZ POWER:0.5W AVG IMPEDANCE:50 OHM NOM VSWR:1.3 MAX CONNECTOR:OSM JACK DIMENSIONS:(INCHES) 0.61 X 0.3 DIA APPROX WEIGHT:(OUNCES) 0.1 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
210A-3	93459	1H6625-LL-HHE-4111	ATTENUATOR,FIXED,COAXIAL	AT1AB	NONE
SPECIFICATIONS: ATTENUATION:3 DB +/- 0.2 DB FREQUENCY RANGE:0.6-18 GHZ IMPEDANCE:50 OHM NOM POWER:5W AVG; 10 KW PEAK VSWR:1.3 MAX CONNECTOR:N (M-F) DIMENSIONS:(INCHES)2.4L X 0.8 DIA APPROX WEIGHT:(OUNCES)8.0 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
214	00443	1H6625-00-395-0779	DETECTOR,RF,TUNABLE,WAVEGUIDE	DE5AA	NONE
SPECIFICATIONS: FREQUENCY RANGE:2.6-3.95 GHZ WAVEGUIDE:WR284 FLANGE:UG-53/U,BRASS (COVER) CONNECTOR:BNC (F) CRYSTAL:1N21 DIMENSIONS:(INCHES)9L X 3W X 1.5H APPROX WEIGHT:(POUNDS)4 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX D

STANDARD EQUIPMENT TO SPECIFICATIONS

STANDARD EQUIPMENT	FSCM	ICP/NSN	NOUN NAME	GMG	SCAT
24-6-34	93459	1H6625-LL-HHE-8021	ATTENUATOR,FIXED,COAXIAL	AT1AC	NONE
SPECIFICATIONS: ATTENUATION:6DB,DC-4GHZ +/-0.4DB.4-8GHZ +/-0.75DB FREQUENCY RANGE:DC-8 GHZ IMPEDANCE:50 OHM NOM POWER:50W AVG,5 KW PEAK,MID IN HORIZONTAL PLANE DIMENSIONS:(INCHES)4.44L X 1.64 DIA APPROX CONNECTOR:N (M-F) DIMENSIONS:(INCHES)4.44LX 1.64 DIA APPROX WEIGHT:(OUNCES) 10 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
240C	12697	1H6625-00-585-4915	RESISTOR,DECADE	RE1GT	4635
SPECIFICATIONS: RANGE:1-999,999 OHMS,6 DECADES,ONE OHM INCREMENTS ACCURACY:+/-5%,DECADE NO.1,+/-2%,DECADES 2-6 MAX CURRENT:0.005-5A DEPENDENT ON RESISTANCE ZERO RESISTANCE:<0.2 OHM RESISTOR TYPE:WIRE WOUND CONNECTORS:BINDING POSTS DIMENSIONS:(INCHES)131 X 8.5W X 5.8H APPROX WEIGHT:(POUNDS)11.5 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
3000-10	99899	9N5985-00-816-4287	COUPLER,DIRECTIONAL,COAXIAL	DC1AA	4880
SPECIFICATIONS: COUPLING:10 DB FREQUENCY RANGE:225-460 MHZ DIRECTIVITY:30 DB MIN POWER:200W AVG;10 KW PEAK VSWR:PRI LINE,1.15;SEC LINE,1.1 CONNECTOR:N (F) DIMENSIONS:(INCHES)12.2L X 0.9W X 2.9H APPROX WEIGHT:(POUNDS)1.9 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
3002-20	99899	9N5985-00-578-5747	COUPLER,DIRECTIONAL,COAXIAL	DC1JM	4885
SPECIFICATIONS: COUPLING:20 DB FREQUENCY RANGE:0.95-2 GHZ DIRECTIVITY:27 DB POWER:500W AVG;10 KW PEAK VSWR:PRI LINE,1.15;SEC LINE,1.3 CONNECTOR:N (F) DIMENSIONS:(INCHES)5.5L X 0.9W X 2.9H APPROX WEIGHT:(POUNDS)1 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
3003-20	99899	9N5985-00-882-8654	COUPLER,DIRECTIONAL,COAXIAL	DC1JQ	4887
SPECIFICATIONS: COUPLING:20 DB FREQUENCY RANGE:2-4 GHZ DIRECTIVITY:27 DB POWER:500W AVG;10 KW PEAK VSWR:PRI LINE,1.15;SEC LINE,1.2 CONNECTOR:N (F) DIMENSIONS:(INCHES)5.5L X 0.9W X 2.9H APPROX WEIGHT:(POUNDS)1 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX D

STANDARD EQUIPMENT TO SPECIFICATIONS

STANDARD EQUIPMENT	FSCM	ICP/NSN	NOUN NAME	GMG	SCAT
3004-10	99899	9N5985-00-788-6962	COUPLER,DIRECTIONAL,COAXIAL	DC1AM	4888
SPECIFICATIONS: COUPLING:10 DB FREQUENCY RANGE:4-10 GHZ DIRECTIVITY:20 DB POWER:200W AVG;10 KW PEAK VSWR:PRI LINE,1;SEC LINE,1.3 CONNECTOR:N (F) DIMENSIONS:(INCHES)6.5L X 0.9W X 2.9H APPROX WEIGHT:(POUNDS)1 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
3004-20	99899	9N5985-00-714-3247	COUPLER,DIRECTIONAL,COAXIAL	DC1JT	4889
SPECIFICATIONS: COUPLING:20 DB FREQUENCY RANGE:4-10 GHZ DIRECTIVITY:17 DB POWER:500W AVG;10 KW PEAK VSWR:PRI LINE,1.2;SEC LINE,1.3 CONNECTOR:N (F) DIMENSIONS:(INCHES)6.5L X 0.9W X 2.9H APPROX WEIGHT:(POUNDS)1 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
3040B-20	99899	1H5985-00-067-6750	COUPLER,DIRECTIONAL,COAXIAL	DC1JC	4881
SPECIFICATIONS: COUPLING:20 DB FREQUENCY RANGE:0.24-0.5 GHZ DIRECTIVITY:20 DB POWER:500W AVG;10 KW PEAK VSWR:PRI LINE,1.1;SEC LINE,1.2 CONNECTOR:N (F) DIMENSIONS:(INCHES)13.6L X 0.9W X 2.9H APPROX WEIGHT:(POUNDS)2 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
3041-10	99899	1H5985-01-039-5404	COUPLER,DIRECTIONAL,COAXIAL	DC1AC	4882
SPECIFICATIONS: COUPLING:10 DB FREQUENCY RANGE:0.5-1 GHZ DIRECTIVITY:20 DB POWER:200W AVG;10 KW PEAK VSWR:PRI LINE,1.1;SEC LINE,1.2 CONNECTOR:N (F) DIMENSIONS:(INCHES)11.6L X 0.9W X 2.8H APPROX WEIGHT:(POUNDS)2 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
3041-20	99899	1R5985-00-757-0549	COUPLER,DIRECTIONAL,COAXIAL	DC1JF	4878
SPECIFICATIONS: COUPLING:20 DB FREQUENCY RANGE:0.5-1 GHZ DIRECTIVITY:20 DB POWER:500W AVG;10 KW PEAK VSWR:PRI LINE,1.1;SEC LINE,1.2 CONNECTOR:N (F) DIMENSIONS:(INCHES)11.6L X 0.9W X 2.8H APPROX WEIGHT:(POUNDS)2 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					

Source: https://assist.dla.mil -- Downloaded: 202640-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX D

STANDARD EQUIPMENT TO SPECIFICATIONS

STANDARD EQUIPMENT	FSCM	ICP/NSN	NOUN NAME	GMG	SCAT
3042B-10	99899	9N5985-00-465-8112	COUPLER,DIRECTIONAL,COAXIAL	DC1AF	4884

SPECIFICATIONS: COUPLING:10 DB
FREQUENCY RANGE:0.92-2.2 GHZ
DIRECTIVITY:20 DB MIN
POWER:200W AVG;10 KW PEAK
VSWR:PRI LINE,1.10;SEC LINE,1.20
CONNECTOR:N (F)
DIMENSIONS:(INCHES)7.5L X 3W X 1.4H APPROX
WEIGHT:(POUNDS)1.25 APPROX

CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.

3043B-10	99899	1H6625-01-065-5289	COUPLER,DIRECTIONAL,COAXIAL	DC1AJ	4886

SPECIFICATIONS: COUPLING:10 DB
FREQUENCY RANGE:1.7-4.2 GHZ
DIRECTIVITY:20 DB MIN
POWER:200W AVG;10 KW PEAK
VSWR:PRI LINE,1.15;SEC LINE,1.20
CONNECTOR:N (F)
DIMENSIONS:(INCHES)4.1L X 2.1W X 1.4H APPROX
WEIGHT:(POUND)1.0 APPROX

CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.

3043B-30	99899	9N5985-00-450-8802	COUPLER,DIRECTIONAL,COAXIAL	DC1SA	4681

SPECIFICATIONS: COUPLING:30 DB
FREQUENCY RANGE:1.7-4.2 GHZ
DIRECTIVITY:20 DB
POWER:500W AVG;10 KW PEAK
VSWR:PRI LINE,1.15;SEC LINE,1.2
CONNECTOR:N (F)
DIMENSIONS:(INCHES)5.6L X 0.9W X 4.9H APPROX
WEIGHT:(POUNDS)1 APPROX

CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.

3045C-10	99899	1R5985-00-604-8604	COUPLER,DIRECTIONAL,COAXIAL	DC1AT	4693

SPECIFICATIONS: COUPLING:10 DB
FREQUENCY RANGE:7-12.4 GHZ
DIRECTIVITY:15 DB MIN
POWER:100W AVG;10 KW PEAK
VSWR:PRI LINE,1.3;SEC LINE,1.3
CONNECTOR:N (F)
DIMENSIONS:(INCHES)7L X 0.9W X 2.9H APPROX
WEIGHT:(OUNCES)12 APPROX

CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.

3060-20	99899	9N5985-00-492-7921	COUPLER,DIRECTIONAL,COAXIAL	DC1JA	4883

SPECIFICATIONS: COUPLING:20 DB
FREQUENCY RANGE:10-200 MHZ
DIRECTIVITY:20 DB MIN
POWER:1W AVG;100W PEAK
VSWR:PRI LINE,1.2;SEC LINE,1.2
CONNECTOR:N (F)
DIMENSIONS:(INCHES)3L X 1W X 1.75H APPROX
WEIGHT:(OUNCES)3.2 APPROX

CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX D

STANDARD EQUIPMENT TO SPECIFICATIONS

STANDARD EQUIPMENT	FSCM	ICP/NSN	NOUN NAME	GMG	SCAT
3122	99899	1H5895-01-079-0537	DETECTOR,RF,DIRECTIONAL	DE1NN	NONE

SPECIFICATIONS: FREQUENCY RANGE:1-18 GHZ
FREQUENCY RESPONSE:+/-1.5 DB
IMPEDANCE:15 OHM OUTPUT,SHUNTED BY 10 PF
VSWR:1.5 MAX
CONNECTOR:N (F),BNC (F)
DETECTOR OUTPUT POLARITY:NEGATIVE
DIMENSIONS:(INCHES)3.1L X 3.6W APPROX
WEIGHT:(OUNCES)2.7 APPROX

CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.

314	00443	1H6625-01-039-5259	DETECTOR,RF,TUNABLE,WAVEGUIDE	DE5AB	NONE

SPECIFICATIONS: FREQUENCY RANGE:3.95-5.85 GHZ
WAVEGUIDE:WR187
FLANGE:UG-149A/U,BRASS (COVER)
CONNECTOR:BNC (F)
CRYSTAL:1N23
DIMENSIONS:(INCHES)10.2L X 2W X 1H APPROX
WEIGHT:(POUNDS)7 APPROX

CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.

3202	88865	1H4931-00-178-1052	FILTER,VARIABLE	FL4TN	4704

SPECIFICATIONS: FREQUENCY RANGE:20 HZ-2 MHZ,VARIABLE
FUNCTION:LOW,HIGH,BANDPASS & BAND REJECT
BANDWIDTH:VARIABLE WITHIN CUT-OFF FREQ LIMITS
INPUT:3V RMS TO 2 MHZ,LP MODE(AC+DC)</=4.2 PEAK
OUTPUT:3V RMS;10MA;INT IMPEDANCE 50 OHM NOM
POWER REQUIREMENTS:105-125/210-250V,50-400 HZ,15W
DIMENSIONS:(INCHES)8.6L X 15.3W X 5.3H APPROX
WEIGHT:(POUNDS)9 APPROX

CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.

3202B-10	99899	9N5985-00-412-2986	COUPLER,DIRECTIONAL,COAXIAL	DC1AQ	4890

SPECIFICATIONS: COUPLING:10 DB
FREQUENCY RANGE:1-12.4 GHZ
DIRECTIVITY:15 DB 1-8 GHZ;12 DB 8-12.4 GHZ
POWER:20W AVG;3 KW PEAK
VSWR:PRI LINE,1.35;SEC LINE,1.5
CONNECTOR:N (F)
DIMENSIONS:(INCHES)5.4L X 0.7W X 2H APPROX
WEIGHT:(OUNCES)4.5 APPROX

CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.

3222-16	99899	1H5985-01-081-7855	COUPLER,DIRECTIONAL,COAXIAL	DC1EN	4877

SPECIFICATIONS: COUPLING:16 DB
FREQUENCY RANGE:1-18 GHZ
DIRECTIVITY:1-12.4 GHZ 15 DB;12.4-18 GHZ 12 DB
POWER:20W AVG;3 KW PEAK
VSWR:PRI LINE,1.4;SEC LINE,1.5
CONNECTOR:N (F)
DIMENSIONS:(INCHES)5.6L X 1.8W X 0.5H APPROX
WEIGHT:(OUNCES)3.4 APPROX

CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX D

STANDARD EQUIPMENT TO SPECIFICATIONS

STANDARD EQUIPMENT	FSCM	ICP/NSN	NOUN NAME	GMG	SCAT
355C	28480	1H5985-00-993-1377	ATTENUATOR,STEP	AT4AN	4662
SPECIFICATIONS: ATTENUATION:0-12 DB IN 1 DB STEPS FREQUENCY RANGE:DC-1 GHZ IMPEDANCE:50 OHM NOM POWER:0.5W AVG;350W PEAK VSWR:1.5 MAX CONNECTOR:BNC (F-F) DIMENSIONS:(INCHES)6L X 2.6W X 2.8H APPROX WEIGHT:(POUNDS)3 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
355D	28480	9N5985-00-957-1860	ATTENUATOR,STEP	AT4UN	4672
SPECIFICATIONS: ATTENUATION:0-120 DB IN 10 DB STEPS FREQUENCY RANGE:DC-1 GHZ IMPEDANCE:50 OHM NOM POWER:0.5W AVG;350W PEAK VSWR:1.5 MAX CONNECTOR:BNC (F-F) DIMENSIONS:(INCHES)6L X 2.6W X 2.8H APPROX WEIGHT:(POUNDS)3 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
360A	28480	9N5915-00-503-1787	FILTER,LOWPASS	FL2AN	4730
SPECIFICATIONS: CUT-OFF FREQUENCY:700 MHZ INSERTION LOSS:<1 DB BELOW 630 MHZ REJECTION:>50 DB AT 875 MHZ IMPEDANCE:50 OHM NOM VSWR:<1.6 AT 600-800 MHZ CONNECTOR:N (M-F) DIMENSIONS:(INCHES)10.9L X 1 DIA APPROX WEIGHT:(POUNDS)2 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
360B	28480	9N5915-00-686-8922	FILTER,LOWPASS	FL2FN	4731
SPECIFICATIONS: CUT-OFF FREQUENCY:1200 MHZ INSERTION LOSS:<1 DB BELOW 1080 MHZ REJECTION:>50 DB AT 1500 MHZ IMPEDANCE:50 OHM NOM VSWR:<1.6 AT 1100-1300 MHZ CONNECTOR:N (M-F) DIMENSIONS:(INCHES)7.2L X 1 DIA APPROX WEIGHT:(POUNDS)2 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
360C	28480	9N5915-00-503-0533	FILTER,LOWPASS	FL2MN	4732
SPECIFICATIONS: CUT-OFF FREQUENCY:2200 MHZ INSERTION LOSS:<1 DB BELOW 1980 MHZ REJECTION:>50 DB AT 2750 MHZ IMPEDANCE:50 OHM NOM VSWR:<1.6 UP TO 2000 MHZ CONNECTOR:N (M-F) DIMENSIONS:(INCHES)10.7L X 1 DIA APPROX WEIGHT:(POUNDS)2 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX D

STANDARD EQUIPMENT TO SPECIFICATIONS

STANDARD EQUIPMENT	FSCM	ICP/NSN	NOUN NAME	GMG	SCAT
360D	28480	9N5915-00-804-5302	FILTER,LOWPASS	FL2TN	4733
SPECIFICATIONS: CUT-OFF FREQUENCY:4100 MHZ INSERTION LOSS:<1 DB BELOW 3690 MHZ REJECTION:>50 DB AT 5125 MHZ IMPEDANCE:50 OHM NOM VSWR:<1.6 3800-4400 MHZ CONNECTOR:N (M-F) DIMENSIONS:(INCHES)7.3L X 1 DIA APPROX WEIGHT:(POUNDS)2 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
371BNM	99899	1H6625-00-970-3685	TERMINATION,COAXIAL	TM1YN	4685
SPECIFICATIONS: FREQUENCY RANGE:2-18 GHZ POWER:10W AVG;5 KW PEAK IMPEDANCE:50 OHM NOM VSWR:1.09 MAX CONNECTOR:N,SPECIFY (M)OR(F) DIMENSIONS:(INCHES) 7.3L X 1 DIA APPROX WEIGHT:(OUNCES) 6 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
3750	88865	1H6625-00-001-2376	FILTER,VARIABLE	FL4JN	4703
SPECIFICATIONS: FREQUENCY RANGE:0.02-20 KHZ,VARIABLE FUNCTION:LOW,HIGH,BANDPASS & BAND REJECT BANDWIDTH:VARIABLE WITHIN CUT-OFF FREQ LIMITS INPUT:+/-15V PEAK AT 0 DB,+/-1.5V PEAK AT 20 DB OUTPUT:15V PEAK;3MA PEAK;INT IMPEDANCE 50 OHM NOM POWER REQUIREMNTS:105-125/210-250V,50-400 HZ,10W DIMENSIONS:(INCHES)16.6L X 13.7W X 5.5H APPROX WEIGHT:(POUNDS)26 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
376BNF	99899	9N5985-00-241-3518	TERMINATION,COAXIAL	TM1FN	4684
SPECIFICATIONS: FREQUENCY RANGE:DC-12.4 GHZ POWER:40W AVG,7.5 KW PEAK IMPEDANCE:50 OHM NOM VSWR:1.09 MAX CONNECTOR:M,SPECIFY (M)OR(F) DIMENSIONS:(INCHES) 1.6L X 4.9W APPROX WEIGHT:(OUNCES)10 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
4M-10	93459	9N5985-00-258-0123	ATTENUATOR,FIXED,COAXIAL	AT1JY	4694
SPECIFICATIONS: ATTENUATION:10 DB +/-0.5 DB FREQUENCY RANGE:DC-18 GHZ IMPEDANCE:50 OHM NOM POWER:2W AVG;500W PEAK VSWR:1.15,DC-4 GHZ;INCR TO 1.35,12.4-18 GHZ CONNECTOR:SMA (M-F) ADD PREFIX M OR F TO MODEL NO. EXAMPLE:FOR FEMALE ORDER F4M-10 DIMENSIONS:(INCHES)1.2L X 0.4 DIA APPROX WEIGHT:(OUNCES)0.35 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					

Source: https://assist.dla.mil -- Downloaded: 202610-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX D

STANDARD EQUIPMENT TO SPECIFICATIONS

STANDARD EQUIPMENT	FSCM	ICP/NSN	NOUN NAME	GMG	SCAT
4M-3	93459	1H6625-LL-HHE-1799	ATTENUATOR,FIXED,COAXIAL	AT1AT	4690
SPECIFICATIONS: ATTENUATION:3 DB +/-0.3 DB FREQUENCY RANGE:DC-18 GHZ IMPEDANCE:50 OHM NOM POWER:2W AVG,500W PEAK VSWR:1.15,DC-4 GHZ;INCR TO 1.35,12.4-18 GHZ CONNECTOR:SMA (M-F) ADD PREFIX M OR F TO MODEL NO. EXAMPLE:FOR FEMALE ORDER F4M-3 DIMENSIONS:(INCHES)1.2L X 0.4 DIA APPROX WEIGHT:(OUNCES)0.35 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
4M-3-6-10	93459	9N6625-01-026-2335	ATTENUATOR,FIXED,COAXIAL,SET	AT2NN	NONE
SPECIFICATIONS: ITEM LISTED AS REFERENCE ONLY REFER TO TYPES 4M-3,4M-6,4M-10 SEPARATELY					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
4M-6	93459	1H6625-01-015-2356	ATTENUATOR,FIXED,COAXIAL	AT1EN	4691
SPECIFICATIONS: ATTENUATION:6 DB +/-0.3 DB FREQUENCY RANGE:DC-18 GHZ IMPEDANCE:50 OHM NOM POWER:2W AVG;500W PEAK VSWR:1.15,DC-4 GHZ;INCR TO 1.35,12.4-18 GHZ CONNECTOR:SMA (M-F) ADD PREFIX M OR F TO MODEL NO. EXAMPLE:FOR FEMALE ORDER F4M-6 DIMENSIONS:(INCHES)1.2L X 0.4 DIA APPROX WEIGHT:(OUNCES)0.35 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
4016D-10	99899	9N5985-01-041-8132	COUPLER,DIRECTIONAL,COAXIAL	DC1AY	4891
SPECIFICATIONS: COUPLING:10 DB +/-1 DB FREQUENCY RANGE:12.4-18 GHZ DIRECTIVITY:15 DB POWER:50W AVG,1 KW PEAK VSWR:PRI LINE:1.35,SEC LINE 1.4 CONNECTOR:SMA (F) DIMENSIONS:(INCHES)1.75L X 0.37W X 0.88H APPROX WEIGHT:(OUNCES)0.63 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
4055-10	99899	9N6625-00-261-7749	COUPLER,DIRECTIONAL,COAXIAL	DC1AW	NONE
SPECIFICATIONS: COUPLING:10 DB FREQUENCY RANGE:7.5-16 GHZ DIRECTIVITY:12 DB POWER:50W AVG;1 KW PEAK VSWR:PRI LINE,1.35;SEC LINE,1.4 CONNECTOR:SMA (F) DIMENSIONS:(INCHES)1.75L X 0.4W X 1.25H APPROX WEIGHT:(OUNCES)0.6 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX D

STANDARD EQUIPMENT TO SPECIFICATIONS

STANDARD EQUIPMENT	FSCM	ICP/NSN	NOUN NAME	GMG	SCAT
4055-20	99899	1H5985-01-100-1668	COUPLER,DIRECTIONAL,COAXIAL	DC1JW	NONE
SPECIFICATIONS: COUPLING:20 DB FREQUENCY RANGE:7.5-16 GHZ DIRECTIVITY:15 DB POWER:50W AVG;2 KW PEAK VSWR:PRI LINE,1.35;SEC LINE,1.4 CONNECTOR:SMA (F) DIMENSIONS:(INCHES)1.8L X 0.4W X 1.3H APPROX WEIGHT:(OUNCES)0.6 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
4055-30	99899	1H5985-01-096-6705	COUPLER,DIRECTIONAL,COAXIAL	DC1SN	NONE
SPECIFICATIONS: COUPLING:30 DB FREQUENCY RANGE:7.5-16 GHZ DIRECTIVITY:15 DB POWER:50W AVG;2 KW PEAK VSWR:PRI LINE,1.35;SEC LINE,1.4 CONNECTOR:SMA (F) DIMENSIONS:(INCHES)1.8L X 0.4W X 1.3H APPROX WEIGHT:(OUNCES)0.7 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
407655	80006	1H5915-00-310-1476	FILTER,NOTCH	FL3NN	NONE
SPECIFICATIONS: FREQUENCY RANGE:5.4-5.75 GHZ INSERTION LOSS:0.5 DB AT 5.4-5.75 GHZ REJECTION:>20 DB AT 5.85 GHZ;>30 DB AT 5.88-6 GHZ VSWR:<1.4 AT 5.4-5.75 GHZ POWER RATING:100 KW PEAK WAVEGUIDE:WR187;FLANGE,SPECIAL FGM-100-148 (CHOKE) DIMENSIONS:(INCHES)5.5L X 5.5W X 2.9H APPROX WEIGHT:(POUNDS)5 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
423A	28480	9N6625-00-880-4978	DETECTOR,RF,FIXED,COAXIAL	DE2AA	4353
SPECIFICATIONS: FREQUENCY RANGE:0.01-12.4 GHZ FREQUENCY RESPONSE:+/-0.2 DB TO +/-0.5 DB IMPEDANCE:50 OHM NOM VSWR:1.5 MAX POWER:100 MW MAX CONNECTOR:N (M),BNC (F) DIMENSIONS:(INCHES)2L X 0.5 DIA APPROX WEIGHT:(POUNDS)1 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
432-D	80138	9N5985-00-087-2547	ATTENUATOR,STEP	AT4NA	4661
SPECIFICATIONS: ATTENUATION:0-101 DB IN 1 DB STEPS FREQUENCY RANGE:DC-1 GHZ IMPEDANCE:50 OHM NOM POWER:0.5W MAX VSWR:1.2 DC-500 MHZ & 1.4 0.5-1 GHZ CONNECTOR:BNC (F-F) DIMENSIONS:(INCHES)2L X 9.8W X 2H APPROX WEIGHT:(POUNDS)3 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					

Source: https://assist.dla.mil -- Downloaded: 202610-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX D

STANDARD EQUIPMENT TO SPECIFICATIONS

STANDARD EQUIPMENT	FSCM	ICP/NSN	NOUN NAME	GMG	SCAT
4375G	99899	1H6625-LL-HHE-8020	TERMINATION,COAXIAL	TM1WP	NONE
SPECIFICATIONS: FREQUENCY RANGE:DC-18.0 GHZ POWER RATING:10W AVG,5 KW PEAK IMPEDANCE:50 OHM NOM VSWR:1.05 MAX CONNECTOR:N,FOR ENDS,SPECIFY M=MALE,F=FEMALE DIMENSIONS:(INCHES)1.624L X 1 SQUARE APPROX WEIGHT:(OUNCES)4 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
442-D	80138	9N5905-00-313-9064	ATTENUATOR,STEP	AT4NN	4666
SPECIFICATIONS: ATTENUATION:0-101 DB IN 1 DB STEPS FREQUENCY RANGE:DC-1 GHZ IMPEDANCE:75 OHM NOM POWER:0.5W MAX VSWR:1.2 MAX CONNECTOR:BNC (F-F) DIMENSIONS:(INCHES)2L X 9.8W X 2H APPROX WEIGHT:(POUNDS)3 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
452-C	80138	9Y5985-00-712-8388	ATTENUATOR,STEP	AT4NY	4665
SPECIFICATIONS: ATTENUATION:0-101 DB IN 1 DB STEPS FREQUENCY RANGE:DC-0.5 GHZ IMPEDANCE:90 OHM NOM POWER:1W MAX VSWR:1.2 MAX CONNECTOR:BNC (F-F) DIMENSIONS:(INCHES)2L X 7W X 2H APPROX WEIGHT:(POUNDS)3 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
4609	99899	1H5985-01-025-3902	ADAPTER,WAVEGUIDE TO COAXIAL	AD3YN	4614
SPECIFICATIONS: FREQUENCY RANGE:12.4-18 GHZ VSWR:1.25 MAX WAVEGUIDE:WR62 FLANGE:UG-419/U,BRASS (COVER) CONNECTOR:SMA (F) DIMENSIONS:(INCHES)1L X 1.4W APPROX WEIGHT:(POUNDS)0.3 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
5015V	98095	1H6625-01-224-0215	POWER SUPPLY,DIRECT VOLTAGE	PS1DN	4115
SPECIFICATIONS: OUTPUT:0-50 VDC,0-1.5A,CONTINUOUSLY ADJUSTABLE LOAD EFFECT:<500 UA FOR INPUT VOLTAGES OF 105-125V SOURCE EFFECT:>.005%+1MV FOR LINE VOLTS OF +/-10% DRIFT:CONSTANT VOLTS MODE-<0.01%+5MV PER 24 HOURS DRIFT:CONSTANT CURRENT MODE-<.05%+500 UA PER 24HRS RIPPLE:CONSTANT VOLTS MODE-<1 MV PEAK TO PEAK RIPPLE:CONSTANT CURRENT MODE-<500 UA PEAK TO PEAK FEATURES:CONSTANT VOLTAGE/CURRENT,REMOTE SENSING DIMENSIONS:(INCHES)11.75L X 8.75W X 4.75H APPROX WEIGHT:(POUNDS) 15 APPROX					
THIS EQUIPMENT IS CLASSIFIED AS TYPE III, CLASS 5, STYLE E, AND COLOR R FOR NAVY USE IN ACCORDANCE WITH MIL-T-28800 AS APPLICABLE.					

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX D

STANDARD EQUIPMENT TO SPECIFICATIONS

STANDARD EQUIPMENT	FSCM	ICP/NSN	NOUN NAME	GMG	SCAT
574-10	00443	1H6625-LL-HHE-8018	COUPLER,DIRECTIONAL,WAVEGUIDE	DC2AA	NONE

SPECIFICATIONS: COUPLING:10 DB NOM
FREQUENCY RANGE:7.05-10 GHZ
DIRECTIVITY:40 DB MIN
POWER:10W MAX
FLANGE:UG-51/U BRASE (COVER)
WAVEGUIDE:WR112
VSWR:PRIMARY LINE-1.10 MAX,AUXILIARY LINE 1.20 MAX
DIMENSIONS:(INCHES)19L X 1.75W X 3H APPROX
WEIGHT:(POUNDS)4 APPROX

CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.

574-20	00443	1H6625-LL-HHE-8019	COUPLER,DIRECTIONAL,WAVEGUIDE	DC2NN	NONE

SPECIFICATIONS: COUPLING:20 DB NOM
FREQUENCY RANGE:7.05-10 GHZ
DIRECTIVITY:40 DB MIN
POWER:100W MAX
FLANGE:UG-51/U BRASS (COVER)
WAVEGUIDE:WR112
VSWR:PRIMARY LINE-1.10 MAX,AUXILIARY LINE-1.20 MAX
DIMENSIONS:(INCHES)19L X 1.75W X 3H APPROX
WEIGHT:(POUNDS)4 APPROX

CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.

613-M	77327	1H6625-00-973-1151	DETECTOR,RF,FIXED,COAXIAL	DE2AN	4348

SPECIFICATIONS: FREQUENCY RANGE:1-12 GHZ
FREQUENCY RESPONSE:+/-0.5 DB
IMPEDANCE:50 OHMS NOM
VSWR:1.5 MAX
POWER:100 MW
CONNECTOR:UG-21/U
DIMENSIONS:(INCHES)2L X 0.5 DIA APPROX
WEIGHT:(POUNDS)0.5 APPROX

CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.

616	99899	9N6625-00-424-5066	ADAPTER,WAVEGUIDE TO COAXIAL	AD3AN	4859

SPECIFICATIONS: FREQUENCY RANGE:1.12-1.7 GHZ
VSWR:1.25 MAX
WAVEGUIDE:WR650
FLANGE:UG-417A/U,COPPER ALLOY (COVER)
CONNECTOR:N (F)
DIMENSIONS:(INCHES)5L X 5.5W APPROX
WEIGHT:(POUNDS)2.5 APPROX

CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX D

STANDARD EQUIPMENT TO SPECIFICATIONS

STANDARD EQUIPMENT	FSCM	ICP/NSN	NOUN NAME	GMG	SCAT
6266B	28480	9G6130-00-137-0167	POWER SUPPLY,DIRECT VOLTAGE	PS1BA	4042

SPECIFICATIONS: OUTPUT:0-40V;0-5A
LOAD EFFECT:VOLTS,0.01%+200 UV;AMPS,0.02%+500 UA
SOURCE EFFECT:VOLTS,0.01%+200 UV;AMPS,0.02%+500 UA
DRIFT:VOLTS,0.03%+500 UV;AMPS,0.03%+0.003A
RIPPLE:VOLTS,200 UA;AMPS,0.003A RMS
FEATURES:CONSTANT VOLTS AND CURRENT;REMOTE SENSING
DIMENSIONS:(INCHES)17.5L X 16.8W X 3.3H APPROX
WEIGHT:(POUNDS)34 APPROX

THIS EQUIPMENT IS CLASSIFIED AS TYPE III, CLASS 5, STYLE E, AND COLOR R FOR NAVY USE IN ACCORDANCE WITH MIL-T-28800 AS APPLICABLE.

6274B	28480	7Z6130-00-160-0827	POWER SUPPLY,DIRECT VOLTAGE	PS1FY	NONE

SPECIFICATIONS: OUTPUT:0-60V;0-15A
LOAD EFFECT:VOLTS,0.01%+200 UV;AMPS,0.02%+500 UA
SOURCE EFFECT:VOLTS,0.01%+200 UV;AMPS,0.02%+500 UA
DRIFT:VOLTS,0.03%+0.002V;AMPS,0.03%+0.005A
RIPPLE:VOLTS,200 UV;AMPS,0.005A RMS
FEATURES:CONSTANT VOLTS AND CURRENT;REMOTE SENSING
DIMENSIONS:(INCHES)17.5L X 16.8W X 5H APPROX
WEIGHT:(POUNDS)48 APPROX

THIS EQUIPMENT IS CLASSIFIED AS TYPE III, CLASS 5, STYLE E, AND COLOR R FOR NAVY USE IN ACCORDANCE WITH MIL-T-28800 AS APPLICABLE.

6294A	28480	&&6130-01-062-6739	POWER SUPPLY,DIRECT VOLTAGE	PS1FA	NONE

SPECIFICATIONS: OUTPUT:0-60V;0-1A
LOAD EFFECT:VOLTS,0.01%+0.002V;AMPS,0.01%+250 UA
SOURCE EFFECT:VOLTS,0.01%+0.002V;AMPS,0.01%+250 UA
DRIFT:VOLTS,0.1%+0.0025V;AMPS,0.1%+0.0025A
RIPPLE:VOLTS,200 UV;AMPS,500 UA RMS
FEATURES:CONSTANT VOLTS AND CURRENT;REMOTE SENSING
DIMENSIONS:(INCHES)14.5L X 8.2W X 3.4H APPROX
WEIGHT:(POUNDS)13 APPROX

THIS EQUIPMENT IS CLASSIFIED AS TYPE III, CLASS 5, STYLE E, AND COLOR R FOR NAVY USE IN ACCORDANCE WITH MIL-T-28800 AS APPLICABLE.

6296A	28480	1H6130-01-067-3777	POWER SUPPLY,DIRECT VOLTAGE	PS1FN	NONE

SPECIFICATIONS: OUTPUT:0-60V;0-3A
LOAD EFFECT:VOLTS,0.01%+0.001V;AMPS,0.5%+0.001A
SOURCE EFFECT:VOLTS,0.01%+0.001V;AMPS,0.05%+0.001A
DRIFT:VOLTS,0.1%+0.0025V;AMPS,0.1%+0.0075A
RIPPLE:VOLTS,500 UV;AMPS,0.003A RMS
FEATURES:CONSTANT VOLTS AND CURRENT;REMOTE SENSING
DIMENSIONS:(INCHES)17.1L X 8.2W X 5H APPROX
WEIGHT:(POUNDS)25 APPROX

THIS EQUIPMENT IS CLASSIFIED AS TYPE III, CLASS 5, STYLE E, AND COLOR R FOR NAVY USE IN ACCORDANCE WITH MIL-T-28800 AS APPLICABLE.

Source: https://assist.dla.mil -- Downloaded: 202610-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX D

STANDARD EQUIPMENT TO SPECIFICATIONS

STANDARD EQUIPMENT	FSCM	ICP/NSN	NOUN NAME	GMG	SCAT
6299A	28480	4G6130-00-406-5695	POWER SUPPLY,DIRECT VOLTAGE	PS1HN	4040

SPECIFICATIONS: OUTPUT:0-100V,0-0.75A
LOAD EFFECT:VOLTS 0.01%+0.002V,AMPS 0.01%+250 UA
SOURCE EFFECT:VOLTS 0.01%+0.002V,AMPS 0.01%+250 UA
DRIFT:VOLTS 0.1%+0.0025v,AMPS 0.1%+0.002A
RIPPLE:VOLTS 200 UV,AMPS 500 UA RMS
FEATURES:CONSTANT VOLTS AND CURRENT,REMOTE SENSING
DIMENSIONS(INCHES)14.6L X 8.2W X 3.4H APPROX
WEIGHT:(POUNDS)13 APPROX

THIS EQUIPMENT IS CLASSIFIED AS TYPE III, CLASS 5, STYLE E, AND COLOR R FOR NAVY USE IN ACCORDANCE WITH MIL-T-28800 AS APPLICABLE.

638	99899	9N6625-01-031-1980	HORN,STANDARD GAIN	HN1TN	4011

SPECIFICATIONS: FREQUENCY RANGE:18-26.5 GHZ
GAIN:(MID FREQ VARIATION)1.5 DB/COMPLETE BAND
BEAM WIDTH:28 DEGREES APPROX,EQUAL IN E&H PLANES
VSWR:1.15 MAX
WAVEGUIDE:(INCHES)0.5 X 0.25 APPROX,WR42
FLANGE:UG-595/U,BRASS (COVER)
DIMENSIONS:(INCHES)2.6L X 1.2W X 1.5H APPROX
WEIGHT:(POUNDS)0.2 APPROX

CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.

640	99899	1R5985-00-729-1297	HORN,STANDARD GAIN	HN1MN	NONE

SPECIFICATIONS: FREQUENCY RANGE:8.2-12.4 GHZ
GAIN:(MID FREQ VARIATION)1.5 DB/COMPLETE BAND
BEAM WIDTH:28 DEGREES APPROX,EQUAL IN E&H PLANES
VSWR:1.15 MAX
WAVEGUIDE:(INCHES)1 X 1.5 APPROX,WR90
FLANGE:UG-135/U,ALUMINUM (COVER)
DIMENSIONS:(INCHES)5L X 2.3W X 3H APPROX
WEIGHT:(POUNDS)0.5 APPROX

CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.

6443B	28480	1H6130-00-163-6201	POWER SUPPLY,DIRECT VOLTAGE	PS1KN	NONE

SPECIFICATIONS: OUTPUT:0-120V;0-2.5A
LOAD EFFECT:VOLTS,0.12V;AMPS,0.025A
SOURCE EFFECT:VOLTS,0.06V;AMPS,0.025A
DRIFT:VOLTS,0.1%+0.006V;AMPS,0.025A
RIPPLE:VOLTS,0.24V;AMPS,DEPENDENT ON LOAD
FEATURES:CONSTANT VOLTS AND CURRENT;REMOTE SENSING
DIMENSIONS:(INCHES)17.5L X 16.8W X 3.3H APPROX
WEIGHT:(POUNDS)31 APPROX

THIS EQUIPMENT IS CLASSIFIED AS TYPE III, CLASS 5, STYLE E, AND COLOR R FOR NAVY USE IN ACCORDANCE WITH MIL-T-28800 AS APPLICABLE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX D

STANDARD EQUIPMENT TO SPECIFICATIONS

STANDARD EQUIPMENT	FSCM	ICP/NSN	NOUN NAME	CMG	SCAT
778D	28480	9N5985-00-239-3215	COUPLER,DIRECTIONAL,COAXIAL	DC1JJ	4692
SPECIFICATIONS: COUPLING:20 DB FREQUENCY RANGE:0.1-2 GHZ DIRECTIVITY:30 DB POWER:50W AVG;10 KW PEAK VSWR:PRI LINE,1.1;SEC LINE,1.1 CONNECTOR:N (F) DIMENSIONS:(INCHES)16.8L X 1.8W X 4.4H APPROX WEIGHT:(POUNDS)5 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
80M	70998	9Y5840-00-669-8675	TERMINATION,COAXIAL	TM1SA	NONE
SPECIFICATIONS: FREQUENCY RANGE:DC-4 GHZ POWER RATING:5W CONTINUOUS IMPEDANCE:50 OHM NOM VSWR:1.1 MAX,DC-1 GHZ & 1.2 MAX,1-4 GHZ CONNECTOR:N (M),FOR N (F) ORDER MODEL 80F DIMENSIONS:(INCHES)0.7L X 3.4W APPROX WEIGHT:(OUNCES)4 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
8085	70998	9N5985-00-477-8165	DUMMY LOAD,COAXIAL	DL1NN	NONE
SPECIFICATIONS: FREQUENCY RANGE:DC-3.5 GHZ POWER RATING:50W CW IMPEDANCE:50 OHM NOM VSWR:1.1 MAX,DC-1 GHZ;1.25 MAX,1-3.5 GHZ CONNECTOR:N (M) DIMENSIONS:(INCHES)5L X 1.8W X 1.8H APPROX WEIGHT:(OUNCES)15 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
8135	70998	9N6625-00-773-7311	DUMMY LOAD,COAXIAL	DL1SN	NONE
SPECIFICATIONS: FREQUENCY RANGE:DC-4 GHZ POWER RATING:150W CONTINUOUS IMPEDANCE:50 OHM NOM VSWR:1.1 MAX,DC-1 GHZ;1.2 MAX,1-4 GHZ CONNECTOR:N (F) DIMENSIONS:(INCHES)9.5L X 4W X 6.4H APPROX WEIGHT:(POUNDS)6 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
8164	70998	1H5985-01-024-8193	DUMMY LOAD,COAXIAL	DL1EA	NONE
SPECIFICATIONS: FREQUENCY RANGE:DC-2.5 GHZ POWER RATING:100W CW IMPEDANCE:50 OHM NOM VSWR:1.1 MAX DC-1 GHZ,1.2 MAS 1-2.5 GHZ CONNECTOR:N (F) DIMENSIONS:(INCHES)76 X 2.8W X 1.8H APPROX WEIGHT:(POUNDS)3 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX D

STANDARD EQUIPMENT TO SPECIFICATIONS

STANDARD EQUIPMENT	FSCM	ICP/NSN	NOUN NAME	GMG	SCAT
8201	70998	1H6625-00-994-6797	DUMMY LOAD,COAXIAL	DL1EN	4683
SPECIFICATIONS: FREQUENCY RANGE:DC-2.5 GHZ POWER RATING:500W CONTINUOUS IMPEDANCE:50 OHM NOM VSWR:1.1 MAX,DC-1 GHZ;1.25 MAX,1-2.5 GHZ CONNECTOR:LC (F) DIMENSIONS:(INCHES)16L X 6W X 8.5H APPROX WEIGHT:(POUNDS)20 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
8404	70998	1H6625-01-150-1897	DUMMY LOAD,COAXIAL	DL1JN	4683
SPECIFICATIONS: FREQUENCY RANGE:DC-3 GHZ POWER RATING:600W AVG IMPEDANCE:50 OHM NOM VSWR:1.1 MAX,DC-1 GHZ;1.2 MAX,1-3 GHZ CONNECTOR:N (F) DIMENSIONS:(INCHES)16L X 6W X 8.5H APPROX WEIGHT:(POUNDS)20 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
8470A	28480	1H6625-00-424-4334	DETECTOR,RF,FIXED,COAXIAL	DE2YN	4352
SPECIFICATIONS: FREQUENCY RANGE:0.01-18 GHZ FREQUENCY RESPONSE:+/-0.2 DB TO +/-1 DB IMPEDANCE:50 OHM NOM VSWR:1.7 MAX POWER:100 MW MAX CONNECTOR:APC-7 (M),BNC (F) DIMENSIONS:(INCHES)2L X 0.5 DIA APPROX WEIGHT:(POUNDS)1 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
8472A-001	28480	1H6625-00-291-1039	DETECTOR,RF,FIXED,COAXIAL	DE2NN	4354
SPECIFICATIONS: FREQUENCY RANGE:0.01-12.4 GHZ FREQUENCY RESPONSE:+/-0.2 DB TO +/-1 DB IMPEDANCE:50 OHM NOM VSWR:1.7 MAX POWER:100 MW MAX CONNECTOR:SMA (M),BNC (F) DIMENSIONS:(INCHES)2L X 0.5 DIA APPROX WEIGHT:(POUNDS)1 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
8491A-003	28480	9N5985-00-167-0544	ATTENUATOR,FIXED,COAXIAL	AT1AF	4688
SPECIFICATIONS: ATTENUATION:3 DB +/-0.3 DB FREQUENCY RANGE:DC-12.4 GHZ IMPEDANCE:50 OHM NOM POWER:2W AVG;100W PEAK VSWR:1.2,DC-8 GHZ & 1.3,8-12.4 GHZ CONNECTOR:N (M-F) DIMENSIONS:(INCHES)2.4L X 0.8 DIA APPROX WEIGHT:(OUNCES)6 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX D

STANDARD EQUIPMENT TO SPECIFICATIONS

STANDARD EQUIPMENT	FSCM	ICP/NSN	NOUN NAME	GMG	SCAT
8491A-006	28480	9N5895-00-230-1827	ATTENUATOR,FIXED,COAXIAL	AT1EA	4686
SPECIFICATIONS: ATTENUATION:6 DB +/-0.3 DB FREQUENCY RANGE:DC-12.4 GHZ IMPEDANCE:50 OHM NOM POWER:2W AVG;100W PEAK VSWR:1.2,DC-8 GHZ & 1.3,8-12.4 GHZ CONNECTOR:N (M-F) DIMENSIONS:(INCHES)2.4L X 0.8 DIA APPROX WEIGHT:(OUNCES)6 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
8491A-010	28480	9N5985-00-865-0108	ATTENUATOR,FIXED,COAXIAL	AT1JA	4687
SPECIFICATIONS: ATTENUATION:10 DB +/-0.5 DB FREQUENCY RANGE:DC-12.4 GHZ IMPEDANCE:50 OHM NOM POWER:2W AVG;100W PEAK VSWR:1.2,DC-8 GHZ & 1.3,8-12.4 GHZ CONNECTOR:N (M-F) DIMENSIONS:(INCHES)2.4L X 0.8 DIA APPROX WEIGHT:(OUNCES)6 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
8491A-020	28480	1H4935-01-031-2694	ATTENUATOR,FIXED,COAXIAL	AT1NN	4689
SPECIFICATIONS: ATTENUATION:20 DB +/-0.5 DB FREQUENCY RANGE:DC-12.4 GHZ IMPEDANCE:50 OHM NOM POWER:2W AVG;100W PEAK VSWR:1.2,DC-8 GHZ & 1.3,8-12.4 GHZ CONNECTOR:N (M-F) DIMENSIONS:(INCHES)2.4L X 0.8 DIA APPROX WEIGHT:(OUNCES)6 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
850-CT2W	83332		ATTENUATOR,STEP	AT4BQ	4668
SPECIFICATIONS: ATTENUATION:0-111 DB IN 0.1 DB STEPS, 3 DIALS FREQUENCY RANGE:DC-10 MHZ IMPEDANCE:600 OHMS, UNBALANCED POWER:2 WATTS MAX ACCURACY:RES ADJ TO +/-0.1%,LOW VALUE LOSS +/-.25% TERMINALS:TELEPHONE JACKS OR REAR SOLDER TERMINALS DIMENSIONS:(INCHES)4D X 12.75 W X 4.75H APPROX WEIGHT:(POUNDS) 5.5 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
973-20	93459	1H6625-00-118-6729	ATTENUATOR,VARIABLE,COAXIAL	AT6AN	NONE
SPECIFICATIONS: ATTENUATION:20 DB MAX FREQUENCY RANGE:2.5-11.0 GHZ VSWR:1.6,2.5-4 GHZ & 1.5,4-11 GHZ;AT 50 OHMS NOM POWER:1W AVG INSERTION LOSS:2.5 AT 20 DB CONNECTOR:N (M-F) DIMENSIONS:(INCHES)14.125L X 1.22 DIA APPROX WEIGHT:(POUNDS)1.25 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					

Source: https://assist.dla.mil -- Downloaded: 2026t0-26T13:40Z
Check the source to verify that this is the currentversion before use.

APPENDIX E

NOUN NAME TO STANDARD EQUIPMENTS

NOUN NAME	STANDARD EQUIPMENT	FSCM	ICP/NSN	GMG	SCAT
ADAPTER,COAXIAL,SET	0874-9099	82316	1H5935-00-370-8549	AD1NN	4604
SPECIFICATIONS:	IMPEDANCE:50 OHM NOM ALL CONNECTORS ADAPT TO TYPE GR874 CONNECTOR,1 EA OF TYPE C (M-F),HN (M-F),SMA (M-F),TNC (M-F0,1 TEE (3 X GR874),1 RIGHT ANGLE LINE SECTION (2 X GR874) AND 1 GR874-A3 50 OHM CABLE TERMINATED W/GR 874 1 END,OTHER END W/BANANA PLUG DIMENSIONS:(INCHES)CASE 7L X 18.5W X 4H APPROX WEIGHT:(POUNDS)4.5 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
ADAPTER,WAVEGUIDE TO COAXIAL	616	99899	9N6625-00-424-5066	AD3AN	4859
SPECIFICATIONS:	FREQUENCY RANGE:1.12-1.7 GHZ VSWR:1.25 MAX WAVEGUIDE:WR650 FLANGE:UG-417A/U,COPPER ALLOY (COVER) CONNECTOR:N (F) DIMENSIONS:(INCHES)5L X 5.5W APPROX WEIGHT:(POUNDS)2.5 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
ADAPTER,WAVEGUIDE TO COAXIAL	S281A	28480	1R4920-01-029-4624	AD3CN	4860
SPECIFICATIONS:	FREQUENCY RANGE:2.6-3.95 GHZ VSWR:1.25 MAX WAVEGUIDE:WR284 FLANGE::UG-584/U,ALUMINUM (COVER) CONNECTOR:N (F) DIMENSIONS:(INCHES)5.5L X 3.0W X 1.5H APPROX WEIGHT:(POUNDS)1.2 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
ADAPTER,WAVEGUIDE TO COAXIAL	TDR-29011	87864	9N5985-00-062-6919	AD3JN	4862
SPECIFICATIONS:	FREQUENCY RANGE:3.5-8.2 GHZ VSWR:1.20 MAX WAVEGUIDE:WR350;MFG NUMBER DR-29 FLANGE:UG-1550/U,ALUMINUM (COVER) CONNECTOR:N (F) DIMENSIONS:(INCHES)5.2L X 1.5W X 0.7H APPROX WEIGHT:(POUNDS)1 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED,					
ADAPTER,WAVEGUIDE TO COAXIAL	G281A	28480	9N5985-00-772-6676	AD3FN	4861
SPECIFICATIONS:	FREQUENCY RANGE:3.95-5.85 GHZ VSWR:1.25 MAX WAVEGUIDE:WR187 FLANGE:UG-407/U,ALUMINUM (COVER) CONNECTOR:N (F) DIMENSIONS:(INCHES)3.8L X 2W X 1H APPROX WEIGHT:(POUNDS)0.5 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX E

NOUN NAME TO STANDARD EQUIPMENTS

NOUN NAME	STANDARD EQUIPMENT	FSCM	ICP/NSN	GMG	SCAT
ADAPTER,WAVEGUIDE TO COAXIAL SPECIFICATIONS:	J281A FREQUENCY RANGE:5.3-8.2 GHZ VSWR:1.25 (1.3:5.3 AT 5.3 GHZ) WAVEGUIDE:WR137 FLANGE:UG-344/U,BRASS (COVER) CONNECTOR:N (F) DIMENSIONS:(INCHES)2L X 1.5W X 0.75H APPROX WEIGHT:(POUNDS)1 APPROX	28480	9N5985-00-606-9161	AD3MN	4610
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
ADAPTER,WAVEGUIDE TO COAXIAL SPECIFICATIONS:	102AC46-1E FREQUENCY RANGE:7-11 GHZ VSWR:1.25 MAX WAVEGUIDE:WR102 FLANGE:RG-320/U,ALUMINUM (COVER) CONNECTOR:N (F) DIMENSIONS:(INCHES)1L X 1.2W APPROX WEIGHT:(POUNDS)0.3 APPROX	01456	1H6625-00-178-0008	AD3QN	4606
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
ADAPTER,WAVEGUIDE TO COAXIAL SPECIFICATIONS:	X281A FREQUENCY RANGE:8.2-12.4 GHZ VSWR:1.25 MAX WAVEGUIDE:WR90 FLANGE:UG-135/U,ALUMINUM (COVER) CONNECTOR:N (F) DIMENSIONS:(INCHES)1.8L X 1W X 0.5H APPROX WEIGHT:(POUNDS)1 APPROX	28480	9N5985-00-892-0732	AD3TN	4605
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
ADAPTER,WAVEGUIDE TO COAXIAL SPECIFICATIONS:	P281B FREQUENCY RANGE:12.4-18 GHZ VSWR:1.25 MAX WAVEGUIDE:WR62 FLANGE:UG-419/U,BRASS (COVER) CONNECTOR:APC-7 (F),ORDER OPT 013 FOR TYPE N (F) DIMENSIONS:(INCHES)2.5L X 0.7W X 0.4H APPROX WEIGHT:(POUNDS)0.2 APPROX	28480	9N5985-00-136-8330	AD3WN	4609
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
ADAPTER,WAVEGUIDE TO COAXIAL SPECIFICATIONS:	4609 FREQUENCY RANGE:12.4-18 GHZ VSWR:1.25 MAX WAVEGUIDE:WR62 FLANGE:UG-419/U,BRASS (COVER) CONNECTOR:SMA (F) DIMENSIONS:(INCHES)1L X 1.4W APPROX WEIGHT:(POUNDS)0.3 APPROX	99899	1H5985-01-025-3902	AD3YN	4614
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX E

NOUN NAME TO STANDARD EQUIPMENTS

NOUN NAME	STANDARD EQUIPMENT	FSCM	ICP/NSN	GMG	SCAT
ATTENUATOR,FIXED,COAXIAL,SET	4M-3-6-10	93459	9N6625-01-026-2335	AT2NN	NONE
SPECIFICATIONS: ITEM LISTED AS REFERENCE ONLY REFER TO TYPES 4M-3,4M-6,4M-10 SEPARATELY					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
ATTENUATOR,FIXED,COAXIAL	8491A-003	28480	9N5985-00-167-0544	AT1AF	4688
SPECIFICATIONS: ATTENUATION:3 DB +/-0.3 DB FREQUENCY RANGE:DC-12.4 GHZ IMPEDANCE:50 OHM NOM POWER:2W AVG;100W PEAK VSWR:1.2,DC-8 GHZ & 1.3,8-12.4 GHZ CONNECTOR:N (M-F) DIMENSIONS:(INCHES)2.4L X 0.8 DIA APPROX WEIGHT:(OUNCES)6 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
ATTENUATOR,FIXED,COAXIAL	210A-3	93459	1H6625-LL-HHE-4111	AT1AB	NONE
SPECIFICATIONS: ATTENUATION:3 DB +/- 0.2 DB FREQUENCY RANGE:0.6-18 GHZ IMPEDANCE:50 OHM NOM POWER:5W AVG; 10 KW PEAK VSWR:1.3 MAX CONNECTOR:N (M-F) DIMENSIONS:(INCHES)2.4L X 0.8 DIA APPROX WEIGHT:(OUNCES)8.0 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
ATTENUATOR,FIXED,COAXIAL	4M-3	93459	1H6625-LL-HHE-1799	AT1AT	4690
SPECIFICATIONS: ATTENUATION:3 DB +/-0.3 DB FREQUENCY RANGE:DC-18 GHZ IMPEDANCE:50 OHM NOM POWER:2W AVG,500W PEAK VSWR:1.15,DC-4 GHZ;INCR TO 1.35,12.4-18 GHZ CONNECTOR:SMA (M-F) ADD PREFIX M OR F TO MODEL NO. EXAMPLE:FOR FEMALE ORDER F4M-3 DIMENSIONS:(INCHES)1.2L X 0.4 DIA APPROX WEIGHT:(OUNCES)0.35 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
ATTENUATOR,FIXED,COAXIAL	2-3	93459	1H6625-01-020-6032	AT1AM	4924
SPECIFICATIONS: ATTENUATION:3 DB +/-0.3 DB FREQUENCY RANGE:DC-18 GHZ IMPEDANCE:50 OHM NOM POWER:5W AVG;1 KW PEAK VSWR:1.15,DC-4 GHZ;INCR TO 1.40,12.4-18 GHZ CONNECTOR:N (M-F) DIMENSIONS:(INCHES)2.3L X 0.8 DIA APPROX WEIGHT:(OUNCES)2.6 APPROX					
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX E

NOUN NAME TO STANDARD EQUIPMENTS

NOUN NAME	STANDARD EQUIPMENT	FSCM	ICP/NSN	GMG	SCAT
ATTENUATOR,FIXED,COAXIAL	24-6-34	93459	1H6625-LL-HHE-8021	AT1AC	NONE
SPECIFICATIONS:	ATTENUATION:6DB,DC-4GHZ +/-0.4DB.4-8GHZ +/-0.75DB FREQUENCY RANGE:DC-8 GHZ IMPEDANCE:50 OHM NOM POWER:50W AVG,5 KW PEAK,MID IN HORIZONTAL PLANE DIMENSIONS:(INCHES)4.44L X 1.64 DIA APPROX CONNECTOR:N (M-F) DIMENSIONS:(INCHES)4.44LX 1.64 DIA APPROX WEIGHT:(OUNCES) 10 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
ATTENUATOR,FIXED,COAXIAL	8491A-006	28480	9N5895-00-230-1827	AT1EA	4686
SPECIFICATIONS:	ATTENUATION:6 DB +/-0.3 DB FREQUENCY RANGE:DC-12.4 GHZ IMPEDANCE:50 OHM NOM POWER:2W AVG;100W PEAK VSWR:1.2,DC-8 GHZ & 1.3,8-12.4 GHZ CONNECTOR:N (M-F) DIMENSIONS:(INCHES)2.4L X 0.8 DIA APPROX WEIGHT:(OUNCES)6 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
ATTENUATOR,FIXED,COAXIAL	4M-6	93459	1H6625-01-015-2356	AT1EN	4691
SPECIFICATIONS:	ATTENUATION:6 DB +/-0.3 DB FREQUENCY RANGE:DC-18 GHZ IMPEDANCE:50 OHM NOM POWER:2W AVG;500W PEAK VSWR:1.15,DC-4 GHZ;INCR TO 1.35,12.4-18 GHZ CONNECTOR:SMA (M-F) ADD PREFIX M OR F TO MODEL NO. EXAMPLE:FOR FEMALE ORDER F4M-6 DIMENSIONS:(INCHES)1.2L X 0.4 DIA APPROX WEIGHT:(OUNCES)0.35 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
ATTENUATOR,FIXED,COAXIAL	2-6	93459	1H6625-01-017-1277	AT1EY	4915
SPECIFICATIONS:	ATTENUATION:6 DB +/-0.3 DB FREQUENCY RANGE:DC-18 GHZ IMPEDANCE:50 OHM NOM POWER:5W AVG;1 KW PEAK VSWR:1.15,DC-4 GHZ;INCR TO 1.40,12.4-18 GHZ CONNECTOR:N (M-F) DIMENSIONS:(INCHES)2.3L X 0.8 DIA APPROX WEIGHT:(OUNCES)2.6 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
ATTENUATOR,FIXED,COAXIAL	8491A-010	28480	9N5985-00-865-0108	AT1JA	4687
SPECIFICATIONS:	ATTENUATION:10 DB +/-0.5 DB FREQUENCY RANGE:DC-12.4 GHZ IMPEDANCE:50 OHM NOM POWER:2W AVG;100W PEAK VSWR:1.2,DC-8 GHZ & 1.3,8-12.4 GHZ CONNECTOR:N (M-F) DIMENSIONS:(INCHES)2.4L X 0.8 DIA APPROX WEIGHT:(OUNCES)6 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					

Source: https://assist.dla.mil -- Downloaded: 202610-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX E

NOUN NAME TO STANDARD EQUIPMENTS

NOUN NAME	STANDARD EQUIPMENT	FSCM	ICP/NSN	GMG	SCAT
ATTENUATOR,FIXED,COAXIAL	4M-10	93459	9N5985-00-258-0123	AT1JY	4694
SPECIFICATIONS:	ATTENUATION:10 DB +/-0.5 DB FREQUENCY RANGE:DC-18 GHZ IMPEDANCE:50 OHM NOM POWER:2W AVG;500W PEAK VSWR:1.15,DC-4 GHZ;INCR TO 1.35,12.4-18 GHZ CONNECTOR:SMA (M-F) ADD PREFIX M OR F TO MODEL NO. EXAMPLE:FOR FEMALE ORDER F4M-10 DIMENSIONS:(INCHES)1.2L X 0.4 DIA APPROX WEIGHT:(OUNCES)0.35 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
ATTENUATOR,FIXED,COAXIAL	2-10	93459	1H6625-01-017-1278	AT1JN	4916
SPECIFICATIONS:	ATTENUATION:10 DB +/-0.5 DB FREQUENCY RANGE:DC-18 GHZ IMPEDANCE:50 OHM NOM POWER:5W AVG;1 KW PEAK VSWR:1.15,DC-4 GHZ;INCR TO 1.40,12.4-18 GHZ CONNECTOR:N (M-F) DIMENSIONS:(INCHES)2.3L X 0.8 DIA APPROX WEIGHT:(OUNCES)2.6 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
ATTENUATOR,FIXED,COAXIAL	8491A-020	28480	1H4935-01-031-2694	AT1NN	4689
SPECIFICATIONS:	ATTENUATION:20 DB +/-0.5 DB FREQUENCY RANGE:DC-12.4 GHZ IMPEDANCE:50 OHM NOM POWER:2W AVG;100W PEAK VSWR:1.2,DC-8 GHZ & 1.3,8-12.4 GHZ CONNECTOR:N (M-F) DIMENSIONS:(INCHES)2.4L X 0.8 DIA APPROX WEIGHT:(OUNCES)6 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
ATTENUATOR,FIXED,COAXIAL	N9412-20	09992	1H5985-01-203-5192	AT1NB	NONE
SPECIFICATIONS:	ATTENUATION:20 DB +/- 2.0 DB TO 18 GHZ FREQUENCY RANGE:DC-18.0 GHZ IMPEDANCE:50 OHMS NOM POWER:2W AVG;3 KW PEAK VSWR:2.0 MAX CONNECTOR:N (M-F) DIMENSIONS:(INCHES)2.42L X 0.82 DIA APPROX WEIGHT:(OUNCES)5.0 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
ATTENUATOR,FIXED,COAXIAL	2-20	93459	1H6625-01-017-1276	AT1NY	4917
SPECIFICATIONS:	ATTENUATION:20 DB +/-0.5 DB FREQUENCY RANGE:DC-18 GHZ IMPEDANCE:50 OHM NOM POWER:5W AVG;1 KW PEAK VSWR:1.15,DC-4 GHZ;INCR TO 1.40,12.4-18 GHZ CONNECTOR:N (M-F) DIMENSIONS:(INCHES)2.3L X 0.8 DIA APPROX WEIGHT:(OUNCES)2.6 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX E

NOUN NAME TO STANDARD EQUIPMENTS

NOUN NAME	STANDARD EQUIPMENT	FSCM	ICP/NSN	GMG	SCAT
ATTENUATOR,FIXED,COAXIAL	2-30	93459	1H6625-01-014-3463	AT1SN	4918
SPECIFICATIONS:	ATTENUATION:30 DB +/-1 DB FREQUENCY RANGE:DC-18 GHZ IMPEDANCE:50 OHM NOM POWER:5W AVG,1 KW PEAK VSWR:1.15,DC-4 GHZ,INCR TO 1.40,12.4-18 GHZ CONNECTOR:N (M-F) DIMENSIONS:(INCHES)2.3L X 0.8 DIA APPROX WEIGHT:(OUNCES)2.6 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
ATTENUATOR,FIXED,COAXIAL	2-40	93459	1H6625-01-014-3464	AT1WN	4919
SPECIFICATIONS:	ATTENUATION:40 DB +/-1 DB FREQUENCY RANGE:DC-18 GHZ IMPEDANCE:50 OHM NOM POWER:5W AVG;1 KW PEAK VSWR:1.15,DC-4 GHZ;INCR TO 1.40,12.4-18 GHZ CONNECTOR:N (M-F) DIMENSIONS:(INCHES)2.7L X 0.8 DIA APPROX WEIGHT:(OUNCES)3.6 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
ATTENUATOR,STEP	850-CT2W	83332		AT4RQ	4668
SPECIFICATIONS:	ATTENUATION:0-111 DB IN 0.1 DB STEPS, 3 DIALS FREQUENCY RANGE:DC-10 MHZ IMPEDANCE:600 OHMS, UNBALANCED POWER:2 WATTS MAX ACCURACY:RES ADJ TO +/-0.1%,LOW VALUE LOSS +/-.25% TERMINALS:TELEPHONE JACKS OR REAR SOLDER TERMINALS DIMENSIONS:(INCHES)4D X 12.75 W X 4.75H APPROX WEIGHT:(POUNDS) 5.5 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
ATTENUATOR,STEP	355C	28480	1H5985-00-993-1377	AT4AN	4662
SPECIFICATIONS:	ATTENUATION:0-12 DB IN 1 DB STEPS FREQUENCY RANGE:DC-1 GHZ IMPEDANCE:50 OHM NOM POWER:0.5W AVG;350W PEAK VSWR:1.5 MAX CONNECTOR:BNC (F-F) DIMENSIONS:(INCHES)6L X 2.6W X 2.8H APPROX WEIGHT:(POUNDS)3 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
ATTENUATOR,STEP	1/432D	80138	9N5985-00-252-8026	AT4DN	NONE
SPECIFICATIONS:	ATTENUATION:0-22.1 DB IN 0.1 DB STEPS FREQUENCY RANGE:DC-0.5 GHZ IMPEDANCE:50 OHM NOM POWER:1W MAX VSWR:1.2 MAX CONNECTOR:BNC (F-F) DIMENSIONS:(INCHES)2L X 9.8W X 2H APPROX WEIGHT:(POUNDS)3 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX E

NOUN NAME TO STANDARD EQUIPMENTS

NOUN NAME	STANDARD EQUIPMENT	FSCM	ICP/NSN	GMG	SCAT
ATTENUATOR,STEP	AF-117A-69-34	93459	9N6625-01-063-9297	AT4GN	4898
SPECIFICATIONS:	ATTENUATION:0-69 DB IN 1 DB STEPS FREQUENCY RANGE:DC-18 GHZ IMPEDANCE:50 OHM NOM POWER:2W AVG;200W PEAK VSWR:1.6 MAX CONNECTOR:N (M-F) DIMENSIONS:(INCHES)3.2L X 4W X 3.3H APPROX WEIGHT:(OUNCES)27 APPROX				
	CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.				
ATTENUATOR,STEP	M602	57646		AT4KN	NONE
SPECIFICATIONS:	ATTENUATION:100 DB MAX FREQUENCY RANGE:DC-500 MHZ IMPEDANCE:90 OHMS NOM POWER:0.5W AVG INSERTION LOSS:<1 DB AT 150 MHZ & <4 DB AT 400 MHZ CONNECTOR:BNC (F-F) DIMENSIONS:(INCHES)11L X 2W X 2H APPROX WEIGHT:(POUNDS)1.5 APPROX				
	CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.				
ATTENUATOR,STEP	432-D	80138	9N5985-00-087-2547	AT4NA	4661
SPECIFICATIONS:	ATTENUATION:0-101 DB IN 1 DB STEPS FREQUENCY RANGE:DC-1 GHZ IMPEDANCE:50 OHM NOM POWER:0.5W MAX VSWR:1.2 DC-500 MHZ & 1.4 0.5-1 GHZ CONNECTOR:BNC (F-F) DIMENSIONS:(INCHES)2L X 9.8W X 2H APPROX WEIGHT:(POUNDS)3 APPROX				
	CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.				
ATTENUATOR,STEP	442-D	80138	9N5905-00-313-9064	AT4NN	4666
SPECIFICATIONS:	ATTENUATION:0-101 DB IN 1 DB STEPS FREQUENCY RANGE:DC-1 GHZ IMPEDANCE:75 OHM NOM POWER:0.5W MAX VSWR:1.2 MAX CONNECTOR:BNC (F-F) DIMENSIONS:(INCHES)2L X 9.8W X 2H APPROX WEIGHT:(POUNDS)3 APPROX				
	CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.				
ATTENUATOR,STEP	452-C	80138	9Y5985-00-712-8388	AT4NY	4665
SPECIFICATIONS:	ATTENUATION:0-101 DB IN 1 DB STEPS FREQUENCY RANGE:DC-0.5 GHZ IMPEDANCE:90 OHM NOM POWER:1W MAX VSWR:1.2 MAX CONNECTOR:BNC (F-F) DIMENSIONS:(INCHES)2L X 7W X 2H APPROX WEIGHT:(POUNDS)3 APPROX				
	CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.				

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX E

NOUN NAME TO STANDARD EQUIPMENTS

NOUN NAME	STANDARD EQUIPMENT	FSCM	ICP/NSN	GMG	SCAT
ATTENUATOR,STEP	355D	28480	9N5985-00-957-1860	AT4UN	4672
SPECIFICATIONS:	ATTENUATION:0-120 DB IN 10 DB STEPS FREQUENCY RANGE:DC-1 GHZ IMPEDANCE:50 OHM NOM POWER:0.5W AVG;350W PEAK VSWR:1.5 MAX CONNECTOR:BNC (F-F) DIMENSIONS:(INCHES)6L X 2.6W X 2.8H APPROX WEIGHT:(POUNDS)3 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
ATTENUATOR,VARIABLE,COAXIAL	973-20	93459	1H6625-00-118-6729	AT6AN	NONE
SPECIFICATIONS:	ATTENUATION:20 DB MAX FREQUENCY RANGE:2.5-11.0 GHZ VSWR:1.6,2.5-4 GHZ & 1.5,4-11 GHZ;AT 50 OHMS NOM POWER:1W AVG INSERTION LOSS:2.5 AT 20 DB CONNECTOR:N (M-F) DIMENSIONS:(INCHES)14.125L X 1.22 DIA APPROX WEIGHT:(POUNDS)1.25 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
ATTENUATOR,VARIABLE,COAXIAL	2-3414-30	09992	9N5985-00-999-8095	AT6FN	4895
SPECIFICATIONS:	ATTENUATION:30 DB MAX FREQUENCY RANGE:0.8-2.5 GHZ VSWR:1.5 AT 50 OHM NOM POWER:10W AVG INSERTION LOSS:0.2 DB CONNECTOR:N (F-F) DIMENSIONS:(INCHES)5D X 1H APPROX WEIGHT:(POUNDS)1.8 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
ATTENUATOR,VARIABLE,COAXIAL	AU-65AMN	12457	1H6625-01-040-9528	AT6MN	NONE
SPECIFICATIONS:	ATTENUATION:80 DB MAX FREQUENCY RANGE:0.3-8 GHZ VSWR:1.5 AT 50 OHM NOM POWER:10W AVG INSERTION LOSS:0.7 DB CONNECTOR:N (M-F) DIMENSIONS:(INCHES)8.3L X 1W X 2.1H APPROX WEIGHT:(OUNCES)25 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
ATTENUATOR,VARIABLE,COAXIAL	0874-9577	82316	&A5840-00-868-1287	AT6TN	4697
SPECIFICATIONS:	ATTENUATION:120 DB MAX FREQUENCY RANGE:100 MHZ-4 GHZ VSWR:<1.03,1 GHZ & 1.12,1-4 GHZ;AT 50 OHM NOM POWER:300W AVG INSERTION LOSS:30.4 DB CONNECTOR:GR874 (SEXLESS) DIMENSIONS:(INCHES)36L INCLUDING CABLE,APPROX WEIGHT:(POUNDS)1.3 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					

Source: https://assist.dla.mil -- Downloaded: 202640-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX E

NOUN NAME TO STANDARD EQUIPMENTS

NOUN NAME	STANDARD EQUIPMENT	FSCM	ICP/NSN	GMG	SCAT
ATTENUATOR,VARIABLE,WAVEGUIDE	J382A	28480	7G6625-00-679-0627	AT7AA	NONE
SPECIFICATIONS:	ATTENUATION:0-50 DB FREQUENCY RANGE:5.3-8.2 GHZ VSWR:1.15 AT 50 OHM NOM POWER:10W MAX FLANGE:UG-441/U,ALUMINUM (COVER) WAVEGUIDE:WR137 DIMENSIONS:(INCHES)25L X 6.2W X 8H APPROX WEIGHT:(POUNDS)17 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
ATTENUATOR,VARIABLE,WAVEGUIDE	X382A	28480	1H6625-00-602-2089	AT7AF	4901
SPECIFICATIONS:	ATTENUATION:0-50 DB FREQUENCY RANGE:8.2-12.4 GHZ VSWR:1.15 AT 50 OHM NOM POWER:10W MAX FLANGE:UG-135/U,ALUMINUM (COVER) WAVEGUIDE:WR90 DIMENSIONS:(INCHES)15.5L X 4.7W X 7.5H APPROX WEIGHT:(POUNDS)8 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
ATTENUATOR,VARIABLE,WAVEGUIDE	P382A	28480	6G6625-00-752-3222	AT7AM	4673
SPECIFICATIONS:	ATTENUATION:0-50 DB FREQUENCY RANGE:12.4-18 GHZ VSWR:1.15 AT 50 OHM NOM POWER:5W MAX FLANGE:UG-419/U,COPPER ALLOY (COVER) WAVEGUIDE:WR62 DIMENSIONS:(INCHES)12.5L X 4.8W X 7.8H APPROX WEIGHT:(POUNDS)8 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
ATTENUATOR,VARIABLE,WAVEGUIDE	K382A	28480	9N5985-00-822-8666	AT7AT	4675
SPECIFICATIONS:	ATTENUATION:0-50 DB FREQUENCY RANGE:18-26.5 GHZ VSWR:1.15 AT 50 OHM NOM POWER:2W MAX FLANGE:UG-597/U,ALUMINUM (COVER) WAVEGUIDE:WR42 DIMENSIONS:(INCHES)7.8L X 4.8W X 6H APPROX WEIGHT:(POUNDS)6 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
ATTENUATOR,VARIABLE,WAVEGUIDE	R382A	28480	1H5985-00-822-7874	AT7AY	4677
SPECIFICATIONS:	ATTENUATION:0-50 DB FREQUENCY RANGE:26.5-40 GHZ VSWR:1.15 AT 50 OHM NOM POWER:1W MAX FLANGE:UG-599/U,COPPER ALLOY (COVER) WAVEGUIDE:WR28 DIMENSIONS:(INCHES)6.4L X 8W X 6.1H APPROX WEIGHT:(POUNDS)6 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX E

NOUN NAME TO STANDARD EQUIPMENTS

NOUN NAME	STANDARD EQUIPMENT	FSCM	ICP/NSN	GMG	SCAT
ATTENUATOR,VARIABLE,WAVEGUIDE	S382C	28480	9N6625-00-179-8448	AT7NA	4670
SPECIFICATIONS:	ATTENUATION:0-60 DB FREQUENCY RANGE:2.6-3.95 GHZ VSWR:1.2,2.6-3 GHZ & 1.15,3-3.95 GHZ;AT 50 OHM NOM POWER:10W MAX FLANGE:UG-584/U,ALUMINUM (COVER) WAVEGUIDE:WR284 DIMENSIONS:(INCHES)25.3L X 8W X 6H APPROX WEIGHT:(POUNDS)22 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
ATTENUATOR,VARIABLE,WAVEGUIDE	G-101	77327	9N5985-00-921-3697	AT7NN	4671
SPECIFICATIONS:	ATTENUATION:0-60 DB FREQUENCY RANGE:3.95-5.85 GHZ VSWR:1.15 AT 50 OHM NOM POWER:15W MAX FLANGE:UG-407/U,ALUMINUM (COVER) WAVEGUIDE:WR187 DIMENSIONS:(INCHES)19L X 7W X 6.3H APPROX WEIGHT:(POUNDS)11 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
CAMERA,OSCILLOSCOPE	C-30BP	80009	7G6720-01-095-2205	CS1NN	NONE
SPECIFICATIONS:	LENS SIZE:56 MM LENS APERTURE(SPEED):F/1.9 F STOP RANGE:F/1.9 TO F/16 FIELD OF VIEW:7 X 9 CM OR 8 X 10 CM W/OPTION 01 SHUTTER SPEED:1/125 TO 1 SECOND,BULB & TIME,X SYNC MAGNIFICATION:0.7-1.5 CONTINUOUSLY VARIABLE FOCUS:SPLIT-IMAGE FOCUS PLATE FILM:POLAROID PACK FILM DIMENSIONS:(INCHES)5.1H X 7.5W X 10.4D APPROX WEIGHT:(POUNDS)4.8 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
CAMERA,OSCILLOSCOPE	197B	28480	&&6720-01-104-3402	CS1AB	NONE
SPECIFICATIONS:	LENS SIZE:75 MM LENS APERATURE(SPEED):F/1.9 F STOP RANGE:F/1.9 TO F/16 FIELD OF VIEW:REDUCTION RATIO CONTROL SHUTTER SPEED:1/30-4 SEC BULB & TIME,SYNC CONTACTS POWER:SELECT SWITCH 115/230 VAC +/-10%,48-66 HZ FOCUS:SPLIT IMAGE,ADJUSTABLE WITH LOCK FILM:POLAROID PACK BACK DIMENSIONS:(INCHES)10.5H X 7.6W X 14D APPROX WEIGHT:(POUNDS)10 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX E

NOUN NAME TO STANDARD EQUIPMENTS

NOUN NAME	STANDARD EQUIPMENT	FSCM	ICP/NSN	GMG	SCAT
CAMERA,OSCILLOSCOPE	C-59AP	80009	1H6720-00-262-4198	CS1AA	NONE
SPECIFICATIONS:	LENS SIZE:56 MM LENS APPERATURE(SPEED)F/2.8 F STOP RANGE:F/2.8 TO F/16 FIELD OF VIEW:10.2 X 12.7 CM SHUTTER SPEED:1/125 TO 1 SECOND,BULB & TIME,X SYNC POWER:15V FROM SOME SCOPES,OR AA SIZE BATTERIES FOCUS:FOCUS PLATE FILM:POLAROID PACK FILM DIMENSIONS:(INCHES)11.5H X 7.6W X 10.7D APPROX WEIGHT:(POUNDS)7 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
CAPACITOR,DECADE	1412-9410	24655	1H6625-00-465-6861	CP1MN	4624
SPECIFICATIONS:	RANGE:50 PF TO 1.11115 MFD IN 100 PF STEPS ACCURACY:+/-(0.5%+5 PF) AT 1 KHZ VOLTAGE:500V (DC OR PEAK)UP TO 35 KHZ RANGE SELECTOR:FIVE ROTARY SWITCHES CONNECTOR:FOUR BINDING POSTS DIMENSIONS:(INCHES) 17.25W X 3.5H X 6.0D APPROX WEIGHT:(POUNDS) 8.5 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
CAPACITOR,DECADE	UNDER REVIEW			CP1U3	4644
SPECIFICATIONS:	RANGE:0.0001-0.011 MFD IN 0.0001 MFD STEPS ACCURACY:+/-2% VOLTAGE:600 VDC MAX,200 VAC MAX RANGE SELECTOR:TWO ROTARY SWITCHES CONNECTOR:BINDING POSTS DIMENSIONS:(INCHES)3.6L X 5W X 3H APPROX WEIGHT:(POUNDS)1 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
CAPACITOR,DECADE	UNDER REVIEW			CP1U2	4646
SPECIFICATIONS:	RANGE:0.01-1.1 MFD IN 0.01 MFD STEPS ACCURACY:+/-3% VOLTAGE:600 VDC MAX,220 VAC MAX RANGE SELECTOR:TWO ROTARY SWITCHES CONNECTOR:BINDING POSTS DIMENSIONS:(INCHES)3.6L X 5W X 3H APPROX WEIGHT:(POUNDS)2 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
CAPACITOR,DECADE	UNDER REVIEW			CP1U1	4647
SPECIFICATIONS:	RANGE:1-10 MFD IN 1 MFD STEPS ACCURACY:+/-3% VOLTAGE:600 VDC MAX,220 VAC MAX RANGE SELECTOR:ONE ROTARY SWITCH CONNECTOR:BINDING POSTS DIMENSIONS:(INCHES)3.6L X 5W X 3H APPROX WEIGHT:(POUNDS)3 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					

Source: https://assist.dla.mil -- Downloaded: 202610-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX E

NOUN NAME TO STANDARD EQUIPMENTS

NOUN NAME	STANDARD EQUIPMENT	FSCM	ICP/NSN	GMG	SCAI
CONVERTER,FREQUENCY,AC	153B/403SD-001	25965	7G6625-01-197-9866	CF1NN	4084
SPECIFICATIONS:	OUTPUT:150 VA,0-130V LINE-NEUTRAL,45 HZ TO 10 KHZ INPUT:0.5 KVA,117V OR 230V,3 PHASE, 47-63 HZ PHASE ANGLE:120 DEGREES +/-1 DEGREE C FREQUENCY TEMP COEFF:+/-0.02% DEGREE C DIMENSIONS:(INCHES) 19L X16.5W X 5.3H APPROX WEIGHT:(POUNDS)70 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
COUPLER,DIRECTIONAL,COAXIAL	3000-10	99899	9N5985-00-816-4287	DC1AA	4880
SPECIFICATIONS:	COUPLING:10 DB FREQUENCY RANGE:225-460 MHZ DIRECTIVITY:30 DB MIN POWER:200W AVG;10 KW PEAK VSWR:PRI LINE,1.15;SEC LINE,1.1 CONNECTOR:N (F) DIMENSIONS:(INCHES)12.2L X 0.9W X 2.9H APPROX WEIGHT:(POUNDS)1.9 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
COUPLER,DIRECTIONAL,COAXIAL	3041-10	99899	1H5985-01-039-5404	DC1AC	4882
SPECIFICATIONS:	COUPLING:10 DB FREQUENCY RANGE:0.5-1 GHZ DIRECTIVITY:20 DB POWER:200W AVG;10 KW PEAK VSWR:PRI LINE,1.1;SEC LINE,1.2 CONNECTOR:N (F) DIMENSIONS:(INCHES)11.6L X 0.9W X 2.8H APPROX WEIGHT:(POUNDS)2 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
COUPLER,DIRECTIONAL,COAXIAL	3042B-10	99899	9N5985-00-465-8112	DC1AF	4884
SPECIFICATIONS:	COUPLING:10 DB FREQUENCY RANGE:0.92-2.2 GHZ DIRECTIVITY:20 DB MIN POWER:200W AVG;10 KW PEAK VSWR:PRI LINE,1.10;SEC LINE,1.20 CONNECTOR:N (F) DIMENSIONS:(INCHES)7.5L X 3W X 1.4H APPROX WEIGHT:(POUNDS)1.25 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
COUPLER,DIRECTIONAL,COAXIAL	3043B-10	99899	1H6625-01-065-5289	DC1AJ	4886
SPECIFICATIONS:	COUPLING:10 DB FREQUENCY RANGE:1.7-4.2 GHZ DIRECTIVITY:20 DB MIN POWER:200W AVG;10 KW PEAK VSWR:PRI LINE,1.15;SEC LINE,1.20 CONNECTOR:N (F) DIMENSIONS:(INCHES)4.1L X 2.1W X 1.4H APPROX WEIGHT:(POUND)1.0 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX E

NOUN NAME TO STANDARD EQUIPMENTS

NOUN NAME	STANDARD EQUIPMENT	FSCM	ICP/NSN	GMG	SCAT
COUPLER,DIRECTIONAL,COAXIAL	3202B-10	99899	9N5985-00-412-2986	DC1AQ	4890
SPECIFICATIONS:	COUPLING:10 DB FREQUENCY RANGE:1-12.4 GHZ DIRECTIVITY:15 DB 1-8 GHZ;12 DB 8-12.4 GHZ POWER:20W AVG;3 KW PEAK VSWR:PRI LINE,1.35;SEC LINE,1.5 CONNECTOR:N (F) DIMENSIONS:(INCHES)5.4L X 0.7W X 2H APPROX WEIGHT:(OUNCES)4.5 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
COUPLER,DIRECTIONAL,COAXIAL	3004-10	99899	9N5985-00-788-6962	DC1AM	4888
SPECIFICATIONS:	COUPLING:10 DB FREQUENCY RANGE:4-10 GHZ DIRECTIVITY:20 DB POWER:200W AVG;10 KW PEAK VSWR:PRI LINE,1;SEC LINE,1.3 CONNECTOR:N (F) DIMENSIONS:(INCHES)6.5L X 0.9W X 2.9H APPROX WEIGHT:(POUNDS)1 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
COUPLER,DIRECTIONAL,COAXIAL	3045C-10	99899	1R5985-00-604-8604	DC1AT	4693
SPECIFICATIONS:	COUPLING:10 DB FREQUENCY RANGE:7-12.4 GHZ DIRECTIVITY:15 DB MIN POWER:100W AVG;10 KW PEAK VSWR:PRI LINE,1.3;SEC LINE,1.3 CONNECTOR:N (F) DIMENSIONS:(INCHES)7L X 0.9W X 2.9H APPROX WEIGHT:(OUNCES)12 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
COUPLER,DIRECTIONAL,COAXIAL	4055-10	99899	9N6625-00-261-7749	DC1AW	NONE
SPECIFICATIONS:	COUPLING:10 DB FREQUENCY RANGE:7.5-16 GHZ DIRECTIVITY:12 DB POWER:50W AVG;1 KW PEAK VSWR:PRI LINE,1.35;SEC LINE,1.4 CONNECTOR:SMA (F) DIMENSIONS:(INCHES)1.75L X 0.4W X 1.25H APPROX WEIGHT:(OUNCES)0.6 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
COUPLER,DIRECTIONAL,COAXIAL	4016D-10	99899	9N5985-01-041-8132	DC1AY	4891
SPECIFICATIONS:	COUPLING:10 DB +/-1 DB FREQUENCY RANGE:12.4-18 GHZ DIRECTIVITY:15 DB POWER:50W AVG,1 KW PEAK VSWR:PRI LINE:1.35,SEC LINE 1.4 CONNECTOR:SMA (F) DIMENSIONS:(INCHES)1.75L X 0.37W X 0.88H APPROX WEIGHT:(OUNCES)0.63 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX E

NOUN NAME TO STANDARD EQUIPMENTS

NOUN NAME	STANDARD EQUIPMENT	FSCM	ICP/NSN	GMG	SCAT
COUPLER,DIRECTIONAL,COAXIAL	3222-16	99899	1H5985-01-081-7855	DC1EN	4877
SPECIFICATIONS:	COUPLING:16 DB FREQUENCY RANGE:1-18 GHZ DIRECTIVITY:1-12.4 GHZ 15 DB;12.4-18 GHZ 12 DB POWER:20W AVG;3 KW PEAK VSWR:PRI LINE,1.4;SEC LINE,1.5 CONNECTOR:N (F) DIMENSIONS:(INCHES)5.6L X 1.8W X 0.5H APPROX WEIGHT:(OUNCES)3.4 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
COUPLER,DIRECTIONAL,COAXIAL	3060-20	99899	9N5985-00-492-7921	DC1JA	4883
SPECIFICATIONS:	COUPLING:20 DB FREQUENCY RANGE:10-200 MHZ DIRECTIVITY:20 DB MIN POWER:1W AVG;100W PEAK VSWR:PRI LINE,1.2;SEC LINE,1.2 CONNECTOR:N (F) DIMENSIONS:(INCHES)3L X 1W X 1.75H APPROX WEIGHT:(OUNCES)3.2 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
COUPLER,DIRECTIONAL,COAXIAL	778D	28480	9N5985-00-239-3215	DC1JJ	4692
SPECIFICATIONS:	COUPLING:20 DB FREQUENCY RANGE:0.1-2 GHZ DIRECTIVITY:30 DB POWER:50W AVG;10 KW PEAK VSWR:PRI LINE,1.1;SEC LINE,1.1 CONNECTOR:N (F) DIMENSIONS:(INCHES)16.8L X 1.8W X 4.4H APPROX WEIGHT:(POUNDS)5 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
COUPLER,DIRECTIONAL,COAXIAL	3040B-20	99899	1H5985-00-067-6750	DC1JC	4881
SPECIFICATIONS:	COUPLING:20 DB FREQUENCY RANGE:0.24-0.5 GHZ DIRECTIVITY:20 DB POWER:500W AVG;10 KW PEAK VSWR:PRI LINE,1.1;SEC LINE,1.2 CONNECTOR:N (F) DIMENSIONS:(INCHES)13.6L X 0.9W X 2.9H APPROX WEIGHT:(POUNDS)2 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
COUPLER,DIRECTIONAL,COAXIAL	3041-20	99899	1R5985-00-757-0549	DC1JF	4878
SPECIFICATIONS:	COUPLING:20 DB FREQUENCY RANGE:0.5-1 GHZ DIRECTIVITY:20 DB POWER:500W AVG;10 KW PEAK VSWR:PRI LINE,1.1;SEC LINE,1.2 CONNECTOR:N (F) DIMENSIONS:(INCHES)11.6L X 0.9W X 2.8H APPROX WEIGHT:(POUNDS)2 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX E

NOUN NAME TO STANDARD EQUIPMENTS

NOUN NAME	STANDARD EQUIPMENT	FSCM	ICP/NSN	GMG	SCAT
COUPLER,DIRECTIONAL,COAXIAL	3002-20	99899	9N5985-00-578-5747	DC1JM	4885
SPECIFICATIONS:	COUPLING:20 DB FREQUENCY RANGE:0.95-2 GHZ DIRECTIVITY:27 DB POWER:500W AVG;10 KW PEAK VSWR:PRI LINE,1.15;SEC LINE,1.3 CONNECTOR:N (F) DIMENSIONS:(INCHES)5.5L X 0.9W X 2.9H APPROX WEIGHT:(POUNDS)1 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
COUPLER,DIRECTIONAL,COAXIAL	3003-20	99899	9N5985-00-882-8654	DC1JQ	4887
SPECIFICATIONS:	COUPLING:20 DB FREQUENCY RANGE:2-4 GHZ DIRECTIVITY:27 DB POWER:500W AVG;10 KW PEAK VSWR:PRI LINE,1.15;SEC LINE,1.2 CONNECTOR:N (F) DIMENSIONS:(INCHES)5.5L X 0.9W X 2.9H APPROX WEIGHT:(POUNDS)1 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
COUPLER,DIRECTIONAL,COAXIAL	3004-20	99899	9N5985-00-714-3247	DC1JT	4889
SPECIFICATIONS:	COUPLING:20 DB FREQUENCY RANGE:4-10 GHZ DIRECTIVITY:17 DB POWER:500W AVG;10 KW PEAK VSWR:PRI LINE,1.2;SEC LINE,1.3 CONNECTOR:N (F) DIMENSIONS:(INCHES)6.5L X 0.9W X 2.9H APPROX WEIGHT:(POUNDS)1 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
COUPLER,DIRECTIONAL,COAXIAL	4055-20	99899	1H5985-01-100-1668	DC1JU	NONE
SPECIFICATIONS:	COUPLING:20 DB FREQUENCY RANGE:7.5-16 GHZ DIRECTIVITY:15 DB POWER:50W AVG;2 KW PEAK VSWR:PRI LINE,1.35;SEC LINE,1.4 CONNECTOR:SMA (F) DIMENSIONS:(INCHES)1.8L X 0.4W X 1.3H APPROX WEIGHT:(OUNCES)0.6 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
COUPLER,DIRECTIONAL,COAXIAL	11692D	28480	9N5985-01-024-3832	DC1NN	4695
SPECIFICATIONS:	COUPLING:22 DB FREQUENCY RANGE:2-18 GHZ DIRECTIVITY:30 DB POWER:50W AVG;250W PEAK VSWR:PRI LINE,1.3;SEC LINE,1.4 CONNECTOR:N (F) DIMENSIONS:(INCHES)16L X 1W X 5.3H APPROX WEIGHT:(POUNDS)6 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX E

NOUN NAME TO STANDARD EQUIPMENTS

NOUN NAME	STANDARD EQUIPMENT	FSCM	ICP/NSN	GMG	SCAT
COUPLER,DIRECTIONAL,COAXIAL	3043B-30	99899	9N5985-00-450-8802	DC1SA	4681
SPECIFICATIONS:	COUPLING:30 DB FREQUENCY RANGE:1.7-4.2 GHZ DIRECTIVITY:20 DB POWER:500W AVG;10 KW PEAK VSWR:PRI LINE,1.15;SEC LINE,1.2 CONNECTOR:N (F) DIMENSIONS:(INCHES)5.6L X 0.9W X 4.9H APPROX WEIGHT:(POUNDS)1 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
COUPLER,DIRECTIONAL,COAXIAL	4055-30	99899	1H5985-01-096-6705	DC1SN	NONE
SPECIFICATIONS:	COUPLING:30 DB FREQUENCY RANGE:7.5-16 GHZ DIRECTIVITY:15 DB POWER:50W AVG;2 KW PEAK VSWR:PRI LINE,1.35;SEC LINE,1.4 CONNECTOR:SMA (F) DIMENSIONS:(INCHES)1.8L X 0.4W X 1.3H APPROX WEIGHT:(OUNCES)0.7 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
COUPLER,DIRECTIONAL,COAXIAL	GM-318-C4	60674	9N6625-01-036-2020	DC1WN	4696
SPECIFICATIONS:	COUPLING:40 DB FREQUENCY RANGE:25 MHZ-8 GHZ DIRECTIVITY:20 DB POWER:1W MAX VSWR:PRI LINE 1.3,SEC LINE 1.45 CONNECTOR:C (F) DIMENSIONS:(INCHES)3.1L X 1.3W X 2.4H APPROX WEIGHT:(OUNCES)14 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
COUPLER,DIRECTIONAL,WAVEGUIDE	574-10	00443	1H6625-LL-HHE-8018	DC2AA	NONE
SPECIFICATIONS:	COUPLING:10 DB NOM FREQUENCY RANGE:7.05-10 GHZ DIRECTIVITY:40 DB MIN POWER:10W MAX FLANGE:UG-51/U BRASE (COVER) WAVEGUIDE:WR112 VSWR:PRIMARY LINE-1.10 MAX,AUXILIARY LINE 1.20 MAX DIMENSIONS:(INCHES)19L X 1.75W X 3H APPROX WEIGHT:(POUNDS)4 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
COUPLER,DIRECTIONAL,WAVEGUIDE	X752C	28480	9N5985-00-646-9472	DC2AF	4905
SPECIFICATIONS:	COUPLING:10 DB NOM FREQUENCY RANGE:8.2-12.4 GHZ DIRECTIVITY:40 DB MIN POWER:10W MAX FLANGE:UG-135/U,ALUMINUM (COVER) WAVEGUIDE:WR90 DIMENSIONS:(INCHES)15.6L X 1W X 0.5H APPROX WEIGHT:(POUNDS)3 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX E

NOUN NAME TO STANDARD EQUIPMENTS

NOUN NAME	STANDARD EQUIPMENT	FSCM	ICP/NSN	GMG	SCAT
COUPLER,DIRECTIONAL,WAVEGUIDE	K752C	28480	9I5985-00-913-9842	DC2AM	4907
SPECIFICATIONS:	COUPLING:10 DB NOM FREQUENCY RANGE:18-26.5 GHZ DIRECTIVITY:40 DB MIN POWER:5W MAX FLANGE:UG-595/U,BRASS (COVER) WAVEGUIDE:WR42 DIMENSIONS:(INCHES)10L X 0.5W X 0.3H APPROX WEIGHT:(POUNDS)1 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
COUPLER,DIRECTIONAL,WAVEGUIDE	R752C	28480	9N4931-00-777-1373	DC2AI	4909
SPECIFICATIONS:	COUPLING:10 DB NOM FREQUENCY RANGE:26.5-40 GHZ DIRECTIVITY:40 DB MIN POWER:5W MAX FLANGE:UG-599/U,BRASS (COVER) WAVEGUIDE:WR28 DIMENSIONS:(INCHES)8.6L X 0.4W X 0.2H APPROX WEIGHT:(POUNDS)1 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
COUPLER,DIRECTIONAL,WAVEGUIDE	574-20	00443	1H6625-LL-HHE-8019	DC2NN	NONE
SPECIFICATIONS:	COUPLING:20 DB NOM FREQUENCY RANGE:7.05-10 GHZ DIRECTIVITY:40 DB MIN POWER:100W MAX FLANGE:UG-51/U BRASS (COVER) WAVEGUIDE:WR112 VSWR:PRIMARY LINE-1.10 MAX,AUXILIARY LINE-1.20 MAX DIMENSIONS:(INCHES)19L X 1.75W X 3H APPROX WEIGHT:(POUNDS)4 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
COUPLER,HYBRID,QUADRATURE	QHB-2-30	12457	1R5985-00-991-1013	CQ1NN	4870
SPECIFICATIONS:	FREQUENCY:CENTER 30 MHZ,BANDWIDTH 10% IMPEDANCE:50 OHM NOM POWER:1W AVG VSWR:1.3:1,AMPLITUDE BALANCE:0.6 DB INSERTION LOSS:0.3 DB MAX ISOLATION:25 DB MIN,COUPLING:-3 DB PHASE QUADRATURE:90 DEG +/-3 DEG CONNECTOR:BNC (F) DIMENSIONS:(INCHES)2.25L X 1.7 W X 0.60H APPROX WEIGHT:(OUNCES)1.5 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX E

NOUN NAME TO STANDARD EQUIPMENTS

NOUN NAME	STANDARD EQUIPMENT	FSCM	ICP/NSN	GMG	SCAT
DETECTOR,RF,DIRECTIONAL	3122	99899	1H5895-01-079-0537	DE1NN	NONE
SPECIFICATIONS:	FREQUENCY RANGE:1-18 GHZ FREQUENCY RESPONSE:+/-1.5 DB IMPEDANCE:15 OHM OUTPUT,SHUNTED BY 10 PF VSWR:1.5 MAX CONNECTOR:N (F),BNC (F) DETECTOR OUTPUT POLARITY:NEGATIVE DIMENSIONS:(INCHES)3.1L X 3.6W APPROX WEIGHT:(OUNCES)2.7 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
DETECTOR,RF,FIXED,COAXIAL	423A	28480	9N6625-00-880-4978	DE2AA	4353
SPECIFICATIONS:	FREQUENCY RANGE:0.01-12.4 GHZ FREQUENCY RESPONSE:+/-0.2 DB TO +/-0.5 DB IMPEDANCE:50 OHM NOM VSWR:1.5 MAX POWER:100 MW MAX CONNECTOR:N (M),BNC (F) DIMENSIONS:(INCHES)2L X 0.5 DIA APPROX WEIGHT:(POUNDS)1 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
DETECTOR,RF,FIXED,COAXIAL	8472A-001	28480	1H6625-00-291-1039	DE2NN	4354
SPECIFICATIONS:	FREQUENCY RANGE:0.01-12.4 GHZ FREQUENCY RESPONSE:+/-0.2 DB TO +/-1 DB IMPEDANCE:50 OHM NOM VSWR:1.7 MAX POWER:100 MW MAX CONNECTOR:SMA (M),BNC (F) DIMENSIONS:(INCHES)2L X 0.5 DIA APPROX WEIGHT:(POUNDS)1 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
DETECTOR,RF,FIXED,COAXIAL	8470A	28480	1H6625-00-424-4334	DE2YN	4352
SPECIFICATIONS:	FREQUENCY RANGE:0.01-18 GHZ FREQUENCY RESPONSE:+/-0.2 DB TO +/-1 DB IMPEDANCE:50 OHM NOM VSWR:1.7 MAX POWER:100 MW MAX CONNECTOR:APC-7 (M),BNC (F) DIMENSIONS:(INCHES)2L X 0.5 DIA APPROX WEIGHT:(POUNDS)1 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
DETECTOR,RF,FIXED,COAXIAL	613-M	77327	1H6625-00-973-1151	DE2AN	4348
SPECIFICATIONS:	FREQUENCY RANGE:1-12 GHZ FREQUENCY RESPONSE:+/-0.5 DB IMPEDANCE:50 OHMS NOM VSWR:1.5 MAX POWER:100 MW CONNECTOR:UG-21/U DIMENSIONS:(INCHES)2L X 0.5 DIA APPROX WEIGHT:(POUNDS)0.5 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					

Source: https://assist.dla.mil -- Downloaded: 202610-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX E

NOUN NAME TO STANDARD EQUIPMENTS

NOUN NAME	STANDARD EQUIPMENT	FSCM	ICP/NSN	GMG	SCAT
DETECTOR,RF,TUNABLE,COAXIAL	UNDER REVIEW			DE4UR	4943
SPECIFICATIONS:	FREQUENCY RANGE:2.4-12.4 GHZ CONNECTOR:N (M) DETECTORS:1N21,1N21 OR 821 SERIES BARRETTER DIMENSIONS:(INCHES)4.5L X 1W X 8H APPROX WEIGHT:(POUNDS)1 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
DETECTOR,RF,TUNABLE,WAVEGUIDE	214	00443	1H6625-00-395-0779	DE5AA	NONE
SPECIFICATIONS:	FREQUENCY RANGE:2.6-3.95 GHZ WAVEGUIDE:WR284 FLANGE:UG-53/U,BRASS (COVER) CONNECTOR:BNC (F) CRYSTAL:1N21 DIMENSIONS:(INCHES)9L X 3W X 1.5H APPROX WEIGHT:(POUNDS)4 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
DETECTOR,RF,TUNABLE,WAVEGUIDE	314	00443	1H6625-01-039-5259	DE5AB	NONE
SPECIFICATIONS:	FREQUENCY RANGE:3.95-5.85 GHZ WAVEGUIDE:WR187 FLANGE:UG-149A/U,BRASS (COVER) CONNECTOR:BNC (F) CRYSTAL:1N23 DIMENSIONS:(INCHES)10.2L X 2W X 1H APPROX WEIGHT:(POUNDS)7 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
DETECTOR,RF,FIXED,WAVEGUIDE	P424A	28480	1R6625-00-980-9302	DE3AN	NONE
SPECIFICATIONS:	FREQUENCY RANGE:12.4-18 GHZ FREQUENCY RESPONSE:+/-0.5 DB WAVEGUIDE:WR62 VSWR:1.5 MAX POWER:100 MW MAX FLANGE:UG-419/U,BRASS (COVER) DIMENSIONS:(INCHES)1L X 0.7W X 0.4H APPROX WEIGHT:(POUNDS)0.5 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
DETECTOR,RF,FIXED,WAVEGUIDE	K422A	28480	1H6625-00-874-7733	DE3NN	4966
SPECIFICATIONS:	FREQUENCY RANGE:18-26.5 GHZ FREQUENCY RESPONSE:+/-2 DB WAVEGUIDE:WR42 VSWR:2.5 MAX POWER:100 MW MAX FLANGE:UG-595/U,BRASS (COVER) DIMENSIONS:(INCHES)2L X 0.5W X 0.3H APPROX WEIGHT:(POUNDS)1 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX E

NOUN NAME TO STANDARD EQUIPMENTS

NOUN NAME	STANDARD EQUIPMENT	FSCM	ICP/NSN	GMG	SCAT
DETECTOR,RF,FIXED,WAVEGUIDE	R422A	28480	1R6625-00-981-9518	DE3YN	4965
SPECIFICATIONS:	FREQUENCY RANGE:26.5-40 GHZ FREQUENCY RESPONSE:+/-2 DB WAVEGUIDE:WR28 VSWR:3 MAX POWER:100 MW MAX FLANGE:UG-599/U,BRASS (COVER) DIMENSIONS:(INCHES)2L X 0.4W X 0.2H APPROX WEIGHT:(POUNDS)1 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
DIVIDER,POWER	1506A	93459	9V6625-00-261-5033	DP1NN	4679
SPECIFICATIONS:	FREQUENCY RANGE:DC-18 GHZ VSWR:1.25,DC-10 GHZ;1.35,10-18 GHZ POWER:1W AVG;1 KW PEAK CONNECTOR:N (M-F) INSERTION LOSS:6 DB NOM *OUTPUT PHASE DIFFERENCE:0 DEGREES NOM* DIMENSIONS:(INCHES)1.6L X 1.8W APPROX WEIGHT:(OUNCES)5 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
DIVIDER,VOLTAGE,DECADE	UNDER REVIEW			DR3UR	4678
SPECIFICATIONS:	RATIO:0.00001-1.00000, 5 DIALS, 10 PPM STEPS INPUT IMPEDANCE:10K OHM, +/-150 PPM VOLTAGE RATING:230V MAX FREQUENCY RESPONSE:DC-690 KHZ DEPENDENT ON VOLTAGE ABSOLUTE LINEARITY:+/-0.03 TO +/-20 PPM OF INPUT CONNECTORS:BINDING POSTS DIMENSIONS:(INCHES)17.3L X 3.5W X 6H APPROX WEIGHT:(POUNDS)7.8 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
DUMMY LOAD,COAXIAL	B-1576	91161	1H5985-00-792-9928	DL1EY	4658
SPECIFICATIONS:	FREQUENCY RANGE:DC-1 GHz POWER RATING:200W NOM,5 KW PEAK IMPEDANCE:50 OHM NOM VSWR:1.15 MAX CONNECTOR:LC (F) DIMENSIONS:(INCHES) 25L X 6.3W X 11.25H APPROX WEIGHT:(POUNDS)33 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
DUMMY LOAD,COAXIAL	8201	70998	1H6625-00-994-6797	DL1EN	4683
SPECIFICATIONS:	FREQUENCY RANGE:DC-2.5 GHZ POWER RATING:500W CONTINUOUS IMPEDANCE:50 OHM NOM VSWR:1.1 MAX,DC-1 GHZ;1.25 MAX,1-2.5 GHZ *CONNECTOR:LC (F)* DIMENSIONS:(INCHES)16L X 6W X 8.5H APPROX WEIGHT:(POUNDS)20 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					

Source: https://assist.dla.mil -- Downloaded: 202610-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX E

NOUN NAME TO STANDARD EQUIPMENTS

NOUN NAME	STANDARD EQUIPMENT	FSCM	ICP/NSN	GMG	SCAT
DUMMY LOAD,COAXIAL	8164	70998	1H5985-01-024-8193	DL1EA	NONE
SPECIFICATIONS:	FREQUENCY RANGE:DC-2.5 GHZ POWER RATING:100W CW IMPEDANCE:50 OHM NOM VSWR:1.1 MAX DC-1 GHZ,1.2 MAS 1-2.5 GHZ CONNECTOR:N (F) DIMENSIONS:(INCHES)7G X 2.6W X 1.8H APPROX WEIGHT:(POUNDS)3 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
DUMMY LOAD,COAXIAL	8404	70998	1H6625-01-150-1897	DL1JN	4683
SPECIFICATIONS:	FREQUENCY RANGE:DC-3 GHZ POWER RATING:600W AVG IMPEDANCE:50 OHM NOM VSWR:1.1 MAX,DC-1 GHZ;1.2 MAX,1-3 GHZ CONNECTOR:N (F) DIMENSIONS:(INCHES)16L X 6W X 8.5H APPROX WEIGHT:(POUNDS)20 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
DUMMY LOAD,COAXIAL	8085	70998	9N5985-00-477-8165	DL1NN	NONE
SPECIFICATIONS:	FREQUENCY RANGE:DC-3.5 GHZ POWER RATING:50W CW IMPEDANCE:50 OHM NOM VSWR:1.1 MAX,DC-1 GHZ;1.25 MAX,1-3.5 GHZ CONNECTOR:N (M) DIMENSIONS:(INCHES)5L X 1.8W X 1.8H APPROX WEIGHT:(OUNCES)15 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
DUMMY LOAD,COAXIAL	8135	70998	9N6625-00-773-7311	DL1SN	NONE
SPECIFICATIONS:	FREQUENCY RANGE:DC-4 GHZ POWER RATING:150W CONTINUOUS IMPEDANCE:50 OHM NOM VSWR:1.1 MAX,DC-1 GHZ;1.2 MAX,1-4 GHZ CONNECTOR:N (P) DIMENSIONS:(INCHES)9.5L X 4W X 6.4H APPROX WEIGHT:(POUNDS)6 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
DUMMY LOAD,COAXIAL	DPTC-25KFM	91161	1H5985-01-152-4077	DL1AA	NONE
SPECIFICATIONS:	FREQUENCY RANGE:DC-110 MHZ POWER RATING:25 KW CONTINUOUS IMPEDANCE:50 OHM NOM VSWR:1.15 MAX CONNECTOR:3-1/8 EIA DIMENSIONS:(INCHES)17L X 17W X 65H APPROX WEIGHT:(POUNDS)100 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX E

NOUN NAME TO STANDARD EQUIPMENTS

NOUN NAME	STANDARD EQUIPMENT	FSCM	ICP/NSN	GMG	SCAT
DUMMY LOAD,COAXIAL	DPTC-50KFM	91161	1H5985-01-152-4078	DL1AN	NONE
SPECIFICATIONS:	FREQUENCY RANGE:DC-110 MHZ POWER RATING:55 KW CONTINUOUS IMPEDANCE:50 OHM NOM VSWR:1.15 MAX CONNECTOR:3-1/8 EIA DIMENSIONS:(INCHES)21L X 21W X 71H APPROX WEIGHT:(POUNDS)120 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
DUMMY LOAD,WAVEGUIDE	WF-0025	00929	7G5985-00-539-6126	DL2AN	NONE
SPECIFICATIONS:	FREQUENCY RANGE:2.6-3.95 GHZ POWER RATING:4.5 KW AVG;3200 KW PEAK VSWR:1.1 MAX WAVEGUIDE:RG-75/U;WR284 FLANGE:UG-584/U,ALUMINUM (COVER) DIMENSIONS:(INCHES)14L X 4.9W X 6.4H APPROX WEIGHT:(POUNDS)11.5 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
DUMMY LOAD,WAVEGUIDE	WE-0035	00929	1H6625-01-067-3271	DL2FN	4002
SPECIFICATIONS:	FREQUENCY RANGE:3.95-5.85 GHZ POWER RATING:800W AVG;5250 KW PEAK (INDEPENDENT PEAK POWER RATING ASSUMES NEGLIGIBLE AVG POWER) VSWR:1.1 MAX WAVEGUIDE:RG-95/U,WR187 FLANGE:UG-407/U,ALUMINUM (COVER) DIMENSIONS:(INCHES)7.8L X 5.3W X 5.3H APPROX WEIGHT:(POUNDS)5 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
DUMMY LOAD,WAVEGUIDE	WF-0050	00929	9N5985-00-572-6267	DL2MN	4599
SPECIFICATIONS:	FREQUENCY RANGE:7.05-10 GHZ POWER RATING:600W AVG;460 KW PEAK VSWR:1.1 MAX WAVEGUIDE:RG-68/U;WR112 FLANGE:UG-138/U,ALUMINUM (COVER) DIMENSIONS:(INCHES)6.3L X 2.5W X 3.1H APPROX WEIGHT:(POUNDS)2.8 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
DUMMY LOAD,WAVEGUIDE	WF-0055	00929	9N5985-00-538-7328	DL2YN	4600
SPECIFICATIONS:	FREQUENCY RANGE:8.2-12.4 GHZ POWER RATING:500W AVG;290 KW PEAK VSWR:1.1 MAX WAVEGUIDE:RG-67/U;WR90 FLANGE:UG-135/U,ALUMINUM (COVER) DIMENSIONS:(INCHES)5.7L X 2.8W X 2.8H APPROX WEIGHT:(POUNDS)1.3 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX E

NOUN NAME TO STANDARD EQUIPMENTS

NOUN NAME	STANDARD EQUIPMENT	FSCM	ICP/NSN	GMG	SCAT
FILTER,BANDPASS	A400 BC	16786	1H6625-01-142-5447	FL1EJ	4705
SPECIFICATIONS:	PASSBAND:4-6 GHZ INSERTION LOSS:(PASSBAND) <2 DB REJECTION:STOPBAND >30 DB IMPEDANCE:50 OHM NOM VSWR:1.5 MAX CONNECTOR:N (F) DIMENSIONS:(INCHES)2.3L X 1.3W X 4.1H APPROX WEIGHT:(OUNCES) 6 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
FILTER,BANDPASS	K362A	28480	9N5985-00-488-7434	FL1JN	4728
SPECIFICATIONS:	PASSBAND:18-26.5 GHZ;STOPBAND:31-80 GHZ INSERTION LOSS:(PASSBAND)<1 DB REJECTION:(STOPBAND)>40 DB IMPEDANCE:50 OHM NOM VSWR:1.5 MAX WAVEGUIDE:WR42;FLANGE UG-595/U,BRASS (COVER) DIMENSIONS:(INCHES)2.5L X 0.5W X 0.3H APPROX WEIGHT:(OUNCES)5.3 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
FILTER,LOWPASS	360A	28480	9N5915-00-503-1787	FL2AN	4730
SPECIFICATIONS:	CUT-OFF FREQUENCY:700 MHZ INSERTION LOSS:<1 DB BELOW 630 MHZ REJECTION:>50 DB AT 875 MHZ IMPEDANCE:50 OHM NOM VSWR:<1.6 AT 600-800 MHZ CONNECTOR:N (M-F) DIMENSIONS:(INCHES)10.9L X 1 DIA APPROX WEIGHT:(POUNDS)2 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
FILTER,LOWPASS	360B	28480	9N5915-00-686-8922	FL2FN	4731
SPECIFICATIONS:	CUT-OFF FREQUENCY:1200 MHZ INSERTION LOSS:<1 DB BELOW 1080 MHZ REJECTION:>50 DB AT 1500 MHZ IMPEDANCE:50 OHM NOM VSWR:<1.6 AT 1100-1300 MHZ CONNECTOR:N (M-F) DIMENSIONS:(INCHES)7.2L X 1 DIA APPROX WEIGHT:(POUNDS)2 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
FILTER,LOWPASS	360C	28480	9N5915-00-503-0533	FL2MN	4732
SPECIFICATIONS:	CUT-OFF FREQUENCY:2200 MHZ INSERTION LOSS:<1 DB BELOW 1980 MHZ REJECTION:>50 DB AT 2750 MHZ IMPEDANCE:50 OHM NOM VSWR:<1.6 UP TO 2000 MHZ CONNECTOR:N (M-F) DIMENSIONS:(INCHES)10.7L X 1 DIA APPROX WEIGHT:(POUNDS)2 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					

Source: https://assist.dla.mil -- Downloaded: 202610-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX E

NOUN NAME TO STANDARD EQUIPMENTS

NOUN NAME	STANDARD EQUIPMENT	FSCM	ICP/NSN	GMG	SCAT
FILTER,LOWPASS	360D	28480	9N5915-00-804-5302	FL2TN	4733
SPECIFICATIONS:	CUT-OFF FREQUENCY:4100 MHZ INSERTION LOSS:<1 DB BELOW 3690 MHZ REJECTION:>50 DB AT 5125 MHZ IMPEDANCE:50 OHM NOM VSWR:<1.6 3600-4400 MHZ CONNECTOR:N (M-F) DIMENSIONS:(INCHES)7.3L X 1 DIA APPROX WEIGHT:(POUNDS)2 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
FILTER,LOWPASS	LA-60N	00929	9N5915-00-725-6051	FL2YN	4003
SPECIFICATIONS:	CUT-OFF FREQUENCY:6000 MHZ INSERTION LOSS:0.2 DB BELOW 6000 MHZ REJECTION:25 DB,7200 MHZ INCR TO 55 DB,9000 MHZ IMPEDANCE:50 OHM NOM VSWR:1.4 MAX CONNECTOR:N (M-F) DIMENSIONS:(INCHES)3.2L X 1 DIA APPROX WEIGHT:(OUNCES)3 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
FILTER,LOWPASS	R362A	28480	9N5915-00-488-7437	FL2WG	4729
SPECIFICATIONS:	PASSBAND:26.5-40 GHZ;STOPBAND:47-120 GHZ INSERTION LOSS:(PASSBAND)<2 DB REJECTION:(STOPBAND)>35 DB IMPEDANCE:50 OHM NOM VSWR:1.8 MAX WAVEGUIDE:WR28;FLANGE UG-599/U,BRASS (COVER) DIMENSIONS:(INCHES)1.7L X 0.4W X 0.2H APPROX WEIGHT:(OUNCES)4 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
FILTER,NOTCH	407655	80006	1H5915-00-310-1476	FL3NN	NONE
SPECIFICATIONS:	FREQUENCY RANGE:5.4-5.75 GHZ INSERTION LOSS:0.5 DB AT 5.4-5.75 GHZ REJECTION:>20 DB AT 5.85 GHZ;>30 DB AT 5.88-6 GHZ VSWR:<1.4 AT 5.4-5.75 GHZ POWER RATING:100 KW PEAK WAVEGUIDE:WR187;FLANGE,SPECIAL FGM-100-148 (CHOKE) DIMENSIONS:(INCHES)5.5L X 5.5W X 2.9H APPROX WEIGHT:(POUNDS)5 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
FILTER,VARIABLE	3750	88865	1H6625-00-001-2376	FL4JN	4703
SPECIFICATIONS:	FREQUENCY RANGE:0.02-20 KHZ,VARIABLE FUNCTION:LOW,HIGH,BANDPASS & BAND REJECT BANDWIDTH:VARIABLE WITHIN CUT-OFF FREQ LIMITS INPUT:+/-15V PEAK AT 0 DB,+/-1.5V PEAK AT 20 DB OUTPUT:15V PEAK;3MA PEAK;INT IMPEDANCE 50 OHM NOM POWER REQUIREMNTS:105-125/210-250V,50-400 HZ,10W DIMENSIONS:(INCHES)16.6L X 13.7W X 5.5H APPROX WEIGHT:(POUNDS)26 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX E

NOUN NAME TO STANDARD EQUIPMENTS

NOUN NAME	STANDARD EQUIPMENT	FSCM	ICP/NSN	GMG	SCAI
FILTER,VARIABLE	3202	88865	1H4931-00-178-1052	FL4TN	4704
SPECIFICATIONS:	FREQUENCY RANGE:20 HZ-2 MHZ,VARIABLE FUNCTION:LOW,HIGH,BANDPASS & BAND REJECT BANDWIDTH:VARIABLE WITHIN CUT-OFF FREQ LIMITS INPUT:3V RMS TO 2 MHZ,LP MODE(AC+DC)</=4.2 PEAK OUTPUT:3V RMS;10MA;INT IMPEDANCE 50 OHM NOM POWER REQUIREMENTS:105-125/210-250V,50-400 HZ,15W DIMENSIONS:(INCHES)8.6L X 15.3W X 5.3H APPROX WEIGHT:(POUNDS)9 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
HORN,STANDARD GAIN	BA-C-110C	00341	1H6625-01-030-5505	HN1FN	4008
SPECIFICATIONS:	FREQUENCY RANGE:3.95-5.85 GHZ GAIN:LOW END 15 DB;HIGH END 18 DB BEAM WIDTH:20-30 DEGREES OVER BAND IN BOTH PLANES VSWR:1.15 MAX WAVEGUIDE:(INCHES)1.87 X 2 APPROX,WR137 FLANGE:UG-344/U,BRASS (COVER) DIMENSIONS:(INCHES)10.3L X 4.8W X 6.3H APPROX WEIGHT:(POUNDS)2.3 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
HORN,STANDARD GAIN	640	99899	1R5985-00-729-1297	HN1MN	NONE
SPECIFICATIONS:	FREQUENCY RANGE:8.2-12.4 GHZ GAIN:(MID FREQ VARIATION)1.5 DB/COMPLETE BAND BEAM WIDTH:28 DEGREES APPROX,EQUAL IN E&H PLANES VSWR:1.15 MAX WAVEGUIDE:(INCHES)1 X 1.5 APPROX,WR90 FLANGE:UG-135/U,ALUMINUM (COVER) DIMENSIONS:(INCHES)5L X 2.3W X 3H APPROX WEIGHT:(POUNDS)0.5 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
HORN,STANDARD GAIN	638	99899	9N6625-01-031-1980	HN1TN	4011
SPECIFICATIONS:	FREQUENCY RANGE:18-26.5 GHZ GAIN:(MID FREQ VARIATION)1.5 DB/COMPLETE BAND BEAM WIDTH:28 DEGREES APPROX,EQUAL IN E&H PLANES VSWR:1.15 MAX WAVEGUIDE:(INCHES)0.5 X 0.25 APPROX,WR42 FLANGE:UG-595/U,BRASS (COVER) DIMENSIONS:(INCHES)2.6L X 1.2W X 1.5H APPROX WEIGHT:(POUNDS)0.2 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
HORN,STANDARD GAIN	V637	99899	9N6625-01-031-1981	HN1YN	4012
SPECIFICATIONS:	FREQUENCY RANGE:26.5-40 GHZ GAIN:(MID FREQ VARIATION)1.5 DB/COMPLETE BAND BEAM WIDTH:28 DEGREES APPROX,EQUAL IN E&H PLANES VSWR:1.15 MAX WAVEGUIDE:(INCHES)0.36 X 0.22 APPROX,WR28 FLANGE:UG-599/U,BRASS (COVER) DIMENSIONS:(INCHES)1.8L X 0.78W X 1H APPROX WEIGHT:(POUNDS)0.1 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX E

NOUN NAME TO STANDARD EQUIPMENTS

NOUN NAME	STANDARD EQUIPMENT	FSCM	ICP/NSN	GMG	SCAT
INDUCTOR,DECADE	1491-9704	24655	1H6625-00-251-1158	LN1NN	NONE
SPECIFICATIONS:	RANGE:0-11.1H IN 0.001H STEPS ZERO INDUCTANCE:1 UH APPROX VOLTAGE:500V RMS RANGE SELECTOR:FIVE ROTARY SWITCHES CONNECTOR:THREE BINDING POSTS DIMENSIONS:(INCHES)7L X 17W X 9H APPROX WEIGHT:(POUNDS)23 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
ISOLATOR,COAXIAL	L20PS	14135	9Q6625-00-738-2716	SR1FN	4798
SPECIFICATIONS:	FREQUENCY RANGE:1-2 GHZ VSWR:1.25 MAX CONNECTOR:N (F-F) ISOLATION:10 DB INSERTION:1.5 DB DIMENSIONS:(INCHES)7.4L X 2.1W APPROX WEIGHT:(OUNCES)36 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
ISOLATOR,COAXIAL	S11PS	14135	9N5985-00-439-3536	SR1MN	4799
SPECIFICATIONS:	FREQUENCY RANGE:2-4 GHZ VSWR:1.15 MAX CONNECTOR:N (F-F) ISOLATION:20 DB MIN INSERTION LOSS:0.7 DB MAX DIMENSIONS:(INCHES)6.9L X 2.1W APPROX WEIGHT:(OUNCES)38 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
ISOLATOR,COAXIAL	C20PS	14135	1H4931-00-921-7357	SR1TN	4797
SPECIFICATIONS:	FREQUENCY RANGE:4-8 GHZ VSWR:1.20 MAX CONNECTOR:N (F-F) ISOLATION:15 DB MIN INSERTION LOSS:1 DB MAX DIMENSIONS:(INCHES)6.7L X 2.1W APPROX WEIGHT:(OUNCES)24 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
ISOLATOR,COAXIAL	CX20PS	14135	9N5985-00-145-3514	SR1YN	4800
SPECIFICATIONS:	FREQUENCY RANGE:7-11 GHZ VSWR:1.25 MAX CONNECTOR:N (F-F) ISOLATION:15 DB MIN INSERTION LOSS:1 DB MAX DIMENSIONS:(INCHES)5.11 X 1.8W APPROX WEIGHT:(OUNCES)16 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					

Source: https://assist.dla.mil -- Downloaded: 202610-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX E

NOUN NAME TO STANDARD EQUIPMENTS

NOUN NAME	STANDARD EQUIPMENT	FSCM	ICP/NSN	GMG	SCAT
MIXER,BALANCED,DOUBLE	10514A	28480	9N5985-00-087-4714	MX1NN	NONE
SPECIFICATIONS:	FREQUENCY RANGE:0.2-500 MHZ CONNECTOR:BNC (F) IMPEDANCE:50 OHM NOM INPUT LEVEL:0.0040A MAX INPUT POWER:0.005W MAX DIMENSIONS:(INCHES)2L X 3W APPROX WEIGHT:(POUNDS)1 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
MODULATOR,WAVEGUIDE	UNDER REVIEW			ML1UR	NONE
SPECIFICATIONS:	FREQUENCY RANGE:8.2-10.6 GHZ VSWR:1.30 MAX WAVEGUIDE:WR90,FLANGE UG-39/U,BRASS (COVER) ATTENUATION:25 DB MAX INSERTION:1 DB MODULATION SPEED:0.2 KHZ DIMENSIONS:(INCHES)3.5L X 1W X 0.5H APPROX WEIGHT:(OUNCES)8 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
POWER SUPPLY,DIRECT VOLTAGE	JQE-36-3M	85604	1H6130-00-471-1735	PS1AN	NONE
SPECIFICATIONS:	OUTPUT:0-36V;0-3A LOAD EFFECT:VOLTS,0.005% OR 200 UV;AMPS,0.01% SOURCE EFFECT:VOLTS,0.0005%;AMPS,0.005% DRIFT:VOLTS,0.01% OR 0.001V;AMPS,0.02% RIPPLE:VOLTS,200 UV RMS;AMPS,0.02% FEATURES:MODULAR;CONSTANT VOLTS & CURRENT;METERED DIMENSIONS:(INCHES)18L X 4W X 4.8H APPROX WEIGHT:(POUNDS)19 APPROX				
THIS EQUIPMENT IS CLASSIFIED AS TYPE III, CLASS 5, STYLE E, AND COLOR R FOR NAVY USE IN ACCORDANCE WITH MIL-T-28800 AS APPLICABLE.					
POWER SUPPLY,DIRECT VOLTAGE	6266B	28480	9G6130-00-137-0167	PS1BA	4042
SPECIFICATIONS:	OUTPUT:0-40V;0-5A LOAD EFFECT:VOLTS,0.01%+200 UV;AMPS,0.02%+500 UA SOURCE EFFECT:VOLTS,0.01%+200 UV;AMPS,0.02%+500 UA DRIFT:VOLTS,0.03%+500 UV;AMPS,0.03%+0.003A RIPPLE:VOLTS,200 UA;AMPS,0.003A RMS FEATURES:CONSTANT VOLTS AND CURRENT;REMOTE SENSING DIMENSIONS:(INCHES)17.5L X 16.8W X 3.3H APPROX WEIGHT:(POUNDS)34 APPROX				
THIS EQUIPMENT IS CLASSIFIED AS TYPE III, CLASS 5, STYLE E, AND COLOR R FOR NAVY USE IN ACCORDANCE WITH MIL-T-28800 AS APPLICABLE.					

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX E

NOUN NAME TO STANDARD EQUIPMENTS

NOUN NAME	STANDARD EQUIPMENT	FSCM	ICP/NSN	GMG	SCAT
POWER SUPPLY,DIRECT VOLTAGE	DCR40-25B	49956	1H6130-01-040-9808	PS1BN	4792
SPECIFICATIONS:	OUTPUT:0-40V;0-25A LOAD EFFECT:VOLTS,0.01%+0.004V;AMPS,0.25% SOURCE EFFECT:VOLTS,0.01%+0.004V;AMPS,0.25% DRIFT:VOLTS,0.1%;AMPS,0.15% RIPPLE:VOLTS,0.09V;AMPS,0.056A FEATURES:CONSTANT VOLTS AND CURRENT;REMOTE SENSING DIMENSIONS:(INCHES)18L X 17W X 5.8H APPROX WEIGHT:(POUNDS)70 APPROX				
THIS EQUIPMENT IS CLASSIFIED AS TYPE III, CLASS 5, STYLE E, AND COLOR R FOR NAVY USE IN ACCORDANCE WITH MIL-T-28800 AS APPLICABLE.					
POWER SUPPLY,DIRECT VOLTAGE	R-1011B	94990	1H6625-01-205-1224	PS1BY	NONE
SPECIFICATIONS:	OUTPUT:1-40 IN 2 RANGES:0-40A IN 3 RANGES LOAD EFFECT:VOLTS,0.1% OF FULL SCALE SOURCE EFFECTS:VOLTS,0.1% OF FULL SCALE DRIFT:VOLTS,0.1% RIPPLE:VOLTS,0.02V RMS FEATURES:SHORT PROTECTION;RFI/EMI PROTECTED,220-240 VAC,50-60 HZ AVAILABLE THRU SHORTING BARS DIMENSIONS:(INCHES)20D X 16W X 8H APPROX WEIGHT:(POUNDS)75 APPROX				
THIS EQUIPMENT IS CLASSIFIED AS TYPE III, CLASS 5, STYLE E, AND COLOR R FOR NAVY USE IN ACCORDANCE WITH MIL-T-28800 AS APPLICABLE.					
POWER SUPPLY,DIRECT VOLTAGE	5015V	98095	1H6625-01-224-0215	PS1DN	4115
SPECIFICATIONS:	OUTPUT:0-50 VDC,0-1.5A,CONTINUOUSLY ADJUSTABLE LOAD EFFECT:<500 UA FOR INPUT VOLTAGES OF 105-125V SOURCE EFFECT:>.005%+1MV FOR LINE VOLTS OF +/-10% DRIFT:CONSTANT VOLTS MODE-<0.01%+5MV PER 24 HOURS DRIFT:CONSTANT CURRENT MODE-<.05%+500 UA PER 24HRS RIPPLE:CONSTANT VOLTS MODE-<1 MV PEAK TO PEAK RIPPLE:CONSTANT CURRENT MODE-<500 UA PEAK TO PEAK FEATURES:CONSTANT VOLTAGE/CURRENT,REMOTE SENSING DIMENSIONS:(INCHES)11.75L X 8.75W X 4.75H APPROX WEIGHT:(POUNDS) 15 APPROX				
THIS EQUIPMENT IS CLASSIFIED AS TYPE III, CLASS 5, STYLE E, AND COLOR R FOR NAVY USE IN ACCORDANCE WITH MIL-T-28800 AS APPLICABLE.					
POWER SUPPLY,DIRECT VOLTAGE	6294A	28480	&&6130-01-062-6739	PS1FA	NONE
SPECIFICATIONS:	OUTPUT:0-60V;0-1A LOAD EFFECT:VOLTS,0.01%+0.002V;AMPS,0.01%+250 UA SOURCE EFFECT:VOLTS,0.01%+0.002V;AMPS,0.01%+250 UA DRIFT:VOLTS,0.1%+0.0025V;AMPS,0.1%+0.0025A RIPPLE:VOLTS,200 UV;AMPS,500 UA RMS FEATURES:CONSTANT VOLTS AND CURRENT;REMOTE SENSING DIMENSIONS:(INCHES)14.5L X 8.2W X 3.4H APPROX WEIGHT:(POUNDS)13 APPROX				
THIS EQUIPMENT IS CLASSIFIED AS TYPE III, CLASS 5, STYLE E, AND COLOR R FOR NAVY USE IN ACCORDANCE WITH MIL-T-28800 AS APPLICABLE.					

Source: https://assist.dla.mil -- Downloaded: 202610-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX E

NOUN NAME TO STANDARD EQUIPMENTS

NOUN NAME	STANDARD EQUIPMENT	FSCM	ICP/NSN	GMG	SCAT
POWER SUPPLY,DIRECT VOLTAGE	6296A	28480	1H6130-01-067-3777	PS1FN	NONE
SPECIFICATIONS:	OUTPUT:0-60V;0-3A LOAD EFFECT:VOLTS,0.01%+0.001V;AMPS,0.5%+0.001A SOURCE EFFECT:VOLTS,0.01%+0.001V;AMPS,0.05%+0.001A DRIFT:VOLTS,0.1%+0.0025V;AMPS,0.1%+0.0075A RIPPLE:VOLTS,500 UV;AMPS,0.003A RMS FEATURES:CONSTANT VOLTS AND CURRENT;REMOTE SENSING DIMENSIONS:(INCHES)17.1L X 8.2W X 5H APPROX WEIGHT:(POUNDS)25 APPROX				
THIS EQUIPMENT IS CLASSIFIED AS TYPE III, CLASS 5, STYLE E, AND COLOR R FOR NAVY USE IN ACCORDANCE WITH MIL-T-28800 AS APPLICABLE.					
POWER SUPPLY,DIRECT VOLTAGE	6274B	28480	7Z6130-00-160-0827	PS1FY	NONE
SPECIFICATIONS:	OUTPUT:0-60V;0-15A LOAD EFFECT:VOLTS,0.01%+200 UV;AMPS,0.02%+500 UA SOURCE EFFECT:VOLTS,0.01%+200 UV;AMPS,0.02%+500 UA DRIFT:VOLTS,0.03%+0.002V;AMPS,0.03%+0.005A RIPPLE:VOLTS,200 UV;AMPS,0.005A RMS FEATURES:CONSTANT VOLTS AND CURRENT;REMOTE SENSING DIMENSIONS:(INCHES)17.5L X 16.8W X 5H APPROX WEIGHT:(POUNDS)48 APPROX				
THIS EQUIPMENT IS CLASSIFIED AS TYPE III, CLASS 5, STYLE E, AND COLOR R FOR NAVY USE IN ACCORDANCE WITH MIL-T-28800 AS APPLICABLE.					
POWER SUPPLY,DIRECT VOLTAGE	6299A	28480	4G6130-00-406-5695	PS1HN	4040
SPECIFICATIONS:	OUTPUT:0-100V,0-0.75A LOAD EFFECT:VOLTS 0.01%+0.002V,AMPS 0.01%+250 UA SOURCE EFFECT:VOLTS 0.01%+0.002V,AMPS 0.01%+250 UA DRIFT:VOLTS 0.1%+0.0025v,AMPS 0.1%+0.002A RIPPLE:VOLTS 200 UV,AMPS 500 UA RMS FEATURES:CONSTANT VOLTS AND CURRENT,REMOTE SENSING DIMENSIONS(INCHES)14.6L X 8.2W X 3.4H APPROX WEIGHT:(POUNDS)13 APPROX				
THIS EQUIPMENT IS CLASSIFIED AS TYPE III, CLASS 5, STYLE E, AND COLOR R FOR NAVY USE IN ACCORDANCE WITH MIL-T-28800 AS APPLICABLE.					
POWER SUPPLY,DIRECT VOLTAGE	6443B	28480	1H6130-00-163-6201	PS1KN	NONE
SPECIFICATIONS:	OUTPUT:0-120V;0-2.5A LOAD EFFECT:VOLTS;0.12V;AMPS,0.025A SOURCE EFFECT:VOLTS,0.06V;AMPS,0.025A DRIFT:VOLTS,0.1%+0.006V;AMPS,0.025A RIPPLE:VOLTS,0.24V;AMPS,DEPENDENT ON LOAD FEATURES:CONSTANT VOLTS AND CURRENT;REMOTE SENSING DIMENSIONS:(INCHES)17.5L X 16.8W X 3.3H APPROX WEIGHT:(POUNDS)31 APPROX				
THIS EQUIPMENT IS CLASSIFIED AS TYPE III, CLASS 5, STYLE E, AND COLOR R FOR NAVY USE IN ACCORDANCE WITH MIL-T-28800 AS APPLICABLE.					

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX E

NOUN NAME TO STANDARD EQUIPMENTS

NOUN NAME	STANDARD EQUIPMENT	FSCM	ICP/NSN	GMG	SCAT
POWER SUPPLY,DIRECT VOLTAGE	DCR150-12B	49956	7Z6625-01-136-3178	PS1MN	4051
SPECIFICATIONS:	OUTPUT:0-150V,0-12A LOAD EFFECT:VOLTS,0.01%+0.004V;AMPS,0.25% SOURCE EFFECT:VOLTS,0.01%+0.004V;AMPS,0.25% DRIFT:VOLTS,0.1%;AMPS,0.15% RIPPLE:VOLTS,0.3V;AMPS,0.024A FEATURES:CONSTANT VOLTS AND CURRENT;REMOTE SENSING DIMENSIONS:(INCHES)21L X 18W X 7.8H APPROX WEIGHT:(POUNDS)90 APPROX				
	THIS EQUIPMENT IS CLASSIFIED AS TYPE III, CLASS 5, STYLE E, AND COLOR B FOR NAVY USE IN ACCORDANCE WITH MIL-T-28800 AS APPLICABLE.				
POWER SUPPLY,DIRECT VOLTAGE	UNDER REVIEW			PS1UR	NONE
SPECIFICATIONS:	OUTPUT:0-160V,0.2A LOAD EFFECT:VOLTS 0.02%+0.002V,AMPS 200 UA SOURCE EFFECT:VOLTS 0.02%+0.002V,AMPS 200 UA DRIFT:VOLTS 0.1%+0.005V,AMPS 0.1%+750 UA RIPPLE:VOLTS 500 UV, AMPS 200 UA RMS FEATURES:CONSTANT VOLTS AND CURRENT,REMOTE SENSING DIMENSIONS:(INCHES)8.5L X 12.5W X 3.5H APPROX WEIGHT:(POUNDS)10 APPROX				
	THIS EQUIPMENT IS CLASSIFIED AS TYPE III, CLASS 5, STYLE E, AND COLOR B FOR NAVY USE IN ACCORDANCE WITH MIL-T-28800 AS APPLICABLE.				
POWER SUPPLY,DIRECT VOLTAGE	LQ-415	80103	1H6625-01-178-9497	PS1RN	NONE
SPECIFICATIONS:	OUTPUT:0-250V;0-0.08A LOAD EFFECT:0.005% + 0.5 MV SOURCE EFFECT:0.005% + 0.5 MV DRIFT:VOLTS,0.2% RIPPLE:VOLTS,300 UV RMS,1MV P-P FEATURES:SERIES/PARALLEL OPERATION;REMOTE SENSING DIMENSIONS:(INCHES)10L X 5.2W X 4.2H APPROX WEIGHT:(POUNDS)9 APPROX				
	THIS EQUIPMENT IS CLASSIFIED AS TYPE III, CLASS 5, STYLE E, AND COLOR B FOR NAVY USE IN ACCORDANCE WITH MIL-T-28800 AS APPLICABLE.				
POWER SUPPLY,DIRECT VOLTAGE	TCR-300S-3-1	89022	1H6625-LL-HHE-4110	PS1TN	4129
SPECIFICATIONS:	OUTPUT:0-300V; 0-3A LOAD EFFECT:VOLTS,0.1%;AMPS,0.1% SOURCE EFFECTS:VOLTS,0.1%;AMPS,0.1% DRIFT:VOLTS,0.05%;AMPS,0.05% RIPPLE;VOLTS,0.25V;AMPS,0.003A RMS FEATURES:CONSTANT VOLTS & CURRENT,REMOTE SENSING DIMSNSIONS:(INCHES)21L X 19W X 3.5H APPROX WEIGHT:(POUNDS)64 APPROX				
	THIS EQUIPMENT IS CLASSIFIED AS TYPE III, CLASS 5, STYLE E, AND COLOR B FOR NAVY USE IN ACCORDANCE WITH MIL-T-28800 AS APPLICABLE.				

Source: https://assist.dla.mil -- Downloaded: 202610-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX E

NOUN NAME TO STANDARD EQUIPMENTS

NOUN NAME	STANDARD EQUIPMENT	FSCM	ICP/NSN	GMG	SCAT
POWER SUPPLY,DIRECT VOLTAGE	BHK-500-0.4M	85604	7Z6625-01-031-8855	PS1VN	4114
SPECIFICATIONS:	OUTPUT:0-500V;0-0.4A LOAD EFFECT:VOLTS,0.01% OR 0.001V;AMPS,100 UA SOURCE EFFECT:VOLTS 0.01%,AMPS <100.0 MA DRIFT:VOLTS,0.01% OR 0.002V;AMPS,0.01% RIPPLE:VOLTS,0.001V RMS;AMPS,100 UA FEATURES:CONSTANT VOLTS AND CURRENT;REMOTE SENSING DIMENSIONS:(INCHES)16.3L X 19W X 5.2H APPROX WEIGHT:(POUNDS)46 APPROX				
THIS EQUIPMENT IS CLASSIFIED AS TYPE III, CLASS 5, STYLE E, AND COLOR B FOR NAVY USE IN ACCORDANCE WITH MIL-T-28800 AS APPLICABLE.					
POWER SUPPLY,DIRECT VOLTAGE.	UNDER REVIEW			PS1UR	NONE
SPECIFICATIONS:	OUTPUT:0-2 KV,0-0.1A LOAD EFFECT:VOLTS,0.005% OR 0.02V,2% OR 0.001 AMP SOURCE EFFECT:VOLTS,0.005% OR 0.02V:AMPS,0.001A DRIFT:VOLTS,0.036%+0.003V:AMPS,0.25%+0.00025A RIPPLE:VOLTS,0.001V AMPS,0.001A RMS FEATURES:CONSTANT VOLTS AND CURRENT, SHORT PROOF DIMENSIONS(INCHES)17.9L X 16.8W X 5H APPROX WEIGHT:(POUNDS)63 APPROX				
THIS EQUIPMENT IS CLASSIFIED AS TYPE III, CLASS 5, STYLE E, AND COLOR B FOR NAVY USE IN ACCORDANCE WITH MIL-T-28800 AS APPLICABLE.					
REGULATOR,LINE	1571-9831	13850	9G6110-00-087-4771	RACAA	4802
SPECIFICATIONS:	INPUT:115 VAC +/-10%;57-63 HZ OUTPUT:103-127 VAC VARIABLE,CURRENT 50A KVA RATING:5.8 CORRECTION RATE:2.5 HZ +1.5 HZ/V,GIVEN IN HZ OF THE LINE FREQUENCY REGULATION:+/-0.25% DIMENSIONS:(INCHES)7H X 19W X 12D APPROX WEIGHT:(POUNDS)53 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
RESISTOR,DECADE	1433-9704	24655	9N6625-00-173-5441	RE1GF	4639
SPECIFICATIONS:	RANGE:0-11,110 OHM;1 OHM INCR;4 DECADES ACCURACY:+/-0.01%+0.002 OHM MAX CURRENT:0.023-0.8A DEPENDENT ON RESISTANCE ZERO RESISTANCE:0.001 OHM PER DECADE RESISTOR TYPE:WIRE WOUND CONNECTORS:BINDING POSTS DIMENSIONS:(INCHES) 3.5H X 12.3W X 5D APPROX WEIGHT:(POUNDS)5.5 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX E

NOUN NAME TO STANDARD EQUIPMENTS

NOUN NAME	STANDARD EQUIPMENT	FSCM	ICP/NSN	GMG	SCAT
RESISTOR,DECADE	1433-9706	24655	&&6625-00-235-6308	RE1KJ	NONE
SPECIFICATIONS:	RANGE:0-111,100 OHM;10 OHM INCR;4 DECADES ACCURACY:+/-0.01%+0.002 OHM MAX CURRENT:0.007-0.25A DEPENDENT ON RESISTANCE ZERO RESISTANCE:0.001 OHM PER DECADE RESISTOR TYPE:WIRE WOUND CONNECTORS:BINDING POSTS DIMENSIONS:(INCHES) 3.5H X 12.3W X 5D APPROX WEIGHT:(POUNDS)4.8 APPROX				
	CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.				
RESISTOR,DECADE	1433-9714	24655	1H6625-00-463-4011	RE1GM	4634
SPECIFICATIONS:	RANGE:0-111,110 OHM;1 OHM INCR;5 DECADES ACCURACY:+/-0.01%+0.002 OHM MAX CURRENT:0.007-0.8A DEPENDENT ON RESISTRANCE ZERO RESISTANCE:0.001 OHM PER DECADE RESISTOR TYPE:WIRE WOUND CONNECTORS:BINDING POSTS DIMENSIONS:(INCHES) 3.5H X 14.8W X 5D APPROX WEIGHT:(POUNDS)6.5 APPROX				
	CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.				
RESISTOR,DECADE	1433-9722	24655	1H6625-00-947-7534	RE1DN	4630
SPECIFICATIONS:	RANGE:0-111,111 OHM;0.1 OHM INCR;6 DECADES ACCURACY:+/-0.01%+0.002 OHM MAX CURRENT:0.007-1.6A DEPENDENT ON RESISTANCE ZERO RESISTANCE:0.001 OHM PER DECADE RESISTOR TYPE:WIRE WOUND CONNECTORS:BINDING POSTS DIMENSIONS:(INCHES) 3.5H X 17.3W X 5D APPROX WEIGHT:(POUNDS)8.5 APPROX				
	CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.				
RESISTOR,DECADE	1433-9729	24655	1H6625-01-205-0820	RE1AN	NONE
SPECIFICATIONS:	RANGE:0:111,111.1 OHM;0.01 OHM INCR;7 DECADES ACCURACY:+/-0.01%+0.002 OHM MAX CURRENT:0.007-4A DEPENDENT ON FREQUENCY ZERO RESISTANCE:0.001 OHM PER DECADE RESISTOR TYPE:WIRE WOUND CONNECTIONS:BINDING POSTS DIMENSIONS:(INCHES) 5.3 H X 17.3W X 5D APPROX WEIGHT:(POUNDS) 8.8 APPROX				
	CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.				
RESISTOR,DECADE	240C	12697	1H6625-00-585-4915	RE1GT	4635
SPECIFICATIONS:	RANGE:1-999,999 OHMS,6 DECADES,ONE OHM INCREMENTS ACCURACY:+/-5%,DECADE NO.1,+/-2%,DECADES 2-6 MAX CURRENT:0.005-5A DEPENDENT ON RESISTANCE ZERO RESISTANCE:<0.2 OHM RESISTOR TYPE:WIRE WOUND CONNECTORS:BINDING POSTS DIMENSIONS:(INCHES)131 X 8.5W X 5.8H APPROX WEIGHT:(POUNDS)11.5 APPROX				
	CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.				

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX E

NOUN NAME TO STANDARD EQUIPMENTS

NOUN NAME	STANDARD EQUIPMENT	FSCM	ICP/NSN	CMG	SCAT
RESISTOR,DECADE	1433-9724	24655	1H6625-00-031-3521	RE1GY	4636
SPECIFICATIONS:	RANGE:0-1,111,110 OHM;1 OHM INCR;6 DECADES ACCURACY:+/-0.01%+0.002 OHM MAX CURRENT:0.0023-0.8A DEPENDENT ON RESISTANCE ZERO RESISTANCE:0.001 OHM PER DECADE RESISTOR TYPE:WIRE WOUND CONNECTORS:BINDING POSTS DIMENSIONS:(INCHES) 3.5H X 17.3W X 5D APPROX WEIGHT:(POUNDS)8.5 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
RESISTOR,DECADE	1433-9731	24655	1H6625-00-480-0950	RE1DY	NONE
SPECIFICATIONS:	RANGE:0-1,111,111 OHM;0.1 OHM INCR;7 DECADES ACCURACY:+/-0.01%+0.002 OHM MAX CURRENT:0.0023-4A DEPENDENT ON RESISTANCE ZERO RESISTANCE:0.001 OHM PER DECADE RESISTOR TYPE:WIRE WOUND CONNECTORS:BINDING POSTS DIMENSIONS:(INCHES) 5.3H X 17.3W X 5D APPROX WEIGHT:(POUNDS)10.3 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
RESISTOR,DECADE	1433-9726	24655	1H6625-00-140-8183	RE1KI	4637
SPECIFICATIONS:	RANGE:0-11,111,110 OHM;10 OHM INCR;6 DECADES ACCURACY:+/-0.01%+0.002 OHM MAX CURRENT:0.0007-0.25A DEPENDENT ON RESISTANCE ZERO RESISTANCE:0.001 OHM PER DECADE RESISTOR TYPE:WIRE WOUND CONNECTORS:BINDING POSTS DIMENSIONS:(INCHES) 3.5H X 17.3W X 5D APPROX WEIGHT:(POUNDS)7 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
TERMINATION,COAXIAL	80M	70998	9Y5840-00-669-8675	TM1SA	NONE
SPECIFICATIONS:	FREQUENCY RANGE:DC-4 GHZ POWER RATING:5W CONTINUOUS IMPEDANCE:50 OHM NOM VSWR:1.1 MAX,DC-1 GHZ & 1.2 MAX,1-4 GHZ CONNECTOR:N (M),FOR N (F) ORDER MODEL 80F DIMENSIONS:(INCHES)0.7L X 3.4W APPROX WEIGHT:(OUNCES)4 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
TERMINATION,COAXIAL	376BNF	99899	9N5985-00-241-3518	TM1FN	4684
SPECIFICATIONS:	FREQUENCY RANGE:DC-12.4 GHZ POWER:40W AVG,7.5 KW PEAK IMPEDANCE:50 OHM NOM VSWR:1.09 MAX CONNECTOR:M,SPECIFY (M)OR(F) DIMENSIONS:(INCHES) 1.6L X 4.9W APPROX WEIGHT:(OUNCES)10 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					

Source: https://assist.dla.mil -- Downloaded: 202610-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX E

NOUN NAME TO STANDARD EQUIPMENTS

NOUN NAME	STANDARD EQUIPMENT	FSCM	ICP/NSN	GMG	SCAT
TERMINATION,COAXIAL	1425-4	93459	1H6930-01-140-4985	TM1MN	NONE
SPECIFICATIONS:	FREQUENCY RANGE:DC-12.4 GHZ POWER:10W AVG;10 KW PEAK IMPEDANCE:50 OHM NOM VSWR:1.3 MAX CONNECTOR:N (M),FOR N (F) ORDER MODEL 1425-3 DIMENSIONS:(INCHES) 3.3L X 1 DIA APPROX WEIGHT:(OUNCHES) 4 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
TERMINATION,COAXIAL	4375G	99899	1H6625-LL-HHE-8020	TM1WP	NONE
SPECIFICATIONS:	FREQUENCY RANGE:DC-18.0 GHZ POWER RATING:10W AVG,5 KW PEAK IMPEDANCE:50 OHM NOM VSWR:1.05 MAX CONNECTOR:N,FOR ENDS,SPECIFY M=MALE,F=FEMALE DIMENSIONS:(INCHES)1.624L X 1 SQUARE APPROX WEIGHT:(OUNCES)4 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
TERMINATION,COAXIAL	2001-6113-00	16179	9N5985-01-064-2513	TM1TJ	4950
SPECIFICATIONS:	FREQUENCY RANGE:DC-18 GHZ POWER:0.5W AVG IMPEDANCE:50 OHMS NOM VSWR:1.3 MAX CONNECTOR:OSM PLUG DIMENSIONS:(INCHES) 0.61 X 0.3 DIA (APPROX) WEIGHT:(OUNCHES) 0.1 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
TERMINATION,COAXIAL	2002-6113-00	16179	9N5985-00-192-0138	TM1TT	4944
SPECIFICATIONS:	FREQUENCY RANGE:DC-18 GHZ POWER:0.5W AVG IMPEDANCE:50 OHM NOM VSWR:1.3 MAX CONNECTOR:OSM JACK DIMENSIONS:(INCHES) 0.61 X 0.3 DIA APPROX WEIGHT:(OUNCES) 0.1 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
TERMINATION,COAXIAL	371BNM	99899	1H6625-00-970-3685	TM1YN	4685
SPECIFICATIONS:	FREQUENCY RANGE:2-18 GHZ POWER:10W AVG;5 KW PEAK IMPEDANCE:50 OHM NOM VSWR:1.09 MAX CONNECTOR:N,SPECIFY (M)OR(F) DIMENSIONS:(INCHES) 7.3L X 1 DIA APPROX WEIGHT:(OUNCES) 6 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					

Source: https://assist.dla.mil -- Downloaded: 202610-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX E

NOUN NAME TO STANDARD EQUIPMENTS

NOUN NAME	STANDARD EQUIPMENT	FSCM	ICP/NSN	GMG	SCAT
TERMINATION,WAVEGUIDE	S501B	00929	1H6625-00-535-9532	TM2JN	NONE
SPECIFICATIONS:	FREQUENCY RANGE:2.6-3.95 GHZ POWER:5W AVG VSWR:1.025 MAX WAVEGUIDE:WR284,RG48 FLANGE:UG-53/U (COVER) DIMENSIONS:(INCHES)9.9L X 3W X 1.5H APPROX WEIGHT:(POUNDS)3.5 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
TERMINATION,WAVEGUIDE	UNDER REVIEW			TM2UR	NONE
SPECIFICATIONS:	FREQUENCY RANGE:8.5-9.6 GHZ POWER RATING:4W MAX VSWR:1.1 MAX WAVEGUIDE:RG-52/U,WR90 FLANGE:UG-39/U,BRASS(COVER) DIMENSIONS:(INCHES)1.53L X 1W X 0.5H APPROX WEIGHT:(POUNDS)2 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
TERMINATION,WAVEGUIDE	X301A	13047	1H5985-01-069-2318	TM2TN	4892
SPECIFICATIONS:	FREQUENCY RANGE:8.2-12.4 GHZ POWER:2W AVG;1 KW PEAK VSWR:1.02 MAX WAVEGUIDE:WR90 FLANGE:UG-39/U,BRASS (COVER) DIMENSIONS:(INCHES)5L X 1W X 0.5H APPROX WEIGHT:(POUNDS)0.7 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
TRANSFORMER,AUTO	W5MT3A	13850	9N5950-00-987-5601	TR1AA	4653
SPECIFICATIONS:	INPUT:120 VAC,50-60 HZ,SINGLE PHASE RATED CURRENT:5.0 AMPERES OUTPUT VOLTAGE RATING:0-140 VAC MAX METER RANGE:(FULL SCALE) AMPERES 1&5,VOLTS 150 MOUNTING:ENCLOSED DIMENSIONS:(INCHES)9.5H X 6.75W X 5.25D APPROX WEIGHT:(POUNDS)11 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
TRANSFORMER,AUTO	W10MT3A	13850	9S6120-00-054-7794	TR1AN	4656
SPECIFICATIONS:	INPUT:120 VAC,50-60 HZ,SINGLE PHASE RATED CURRENT:10.0 AMPERES OUTPUT VOLTAGE RATING:0-140 VAC MAX METER RANGE:(FULL SCALE)AMPERES 2&10,VOLTS 150 MOUNTING:ENCLOSED DIMENSIONS:(INCHES)11.94H X 8.63W X 5.38D APPROX WEIGHT:(POUNDS)18 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX E

NOUN NAME TO STANDARD EQUIPMENTS

NOUN NAME	STANDARD EQUIPMENT	FSCM	ICP/NSN	GMG	SCAI
TRANSFORMER,AUTO	M5	13850	9N5950-00-504-9090	TR1FN	4655
SPECIFICATIONS:	INPUT:120 VAC,400 HZ,SINGLE PHASE RATED CURRECT:6.0 AMPERES,7.8 AMPERES MAX KVA RATING:0.94 KVA (MAX LOAD CURRENT X INPUT VAC) OUTPUT VOLTAGE RATING:0-140 VAC MOUNTING:OPEN DIMENSIONS:(INCHES)4.94H X 4.5W X 2.69D APPRX WEIGHT:(POUNDS)3 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
TRANSFORMER,AUTO	M2G3	13850	9N5950-00-877-4863	TR1MN	4652
SPECIFICATIONS:	INPUT:120-208-240 VAC,400 HZ,THREE PHASE RATED CURRENT:2.4 AMPERES,3.1 AMPERES MAX KVA RATING:1.30 KVA (MAX LOAD CURRENT X INPUT VAC) OUTPUT VOLTAGE RATING:0-240 VAC OVERVOLTAGE:17% PERMITTED ON 120/208 VAC INPUT MOUNTING:OPEN,WYE CONNECTION DIMENSIONS:(INCHES)3.69H X 3.5W X 8.25D APPROX WEIGHT:(POUNDS)5 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
TRANSFORMER,AUTO	W5G3M	13850	9G6120-00-879-3698	TR1TJ	NONE
SPECIFICATIONS:	INPUT:208 VAC,50-60 HZ,THREE PHASE RATED CURRENT:5.0 AMPERES,6.5 AMPERES MAX KVA RATING:2.70 KVA (MAX LOAD CURRENT X INPUT VAC) OUTPUT VOLTAGE RATING:2-240 VAC MOUNTING:ENCLOSED,WYE CONNECTION DIMENSIONS:(INCHES)6.75H X 5.13W X 12.25D APPROX WEIGHT:(POUNDS)22 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
TRANSFORMER,AUTO	W10G3M	13850	9G6120-00-033-3776	TR1TT	NONE
SPECIFICATIONS:	INPUT:208-240 VAC,50-60 HZ,THREE PHASE RATED CURRENT:10.0 AMPERES,13.0 AMPERES MAX KVA RATING:5.40 KVA (MAX LOAD CURRENT X INPUT VAC) OUTPUT VOLTAGE RATING:0-240 VAC MOUNTING:OPEN,WYE CONNECTION DIMENSIONS:(INCHES)9.69H X 7.13 X 14.19 APPROX WEIGHT:(POUNDS)43 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
TRANSFORMER,AUTO	W10HG3M	13850	1H6120-00-032-1173	TR1YN	4648
SPECIFICATIONS:	INPUT:480 VAC,50-60 HZ,THREE PHASE RATED CURRENT:4.0 AMPERES,5.2 AMPERES MAX KVA RATING:4.32 KVA (MAX LOAD CURRENT X INPUT VAC) OUTPUT VOLTAGE RATING:0-480 VAC MOUNTED:ENCLOSED,WYE CONNECTION DIMENSIONS:(INCHES)9.69H X 7.13W X 14.19D APPROX WEIGHT:(POUNDS)42 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX E

NOUN NAME TO STANDARD EQUIPMENTS

NOUN NAME	STANDARD EQUIPMENT	FSCM	ICP/NSN	GMG	SCAT
TRANSFORMER,ISOLATION	P6161	80089	9N5950-00-645-1807	TR3AN	4795
SPECIFICATIONS:	INPUT:105/115/125 VAC,50-60 HZ OUTPUT:115 VAC VOLT-AMPS CAPACITY:250 VA RMS TEST VOLTAGE:1500V DIMENSIONS:(INCHES)5.5L X 3.8W X 4.7H APPROX WEIGHT:(POUNDS)14 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
TRANSFORMER,ISOLATION	ST-100	88869	9N5950-00-679-6862	TR3NN	4659
SPECIFICATIONS:	FREQUENCY RANGE:20-5000 HZ TURNS RATIO:4:1 DC RESISTANCE:100 OHM-LOW SIDE;2.7K OHM-HIGH SIDE INPUT IMPEDANCE:>15K OHM AT 400 HZ INPUT VOLTAGE:115V RMS AT 60 HZ CONNECTOR:FOUR BINDING POSTS DIMENSIONS:(INCHES)3.5L X 4.4W X 4.3H APPROX WEIGHT:(POUNDS)2.5 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
TRANSFORMER,ISOLATION	SPX-3031	88869	1H5950-01-040-0282	TR3YN	4660
SPECIFICATIONS:	FREQUENCY RANGE:50 HZ-10 KHZ TURNS RATIO:1:1 DC RESISTANCE:10 OHM APPROX INPUT IMPEDANCE:>250K OHM AT 400 HZ INPUT VOLTAGE:350V MAX CONNECTOR:FOUR BINDING POSTS DIMENSIONS:(INCHES)3.5L X 4.4W X 4.3H APPROX WEIGHT:(POUNDS)2.5 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
TRANSFORMER,RATIO	M-1012A	88869	1H6625-01-206-2974	TR4JN	4643
SPECIFICATIONS:	FREQUENCY RANGE:30-1000 HZ RESOLUTION:0.00001 % ACCURACY:+/-(0.0001%+[0.00005%]),30-400 HZ INPUT VOLTAGE:2.5 X FREQUENCY WITH 350V MAX SERIES OUTPUT IMP:RS-5 OHM,LS-350 UV INPUT IMP:2.5 X INPUT FREQ,220K OHMS TYPICALLY DIMENSIONS:(INCHES)17W X 5.875H X 16.875D APPROX WEIGHT:(POUNDS)26 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					
TRANSFORMER,RATIO	RT-20A	88869	1H5950-01-067-3203	TR4TJ	4649
SPECIFICATIONS:	FREQUENCY RANGE:50 HZ TO 10 KHZ RESOLUTION:INTERPOLATING POTENTIOMETER PROVIDING A VARIATION OF 1 PPM ACCURACY:+/-(.001%+.0001%/RATIO)@50-3000 HZ,+/-(.0 1%+.0001%/RATIO)@3000/10000 HZ INPUT VOLTAGE:0.35 X FREQ IN HZ TO 350 VRMS MAX SERIES OUTPUT IMP:RS=3.0 OHMS,LS=75 MICRO HENRIES INPUT IMP:45K OHMS,DEPENDENT ON FREQUENCY DIMENSIONS(INCHES)17W X 5.25H X 16.875D APPROX WEIGHT(POUNDS)16 APPROX				
CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.					

Source: https://assist.dla.mil -- Downloaded: 20260-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX E

NOUN NAME TO STANDARD EQUIPMENTS

NOUN NAME	STANDARD EQUIPMENT	FSCM	ICP/NSN	GMG	SCAI
TRANSFORMER,RATIO	RT-30A	88869	1H6625-LL-HHE-4050	TR4TT	4650

SPECIFICATIONS: FREQUENCY RANGE:50 HZ TO 10 KHZ
RESOLUTION:INTERPOLATING POTENTIOMETER PROVIDING
CONTINUOUS READINGS TO SEVEN PLACES
ACCURACY:0.0001/RATIO % AT 400 HZ
INPUT VOLTAGE:0.35 X FREQ OR 350V,WHATEVER IS LESS
SERIES OUTPUT IMPEDANCE:RS-4,LS-200 UH
INPUT IMP:(AT 20V,400 HZ) 150K OHM MIN.
DIMENSIONS:(INCHES)19W X 5.25H X 6.5D APPROX
WEIGHT:(POUNDS)11 APPROX

CLASSIFICATION OF THIS ITEM, IN ACCORDANCE WITH MIL-T-28800, HAS NOT BEEN DEVELOPED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX F

NAVSEA SCAT CODE TO STANDARD EQUIPMENT

SCAT	STANDARD EQUIPMENT	FSCM	ICP/NSN	NOUN NAME	CMG
NONE	AU-65AMN	12457	1H6625-01-040-9528	ATTENUATOR,VARIABLE,COAXIAL	AT6MN
NONE	C-30BP	80009	7G6720-01-095-2205	CAMERA,OSCILLOSCOPE	CS1NN
NONE	C-59AP	80009	1H6720-00-262-4198	CAMERA,OSCILLOSCOPE	CS1AA
NONE	DPTC-25KFM	91161	1H5985-01-152-4077	DUMMY LOAD,COAXIAL	DL1AA
NONE	DPTC-50KFM	91161	1H5985-01-152-4078	DUMMY LOAD,COAXIAL	DL1AN
NONE	JQE-36-3M	85604	1H6130-00-471-1735	POWER SUPPLY,DIRECT VOLTAGE	PS1AN
NONE	J382A	28480	7G6625-00-679-0627	ATTENUATOR,VARIABLE,WAVEGUIDE	AT7AA
NONE	LQ-415	80103	1H6625-01-178-9497	POWER SUPPLY,DIRECT VOLTAGE	PS1RN
NONE	M602	57646	NSNL	ATTENUATOR,STEP	AT4KN
NONE	N9412-20	09992	1H5985-01-203-5192	ATTENUATOR,FIXED,COAXIAL	AT1NB
NONE	P424A	28480	1R6625-00-980-9302	DETECTOR,RF,FIXED,WAVEGUIDE	DE3AN
NONE	R-1011B	94990	1H6625-01-205-1224	POWER SUPPLY,DIRECT VOLTAGE	PS1BY
NONE	S501B	00929	1H6625-00-535-9532	TERMINATION,WAVEGUIDE	TM2JN
NONE	UNDER REVIEW		NSNL	POWER SUPPLY,DIRECT VOLTAGE	PS1UR
NONE	UNDER REVIEW		NSNL	POWER SUPPLY,DIRECT VOLTAGE	PS1UR
NONE	UNDER REVIEW		NSNL	TERMINATION,WAVEGUIDE	TM2UR
NONE	UNDER REVIEW		NSNL	MODULATOR,WAVEGUIDE	ML1UR
NONE	WF-0025	00929	7G5985-00-539-6126	DUMMY LOAD,WAVEGUIDE	DL2AN
NONE	W10G3M	13850	9G6120-00-033-3776	TRANSFORMER,AUTO	TR1TT
NONE	W5G3M	13850	9G6120-00-879-3698	TRANSFORMER,AUTO	TR1TJ
NONE	1/432D	80138	9N5985-00-252-8026	ATTENUATOR,STEP	AT4DN
NONE	10514A	28480	9N5985-00-087-4714	MIXER,BALANCED,DOUBLE	MX1NN
NONE	1425-4	93459	1H6930-01-140-4985	TERMINATION,COAXIAL	TM1MN
NONE	1433-9706	24655	5A6625-00-235-6308	RESISTOR,DECADE	RE1KJ
NONE	1433-9729	24655	1H6625-01-205-0820	RESISTOR,DECADE	RE1AN
NONE	1433-9731	24655	1H6625-00-480-0950	RESISTOR,DECADE	RE1DY
NONE	1491-9704	24655	1H6625-00-251-1158	INDUCTOR,DECADE	LN1NN

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX F

NAVSEA SCAI CODE TO STANDARD EQUIPMENT

SCAI	STANDARD EQUIPMENT	FSCM	ICP/NSN	NOUN NAME	GMG
NONE	197B	28480	&&6720-01-104-3402	CAMERA,OSCILLOSCOPE	CS1AB
NONE	210A-3	93459	1H6625-LL-HHE-4111	ATTENUATOR,FIXED,COAXIAL	AT1AB
NONE	214	00443	1H6625-00-395-0779	DETECTOR,RF,TUNABLE,WAVEGUIDE	DE5AA
NONE	24-6-34	93459	1H6625-LL-HHE-8021	ATTENUATOR,FIXED,COAXIAL	AT1AC
NONE	3122	99899	1H5895-01-079-0537	DETECTOR,RF,DIRECTIONAL	DE1NN
NONE	314	00443	1H6625-01-039-5259	DETECTOR,RF,TUNABLE,WAVEGUIDE	DE5AB
NONE	4M-3-6-10	93459	9N6625-01-026-2335	ATTENUATOR,FIXED,COAXIAL,SET	AT2NN
NONE	4055-10	99899	9N6625-00-261-7749	COUPLER,DIRECTIONAL,COAXIAL	DC1AW
NONE	4055-20	99899	1H5985-01-100-1668	COUPLER,DIRECTIONAL,COAXIAL	DC1JW
NONE	4055-30	99899	1H5985-01-096-6705	COUPLER,DIRECTIONAL,COAXIAL	DC1SN
NONE	407655	80006	1H5915-00-310-1476	FILTER,NOTCH	FL3NN
NONE	4375G	99899	1H6625-LL-HHE-8020	TERMINATION,COAXIAL	TM1WP
NONE	574-10	00443	1H6625-LL-HHE-8018	COUPLER,DIRECTIONAL,WAVEGUIDE	DC2AA
NONE	574-20	00443	1H6625-LL-HHE-8019	COUPLER,DIRECTIONAL,WAVEGUIDE	DC2NN
NONE	6274B	28480	7Z6130-00-160-0827	POWER SUPPLY,DIRECT VOLTAGE	PS1FY
NONE	6294A	28480	&&6130-01-062-6739	POWER SUPPLY,DIRECT VOLTAGE	PS1FA
NONE	6296A	28480	1H6130-01-067-3777	POWER SUPPLY,DIRECT VOLTAGE	PS1FN
NONE	640	99899	1R5985-00-729-1297	HORN,STANDARD GAIN	HN1MN
NONE	6443B	28480	1H6130-00-163-6201	POWER SUPPLY,DIRECT VOLTAGE	PS1KN
NONE	80M	70998	9Y5840-00-669-8675	TERMINATION,COAXIAL	TM1SA
NONE	8085	70998	9N5985-00-477-8165	DUMMY LOAD,COAXIAL	DL1NN
NONE	8135	70998	9N6625-00-773-7311	DUMMY LOAD,COAXIAL	DL1SN
NONE	8164	70998	1H5985-01-024-8193	DUMMY LOAD,COAXIAL	DL1EA
NONE	973-20	93459	1H6625-00-118-6729	ATTENUATOR,VARIABLE,COAXIAL	AT6AN
4002	WE-0035	00929	1H6625-01-067-3271	DUMMY LOAD,WAVEGUIDE	DL2FN
4003	LA-60N	00929	9N5915-00-725-6051	FILTER,LOWPASS	FL2YN
4008	BA-C-110C	00341	1H6625-01-030-5505	HORN,STANDARD GAIN	HN1FN

Source: https://assist.dla.mil -- Downloaded: 202640-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX F

NAVSEA SCAI CODE TO STANDARD EQUIPMENT

SCAI	STANDARD EQUIPMENT	FSCM	ICP/NSN	NOUN NAME	CMG
4011	638	99899	9N6625-01-031-1980	HORN,STANDARD GAIN	HN1TN
4012	W637	99899	9N6625-01-031-1981	HORN,STANDARD GAIN	HN1YN
4040	6299A	28480	4G6130-00-406-5695	POWER SUPPLY,DIRECT VOLTAGE	PS1HN
4042	6266B	28480	9G6130-00-137-0167	POWER SUPPLY,DIRECT VOLTAGE	PS1BA
4051	DCR150-12B	49956	7Z6625-01-136-3178	POWER SUPPLY,DIRECT VOLTAGE	PS1MN
4084	153B/403SD-001	25965	7G6625-01-197-9866	CONVERTER,FREQUENCY,AC	CF1NN
4114	BHK-500-0.4M	85604	7Z6625-01-031-8855	POWER SUPPLY,DIRECT VOLTAGE	PS1VN
4115	5015V	98095	1H6625-01-224-0215	POWER SUPPLY,DIRECT VOLTAGE	PS1DN
4129	TCR-300S-3-1	89022	1H6625-LL-HHE-4110	POWER SUPPLY,DIRECT VOLTAGE	PS1TN
4348	613-M	77327	1H6625-00-973-1151	DETECTOR,RF,FIXED,COAXIAL	DE2AN
4352	8470A	28480	1H6625-00-424-4334	DETECTOR,RF,FIXED,COAXIAL	DE2YN
4353	423A	28480	9N6625-00-880-4978	DETECTOR,RF,FIXED,COAXIAL	DE2AA
4354	8472A-001	28480	1H6625-00-291-1039	DETECTOR,RF,FIXED,COAXIAL	DE2NN
4599	WF-0050	00929	9N5985-00-572-6267	DUMMY LOAD,WAVEGUIDE	DL2MN
4600	WF-0055	00929	9N5985-00-538-7328	DUMMY LOAD,WAVEGUIDE	DL2YN
4604	C874-9099	82316	1H5935-00-370-8549	ADAPTER,COAXIAL,SET	AD1NN
4605	N281A	28480	9N5985-00-892-0732	ADAPTER,WAVEGUIDE TO COAXIAL	AD3TN
4606	102AC46-1E	01456	1H6625-00-178-0008	ADAPTER,WAVEGUIDE TO COAXIAL	AD3QN
4609	F281B	28480	9N5985-00-136-8330	ADAPTER,WAVEGUIDE TO COAXIAL	AD3WN
4610	1281A	28480	9N5985-00-606-9161	ADAPTER,WAVEGUIDE TO COAXIAL	AD3MN
4614	4609	99899	1H5985-01-025-3902	ADAPTER,WAVEGUIDE TO COAXIAL	AD3YN
4624	1412-9410	24655	1H6625-00-465-6861	CAPACITOR,DECADE	CP1MN
4630	1433-9722	24655	1H6625-00-947-7534	RESISTOR,DECADE	RE1DN
4634	1433-9714	24655	1H6625-00-463-4011	RESISTOR,DECADE	RE1GM
4635	240C	12697	1H6625-00-585-4915	RESISTOR,DECADE	RE1GT
4636	1433-9724	24655	1H6625-00-031-3521	RESISTOR,DECADE	RE1GY
4637	1433-9726	24655	1H6625-00-140-8183	RESISTOR,DECADE	RE1KT

Source: https://assist.dla.mil -- Downloaded: 202610-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX F

NAVSEA SCAT CODE TO STANDARD EQUIPMENT

SCAT	STANDARD EQUIPMENT	FSCM	ICP/NSN	NOUN NAME	GMG
4639	1433-9704	24655	9N6625-00-173-5441	RESISTOR,DECADE	RE1GF
4643	M-1012A	88869	1H6625-01-206-2974	TRANSFORMER,RATIO	TR4JN
4644	UNDER REVIEW		NSNL	CAPACITOR,DECADE	CP1U3
4646	UNDER REVIEW		NSNL	CAPACITOR,DECADE	CP1U2
4647	UNDER REVIEW		NSNL	CAPACITOR,DECADE	CP1U1
4648	W10HG3M	13850	1H6120-00-032-1173	TRANSFORMER,AUTO	TR1YN
4649	RT-20A	88869	1H5950-01-067-3203	TRANSFORMER,RATIO	TR4TJ
4650	RT-30A	88869	1H6625-LL-HHE-4050	TRANSFORMER,RATIO	TR4TT
4652	M2G3	13850	9N5950-00-877-4863	TRANSFORMER,AUTO	TR1MN
4653	W5MT3A	13850	9N5950-00-987-5601	TRANSFORMER,AUTO	TR1AA
4655	M5	13850	9N5950-00-504-9090	TRANSFORMER,AUTO	TR1FN
4656	W10MT3A	13850	9S6120-00-054-7794	TRANSFORMER,AUTO	TR1AN
4658	B-1576	91161	1H5985-00-792-9928	DUMMY LOAD,COAXIAL	DL1EY
4659	ST-100	88869	9N5950-00-679-6862	TRANSFORMER,ISOLATION	TR3NN
4660	SPX-3031	88869	1H5950-01-040-0282	TRANSFORMER,ISOLATION	TR3YN
4661	432-D	80138	9N5985-00-087-2547	ATTENUATOR,STEP	AT4NA
4662	355C	28480	1H5985-00-993-1377	ATTENUATOR,STEP	AT4AN
4665	452-C	80138	9Y5985-00-712-8388	ATTENUATOR,STEP	AT4NY
4666	442-D	80138	9N5905-00-313-9064	ATTENUATOR,STEP	AT4NN
4668	850-CT2W	83332	NSNL	ATTENUATOR,STEP	AT4RQ
4670	S382C	28480	9N6625-00-179-8448	ATTENUATOR,VARIABLE,WAVEGUIDE	AT7NA
4671	G-101	77327	9N5985-00-921-3697	ATTENUATOR,VARIABLE,WAVEGUIDE	AT7NN
4672	355D	28480	9N5985-00-957-1860	ATTENUATOR,STEP	AT4UN
4673	P382A	28480	6G6625-00-752-3222	ATTENUATOR,VARIABLE,WAVEGUIDE	AT7AM
4675	K382A	28480	9N5985-00-822-8666	ATTENUATOR,VARIABLE,WAVEGUIDE	AT7AT
4677	R382A	28480	1H5985-00-822-7874	ATTENUATOR,VARIABLE,WAVEGUIDE	AT7AY
4678	UNDER REVIEW		NSNL	DIVIDER,VOLTAGE,DECADE	DR3UR

Source: https://assist.dla.mil -- Downloaded: 202610-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX F

NAVSEA SCAT CODE TO STANDARD EQUIPMENT

SCAT	STANDARD EQUIPMENT	FSCM	ICP/NSN	NOUN NAME	GMG
4679	1506A	93459	9V6625-00-261-5033	DIVIDER,POWER	DP1NN
4681	3043B-30	99899	9N5985-00-450-8802	COUPLER,DIRECTIONAL,COAXIAL	DC1SA
4683	8201	70998	1H6625-00-994-6797	DUMMY LOAD,COAXIAL	DL1EN
4683	8404	70998	1H6625-01-150-1897	DUMMY LOAD,COAXIAL	DL1JN
4684	376BNF	99899	9N5985-00-241-3518	TERMINATION,COAXIAL	TM1FN
4685	371BNM	99899	1H6625-00-970-3685	TERMINATION,COAXIAL	TM1YN
4686	8491A-006	28480	9N5895-00-230-1827	ATTENUATOR,FIXED,COAXIAL	AT1EA
4687	8491A-010	28480	9N5985-00-865-0108	ATTENUATOR,FIXED,COAXIAL	AT1JA
4688	8491A-003	28480	9N5985-00-167-0544	ATTENUATOR,FIXED,COAXIAL	AT1AF
4689	8491A-020	28480	1H4935-01-031-2694	ATTENUATOR,FIXED,COAXIAL	AT1NN
4690	4M-3	93459	1H6625-LL-HHE-1799	ATTENUATOR,FIXED,COAXIAL	AT1AT
4691	4M-6	93459	1H6625-01-015-2356	ATTENUATOR,FIXED,COAXIAL	AT1EN
4692	778D	28480	9N5985-00-239-3215	COUPLER,DIRECTIONAL,COAXIAL	DC1JJ
4693	3045C-10	99899	1R5985-00-604-8604	COUPLER,DIRECTIONAL,COAXIAL	DC1AT
4694	4M-10	93459	9N5985-00-258-0123	ATTENUATOR,FIXED,COAXIAL	AT1JY
4695	11692D	28480	9N5985-01-024-3832	COUPLER,DIRECTIONAL,COAXIAL	DC1NN
4696	GM-318-C4	60674	9N6625-01-036-2020	COUPLER,DIRECTIONAL,COAXIAL	DC1WN
4697	0874-9577	82316	&&5840-00-868-1287	ATTENUATOR,VARIABLE,COAXIAL	AT6TN
4703	3750	88865	1H6625-00-001-2376	FILTER,VARIABLE	FL4JN
4704	3202	88865	1H4931-00-178-1052	FILTER,VARIABLE	FL4TN
4705	A400 BC	16786	1H6625-01-142-5447	FILTER,BANDPASS	FL1EJ
4728	K362A	28480	9N5985-00-488-7434	FILTER,BANDPASS	FL1JN
4729	R362A	28480	9N5915-00-488-7437	FILTER,LOWPASS	FL2WG
4730	360A	28480	9N5915-00-503-1787	FILTER,LOWPASS	FL2AN
4731	360B	28480	9N5915-00-686-8922	FILTER,LOWPASS	FL2FN
4732	360C	28480	9N5915-00-503-0533	FILTER,LOWPASS	FL2MN
4733	360D	28480	9N5915-00-804-5302	FILTER,LOWPASS	FL2TN

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX F

NAVSEA SCAT CODE TO STANDARD EQUIPMENT

SCAT	STANDARD EQUIPMENT	FSCM	ICP/NSN	NOUN NAME	GMG
4792	DCR40-25B	49956	1H6130-01-040-9808	POWER SUPPLY,DIRECT VOLTAGE	PS1BN
4796	P6161	80089	9N5950-00-645-1807	TRANSFORMER,ISOLATION	TR3AN
4797	C20PS	14135	1H4931-00-921-7357	ISOLATOR,COAXIAL	SR1TN
4798	L20PS	14135	906625-00-738-2716	ISOLATOR,COAXIAL	SR1FN
4799	S11PS	14135	9N5985-00-439-3536	ISOLATOR,COAXIAL	SR1MN
4800	CX20PS	14135	9N5985-00-145-3514	ISOLATOR,COAXIAL	SR1YN
4802	1571-9831	13850	9G6110-00-087-4771	REGULATOR,LINE	RACAA
4859	616	99899	9N6625-00-424-5066	ADAPTER,WAVEGUIDE TO COAXIAL	AD3AN
4860	S281A	28480	1R4920-01-029-4624	ADAPTER,WAVEGUIDE TO COAXIAL	AD3CN
4861	G281A	28480	9N5985-00-772-6676	ADAPTER,WAVEGUIDE TO COAXIAL	AD3FN
4862	TDR-29011	87864	9N5985-00-062-6919	ADAPTER,WAVEGUIDE TO COAXIAL	AD3JN
4870	QHB-2-30	12457	1R5985-00-991-1013	COUPLER,HYBRID,QUADRATURE	CQ1NN
4877	3222-16	99899	1H5985-01-081-7855	COUPLER,DIRECTIONAL,COAXIAL	DC1EN
4878	3041-20	99899	1R5985-00-757-0549	COUPLER,DIRECTIONAL,COAXIAL	DC1JF
4880	3000-10	99899	9N5985-00-816-4287	COUPLER,DIRECTIONAL,COAXIAL	DC1AA
4881	3040B-20	99899	1H5985-00-067-6750	COUPLER,DIRECTIONAL,COAXIAL	DC1JC
4882	3041-10	99899	1H5985-01-039-5404	COUPLER,DIRECTIONAL,COAXIAL	DC1AC
4883	3060-20	99899	9N5985-00-492-7921	COUPLER,DIRECTIONAL,COAXIAL	DC1JA
4884	3042B-10	99899	9N5985-00-465-8112	COUPLER,DIRECTIONAL,COAXIAL	DC1AF
4885	3002-20	99899	9N5985-00-578-5747	COUPLER,DIRECTIONAL,COAXIAL	DC1JM
4886	3043B-10	99899	1H6625-01-065-5289	COUPLER,DIRECTIONAL,COAXIAL	DC1AJ
4887	3003-20	99899	9N5985-00-882-8654	COUPLER,DIRECTIONAL,COAXIAL	DC1JQ
4888	3004-10	99899	9N5985-00-788-6962	COUPLER,DIRECTIONAL,COAXIAL	DC1AM
4889	3004-20	99899	9N5985-00-714-3247	COUPLER,DIRECTIONAL,COAXIAL	DC1JT
4890	3202B-10	99899	9N5985-00-412-2986	COUPLER,DIRECTIONAL,COAXIAL	DC1AQ
4891	4016D-10	99899	9N5985-01-041-8132	COUPLER,DIRECTIONAL,COAXIAL	DC1AY
4892	X301A	13047	1H5985-01-069-2318	TERMINATION,WAVEGUIDE	TM2TN

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX F

NAVSEA SCAT CODE TO STANDARD EQUIPMENT

SCAT	STANDARD EQUIPMENT	FSCM	ICP/NSN	NOUN NAME	GMG
4895	2-3414-30	09992	9N5985-00-999-8095	ATTENUATOR,VARIABLE,COAXIAL	AT6FN
4898	AF-117A-69-34	93459	9N6625-01-063-9297	ATTENUATOR,STEP	AT4GN
4901	X382A	28480	1H6625-00-602-2089	ATTENUATOR,VARIABLE,WAVEGUIDE	AT7AF
4905	X752C	28480	9N5985-00-646-9472	COUPLER,DIRECTIONAL,WAVEGUIDE	DC2AF
4907	K752C	28480	915985-00-913-9842	COUPLER,DIRECTIONAL,WAVEGUIDE	DC2AM
4909	R752C	28480	9N4931-00-777-1373	COUPLER,DIRECTIONAL,WAVEGUIDE	DC2AT
4915	2-6	93459	1H6625-01-017-1277	ATTENUATOR,FIXED,COAXIAL	AT1EY
4916	2-10	93459	1H6625-01-017-1278	ATTENUATOR,FIXED,COAXIAL	AT1JN
4917	2-20	93459	1H6625-01-017-1276	ATTENUATOR,FIXED,COAXIAL	AT1NY
4918	2-30	93459	1H6625-01-014-3463	ATTENUATOR,FIXED,COAXIAL	AT1SN
4919	2-40	93459	1H6625-01-014-3464	ATTENUATOR,FIXED,COAXIAL	AT1WN
4924	2-3	93459	1H6625-01-020-6032	ATTENUATOR,FIXED,COAXIAL	AT1AM
4943	UNDER REVIEW		NSNL	DETECTOR,RF,TUNABLE,COAXIAL	DE4UR
4944	2002-6113-00	16179	9N5985-00-192-0138	TERMINATION,COAXIAL	TM1TT
4950	2001-6113-00	16179	9N5985-01-064-2513	TERMINATION,COAXIAL	TM1TJ
4965	R422A	28480	1R6625-00-981-9518	DETECTOR,RF,FIXED,WAVEGUIDE	DE3YN
4966	K422A	28480	1H6625-00-874-7733	DETECTOR,RF,FIXED,WAVEGUIDE	DE3NN

Source: https://assist.dla.mil -- Downloaded: 202610-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX G

FEDERAL SUPPLY CODE TO MANUFACTURER'S NAME

FSCM	MANUFACTURER'S NAME
00213	SUDSIDIARY OF NYTRONICS INC. NYTRONICS COMPONENTS GROUP INC.
00213	NYTRONICS COMPONENTS GROUP INC SUDSIDIARY OF NYTRONICS INC.
00341	STRUTHERS ELECTRONICS CORP.
00443	WAVELINE, INC.
00929	MICROLAB/FXR, INC.
01113	GENERAL INSTRUMENTS CORP. (USE FSCM 23042)
01341	MICROPHASE CORP.
01456	MICROWAVE DEVELOPMENT LABORATORIES, INC. (MDL)
03782	ALFRED ELECTRONICS (USE FSCM 88869)
03950	SHIPS PARTS CONTROL CENTER
04423	TELONIC/BERKELEY, INC.
05591	GENERAL RESISTANCE, INC. SUB., PRIME TECHNOLOGY, INC.
05591	PRIME TECHNOLOGY, INC., GENERAL RESISTANCE, INC. SUB.
05049	ELECTRONICS DIV., TOPAZ, INC.
05049	TOPAZ, INC., ELECTRONICS DIV.
06351	MICROWAVE RESEARCH CORP.
05424	DEFENSE PRODUCTS GROUP, SPERRY CORP. (USE FSCM 99899)
05424	SPERRY CORP. DEFENSE PRODUCTS GROUP. (USE FSCM 99899)
07239	BIDDLE INSTRUMENTS
07342	NORTH ATLANTIC INDUSTRIES, INC.
03449	RAMCOR, INC. (USE FSCM 00443)
03992	ANTENNA AND RADOME RESEARCH ASSOCIATES CORP.
10110	INSTRUMENTATION DIV., SCIENTIFIC-ATLANTA, INC.
10110	SCIENTIFIC-ATLANTA, INC., INSTRUMENTATION DIV.
11242	BAY STATE ELECTRONICS (USE FSCM 99872)
11332	GENERAL MICROWAVE CORP.
11787	MICROWAVE COMPONENTS DIV., MCS CORP. (LOCATION UNKNOWN)
11787	MCS CORP., MICROWAVE COMPONENTS DIV. (LOCATION UNKNOWN)
11920	ELASCO DIV., SIGMA INSTRUMENTS, INC.
11920	SIGMA INSTRUMENTS, INC., ELASCO DIV.
12110	INFORMATION MANAGEMENT SYSTEMS DIV., MICROWAVE COMPONENTS, EATON
12110	EATON CORP., INFORMATION MANAGEMENT SYSTEMS DIV. MICROWAVE COMPON
12457	MERRIMAC INDUSTRIES, INC.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX G

FEDERAL SUPPLY CODE TO MANUFACTURER'S NAME

FSCM	MANUFACTURER'S NAME
12598	RLC ELECTRONICS, INC.
12678	ELECTRONIC INSTRUMENTATION DIV., EATON CORP. (USE FSCM 88869)
12678	EATON CORP., ELECTRONIC INSTRUMENTATION DIV. (USE FSCM 88869)
12697	CLAROSTAT MANUFACTURING CO., INC.
12868	ASTROSYSTEMS, INC.
12996	FOWLER INDUSTRIES, INC.
13047	MAURY MICROWAVE CORP.
14135	E&M LABORATORIES DIV., TRAK MICROWAVE CORP.
14135	TRAK MICROWAVE CORP., E & M LABORATORIES DIV.
14140	EDISON ELECTRONICS (USE FSCM 58880)
14655	CORNELL-DUBLIER ELECTRONICS DIV., FEDERAL PACIFIC ELECTRIC CO.
14655	FEDERAL PACIFIC ELECTRIC CO., CORNELL-DUBLIER ELECTROINCS DIV.
15305	OMEGA LABORATORIES, INC.
16055	NDL, INC. (BUSINESS DISCONTINUED)
16179	MICROWAVE COMPONENTS DIV., M/A-COM OMNI SPECTRA CORP.
16179	M/A-COM OMNI SPECTRA CORP., MICROWAVE COMPONENTS DIV.
16786	FREQUENCY ENGINEERING LABORATORIES, DBA
17773	U.S. ARMY (USE FSCM 18876)
17870	DAVEN (USE FSCM 57646)
18778	DUMONT (USE FSCM 30669)
18876	U.S. ARMY
23534	POWER/MATE CORP.
24655	BOARD TEST DIV., GENRAD, INC.
24655	GENRAD, INC., BOARD TEST DIV.
25965	ELGAR CORP.
26512	GRUMMAN AEROSPACE CORP.
27634	MICROWAVE FILTER CO., INC.
28480	HEWLETT-PACKARD CO.
30669	DUMONT OSCILLOSCOPE LABORATORIES, INC.
31731	3DBM CO., INC.
44655	OHMITE MANUFACTURING CO.
45413	SUB OF TELEDYNE INC.TELEDYNE ELECTRONICS, TELEDYNE INDUSTRIES INC
45413	TELEDYNE ELECTRONICS, TELEDYNE INDUSTRIES INC. SUB OF TELEDYNE IN

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX G

FEDERAL SUPPLY CODE TO MANUFACTURER'S NAME

FSCM	MANUFACTURER'S NAME
47904	POLAROID CORP.
49956	RAYTHEON CO.
50423	BALLANTINE LABORATORIES, INC.
52542	SYSTRON-DONNER CORP.
54294	SHALLCROSS, INC. SUB., HIRSCH & ASSOCIATES
54294	HIRSCH & ASSOCIATES, SHALLCROSS, INC. SUB.
54778	SIERRA ELECTRONIC DIV., LEAR SIEGLER, INC.
54778	LEAR SIEGLER, INC., SIERRA ELECTRONIC DIV.
55026	SIMPSON ELECTRONIC CO. DIV., AMERICAN GAGE & MACHINE CO.
55026	AMERICAN GAGE & MACHINE CO., SIMPSON ELECTRONIC CO., DIV.
57646	AUTOMATED INDUSTRIAL ELECTRONICS CORP.
58474	SUPERIOR ELECTRIC CO.
60674	MICROWAVE DEVICES, INC.
70998	BIRD ELECTRONIC CORP.
76526	MOELLER INSTRUMENTS CO.
77327	PRD ELECTRONICS DIV., HARRIS CORP.
77327	HARRIS CORP., PRD ELECTRONICS DIV.
80006	AIRTRON DIV., LITTON SYSTEMS, INC.
80006	LITTON SYSTEMS, INC., AIRTRON DIV.
80009	TEKTRONIX, INC.
80089	ESSEX ELECTROMECHANICAL DIV., UNITED TECHNOLOGIES CORP.
80089	UNITED TECHNOLOGIES CORP., ESSEX ELECTROMECHANICAL DIV.
80103	LAMBDA ELECTRONICS DIV., VEECO INSTRUMENTS, INC.
80103	VEECO INSTRUMENTS, INC., LAMBDA ELECTRONICS DIV.
80138	KAY ELEMETRICS CORP.
82199	POLARAD ELECTRONICS, INC.
82316	SUB OF TRANSITRON ELECTRONIC CORP., GILBERT ENGINEERING CO. INC.
82316	GILBERT ENGINEERING CO. INC. SUB OF TRANSITRON ELECTRONIC CORP.
83008	STACO ENERGY PRODUCTS CO.
83332	TECH LABORATORIES, INC.
85504	KEPCO, INC.
87864	TECHNICRAFT DIV., TECH SYSTEMS CORP.
87864	TECH SYSTEMS CORP., TECHNICRAFT DIV.

Source: https://assist.dla.mil -- Downloaded: 202610-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX G

FEDERAL SUPPLY CODE TO MANUFACTURER'S NAME

FSCM	MANUFACTURER'S NAME
88865	KROHN-HITE CORP.
88869	ELECTRONIC INSTRUMENT DIV. LOS ANGELES PLANT, EATON CORP.
88869	EATON CORP., ELECTRONIC INSTRUMENT DIV. LOS ANGELES PLANT
89022	ELECTRONIC MEASUREMENTS, INC.
89536	FLUKE MANUFACTURING CO., INC.
90101	UNIVERSAL AD-YU ELECTRONICS, INC.
91161	ELECTRO-IMPULSE LABORATORY, INC.
93459	WEINSCEL ENGINEERING CO., INC.
93953	MELSTROM MANUFACTURING CORP.
94990	GOVERNMENT ELECTRONICS DIV., MOTOROLA, INC.
94990	MOTOROLA, INC., GOVERNMENT ELECTRONICS DIV.
95712	MICROWAVE DEVICES, BENDIX CORP. (USE FSCM 60674)
95712	BENDIX CORP., MICROWAVE DEVICES (USE FSCM 60674)
95924	CONTROL ELECTRONICS CO., INC.
96214	EQUIPMENT GROUP, TEXAS INSTRUMENTS, INC.
96214	TEXAS INSTRUMENTS, INC., EQUIPMENT GROUP
96341	MICROWAVE ASSOCIATES, INC., SUB OF M/A COM INC.
96341	M/A COM INC., MICROWAVE ASSOCIATES, INC., SUB OF
96752	ERA TRANSPAC CORP.
98095	POWER DESIGNS, INC.
98521	CASCADE RESEARCH DIV., HUGGINS LABORATORY, INC. (LOCATION UNKNOWN
98521	HUGGINS LABORATORY, INC., CASCADE RESEARCH DIV. (LOCATION UNKNOWN
98732	LIECO INC.
99899	NARDA MICROWAVE CORP.
MIL	MILITARY NOMENCLATURE

Source: https://assist.dla.mil -- Downloaded: 202610-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX H

MANUFACTURER'S NAME TO FEDERAL SUPPLY CODE

MANUFACTURER'S NAME	FSCM
AIRTRON DIV., LITTON SYSTEMS, INC.	80006
ALFRED ELECTRONICS (USE FSCM 88869)	03782
AMERICAN GAGE & MACHINE CO., SIMPSON ELECTRONIC CO., DIV.	55026
ANTENNA AND RADOME RESEARCH ASSOCIATES CORP.	09992
ASTROSYSTEMS, INC.	12868
AUTOMATED INDUSTRIAL ELECTRONICS CORP.	57646
BALLANTINE LABORATORIES, INC.	50423
BAY STATE ELECTRONICS (USE FSCM 99872)	11242
BENDIX CORP., MICROWAVE DEVICES (USE FSCM 60674)	95712
BIDDLE INSTRUMENTS	07239
BIRD ELECTRONIC CORP.	70998
BOARD TEST DIV., GENRAD, INC.	24655
CASCADE RESEARCH DIV., HUGGINS LABORATORY, INC. (LOCATION UNKNOW	98521
CLAROSTAT MANUFACTURING CO., INC.	12697
CONTROL ELECTRONICS CO., INC.	95924
CORNELL-DUBLIER ELECTRONICS DIV., FEDERAL PACIFIC ELECTRIC CO.	14655
DAVEN (USE FSCM 57646)	17870
DEFENSE PRODUCTS GROUP, SPERRY CORP. (USE FSCM 99899)	06424
DUMONT (USE FSCM 30669)	18778
DUMONT OSCILLOSCOPE LABORATORIES, INC.	30669
E&M LABORATORIES DIV., TRAK MICROWAVE CORP.	14135
EATON CORP., ELECTRONIC INSTRUMENT DIV. LOS ANGELES PLANT	88869
EATON CORP., ELECTRONIC INSTRUMENTATION DIV. (USE FSCM 88869)	12678
EATON CORP., INFORMATION MANAGEMENT SYSTEMS DIV. MICROWAVE COMPO	12110
EDISON ELECTRONICS (USE FSCM 58880)	14140
ELASCO DIV., SIGMA INSTRUMENTS, INC.	11920
ELECTRO-IMPULSE LABORATORY, INC.	91161
ELECTRONIC INSTRUMENT DIV. LOS ANGELES PLANT, EATON CORP.	88869
ELECTRONIC INSTRUMENTATION DIV., EATON CORP. (USE FSCM 88869)	12678
ELECTRONIC MEASUREMENTS, INC.	89022
ELECTRONICS DIV., TOPAZ, INC.	06049
ELGAR CORP.	25965
EQUIPMENT GROUP, TEXAS INSTRUMENTS, INC.	96214

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX H

MANUFACTURER'S NAME TO FEDERAL SUPPLY CODE

MANUFACTURER'S NAME	FSCM
ERA TRANSPAC CORP.	96762
ESSEX ELECTROMECHANICAL DIV., UNITED TECHNOLOGIES CORP.	80089
FEDERAL PACIFIC ELECTRIC CO., CORNELL-DUBLIER ELECTROINCS DIV.	14655
FLUKE MANUFACTURING CO., INC.	89536
FOWLER INDUSTRIES, INC.	12996
FREQUENCY ENGINEERING LABORATORIES, DBA	16786
GENERAL INSTRUMENTS CORP. (USE FSCM 23042)	01113
GENERAL MICROWAVE CORP.	11332
GENERAL RESISTANCE, INC. SUB., PRIME TECHNOLOGY, INC.	05591
GENRAD, INC., BOARD TEST DIV.	24655
GILBERT ENGINEERING CO. INC. SUB OF TRANSITRON ELECTRONIC CORP.	82316
GOVERNMENT ELECTRONICS DIV., MOTOROLA, INC.	94990
GRUMMAN AEROSPACE CORP.	26512
HARRIS CORP., PRD ELECTRONICS DIV.	77327
HEWLETT-PACKARD CO.	28480
HIRSCH & ASSOCIATES, SHALLCROSS, INC. SUB.	54294
HUGGINS LABORATORY, INC., CASCADE RESEARCH DIV. (LOCATION UNKNOW	98521
INFORMATION MANAGEMENT SYSTEMS DIV., MICROWAVE COMPONENTS, EATON	12110
INSTRUMENTATION DIV., SCIENTIFIC-ATLANTA, INC.	10110
KAY ELEMETRICS CORP.	80138
KEPCO, INC.	85604
KROHN-HITE CORP.	88865
LAMBDA ELECTRONICS DIV., VEECO INSTRUMENTS, INC.	80103
LEAR SIEGLER, INC., SIERRA ELECTRONIC DIV.	54778
LIECO INC.	98732
LITTON SYSTEMS, INC., AIRTRON DIV.	80006
M/A COM INC., MICROWAVE ASSOCIATES, INC., SUB OF	96341
M/A-COM OMNI SPECTRA CORP., MICROWAVE COMPONENTS DIV.	16179
MAURY MICROWAVE CORP.	13047
MCS CORP., MICROWAVE COMPONENTS DIV. (LOCATION UNKNOWN)	11787
MELSTROM MANUFACTURING CORP.	93953
MERRIMAC INDUSTRIES, INC.	12457
MICROLAB/FXR, INC.	00929

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX H

MANUFACTURER'S NAME TO FEDERAL SUPPLY CODE

MANUFACTURER'S NAME	FSCM
MICROPHASE CORP.	01341
MICROWAVE ASSOCIATES, INC., SUB OF M/A COM INC.	96341
MICROWAVE COMPONENTS DIV., M/A-COM OMNI SPECTRA CORP.	16179
MICROWAVE COMPONENTS DIV., MCS CORP. (LOCATION UNKNOWN)	11787
MICROWAVE DEVELOPMENT LABORATORIES, INC. (MDL)	01456
MICROWAVE DEVICES, BENDIX CORP. (USE FSCM 60674)	95712
MICROWAVE DEVICES, INC.	60674
MICROWAVE FILTER CO., INC.	27834
MICROWAVE RESEARCH CORP.	06351
MILITARY NOMENCLATURE	MIL
MOELLER INSTRUMENTS CO.	76526
MOTOROLA, INC., GOVERNMENT ELECTRONICS DIV.	94990
NARDA MICROWAVE CORP.	99899
NDL, INC. (BUSINESS DISCONTINUED)	16055
NORTH ATLANTIC INDUSTRIES, INC.	07342
NYTRONICS COMPONENTS GROUP INC SUDSIDIARY OF NYTRONICS INC.	00213
OHMITE MANUFACTURING CO.	44655
OMEGA LABORATORIES, INC.	15305
POLARAD ELECTRONICS, INC.	82199
POLAROID CORP.	47904
POWER DESIGNS, INC.	98095
POWER/MATE CORP.	23934
PRD ELECTRONICS DIV., HARRIS CORP.	77327
PRIME TECHNOLOGY, INC., GENERAL RESISTANCE, INC. SUB.	05591
RAMCOR, INC. (USE FSCM 00443)	09449
RAYTHEON CO.	49956
RLC ELECTRONICS, INC.	12598
SCIENTIFIC-ATLANTA, INC., INSTRUMENTATION DIV.	10110
SHALLCROSS, INC. SUB., HIRSCH & ASSOCIATES	54294
SHIPS PARTS CONTROL CENTER	03950
SIERRA ELECTRONIC DIV., LEAR SIEGLER, INC.	54778
SIGMA INSTRUMENTS, INC., ELASCO DIV.	11920
SIMPSON ELECTRONIC CO. DIV., AMERICAN GAGE & MACHINE CO.	55026

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:40Z
Check the source to verify that this is the current version before use.

APPENDIX H

MANUFACTURER'S NAME TO FEDERAL SUPPLY CODE

MANUFACTURER'S NAME	FSCM
SPERRY CORP. DEFENSE PRODUCTS GROUP. (USE FSCM 99999)	06424
STACO ENERGY PRODUCTS CO.	83008
STRUTHERS ELECTRONICS CORP.	00341
SUB OF TELEDYNE INC.TELEDYNE ELECTRONICS, TELEDYNE INDUSTRIES IN	45413
SUB OF TRANSITRON ELECTRONIC CORP., GILBERT ENGINEERING CO. INC.	82316
SUDSIDIARY OF NYTRONICS INC. NYTRONICS COMPONENTS GROUP INC.	00213
SUPERIOR ELECTRIC CO.	58474
SYSTRON-DONNER CORP.	52542
TECH LABORATORIES, INC.	83332
TECH SYSTEMS CORP., TECHNICRAFT DIV.	87864
TECHNICRAFT DIV., TECH SYSTEMS CORP.	87864
TEKTRONIX, INC.	80009
TELEDYNE ELECTRONICS, TELEDYNE INDUSTRIES INC. SUB OF TELEDYNE I	45413
TELONIC/BERKELEY, INC.	04423
TEXAS INSTRUMENTS, INC., EQUIPMENT GROUP	96214
TOPAZ, INC., ELECTRONICS DIV.	06049
TRAK MICROWAVE CORP., E & M LABORATORIES DIV.	14135
U.S. ARMY	18876
U.S. ARMY (USE FSCM 18876)	17773
UNITED TECHNOLOGIES CORP., ESSEX ELECTROMECHANICAL DIV.	80089
UNIVERSAL AD-YU ELECTRONICS, INC.	90101
VEECO INSTRUMENTS, INC., LAMBDA ELECTRONICS DIV.	80103
WAVELINE, INC.	00443
WEINSCEL ENGINEERING CO., INC.	93459
3DBM CO., INC.	31791

Source: https://assist.dla.mil -- Downloaded: 202610-26T13:40Z
Check the source to verify that this is the current version before use.

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
	☐ USER
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 202610-26T13:40Z
Check the source to verify that this is the current version before use.