MILITARY SPECIFICATION

LIGHT, MARKER, DISTRESS, AIRCREW, SDU-30

This amendment forms a part of Military Specification MIL-L-23614B, dated 5 October 1973, and is approved for use by all Departments and Agencies of the Department of Defense.

Page 1

Add the following to the bottom of the page:

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to : Engineering Specifications and Standards Department, (Code 93), Naval Air Engineering Center, Lakehurst, NJ 08733, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

1.1 Delete and substitute:

"1.1 This specification covers requirements for one type of battery powered aircrew distress marker light (SANS Batteries)."

Page 3

3.2 Delete the last sentence in its entirety.

3.3 (1) In first sentence insert "Batery Powered" before "Water-Proof".

(2) Delete fourth sentence in its entirety.

3.4.1 (1) Add "For Testing purposed", to the beginning of the first sentence.

(2) Delete the second sentence (The light shall . . . packaged together).

Page 5

3.5.1 Change Vertical Minumum Average Candlepower from "40.0" to "18.0".

Custodians:
Navy - AS

Review Activities:
Navy SH

User Activities:
Army ME
Navy CG

Preparing Activity
Navy - AS

(Project No. 6230-0242)

6230

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:21Z
Check the source to verify that this is the current version before use.