PERFORMANCE SPECIFICATION

RESISTORS, THERMAL (THERMISTOR) INSULATED,
GENERAL SPECIFICATION FOR

This amendment forms a part of MIL-PRF-23648E, dated 11 October 2002, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 3

Table III, delete and substitute:

"TABLE III. Resistance tolerance versus temperature for each resistance tolerance.

Sequence	Temperature	F (± percent)	G (± percent)	J (± percent)	K (± percent)
1	-55	1/ 10 (15)	1/ 12 (17)	1/ 15 (20)	1/ 20 (25)
2	-15	1/ 5 (9)	1/ 6 (10)	1/ 9 (13)	1/ 14 (18)
3	0	3	4	7	12
4	25	1	2	5	10
5	50	3	4	7	12
6	75	5	6	9	14
7	100	7	9	12	17
8	125	10	12	15	20
9	2/ 200	15	18	25	30
10	2/ 275	20	25	35	40

1/ The percentages in parentheses are for positive coefficient thermistors.
2/ These temperatures are not applicable styles (see 3.1)."

Custodians:
Army - CR
Navy - EC
Air Force - 11

Preparing activity:
DLA - CC

(Project 5905-1690)

Review activities:
Army - AR, AT, AV, CR4
Navy - AS, CG, MC, OS
Air Force - 19, 99
NASA - NA

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:28Z
Check the source to verify that this is the current version before use.