MIL-T-23643(Wep)
5 February 1963

MILITARY SPECIFICATION
TEST SET, TARGET CONTROL SYSTEM AN/SRM SERIES
(AN/SRM-2, AN/SRM-3, AN/SRM-4, AN/SRM-5, AND AN/SRM-6)

This specification has been approved by the
Bureau of Naval Weapons Department of the Navy

1 SCOPE

1 1 Scope The equipment covered by this specification shall be capable of performing all maintenance tests for Target Control Systems of the AN/SRW-4 Series.

1.2 Classification Test Sets, Target Control Systems of the AN/SRM Series, shall be of the following types. (see 6.3)

Items	Type Designation	Applicable Paragraph
Test Set, Target Control System	AN/SRM-2	3 4.1 Test Console AN/SRW-4 System Components
Test Set, Target Control System	AN/SRM-3	3 4 2 Receiver-Analyzer, Fixed and Rotary Wing Test
Test Set, Target Control System	AN/SRM-4	3 4.3 Receiver-Analyzer, Rotary Wing Test
Test Set, Target Control System	AN/SRM-5	3 4 4 Signal Generator, Fixed and Rotary Wing Test
Test Set, Target Control System	AN/SRM-6	3 4 5 Signal Generator, Rotary Wing Test

2. APPLICABLE DOCUMENTS

2 1 The following documents of the issue in effect on the date of invitation for bids form a part of this specification to the extent specified herein

SPECIFICATIONS

Federal

QQ-A-270 Aluminum Alloy, Bars, Rods, and Shapes, Extruded, 6061 and 6062

QQ-A-318 Aluminum Alloy 52S, Plate and Sheet

QQ-C-320 Chromium Plating (Electrodeposited)

QQ-A-325 Aluminum Alloy 615, Bars, Rods, Shapes and Wire, Rolled or Drawn

QQ-P-330 Phospher Bronze Bars, Plate, Rods, Sheets, Strips, Flat Wire, and Structural and Special Shaped Sections

QQ-P-416 Plating, Cadmium (Electrodeposited)

QQ-B-626 Brass, Leaded and No-Leaded, Rods, Shapes, Forgings, and Flat Products with Finished Edge (Bars, Flat Wire, and Strips)

FSC 6625

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:26Z
Check the source to verify that this is the current version before use.

QQ-S-633 Steel Bars, Carbon, Cold Finished and Hot Rolled (General Purpose)

QQ-S-635 Steel, Carbon, Plate

QQ-S-00643 Steel, Carbon, Tubing, Mechanical Round Seamless and Welded

AN-QQ-S-685 Chrome-Molybdenum-E-4130 Steel Sheet

Military

MIL-P-116 Preservation, Methods of

MIL-E-4682 Electron Tubes and Transistors, Choice and Application of

MIL-E-5422 Testing, Environmental, Aircraft Electronic Equipment

MIL-I-6181 Interference Control Requirements, Aircraft Control Equipment

MIL-S-6758 Steel, Chrome-Molybdenum 4130 Bars, Rods, and Forging Stock for Aircraft Application

MIL-W-6858 Welding, Low Carbon Steel, Austenitic Steel, and Nickel Alloys, Spot and Seam

MIL-A-8625 Anodic Coating for Aluminum and Aluminum Alloys

MIL-E-15090 Enamel, Equipment, Light Grey Formula No. 111

MIL-I-16910 (Ships) Interference Measurements, Radio, Methods and Limits 14 Kilocycles to 1,000 Megacycles (Including Amendment 2)

MIL-E-17555 Electronic and Electrical Equipment and Associated Repair Parts, Preparation for Delivery of Repair Parts

MIL-T-18303 Test Procedures, Preproduction and Inspection for Aircraft Electronic Equipment, Format for

MIL-N-18307 Nomenclature and Nameplates for Aeronautical and Associated Equipment

MIL-F-19207 Fuseholders, Extractor Post Type, Blown Fuse Indicating and Non-indicating

MIL-T-21200 Test Equipment for Use with Electronic and Fire Control Systems, General Specification for

(When requesting specifications, standards, drawings, and publications, refer

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:26Z
Check the source to verify that this is the current version before use.

to both title and number. Copies of this specification and applicable specifications required by contractors in connection with specific procurement functions may be obtained upon application to the Commanding Officer, Naval Supply Depot, Code CDS, 5801 Tabor Avenue, Philadelphia 20, Pennsylvania.)

3 REQUIREMENTS

3.1 Parts and Materials In the selection of parts and materials, the following shall govern

(1) Parts and materials requirements shall conform to Specification MIL-T-21200

(2) Nonrepairable subassemblies, as outlined in Specification MIL-T-21200, shall be used when practicable The general size of the subassembly, and the amount of circuitry to be included therein, shall be approved by the procuring activity.

(3) When previously produced models of this equipment did not use nonrepairable subassemblies, the design shall not be changed to employ nonrepairable assemblies without the approval of the procuring activity.

3.1.1 Nonstandard Parts and Material Approval. Approval for the use of nonstandard parts and materials shall be obtained as outlined in Specification MIL-T-21200

3.1.2 Electron Devices. Electron tubes, transistors, and diodes shall be chosen and applied, and the complements reported, as outlined in Specification MIL-E-4682

3.1.3 Fungus-Inert Material. All materials used shall be non-nutrients for fungus and insects.

3.2 Design and Construction Unless otherwise specified herein, the equipment shall conform with all the applicable requirements of Specification MIL-T-21200 for design, construction, and workmanship.

3.2.1 Total Weight The total weights of Test Sets, Target Control System of the AN/SRM Series, shall be minimum consistent with good design and shall not exceed the following

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:26Z
Check the source to verify that this is the current version before use.

Test Set Target Control System	Total Weight (pounds)
AN/SRM-2	2,344
AN/SRM-3	708
AN/SRM-4	593
AN/SRM-5	769
AN/SRM-6	628

3.2.2 Operating Life.

3.2.2.1 Operational Stability. The electronic equipments of Test Sets, Target Control System of the AN/SRM Series, shall operate with optimum performance for 300 hours, continuously or intermittently, without the necessity for adjustment of any controls which are inaccessible to the operator

3.2.2.2 Total Operating Life The electronic equipments of Test Sets, Target Control System of the AN/SRM Series, shall have a minimum total operating life of 5000 hours with reasonable servicing and replacement of parts Parts requiring replacement within this interval and the life of such parts shall be specified by the manufacturer.

3.2.2.3 Mean Time Between Failures. The electronic equipments of Test Sets, Target Control System of the AN/SRM Series, shall have a minimum of 300 hours of mean time between failures A failure shall be defined as any malfunctioning which causes the equipment to fail to meet the minimum performance requirements specified for the equipment

3.2.3 Cabling and Connections

3.2.3.1 Cables and Connectors The electronic equipments of Test Sets, Target Control System of the AN/SRM Series, shall provide for the use of cables and connectors in accordance with Specification MIL-T-21200

3.2.4 Control Panels All rack or console mounted control panels shall conform to the applicable requirements of Specification MIL-T-21200

3.2.5 Interchangeability. The equipment shall meet the interchangeability requirements as defined in Specification MIL-T-21200, except that this shall not preclude product improvement changes during the life of the contract as may be agreed to between the contractor and contracting agency

3.2.6 Interference Control. The generation of radio interference by the electronic equipments of Test Sets, Target Control System of the AN/SRM Series, when installed in appropriate cabinets having radio interference filters, and the vulnerability of the equipments to radio interference shall be controlled within the limits of Specification MIL-I-6181, except that radio frequency output on frequencies other than the fundamental shall be within the limits specified in Specification MIL-I-16910.

Source: https://assist.dla.mil -- Downloaded: 202610-19T17:26Z
Check the source to verify that this is the current version before use.

3.2.7 Maintenance Provisions and Field Testing. Provisions for maintenance shall be as specified in Specification MIL-T-21200. Specific test points and test facilities shall be provided to the greatest extent practicable for ease of field testing and maintenance

3.2.8 Nomenclature and Nameplates Nomenclature assignment and nameplate approval for equipment identification shall be in accordance with Specification MIL-N-18307

3.2.9 Standard Conditions The following conditions shall be used to establish normal performance characteristics under standard conditions and for making laboratory bench tests.

Temperature	Room ambient (25°±10°C)
Altitude	Normal ground
Vibration	None
Humidity	Room ambient to 90 percent relative
Input power voltage	115 ±1.0 volts ac single phase 220 ±2.0 volts ac three phase

3.2.10 Service Conditions Except as modified herein, the equipment shall operate satisfactorily under any of the environmental service conditions or reasonable combination of these conditions as specified in Specification MIL-T-21200 for Class 3 equipment

3.2.10.1 Vibration. Electronic equipments of Test Sets, Target Control System of the AN/SRM Series, shall operate satisfactorily when subjected to vibration along each of the three mutually perpendicular axes within the frequency range and amplitudes specified below when installed in appropriate cabinets which are equipped with suitable vibration isolators

Frequency Range	Double Amplitude
5 to 15 cps	0.06 inch
15 to 25 cps	0.04 inch
25 to 55 cps	0.02 inch

3.2.10.2 Temperature Electronic equipments of Test Sets, Target Control System of the AN/SRM Series, shall operate satisfactorily when subjected to the temperature requirements of Specification MIL-T-21200 except the maximum operating temperature shall not exceed 55°C and the minimum operating temperature shall not be less than 0°C.

3.2.10.3 Altitude. Electronic equipments of Test Sets, Target Control System of the AN/SRM Series, shall be required to operate satisfactorily at sea level altitude

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:26Z
Check the source to verify that this is the current version before use.

only. However, the equipment shall not be damaged when subjected to altitude in accordance with Specification MIL-T-21200 in a nonoperating condition.

3.2.10.4 Salt-Sea Atmosphere. The equipment paint finishes shall withstand exposure to salt spray as described in Specification MIL-T-5422.

3.2.10.5 Drop. Cabinets of the equipment shall not be required to withstand drop conditions as specified in Specification MIL-T-21200.

3.2.10.6 Shock. Electronic equipment of Test Sets, Target Control System of the AN/SRM Series, shall meet the requirements of Specification MIL-T-2100 when mounted in appropriate cabinets equipped with shock mounts. Testing of the equipment shall be as outlined in 4.1.3.1.7.

3.2.11 Warmup Time. The time required for the equipments to warm up prior to operation shall be kept to a minimum and shall not exceed the following:

Test Set, Target Control System	Warmup Time Under Standard Conditions (Minutes)	Warmup Time At Extreme Service Conditions (Minutes)
AN/SRM-2	30	60
AN/SRM-3	10	20
AN/SRM-4	10	20
AN/SRM-5	30	60
AN/SRM-6	30	60

3.2.12 Primary Input Power Requirements. The equipment shall meet all applicable requirements of Specification MIL-T-21200 and shall give specified performance from the following power sources with characteristics as defined in specification MIL-T-21200 having limits as specified therein. The power required shall not exceed the following limits:

Test Set, Target Control System	60-Cycle A-C Power (Single Phase)	60-Cycle A-C Power (Three Phase)
AN/SRM-2	115 volt, 5000 VA	220 volt, 3500 VA
AN/SRM-3	115 volt, 600 VA	None
AN/SRM-4	115 volt, 600 VA	None
AN/SRM-5	115 volt 1000 VA	None
AN/SRM-6	115 volt, 900 VA	None

3.2.12.1 Input Power Connections. Input power connections shall be in accordance with Specification MIL-T-21200.

Source: https://assist.dla.mil -- Downloaded: 202610-19T17:26Z
Check the source to verify that this is the current version before use.

3.2.12.2 Undervoltage Protection. The equipment shall not be damaged by voltages below the minimum specified herein and shall automatically resume normal operation when the voltage returns within limits.

3 2 13 Standby Provisions The equipment shall provide for a standby position whereby rated voltage shall be applied to all tube filaments. Except for the associated filament circuits, voltages shall not be applied to other parts of the equipment.

3.2.14 Safety Provisions. Provisions shall be made for an adequate ground which provides a positive low-resistance electrical path from the cabinet structure to the metal structure of the ship. Provisions shall be made for adequate grounding during checkout.

3 3 Performance. Unless otherwise specified, values set forth to establish the requirements for satisfactory performance apply to performance under both standard and extreme service conditions. When reduced performance under the extreme conditions is acceptable, tolerances or values setting forth acceptable variations from the performance under the standard conditions will be specified

3 3.1 Test Set, Target Control System AN/SRM-2. The Test Set, Target Control System AN/SRM-2, shall provide facilities for the electronic phases of maintaining and testing the components comprising the Target Control System AN/SRW-4 and all revisions thereof. Performance of specific components comprising the Test Set, Target Control System AN/SRM-2, shall be as follows

3.3.1.1. Test Stand, Electronic Equipment MT-2732/SRM-2

3.3.1.1 1 Operation The Test Stand, Electronic Equipment MT-2732/SRM-2, shall provide electrical interconnecting, support, cooling, and circuit protection facilities for the equipments contained therein.

3.3 1.2 Test Set, Relay TS-1752/SRM-2

3 3 1.2.1 Operation. The Test Set, Relay TS-1752/SRM-2, shall provide for testing the Switch, Radio Frequency Transmission Line SA-631/SRW-4, and each type of relay contained in the Target Control System AN/SRW-4 or any revision thereof.

3 3 1.3 Test Set, Radio Set Transfer Control TS-1749/SRM-2.

3.3.1.3.1 Operation. The Test Set, Radio Set Transfer Control TS-1749/SRM-2, shall provide for testing the switching circuits of a transfer control by comparing the transfer control switching circuits with standard switching circuits in the test set. Facilities shall be provided for selecting the desired level of the simulated power signals applied to the transfer control, and for displaying the resulting conditions of operation of the transfer control.

3 3.1.4 Test Set, Transmitter TS-1753/SRM-2.

Source: https://assist.dla.mil -- Downloaded: 202610-19T17:26Z
Check the source to verify that this is the currentversion before use.

3.3.1.4.1 Operation. The Test Set, Transmitter TS-1753/SRM-2, shall provide for testing of the subassemblies contained in Transmitting Set, Radio AN/URW-14, and Transmitting Set, Radio AN/URW-14A, of Target Control System AN/SRW-4 or any revision thereof The Test Set, Transmitter TS-1753/SRM-2, shall provide necessary voltages, dummy loads, controls, and indicators to individually test and calibrate each subassembly

3.3.1 5 Test Set, Receiver TS-1751/SRM-2

3 3 1 5.1 Operation The Test Set, Receiver TS-1751/SRM-2, shall provide for testing and calibrating various subassemblies, circuits, and components of the Receiver, Radio R-999/URW-16, of Target Control System AN/SRW-4, or any revision thereof. The power, controls, dummy loads, indicators, and meters required to test and calibrate the decoder subassembly and components of the Receiver, Radio R-999/URW-16, shall be provided by the Test Set, Receiver TS-1751/SRM-2

3.3.1.6 Test Set, Power Supply TS-1750/SRM-2

3.3.1.6.1 Operation The Test Set, Power Supply TS-1750/SRM-2, shall provide for testing of the Power Supply PP-2658/UR which, in turn, shall enable testing of Amplifier, Radio Frequency AM-2643/UR, when used in conjunction with the power supply under test The power supply test set shall be capable of either metering output voltages from the power supply test set or metering test voltages from the power supply Controls and indicators shall be provided to test all interlock circuits and calibrate all overload protection circuits

3 3 1 7 Amplifier-Frequency Multiplier AM-3311/SRM

3.3.1.7.1 Operation The Amplifier-Frequency Multiplier AM-3311/SRM, shall provide for generating radio-frequency signals within the frequency range of 406 to 549 5 megacycles The generated radio-frequency signals shall be frequency modulated to a maximum deviation of ±300 kilocycles when supplied with signals in the range of 300 cycles per second to 100 kilocycles from an external source The Amplifier-Frequency Multiplier AM-3311/SRM shall be capable of receiving external audio-frequency signals supplied by either the Coder Audio Frequency KY-430 SRM or the Coder Audio Frequency KY-431 SRM The Amplifier-Frequency Multiplier AM-3311 SRM shall supply a variable calibrated output amplitude from 1 to 1000 000 microvolts

3.3 1.7.2 Radio-Frequency Output The Amplifier-Frequency Multiplier AM-3311/SRM shall provide a continuous wave or frequency-modulated r-f signals in accordance with the following requirements An external audio signal source shall be required during modulated operation.

3.3.1.7.2.1 Frequency. The Amplifier-Frequency Multiplier AM-3311/SRM shall provide any desired frequency within the specified range of 406 to 549. 5 megacycles, and shall be capable of continuous tuning throughout the range without band switching.

Source: https://assist.dla.mil -- Downloaded: 202610-19T17:26Z
Check the source to verify that this is the current version before use.

3.3.1.7.2.2 Accuracy. It shall be possible to select any desired frequency within the specified range with an accuracy of 0.005 percent. Continuous visual presentation shall be made of the operating frequency at all times.

3.3.1.7.2.3 Amplitude. R-f test signals shall be furnished at an adjustable, variable level within the range of 1.0 to 100,000 microvolts across the rated load. The level of the r-f test signals shall be adjustable by means of a front panel control, and a suitable means shall be provided to directly indicate this level. The variable level shall be indicated in terms of microvolts across the rated load.

3.3.1.7.2.4 Output Impedance. The nominal output impedance shall be 52 ohms, resistive.

3.3.1.7.2.5 Spurious Frequency Modulation. The incidental, uncontrolled frequency-modulation of continuous wave r-f test signals shall not cause a frequency deviation in excess of 40 db below ±300 kilocycle deviation.

3.3.1.7.2.6 Spurious Amplitude Modulation. The incidental, uncontrolled amplitude modulation of continuous wave r-f test signals shall not exceed 10 percent.

3.3.1.7.3 Output Connector. R-f test signals shall be furnished at a front panel connector which shall mate with a Type N connector.

3.3.1.7.4 Rated Load. The r-f signal circuits shall furnish r-f test signals to a rated load of 52 ohms resistance and the requirements in regard to these test signals shall apply when furnished to the rated load.

3.3.1.7.5 Amplitude Calibrator. A means shall be provided to set the carrier monitor at a reference level for calibration of the full scale output level of the attenuator.

3.3.1.7.6 External Modulation. The equipment shall include a modulator capable of accepting signals from an external source within the range of 300 to 100,000 cycles per second. A signal within the specified range, and having an amplitude within the range of 0.8 volt RMS to 6 volts RMS for a sine wave configuration, shall be usable for producing a carrier deviation of ±300 kilocycles.

3.3.1.7.7 Frequency Deviation Monitor. The modulation circuits shall include a meter calibrated control or other suitable means for indicating the deviation of frequency modulated r-f test signals with an error of less than 10 percent of the actual deviation. Deviation ranges of 0 to 300 kilocycles, 0 to 150 kilocycles, and 0 to 50 kilocycles shall be provided.

3.3.1.7.8 Deviation Control. The deviation of modulated r-f test signals shall be adjustable within the range of 0 to 300 kilocycles by means of a front panel control.

3.3.1.7.9 Input Impedance. Provisions shall be included for selection of either 560 ohms or 20,000 ohms input impedance for external modulating signals.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:26Z
Check the source to verify that this is the current version before use.

3.3.1.7.10 Compressor. The compressor shall be capable of maintaining a constant carrier deviation within the standard IRIG frequency range of 7.5 to 75 kilocycles. A switch shall be provided for selecting modulation directly without the compressor.

3.3.1.8 Power Supply PP-3373/SRM

3.3.1.8.1 Operation The Power Supply PP-3373/SRM shall provide all electrical power required for operation of the Amplifier-Frequency Multiplier AM-3311/SRM A front panel connector shall be provided to supply the following voltages and currents for an external audio coder

(1) 26 volts ac at 1 1 amperes

(2) 180 volts dc at 45 milliamperes

3 3 1.9 Coder, Audio Frequency KY-430/SRM

3.3.1.9 1 Operation The Coder, Audio Frequency KY-430/SRM, shall provide for generating the first twenty IRIG audio-frequency tones which shall be selected either manually by toggle switches located on the front panel of the equipment or remotely through grounding terminals in the connector provided These audio-frequency tones shall be utilized to modulate either the associated Amplifier-Frequency Multiplier AM-3311 SRM or the transmitter of the Target Control System AN/SRW-4 or any revision thereof, and shall be utilized to test the decoder of the Target Control System AN/SRW-4 or any revision thereof.

3.3 1.9.2 Output Frequency The Coder, Audio Frequency KY-430/SRM, shall provide operation at 20 preset frequencies within the range of 7 4 to 74 kilocycles The accuracy of each frequency shall be - 1.0 percent

3.3.1.9.3 Output Amplitude. The uncompressed output of each channel shall be variable from 0 to 2.0 volts RMS when measured across a 500-ohm load.

3.3.1.9 4 Compressor The compressor shall be capable of maintaining a constant output amplitude during simultaneous operation of one to six audio channels. A switch shall be provided for selecting compressed or uncompressed operation.

3.3.1.9.5 Output Impedance The nominal output impedance of the Coder, Audio Frequency KY-430/SRM, shall be 500 ohms

3.3.1.10 Coder, Audio Frequency KY-431/SRM

3.3 1 10 1 Operation The Coder, Audio Frequency KY-431/SRM, shall provide means for testing the rotary wing components within the Target Control System AN/SRW-4 or any revision thereof. The Coder, Audio Frequency KY-431/SRM shall have facilities to initiate and develop digitally-coded command signals similar to those utilized to control rotary wing aircraft. Facilities shall be provided to enable the command signals to be initiated remotely or locally and the Coder, Audio Frequency KY-431/SRM, shall be capable of complete operation either independent of, or in conjunction with, the remote facilities.

Source: https://assist.dla.mil -- Downloaded: 202640-19T17:26Z
Check the source to verify that this is the currentversion before use.

3.3.1.11 Control, Coder C-4123/SRM.

3.3.1.11.1 Operation. The Control, Coder C-4123/SRM, shall provide facilities to remotely operate the Coder, Audio Frequency KY-431/SRM for testing rotary wing components of the Target Control System AN/SRW-4 or any revision thereof

3 3 1 12 Tool Kit, Target Control Systen TK-142/SRM-2

3.3.1 12.1 Operation. The Tool Kit, Target Control System TK-142/SRM-2, shall provide various special tools which shall be utilized in servicing and repairing components of the Target Control System AN/SRW-4 or any revision thereof.

3 3 1 13 Truck, Electronic Equipment V-244/SRM-2

3 3 1 13 1 Operation The Truck, Electronic Equipment V-244/SRM-2, shall provide for supporting and transporting specific components of the Target Control System AN/SRW-4 or any revision thereof

3 3 1 14 Hoisting Unit, Portable, Electronic Equipment E-42/SRM-2

3 3 1.14 1 Operation The Hoisting Unit, Portable, Electronic Equipment E-42 SRM-2, when utilized in conjunction with the Beam, Hoisting, Electronic Equipment MX-4124/SRM-2, shall provide facilities for lifting components comprising the Target Control System AN/SRW-4 or any revision thereof

3.3 1 15 Beam, Hoisting, Electronic Equipment MX-4124/SRM-2.

3 3 1 15 1 Operation The Beam, Hoisting Electronic Equipment MX-4124/SRM-2 when used in conjunction with the Hoisting Unit, Portable, Electronic Equipment E-42 SRM-2, shall provide for lifting the individual components of the Target Control System AN/SRW-4 or any revision thereof from their individual cases

3 3 2 Test Set, Target Control System AN/SRM-3 The Test Set, Target Control System AN/SRM-3, shall provide facilities to receive and analyze UHF frequency-modulated radio-control signals generated and transmitted by the Target Control System AN/SRW-4 or any revision thereof for test purposes Performance of specific components comprising the Test Set, Target Control System AN/SRM-3, shall be as follows

3.3.2.1 Cabinet, Electrical Equipment CY-3584/SRM-3.

3.3.2.1.1 Operation. The Cabinet, Electrical Equipment CY-3584/SRM-3, shall provide electrical interconnection, support, and cooling facilities for the equipment contained therein.

3.3.2.2 Receiver, Radio R-1135/SRM.

Source: https://assist.dla.mil -- Downloaded: 202640-19T17:26Z
Check the source to verify that this is the currentversion before use.

3.3.2.2.1 Operation. The Receiver, Radio R-1135/SRM, shall serve as a monitoring receiver for UHF frequency-modulated radio-control signals within the frequency range of 406 to 549.5 megacycles having a carrier deviation up to ±300 kilocycles and providing a level of 5 microvolts or more to the r-f input receptacle. Metering circuitry shall be incorporated to indicate received carrier deviation in kilocycles (plus and minus), received frequency differential with reference to the receiver operating frequency, received carrier level, and internal currents required to tune the equipment. The front panel of the equipment shall contain a momentary contact noise generator on-off switch and an indicator lamp to indicate noise generator operation, a tune-up select switch to determine the function of the tune-up meter, a receive-standby switch and an indicator lamp to indicate the receive condition, and carrier indicator lamps. The equipment shall be crystal controlled within the specified frequency range. Selection of crystal controlled radio frequency channels shall be accomplished by positioning of a selector switch mounted on a frequency selection sub-panel. This switch shall provide for selection of any one of up to six crystals installed in three dual crystal ovens. Oscillator, mixer and r-f tuning controls shall also be located on this frequency selection sub-panel.

3.3.2.2.2 Radio Frequency Characteristics. The radio-frequency range of the Receiver, Radio R-1135/SRM, shall be from 406 to 549.5 megacycles, inclusive. The radio-frequency carrier shall be frequency modulated to a deviation up to 300 kilocycles. Operation of the equipment shall be within ±0.005 percent from the selected operating frequency.

3.3.2.2.3 Sensitivity. The Receiver, Radio R-1135/SRM, shall provide reliable reception of distant UHF frequency-modulated signals providing an input amplitude within the range of 5 to 100,000 microvolts under standard conditions and within the range of 10 to 100,000 microvolts under extreme environmental conditions. A manually operated attenuator shall be adjustable in 1 db increments from 0 to 59 db.

3.3.2.2.4 Selectivity. The r-f selectivity of the Receiver, Radio R-1135/SRM, shall be such that when operating with the attenuator out of the circuit, operation of the equipment shall not be degraded by r-f signals of 100,000 microvolts amplitude which are two megacycles removed from the center frequency of the desired signal while the desired signal is 100 microvolts or greater in amplitude.

3.3.2.2.5 Image and Spurious Response. Response of the Receiver, Radio R-1135/SRM, to image, spurious and parasitic frequency signals shall be at least 60 db less than response to the desired signal.

3.3.2.2.6 Audio Output. The Receiver, Radio R-1135/SRM, shall incorporate three separate audio output receptacles. Each of two rear panel receptacles shall provide an audio output connection having a nominal impedance of 500 ohms and a front panel receptacle shall provide an audio output connection having a nominal impedance of 50 ohms. These output connections shall provide signals for external decoding and monitoring equipments.

3.3.2.3 Case, Crystal-Oven CY-2923/U

Source: https://assist.dla.mil -- Downloaded: 202640-19T17:26Z
Check the source to verify that this is the currentversion before use.

3.3.2.3 1 Operation. The Case, Crystal-Oven CY-2923/U, shall contain the necessary crystals together with three dual crystal ovens to provide operation of the Receiver, Radio R-1135/SRM, on the half megacycle points at one-megacycle increments from 406.5 to 549.5 megacycles, inclusive.

3 3 2.4 Case, Crystal-Oven CY-2924/U.

3 3 2 4 1 Operation The Case, Crystal-Oven CY-2924 /U, shall contain the necessary crystals together with three dual crystal ovens to provide operation of the Receiver, Radio R-1135/SRM, on the integral whole-megacycle increments from 406 to 549 megacycles, inclusive.

3 3.2 5 Case, Crystal-Oven CY-3690/SRM

3.3.2.5.1 Operation. The Case, Crystal-Oven CY-3690/SRM, shall contain the necessary crystals together with six dual crystal ovens to provide operation of the Receiver, Radio R-1135/SRM, on the classified "DASH" control frequencies

3 3 2 6 Decoder, Audio Frequency KY-432/SRM-3

3.3 2 6.1 Operation. The Decoder, Audio Frequency KY-432/SRM-3, shall be capable of receiving audio signals supplied by either the Receiver, Radio R-1135/SRM, or an auxiliary receiver. The received audio frequency signals shall comprise control signals for any one of the following types of fixed wing drone aircraft F9F, KDA, Q2C, KDB, or KD2R5 The equipment shall contain a decoder subassembly which shall serve as a 22-channel decoder capable of decoding the received audio-frequency signals. The decoded information shall be displayed, for test purposes, as indications representative of the control functions of a drone aircraft

3 3 2 7 Decoder, Audio Frequency KY-433/SRM

3 3.2 7 1 Operation The Decoder, Audio Frequency KY-433/SRM, shall be capable of receiving audio frequencies of 43 68 and 47 68 kilocycles from either the Receiver, Radio R-1135/SRM, or from an auxiliary receiver, and shall contain a decoder subassembly which shall be a digital decoder capable of decoding the received signals. The received audio-frequency signals comprising command signals for the control of rotary wing aircraft shall be decoded and the decoded information shall be applied to indicator circuits The indicators shall visually display for testing purposes, indications representative of the functions of a drone aircraft

3 3.2.7.2 Input Characteristics. The input signal frequency range shall be 43. 68 and 47. 68 kilocycles and the nominal input signal amplitude shall be 1.25 volts. The nominal input impedance shall be 500 ohms.

3.3 3 Test Set, Target Control System AN/SRM-4. The Test Set, Target Control System AN/SRM-4, shall provide facilities to receive and analyze UHF frequency-modulated signals generated and transmitted by Target Control System

Source: https://assist.dla.mil -- Downloaded: 202610-19T17:26Z
Check the source to verify that this is the current version before use.

AN/SRW-4 or any revision thereof. Performance of specific components comprising the Test Set, Target Control System AN/SRM-4, shall be as follows:

3 3.3.1 Cabinet, Electrical Equipment CY-3585/SRM-4

3.3 3.1 1 Operation The Cabinet, Electrical Equipment CY-3585/SRM-4, shall provide electrical interconnection, support, and cooling facilities for the equipment contained therein

3.3.3.2 Case, Crystal-Oven CY-3690/SRM Performance of the Case, Crystal-Oven CY-3690/SRM, shall be as specified in 3.3.2.5

3.3.3.3 Decoder, Audio Frequency KY-433/SRM. Performance of the Decoder, Audio Frequency KY-433/SRM, shall be as specified in 3.3 2 7

3.3.3.4 Receiver, Radio R-1135/SRM Performance of the Receiver, Radio R-1135/SRM, shall be as specified in 3.3 2.2

3.3.4 Test Set, Target Control System AN/SRM-5 The Test Set, Target Control System AN/SRM-5, shall generate UHF frequency-modulated signals which shall represent command signals for the control of either fixed or rotary wing aircraft and shall be utilized for testing the electronic performance of portions of the Target Control System AN/SRW-4 or any revision thereof

3.3 4.1 Cabinet, Electrical Equipment CY-3586/SRM-5

3.3.4.1.1 Operation. The Cabinet, Electrical Equipment CY-3586/SRM-5, shall provide electrical interconnection, support, and cooling facilities for the equipments contained therein

3 3 4 2 Amplifier-Frequency Multiplier AM-3311/SRM Performance of the Amplifier-Frequency Multiplier AM-3311/SRM shall be as specified in 3.3.1 7

3.3.4.3 Power Supply PP-3373/SRM Performance of the Power Supply PP-3373/SRM shall be as specified in 3.3 1.8.

3.3 4.4 Coder, Audio Frequency KY-430/SRM Performance of the Coder, Audio Frequency KY-430/SRM, shall be as specified in 3 3 1 9

3.3.4 5 Coder, Audio Frequency KY-431/SRM Performance of the Coder, Audio Frequency KY-431/SRM shall be as specified in 3 3 1 10

3.3 4 6 Control, Coder C-4123/SRM Performance of the Control, Coder C-4123/SRM, shall be as specified in 3.3 1.11

3.3.5 Test Set, Target Control System AN/SRM-6. The Test Set, Target Control System AN/SRM-6, shall generate UHF frequency-modulated signals.

Source: https://assist.dla.mil -- Downloaded: 202610-19T17:26Z
Check the source to verify that this is the current version before use.

which represent command signals for the control of rotary wing aircraft and are utilized for testing the electronic performance of portions of the Target Control System AN/SRW-4 or any revision thereof.

3.3.5.1 Cabinet, Electrical Equipment CY-3587/SRM-6.

3.3.5.1.1 Operation The Cabinet, Electrical Equipment CY-3587/SRM-6, shall provide electrical interconnection, support, and cooling facilities for the equipment contained therein.

3.3.5.2 Coder, Audio-Frequency KY-431/SRM Performance of the Coder, Audio-Frequency KY-431/SRM, shall be as specified in 3.3.1.10

3.3.5.3 Control, Coder C-4123/SRM Performance of the Control, Coder C-4123/SRM, shall be as specified in 3.3.1.11

3.3.5.4 Amplifier-Frequency Multiplier AM-3311/SRM Performance of the Amplifier-Frequency Multiplier AM-3311/SRM shall be as specified in 3.3.1.7

3.3.5.5 Power Supply PP-3373/SRM Performance of the Power Supply PP-3373/SRM shall be as specified in 3.3.1.8.

3.4 Detail Requirements.

3.4.1 Test Set, Target Control System AN/SRM-2 Detail requirements of the Test Set, Target Control System AN/SRM-2, shall be as follows.

3.4.1.1 Test Stand, Electronic Equipment MT-2732/SRM-2 The Test Stand, Electronic Equipment MT-2732/SRM-2, shall meet the following detail requirements

3.4.1.1.1 Function The Test Stand, Electronic Equipment MT-2732/SRM-2, shall provide facilities for supporting the following equipment on extending type drawer slides Test Set Relays TS-1752/SRM-2 Test Set, Transfer Control TS-1749/SRM-2 Test Set, Transmitter TS-1753/SRM-2, Test Set, Power Supply TS-1750/SRM-2, Test Set, Receiver TS-1751/SRM-2, Amplifier-Frequency Multiplier AM-3311/SRM, Power Supply PP-3373/SRM, Coder, Audio Frequency KY-430/SRM and Coder, Audio Frequency KY-431/SRM The Test Stand, Electronic Equipment MT-2732/SRM-2, shall also provide electrical interconnection, cooling air, and circuit protection facilities for the equipment contained therein Adequate storage facilities shall be provided for the Tool Kit, Target Control System TK-142/SRM-2 the Control, Coder C-4123/SRM, external cables, and handbooks.

3.4.1.1.2 Form Factor The maximum external dimensions of the Test Stand, Electronic Equipment MT-2732/SRM-2, shall be as follows:

Height	75 inches
Weight	76 inches
Depth.	52 inches

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:26Z
Check the source to verify that this is the current version before use.

3.4.1.1.3 Weight. The weight of the Test Stand, Electronic Equipment MT-2732/SRM-2, shall not exceed 1575 pounds.

3.4.1.1.4 Contents of Unit. The Test Stand, Electronic Equipment MT-2732/SRM-2, shall contain the following units

(1) Control Panel

(2) Blower Assembly

(3) Tray, Tool Mounting

3.4.1.1.4.1 Control Panel. The control panel shall meet the following requirements:

3.4 1 1.4.1.1 Function The control panel shall provide the facilities for controlling the application of external power to the Test Stand, Electronic Equipment MT-2732/SRM-2, for protecting the equipment from electrical overloads and shorts and for indicating the total equipment operating time

3.4.1 1 4 1 2 Form Factor. The maximum external dimensions of the control panel shall be as follows

Height	5-1/4 inches
Width	19 inches
Length	10 inches

3.4.1.1.4.1.3 Weight The weight of the control panel shall not exceed 15 pounds

3 4.1.1 4 1 4 Contents of Unit The control panel shall contain an elapsed time meter, two circuit breakers, and two indicator lamps.

3 4 1 1 4 1 4.1 Elapsed Time Meter The elapsed time meter shall indicate the total equipment operating time and shall be mounted on the front of the control panel The meter shall be a motor driven type and shall utilize 115-volt, 60-cycle power The meter shall be capable of indicating the equipment operating time to a total of 9999.9 hours in 0 1-hour increments.

3.4.1.1 4.1 4.2 Circuit Breakers Two circuit breakers shall be provided for controlling the application of power to the equipment and for protecting the equipment from electrical overloads and shorts The circuit breakers shall be mounted on the front of the control panel and shall be designated 115 V and 230 V

3.4.1.1.4.1.4.3 Indicator Lamps. Two indicator lamps shall be provided for indicating when the main power circuit breakers are closed. The indicator lamps shall be mounted on the front of the control panel and shall be designated 115 V POWER ON and 230 V POWER ON.

Source: https://assist.dla.mil -- Downloaded: 202640-19T17:26Z
Check the source to verify that this is the current version before use.

3 4.1.1.4.2 Blower Assembly. The blower assembly shall meet the following requirements:

3 4.1.1.4.2.1 Function. The blower assembly shall provide air circulation capable of cooling, under normal operating conditions, all the electronic equipment contained in the Test Stand, Electronic Equipment MT-2732/SRM-2.

3 4 1 1 4 2 2 Form Factor The maximum external dimensions of the blower assembly shall be as follows

Height	12-1/4 inches
Width	19 inches
Depth	23 inches

3 4.1 1 4.2.3 Weight The weight of the blower assembly shall not exceed 65 pounds

3 4 1 1 4 2.4 Contents of Unit. The blower assembly shall contain a squirrel cage type electric blower which utilizes 800 watts of 220-volt three-phase power

3 4.1 1 4.3 Tray, Tool Mounting A tray, tool mounting, shall be provided in a storage drawer of the Test Stand, Electronic Equipment MT-2732/SRM-2, to retain the tools which comprise the Tool Kit, Target Control System TK-142/SRM The tray shall be made of steel and welded in conformance with Specification MIL-W-6858 The tray shall have a gray finish conforming with Specification MIL-E-15090. A polyethyl styrene mounting surface with retaining straps and fitted slots shall be provided to secure the tools.

3 4 1 1 5 Electrical Connections Connections to external circuits shall be provided as follows

Reference Designation	Receptacle Type	Function
J1	MS3102R22-2P	115-Volt A-C Input Power
J2	MS3102R20-4P	230-Volt A-C Input Power

3 4 1 2 Test Set, Relay TS-1752/SRM-2 The Test Set, Relay TS-1752/SRM-2, shall meet the following detail requirements

3 4 1 2 1 Function. The Test Set, Relay TS-1752/SRM-2, shall be designed to test the operation of the Switch, Radio Frequency Transmission Line SA-631/SRW-4, and each type of relay contained in the Target Control System AN/SRW-4 or any revision thereof.

3.4.1.2.2 Form Factor. The maximum external dimensions of the Test Set, Relay TS-1752/SRM-2, shall be as follows:

Source: https://assist.dla.mil -- Downloaded: 20260-19T17:26Z
Check the source to verify that this is the current version before use.

Height: 8-3/4 inches
Width: 19 inches
Depth: 18 inches

3 4 1 2 3 Weight The weight of the Test Set, Relay TS-1752/SRM-2, shall not exceed 50 pounds

3 4 1.2 4 Contents of Unit The Test Set, Relay TS-1752/SRM-2, shall contain the following circuits

(1) Power Supply and Metering Circuit

(2) Component Selection, Testing and Indicating Circuitry.

3.4 1.2 4 1 Power Supply and Metering Circuit The power supply and metering circuit shall provide all the variable and constant d-c voltages required by the Test Set, Relay TS-1752 SRM-2, and the equipment it shall test The metering portion of the circuitry shall indicate the voltage being utilized by the equipment being tested The circuitry shall include a variac, a power transformer, six diode rectifiers, a choke, and a milliammeter

3.4 1.2 4.2 Component Selection, Testing and Indicating Circuitry The component selection, testing and indicating circuitry shall provide the facilities for selecting and testing either the desired relay type or the Switch, Radio Frequency Transmission Line SA-631/SRW-4 Facilities for displaying the test results shall also be provided The circuitry shall include a 12-pole, 12-position selector switch, a two-position toggle switch, 12 indicator lamps and seven receptacles

3 4 1 2.5 Controls and Indicators The following controls and indicators shall be provided on the front panel of the Test Set, Relay TS-1752/SRM-2

(1) Primary Power Control A two-position toggle switch shall be provided for controlling the application of primary power This switch shall be designated PWR, ON, OFF

(2) Fuses and Fuseholders A fuse and fuseholder shall be provided for protecting the equipment from electrical overloads and shorts, and a spare fuse and fuseholder shall be provided These fuseholders shall be designated as F1 2 AMP and SPARE Fuseholders shall be of the blown-fuse indicating type as specified in Specification MIL-F-19207

(3) Component Selection Control Switch A 12-position, 12-pole rotary selector switch for selecting either the type of relay or the Switch, Radio Frequency Transmission Line SA-631/SRW-4, to be tested. The switch shall be designated RELAY SEL and shall have indications designating the type of relays tested, the corresponding receptacle, and the meter multiplier for each of the 12 positions

Source: https://assist.dla.mil -- Downloaded: 202640-19T17:26Z
Check the source to verify that this is the current version before use.

(4) Output Voltage Control. A variac control shall be provided for controlling the d-c voltage applied to the coil of the component being tested The control shall be designated RELAY V CONT, MIN, MAX.

(5) Switch, Radio Frequency Transmission Line SA-631/SRW-4, Position Selector. A two-position toggle switch shall be provided for selecting either position of the Switch, Radio Frequency Transmission Line SA-631/SRW-4, for testing The switch shall be designated POS 1, POS 2

(6) Primary Power Indicator Lamp An indicator lamp shall be provided to indicate when primary power is applied to the equipment The indicator lamp shall be designated PWR.

(7) Relay Contact Indicator Lamps Eight indicator lamps shall be provided for indicating the closed and open positions of the relay contacts being tested They shall be designated CLOSED, OPEN.

(8) Meter Indicator A meter indicator shall be provided for displaying the voltage applied to the component being tested

(9) SA-631/SRW-4 RF Coaxial Transmission Switch Indicator Lamps Three indicator lamps shall be provided for displaying if the high-voltage interlock circuit and the RF contacts of positions 1 and 2 are closed. The lamps shall be designated HV INTLK, POS 1, POS 2

3 4 1 2 6 Primary Input Power Requirements The Test Set, Relay TS-1752/SRM-2. shall meet all applicable requirements of Specification MIL-T-21200 and shall give specified performance from the following power sources with characteristics as defined in Specification MIL-T-21200 having limits specified therein The power required shall not exceed the specified amounts

(1) AC Power (Single Phase), 60 cycle, 102 to 126 volt, 25 VA

3.4.1.2 7 Electrical Connections Connections to external circuits shall be provided as follows:

(1) Rear Panel Electrical Connections.

Reference Designation	Receptacle Type	Function
J8	SPO2A-12-3P	Primary Input Power

Source: https://assist.dla.mil -- Downloaded: 20260-19T17:26Z
Check the source to verify that this is the current version before use.

(2) Front Panel Electrical Connections.

Reference Designation	Receptacle Type	Function
J1	MS3102A-22-19S	Receptacle for Relay Type 404P206
J2	MS3102A-20-27S	Receptacle for Relay Type AN 3303-1 and 4C4P369
J3	BEC 2100	Receptacle for Relay Types BR7Y-8E8-.12-1 2V, BR7X-900E8-14-14, BR7Z-1600E8-26V
J4	BEC 20587	Receptacle for Relay Types BR8-600A1-1.2-12 5V, BR8-8 5KA8-2.0-5 0, BR8-5KA1-A8
J5	Viking VB16 1EE20-43	Receptacle for Relay Type BR14X-150A1-26V
J6	MS3102A-16S-1S	Output to Switch, Radio Frequency Transmission Line SA-631/SRW-4.
J7	MS3102A-14S-2S	Output to Switch, Radio Frequency Transmission Line SA-631/SRW-4.

3.4.1 3 Test Set, Radio Set Transfer Control TS-1749/SRM-2 The Test Set, Radio Set Transfer Control TS-1749/SRM-2, shall meet the following requirements

3.4.1.3 1 Function. The Test Set, Radio Set Transfer Control TS-1749/SRM-2, shall be designed to test the operation of the switching circuits of the Control, Transfer C-3307/UR, of the Power Supply PP-2658/UR.

3.4 1.3.2 Form Factor The maximum external dimensions of the Test Set, Radio Set Transfer Control TS-1749/SRM-2, shall be as follows

Height 8-3/4 inches
Width 19 inches
Depth: 18 inches

3.4.1.3.3 Weight. The weight of the Test Set, Radio Set Transfer Control TS-1749/SRM-2, shall not exceed 60 pounds.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:26Z
Check the source to verify that this is the current version before use.

3.4.1.3.4 Contents of Unit. The Test Set, Radio Set Transfer Control TS-1749/SRM-2, shall contain the following circuits:

(1) Regulated D-C Power Supply and Metering Circuitry.

(2) Variable D-C Bias Supply and Metering Circuitry.

(3) 28-Volt D-C and 6 3-Volt A-C Filament Voltage Power Supply Circuitry.

(4) Controls, Switches, and Indicator Lamp Circuits

3 4.1.3 4.1 Regulated D-C Power Supply and Metering Circuitry The regulated d-c power supply and metering circuit shall supply regulated 230 volts d-c to the control, transfer, under test The 230 volts d-c shall be supplied as B+ to the transfer control circuits of the equipment under test The metering portions of the circuitry shall be capable of monitoring the outputs of the regulated d-c power supply.

3.4 1 3 4.2 Variable D-C Bias Supply The variable d-c bias supply shall simulate forward and reflected power, and shall be supplied as such to the control, transfer, under test The simulated forward and reflected power shall be monitored by a metering circuit.

3 4.1 3 4 3 +28-Volt D-C and 6.3-Volt A-C Filament Voltage Power Supply Circuitry. The +28-volt d-c circuitry shall provide the voltage utilized by the relays contained in the Test Set, Radio Set Transfer Control TS-1749/SRM-2, and the control, transfer, under test. The 6 3-volt a-c circuitry shall supply the voltage utilized by the tube filaments and indicator lamps contained in the Test Set, Radio Set Transfer Control TS-1749/SRM-2 The 6.3 volts ac shall also be supplied to the control, transfer, under test

3 4.1.3.4 4 Controls, Switches, and Indicator Lamp Circuits. The controls, switches, and indicator lamp circuits shall provide the facilities for controlling the testing sequence and for monitoring the test results of the control, transfer

3 4 1.3.5 Controls and Indicators. The following controls and indicators shall be provided on the front panel of the Test Set, Radio Set Transfer Control TS-1749/SRM-2

(1) Primary Power Switch A two-position toggle switch shall be provided for controlling the application of primary power to the Test Set, Radio Set Transfer Control TS-1749/SRM-2 The switch shall be designated MAIN PWR, ON, OFF.

(2) Regulated D-C Power Supply Switch. A two-position toggle switch shall be provided for energizing the regulated d-c power supply circuits of the Test Set, Radio Set Transfer Control TS-1749/SRM-2. The switch shall be designated HV, ON, OFF.

Source: https://assist.dla.mil -- Downloaded: 202610-19T17:26Z
Check the source to verify that this is the current version before use.

(3) Control, Transfer, High Voltage Control Switch. A two-position toggle switch shall be provided for controlling the high-voltage circuits of the control, transfer, under test. The switch shall be designated HV CONT, ON, OFF.

(4) Switching Circuits Switch. A two-position toggle switch shall be provided for selecting the control circuits of either the control, transfer, under test or the Test Set, Radio Set Transfer Control TS-1749/SRM-2 The switch shall be designated TEST SEL, INT TEST, EXT TEST

(5) Control, Transfer, Carrier Switch A two-position toggle switch shall be provided for energizing the carrier circuitry of the control, transfer, under test The switch shall be designated CARRIER CONT, KEYED, CONT.

(6) Control, Transfer, Reset Switch A momentary-contact toggle switch shall be provided for resetting the switching circuits of the control, transfer, under test. The switch shall be designated TRANSFER RESET, ON, OFF

(7) Voltage-Monitor Switch A five-position selector switch shall be provided for monitoring the five d-c voltages utilized by the Test Set, Radio Set Transfer Control TS-1749/SRM-2 The switch shall be designated VOLTAGE MONITOR SEL.

(8) Variable D-C Voltage Controls Two variable potentiometers shall be provided for selecting the amount of simulated forward and reflected power supplied to the control, transfer, under test. They shall be designated as FORWARD PWR ADJ, MIN, MAX, and REFLECTED PWR ADJ, MIN, MAX.

(9) Meter Indicator A meter shall be provided for monitoring all the d-c outputs of the Test Set, Radio Set Transfer Control TS-1749/SRM-2

(10) Primary Power Indicator Lamp An indicator lamp shall be provided for displaying when primary power is applied to the equipment The indicator lamp shall be designated MAIN PWR.

(11) Regulated D-C Power Supply Indicator Lamp. An indicator lamp shall be provided for displaying when the regulated d-c power supply circuit is energized. The indicator lamp shall be designated HV

(12) Internal, External Control Circuit Indicator Lamps Indicator lamps shall be provided for displaying proper operation of the switching circuits of the control, transfer, under test. They shall be designated INT TEST and EXT TEST.

(13) Fuses. Two fuses and fuseholders shall be provided for protecting the equipment from electrical overloads or shorts. Two spare fuses and fuseholders shall also be provided. They shall be designated as F1, 3 AMP FIL, F2 2 AMP HV and SPARE. Fuseholders shall be of the blown fuse indicating type as specified in Specification MIL-F-19207.

Source: https://assist.dla.mil -- Downloaded: 202610-19T17:26Z
Check the source to verify that this is the currentversion before use.

3.4.1 3.6 Primary Input Power Requirements. The Test Set, Radio Set Transfer Control TS-1749/SRM-2, shall meet all applicable requirements of Specification MIL-T-21200 and shall give specified performance from the following power sources with characteristics as defined in Specification MIL-T-21200 having limits specified therein. The power required shall not exceed the specified amounts.

(1) AC Power (Single Phase), 60 cycle, 102 to 126 volt, 125 VA

3 4 1 3.7 Electrical Connections Connections to external circuits shall be provided as follows:

(1) Front Panel Electrical Connectors.

Reference Designation	Receptacle Type	Function
J1	MS24019-1	Output to Control, Transfer C-3307/UR

(2) Rear Panel Electrical Connectors

Reference Designation	Receptacle Type	Function
J2	SPO2A-12-3P	Primary Input Power

3.4 1 4 Test Set, Transmitter TS-1753/SRM-2 The Test Set, Transmitter TS-1753/SRM-2, shall meet the following detail requirements

3 4.1 4.1 Function The Test Set, Transmitter TS-1753/SRM-2, shall be designed to test and calibrate each subassembly contained in the Transmitting Set, Radio AN/URW-14, and Transmitting Set, Radio AN/URW-14A, of Target Control System AN/SRW-4 or any revision thereof.

3 4 1 4.2 Form Factor. The maximum external dimensions of the Test Set, Transmitter TS-1753/SRM-2, shall be as follows

Height	17-1/2 inches
Width	19 inches
Depth	23 inches

3.4 1.4.3 Weight. The weight of the Test Set, Transmitter TS-1753/SRM-2, shall not exceed 200 pounds.

3.4.1.4.4 Contents of Unit. The Test Set, Transmitter TS-1753/SRM-2, shall contain the following circuits.

(1) Primary Power Control and Protection Circuitry.

Source: https://assist.dla.mil -- Downloaded: 202610-19T17:26Z
Check the source to verify that this is the currentversion before use.

(2) Regulated +410, +300 or +150-Volt D-C Power Supply Circuitry

(3) +1260 Volt D-C Power Supply Circuitry

(4) External Low-Voltage A-C Power Supply Circuitry

(5) +28-Volt D-C Power Supply Circuitry

(6) -70 and -30-Volt D-C Power Supply Circuitry

(7) Internal Low Voltage A-C Power Supply Circuitry

(8) Internal +300-Volt D-C Power Supply Circuitry

(9) External +300-Volt D-C Power Supply Circuitry

(10) Regulated +200, +180 and -108-Volt D-C Power Supply Circuitry

(11) Internal and External Power Supply Monitoring Circuitry

(12) Tune-Up Signal Monitoring Circuitry

(13) Audio-Frequency Coder Subassembly Control and Monitoring Circuitry

(14) External Coder Control Circuitry

3 4.1.4 4.1 Primary Power Control and Protection Circuitry The primary power control and protection circuitry shall provide the facilities for controlling the application of 115-volt 60-cycle power to circuits of the Test Set, Power Supply TS-1750/SRM-2, and for protecting the circuits from electrical overloads and shorts.

3.4.1 4.4.2 Regulated +410, +300, or +150-Volt D-C Power Supply Circuitry The regulated +410, +300, or +150-volt d-c power supply circuitry shall supply a +410-volt regulated d-c voltage and either a +300 or +150-volt regulated d-c voltage for testing an amplifier-subassembly or frequency multiplier subassembly of the Transmitting Set, Radio AN/URW-14, or Transmitting Set, Radio AN/URW-14A.

3 4.1.4 4 3 +1260-Volt D-C Power Supply Circuitry The +1260-volt d-c power supply circuitry shall supply a +1260-volt d-c voltage for testing an amplifier-frequency multiplier subassembly of the Transmitting Set, Radio AN/URW-14, or Transmitting Set, Radio AN/URW-14A, and shall provide the facilities for monitoring the plate current of the final amplifier.

3.4.1.4.4.4 External Low-Voltage A-C Power Supply Circuitry. The external low-voltage a-c power supply circuitry shall supply 6.3 and 12.6-volt a-c filament voltages to external subassemblies of the Transmitting Set, Radio AN/URW-14, or Transmitting Set, Radio AN/URW-14A, under test. The metering circuit shall indicate current utilized during the cycling of the crystal-oven

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:26Z
Check the source to verify that this is the current version before use.

heaters when an amplifier-modulator subassembly of the Transmitting Set, Radio AN/URW-14, or Transmitting Set, Radio AN/URW-14A, is under test.

3.4.1.4.4.5 +28-Volt D-C Power Supply Circuitry. The +28-volt d-c power supply circuitry shall supply the +28 volts dc utilized internally by the Test Set, Transmitter TS-1753/SRM-2, and shall supply +28 volts dc to the oven heater of variable inductor Z404 when testing an amplifier-modulator subassembly of the Transmitting Set, Radio AN/URW-14, or Transmitting Set, Radio AN/URW-14A. A lamp shall display when the variable inductor Z404 oven heater of an amplifier-modulator subassembly of the Transmitting Set, Radio AN/URW-14, or Transmitting Set, Radio AN/URW-14A, is energized.

3.4.1.4.4.6 -70 and -30-Volt D-C Power Supply Circuits. The -70 and -30-volt d-c power supply circuits shall supply -70 and -30 volts dc for testing an amplifier-frequency multiplier subassembly of the Transmitting Set, Radio AN/URW-14, or Transmitting Set, Radio AN/URW-14A, and -30 volts dc for testing an amplifier-modulator subassembly.

3.4.1.4.4.7 Internal Low Voltage A-C Power Supply Circuitry. The internal low voltage a-c power supply circuitry shall supply all 6.3-volt a-c filament voltages required by the Test Set, Transmitter TS-1753/SRM-2.

3.4.1.4.4.8 Internal +300-Volt D-C Power Supply Circuitry. The internal +300-volt d-c power supply circuitry shall supply +300 volts dc as B+ to the +200, +180, and +108-volt regulated d-c power supply circuit of the Test Set, Transmitter TS-1753/SRM-2.

3.4.1.4.4.9 External +300-Volt D-C Power Supply Circuitry. The external +300-volt d-c power supply circuitry shall supply +300 volts dc for testing either an amplifier-modulator subassembly of the Transmitting Set, Radio AN/URW-14, or Transmitting Set, Radio AN/URW-14A, or an audio-frequency coder subassembly.

3.4.1.4.4.10 Regulated +200, +180, and +108-Volt D-C Power Supply Circuitry. The Regulated +200, +180, and +108-volt d-c power supply circuitry shall supply regulated +200, +180, and +108 volts dc for testing either an amplifier-modulator subassembly of the Transmitting Set, Radio AN/URW-14, or Transmitting Set, Radio AN/URW-14A, or an audio frequency coder subassembly.

3.4.1.4.4.11 Internal and External Power Supply Monitoring Circuitry. The internal and external power supply monitoring circuitry shall provide the facilities for monitoring all d-c voltages internally generated by the Test Set, Transmitter TS-1753/SRM-2, or all d-c voltages supplied by the power supply subassembly under test.

3.4.1.4.4.12 Tune-Up Signal Monitoring Circuitry. The tune-up signal monitoring circuitry shall facilitate the monitoring of the amplifier-modulator and amplifier-frequency multiplier of the Transmitting Set, Radio AN/URW-14, or Transmitting Set, Radio AN/URW-14A, during tune-up or operation.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:26Z
Check the source to verify that this is the current version before use.

3.4.1.4.4.13 Audio-Frequency Coder Subassembly Control and Monitoring Circuitry. The audio-frequency coder subassembly control and monitoring circuitry shall provide facilities for monitoring the carrier level, for selecting the carrier mode, for controlling the coder output, for controlling the external audio input level, and for controlling the carrier sidetone bias level This circuitry shall also provide facilities for selecting either the internal coder or an external coder and controlling the compressor mode of the audio-frequency coder assembly of the Transmitting Set, Radio AN/URW-14, or Transmitting Set, Radio AN/URW-14A, being tested

3 4.1 4.4 14 External Coder Audio Input Control Circuitry The external coder audio input control circuitry shall provide the facilities for controlling the level of the audio signal when testing an audio frequency coder subassembly of the Transmitting Set, Radio AN/URW-14, or Transmitting Set,Radio AN/URW-14A, in conjunction with an external coder.

3 4.1 4 5 Controls and Indicators. The following controls and indicators shall be provided on the front panel of the Test Set, Transmitter TS-1753/SRM-2.

(1) Power Switch A two-position toggle switch shall be utilized to control the application of external power to the Test Set, Transmitter TS-1753/SRM-2 The switch shall be designated MAIN PWR

(2) High Voltage Switch. A two-position toggle switch shall be utilized to energize the internal high voltage and B+ circuits of the Test Set, Transmitter TS-1753/SRM-2 The switch shall be designated HV, ON, OFF.

(3) Power Mode Switch A two-position toggle switch shall be utilized to select either the +150 or +300-volt d-c regulated voltage for testing an amplifier-frequency multiplier of the Transmitting Set, Radio AN/URW-14, or Transmitting Set, Radio AN/URW-14A The switch shall be designated PWR MODE, HI PWR, LOW PWR

(4) Carrier Mode Switch A two-position toggle switch shall be utilized to select either continuous or keyed carrier operation for testing an audio-frequency coder subassembly of the Transmitting Set, Radio AN/URW-14, or Transmitting Set, Radio AN/URW-14A The switch shall be designated CARRIER MODE, KEYED, CONT

(5) Coder Selector Switch A two-position toggle switch shall be utilized to select either the internal or external audio circuitry when testing an audio-frequency coder subassembly of the Transmitting Set, Radio AN/URW-14, or Transmitting Set, Radio AN/URW-14A. The switch shall be designated CODER SEL, INT, EXT.

(6) Compressor Mode Switch. A two-position switch shall be utilized to select either the coder or compressor output signal supplied from the audio-frequency coder subassembly of the Transmitting Set, Radio AN/URW-14, or Transmitting Set, Radio AN/URW-14A. The switch shall be designated COMPR MODE, IN, OUT.

Source: https://assist.dla.mil -- Downloaded: 202640-19T17:26Z
Check the source to verify that this is the currentversion before use.

(7) Carrier Sidetone Control. A combination potentiometer and on-off switch shall be utilized to control the level of the carrier sidetone bias when testing an audio-frequency coder subassembly of the Transmitting Set, Radio AN-URW-14, or Transmitting Set, Radio AN/URW-14A. The control shall be designated CARRIER SIDETONE CONTROL, OFF, MAX

(8) External Coder Audio Level Control. A potentiometer shall be utilized to control the level of the audio-frequency signal when testing an audio-frequency coder subassembly of the Transmitting Set, Radio AN/URW-14, or Transmitting Set, Radio AN/URW-14A, in conjunction with an external coder. The control shall be designated EXT CODER, MIN, MAX, LEVEL ADJ.

(9) Voltage Monitor Select Switch A two-position 12-pole selector switch shall be utilized to select, for monitoring purposes, either the internally generated voltages of the Test Set, Transmitter TS-1753/SRM-2, or external voltages supplied when testing a power supply subassembly of the Transmitting Set, Radio AN/URW-14, or Transmitting Set, Radio AN/URW-14A. The switch shall be designated SUPPLY MONITOR SEL, TEST SET, PP-2287 PP-2603.

(10) Voltage Supply Select Switch. An 11-position, two-pole selector switch shall be utilized for monitoring any one of 11 voltages either internally generated or externally supplied when testing a power supply subassembly of the Transmitting Set, Radio AN/URW-14, or Transmitting Set, Radio AN/URW-14A. The switch shall be designated SUPPLY VM SEL and shall indicate the value of each of the 11 voltages monitored.

(11) Tune-Up Meter Selector Switch A seven-position selector switch shall be utilized to monitor the amplifier-modulator and amplifier-frequency multiplier subassemblies of the Transmitting Set, Radio AN/URW-14, or Transmitting Set, Radio AN/URW-14A, under test during tune-up operation. The switch shall be designated TUNE UP METER SEL and shall indicate each signal monitored.

(12) Voltmeters Two voltmeters shall be provided, one to monitor the tune-up voltages when testing an amplifier-frequency multiplier and an amplifier-modulator subassembly of the Transmitting Set, Radio AN/URW-14, or Transmitting Set, Radio AN/URW-14A, and one to monitor power-supply voltages when testing a power supply subassembly.

(13) Milliammeters Two milliammeters shall be provided, one to indicate the plate current of the final amplifier when testing the amplifier-frequency multiplier subassembly of the Transmitting Set, Radio AN/URW-14, or Transmitting Set, Radio AN/URW-14A, and one to indicate the crystal oven heater current when testing the amplifier-modulator subassembly.

(14) Deviation Meter. A deviation meter shall be provided to indicate the amount of deviation of the radio-frequency signal when testing an amplifier-modulator subassembly in conjunction with an audio-frequency coder

Source: https://assist.dla.mil -- Downloaded: 202610-19T17:26Z
Check the source to verify that this is the current version before use.

subassembly of the Transmitting Set, Radio AN/URW-14, or Transmitting Set, Radio AN/URW-14A

(15) Indicator Lamps. Four indicator lamps shall be provided, one to indicate when main power is applied to the Test Set, Transmitter TS-1753/SRM-2 one to indicate when the high voltage circuits of the Test Set, Transmitter TS-1753/SRM-2, are energized, one to indicate carrier control relay operation when testing an audio-frequency coder subassembly of the Transmitting Set, Radio AN/URW-14, or Transmitting Set, Radio AN/URW-14A, and one to indicate whether the crystal oven heaters are energized when testing the modulation amplifier subassembly They shall be designated MAIN PWR, HV, CARRIER MODE, and Z404 OVEN MONITOR AM-2148 AM-2538

(16) Fuses. Five fuses and corresponding fuseholders shall be provided for protecting the equipment from electrical overloads and shorts Five spare fuses and corresponding fuseholders shall also be provided The fuseholders shall be designated F1 3 AMP FIL, F2 3 AMP FIL, F3 8 AMP HV, F4 2 AMP 300 VDC, F5 1 AMP 180 VDC, and SPARES. Fuseholders shall be of the blown fuse indicating type as specified in Specification MIL-F-19207

3.4.1.4.6 Primary Input Power Requirements The Test Set, Transmitter TS-1753/SRM-2, shall meet all applicable requirements of Specification MIL-T-21200 and shall give specified performance from the following power sources with characteristics as defined in Specification MIL-T-21200 having limits specified therein The power required shall not exceed the specified amounts

(1) AC Power (Single Phase), 60 cycle, 102 to 126 volt, 1,500 VA

3.4.1.4.7 Electrical Connections Connections to external circuits shall be provided as follows:

(1) Front Panel Electrical Connections

Reference Designation	Receptacle Type	Function
J1	UG-657/U	External Coder Audio Input
J2	UG-657/U	Audio Monitor Connection
J3	A15-S	Amplifier-Frequency Multiplier Subassembly Test Connection
J4	MS24055-1	Amplifier-Frequency Multiplier Subassembly Test Connection
J5	MS24055-1	Amplifier-Modulator Subassembly Test Connection

Source: https://assist.dla.mil -- Downloaded: 202640-19T17:26Z
Check the source to verify that this is the current version before use.

Reference Designation	Receptacle Type	Function
J6	MRE9SG/V	Amplifier-Modulator Subassembly Test Connection
J7	UG-657/U	Amplifier-Modulator Subassembly Audio Input Connection
J8	UG-657/U	External Coder Audio Output Connection
J9	UG-657/U	Audio Frequency Coder Subassembly Audio Output Connection
J10	UG-657/U	Audio Frequency Coder Subassembly Compressor Output Connection
J11	MS24013-1	Audio Frequency Coder Subassembly Test Connection
J12	MS3102A-18-1P	Power Supply Subassembly Test Connection
J13	MS24008-1	Power Supply Subassembly Test Connection
J14	MS24014-1	Power Supply Subassembly Test Connection
J15	A15-P	Power Supply Subassembly Test Connection
J16	JJ-034	Sidetone Monitor Connection

(2) Rear Panel Electrical Connections

Reference Designation	Receptacle Type	Function
J17	SP02A-12-3P	Primary Input Power

3.4.1.5 Test Set, Receiver TS-1751/SRM-2 The Test Set, Receiver TS-1751/SRM-2, shall meet the following detail requirements

3.4.1.5.1 Function The Test Set, Receiver TS-1751/SRM-2, shall be designed to facilitate testing and calibration of the decoder subassembly and the various components and circuits contained in Receiver, Radio R-999/URW-16, of Target Control System AN/SRW-4 or any revision thereof.

3.4.1.5.2 Form Factor. The maximum external dimensions of the Test Set, Receiver TS-1751/SRM-2, shall be as follows:

Source: https://assist.dla.mil -- Downloaded: 20261O-19T17:26Z
Check the source to verify that this is the currentversion before use.

Height: 15-3/4 inches
Width: 19 inches
Depth: 23 inches

3.4.1.5.3 Weight. The weight of the Test Set, Receiver TS-1751/SRM-2, shall not exceed 60 pounds.

3.4.1.5.4 Contents of Unit. The Test Set, Receiver TS-1751/SRM-2, shall include the following circuits.

(1) Primary Power Control, Indicating, and Protective Circuitry

(2) Regulated +200-Volt D-C Power Supply Circuitry

(3) -22-Volt D-C Power Supply Circuitry.

(4) Low Voltage A-C Power Supply and Metering Circuitry

(5) Noise Generator and Sensitivity Circuitry Control

(6) Tune-Up Signal Metering Circuitry

(7) Internal and External D-C Voltage Metering Circuitry

3.4.1.5.4.1 Primary Power Control, Indicating, and Protective Circuitry. The primary power control, indicating, and protective circuitry shall provide the facilities for controlling the application of primary power to the Test Set, Receiver TS-1751/SRM-2, and for protecting the circuits of the equipment from electrical overloads and shorts.

3.4.1.5.4.2 Regulated +200-Volt D-C Power Supply Circuits. The regulated +200-volt d-c power supply circuits shall provide regulated +200-volts dc for testing i-f and r-f amplifiers of the subassemblies of the Receiver, Radio R-999/URW-16.

3.4.1.5.4.3 -22-Volt D-C Power Supply Circuitry. The -22 volt d-c power supply circuitry shall provide -22 volts dc for testing a decoder subassembly of the Receiver Radio R-999/URW-16.

3.4.1.5.4.4 Low-Voltage A-C Power Supply and Metering Circuitry. The low-voltage a-c power supply and metering circuitry shall provide 6.3 and 12.6-volt a-c filament voltages to the Test Set Receiver TS-1751/SRM-2 and to the components under test. Facilities for indicating the amount of current utilized during the crystal oven heating cycle when testing an r-f amplifier assembly of the Receiver, Radio R-999/URW-16, shall also be provided by this circuit.

3.4.1.5.4.5 Noise Generator and Sensitivity Control Circuitry. The noise generator and sensitivity control circuitry shall provide control for checking the noise generator and sensitivity relay control circuits of the radio-frequency amplifier of the Receiver, Radio R-999/URW-16.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:26Z
Check the source to verify that this is the current version before use.

3.4.1.5.4.6 Tune-Up Signal Metering Circuitry. The tune-up signal metering circuitry shall provide the facilities for monitoring the tune-up signals of the i-f and r-f amplifiers of the Receiver, Radio R-999/URW-16.

3 4.1.5.4 7 Internal and External D-C Voltage Metering Circuitry. The internal and external d-c voltage metering circuitry shall provide the facilities for metering either the d-c voltages generated by the Test Set, Receiver TS-1751/SRM-2, or the d-c voltage generated by the power supply circuitry of the Receiver, Radio R-999/URW-16, being tested.

3 4 1.5.5 Controls and Indicators. The following controls and indicators shall be provided on the front panel of the equipment

(1) Main Power Switch. A two-position toggle switch shall be provided for controlling the application of primary power to the Test Set, Receiver TS-1751/SRM-2 The switch shall be designated MAIN PWR, ON and OFF

(2) High-Voltage Switch A two-position toggle switch shall be provided for energizing the internal high-voltage circuits of the Test Set, Receiver TS-1751/SRM-2, and for applying 6 3 volts a-c to the indicator lights of the decoder subassembly of the Receiver, Radio R-999/URW-16 This switch shall be designated HV, ON and OFF.

(3) Noise Generator Switch A two-position toggle switch shall be provided for controlling the noise generator located in the r-f amplifier of the Receiver, Radio R-999/URW-16. This switch shall be designated NOISE GEN, ON and OFF

(4) Sensitivity Switch A two-position toggle switch shall be provided for selecting either a low or high sensitivity position of the sensitivity control relay in the r-f amplifier of the Receiver, Radio R-999/URW-16 This switch shall be designated SENSITIVITY and LOW

(5) Remote Power Switch. A two-position toggle switch shall be provided for energizing the transmitter override circuitry of the Receiver, Radio R-999/URW-16, being tested. The switch shall be designated REMOTE PWR, ON and OFF

(6) Tune-Up Meter Selector Switch A five-position rotary selector switch shall be provided for metering the tune-up signals of the i-f and r-f amplifier being tested The switch shall be designated TUNE-UP METER SELECTOR and shall indicate what signals may be metered.

(7) Supply Monitor Selector Switch. A two-position, six-pole selector shall be provided to select, for metering purposes, d-c voltage generated by either the Test Set, Receiver TS-1751/SRM-2, or the power supply circuitry of the Receiver, Radio R-999/URW-16, being tested. This switch shall be designated SUPPLY MONITOR SELECTOR with positions TEST SET and R-999.

Source: https://assist.dla.mil -- Downloaded: 202640-19T17:26Z
Check the source to verify that this is the currentversion before use.

(8) Voltage Monitor Selector Switch. A six-position, two-pole selector switch shall be provided to select, for metering purposes, d-c voltages generated by either the Test Set, Receiver TS-1751/SRM-2, or the power supply circuitry of the Receiver, Radio-999/URW-16, being tested. This switch shall be designated SUPPLY VM SELECTOR, and shall indicate the voltages to be metered.

(9) Channel Selector Switch. A 20-position, single-pole rotary selector switch shall be provided for selecting the desired decoding channel of the decoder subassembly of the Receiver, Radio R-999/URW-16. This switch shall be designated KY-340 CHANNEL SELECTOR and shall indicate the channels to be tested.

(10) Indicator Lamps. Four indicator lamps shall be provided, one for indicating that primary power is applied to the Test Set, Receiver TS-1751/SRM-2, one for indicating when the high-voltage circuits of the Test Set, Receiver TS-1751/SRM-2, are energized, one for indicating when a noise-generator signal is applied to the r-f amplifier of the Receiver, Radio R-999/URW-16, and one for indicating when a high-sensitivity control signal is applied to the r-f amplifier of the Receiver Radio R-999/URW-16. These indicator lamps shall be designated MAIN PWR, HV, NOISE GEN, and SENSITIVITY respectively.

(11) Channel Indicator Lamps. Two indicator lamps shall be provided for displaying the state (on-off) of the individual decoding channel being checked when testing a decoder subassembly of the Receiver, Radio R-999/URW-16. These indicator lamps shall be designated OFF, CHANNEL, ON.

(12) Voltmeters. Two voltmeters shall be provided, one for indicating the internally generated and externally generated voltages and one for indicating the tune-up signals of the i-f and r-f amplifiers of the Receiver, Radio R-999/URW-16.

(13) Milliammeter. A milliammeter shall be provided for indicating the current utilized by the crystal oven heaters of the r-f amplifier of the Receiver, Radio R-999/URW-16.

(14) Fuses and Fuseholders. Two fuses and fuseholders shall be provided for protecting the equipment from electrical overloads and shorts. Two spare fuses and fuseholders shall also be provided. The fuseholders shall be designated F1 3 AMP, F2 1.5 AMP, and SPARES. Fuseholders shall be of the blown fuse indicating type as specified in Specification MIL-F-19207.

3.4.1.5.6 Primary Input Power Requirements. The Test Set, Receiver TS-1751/SRM-2, shall meet all applicable requirements of Specification MIL-T-21200 and shall give specified performance from the following power sources with characteristics as defined in Specification MIL-T-21200 having limits specified therein. The power required shall not exceed the specified amounts.

(1) AC Power (Single Phase), 60 cycle, 102 to 126 volt 200 VA.

3.4.1.5.7 Electrical Connections. Connections to external circuits shall be as follows:

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:26Z
Check the source to verify that this is the current version before use.

(1) Front Panel Electrical Connections.

Reference Designation	Receptacle Type	Function
J1	MS3102A-14S-5S	Receiver, Radio R-999/URW-16, Main Chassis Power Test Connection
J2	SP02A-14-19S	Radio Frequency Amplifier Test Connection
J3	SP02A-12-10S	Intermediate Frequency Amplifier Test Connection
J4	MS24055-1	Decoder Subassembly Test Connection
J5	MS24056-1	Receiver, Radio R-999/URW-16, Main Chassis Power Supply Output to Decoder Test Connection
J6	SP02A-12-10P	Receiver, Radio R-999/URW-16, Main Chassis Power Supply Output to I-F Amplifier Test Connection
J7	SP02A-14-19P	Receiver Radio R-999/URW-16, Main Chassis Power Supply Output to Radio Frequency Amplifier Test Connection
J8	MS3102A-28-21S	Decoder, Audio Frequency KY-340/URW-16, Test Connector
J9	MS3102A-28-12S	Decoder, Audio Frequency KY-340/URW-16, Test Connector

(2) Rear Panel Electrical Connections

Reference Designation	Receptacle Type	Function
J10	SP02A-12-3P	Primary Input Power Connection to Test Set

3 4 1.6 Test Set, Power Supply TS-1750/SRM-2 The Test Set, Power Supply TS-1750/SRM-2, shall meet the following detail requirements

3 4 1 6.1 Function The Test Set, Power Supply TS-1750/SRM-2, shall test the Power Supply PP-2658/UR and shall enable testing of the Amplifier, Radio Frequency AM-2640/UR, when used in conjunction with the Power Supply PP-2658/UR The Test Set, Power Supply TS-1750/SRM-2, shall operate independently of the Test Set, Target Control System AN/SRM-2, while testing the Power Supply PP-2658/UR.

Source: https://assist.dla.mil -- Downloaded: 202610-19T17:26Z
Check the source to verify that this is the current version before use.

3.4.1.6.2 Form Factor. The maximum external dimensions of the Test Set, Power Supply TS-1750/SRM-2, shall be as follows:

Width: 19 inches
Height 17-1/2 inches
Depth 23 inches

3.4 1 6.3 Weight. The weight of the Test Set, Power Supply TS-1750/SRM-2, shall not exceed 80 pounds

3.4.1 6 4 Contents of Unit The Test Set, Power Supply TS-1750/SRM-2, shall contain the following

(1) Variable A-C Power Supply and Metering Circuitry

(2) +28-Volt D-C Power Supply.

(3) Input-Voltage Metering Circuitry

(4) Control, Switching, and Indicator Lamp Circuitry

3.4 1 6.4 1 Variable A-C Power Supply and Metering Circuitry The variable a-c power supply shall provide three-phase and single-phase variable operating power to the Power Supply PP-2658/UR under test The metering circuitry shall be capable of indicating the three-phase and single-phase input and output voltage levels of the variable a-c power supply

3.4.1.6.4.2 -28 Volt D-C Power Supply The -28 volt d-c power supply shall provide 28 volt d-c power for standby voltage to the unit under test This -28-volt power shall be controlled by a front panel two-position toggle switch.

3 4 1 6 4.3 Input-Voltage Metering Circuitry The input-voltage metering circuitry shall incorporate rectifying and voltage-dividing networks to provide proper metering of operating voltages of the unit under test These voltages of the unit under test shall be indicated on a front panel voltmeter Loading networks incorporated into the circuitry of the Test Set, Power Supply TS-1750/SRM-2, shall provide the proper simulated loads for the unit under test.

3.4.1.6 4 4 Control Switching, and Indicator Lamp Circuits The control, switching, and indicator lamp circuits shall provide the facilities for controlling the testing sequence and for monitoring the test results of the unit under test.

3 4 1.6.5 Controls and Indicators The following controls and indicators shall be provided on the front panel of the equipment

(1) Single-Phase Primary Power Switch. A two-position toggle switch shall be provided for controlling the application of single-phase 115-volt a-c primary power to the Test Set, Power Supply TS-1750/SRM-2. This switch shall be designated 1 Ø PWR, ON and OFF.

Source: https://assist.dla.mil -- Downloaded: 202640-19T17:26Z
Check the source to verify that this is the currentversion before use.

(2) Three-Phase Primary Power Switch. A two-position toggle switch shall be provided for controlling the application of three-phase 230-volt a-c primary power to the Test Set, Power Supply TS-1750/SRM-2. This switch shall be designated 3 Ø PWR, ON, and OFF.

(3) Single-Phase Primary Power Indicator Lamp An indicator lamp shall be provided for displaying when the single-phase 115-volt a-c primary power has been applied to the Test Set, Power Supply TS-1750/SRM-2. This indicator lamp shall be designated 1 Ø PWR

(4) Three-Phase Primary Power Indicator Lamp An indicator lamp shall be provided for displaying when three-phase 230-volt a-c primary power has been applied to the Test Set, Power Supply TS-1750/SRM-2. This indicator lamp shall be designated 3 ØPWR

(5) Single-Phase Adjust A variac shall be provided for adjusting the single-phase 115-volt a-c input power voltage applied to the unit under test. This control shall be designated 1 Ø ADJ, MIN, LINE, and MAX

(6) Three-Phase Adjust A variac shall be provided for adjusting the three-phase 230-volt a-c input power voltage applied to the unit under test This control shall be designated 3 Ø ADJ, MIN, LINE, and MAX

(7) 115-Volt A-C Voltmeter A voltmeter shall be provided for monitoring the 115-volt a-c input power to the unit under test This voltmeter shall be designated INPUT VOLTAGE VOLTS AC.

(8) 230-Volt A-C Voltmeters A voltmeter shall be provided for monitoring each phase of the three-phase 230-volt a-c input power to the unit under test These three voltmeters shall be designated INPUT VOLTAGE VOLTS A-C

(9) Input Voltage Metering Switch A two-position rotary switch shall be provided for selecting the input or output variac voltages to be monitored on the single-phase and three-phase voltmeters This switch shall be designated INPUT V METERING, PRI, and SEC

(10) Standby Switch A two-position toggle switch shall be provided for controlling the application of 28-volt d-c standby voltage to the unit under test This switch shall be designated STBY, ON, and OFF

(11) Standby Indicator Lamp An indicator lamp shall be provided for displaying the application of standby voltage to the unit under test. This indicator lamp shall be designated STBY.

(12) Local Control Switch. A two-position toggle switch shall be provided for controlling the ground continuity of the local control circuitry of the unit under test. This switch shall be designated LOCAL CONT, ON and OFF.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:26Z
Check the source to verify that this is the current version before use.

(13) High-Voltage Switch. A two-position toggle switch shall be provided for controlling the ground continuity of the high-voltage control circuitry of the unit under test. This switch shall be designated HV, ON, and OFF.

(14) High-Voltage Indicator Lamp. An indicator lamp shall be provided for displaying the application of ground continuity to the high-voltage circuitry of the unit under test This indicator lamp shall be designated HV.

(15) Interlock Switches Three normally-closed momentary toggle switches shall be provided to control ground continuity for the internal-power interlock circuit of the unit under test, ground continuity for the internal-blower interlock circuit of the unit under test, and control transfer interlock circuitry continuity of the unit under test The momentary toggle switches shall be designated INTERLOCKS, PWR, BLO, and CONT TRANSFER.

(16) Monitor Voltmeter. A voltmeter shall be provided for monitoring primary and secondary operating and control voltages of the unit under test. This voltmeter shall be designated VOLTAGE MONITOR.

(17) Monitor Selector Switch A 13-position switch shall be provided for selecting the voltage from the unit under test to be applied to the monitor voltmeter. This switch shall be designated METER SELECTOR

(18) Fuses and Fuseholders Four fuses and fuseholders shall be provided for protecting the equipment from electrical overloads or shorts Four corresponding spare fuses and fuseholders shall also be provided. The fuses shall be designated F1 10 AMP, F2 10 AMP, F3 10 AMP, F4 10 AMP, and SPARES Fuseholders shall be of the blown fuse indicating type per Specification MIL-F-19207

3 4.1.6.7 Primary Input Power Requirements The Test Set, Power Supply TS-1750/SRM-2, shall meet all applicable requirements of Specification MIL-T-21200 and shall give specified performance from the following power sources with characteristics as defined in Specification MIL-T-21200 having limits specified therein The power required shall not exceed the specified amounts.

(1) AC Power (Single Phase), 60 cycle, 102 to 126 volt, 790 VA

(2) AC Power (Three Phase), 60 cycle, 220 volt, 2,640 VA

3 4.1.6 7 Electrical Connections. Connections to external circuits shall be provided as follows:

Reference Designation	Receptacle Type	Function
J11	SP02A-14-5P	Three Phase, 230 Volt A-C, Power Input to Test Set, Power Supply TS-1750/SRM-2.

Source: https://assist.dla.mil -- Downloaded: 202610-19T17:26Z
Check the source to verify that this is the currentversion before use.

Reference Designation	Receptacle Type	Function
J12	SP02A-12-3P	Single Phase, 115 Volt A-C, Power Input to Test Set, Power Supply TS-1750/SRM-2.
J1	MS3102A-18-5S	Variable Single Phase, 115 Volt A-C Output to Unit Under Test
J2	MS3102A-18-15S	Variable Three Phase, 230 Volt A-C Output to Unit Under Test
J3	MS3102A-14S-5P	Unit Under Test, Voltage Monitoring Input to Test Set, Power Supply TS-1750/SRM-2
J4	MS3102A-24-28S	Control to Unit Under Test
J5	MS24040-1	Unit Under Test, Voltage Monitoring Input to Test Set, Power Supply TS-1750/SRM-2
J6	MS3102A-24-28P	Control to Unit Under Test
J7	MS3102A-20-33P	Unit Under Test, Voltage Monitoring Input and Control to Test Set, Power Supply TS-1750/SRM-2
J8	MS3102A-18-8P	Unit Under Test, Voltage Monitoring Input and Control to Test Set, Power Supply TS-1750/SRM-2
J9	CA-2831	Unit Under Test, Current Monitoring Input to Test Set, Power Supply TS-1750/SRM-2
J10	CA-2831	Unit Under Test, Voltage Monitoring Input to Test Set, Power Supply TS-1750/SRM-2

3.4.1.7 Coder, Audio Frequency KY-430/SRM. The Coder, Audio Frequency KY-430/SRM shall meet the following detail requirements

3.4.1.7.1 Function. The Coder, Audio Frequency KY-430/SRM, shall be designed to generate 20 audio-frequency tones which shall correspond to the 20 IRIG audio-frequency tones any 6 of which can be operated at any one time. Each individual channel shall have a maximum output of 2.0 volts a-c RMS

Source: https://assist.dla.mil -- Downloaded: 202640-19T17:26Z
Check the source to verify that this is the currentversion before use.

across a 500-ohm load and each channel shall be selected either manually, by a toggle switch located on the front panel of the equipment or remotely through grounding a terminal in the connector provided on the rear of the unit.

3.4.1.7.2 Form Factor. The maximum external dimensions of the Coder, Audio Frequency KY-430/SRM, shall be as follows:

Height 8-3/4 inches
Width 19 inches
Depth. 23 inches

3.4.1.7.3 Weight. The weight of the Coder, Audio Frequency KY-430/SRM, shall not exceed 75 pounds.

3.4.1.7.4 Contents of Unit. The Coder, Audio Frequency KY-430/SRM, shall contain the following.

(1) Audio Oscillator Circuitry

(2) Audio Amplifier Circuitry

(3) Power Supply Circuitry

3.4.1.7.4.1 Audio Oscillator Circuitry. Twenty audio oscillator circuits shall be included. The frequency of each oscillator shall be tuned to one of the first 20 IRIG audio frequencies Each audio oscillator shall remain quiescent until a ground return is applied to its catnode. The ground return shall be applied either by a toggle switch located on the front panel of the equipment or the associated relay which may be energized remotely

3.4.1.7.4.2 Audio Amplifier Circuitry. The audio amplifier circuitry shall consist of a two-stage amplifier obtaining feedback from a catnode follower.

3.4.1.7.4.3 Power Supply Circuitry. The power supply circuitry shall consist of a full-wave rectifier, a regulator stage and the necessary filtering facilities.

3.4.1.7.5 Controls. The following controls shall be located on the front panel of the Coder, Audio Frequency KY-430/SRM.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:26Z
Check the source to verify that this is the current version before use.

(1) Twenty modulation channel toggle switches shall be placarded 1 through 20 and shall energize the audio oscillator circuits individually.

(2) A power toggle switch with placarded positions POWER and OFF shall apply power to the equipment. The power on condition shall be denoted by an indicator lamp.

(3) A fuse and fuseholder for protecting the equipment against electrical overloads and shorts shall be provided. This fuse shall be mounted on the front panel and in the main power circuit and shall be of 1-1/2-ampere capacity. Fuseholders shall be of the blown fuse indicating type as specified in Specification MIL-F-19207.

3.4.1.7.6 Primary Input Power Requirements. The Coder, Audio Frequency KY-430 SRM, shall meet all applicable requirements of Specification MIL-T-21200 and shall give specified performance from the following power sources with characteristics as defined in Specification MIL-T-21200 having limits specified therein. The power required shall not exceed the specified amounts.

(1) AC Power (Single Phase), 60 cycle, 102 to 126 volt, 100 VA

3.4.1.7.7 Electrical Connections Connections to external circuits shall be provided as follows

Reference Designation	Receptacle Type	Function
J106	UG-657/U	Audio Frequency Monitor
J107	UG-657/U	Audio Frequency Output
J108	MS3102A-24-28S	Remote Control
J109	MS3102A-10SL-3P	Input Power

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:26Z
Check the source to verify that this is the current version before use.

3.4.1.8 Coder, Audio Frequency KY-431/SRM. The Coder, Audio Frequency KY-431/SRM, shall meet the following detail requirements:

3.4.1.8.1 Function. The Coder, Audio Frequency KY-431/SRM, shall either locally or remotely initiate coded logic signals for checkout of rotary wing components of Target Control System AN/SRW-4. The Coder, Audio Frequency KY-431/SRM, shall contain a coder-digital subassembly which shall convert the coded command signals to two digitally coded audio signals. Facilities shall be provided for applying the audio frequency signals to associated equipment.

3.3.1.8.2 Form Factor. The Coder, Audio Frequency KY-431/SRM, shall consist of two major assemblies. The maximum dimensions of each major assembly shall not exceed the following

Height:	8-3/4 inches	Height:	8-1/2 inches
Width:	19 inches	Width	8-1/2 inches
Depth:	24 inches	Depth	19-3/4 inches

3.4.1.8.3 Weight. The weight of the Coder, Audio Frequency KY-431/SRM, shall not exceed 60 pounds

3.4.1.8.4 Contents of Unit. The Coder, Audio Frequency KY-431/SRM, shall include the following subassemblies and components

(1) Coder-Digital Subassembly

(2) Regulator Subassembly

(3) Main Chassis

(4) Control, Coder C-4123/SRM

3.4.1.8.4.1 Coder-Digital Subassembly. The detail requirements of the coder-digital subassembly shall be as follows

3.4.1.8.4.1.1 Function. The coder-digital subassembly shall convert coded binary command signals to audio-frequency command signals of 43.68 and 47.68 kilocycles. In the resultant digital scheme, nine word bits shall complete one word and eleven words shall complete one information frame. The coding sequence shall be such as to produce one blank word, two synchronizing words, and eight command words per information frame. Three bits in the second synchronizing word of each information frame shall be variable and shall determine the security address code selected. The sequence of the three variable bits of the second synchronizing word shall be determined by the equipment ADDRESS switch.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:26Z
Check the source to verify that this is the current version before use.

3.4.1.8.4.1.2 Form Factor. The maximum external dimensions of the coder-digital subassembly shall be as follows:

Height 6-1/2 inches

Width 10-13/16 inches

Depth 12 inches

3.4.1.8.4.1.3 Weight The maximum weight of the coder-digital subassembly shall not exceed 11.5 pounds.

3.4.1.8.4.1.4 Contents of Unit. The coder-digital subassembly shall include the following non-repairable, printed circuit, plug-in type subassembly boards:

(1) Clock Oscillator Plug-In Subassembly

(2) Clock Counter Plug-In Subassembly

(3) Digit Counter Plug-In Subassembly

(4) Digit Matrix No. 1 Plug-In Subassembly

(5) Digit Matrix No 2 Plug-In Subassembly

(6) Temporary Register No. 1 Plug-In Subassembly

(7) Temporary Register No 2 Plug-In Subassembly

(8) "And" Gate Plug-In Subassembly

(9) Memory Counter Plug-In Subassembly

(10) Subcarrier Plug-In Subassembly

(11) Subcarrier Oscillator Plug-In Subassembly

(12) Gray Converter Plug-In Subassembly

(13) Word Matrix No 3 Plug-In Subassembly

(14) Word Counter Plug-In Subassembly

(15) Word Matrix No. 1 Plug-In Subassembly

(16) Word Matrix No. 2 Plug-In Subassembly

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:26Z
Check the source to verify that this is the current version before use.

3.4.1.8.4.1.4.1 Clock Oscillator Plug-In Subassembly. The clock oscillator plug-in subassembly shall generate the basic timing pulse utilized by the coder-digital subassembly. The clock oscillator plug-in subassembly shall be designated C/CO.

3 4 1.8.4.1 4.2 Clock Counter Plug-In Subassembly. The clock counter plug-in subassembly shall divide the output of the clock oscillator to produce the word frequency. The clock counter plug-in subassembly shall be designated C/CC

3 4.1.8.4.1.4 3 Digit Counter Plug-In Subassembly. The digit counter plug-in subassembly shall produce the word rate frequency. The digit counter plug-in subassembly shall be designated DC.

3.4.1.8 4.1.4 4 Digit Matrix No. 1 Plug-In Subassembly. The digit matrix No. 1 plug-in subassembly shall be used in conjunction with digit matrix No. 2 plug-in subassembly to produce time sequenced pulses for application of the temporary register No 1 and No. 2 plug-in subassemblies The digit matrix No. 2 plug-in subassembly shall be designated C/DM1.

3.4.1.8 4.1 4.5 Digit Matrix No. 2 Plug-In Subassembly. The function of the digit matrix No. 2 plug-in subassembly shall be as specified in 3.4 1 8.4.1 4 4. The digit matrix No. 2 plug-in subassembly shall be designated C/DM2.

3.4.1.8 4.1.4.6 Temporary Register No 1 Plug-In Subassembly The temporary register No 1 plug-in subassembly shall be used in conjunction with temporary register No 2 plug-in subassembly to serve as temporary information storage circuits during the parallel to series information conversion process. The temporary register No 1 plug-in subassembly shall be designated C/TR1.

3.4.1.8.4.1 4 7 Temporary Register No 2 Plug-In Subassembly The function of the temporary register No. 2 plug-in subassembly shall be as specified in 3.4 1.8 4.1 4.6 The temporary register No. 2 plug-in subassembly shall be designated C/TR2.

3.4.1.8 4.1 4.8 "And" Gate Plug-In Subassembly The "and" gate plug-in subassembly shall provide the circuits to "and" the timing pulses produced by digit matrix No 1 and No. 2 plug-in subassemblies with pulse information generated by the command function control circuits. The "and" gate plug-in subassembly shall be designated C AG

3.4.1 8.4.1 4 9 Memory Counter Plug-In Subassembly. The memory counter plug-in subassembly shall provide the delay function when transmitting a station memory command signal The memory plug-in subassembly shall be designated C/MC.

3.4.1.8.4.1.4.10 Subcarrier Plug-In Subassembly. The subcarrier plug-in subassembly shall convert the binary coded information to audio frequency signals. The subcarrier plug-in subassembly shall be designated C/SC.

Source: https://assist.dla.mil -- Downloaded: 202610-19T17:26Z
Check the source to verify that this is the current version before use.

3.4.1.8.4.1.4.11 Subcarrier Oscillator Plug-In Subassembly. The subcarrier oscillator plug-in subassembly shall produce the audio frequency signals utilized in the digital to audio frequency conversion process. The subcarrier oscillator plug-in subassembly shall be designated C/SCO.

3 4 1.8.4.1 4.12 Gray Converter Plug-In Subassembly. The Gray converter plug-in subassembly shall convert the Gray coded binary information to digitally coded binary information and shall also provide the parity circuits. The Gray converter plug-in subassembly shall be designated C/GC.

3 4 1.8.4.1 4.13 Word Matrix No. 3 Plug-In Subassembly. The word matrix No. 3 plug-in subassembly shall be used in conjunction with word matrix No. 1 and No. 2 plug-in subassemblies to generate sequenced time pulses utilized to sample the command signals produced by the command function control circuits. The word matrix No. 3 plug-in subassembly shall be designated C/WM3.

3 4 1 8 4.1.4.14 Word Counter Plug-In Subassembly. The word counter plug-in subassembly shall produce the information frame frequency. The word counter plug-in subassembly shall be designated WC.

3.4.1.8 4 1.4.15 Word Matrix No. 1 Plug-In Subassembly. The function of the word matrix No. 1 plug-in subassembly shall be as specified in 3.4.1.8 4.1 4 13. The word matrix No. 1 plug-in subassembly shall be designated C/WM1.

3 4.1 8 4.1 4 16 Word Matrix No. 2 Plug-In Subassembly. The function of the word matrix No. 2 plug-in subassembly shall be as specified in 3 4.1 8 4 1.4 13. The word matrix No. 2 plug-in subassembly shall be designated C/WM2

3 4 1 8 4.2 Regulator Subassembly The detail requirements of the regulator subassembly shall be as follows

3 4 1 8 4 2 1 Function The regulator subassembly shall supply +18, +6, +3, -12, and -18-volt regulated d-c voltages to be utilized by the Coder Audio Frequency KY-431/SRM

3 4 1 8 4.2 2 Form Factor The maximum external dimensions of the regulator subassembly shall be as follows:

Height 6-3/4 inches

Width 4 inches

Depth: 8-1/2 inches

3.4.1.8.4.2.3 Weight. The maximum weight of the regulator subassembly shall not exceed 4 pounds.

Source: https://assist.dla.mil -- Downloaded: 202610-19T17:26Z
Check the source to verify that this is the current version before use.

3.4.1.8.4.2.4 Contents of Unit. The regulator subassembly shall contain the following non-repairable, printed circuit, plug-in subassembly boards:

(1) +3 and +6-Volt D-C Voltage Regulator Plug-In Subassembly Board

(2) +18-Volt D-C Voltage Regulator Plug-In Subassembly Board

(3) -12 and -18-Volt D-C Voltage Regulator Plug-In Subassembly Board

3.4.1.8.4.2.4.1 +3 and +6-Volt D-C Voltage Regulator Plug-In Subassembly Board. The +3 and +6-volt d-c voltage regulator plug-in subassembly board shall consist of transistor regulator circuits which shall provide the +3 and +6-volt regulated d-c voltages utilized by the equipment.

3.4.1.8.4.2.4.2 +18-volt D-C Voltage Regulator Plug-In Subassembly Board. The +18-volt d-c voltage regulator plug-in subassembly board shall consist of a transistorized regulator circuit which shall provide the +18-volt regulated d-c voltage utilized by the equipment.

3.4.1.8.4.2.4.3 -12 and -18-Volt D-C Voltage Regulator Plug-In Subassembly Board. The -12 and -18-volt d-c voltage regulator plug-in subassembly shall consist of transistor regulator circuits which shall provide the -12 and -18-volt regulated d-c voltages utilized by the equipment.

3.4.1.8.4.3 Main Chassis. The main chassis shall house the coder-digital subassembly and the regulator assembly. In addition, the following circuits, controls, and indicators shall be provided on the equipment main chassis.

(1) Power Supply Circuits

(2) "OR" Gate Circuits

(3) Power Switch

(4) External Control Switch

(5) Address Selector Switch

(6) Multiple Position Encoding Switches

(7) Two-position Encoding Switch

(8) Fuses and Fuseholders

(9) Indicator Lamps

Source: https://assist.dla.mil -- Downloaded: 202610-19T17:26Z
Check the source to verify that this is the currentversion before use.

3.4.1.8.4.3.1 Power Supply Circuits. The power supply circuits shall convert the primary input power to all voltages required by the Coder, Audio Frequency KY-431/SRM.

3.4.1.8.4.3.2 "OR" Gate Circuits. The "or" gate circuits shall include gating diodes which shall be utilized in conjunction with the encoding switches provided on the front panel to program the command signals to the coder-digital subassembly.

3.4.1.8.4.3.3 Power Switch. A two-position toggle switch for controlling the application of primary power shall be provided and shall be designated MAIN POWER, ON, OFF.

3.4.1.8.4.3.4 External Control Switch. A two-position toggle switch for selecting either internally generated command signals or externally supplied command signals shall be provided. The switch shall disable the internal command encoding switches and complete the circuit path for the externally applied command signals when in the external position. The switch shall be designated EXT CONTROLLER, EXT, INT.

3.4.1.8.4.3.5 Address Selector Switch. An eight-position selector switch for selecting any one of eight different security codes shall be provided. The switch shall be designated ADDRESS, A, B, C, D, E, F, G, and H.

3.4.1.8.4.3.6 Multiple Position Encoding Switches. Three 11-position selector switches for selecting coded command signals representing the desired altitude, pitch attitude, and roll attitude of the controlled rotary wing aircraft shall be provided. The switches shall be designated ALTITUDE, PITCH ATTITUDE, and ROLL ATTITUDE. A 12-position selector switch for selecting coded command signals representing the heading of the controlled rotary wing aircraft shall be provided. The switch shall be designated HEADING.

3.4.1.8.4.3.7 Two-Position Encoding Switches. Ten two-position toggle switches, including two spares, shall be provided for selecting coded command signals representing functions of the controlled rotary wing aircraft. The switch designations shall be adjacent to the switches and shall state the function each switch shall initiate.

3.4.1.8.4.3.8 Fuses and Fuseholders. Two fuses and corresponding fuseholders for protecting the equipment against electrical overloads or shorts shall be provided and shall be designated as F1 3 AMP and F2 3 AMP. Two spare fuses and corresponding fuseholders shall be provided and shall be designated SPARE. Fuseholders shall be of the blown fuse indicating type per Specification MIL-F-19207.

3.4.1.8.4.3.9 Indicator Lamps. Two indicator lamps shall be provided for displaying when primary power and external command signals are applied to the equipment. The lamps shall be designated as MAIN POWER and EXT. CONT.

Source: https://assist.dla.mil -- Downloaded: 20260-19T17:26Z
Check the source to verify that this is the current version before use.

3.4.1.8.4.3.10 Primary Input Power Requirements. The Coder, Audio Frequency KY-431/SRM, shall meet all applicable requirements of Specification MIL-T-21200 and shall give specified performance from the following power sources with characteristics as defined in Specification MIL-T-21200 having limits specified therein. The power required shall not exceed the specified amounts.

(1) AC Power (Single Phase), 60 cycle, 102 to 126 volt, 100 VA

3.4.1.8.4.3.11 Electrical Connections

3.4.1.8.4.3.11.1 Front Panel Connectors. The following external connectors shall be provided on the front panel of the equipment

Reference Designation	Receptacle Type	Function
J1	MS3102E28-21S	External Command Input Signals
J2	UG-909	External Audio Frequency Output

3.4.1.8.4.3.11.2 Rear Panel Connectors. The following connectors shall be provided on the rear panel of the equipment

Reference Designation	Receptacle Type	Function
J4	MS3102E14S-2P	Primary Input Power
J5	UG-492	Audio Frequency Output

3.4.1.8.4.4 Control, Coder C-4123/SRM. The Control, Coder C-4123/SRM, shall meet the following requirements.

3.4.1.8.4.4.1 Function. The Control, Coder C-4123/SRM, shall provide the facilities to remotely operate the Coder, Audio Frequency, KY-431/SRM.

3.4.1.8.4.4.2 Form Factor. The maximum external dimensions of the Control, Coder C-4123/SRM, including the transit case, shall not exceed the following:

Height: 8-1/2 inches

Width: 8-1/2 inches

Depth: 10-3/4 inches

3.4.1.8.4.4.3 Weight. The weight of the Control, Coder C-4123/SRM, including the transit case, shall not exceed ten pounds.

Source: https://assist.dla.mil -- Downloaded: 20260-19T17:26Z
Check the source to verify that this is the current version before use.

3 4 1 8.4.4 4 Contents of Unit. The Control, Coder C-4123/SRM, shall include the following components.

(1) Transit Case

(2) Interconnecting Cable

(3) Main Chassis

3 4 1.8 4 4 4.1 Transit Case. The transit case shall house the Control, Coder C-4123/SRM, and interconnecting cable during storage and transit.

3 4 1 8.4.4 4.2 Interconnecting Cable. The interconnecting cable shall connect the Control, Coder C-4123/SRM, either to Interconnecting Box J-1038/SRW or Interconnecting Box J-1039/SRW-4. The interconnecting cable shall have a maximum length of 3 feet and shall be equipped with the following electrical connector types

(1) MS3106C-28-21S

(2) MS3101E-28-21P

3 4 1 8 4 4 4.3 Main Chassis. The main chassis shall house the interconnecting wiring for the switches and the indicator provided on the main chassis. The following controls and indicators shall be mounted on the main chassis front panel.

(1) Heading Command Encoding Switch

(2) Pitch Command Encoding Switch

(3) Roll Command Encoding Switch

(4) Altitude Command Encoding Switch

(5) Command Select Encoding Switch

(6) Memory-Station Encoding Switch

(7) Indicator Lamps

3 4 1.8 4.4 4.3.1 Heading Command Encoding Switch. A nine-position selector switch for encoding rotary wing drone aircraft heading control signals shall be provided and shall be designated HEADING.

3.4.1 8 4.4.4.3.2 Pitch Command Encoding Switches. A nine-position selector switch for encoding rotary wing drone aircraft pitch control signals shall be provided and shall be designated PITCH.

Source: https://assist.dla.mil -- Downloaded: 202610-19T17:26Z
Check the source to verify that this is the current version before use.

3.4.1.8.4.4.4.3 3 Roll Command Encoding Switch. A nine-position selector switch for encoding rotary wing drone aircraft roll control signals shall be provided and shall be designated ROLL.

3.4.1.8.4.4.4.3.4 Altitude Command Encoding Switch. An eleven-position selector switch for encoding rotary wing drone aircraft altitude control signals shall be provided and shall be designated ALTITUDE

3.4.1 8.4 4 4 3.5 Command Select Encoding Switch An eight-position selector switch for encoding commands to initiate any one of eight functions of a rotary wing drone aircraft shall be provided and shall be designated COMMAND

3 4.1 8 4 4 4.3 6 Memory-Station Encoding Switch A two-position toggle switch for encoding either a station command or a memory command for rotary wing drone aircraft shall be provided and shall be designated MEMORY, STATION.

3.4.1.8.4 4 4 3.7 Indicator Lamps Indicator lamps to monitor the application of 115-volt 60-cycle and 28-volt d-c power shall be provided and shall be designated 115V AC and 28V DC

3 4.1.8.4 4 5 Electrical Connections The following external connector shall be provided on the front panel of the equipment

Reference Designation	Receptacle Type	Function
J1	MS3102E-28-21P	Command Signals Output

3 4 1 9 Amplifier-Frequency Multiplier AM-3311/SRM The Amplifier-Frequency Multiplier AM-3311/SRM shall meet the following detail requirements

3 4 1.9 1 Function The Amplifier-Frequency Multiplier AM-3311/SRM shall provide facilities for generating radio-frequency signals over the range of 406 to 549 5 megacycles at a variable calibrated power output from 1 0 to 100 000 microvolts Capabilities shall be provided for frequency modulating these signals to a deviation up to ±300 kilocycles when supplied with signals in the range of 300 to 100. 000 cycles per second It shall be from an external source.

3 4.1 9.2 Form Factor The maximum external dimensions of the Amplifier-Frequency Multiplier AM-3311/SRM. shall be as follows

Height 12-1/4 inches
Width 19 inches
Depth. 23 inches

3.4.1.9.3 Weight. The weight of the Amplifier-Frequency Multiplier AM-3311/SRM shall not exceed 90 pounds.

Source: https://assist.dla.mil -- Downloaded: 202610-19T17:26Z
Check the source to verify that this is the current version before use.

3 4 1.9 4 Contents of Unit. The Amplifier-Frequency Multiplier AM-3311/SRM shall contain the following circuit sections.

(1) Oscillator

(2) RF Multipliers and Amplifiers

(3) Modulating Amplifiers

(4) Meter Amplifiers

(5) Output Attenuator

(6) Deviation Meter

(7) Output Level Meter

(8) Frequency Counter

(9) Frequency Readout Presentation

3 4 1 9 5 Controls The following controls shall be provided

(1) Frequency Tuning

(2) Power On-Off

(3) Plate Supply On-Off

(4) Attenuator

(5) Deviation Adjust

(6) Audio Function

(7) Deviation Range

(8) Attenuator Calibrate

(9) Output and Filter Tuning

3 4 1 9 6 Indicators The following indicators shall be provided

(1) Power On Lamp

(2) Plate Power On Lamp

(3) Crystal Oven On Lamp

Source: https://assist.dla.mil -- Downloaded: 202640-19T17:26Z
Check the source to verify that this is the current version before use.

(4) Oscillator Oven On Lamp (Signal Generator)

(5) Deviation Meter

(6) RF Meter

(7) Megacycle Hundreds Indicator

(8) Megacycle Tens Indicator

(8) Megacycle Units Indicator

(10) Kilocycle Hundreds Indicator

(11) Kilocycle Tens Indicator

3 4 1 9 7 Electrical Connections The following electrical connections shall be provided

(1) Power In

(2) RF Out

(3) Modulation In

3.4 1 10 Power Supply PP-3373/SRM The Power Supply PP-3373/SRM shall meet the following detail requirements

3 4 1 10 1 Function The Power Supply PP-3373/SRM shall provide all of the electrical power required for operation of the Amplifier-Frequency Multiplier AM-3311/SRM

3 4.1.10.2 Form Factor The maximum external dimensions of the Power Supply PP-3373/SRM shall be as follows

Height: 12-1/4 inches
Width 19 inches
Depth: 23 inches

3 4 1.10.3 Weight The weight of the Power Supply PP-3373/SRM shall not exceed 110 pounds.

3 4 1 10 4 Contents of Unit The Power Supply PP-3373/SRM shall contain the following circuit sections

(1) Basic Plate Power Supply

(2) 472-Volt Regulated Supply

Source: https://assist.dla.mil -- Downloaded: 202610-19T17:26Z
Check the source to verify that this is the current version before use.

(3) 300-Volt Regulated Supply

(4) 250-Volt Regulated Supply

(5) 200-Volt Regulated Supply

(6) 150-Volt Regulated Supply

(7) 100-Volt Unregulated Supply

(8) -20-Volt Regulated Supply

(9) -6.2-Volt Regulated Supply

(10) Filament Supply

(11) 180-Volt, 45 Milliampere Supply

(12) 28-Volt AC, 1 1 Ampere Supply

(13) Overload Protection Circuits

3 4 1 10 5 Controls No controls are included in the Power Supply PP-3373/SRM All controls are provided on the front panel of the Amplifier, Frequency Multiplier AM-3311/SRM.

3.4 1.10 6 Indicators The following indicators shall be provided·

(1) Master 115-Volt A-C Power Supply Overload Indicator

(2) Plate Supply Overload Indicator

3 4 1 10 7 Primary Input Power Requirements The Power Supply PP-3373/SRM shall meet all applicable requirements of Specification MIL-T-21200 and shall give specified performance from the following power sources with characteristics as defined in Specification MIL-T-21200 having limits specified therein The power required shall not exceed the specified amounts

(1) AC Power (Single Phase), 60 cycle 102 to 126 volt, 650 V A

3 4 1 10 8 Electrical Connections The following electrical connections shall be provided

(1) AC Power In

(2) Power Out

(3) External Power Out

Source: https://assist.dla.mil -- Downloaded: 202610-19T17:26Z
Check the source to verify that this is the current version before use.

3.4 1.10 9 Fuses and Fuseholders. Two fuses and fuseholders for protecting the equipment against electrical overloads or shorts shall be provided. Two spare fuses and fuseholders shall be provided The main-power fuse shall be of 8-ampere capacity and the high-voltage fuse shall be of 3/4-ampere capacity. Fuse-holders shall be of the blown fuse indicating type as specified in Specification MIL-F-19207

3 4 1 11 Tool Kit, Target Control System TK-142/SRM-2 The Tool Kit, Target Control System TK-142/SRM-2, shall meet the following detail requirements

3 4 1.11 1 Function The tools which comprise the Tool Kit, Target Control System TK-142/SRM-2, shall be retained in the tray, tool mounting, of the Test Stand, Electronic Equipment MT-2732/SRM-2, and shall perform the following functions

3.4.1.11.1 1 Adjusting Tool, Lead Screw An adjusting tool, lead screw, shall be utilized for adjusting the lead screw of the AM-2643/UR cavity The adjusting tool lead screw shall be manufactured from a steel bar conforming with Specification MIL-S-6758 and shall have a cadmium plated finish in conformance with Specification QQ-P-416

3 4 1 11 1 2 Alignment Tool, Washer An alignment tool, washer, shall be utilized for positioning the washer on the probe screw of the AM-2643/UR cavity. The alignment tool washer shall be manufactured from materials conforming with Specification QQ-P-330 and shall have a cadmium plated finish in conformance with Specification QQ-P-416.

3 4.1 11 1 3 Bolt, Eye A bolt, eye, shall be utilized for attaching units of the Target Control System AN/SRW-4 and all revisions thereof to the Beam, Hoisting, Electronic Equipment MX-4124/SRM-2 The bolt eye, shall be manufactured from carbon steel with a safe workload of 0.2 tons and shall have a cadmium plated finish in conformance with Specification QQ-P-416.

3 4.1 11 1 4 Extractor, Tuned Cavity An extractor, tuned cavity, shall be utilized for extracting the inner support assembly tube from the AM-2643/UR cavity The extractor, tuned cavity, shall be manufactured from aluminum alloy and stainless steel and shall have an anodized and passivated finish, respectively.

3.4 1 11 1.5 Gage, Gear Mounting A gage, gear mounting, shall be utilized for positioning the ring gear of the AM-2643/UR cavity The gage, gear mounting, shall be of cadmium plated finish in accordance with Specification QQ-P-416.

3.4.1 11 1 6 Gage Tube Socket A gage tube socket, shall be utilized for positioning the fingers that form the tube sockets of the AM-2643/UR cavity. The gage, tube socket, shall be manufactured from aluminum plate and shall have an alodined finish.

Source: https://assist.dla.mil -- Downloaded: 202640-19T17:26Z
Check the source to verify that this is the currentversion before use.

3.4.1.11.1.7 Jig, Cavity. A jig, cavity, shall be utilized for holding and aligning the AM-2538/URW-14A and the AM-2147/URW-14 cavities during assembly. The jig, cavity, shall be manufactured from aluminum plate conforming with Specification QQ-A-325 and shall have an alodined finish.

3.4.1.11.1.8 Jig, Positioning Ring. A jig, positioning ring, shall be utilized for positioning the epoxy ring on the support assembly of the AM-2643/UR cavity. The jig, positioning ring, shall be manufactured from aluminum tubing conforming with Specification QQ-A-270 and shall have anodized finish in conformance with Specification MIL-A-8625.

3.4.1.11.1.9 Jig, R-F Probe. A jig, r-f probe, shall be utilized for positioning the output coupling adapter support of the AM-2643/UR cavity. The jig, r-f probe, shall be manufactured from aluminum alloy and shall have an alodined finish.

3.4.1.11.1.10 Pilot, Gasket and Cavity. A pilot, gasket and cavity, shall be utilized for aligning the mylar gaskets of the AM-2643/UR grid cavity. The pilot, gasket and cavity, shall be manufactured from a brass rod conforming with Specification QQ-B-626 and shall have a cadmium plated finish conforming with Specification QQ-P-416.

3.4.1.11.1.11 Ring, Aligning, Cavity. A ring, aligning, cavity, shall be utilized for supporting and protecting the AM-2643/UR cavity during assembly. The ring, aligning cavity, shall be manufactured from aluminum tubing conforming with Specification QQ-A-270 and shall have a cadmium plated finish in conformance with Specification QQ-P-416.

3.4.1.11.1.12 Screwdriver Assembly. A screwdriver assembly shall be utilized for removing and tightening coined slot captive screws. The screwdriver assembly shall have a chrome plated finish conforming with Specification QQ-C-32

3.4.1.11.1.13 Screwdriver, Special Purpose Adapter. A screwdriver, special purpose adapter, shall be utilized for holding the r-f probe while inserting it into the AM-2643/UR cavity and for tightening the r-f probe. The screwdriver shall be manufactured from a steel rod conforming with Specification MIL-S-6758 and shall have a cadmium plated finish in conformance with Specification QQ-P-416. The screwdriver handle and extension shall be manufactured from aluminum conforming with Specification QQ-A-325 and shall have an anodized finish in conformance with Specification MIL-A-8625.

3.4.1.11.1.14 Screw Jack Assembly. A screw jack assembly shall be utilized for positioning equipment in the cabinet to align rack mounting screws. The screw jack assembly shall be manufactured from steel and shall have a cadmium plated finish conforming with Specification QQ-P-416.

3.4.1.11.1.15 Template, Cavity Pick-up Loop. A template, cavity pick-up loop, shall be utilized for positioning the pick-up loop on the AM-2538/URW-14A and

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:26Z
Check the source to verify that this is the current version before use.

the AM-2147/URW-14 cavities. The template, cavity pick-up loop, shall be manufactured from aluminum alloy conforming with Specification QQ-A-318 and shall have an alodined finish

3.4.1.11.1.16 Wrench, Bushing. A wrench, bushing, shall be utilized for adjusting the eccentric bushing on the AM-2643/UR cavities. The wrench, bushing, shall be manufactured from a steel sheet and shall have a cadmium plated finish in conformance with Specification QQ-P-416.

3.4.1.11.1.17 Wrench, Hose Clamp. A wrench, hose clamp, shall be utilized for tightening hose clamps on the AM-2643/UR cavity. The wrench, hose clamp, shall have a cadmium plated finish conforming with Specification QQ-P-416

3.4.1.11.2 Identification. The tools which comprise the Tool Kit, Target Control System TK-142/SRM, shall be identified by the manufacturer's part number.

3.4.1.11.3 Interchangeability. All tools having the same manufacturer's part number shall be directly and completely interchangeable with each other with respect to installation and performance

3.4.1.12 Truck, Electronic Equipment V-244/SRM-2. The Truck, Electronic Equipment V-244, SRM-2, shall meet the following detail requirements

3.4.1.12.1 Function. The Truck, Electronic Equipment V-244/SRM-2, shall provide facilities for supporting and transporting specific components, except rotary wing components, comprising the Target Control System AN/SRW-4 and all revisions thereof. The Truck, Electronic Equipment V-244/SRM-2, shall utilize three pairs of interchangeable arms to support the subject units during transporting and testing. The supporting racks of the Truck, Electronic Equipment V-244/SRM-2, shall provide 360-degree rotation while supporting any of the subject units

3.4.1.12.2 Form Factor. The maximum external dimensions of the Truck, Electronic Equipment V-244/SRM shall be as follows

Height	36 inches
Width	24-1/8 inches
Depth	70-1/8 inches

3.4.1.12.3 Weight. The weight of the Truck, Electronic Equipment V-244/SRM, shall not exceed 355 pounds

3.4.1.12.4 Safe Load Capacity. The Truck, Electronic Equipment V-244/SRM, shall have a safe load capacity of 650 pounds.

3.4.1.12.5 Contents of Unit. The Truck, Electronic Equipment V-244/SRM, shall consist of a frame, equipment supports, and a folding tongue handle.

Source: https://assist.dla.mil -- Downloaded: 202610-19T17:26Z
Check the source to verify that this is the current version before use.

3 4 1 12 5 1 Frame The frame shall be constructed of welded steel angles with floor stops and casters The frame shall be welded in accordance with Specification MIL-W-6858 The frame shall provide for attachment of the equipment supports and the folding tongue handle

3 4 1 12 5.1 1 Casters The casters shall have wheels with locking provisions to facilitate steering and shall conform with Specification MS-24380

3 4 1 12 5 2 Equipment Support The equipment support which shall be attache to the frame by four stainless steel pins, shall consist of two steel A-frames each having a 6-inch diameter swivel plate to which three pairs of interchangeable arms shall attach

3 4 1 12 5 2 1 A-frames The A-frames shall be constructed of steel and welde in conformance with Specification MIL-W-6858 The A-frame trunnion shall be attached to the frame by four stainless steel pins ground in conformance with Specification MIL-S-7720 condition A The 6-inch hameter swivel plates of the A-frames shall provide attachment of any one of the three pairs of interchangeabl arms

3 4 1 12 5 2 2 Interchangeable Arms Three pairs of interchangeable arms sha be provided to support units of the Target Control System AN/SRW-4 and all revisions thereof The pair of arms utilized shall be held in working position by grip pins and storage for the arms not in use shall be provided on the frame

3 4 1 12 5 3 Folding Tongue Handle. The folding tongue handle shall be of A-frame steel construction and shall be welded in conformance with Specification MIL-W-6858. The handle trunnion shall be attached by two pins to the frame.

3 4 1 12 6 Mobility The Truck Electronic Equipment V-244/SRM, shall be mounted on four casters for mobility and shall be rendered immobile by floor stops A lock in each caster shall fix the direction of travel if so desired

3 4 1 12 7 Lubrication Adequate means shall be provided for lubrication of the casters Arrangements for lubrication shall be such as to require infrequent attention

3 4 1 12 8 Interchangeability. All parts having the same manufacturer's part number shall be directly and completely interchangeable with each other with respect to installation and performance

3 4 1 12 9 Paint The color of the truck shall be gray and shall conform with Specification MIL-E-15090 The 6-inch diameter swivel plates shall be cadmium plated in conformance with Specification QQ-P-416

3.4 1.13 Hoisting Unit, Portable, Electronic Equipment E-42/SRM-2. The Hoisting Unit, Electronic Equipment E-42/SRM-2, shall meet the following detail requirements

Source: https://assist.dla.mil -- Downloaded: 20260-19T17:26Z
Check the source to verify that this is the current version before use.

3.4.1.13.1 Function. The Hoisting Unit, Portable, Electronic Equipment E-42/SRM-2, when used in conjunction with the Beam, Hoisting Electronic Equipment MX-4124/SRM-2, shall provide facilities for lifting components comprising the Target Control System AN/SRW-4 and all revisions thereof from their individual cases.

3.4.1.13.2 Form Factor. The maximum external dimensions of the Hoisting Unit, Portable, Electronic Equipment E-42/SRM-2, shall be as follows:

Height	74 inches
Width	51 inches
Depth	42 inches

3.4.1.13.3 Weight. The weight of the Hoisting Unit, Portable, Electronic Equipment E-42/SRM-2, shall not exceed 260 pounds.

3.4.1.13.4 Safe Load Capacity. The Hoisting Unit, Portable, Electronic Equipment E-42/SRM-2, shall have a safe load capacity of 650 pounds.

3.4.1.13.5 Contents of Unit. The Hoisting Unit, Portable, Electronic Equipment E-42/SRM-2, shall consist of a hoist and a tripod.

3.4.1.13.5.1 Hoist. The hoist shall be lever operated with a wire rope load line and shall be attached to a tripod for accessibility.

3.4.1.13.5.1.1 Lowering. The Hoisting Unit, Portable, Electronic Equipment E-42/SRM-2, shall include an efficient device to prevent a suspended load from self-lowering. Lowering shall be possible only by continuous manual operation of the lever.

3.4.1.13.5.1.2 Wire Rope. The wire rope for the Hoisting Unit, Portable, Electronic Equipment E-42/SRM, shall be constructed of stainless steel. One end of the wire rope shall be attached to the wire rope drum in a manner which will permit ready removal for replacement purposes.

3.4.1.13.5.1.3 Wire Rope Drum. The wire rope drum for the Hoisting Unit, Portable, Electronic Equipment E-42/SRM-2, shall be of suitable size and reeling capacity for the intended service and shall prevent the cable from fouling the ratchet teeth or jumping the drum when an off-center pull is applied to the wire rope.

3.4.1.13.5.1.4 Lever. The lever shall be removable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:26Z
Check the source to verify that this is the current version before use.

3 4.1.13.5.2 Tripod. The tripod shall be adjustable in height and shall be mounted on wheels. The tripod shall be constructed of the following extra strong steel tubing which shall conform with Federal Specification QQ-S-00643 for Hot Roll 1020, steel plates which shall conform with Federal Specification QQ-S-635 for Hot Roll 1020, steel bars which shall conform with Federal Specification QQ-S-633 for Hot Roll 1020 Welding shall conform with Specification MIL-W-6858

3 4 1 13 5 2 1 Adjustability. The tripod shall be adjustable from 74 inches to 3 inches in height

3 4 1 13.5.2.2 Mobility The tripod shall be mounted on three wheels for mobility and shall be rendered immobile by two floor stops

3 4 1 13 5 2 3 Hoist Suspension The hoist shall be attached to one leg of the tripod and a load pulley shall be suspended from the apex of the tripod by the load line. The load line, which shall suspend the load pulley, shall be attached to the apex of the tripod and shall connect to the hoist through a pulley also attached to the apex of the tripod The load pulley shall provide a means of connecting to the Beam, Hoisting, Electronic Equipment MX-4124/SRM-2

3 4 1 13 5 2 4 Lubrication Adequate means shall be provided for lubrication of the casters Arrangements for lubrication shall be such as to require infrequent attention

3 4 1 13 6 Interchangeability. All parts having the same manufacturer's part number shall be directly and completely interchangeable with respect to installation and performance

3 4 1 13 7 Paint and Finish

3 4 1 13 7 1 Hoist The hoist shall be anodized

3 4 1 13 7.2 Tripod. The color of the tripod shall be light gray and shall conform with Specification MIL-E-15090

3 4 1 14 Beam, Hoisting, Electronic Equipment MX-4124/SRM-2 The Beam, Hoisting, Electronic Equipment MX-4124/SRM-2, shall meet the following detail requirements

3.4.1.14.1 Function. The Beam, Hoisting, Electronic Equipment MX-4124/SRM-2, when used in conjunction with the Hoisting Unit, Portable

Source: https://assist.dla.mil -- Downloaded: 202640-19T17:26Z
Check the source to verify that this is the current version before use.

Electronic Equipment E-42/SRM-2, shall provide facilities for lifting the individual components comprising the Target Control System AN/SRW-4 and all revisions thereof from their individual cases.

3 4.1.14.2 Form Factor The maximum external dimensions of the Beam, Hoisting, Electronic Equipment MX-4124/SRM-2, shall be as follows:

Height	2-7/8 inches
Width	21-7/8 inches
Depth	28-3/4 inches

3.4 1.14.3 Weight The weight of the Beam, Hoisting, Electronic Equipment MX-4124/SRM-2, shall not exceed 30 pounds

3 4.1.14 4 Safe Load Capacity The Beam, Hoisting, Electronic Equipment MX-4124/SRM-2, shall have a safe load capacity of 650 pounds

3.4 1.14 5 Contents of Units The Beam, Hoisting, Electronic Equipment MX-4124/SRM-2, shall consist of a rectangular-shaped steel beam with shackles for attaching a component of Target Control System AN/SRW-4, or any revision thereof and a means for attachment to the Hoisting Unit Portable Electronic Equipment E-42/SRM-2

3 4 1 14 5 1 Beam. The beam shall be constructed of steel which shall conform to the requirements of Specification MIL-S-6758 and shall be welded in conformance with Specification MIL-W-6858

3 4 1 14 6 Interchangeability All parts having the same manufacturer's part number shall be directly and completely interchangeable with each other with respect to installation and performance

3.4.1.14 7 Finish The Beam, Hoisting, Electronic Equipment MX-4124/SRM-2, shall be painted in conformance with Specification MIL-E-15090, Formula No. 111

Source: https://assist.dla.mil -- Downloaded: 202640-19T17:26Z
Check the source to verify that this is the current version before use.

3.4.2 Test Set, Target Control System AN/SRM-3. Detail requirements of the Test Set, Target Control System AN/SRM-3, shall be as follows:

3.4.2.1 Cabinet, Electrical Equipment CY-3584/SRM-3. The Cabinet, Electrical Equipment CY-3584 SRM-3, shall meet the following detail requirements

3.4.2.1.1 Function The Cabinet, Electrical Equipment CY-3584/SRM-3, shall provide facilities for supporting on extending drawer slides the Receiver, Radio R-1135/SRM, the Decoder, Audio Frequency KY-433/SRM, and the Decoder, Audio Frequency KY-432/SRM-3 The Cabinet, Electrical Equipment CY-3584/SRM-3, shall provide electrical interconnection facilities for the equipments contained therein and a blower assembly capable of providing sufficient air for cooling the contained equipments.

3.4.2.1.2 Form Factor The maximum external dimensions of the Cabinet Electrical Equipment CY-3584/SRM-3, shall be as follows:

Height 54-1/4 inches

Width 24-1/2 inches

Depth 28 inches

3.4.2.1.3 Weight. The weight of the Cabinet, Electrical Equipment CY-3584/SRM-3, shall not exceed 340 pounds.

3.4.2.1.4 Contents of Unit. The Cabinet, Electrical Equipment CY-3584/SRM-3, shall contain a blower assembly

3.4.2.1.4.1 Blower Assembly The detail requirements of the blower assembly shall be as follows

3.4.2.1.4.1.1 Function The blower assembly shall provide air circulation capable of cooling, under normal operating conditions, all electronic equipment contained in the Cabinet, Electrical Equipment CY-3584/SRM-3.

3.4.2.1.4.1.2 Form Factor. The maximum external dimensions of the blower assembly shall be as follows

Height 8-3/4 inches

Width 19 inches

Length: 22 inches

3.4.2.1.4.1.3 Weight. The weight of the blower assembly shall not exceed 50 pounds.

3.4.2.1.4.1.4 Contents of Unit. The blower assembly shall contain a squirrel cage type electric blower which shall utilize approximately 110-volt-amperes of 115-volt single-phase power and shall be capable of delivering 750 cubic feet of

Source: https://assist.dla.mil -- Downloaded: 202640-19T17:26Z
Check the source to verify that this is the current version before use.

air per minute under normal conditions. The blower assembly shall also contain an aluminum wire mesh type filter which shall be capable of filtering the circulated air.

3.4.2.1.5 Electrical Connections. Connections to external circuits shall be provided on the rear of the equipment as follows

Reference Designation	Receptacle Type	Function
J1	MS3102E16-10P	External Input Power

3.4.2.2 Receiver, Radio R-1135/SRM.

3.4.2.2.1 Function. The Receiver, Radio R-1135/SRM, shall serve to monitor UHF frequency-modulated radio-control signals transmitted from a transmitter providing an input amplitude of at least 5 microvolts. The Receiver, Radio R-1135/SRM, shall provide indications of input carrier level, input signal frequency differential with reference to the selected operating frequency, input carrier deviation, and whether or not a carrier is being received. An audio output receptacle shall be provided for connection to external audio decoding and monitoring equipments. The equipment shall be designed for mounting in a standard 19-inch equipment cabinet in order that it may be utilized as an integral component of a test set consisting of two or more separate equipments.

3.4.2.2.2 Form Factor. The maximum external dimensions of the Receiver, Radio R-1135/SRM, shall be as follows

Height: 12-1/4 inches

Width 19 inches

Depth 23 inches

3.4.2.2.3 Weight. The weight of the Receiver, Radio R-1135/SRM, shall not exceed 80 pounds.

3.4.2.2.4 Contents of Unit The Receiver, Radio R-1135/SRM, shall be of subassembly construction. The following subassemblies shall be provided

(1) Frequency Selection Assembly

(2) I-F Strip

(3) Power Supply

3.4.2.2.4.1 Frequency Selection Assembly. The frequency selection assembly shall include the frequency selection subpanel, crystal oven sockets, crystal-selector switch, crystal oscillator and multipliers, radio-frequency preselector, mixer, 50-db attenuator and relay, and noise generator.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:26Z
Check the source to verify that this is the current version before use.

3.4.2.2.4.1.1 Frequency Selection Subpanel. The frequency selection subpanel shall contain three crystal oven sockets, a crystal selector switch, an oscillator tuning control, a mixer tuning control and an r-f tuning control. All controls, switches, and crystal oven sockets shall be accessible from the front of the subpanel.

3.4.2.2.4.1.2 Crystal Oven Sockets. Three crystal oven sockets shall be provided as part of the frequency selection subpanel. Each of these sockets shall provide for retaining a dual crystal oven.

3.4.2.2.4.1.3 Crystal Selector Switch. The crystal selector switch shall provide a means of selecting any one of the installed crystals.

3.4.2.2.4.1.4 Crystal Oscillator and Multipliers. The output of the crystal oscillator shall be frequency multiplied to a frequency such that it can be properly mixed with the received signal to generate the correct intermediate frequency. The last frequency multiplier stage shall utilize a crystal diode in a non-linear harmonic generator circuit whose output tank (harmonic selector) shall be a tuned-line cavity. The frequency multiplied output signal from the crystal oscillator shall be frequency stabilized to within ±0.005 percent under all specified service conditions.

3.4.2.2.4.1.5 Radio-Frequency Preselector. The radio-frequency preselector shall consist of two tuned-line cavities connected in cascade. The second tuned-line cavity output link shall be commonly connected to the mixer and i-f input circuits of the equipment.

3.4.2.2.4.1.6 Mixer. The mixer shall utilize a crystal diode to mix incoming signals with the local oscillator signal in such a manner as to produce a difference frequency suitable for utilization as the intermediate frequency signal of the equipment. This mixed i-f signal shall be applied to the i-f amplifier of the equipment through the output link of the second tuned-line cavity of the mixer section.

3.4.2.2.4.1.7 50-db Attenuator and Relay. The frequency selector assembly shall incorporate a 50-db attenuator which shall be switched in and out of the radio-frequency circuit of the equipment by an associated relay.

3.4.2.2.4.1.8 Noise Generator. The equipment shall contain a noise generator circuit capable of providing sufficient signal level that the equipment may be tuned in the absence of a received carrier.

3.4.2.2.4.2 I-F Strip. The i-f strip shall contain an i-f amplifier, limiters, and an f-m discriminator.

3.4.2.2.4.2.1 I-F Amplifiers and Limiters. The i-f amplifiers and limiters shall provide necessary amplification and shall have passband characteristics capable of satisfying the sensitivity and selectivity requirements as specified in 3.3.2.2.3 and 3.3.2.2.4. The limiter stages shall serve to minimize adverse effects of amplitude modulated interferences.

Source: https://assist.dla.mil -- Downloaded: 20260-19T17:26Z
Check the source to verify that this is the current version before use.

3.4.2.2.4.3 Power Supply. The power supply shall include an audio amplifier section, a power supply section, a front panel, and a main chassis.

3.4.2.2.4.3.1 Audio Amplifier Section. The audio amplifier section shall contain four separate cathode follower type audio amplifier circuits. Two of these cathode follower circuits shall provide rear panel audio output connections each having a nominal output impedance of 500 ohms. Each of these two cathode follower circuits shall be driven directly by audio output signals produced by the f-m discriminator section within the i-f strip. An amplifier circuit shall serve to drive an audio output cathode follower stage which shall provide a front panel audio output connection having an output impedance of 50 ohms, nominal, as well as to drive deviation metering circuitry of the equipment. Input signals for the driver circuit shall be audio signals produced by the f-m discriminator section of the i-f strip.

3.4.2.2.4.3.2 Power Supply Section The power supply section shall provide all operating voltages required by the equipment. This power supply shall utilize a primary input power of 115 volts ac 60 cycles, nominal, and shall transform, rectify, filter, and regulate this power as necessary

3.4 2.2 4.3.3 Front Panel The front panel shall contain all switches, meters, indicator lamps, fuses, and external connectors of the equipment A front panel access cover shall provide access to the frequency selection subpanel of the frequency selection assembly.

3.4.2.2.4.3.3.1 Switches. Front panel switches of the equipment shall include a main power on-off switch, a standby-receive switch, a momentary contact noise generator on switch, a rotary type meter selector switch, a 0 to 59-db attenuator selector switch and a 50-db attenuator in-out switch A six-position rotary type crystal selector switch shall be accessible under the front panel access cover of the equipment. An oscillator tuning control, a mixer tuning control and an r-f tuning control shall also be accessible under the front panel access cover of the equipment.

3.4.2.2.4.3.3.2 Meters. Meters located on the front panel of the equipment shall include a deviation meter, a frequency differential meter, an r-f level meter and a multi-function tune-up meter.

3.4.2.2 4.3 3.3 Indicator Lamps. Front panel indicator lamps shall include a main power on indicator lamp, a receive indicator lamp, a noise generator on indicator lamp, a carrier on indicator lamp and a carrier off indicator lamp.

3.4.2.2.4.3.3.4 Fuses and Fuseholders. The front panel shall incorporate four fuseholders. These fuseholders shall contain a 3-ampere main-power fuse, a 2-ampere high-voltage fuse, and one spare for each of these fuses. Fuseholders shall be of the blown fuse indicating type as specified in Specification MIL-F-19207.

3.4.2.2.4.3.3.5 Connectors. The front panel of the equipment shall contain two connectors, one providing connection for the r-f input signal and the other providing a 50-ohm audio output connection. Three rear panel connectors shall

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:26Z
Check the source to verify that this is the current version before use.

also be incorporated, one providing for input power connection and the other two providing separate 500-ohm audio output connections.

3.4.2.2.4.3.4 Main Chassis. The main chassis shall provide necessary wiring for the interconnection of all assemblies of the equipment together with three rear receptacles for connection to external input power, audio decoding, and monitoring equipment. The main chassis shall incorporate necessary facilities for installation of the equipment into matching drawer type sliding supports.

3.4.2.2.5 Primary Input Power Requirements. The Receiver, Radio R-1135/SRM shall meet all applicable requirements of Specification MIL-T-21200 and shall give specified performance from the following power sources with characteristics as defined in Specification MIL-T-21200 having limits specified therein. The power required shall not exceed the specified amounts.

(1) AC Power (Single Phase), 60 cycle, 102 to 126 volt, 250 VA.

3.4.2.2.6 Electrical Connections. Connections to external circuits shall be provided as follows

Reference Designation	Receptacle Type	Function	Location
J1	UG-909/U	R-F Input	Front Panel
J2	UG-909/U	Audio Output	Front Panel
J3	MS3102E14S-2P	Input Power	Rear Panel
J4	UG-909/U	Audio Output	Rear Panel
J5	UG-909/U	Audio Output	Rear Panel

3.4.2.3 Case Crystal-Oven CY-2923/U. The Case, Crystal-Oven CY-2923/U, shall meet the following detail requirements

3.4.2.3.1 Function. The Case, Crystal-Oven CY-2923/U, shall contain the necessary crystals together with three crystal ovens to provide operation of the Receiver, Radio R-1135/SRM, on the half megacycle points in one megacycle increments from 406.5 to 549.5 megacycles.

3.4.2.3.2 Form Factor The maximum external dimensions of the Case, Crystal-Oven CY-2923/U, shall be as follows

Height: 3 inches

Width: 9-1/2 inches

Depth: 10-3/8 inches

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:26Z
Check the source to verify that this is the current version before use.

3.4.2.3.3 Weight. The weight of the Case, Crystal-Oven CY-2923/U, shall not exceed five pounds.

3.4.2.3.4 Construction. The Case, Crystal-Oven CY-2923/U, shall be of aluminum construction. It shall protect the contained crystals and ovens under all service conditions specified in Specification MIL-T-21200 for Class 3 equipment.

3.4.2.3.5 Contents of Unit. The Case, Crystal-Oven CY-2923/U, shall contain all crystals necessary to cover the half megacycle points in one megacycle increments over the radio-frequency range specified herein The case shall also contain three dual crystal ovens.

3.4.2.4 Case, Crystal-Oven CY-2924/U. The Case, Crystal-Oven CY-2924/U, shall meet the following detail requirements:

3.4.2.4.1 Function. The Case, Crystal-Oven CY-2924/U, shall contain the necessary crystals together with three crystal ovens to provide operation of the Receiver, Radio R-1135/SRM, on the integral whole-megacycle increments from 406 to 549 megacycles, inclusive.

3.4.2.4.2 Form Factor. The maximum external dimensions of the Case, Crystal-Oven CY-2924/U, shall be as follows:

Height: 3 inches
Width: 9-1/2 inches
Depth: 10-3/8 inches

3.4.2.4.3 Weight The weight of the Case, Crystal-Oven CY-2924/U, shall not exceed five pounds.

3.4.2.4.4 Construction. The Case, Crystal-Oven CY-2924/U, shall be of aluminum construction. It shall protect the contained crystals and ovens under all service conditions as specified in Specification MIL-T-21200 for Class 3 equipment.

3.4.2.4.5 Contents of Unit. The Case, Crystal-Oven CY-2924/U, shall contain all crystals necessary to cover the integral whole-megacycle increments over the radio-frequency range specified herein The case shall also contain three dual crystal ovens.

3.4.2.5 Case, Crystal-Oven CY-3690/SRM. The Case, Crystal-Oven CY-3690/SRM, shall meet the following detail requirements:

3.4.2.5.1 Function. The Case, Crystal-Oven CY-3690/SRM, shall contain the necessary crystals together with six crystal ovens to provide operation of the Receiver, Radio R-1135/SRM on the classified "DASH" control frequencies.

3.4.2.5.2 Form Factor. The maximum external dimensions of the Case, Crystal-Oven CY-3690/SRM, shall be as follows:

Source: https://assist.dla.mil -- Downloaded: 202640-19T17:26Z
Check the source to verify that this is the currentversion before use.

Height: 3 inches
Width: 9-3/4 inches
Depth: 10-1/2 inches

3.4.2.5 3 Weight. The weight of the Case, Crystal-Oven CY-3690/SRM, shall not exceed five pounds.

3 4.2.5.4 Construction The Case, Crystal-Oven CY-3690/SRM, shall be of aluminum construction and shall protect the contained crystals and ovens under all service conditions as specified in Specification MIL-T-21200 for Class 3 equipment

3.4.2.5.5 Contents of Unit. The Case, Crystal-Oven CY-3690/SRM, shall contain 35 color-coded crystals and 6 color-coded dual ovens The crystals for channels 1 through 6 shall be color-coded green and the crystals for channels 11 through 39 shall be color-coded red. Three of the dual ovens shall be color-coded green and three of the dual ovens shall be color-coded red The channel frequencies shall be in accordance with BuWeps confidential letter RMWC-53, Serial 08133, dated 7-24-61, as amended by BuWeps confidential letter RMWC-53, Serial 04651, dated 11-2-61.

3 4 2.6 Decoder, Audio Frequency KY-432/SRM-3 The Decoder, Audio Frequency KY-432/SRM-3, shall meet the following detail requirements:

3 4.2.6.1 Function. The Decoder, Audio Frequency KY-432/SRM-3, shall be designed to receive audio frequency signals comprising command signals for the control of any one of the following five types of fixed wing aircraft F9F, KDA, Q2C, KDB, or KD2R5, and shall utilize these signals to produce visual indications for testing purposes

3 4 2 6.2 Form Factor The maximum external dimensions of the Decoder, Audio Frequency KY-432/SRM-3, shall be as follows:

Height 15-3/4 inches
Width 19 inches
Depth: 24 inches

3 4.2.6.3 Weight The weight of the Decoder, Audio Frequency KY-432/SRM-3, shall not exceed 110 pounds.

3.4.2 6.4 Contents of Unit The Decoder, Audio Frequency KY-432/SRM-3, shall consist of the following

(1) Decoder Subassembly

(2) Relay Assembly

(3) Main Chassis

3.4.2.6.4.1 Decoder Subassembly. The detail requirements of the decoder subassembly shall be as follows:

Source: https://assist.dla.mil -- Downloaded: 202610-19T17:26Z
Check the source to verify that this is the current version before use.

3.4.2.6.4.1.1 Function. The decoder subassembly shall provide 22 decoding channels capable of decoding the received audio frequency signals and shall permit any six of the decoding channels to operate simultaneously. The decoder subassembly shall provide ground return signals for application to the demultiplexing relays of the relay assembly and proportional voltages for application to the pitch and roll meter indicator circuits

3.4.2.6.4.1.2 Form Factor. The maximum dimensions of the decoder subassembly shall be as follows

Height: 4-3/4 inches
Width: 10-5/8 inches
Depth 13-1/2 inches

3.4.2.6.4.1.3 Weight. The weight of the decoder subassembly shall not exceed 20 pounds.

3.4.2.6 4 1.4 Contents of Unit The decoder subassembly shall consist of the following components and circuits:

(1) Audio-Frequency Filter Channels

(2) Amplifier Circuits

(3) Audio-Frequency, AGC and Coupling Amplifier Circuits

3.4.2.6.4.1.4.1 Audio-Frequency Filters. The audio-frequency filter channels and their corresponding frequency ranges shall be as follows:

Filter Channel Number	Filter Frequency Response (in Kilocycles)
1	7.500 ±1%
2	8.460 ±1%
3	9.540 ±1%
4 *	10.760 ±1%
5	12.140 ±1%
6 *	13.700 ±1%
7	15.450 ±1%

* The equipment shall include two each of the channel 4 and channel 6 audio filters. One pair shall provide inputs to the proportional amplifiers and one pair shall provide inputs to the on-off type amplifier.

Source: https://assist.dla.mil -- Downloaded: 202610-19T17:26Z
Check the source to verify that this is the currentversion before use.

Filter Channel Number	Filter Frequency Response (in Kilocycles)
8	17.430 ±1%
9	19 660 ±1%
10	22.170 ±1%
11	25.010 ±1%
12	28.210 ±1%
13	31.830 ±1%
14	35.900 ±1%
15	40.490 ±1%
16	45.680 ±1%
17	51 520 ±1%
18	58 120 ±1%
19	65.560 ±1%
20	73.950 ±1%

3 4.2.6.4.1.4.2 Amplifier Circuits. The 22 amplifier circuits shall consist of 20 on-off type amplifier stages and two proportional type amplifier stages The 20 on-off type amplifier stages shall generate ground return signals for controlling the demultiplexing relays of the relay assembly The two proportional type amplifier stages shall provide voltages for application to the pitch and roll meter control circuits

3.4.2.6.4.1.4.3 Audio-Frequency, AGC, and Coupling Amplifier Circuits. The audio-frequency amplifier circuit shall provide two stages of amplification for the received audio frequency signals. The AGC circuits shall consist of an amplifier and rectifier which shall provide feedback voltages to the audio-frequency amplifiers to ensure uniform amplifier output amplitudes A variable AGC control shall be provided The coupling circuit, consisting of a transformer-coupled audio amplifier, shall provide the facilities for applying audio frequency signals to 22 decoding channel circuits.

3.4.2.6.4.2 Relay Assembly. The relay assembly shall include 65 demultiplexing relays controlled by ground return signal information as supplied by the decoder subassembly. The relay assembly shall provide voltages for application to the on-off decoding channel indicator lamps.

Source: https://assist.dla.mil -- Downloaded: 202610-19T17:26Z
Check the source to verify that this is the currentversion before use.

3.4.2.6.4.3 Main Chassis. The main chassis shall house the decoder subassembly and the relay assembly and shall include the following circuits, components, controls, and indicators:

(1) Power-Supply Circuits

(2) Meter-Indicator Control Circuits

(3) Power Switch

(4) Standby Switch

(5) Drone Type Selector Switches

(6) Fuses and Fuseholders

(7) Power-Indicator Lamp

(8) Standby-Indicator Lamp

(9) Drone Type Indicator Lamps

(10) On-Off Decoding Channel Indicator Lamps

(11) Meter

3.4.2.6.4 3.1 Power-Supply Circuits. The power-supply circuits shall convert the a-c input power to all voltages required by the Decoder, Audio Frequency KY-432/SRM-3

3 4.2.6 4.3.2 Meter-Indicator Control Circuits The meter-indicator control circuits shall receive information from the decoder subassembly and shall convert this information to meter indications.

3 4.2.6 4.3.3 Power Switch A two-position switch for controlling the application of primary power shall be provided on the front panel of the main chassis and shall be designated as MAIN POWER.

3.4.2.6.4.3.4 Standby Switch. A momentary contact pushbutton switch for selecting the standby operational condition shall be provided on the front panel of the main chassis and shall be designated STANDBY.

3.4.2.6.4.3.5 Drone Type Selector Switches Five momentary-contact pushbutton switches shall be provided on the front panel of the main chassis for selecting the desired type of drone aircraft command signal to be monitored. These switches shall be designated as F9F, KDA, Q2C, KDB and KD2R5. Two spare momentary-contact pushbutton switches shall also be provided.

3.4.2.6.4.3.6 Fuses and Fuseholders. Two fuses and fuseholders shall be provided on the front panel of the main chassis for protecting the equipment

Source: https://assist.dla.mil -- Downloaded: 202610-19T17:26Z
Check the source to verify that this is the current version before use.

against electrical overloads or shorts. The two fuseholders shall be designated F1 and F2, respectively. Two fuses and fuseholders designated SPARE shall also be provided on the front panel of the main chassis. Fuseholders shall be of the blown fuse indicating type per Specification MIL-F-19207.

3 4.2 6.4.3.7 Power-Indicator Lamp. An indicator lamp shall be provided on the front panel of the main chassis and shall be illuminated when filament and bias voltages are applied.

3 4.2.6.4.3.8 Standby-Indicator Lamp. An indicator lamp shall be provided on the front panel of the main chassis and shall be illuminated when the equipment is in the standby condition of operation. The indicator lamp shall be designated STANDBY.

3.4.2.6.4.3.9 Drone Type Indicator Lamps. Five indicator lamps shall be provided on the front panel of the main chassis for displaying which type of drone aircraft command signal is being monitored The five indicator lamps shall be designated F9F, KDA, Q2C, KDB, and KD2R5. Two spare indicator lamps shall also be provided.

3 4 2 6.4.3 10 On-Off Decoding Channel Indicator Lamps. Seventy on-off decoding channel indicator lamps shall be provided on the front panel of the main chassis for displaying the drone aircraft command signal functions Each indicator lamp shall be designated by the nomenclature of the function the lamp monitors. Table I lists the 70 indicator lamp functions and the decoder channel outputs required to illuminate the applicable lamps for each drone aircraft type. Eight spare on-off decoding channel indicator lamps shall also be provided on the front panel of the main chassis.

3 4 2 6 4 3.11 Meter Indicators. Two meters for indicating the pitch and roll commands of the KD2R5 type drone aircraft shall be provided on the front panel of the main chassis. The meters shall be designated as PITCH and ROLL

3 4 2 6 5 Primary Input Power Requirements The Decoder, Audio Frequency KY-432/SRM-3, shall meet all applicable requirements of Specification MIL-T-21200 and shall give specified performance from the following power sources with characteristics as defined in Specification MIL-T-21200 having limits specified therein The power required shall not exceed the specified amounts.

(1) AC Power (Single Phase), 60 cycle, 102 to 126 Volt, 200 VA

3.4.2.6.6 Electrical Connections.

3 4.2.6 6.1 The following external connector shall be provided on the front panel of the Decoder, Audio Frequency KY-432/SRM-3:

Reference Designation	Receptacle Type	Function
J1	UG-492/U	External Audio Input

Source: https://assist.dla.mil -- Downloaded: 202610-19T17:26Z
Check the source to verify that this is the current version before use.

3.4.2.6.6.2 The following external connectors shall be provided on the rear panel of the Decoder, Audio Frequency KY-432/SRM-3:

Reference Designation	Receptacle Type	Function
J2	MS3102E14S-2P	Primary Input Power
J3	UG-909/U	Internal Audio Input

Table I. Command Channel Functions.

Drone Aircraft Function (Lamp Designations)	Drone Aircraft Type and Decoding Channel Required to Energize Corresponding Function					
	F9F-6K	F9F-6K2	KDA	Q2C	KDB	KD2R5
Brakes Off	2	2				
Brakes On	3	3				
Cruise Airspeed	4	4				
Landing Gear Up	5	5				
Landing Gear Down	6	6				
Climb	7	7	4	5 and 6	3	
Dive	8	8	5	6 and 7	1	
Left Turn	9	9	8	8 and 9	4	
Right Turn	10	10	7	5 and 7	2	
Turn Center	11	11				
Altitude Retain	13	13				
Airspeed Increase	14	14	2	5		
Airspeed Decrease	15	15	3	7		
Right Rudder	16	16	10	8		
Left Rudder	17	17	6	9		
Smoke On	1 and 2	1 and 2	4 and 5	3		
Cameras On	1 and 5	1 and 5				
FEI Pod Jettison	1 and 6	1 and 6				
Automatic Take Off	18	18				
Direct Throttle On	19	19				
Approach Airspeed	20	20				
Wing Fuel Jettison	1 and 3	1 and 3				
Smoke Off	1 and 4	1 and 4				
Drag Chute Jettison	1 and 7	1 and 7				
Wing Flaps Down	1 and 8	1 and 8				
Wing Flaps Up	1 and 9	1 and 9				
Drag Chute Deploy	1 and 10	1 and 10				
S-Band Beacon On	1 and 11	1 and 11				
S-Band Beacon Off	1 and 12	1 and 12				
Speed Brakes Down	1 and 13	1 and 13				
Speed Brakes Up	1 and 14	1 and 14				
Pre-Set Dive	1 and 15	1 and 15				
Pre-Set Climb	1 and 16	1 and 16				
Arresting Hooks Down	1 and 17	1 and 17				

Source: https://assist.dla.mil -- Downloaded: 202610-19T17:26Z
Check the source to verify that this is the current version before use.

Table I. Command Channel Functions (Cont'd)

Drone Aircraft Function (Lamp Designations)	Drone Aircraft Type and Decoding Channel Required to Energize Corresponding Function					
	F9F-6K	F9F-6K2	KDA	Q2C	KDB	DK2R5
Arresting Hooks Up	1 and 18	1 and 18				
Flying Tail In	1 and 19	1 and 19				
Flying Tail Out	1 and 20	1 and 20				
Low Altitude Control On		12 and 3				
C-Band Beacon Off		12 and 4				
C-Band Beacon On		12 and 5				
Telemeter Calibrate		12 and 6		5 and 8		
Ext. Stores Jettison		12 and 7				
UHF Homing On		12 and 8				
UHF Homing Off		12 and 9				
IR Aug. On		12 and 10				
IR Aug. Off		12 and 11				
F9F Spare		12 and 13				
F9F Spare		12 and 14				
F9F Spare		12 and 15				
F9F Spare		12 and 16				
F9F Spare		12 and 17				
F9F Spare		12 and 18				
F9F Spare		12 and 19				
F9F Spare		12 and 20				
Straight Level			1	7 and 8		
Flares				6 and 9		
Bank Angle Override			6 and 10	6 and 8		
Left Aug. Antenna				10		
Right Aug. Antenna				6		
Emergency Chute				2		
Scoring				4		
Command Chute			9	1	Interrupts 6 Keys 4 and 2	Interrupts 4
KDA Spare			7 and 8			
Q2C Spare				10 and 5		
Q2C Spare				10 and 7		
Q2C Spare				10 and 6		
Q2C Spare				5 and 9		
Q2C Spare				7 and 9		
KDB Spare					5	
KD2R5 Spare						1
Pitch Meter						*4
Roll Meter						*6

* Proportional Amplifier Outputs.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:26Z
Check the source to verify that this is the current version before use.

3.4.2.7 Decoder, Audio Frequency KY-433/SRM. The Decoder, Audio Frequency KY-433/SRM, shall meet the following detail requirements:

3.4.2.7.1 Function. The Decoder, Audio Frequency KY-433/SRM, shall be designed to receive audio frequency signals from either the Receiver, Radio R-1135/SRM, or from an auxiliary receiver. The received signals, representing command signals for the control of rotary wing aircraft, shall be decoded by the decoder subassembly which shall be a digital decoder. The decoded command signals shall be utilized to produce visual indications for test purposes.

3.4.2.7.2 Form Factor. The maximum external dimensions of the Decoder, Audio Frequency KY-433/SRM, shall be as follows

Height: 12-1/4 inches
Width: 19 inches
Depth: 23 inches

3.4.2 7.3 Weight. The weight of the Decoder, Audio Frequency KY-433/SRM, shall not exceed 85 pounds.

3.4.2.7.4 Contents of Unit. The Decoder, Audio Frequency KY-433/SRM, shall contain the following subassemblies

(1) Decoder Subassembly

(2) Voltage-Regulator and Servo-Amplifier Subassembly

(3) Main Chassis

3.4.2.7.4.1 Decoder Subassembly The detail requirements of the decoder subassembly shall be as follows·

3.4.2.7.4 1.1 Function. The decoder subassembly shall convert received audio signals having frequencies of 43 68 and 47 68 to command voltages which shall be applied to the servo-amplifier and indicator circuits The audio signals shall comprise information frames Each information frame shall consist of one blank word, two synchronizing words, and eight command words. Each of the command and synchronizing words shall be comprised of nine bits. Three bits in the second synchronizing word of each information frame shall be variable and shall determine the security code. The applicable sequence of the three variable bits shall be selected by the equipment ADDRESS switch.

3.4.2.7.4.1.2 Form Factor The maximum dimensions of the decoder subassembly shall be as follows:

Height: 9 inches
Width: 10-7/8 inches
Depth: 11-3/4 inches

3.4.2.7.4.1.3 Weight. The maximum weight of the decoder subassembly shall not exceed 15 pounds.

Source: https://assist.dla.mil -- Downloaded: 202640-19T17:26Z
Check the source to verify that this is the currentversion before use.

3.4.2.7.4.1.4 Contents of Unit. The decoder subassembly shall include the following nonrepairable, printed circuit, plug-in type, card subassemblies:

(1) Code Board Plug-in Subassembly

(2) Storage Register No. 1 Plug-in Subassembly

(3) Temporary Register No. 1 Plug-in Subassembly

(4) Digit Matrix No 1 Plug-in Subassembly

(5) Digit Counter Plug-in Subassembly

(6) Digit Matrix No. 2 Plug-in Subassembly

(7) Control Gate No. 2 Plug-in Subassembly

(8) Control Gate No. 1 Plug-in Subassembly

(9) Clock Counter Plug-in Subassembly

(10) Clock Oscillator Plug-in Subassembly

(11) Register Reset Plug-in Subassembly

(12) Storage Register No. 2 Plug-in Subassembly

(13) Temporary Register No. 2 Plug-in Subassembly

(14) Word Matrix No. 1 Plug-in Subassembly

(15) Word Matrix No. 2 Plug-in Subassembly

(16) Word Counter Plug-in Subassembly

(17) Word Matrix No. 3 Plug-in Subassembly

(18) Frame Reset Plug-in Subassembly

(19) Sub Carrier Plug-in Subassembly

3.4.2.7.4.1.4.1 Code Board Plug-In Subassembly. The code board plug-in subassembly shall include 16 diodes which shall establish a preselected pulse pattern for the two synchronizing words of the received information frames. When the synchronizing words are of the correct coded sequence, the code board allows the received information frames to be decoded. The code board plug-in subassembly shall be designated D/CB.

3.4.2.7.4.1.4.2 Storage Register No. 1 Plug-in Subassembly. The storage register No. 1 plug-in subassembly shall consist of four flip-flop circuits and

Source: https://assist.dla.mil -- Downloaded: 202640-19T17:26Z
Check the source to verify that this is the currentversion before use.

shall be used in conjunction with storage register No. 2 to serve as storage circuits to allow time for relay sequencing during the decoding process. The storage register No. 1 plug-in subassembly shall be designated D/SR.

3.4.2.7.4.1.4.3 Temporary Register No. 1 Plug-in Subassembly. The temporary register No. 1 plug-in subassembly shall consist of four flip-flop circuits and shall be used in conjunction with temporary register No. 2 to serve as information storage circuits to allow time for checking the parity of the received coded information. The temporary register No 1 plug-in subassembly shall be designated D/TR.

3.4.2.7.4.1.4.4 Digit Matrix No. 1 Plug-in Subassembly. The digit matrix No. 1 plug-in subassembly shall be utilized in conjunction with digit matrix No. 2 to apply, in a timed sequence, the received word information to the temporary registers No. 1 and No. 2. The digit matrix No. 1 plug-in subassembly shall be designated D/DM1.

3.4.2 7.4.1.4 5 Digit Counter Plug-in Subassembly.The digit counter plug-in subassembly shall consist of a 9-to-1 frequency divider circuit which shall produce the word rate frequency. The digit counter plug-in subassembly shall be designated DC.

3.4.2.7.4.1.4.6 Digit Matrix No 2 Plug-in Subassembly. The function of digit matrix No 2 plug-in subassembly is explained in 3.4.2.7.4.1.4.4. The digit matrix No. 2 plug-in subassembly shall be designated D/DM2.

3.4.2.7.4.1.4.7 Control Gate No. 2 Plug-in Subassembly. The control gate No. 2 plug-in subassembly shall include the parity counter circuit and the clock pulse generator circuit The control gate No 2 shall not pass the received coded information if the parity is incorrect. The control gate No. 2 plug-in subassembly shall be designated D/CG2.

3.4.2.7.4.1.4.8 Control Gate No. 1 Plug-in Subassembly The control gate No. 1 plug-in subassembly shall include the carrier loss and master control circuits which shall disable the decoding circuits when the carrier level of the received signal drops below a predetermined level. The control gate No. 1 plug-in subassembly shall be designated D/CG1.

3.4.2.7.4.1.4.9 Clock Counter Plug-in Subassembly. The clock counter plug-in subassembly shall consist of a gated 16-to-1 frequency divider circuit which shall produce the decoding word frequency as controlled by the control gate No. 1. The clock counter plug-in subassembly shall be designated D/CC.

3.4.2.7.4.1.4.10 Clock Oscillator Plug-in Subassembly. The clock oscillator plug-in subassembly shall consist of a free-running oscillator circuit which shall generate the basic timing pulse utilized by the decoder subassembly. The clock oscillator plug-in subassembly shall be designated D/CO.

3.4.2.7.4.1.4.11 Register Reset Plug-in Subassembly. The register reset plug-in subassembly shall provide the circuitry to generate the pulse which

Source: https://assist.dla.mil -- Downloaded: 202640-19T17:26Z
Check the source to verify that this is the current version before use.

shall be utilized for resetting the temporary and storage registers at the completion of each word readout cycle. The register reset plug-in subassembly shall be designated D/RR.

3.4.2.7 4.1 4.12 Storage Register No 2 Plug-in Subassembly. The function of the storage register No 2 plug-in subassembly is explained in 3.4 2 7.4.1.4.2. The storage register No. 2 plug-in subassembly shall be designated D/SR.

3 4.2.7 4 1 4.13 Temporary Register No 2 Plug-in Subassembly. The function of the temporary register No. 2 plug-in subassembly is explained in 3 4 2.7.4 1.4.3. The temporary register No. 2 plug-in subassembly shall be designated D/TR.

3 4.2.7 4.1.4.14 Word Matrix No 1 Plug-in Subassembly. The word matrix No. 1 plug-in subassembly, in conjunction with word matrix No 2 subassembly, shall provide the power-amplification circuits and time-sequencing circuits to produce the signals utilized to energize the demultiplexing relays. The word matrix No. 1 plug-in subassembly shall be designated D/WM1.

3 4.2 7 4.1.4 15 Word Matrix No 2 Plug-in Subassembly. The function of the word matrix No. 2 plug-in subassembly is explained in 3 4.2.7.4.1.4.14. The word matrix No 2 plug-in subassembly shall be designated D/WM2

3 4.2 7 4.1.4.16 Word Counter Plug-in Subassembly. The word counter plug-in subassembly shall consist of an 11-to-1 frequency divider circuit which shall produce the information frame frequency utilized during the decoding process. The word counter plug-in subassembly shall be designated WC.

3.4.2 7.4.1.4.17 Word Matrix No. 3 Plug-in Subassembly. The word matrix No. 3 plug-in subassembly shall include the synchronizing gate recognition circuits and the frame reset pulse generating circuits These circuits shall produce the pulse which shall be utilized to place control gate No 1 in the off condition The word matrix No. 3 plug-in subassembly shall be designated D/WM3

3 4.2.7.4.1.4.18 Frame Reset Plug-in Subassembly. The frame reset subassembly shall provide the amplifier and buffer circuits for amplifying the frame reset pulse generated by word matrix No 3. The frame reset plug-in subassembly shall be designated D/FR.

3.4.2 7 4.1.4.19 Sub-Carrier Plug-in Subassembly The sub-carrier plug-in subassembly shall contain the circuits necessary for converting the input audio frequency signals to digitally coded command signals. The sub-carrier plug-in subassembly shall be designated D/SC.

3.4.2.7.4.2 Voltage-Regulator and Servo-Amplifier Subassembly. The detail requirements of the voltage-regulator and servo-amplifier subassembly shall be as follows:

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:26Z
Check the source to verify that this is the current version before use.

3.4.2.7.4.2 1 Function. The voltage-regulator and servo-amplifier subassembly shall supply +18, +12, +6, +3, -12, and -18-volt d-c regulated voltages, and shall provide the amplifier circuits for driving the altitude and heading servo mechanism indicators provided on the front panel of the equipment.

3.4.2.7.4.2.2 Form Factor. The maximum external dimensions of the voltage-regulator and servo-amplifier subassembly shall not exceed the following

Height: 6-3/4 inches
Width. 4 inches
Depth: 10-1/2 inches

3.4.2.7.4.2.3 Weight. The weight of the voltage-regulator and servo-amplifier subassembly shall not exceed 5 pounds.

3.4.2.7.4.2.4 Contents of Unit. The voltage-regulator and servo-amplifier subassembly shall contain the following nonrepairable, printed circuit, plug-in type subassembly boards:

(1) Altitude-Servo Amplifier Plug-in Subassembly Board

(2) Heading-Servo Amplifier Plug-in Subassembly Board

(3) +3 and +6-Volt D-C Voltage Regulator Plug-in Subassembly Board

(4) +12 and +18-Volt D-C Voltage Regulator Plug-in Subassembly Board

(5) -12 and -18-Volt D-C Voltage Regulator Plug-in Subassembly Board

3.4.2.7.4.2.4.1 Altitude-Servo Amplifier Plug-in Subassembly Board. The altitude-servo amplifier plug-in subassembly board shall provide the transistor amplifier circuits for driving the altitude-servo mechanism indicator provided on the equipment front panel.

3.4.2.7.4.2.4.2 Heading-Servo Amplifier Plug-in Subassembly Board. The heading-servo amplifier plug-in subassembly board shall provide the transistor amplifier circuits for driving the heading servo mechanism indicator provided on the decoder front panel.

3.4.2.7.4.2.4.3 +3 and +6-Volt D-C Voltage Regulator Plug-in Subassembly Board. The +3 and +6-volt d-c voltage regulator plug-in subassembly board shall consist of transistor regulator circuits which provide the +3 and +6-volt regulated d-c voltaages utilized by the decoder.

3.4.2.7.4.2.4.4 +12 and +18-Volt D-C Voltage Regulator Plug-in Subassembly Board. The +12 and +18-volt d-c voltage regulator plug-in subassembly board shall consist of transistor regulator circuits which provide the +12 and +18 volt regulated d-c voltages utilized by the decoder.

3.4.2.7.4.2.4.5 -12 and -18-Volt D-C Voltage Regulator Plug-in Subassembly Board. The -12 and -18-volt d-c voltage regulator plug-in subassembly board

Source: https://assist.dla.mil -- Downloaded: 20260-19T17:26Z
Check the source to verify that this is the currentversion before use.

shall consist of transistor regulator circuits which provide the -12 and -18-volt regulated d-c voltages utilized by the decoder.

3.4.2.7.4.3 Main Chassis. The main chassis shall house the decoder subassembly and the voltage regulator and the servo amplifier subassembly. In addition the following circuits, controls, and indicators shall be provided on the decoder main chassis

(1) +28-Volt D-C Power Supply Circuit

(2) -28-Volt D-C Power Supply Circuit

(3) 400-Cycle Static-Inverter Circuit

(4) Power Switch

(5) Code-Selector Switch

(6) Audio-Selector Switch

(7) Fuses and Fuseholders

(8) Meters

(9) Indicating Servo Mechanisms

(10) On-Off Indicators

3.4.2.7.4.3.1 +28-Volt D-C Power-Supply Circuit. This circuit shall include a transformer, four rectifying diodes, and a filter network, and shall provide the +28 volts dc utilized by the decoder.

3.4.2.7.4.3.2 -28-Volt D-C Power-Supply Circuit. This circuit shall include a transformer, four rectifying diodes, and a filter network, and shall provide the -28 volts dc utilized by the decoder.

3.4.2.7.4.3.3 400-Cycle Static-Inverter Circuit. This circuit shall include two transformers and two transistors, and shall convert +28 volts dc to two voltages having a 90-degree phase difference and values of 115 volts 400 cycles and 15 volts, 400 cycles. The 400-cycle voltages shall be utilized to drive the altitude and heading servo mechanism indicators.

3.4.2.7.4.4.4 Power Switch. A two-position toggle switch for controlling the application of external power shall be provided. The switch shall be designated MAIN POWER, ON-OFF.

3.4.2.7.4.4.5 Code-Selector Switch. A nine-position rotary switch for selecting different security codes shall be provided. The switch shall be designated ADDRESS, A, B, C, D, E, F, G, H, and ALL.

Source: https://assist.dla.mil -- Downloaded: 202610-19T17:26Z
Check the source to verify that this is the current version before use.

3.4.2.7.4.4.6 Audio-Selector Switch. A two-position switch shall be provided for selecting either an input signal supplied by the Receiver, Radio R-1135/SRM, or an input signal supplied by an auxiliary receiver. The switch shall be designated AUDIO SELECTOR SWITCH, INTERNAL, and EXTERNAL. The INTERNAL position shall select an input signal supplied by the Receiver, Radio R-1135/SRM. The EXTERNAL position shall select an input signal supplied by an auxiliary receiver.

3.4.2.7.4.4.7 Fuses and Fuseholders. A fuse and fuseholder for protecting the equipment against electrical overloads or shorts shall be provided. A spare fuse and fuseholder shall be provided. These fusheolders shall be designated as FUSE and SPARE. Fuseholders shall be of the blown fuse indicating type as specified in Specification MIL-F-19207.

3 4 2.7.4.4.8 Meters. Two meters for indicating the pitch attitude and roll attitude command functions shall be provided. The meters shall be designated as PITCH ATTITUDE and ROLL ATTITUDE.

3.4.2.7 4.4.9 Indicating Servo Mechanisms. Two servo mechanisms for indicating the heading and altitude command functions shall be provided. They shall be designated HEADING and ALTITUDE.

3.4.2.7.4.4.10 On-Off Indicators. Ten on-off indicator lamps shall be provided. Nine of these lamps shall denote the command functions for rotary wing aircraft and one shall indicate when the received audio signals are of insufficient level to be properly decoded. Engraving shall be provided on the face of each indicator and shall denote the command signal function being monitored.

3.4.2.7.5 Primary Input Power Requirements The Decoder Audio Frequency KY-433/SRM, shall meet all applicable requirements of Specification MIL-T-21200 and shall give specified performance from the following power sources with characteristics as defined in Specification MIL-T-21200 having limits specified therein. The power required shall not exceed the specified amounts.'

(1) AC Power (Single Phase), 60 cycle, 102 to 126 volt, 130 VA

3.4.2.7.6 Electrical Connections.

3.4.2.7.6.1 The following external connector shall be provided on the front panel of the Decoder, Audio Frequency KY-433 /SRM

Reference Designation	Receptacle Type	Function
J1	UG-909/U	Auxiliary Audio Frequency Input

3.4.2.7.6 The following external connectors shall be provided on the rear panel of the Decoder, Audio Frequency KY-433/SRM·

Source: https://assist.dla.mil -- Downloaded: 202640-19T17:26Z
Check the source to verify that this is the currentversion before use.

Reference Designation	Receptacle Type	Function
J2	UG-911/U	Audio Frequency Input
J3	MS3102E14S-2P	Primary Input Power

3.4.3 Test Set, Target Control System AN/SRM-4. Detail requirements of the Test Set, Target Control System AN/SRM-4, shall be as follows

3.4.3.1 Cabinet, Electrical Equipment CY-3585/SRM-4. The Cabinet, Electrical Equipment CY-3585/SRM-4, shall meet the following detail requirements

3.4.3.1.1 Function. The Cabinet, Electrical Equipment, CY-3585/SRM-4, shall provide facilities for supporting on extending drawer type slides the Receiver, Radio R-1135/SRM, the Decoder, Audio Frequency KY-433/SRM, and a storage container. The Cabinet, Electrical Equipment CY-3585/SRM-4, shall also provide the electrical interconnection facilities for the equipments contained therein and a blower assembly capable of providing sufficient air for cooling the contained equipments

3.4.3.1.2 Form Factor. The maximum external dimensions of the Cabinet, Electrical Equipment CY-3585/SRM-4, shall be as follows

Height 54-1/4 inches
Width 24-1/2 inches
Depth 28 inches

3.4.3.1.3 Weight. The weight of the Cabinet Electrical Equipment CY-3585 SRM-4, shall not exceed 320 pounds.

3.4.3.1.4 Contents of Unit. The Cabinet, Electrical Equipment CY-3585/SRM-4, shall contain a blower assembly.

3.4.3.1.4.1 Blower Assembly. The detail requirements of the blower assembly shall be as follows

3.4.3.1.4.1.1 Function. The blower assembly shall provide air circulation capable of cooling under normal operating conditions, all electronic equipment contained in the Cabinet, Electrical Equipment CY-3585/SRM-4.

3.4.3.1.4.1.2 Form Factor. The maximum dimensions of the blower assembly shall be as follows

Height. 8-3/4 inches
Width: 19 inches
Depth: 24 inches

3.4.3.1.4.1.3 Weight. The weight of the blower assembly shallnot exceed 40 pounds.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:26Z
Check the source to verify that this is the current version before use.

3.4.3.1.4.1.4 Contents of Unit. The blower assembly shall contain a squirrel cage type electric blower which shall utilize approximately 110-volt-amperes of 115-volt single-phase power and shall be capable of delivering 700 cubic feet of air per minute under normal conditions. The blower assembly shall also contain an aluminum wire mesh type filter which shall be capable of filtering the air circulated by the electric blower.

3.4.3.1.5 Electrical Connections. Connections to external circuits shall be provided on the rear of the equipment as follows

Reference Designation	Receptacle Type	Function
J1	MS3102R16-10P	External Input Power

3.4.3.2 Receiver, Radio R-1135/SRM. Detail requirements of the Receiver, Radio R-1135/SRM, shall be as specified in 3.4.2.2.

3.4.3.3 Case, Crystal-Oven CY-3690/SRM. Detail requirements of the Case, Crystal-Oven CY-3690 SRM, shall be as specified in 3.4.2.5.

3.4.3.4 Decoder, Audio Frequency KY-433/SRM. Detail requirements of the Decoder, Audio Frequency KY-433/SRM, shall be as specified in 3.4.2.7.

3.4.4 Test Set, Target Control System AN/SRM-5 Detail requirements of the Test Set, Target Control System AN/SRM-5, shall be as follows

3.4.4.1 Cabinet, Electrical Equipment CY-3586/SRM-5. The Cabinet, Electrical Equipment CY-3586/SRM-5, shall meet the following detail requirements

3.4.4.1.1 Function. The Cabinet, Electrical Equipment CY-3586/SRM-5, shall provide facilities for supporting the following equipments on extending drawer type slide Amplifier-Frequency Multiplier AM-3311/SRM Power Supply PP-3373/SRM, Coder, Audio Frequency KY-430/SRM and Coder, Audio Frequency KY-431/SRM. The Cabinet Electrical Equipment CY-3586/SRM-5, shall also provide the electrical interconnection and cooling facilities for the equipment contained therein.

3.4.4.1.2 Form Factor. The maximum external dimensions (excluding mounts) of the Cabinet, Electrical Equipment CY-3586/SRM-5, shall be as follows

Height 63 inches
Width 24-1/2 inches
Depth. 28 inches

3.4.4.1.3 Weight. The weight of the Cabinet, Electrical Equipment CY-3586/SRM-5, shall not exceed 415 pounds.

3.4.4.1.4 Contents of Unit. The Cabinet, Electrical Equipment CY-3586/SRM-2, shall contain a blower. The detail requirements of the blower shall be as follows:

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:26Z
Check the source to verify that this is the current version before use.

3.4.4.1 4.1 Function. The blower shall be capable of supplying air in sufficient quantity to cool, under normal operating conditions, all electronic equipment contained in the Cabinet, Electrical Equipment CY-3586/SRM-5.

3 4 4.1 4.2 Form Factor. The maximum external dimensions of the blower shall be as follows

Height	8-3/4 inches
Width	19 inches
Depth	24 inches

3.4.4 1 4 3 Weight The weight of the blower shall not exceed 40 pounds.

3.4.4 1.4.4 Contents of Unit. The blower shall consist of an electric blower and a wire mesh type air filter. The blower shall be a squirrel cage type blower which utilizes approximately 100-volt-amperes of 115-volt single-phase power and shall be capable of delivering 300 cubic feet of air per minute under normal conditions. The wire mesh type filter shall be capable of filtering dust particles from the air circulated by the blower.

3.4 4.1.5 Electrical Connections Connections to external circuits shall be provided on the rear of the equipment as follows

Reference Designation	Receptacle Type	Function
J1	MS3102R16-10P	Primary Input Power

3.4.4.2 Coder, Audio Frequency KY-430/SRM Detail requirements of the Coder, Audio Frequency KY-430/SRM, shall be as specified in 3.4.1.7.

3 4.4.3 Coder, Audio Frequency KY-431 SRM Detail requirements of the Coder Audio Frequency KY-431/SRM, shall be as specified in 3.4.1.8.

3 4 4 3.1 Control, Coder C-4123 SRM. Detail requirements of the Control, Coder C-4123 SRM, shall be as specified in 3.4.1.8.4.4.

3 4.4.4 Amplifier-Frequency Multiplier AM-3311/SRM. Detail requirements of the Amplifier-Frequency Multiplier AM-3311/SRM shall be as specified in 3 4.1.9.

3.4.4.5 Power Supply PP-3373/SRM. Detail requirements of the Power Supply PP-3373 SRM shall be as specified in 3.4.1.10.

3.4.5 Test Set, Target Control System AN/SRM-6. Detail requirements of the Test Set, Target Control System AN/SRM-6 shall be as follows:

Source: https://assist.dla.mil -- Downloaded: 202610-19T17:26Z
Check the source to verify that this is the current version before use.

3.4.5.1 Cabinet, Electrical Equipment CY-3587/SRM-6. The Cabinet, Electrical Equipment CY-3587/SRM-6, shall meet the following detail requirements:

3.4.5.1.1 Function The Cabinet, Electrical Equipment CY-3587/SRM-6, shall provide facilities for supporting the Amplifier-Frequency Multiplier AM-3311/SRM, the Power Supply PP-3373/SRM, and the Coder, A to Frequency KY-431/SRM, on extending drawer type slides. The Cabinet, Electrical Equipment CY-3587/SRM-6, shall also provide the electrical interconnection and cooling facilities for the equipment contained therein.

3.4.5.1.2 Form Factor. The maximum external dimensions (excluding mounts) of the Cabinet, Electrical Equipment CY-3587/SRM-6, shall be as follows:

Height 54-1/2 inches
Width 24-1/2 inches
Depth 26 inches

3.4.5.1.3 Weight. The weight of the Cabinet, Electrical Equipment CY-3587/SRM-6, shall not exceed 325 pounds

3.4.5.1.4 Contents of Unit. The Cabinet, Electrical Equipment CY-3587/SRM-6, shall contain a blower. The detail requirements of the blower shall be as follows:

3.4.5.1.4.1 Function The blower shall be capable of supplying air in sufficient quantity to cool, under normal operating conditions, all electronic equipment contained in the Cabinet, Electrical Equipment CY-3587/SRM-6

3.4.5.1.4.2 Form Factor The maximum external dimensions of the blower shall be as follows

Height 8-3/4 inches
Width 19 inches
Depth 24 inches

3.4.5.1.4.3 Weight. The weight of the blower shall not exceed 40 pounds.

3.4.5.1.4.4 Contents of Unit. The blower shall consist of an electric blower and a wire mesh type air filter. The electric blower shall be a squirrel cage type blower and shall utilize approximately 100-volt-amperes of 115-volt single-phase power and shall be capable of delivering 300 cubic feet of air per minute under normal conditions. The wire mesh type filter shall be capable of filtering the air circulated by the blower.

Source: https://assist.dla.mil -- Downloaded: 202610-19T17:26Z
Check the source to verify that this is the current version before use.

3.4.5.1.5 Electrical Connections. Connections to external circuits shall be provided on the rear of the equipment as follows.

Reference Designation	Receptacle Type	Function
J1	MS3102R16-10P	Primary Input Power

3.4.5.2 Coder, Audio Frequency KY-431/SRM. Detail requirements of the Coder, Audio Frequency KY-431/SRM, shall be as specified in 3.4.1.8.

3.4.5.2.1 Control, Coder C-4123/SRM. Detail requirements of the Control, Coder C-4123/SRM, shall be as specified in 3.4.1.8.4.4.

3.4.5.3 Amplifier-Frequency Multiplier AM-3311/SRM. Detail requirements of the Amplifier-Frequency Multiplier AM-3311/SRM, shall be as specified in 3.4.1.9.

3.4.5.4 Power Supply PP-3373/SRM. Detail requirements of the Power Supply PP-3373/SRM, shall be as specified in 3.4.1.10.

3.5 Workmanship. Workmanship, fabrication, and manufacturing processes shall conform to the requirements of Specification MIL-T-21200.

3.6 Associated Equipment. The equipments covered by this specification shall be capable of testing components of the Target Control System AN/SRW-4 and all revisions thereof but shall not be supplied as a part thereof.

Source: https://assist.dla.mil -- Downloaded: 202610-19T17:26Z
Check the source to verify that this is the currentversion before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Electronic Equipments. All electronic equipments of the Test Set, Target Control System AN/SRM Series, covered by this specification shall be subjected to the following tests to determine compliance with all applicable requirements:

(1) Preproduction Tests

(2) Acceptance Tests

4.1.1 Preproduction Tests. Preproduction tests shall be made on an equipment representative of the production equipments to be supplied under the contract. Preproduction tests shall consist of the following:

(1) Contractor's Demonstration Tests

(2) Service Approval Tests

4.1.1.1 Contractor's Demonstration Tests. Contractor's demonstration tests shall be accomplished under the responsibility of the contractor and shall be conducted in accordance with the approved test procedure of 4 1.3. The government inspector and the procuring activity shall be advised when tests are to be conducted so that a representative may be designated to witness or supervise the tests when so desired. Contractors not having adequate facilities to conduct all required tests shall obtain the services of a commercial testing laboratory.

4.1.1.1.1 The contractor shall submit all data collected in conducting these tests to the procuring agency for review and approval. This data shall include a list of all electrical and electronic parts giving their specified voltage, current, and temperature rating and the applied circuit voltage, current, and ambient and surface temperatures. The ambient and surface temperature shall be obtained under the extreme high temperature operating condition. Such data on parts may be included as part of the preliminary parts list.

4.1 1.2 Service Approval Tests. At the completion of the contractor's demonstration tests and when requested by the procuring activity, the equipment shall be delivered to a specified government laboratory for additional testing. This additional testing may consist of duplicating tests previously conducted and such other tests as are deemed necessary to determine compliance with all applicable design and performance requirements.

4 1.1.2.1 Accessory Material In addition to the complete equipment submitted for service approval tests, the contractor shall also submit the accessory material and design and test data specified in Specification MIL-T-21200. This information shall indicate the physical and electrical characteristics of the equipment and establish the equipment's compliance with applicable requirements.

4.1.1.3 Scope of Tests. Preproduction tests shall include all tests deemed necessary to determine that the equipment meets all the requirements of this specification and the contract. Preproduction tests shall include environmental and other

Source: https://assist.dla.mil -- Downloaded: 202640-19T17:26Z
Check the source to verify that this is the currentversion before use.

tests in accordance with Specification MIL-T-21200 and interference tests in accordance with Specification MIL-I-6181 and MIL-I-16910.

4.1.1.4 Preproduction Approval. Approval of the preproduction model shall be by the procuring activity upon satisfactory completion of all tests. Prefabrication of production equipment prior to the approval of the preproduction model is at the contractor's own risk. The approved preproduction model will be returned to the contractor for his use in the fabrication and testing of equipment to be submitted for acceptance. The preproduction model shall not be considered as one of the equipments under the contract, however, it may be reworked by the contractor and submitted for acceptance as a production equipment.

4.1.1.5 Equipments supplied under the contract shall in all respects, including design, construction, workmanship, performance and quality, be equivalent to the approved preproduction sample. Each equipment shall be capable of successfully passing the same tests imposed on the preproduction sample. Evidence of non-compliance with the above shall constitute cause for rejection and for equipment already accepted by this government it shall be the obligation of the contractor to make necessary corrections as approved by the procuring activity.

4.1.2 Acceptance Tests. The contractor shall furnish all samples and shall be responsible for accomplishing the acceptance tests. All inspection and testing shall be under the supervision of the government inspector. Contractors not having testing facilities satisfactory to the procuring activity shall engage the service of a commercial testing laboratory acceptable to the procuring activity. The contractor shall furnish test reports showing quantitative results for all acceptance tests. Such reports shall be signed by an authorized representative of the contractor or laboratory as applicable. Acceptance or approval of material during the course of manufacture shall not be construed as a guarantee of the acceptance of the finished product. Acceptance tests shall consist of the following.

(1) Individual Tests

(2) Sampling Tests

4.1.2.1 Individual Tests. Each equipment submitted for acceptance shall be subjected to the individual tests. These tests shall be adequate to determine compliance with the requirements of material, workmanship, operational adequacy, and reliability. As a minimum, each equipment accepted shall have passed the following tests.

(1) Examination of Product

(2) Operational Test

(3) Manufacturing Reliability Test

4.1.2.1.1 Examination of Product. Each equipment shall be examined carefully to determine that the material and workmanship requirements have been met.

Source: https://assist.dla.mil -- Downloaded: 202610-19T17:26Z
Check the source to verify that this is the currentversion before use.

4.1.2.1.2 Operational Test. Each equipment shall be operated long enough to permit the equipment temperature to stabilize and to check sufficient characteristics and record adequate data to assure satisfactory equipment operation.

4.1.2.1.3 Manufacturing Reliability Test. Each equipment shall be operated under the conditions specified herein for a period of six hours without failure A failure shall be defined as anything which causes malfunctioning of the equipment. Only those adjustments will be permitted which can be made by using such controls and adjustments that are accessible to the operator during the normal use of the equipment

Temperature	Ambient room
Humidity	Ambient room

Upon completing the six-hour period of operation the equipment shall be cycled through its various phases of operation Should failure occur, it should be repaired and the test started over. Should repetitive failures occur, corrective action shall be taken to eliminate this defect from future equipment. A record shall be kept of all failures. The six hour period specified above may be composed of two three-hour periods to conform with standard working hours.

4.1.2.2 Sampling Tests. Sampling tests shall be conducted on equipments having successfully passed the individual test. Equipments shall be selected for sampling tests by the Government Inspector in accordance with the following

Quantity of Equipments Offered for Acceptance	Quantity to be Selected For Sampling Test
First 10	1
Next 50	1
Next 75	1
Next 100	1
	1 for each additional 200 or fraction thereof

4.1.2.2.1 Scope of Tests. As a minimum, each equipment selected for sampling tests shall be subjected to the following tests

(1) Complete operational test at ambient room conditions, making all necessary measurements to assure that all applicable specification requirements have been met.

(2) Operational test at certain environmental conditions. The conditions may vary for each equipment tested and should be based on results of the preproduction and production tests.

Source: https://assist.dla.mil -- Downloaded: 202610-19T17:26Z
Check the source to verify that this is the current version before use.

(3) Manufacturing reliability test specified in 4.1.2.1.3 except that the test duration shall be 120 hours with no restriction on the number of failures. However, each failure shall be analyzed as to cause and remedial action necessary to reduce the possibility of its recurrence in future equipment.

4.1.3 Test Procedures. The procedures used for conducting preproduction tests and acceptance tests shall be prepared by the contractor and submitted to the procuring activity for review and approval. The right is reserved by the procuring activity or the government inspector to modify the tests or require any additional tests deemed necessary to determine compliance with the requirements of this specification or the contract. Specification MIL-T-18303 shall be used as a guide for preparation of test procedures. When test procedures are available from previous contracts, such procedures may be used when approved by the procuring activity.

4.1.3.1 Tests. Preproduction tests shall consist of all tests necessary to determine that the test equipment complies with all applicable requirements. Interference tests shall be in accordance with Specification MIL-I-6181 and MIL-I-16910 and environmental tests shall be in accordance with Specification MIL-T-21200 except as modified herein.

4.1.3.1.1 Vibration. The equipment shall be equipped with shock mounts and subjected to vibration along each of the three mutually perpendicular axes within the frequency range and amplitudes specified below in accordance with the applicable procedure of Specification MIL-T-5422.

Frequency Range	Double Amplitude
5 to 15 cps	0.06 inch
15 to 25 cps	0.04 inch
25 to 55 cps	0.02 inch

4.1.3.1.2 Temperature Tests. The equipment shall be subjected to temperature tests in accordance with Specification MIL-T-5422 except the maximum temperature shall not exceed 55°C and the minimum temperature shall not be less than 0°C with equipment operating.

4.1.3.1.3 Salt-Spray Tests. The equipment paint finishes shall be subjected to salt-spray tests in accordance with Specification MIL-T-5422.

4.1.3.1.4 Altitude Tests. The equipment shall be subjected to altitude tests only in a non-operating condition.

4.1.3.1.5 Drop Tests. The equipment cabinet shall not be subjected to drop tests.

4.1.3.1.6 Fungus Test. The equipment shall not be subjected to fungus tests; however, only non-nutrient materials shall be used.

Source: https://assist.dla.mil -- Downloaded: 202640-19T17:26Z
Check the source to verify that this is the currentversion before use.

4.1.3.1.7 Shock Tests. Shock testing shall be performed with the equipment mounted in its normal installation position. The unit shall be hoisted to the proper height above the test bed by means of an attachment to the top of the cabinet and then dropped to the test bed by means of a quick-release mechanism. Tests will not be performed in any other plane.

4.1.4 Presubmission Testing. No item, part or complete equipment shall be submitted by the contractor until it has been previously tested and inspected by the contractor and found to comply to the best of his knowledge and belief, with all applicable requirements.

4.1.5 Rejection and Retest. Equipment which has been rejected may be reworked or have parts replaced to correct the defects and resubmitted for acceptance. Before resubmitting, full particulars concerning previous rejection and the action taken to correct the defects found in the original shall be furnished the government inspector. Units rejected after retest shall not be resubmitted without the specific approval of the procuring activity.

4.2 Handling Equipment. All handling equipments of the Test Set, Target Control System AN/SRM Series, covered by this specification shall be subjected to the following tests to determine compliance with all applicable requirements.

4.2.1 Tool Kit, Target Control System TK-142 SRM-2.

4.2.1.1 Qualification Tests. Qualification tests shall be conducted at a Government laboratory designated by the procuring activity. These tests shall consist of the tests specified in 4.2.1.3.

4.2.1.2 Sampling for Lot Acceptance

4.2.1.2.1 Lot. For purposes of sampling, a lot shall consist of all Tool Kit, Target Control System TK-142/SRM-2, offered for delivery at one time.

4.2.1.2.2 Lot Acceptance Test. One sample of the Tool Kit, Target Control System TK-142 SRM-2 shall be selected from each lot by the Government inspector and shall be subjected to each of the following named tests, which shall be conducted or witnessed by the Government inspector, and the results of each test compared with this specification. Failure to conform to this requirement shall be counted as a defect and the equipment shall be rejected and the lot represented by the sample shall be rejected. Rejected lots may be offered again for Government inspection tests provided all equipment in the lot has been retested by the contractor for test(s) causing rejection and all noncompliance corrected.

Tests	Reference
Visual and Dimensional Inspection	4.2.1.3.1

Source: https://assist.dla.mil -- Downloaded: 20260-19T17:26Z
Check the source to verify that this is the current version before use.

4.2.1.3 Test Procedure.

4.2.1.3.1 Visual and Dimensional Inspection. A visual and dimensional inspection shall be made of the sample Tool Kit, Target Control System TK-142/SRM-2, to verify compliance with this specification and to determine that accepted manufacturing practice is being used and first class workmanship is being maintained during production.

4.2.2 Truck, Electronic Equipment V-244/SRM-2.

4.2.2.1 Qualification Tests. Qualification tests shall be conducted at a Government laboratory designated by the procuring activity. These tests shall consist of the test specified in 4.2.2.3.

4.2.2.2 Sampling for Lot Acceptance.

4.2.2.2.1 Lot. For purposes of sampling, a lot shall consist of all Trucks, Electronic Equipment V-244/SRM-2, offered for delivery at one time.

4.2.2.2.2 Lot Acceptance Test. One sample of the equipment shall be selected from each lot by the Government inspector and shall be subjected to each of the following named tests, which shall be conducted or witnessed by the Government inspector, and the results of each test compared with this specification. Failure to conform to this requirement shall be counted as a defect and the equipment shall be rejected and the lot represented by the sample shall be rejected. Rejected lots may be offered again for Government inspection tests provided all equipments in the lot have been retested by the contractor for test(s) causing rejection and all noncompliance corrected.

Tests	Reference
Visual and Dimensional Inspection	4.2.2.3.1
Static Overload	4.2.2.3.2
Dynamic Overload	4.2.2.3.3

4.2.2.3 Test Procedure.

4.2.2.3.1 Visual and Dimensional Inspection. A visual and dimensional inspection shall be made of the sample equipment to verify compliance with this specification and to determine that accepted manufacturing practice is being used and first class workmanship is being maintained during production.

4.2.2.3.2 Static Overload. The sample equipment shall support a load of twice the rated capacity for a period of 5 minutes. No breakage or permanent distortion of equipment parts shall occur during or after this test.

Source: https://assist.dla.mil -- Downloaded: 20260-19T17:26Z
Check the source to verify that this is the current version before use.

4.2.2.3.3 Dynamic Overload Test. The sample equipment shall be loaded to 150 percent of rated capacity. The supported load shall be rotated 15 times and shall be transported by the equipment. The truck shall operate satisfactorily without evidence of permanent distortion or dan age to any part. Excessive wear on any equipment part shall be cause for rejection.

4.2.3 Hoisting Unit, Portable, Electronic Equipment E-42/SRM-2

4 2 3.1 Qualification Tests. Qualification tests shall be conducted at a Government laboratory designated by the procuring activity These tests shall consist of the test specified in 4.2.3.3.

4.2.3.2 Sampling for Lot Acceptance.

4.2.3.2.1 Lot. For purposes of sampling, a lot shall consist of all Hoisting Units, Portable, Electronic Equipment E-42/SRM-2, offered for delivery at one time.

4.2 3.2.2 Lot Acceptance Test. One sample of the Hoisting Unit, Portable, Electronic Equipment E-42/SRM-2, shall be selected from each lot by the Government inspector and shall be subjected to each of the following named tests, which shall be conducted or witnessed by the Government Inspector, and the results of each test compared with this specification Failure to conform to this requirement shall be counted as a defect and the equipment shall be rejected and the lot represented by the sample shall be rejected Rejected lots may be offered again for Government inspection tests provided all equipment in the lot have been retested by the contractor for test(s) causing rejection and all noncompliance corrected

Tests	Reference
Visual and Dimensional Inspection	4.2.3.3.1
Static Overload	4.2.3.3.2
Dynamic Overload	4 2.3 3.3

4.2.3.3 Test Procedure.

4.2.3.3.1 Visual and Dimensional Inspection A visual and dimensional inspection shall be made of the sample Hoisting Unit, Portable, Electronic Equipment E-42/SRM-2, to verify compliance with this specification and to determine that accepted manufacturing practice is being used and first class workmanship is being maintained during production.

4.2.3.3.2 Static Overload. The sample Hoisting Unit, Portable, Electronic Equipment E-42/SRM-2, shall support a load of twice the rated capacity for a period of 5 minutes. This load shall be suspended on the hoist wire rope line to the limit of the manufacturer's facilities but not less than 6 inches. No breakage or permanent distortion of equipment parts shall occur during or after this test.

Source: https://assist.dla.mil -- Downloaded: 202640-19T17:26Z
Check the source to verify that this is the currentversion before use.

4.2.3.3.3 Dynamic Overload Test. The sample Hoisting Unit, Portable, Electronic Equipment E-42/SRM-2, shall be loaded to 150 percent of rated capacity and operated by hoisting and lowering to the full extent of the manufacturer's facilities but not less than 6 inches. This test shall be performed 15 times at the highest rate of speed of which the operator is capable. Hoists shall operate satisfactorily without evidence of permanent distortion or damage to any part. Excessive wear of any equipment parts shall be cause for rejection

4.2.4 Beam, Hoisting, Electronic Equipment MX-4124/SRM-2.

4.2.4.1 Qualification Tests. Qualification tests shall be conducted at a Government laboratory designated by the procuring activity. These tests shall consist of the test specified in 4.2.4.3.

4.2.4.2 Sampling for Lot Acceptance.

4.2.4.2.1 Lot For purposes of sampling, a lot shall consist of all Beams, Hoisting, Electronic Equipment MX-4124/SRM-2, offered for delivery at one time.

4.2.4.2.2 Lot Acceptance Test. One sample of the Beam, Hoisting, Electronic Equipment MX-4124/SRM-2, shall be selected from each lot by the Government inspector and shall be subjected to each of the following named tests, which shall be conducted or witnessed by the Government inspector, and the results of each test compared with this specification Failure to conform to this specification shall be counted as a defect and the equipment shall be rejected and the lot represented by the sample shall be rejected Rejected lots may be offered again for Government inspection tests provided all equipment in the lot have been retested by the contractor for test(s) causing rejection and all noncompliance corrected

Tests	Reference
Visual and Dimensional Inspection	4.2.4.3.1
Static Overload	4.2.4.3.2
Dynamic Overload	4.2.4.3.3

4.2.4.3 Test Procedure.

4.2.4.3.1 Visual and Dimensional Inspection A visual and dimensional inspection shall be made of the sample Beam, Hoisting, Electronic Equipment MX-4124/SRM-2, to verify compliance with this specification and to determine that accepted manufacturing practice is being used and first class workmanship is being maintained during production.

4.2.4.3.2 Static Overload. The sample Beam, Hoisting, Electronic Equipment MX-4124/SRM-2, shall support a load of twice the rated capacity for a period of 5 minutes. No breakage or permanent distortion of equipment parts shall occur during or after this test.

Source: https://assist.dla.mil -- Downloaded: 202640-19T17:26Z
Check the source to verify that this is the currentversion before use.

4.2.4.3.3 Dynamic Overload Test The sample Beam, Hoisting, Electronic Equipment MX-4124/SRM-2, shall be loaded 150 percent of rated capacity and operated by hoisting and lowering 15 times at the highest rate of speed of which the operator is capable. The Beam, Hoisting, Electronic Equipment MX-4124/SRM-2, shall sustain the load without evidence of permanent distortion or damage to any part. Permanent distortion or damage to any part shall be cause for rejection

5. PREPARATION FOR DELIVERY

5.1 Electronic Equipments of Test Sets, Target Control System of the AN/SRM Series.

5.1.1 Preservation and Packaging. Preservation and packaging shall conform to levels A or C of Specification MIL-P-17555, as specified in the contract or order

5.1.2 Packing. Packing shall conform to levels A, B, or C of Specification MIL-P-17555 as specified in the contract or order.

5.2 Handling Equipments of Test Sets, Target Control System of the AN/SRM Series.

5.2.1 Preservation, Packaging and Packing Preservation, packaging, and packing shall conform to level C of Specification MIL-P-7936

5.3 Marking. All interior packages and exterior shipping containers shall be marked to MIL-STD-129

6. NOTES

6.1 Intended Use The electronic equipment covered by this specification is intended to test electronic performance of the components comprising the Target Control System AN/SRW-4 and all revisions thereof. The handling equipment covered by this specification is intended for lifting, supporting, and transporting specific components, comprising the Target Control System AN/SRW-4 and all revisions thereof.

6.2 Test Values. Normal and limiting values of performance data shall be determined at input voltages of 220 ±2 volts ac and 115 ±1 volt ac as applicable These data are to be used in testing the equipment at installation points for compliance with minimum acceptable standard of performance.

6.3 Detailed Classification The detailed classification of each of the Test Sets Target Control System of the AN/SRM Series, is as follows

6.3.1 Test Set, Target Control System AN/SRM-2 The specific components comprising the Test Set Target Control System AN/SRM-2, are as follows

Items	Type Designation	Appl. Para.
Test Stand, Electronic Equipment	MT-2732/SRM-2	3.4.1.1
Test Set, Relay	TS-1752/SRM-2	3.4.1.2
Test Set, Radio Set Transfer Control	TS-1749/SRM-2	3.4.1.3

Source: https://assist.dla.mil -- Downloaded: 202610-19T17:26Z
Check the source to verify that this is the current version before use.

Items	Type Designation	Appl. Para.
Test Set, Transmitter	TS-1753/SRM-2	3.4.1.4
Test Set, Receiver	TS-1751/SRM-2	3.4.1.5
Test Set, Power Supply	TS-1750/SRM-2	3.4.1.6
Coder, Audio Frequency	KY-430/SRM	3.4.1.7
Coder, Audio Frequency	KY-431/SRM	3.4.1.8
Control, Coder	C-4123/SRM	3.4.1.8.4.4
Amplifier-Frequency Multiplier	AM-3311/SRM	3.4.1.9
Power Supply	PP-3373/SRM	3.4.1.10
Tool Kit, Target Control System	TK-142/SRM-2	3.4.1.11
Truck, Electronic Equipment	V-244 SRM-2	3.4.1.12
Hoisting Unit, Portable, Electronic Equipment	E-42/SRM-2	3.4.1.13
Beam, Hoisting, Electronic Equipment	MX-4124/SRM-2	3.4.1.14

6.3.2 Test Set, Target Control System, AN/SRM-3. The specific components comprising the Test Set, Target Control System AN/SRM-3, are as follows

Item	Type Designation	Appl. Para.
Cabinet, Electrical Equipment	CY-3584/SRM-3	3.4.2.1
Receiver, Radio	R-1135 SRM	3.4.2.2
Case, Crystal-Oven	CY-2923/U	3.4.2.3
Case, Crystal-Oven	CY-2924/U	3.4.2.4
Case, Crystal-Oven	CY-3690/SRM	3.4.2.5
Decoder, Audio Frequency	KY-432/SRM-3	3.4.2.6
Decoder, Audio Frequency	KY-433/SRM	3.4.2.7

6.3.3 Test Set, Target Control System AN/SRM-4. The specific components comprising the Test Set, Target Control System AN/SRM-4, are as follows

Source: https://assist.dla.mil -- Downloaded: 202640-19T17:26Z
Check the source to verify that this is the current version before use.

Items	Type Designation	Appl. Para.
Cabinet, Electrical Equipment	CY-3585/SRM-4	3.4.3.1
Receiver, Radio	R-1135/SRM	3.4.3.2
Case, Crystal-Oven	C-3690/SRM	3.4.3.3
Decoder, Audio Frequency	KY-433/SRM	3 4.3.4

6.3.4 Test Set, Target Control System AN/SRM-5. The specific components comprising the Test Set, Target Control System AN/SRM-5, are as follows

Items	Type Designation	Appl. Para.
Cabinet, Electrical Equipment	CY-3586/SRM-5	3.4.4.1
Coder, Audio Frequency	KY-430/SRM	3.4.4.2
Coder, Audio Frequency	KY-431/SRM	3.4.4.3
Control, Coder	C-4123/SRM	3.4.4.3.1
Amplifier-Frequency Multiplier	AM-3311/SRM	3.4.4.4
Power Supply	PP-3373/SRM	3.4.4.5

6.3.4 Test Set, Target Control System AN/SRM-6. The specified components comprising the Test Set, Target Control System AN/SRM-6, are as follows

Items	Type Designation	Appl. Para
Cabinet, Electrical Equipment	CY-3587/SRM-6	3.4.5.1
Coder, Audio Frequency	KY-431/SRM	3 4.5.2
Control, Coder	C-4123/SRM	3.4.5.2.1
Amplifier-Frequency Multiplier	AM-3311/SRM	3.4.5.3
Power Supply	PP-3373/SRM	3 4.5.4

6.4 Precedence of Documents. When the requirements of the contract, this specification, or applicable subsidiary specifications are in conflict, the following precedence shall apply:

(1) Contract. The contract shall have precedence over any specification.

(2) This Specification. This specification shall have precedence over all applicable subsidiary specifications. Any deviation from this specification,

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:26Z
Check the source to verify that this is the current version before use.

or from subsidiary specifications where applicable, shall be specifically approved in writing by the procuring activity.

(3) Referenced Specifications. Any referenced specification shall have precedence over all applicable subsidiary specifications referenced therein. All referenced specifications shall apply to the extent specified

6 5 Procurement Data The procedures used for conducting preproduction and acceptance tests shall be prepared by the contractor and submitted to the procuring activity for review and approval per paragraph 4.1.3.

NOTICE When Government drawings, specification, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever, and the fact that the Government may have formulated, furnished or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto

Source: https://assist.dla.mil -- Downloaded: 202610-19T17:26Z
Check the source to verify that this is the current version before use.

PECIFICATION ANALYSIS SHEET
WWEPS FORM 4121/3 (8-62)

FORM APPROVED
BUDGET BUREAU NO 45 R309

INSTRUCTIONS

is sheet is to be filled out by Government or contractor rsonnel involved in the use of this specification in ocurement of products for ultimate use by the activity own on the reverse of this sheet.

is sheet is provided for obtaining information which ll aid the activity shown in insuring that through use of this specification suitable products can be procured with a minimum amount of delay and at the least cost.

Comments and the return of this sheet will be appreciated.

Fold on dotted lines or reverse side staple in corner, and send to the activity shown

ECIFICATION (No and abbrev title)

GANIZATION	CITY	STATE

NTRACT NUMBER	QUANTITY OF ITEMS PROCURED	DOLLAR AMOUNT
		$

ATERIAL PROCURED UNDER A DIRECT GOVERNMENT CONTRACT		OR A SUBCONTRACT	

HAS ANY PART OF THIS SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
(If so give paragraph numbe and wording and recommendations for correcting the deficiencies)

COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF YES IN WHAT WAY

REMARKS *(Attach any pertinent data which may be of use in improving this specification If additional papers are attached send this form and papers in an envelope This form is addressed for use in window envelope when appropriate)*

BMITTED BY *(Print name and title)*	DATE

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:26Z
Check the source to verify that this is the current version before use.

Fold

DEPARTMENT OF THE NAVY
BUREAU OF NAVAL WEAPONS
WASHINGTON 25, D C

OFFICIAL BUSINESS

POSTAGE AND FEES PA
NAVY DEPARTMENT

Chief, Bureau of Naval Weapons (RREN-5)

Navy Department

Washington 25, D C.

Fold

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:26Z
Check the source to verify that this is the current version before use.