INCH-POUND

MIL-C-83723/76B
30 June 1992

SUPERSEDING
MIL-C-83723/76A
13 November 1975

MILITARY SPECIFICATION SHEET

CONNECTORS, ELECTRICAL, (CIRCULAR, ENVIRONMENT RESISTING), PLUG, (SINGLE HOLE MOUNT, BAYONET COUPLING, CRIMP PIN CONTACT), (SERIES III, CLASSES A, G, R, AND W)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

(B) The requirements for acquiring the connectors described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-C-83723.





FIGURE 1. Dimensions and configurations.

(B) denotes changes

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:22Z
Check the source to verify that this is the current version before use.



(B) Connector dimensions.

Shell size	A	G	H	J	L	U	V
8	.312	.352	.415 .424	.540 .545	.632	.776	.025
10	.388	.428	.517 .526	.662 .667	.760	.906	.031
12	.558	.598	.687 .696	.832 .837	.930	1.078	.031
14	.627	.667	.756 .765	.901 .906	.999	1.141	.031
16	.772	.794	.883 .892	1.028 1.033	1.126	1.266	.031
18	.860	.900	.989 .998	1.134 1.139	1.232	1.375	.031
20	.985	1.025	1.114 1.123	1.261 1.266	1.357	1.510	.031
22	1.110	1.150	1.239 1.248	1.384 1.389	1.482	1.625	.031
24	1.235	1.275	1.364 1.373	1.511 1.516	1.607	1.760	.031

FIGURE 1. Dimensions and configurations - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:22Z
Check the source to verify that this is the current version before use.

Inches	mm	Inches	mm	Inches	mm	Inches	mm	Inches	mm
.008	0.20	.177	4.50	.545	13.84	.900	22.86	1.235	31.37
.015	0.38	.182	4.62	.552	14.02	.901	22.89	1.239	31.47
.018	0.46	.185	4.70	.558	14.17	.906	23.01	1.248	31.70
.020	0.51	.198	5.03	.598	15.19	.930	23.62	1.261	32.03
.022	0.56	.200	5.08	.627	15.93	.985	25.02	1.266	32.16
.025	0.64	.204	5.18	.632	16.05	.989	25.12	1.275	32.39
.031	0.79	.211	5.36	.662	16.81	.998	25.35	1.357	34.47
.032	0.81	.259	6.58	.667	16.94	.999	25.37	1.364	34.65
.042	1.07	.312	7.92	.678	17.22	1.025	26.04	1.373	34.87
.046	1.17	.316	8.03	.687	17.45	1.028	19.84	1.375	34.93
.065	1.65	.320	8.13	.696	17.68	1.033	26.24	1.384	35.15
.069	1.75	.330	8.38	.756	19.20	1.078	27.38	1.389	35.28
.084	2.13	.352	8.94	.760	19.30	1.110	28.19	1.482	37.64
.090	2.29	.366	9.30	.765	19.43	1.114	28.30	1.510	38.35
.097	2.46	.383	9.73	.772	19.61	1.123	28.52	1.511	38.38
.101	2.57	.388	9.86	.776	19.71	1.126	28.60	1.516	38.51
.106	2.69	.415	10.54	.794	20.17	1.134	28.80	1.607	40.82
.112	2.84	.424	10.77	.832	21.13	1.139	28.93	1.625	41.28
.125	3.18	.428	10.87	.837	21.26	1.141	28.98	1.760	44.70
.138	3.51	.517	13.13	.860	21.84	1.150	29.21		
.144	3.66	.526	13.36	.883	22.43	1.230	31.24		
.170	4.32	.540	13.72	.892	22.66	1.232	31.29		

(B) NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Unless otherwise specified, tolerances are .005 (0.13 mm) for three place decimals and .01 (0.25 mm) for two place decimals and ±1 for all angles.
4. Rear accessory interchangeability dimensions shall be in accordance with MIL-C-83723.

REQUIREMENTS:

Dimensions and configuration: See figure 1.

(B) For insert arrangements, see MIL-STD-1554 and table I.

TABLE I. Insert arrangements requiring reduced diameters for lead-in chamfer on contact cavities as indicated.

Shell size	Insert arrangements	Contact cavities
8	(B) 03	1, 2, and 3
10	(B) 06	1, 2, 3, 4, 5, 6


FIGURE 1. Dimensions and configuration - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:22Z
Check the source to verify that this is the current version before use.

(B) For connector accessories, see MIL-C-85049.

This connector mates with MIL-C-83723/71 and 73.

(B) Part or Identifying Number (PIN) example:



CONCLUDING MATERIAL

(B) Custodians:
Army - CR
Navy - AS
Air Force - 85

(B) Review activities:
Army - AR, MI
Navy - EC
Air Force - 11, 15, 17, 80
DLA - ES

Preparing activity
Air Force - 85

Agent:
DLA - ES

(Project 5935-3728-09)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:22Z
Check the source to verify that this is the current version before use.