INCH-POUND

MIL-C-83723/98B
24 April 1992

SUPERSEDING
MIL-C-83723/98A
10 March 1983

MILITARY SPECIFICATION SHEET

CONNECTORS, ELECTRICAL, (CIRCULAR, ENVIRONMENT RESISTING), PLUG, (THREADED COUPLING, SELF-LOCKING, R.F.I. GROUNDING, CRIMP PIN CONTACTS), (SERIES III, CLASSES N AND S FIREWALL)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

B The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of specifications and Standards (DODISS) specified in the solicitation: MIL-C-83723.





FIGURE 1. Dimensions and configurations.

B denotes changes

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:24Z
Check the source to verify that this is the current version before use.



NOTE SEE TABLE I FOR CONTACT CAVITIES REQUIRING THIS DIMENSION

Connectors dimensions.

Shell size	A Thread UNRF-2B	B	(B) C	H	J	K	L	M	N
8	.562-24	.290	.025	.294	.405 .396	.575	.425	.967	12
10	.688-24	.388	.031	.428	.526 .517	.707	.546	1.093	15
12	.875-20	.558	.031	.598	.696 .687	.895	.711	1.170	21
14	.938-20	.627	.031	.667	.765 .756	.957	.785	1.310	24
16	1.062-18	.772	.031	.794	.892 .883	1.084	.912	1.500	30
18	1.188-18	.860	.031	.900	.998 .989	1.209	1.018	1.562	33
22	1.438-18	1.110	.031	1.150	1.248 1.239	1.459	1.268	1.812	39

FIGURE 1. Dimensions and configurations - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:24Z
Check the source to verify that this is the current version before use.

Inches	mm	Inches	mm	Inches	mm	Inches	mm
.005	0.13	.125	3.18	.517	13.13	.895	22.73
.007	0.18	.138	3.51	.526	13.36	.900	22.86
.008	0.20	.144	3.66	.558	14.71	.938	23.83
.015	0.38	.198	5.03	.562	14.27	.957	24.31
.018	0.46	.204	5.18	.575	14.60	.967	24.56
.020	0.51	.215	5.46	.598	15.19	.989	25.12
.022	0.56	.221	5.46	.627	15.93	.998	25.35
.025	0.64	.235	5.97	.667	16.94	1.084	27.53
.031	0.79	.243	6.17	.675	17.15	1.093	27.76
.032	0.81	.260	6.60	.687	17.45	1.110	28.19
.042	1.07	.290	7.37	.688	17.48	1.150	29.21
.046	1.17	.294	7.47	.696	17.68	1.170	29.71
.048	1.22	.330	8.38	.707	17.96	1.209	30.71
.065	1.65	.388	9.86	.756	19.20	1.239	31.47
.068	1.73	.396	10.05	.765	19.43	1.248	31.70
.069	1.75	.400	10.16	.772	19.61	1.280	32.51
.084	2.13	.405	10.29	.775	19.69	1.310	33.27
.090	2.29	.428	10.87	.794	20.17	1.459	37.06
.097	2.46	.433	11.00	.860	21.84	1.500	38.10
.101	2.57	.479	12.17	.875	22.23	1.562	39.67
.106	2.69	.500	12.70	.883	22.43	1.812	46.02
.112	2.84	.510	12.95	.892	22.66		

NOTES:
1. Dimensions are inches.
2. Metric equivalents (to the nearest .01 mm) are given for general information only and are based upon 1 inch = 25.4 mm.
3. Unless otherwise specified, tolerances are .005 (0.13 mm) for three place decimals and .01 (0.25 mm) for two place decimals; angular tolerance +1°0′ and +30′.
4. The dimensions showing relationship of coupling ring to shell apply only when coupling ring is in the fully forward position.
5. Rear accessory interchangeability dimensions shall be in accordance with MIL-C-83723.
6. Shell size 8 will not mate with MIL-C-26500 connectors.
7. (B) The centerline of indicated projection must be located on vertical centerline within 2.0°.

FIGURE 1. Dimensions and configuration - Continued.

REQUIREMENTS:

Dimensions and configuration: See figure 1.

This connector mates with MIL-C-83723/82 and 84.

(B) Insert arrangements and polarizing positions: See MIL-STD-1554 and table I.

TABLE I. Insert arrangements requiring reduced diameters for lead-in chamfer on outer row of the cavities as indicated.


Shell size	Insert arrangements	Contact cavities
8	(B) 03	1, 2, 3
(B) 10	06	1, 2, 3, 4, 5, 6

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:24Z
Check the source to verify that this is the current version before use.

(B) Connector accessories: See MIL-C-85049.

RFI spring strip shall have a minimum of six fingers per inch and shall point to the rear of connector.

(B) Part or Identifying Number (PIN) example:



CONCLUDING MATERIAL

Custodians:
Army - CR
Navy - AS
Air Force - 85

Review activities:
Army - AR, MI
Navy - EC
Air Force - 11, 15, 17, 99
DLA - ES

Preparing activity
Air Force - 85

Agent:
DLA - ES

(Project 5935-3728-31)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:24Z
Check the source to verify that this is the current version before use.