INCH-POUND


MIL-DTL-83796/1C
6 August 2014
SUPERSEDING
MIL-DTL-83796/1B
11 August 2008

DETAIL SPECIFICATION SHEET

HOSE ASSEMBLY, RUBBER, LIGHTWEIGHT, MEDIUM PRESSURE, FIELD ATTACHABLE END FITTINGS, FLARE TO FLARE

This specification is approved for use by all
Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-83796.



NOTE: In the Part or Identifying Number (PIN) add the letter “L” after style for lockwire holes, example: DL.

FIGURE 1. Hose assembly styles, field attachable fittings, flare-to-flare.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:41Z
Check the source to verify that this is the current version before use.

Hose assembly elbow fitting drop height. Elbow fitting drop height, A and B as shown on figure 2, are as specified in the applicable fitting specification sheet (see table I).


TABLE I. Hose assembly, field attachable fittings, HCOF, styles A thru M.

Style	Fitting ends MIL-DTL-83798		MIL-DTL-83797 hose cut off factor (HCOF) inches verses hose dash size number 1/										
	Fitting 1	Fitting 2	-03	-04	-05	-06	-08	-10	-12	-16	-20	-24	-32
A and B	M83798/1	M83798/1	1.48	1.48	1.52	1.68	1.94	2.10	2.22	2.68	3.08	3.40	4.08
C and D	M83798/1	M83798/2	1.68	1.81	1.90	2.06	2.28	2.49	2.83	3.37	3.85	4.23	4.94
E and F	M83798/1	M83798/3	1.53	1.68	1.74	1.91	2.12	2.32	2.70	3.27	3.77	4.17	4.90
G and H	M83798/2	M83798/2	1.88	2.14	2.28	2.44	2.62	2.88	3.44	4.06	4.62	5.06	5.80
J and K	M83798/2	M83798/3	1.73	2.01	2.12	2.29	2.48	2.71	3.31	3.96	4.54	5.00	5.78
L and M	M83798/3	M83798/3	1.58	1.88	1.96	2.14	2.30	2.54	3.18	3.86	4.46	4.94	5.72

1/ Example of hose cut-off factor: for a -04, 1/4 hose OD, 18-1/2 assembly length, style D, the bulk hose length = 18.50 - the HCOF = 18.50 -1.81 = 16.69. Bulk hose length required is 16.69.

Hose assembly length. The hose assembly length is calculated as shown on figure 2.


Hose assembly elbow fitting drop height. Elbow fitting drop height B and C is calculated as shown on figure 2. Drop height dimensions for B and C can be found in the applicable MIL-DTL-83798 slash sheet as specified in table I herein.




STYLE A or B

FIGURE 2. Hose assembly dimensions.


Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:41Z
Check the source to verify that this is the current version before use.



STYLE C or D




STYLE E or F




STYLE G or H

FIGURE 2. Hose assembly dimensions - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:41Z
Check the source to verify that this is the current version before use.



STYLE J or K



STYLE L or M


NOTES:

1. For straight hose assembly types the length “L” is to be measured between straight fitting end along a straight line parallel to hose, with hose laid out horizontally and straight, to straight fitting end.
2. For straight and 45° hose assembly types the length “L” is to be measured between sealing surface of fitting end along a straight line parallel to hose, with hose laid out horizontally and straight, to center line of 45° fitting end.
3. For straight and 90° hose assembly types the length “L” is to be measured between straight fitting end along a straight line parallel to hose, with hose laid out horizontally and straight, to center line of 90° fitting.
4. 45° and 90° hose assembly types the length “L” is to be measured between center line of 45° fitting end along a straight line parallel to hose, with hose laid out horizontally and straight, to center line of 90° fitting.
5. 90° hose assembly types the length “L” is to be measured between center line of 90° fitting end along a straight line parallel to hose, with hose laid out horizontally and straight, to center line of 90° fitting end.

FIGURE 2. Hose assembly dimensions - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:41Z
Check the source to verify that this is the current version before use.

Angular displacement. Angular displacement shall be as shown on figure 3.



NOTES:

1. Angular displacement for hose assemblies with elbow fittings on both ends shall have the angular displacement between elbows, measured counter-clockwise from the centerline of the nearest fitting, positioned at six-o' clock, to the centerline of the other fitting (see SAE-J517).
2. The near end of the connector shall be put in numerical order relative to the far end (see table I). Example: Near end adapter 45°, far end 90°.
3. Angular displacement shall be measured in degrees with a tolerance of ± 3° for lengths up to 2 feet (61 cm) and ± 5° for all lengths over 2 feet (61 cm).
4. The angular displacement shall be expressed in two digits number of degrees divided by 5, example 180°/5 = 36.
5. Making the angular determination in the wrong direction will result in an unacceptable part.

FIGURE 3. Elbow fitting drop height and angular alignment.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:41Z
Check the source to verify that this is the current version before use.

REQUIREMENTS

Hose assemblies shall be as specified on figures 1, 2, and 3.

Hose assembly length tolerance shall be in accordance with MIL-DTL-83796.

Fittings shall mate with parts in accordance with SAE-AS4395.

Size codes shall be as specified in table II.

TABLE II. Size code. 1/ 2/

Dash number		-03	-04	-05	-06	-08	-10	-12	-16
Size code		B	E	F	G	H	J	K	M
Hose OD reference	Inches fraction	3/16	1/4	5/16	3/8	1/2	5/8	3/4	1
	Inches decimal	.188	.250	.313	.375	.500	.625	.750	1.000
	mm	4.78	6.35	7.95	9.53	12.70	15.88	19.05	25.40

Dash number		-20	-24	-32
Size code		N	P	R
Hose OD reference	Inches fraction	1 1/4	1 1/2	2
	Inches decimal	1.250	1.500	2.000
	mm	31.75	38.10	50.80

1/ Dimensions are in inches.
2/ Metric equivalents are for information only.

Materials and finishes for hose fittings shall be in accordance with MIL-DTL-83798 and table III.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:41Z
Check the source to verify that this is the current version before use.

TABLE III. Nut and nipple material and finish code. 1/

Material and finish code	Material	Plating Finish
Blank	Steel (sizes -3, -4, and -5)	Cadmium plating in accordance with SAE-AMS-C-81562, type II, class 3 or SAE-AMS-QQ-P-416, type II, class 2.
	Aluminum (sizes -6 and above)	Anodize in accordance with MIL-A-8625, type II
A	Steel (sizes -3, -4, and -5)	Aluminum-nickel in accordance with ASTM F1136/F1136M, grade 3, NC
B	Aluminum (sizes -6 and above)	Anodize above with NAVAIR trivalent chromium pretreatment (TCP) in accordance with MIL-DTL-81706, type II, class 1A.
CN	Steel (sizes -3, -4, and -5)	Cadmium plating in accordance with SAE-AMS-C-81562, type II, class 3 or SAE-AMS-QQ-P-416, type II, class 2 with NAVAIR TCP in accordance with MIL-DTL-81706, type II, class 1A.
H	Steel (sizes -3, -4, and -5)	Zinc phosphate finish in accordance MIL-DTL-16232 type Z, class1 2/
J	Steel (sizes -3, -4, and -5)	Zinc plating in accordance with ASTM B633; type II or III, Fe/Zn 5, or ASTM B695, type II, class 5
N	Steel (sizes -3, -4, and -5)	NAVAIR TCP above.
R	Steel (sizes -3, -4, and -5)	Zinc plating in accordance with ASTM B633; type VI, Fe/Zn 5.
S	Corrosion resistant steel	No additional finish. Passivation in accordance with SAE-AMS2700, method 2
T 3/	Titanium (all sizes)	Annealed
V	Steel (sizes -3, -4, and -5)	Zinc-nickel in accordance with SAE-AMS2417, type 1
Z	Zinc any type above	PIN code F, G, H, J, R, V
ZN	Zinc any type above	PIN code F, G, H, J, R, V with NAVAIR TCP in accordance with MIL-DTL-81706, type II, class 1A.


1/ Shall be capable of withstanding minimum of 96 hours salt spray.
2/ Hexavalent chromium free.
3/ Titanium shall not be used in oxygen systems.

Trivalent wrenchability. When the finish has been damaged due to poor wrenchability, the surface of the connector shall be touched up using the brush plating process below. The term “trivalent wrenchability” is used to evaluate the ability of the finish to withstand abrasion from an excessive amount of wrenching.

a. Brush plating of hard chromium by electrodeposition shall be in accordance with SAE-AMS2451/5.
b. Brush plating of medium-hardness, low stress nickel by electrodeposition shall be in accordance with SAE-AMS2451/9.
c. Brush plating of NAVAIR TCP shall be in accordance with MIL-DTL-81706, type II, class 1A, material form 1 through 6, application method B. Example of a PIN: M817062A6B.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:41Z
Check the source to verify that this is the current version before use.

PIN example:



M83796/1H082F06T indicates - Hose assembly for 1/2 hose OD, 8 1/4 inches in length, style F, 30° between elbows, titanium alloy.

M83796/1H082FL06S indicates - Hose assembly for 1/2 hose OD, 8 1/4 inches in length, style F with lockwire holes, 30° between elbows, corrosion resistant steel.

Cadmium is not recommended. To the users of this document, it is recommended that the use of carbon steel material with cadmium plating be used only when other materials and finishes specified in this document cannot meet performance requirements.

Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Referenced documents. In addition to MIL-DTL-83796, this document references the following:

MIL-A-8625	ASTM B695	SAE-AMS2451/9
MIL-DTL-16232	ASTM F1136/F1136M	SAE-AMS2700
MIL-DTL-81706	SAE-AMS-C-81562	SAE-AS4395
MIL-DTL-83797	SAE-AMS-QQ-P-416	SAE-J517
MIL-DTL-83798	SAE-AMS2417	
ASTM B633	SAE-AMS2451/5	

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:41Z
Check the source to verify that this is the current version before use.

CONCLUDING MATERIAL

Custodians:
Army - AV
Navy - AS
Air Force - 99
DLA - CC

Preparing activity:
DLA - CC

(Project 4720-2014-018)

Review activities:
Army - AT
Navy - MC, SA, SH
Air Force 71, 85

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:41Z
Check the source to verify that this is the current version before use.