MILITARY SPECIFICATION

CONTROL, DEGAUSSING COMPASS COMPENSATING TYPE A-1

This amendment forms a part of Military Specification MIL-C-21640A(SHIPS), 12 February 1970 and is approved for use by the Naval Sea Systems Command and is available for use by all Departments and Agencies of the Department of Defense.

Page 2

3.4, add: "In case of conflict between information shown on the drawing and this specification, this specification shall govern."

3.8, delete and substitute:

"3.8 Wiring. Internal wiring shall be protected with insulation capable of withstanding continuous heat dissipation, from each of the three circuit assemblies, of 150 watts with all circuits operating simultaneously. All wiring shall be positioned, protected and secured to prevent chafing and damage of insulation of any of the conductors due to vibration. Wiring shall not interfere with any resistor adjustment. Electrical insulation shall be capable of satisfactory service with the heat dissipation specified herein."

Page 3

3.9: Add as fourth sentence "Resistor adjustments of each circuit shall be clearly identified with the associated output circuit on the terminal block."

3.10: Delete.

3.10.8, line 2: Delete "mounted" and substitute "riveted securely".

Add as item (e):

"(e) Degaussing coil symbol. Space shall be provided to etch or stamp a twelve letter coil symbol."

Page 4

3.16, delete and substitute:

"3.16 Designation and marking. A schematic wiring diagram shall be pasted on the inside of the cover of each compass compensating control box and shall be coated with varnish or shellac. All data and information required to be placed on components by Drawing S38106-3232364 may be applied by silk screening. Each resistor assembly shall be marked "fine adjustment" or "course adjustment" as applicable, and clearly identified with the associated output circuit on the terminal block."

4.2, line 2: Delete "4.5.8." and substitute "4.5.9.".

4.3, line 2: Delete "and 4.5.5." and substitute ", 4.5.5 and 4.5.9.".

4.5.1, line 2: Delete "3.6" and substitute "3.7".

Page 5

Add as paragraph 4.5.9:

"4.5.9 Electrical tests. With each 6-ohm load resistor connected at a time in accordance with the connection set up of 4.5.8, the voltage measured at the load shall be adjustable from $0^{+0.01}_{-0}$ to 12-volt $^{+0}_{-0.01}$ volts using a 12-volt power source."

Preparing activity:
Navy - SH
(Project 1075-N034)

FSC 1075

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T10:13Z
Check the source to verify that this is the current version before use.