INCH-POUND
MIL-C-21640B(SH)
8 July 1988
SUPERSEDING
MIL-C-21640A(SHIPS)
12 February 1970
(See 6.7)

MILITARY SPECIFICATION

# CONTROL, DEGAUSSING COMPASS COMPENSATING TYPE A-1

This specification is approved for use within the Naval Sea Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

## 1. SCOPE

1.1 Scope. This specification covers type A-1 degaussing compass compensating control assemblies which are used to provide control currents to degaussing compass compensating coil assemblies.

## 2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DoDISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

FEDERAL

QQ-B-613 - Brass, Leaded and Non-Leaded: Flat Products (Plate, Bar, Sheet, and Strip).

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, Naval Sea Systems Command, SEA 55Z3, Department of the Navy, Washington, DC 20362-5101 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 1075
DISTRIBUTION STATEMENT A Approved for public release; distribution unlimited

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T10:12Z
Check the source to verify that this is the current version before use.

MILITARY

| | |
|---|---|
| MIL-S-901 | - Shock Tests, H.I. (High-Impact); Shipboard Machinery, Equipment and Systems, Requirements for. |
| MIL-E-917 | - Electric Power Equipment, Basic Requirements (Naval Shipboard Use) |
| MIL-P-15024 | - Plates, Tags and Bands for Identification of Equipment. |
| MIL-E-15090 | - Enamel, Equipment, Light-Gray (Formula No. 111). |
| MIL-R-15109 | - Resistors and Rheostats, Naval Shipboard. |
| DOD-P-15328 | - Primer (Wash), Pretreatment (Formula No. 117 for Metals). (Metric) |
| MIL-E-17555 | - Electronic and Electrical Equipment, Accessories, and Provisioned Items (Repair Parts): Packaging of. |
| MIL-E-24142 | - Enclosures for Electrical Fittings and Fixtures, General Specification for. |
| MIL-E-24142/3 | - Enclosure for Electrical Fittings and Fixtures, Submersible, Size 6 by 9 (15-Foot). |

STANDARDS

MILITARY

| | |
|---|---|
| MIL-STD-108 | - Definitions of and Basic Requirements for Enclosures for Electric and Electronic Equipment. |
| MIL-STD-167-1 | - Mechanical Vibrations of Shipboard Equipment (Type I - Environmental and Type II - Internally Excited). |
| MIL-STD-202 | - Test Methods for Electronic and Electrical Component Parts. |
| MIL-STD-454 | - Standard General Requirements for Electronic Equipment. |
| MIL-STD-810 | - Environmental Test Methods and Engineering Guidelines. |

2.1.2 Other Government drawing. The following other Government drawing forms a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

DRAWING

NAVAL SEA SYSTEMS COMMAND (NAVSEA)

| | |
|---|---|
| S8106-3232364 | - Type A-1 Degaussing Compass Compensating Control Box. |

(Copies of specifications, standards, and drawings required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)



Source: https://assist.dla.mil -- Downloaded: 2026-10-19T10:12Z
Check the source to verify that this is the current version before use.

2.2 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein (except for associated detail specifications, specification sheets or MS standards), the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified in the contract or purchase order, a sample shall be subjected to first article inspection (see 4.3 and 6.3).

3.2 Materials. The materials shall be as specified herein and shall be the lightest practicable, consistent with the strength required for sturdiness, serviceability, safety, and reliability.

3.2.1 Nonmagnetic materials. Materials used in this equipment shall have a magnetic permeability not greater than 1.08 before fabrication and 2.0 after fabrication.

3.2.2 Recovered materials. Unless otherwise specified herein, all equipment, material, and articles incorporated in the products covered by this specification shall be new and may be fabricated using materials produced from recovered materials to the maximum extent practicable without jeopardizing the intended use. The term "recovered materials" means materials which have been collected or recovered from solid waste and reprocessed to become a source of raw materials, as opposed to virgin raw materials. None of the above shall be interpreted to mean that the use of used or rebuilt products is allowed under this specification unless otherwise specifically specified.

3.3 Construction. The construction, layout, and assembly of the units and their component parts shall be such as to facilitate quantity production. Jigs shall be used to position parts during welding and assembly operations.

3.4 Component parts. The type A-1 degaussing compass compensating control assembly shall be in accordance with Drawing 38106-3232364 and shall consist of six resistor assemblies (see 3.9) and one 8-terminal, terminal board, located within a lightweight, watertight enclosure (see 3.10).

3.4.1 Size and weight. In the construction of all components, emphasis shall be placed upon reduction of the weight of the unit. Mounting and overall dimensions shall conform to Drawing S8106-3232364.

3.4.2 Interchangeability. In no case shall parts be physically interchangeable or reversible unless such parts are also interchangeable or reversible with regard to function, performance and strength.

3.5 Painting. After all machining, welding, and brazing operations are completed, the exterior and interior surfaces of all enclosures shall have all rust or other visible corrosion products removed; shall be thoroughly cleaned of all grease, oil, and dirt by solvent wiping, vapor degreasing, or caustic washing and rinsing; and shall then be painted as specified in 3.5.1 and 3.5.2.



Source: https://assist.dla.mil -- Downloaded: 2026-10-19T10:12Z
Check the source to verify that this is the current version before use.

3.5.1 Primer. One coat of primer, manufactured in accordance with DOD-P-15328 shall be applied as a continuous film 0.0002 to 0.0005 inch thick.

3.5.2 Enamel. Two coats of gray enamel, conforming to type II, class 2 of MIL-E-15090, shall be applied as continuous films approximately 0.001 inch thick. Class 2 (semigloss) shall be applied on permanently installed equipment and class 1 (gloss) followed by a heavy coat of hard wax shall be applied on portable equipment.

3.6 Rounded corners and edges. Edges and corners of external surfaces, normally exposed or to be painted, shall be rounded. Sharp surfaces of any kind shall be avoided.

3.7 Insulation distances. The minimum creepage and clearance distances between electric circuits or between any electric circuit and ground shall be as follows:

Clearance in air - 1/4 inch.
Surface creepage - 1/4 inch.

Creepage and clearance distances shall be as defined in MIL-E-917.

3.8 Wiring. Internal wiring shall be protected with insulation that shall withstand continuous heat dissipation, from each of the three circuit assemblies, of 150 watts with all circuits operating simultaneously. Wiring shall be positioned, protected and secured to prevent chafing and damage of insulation of any of the conductors due to vibration. Wiring shall not interfere with any resistor adjustment. Electrical insulation shall produce satisfactory service with the heat dissipation specified herein.

3.9 Resistor assemblies. The control assembly shall consist of six resistor assemblies comprised of three coarse adjustment variable resistors and three fine adjustment variable resistors. The resistors shall be grouped to form three circuits. Each circuit shall include one coarse adjustment and one fine adjustment resistor. Resistor adjustments of each circuit shall be clearly identified with the associated output circuit on the terminal block. Circuitry and circuit components, and assemblies shall be constructed in accordance with and interchangeable with those shown on Drawing S8106-3232364.

3.9.1 Resistors. The resistors used in each resistor assembly shall conform to MIL-R-15109. They shall be constructed for continuous duty and shall operate under rated conditions.

3.9.1.1 Electrical and mechanical characteristics. The electrical and mechanical characteristics of the resistor units shall approximate that shown in table I.


Source: https://assist.dla.mil -- Downloaded: 2026-10-19T10:12Z
Check the source to verify that this is the current version before use.

TABLE I. Electrical and mechanical characteristics.

| Resistor | Tube dimensions (inches) | | | Allowable resistance variations | Ohms per winding | Number turns per | Length of tube covered by winding | Winding ampere capacity (continuous) |
|---|---|---|---|---|---|---|---|---|
| | Length | Od | Id | | | | | |
| 15 ohm | 2-3/4 | 9/16 | 3/8 | Percent ± 10 | 15 | 55 | Percent 100 | 2.0 |
| 300 ohm | 2-3/4 | 1-1/8 | 3/4 | -10, +20 | 260 | 77 | 50 | 0.40 |
| | | | | | 40 | 33 | 50 | 1.30 |

3.9.1.2 Terminal block. An 8-terminal, terminal block shall be provided in the control assembly. Materials used in this block shall withstand the heat dissipation specified in 3.8. Creepage and clearance distances involved shall be in accordance with 3.7. Each terminal shall be marked to indicate its function in the electrical circuit. The terminal board shall have an identification strip and shall be marked in accordance with Drawing S8106-3232364.

3.10 Enclosure. The enclosure shall be constructed in accordance with MIL-E-24142 and MIL-E-24142/3. The enclosure material shall be brass in accordance with QQ-B-613. This enclosure shall be as lightweight as practicable.

3.10.1 Degree of enclosure. The degree of enclosure shall be watertight as specified in MIL-STD-108.

3.10.2 Enclosure mounting. The enclosure shall be constructed for bulkhead mounting. Mounting dimensions shall be in accordance with Drawing S8106-3232364.

3.10.3 Accessibility. The enclosure shall be constructed for maximum accessibility for repair and replacement of parts. The resistor assemblies shall be mounted to permit replacement of those components likely to become defective without extensive disassembly of other parts and assemblies within the enclosure.

3.10.4 Cover bolts. The enclosure cover bolts shall be nonremovable.

3.10.5 Condensation drain. A removable plug shall be provided in the bottom of the enclosure for draining any condensate.

3.10.6 Terminal tubes. Terminal tubes shall not be provided by the contractor.

3.10.7 Identification plate. A type A identification plate in accordance with MIL-P-15024 shall be riveted securely on the outside of the enclosure cover. The identification plate shall be in general accordance with the sample shown in MIL-P-15024 and shall contain the following information:



Source: https://assist.dla.mil -- Downloaded: 2026-10-19T10:12Z
Check the source to verify that this is the current version before use.

(a) Compass compensating control box, type A-1.
(b) National stock number H1075-511-7174.
(c) Manufacturer.
(d) Contract number.
(e) Degaussing coil symbol (space shall be provided to etch or stamp a 12-letter coil symbol).

3.11 Temperature and humidity. The type A-1 control assembly shall provide satisfactory, continuous operation in any ambient temperature between the limits of minus 20 and 180 degrees Fahrenheit (°F) and in any relative humidity of 95 percent or less. This equipment shall be suitable for extended storage in any ambient temperature between the limits of minus 65 and 180°F.

3.12 Salt spray. The equipment shall withstand the salt spray test specified in 4.6.4.

3.13 Dielectric strength. The equipment shall withstand the dielectric test voltages specified in 4.6.5.

3.14 Vibration. The equipment shall withstand the vibration test specified in 4.6.6 without mechanical or electrical damage.

3.15 Shock. The equipment shall withstand the H.I. shock test specified in 4.6.7 without mechanical or electrical damage.

3.16 Designation and marking. A schematic wiring diagram shall be pasted on the inside of the cover of each compass compensating control box and shall be coated with varnish or shellac. Information required to be placed on components by Drawing S38106-3232364 may be applied by silk screening. Each resistor assembly shall be marked "fine adjustment" or "course adjustment" as applicable, and clearly identified with the associated output circuit on the terminal block.

3.17 Workmanship. Workmanship shall be in accordance with requirement 9 of MIL-STD-454. The equipment shall comply with the visual examination specified in 4.5.

## 4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies


Source: https://assist.dla.mil -- Downloaded: 2026-10-19T10:12Z
Check the source to verify that this is the current version before use.

submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.1.2 Inspection system. When specified in the contract or order, an inspection system program plan shall be prepared (see 6.2.2).

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

(a) First article inspection (see 4.3).
(b) Quality conformance inspection (see 4.4).

4.3 First article inspection. First article inspection shall consist of the examination and tests specified in 4.5 and 4.6.1 through 4.6.9. When specified in the contract or order, a first article inspection procedure and report shall be prepared (see 6.2.2).

4.4 Quality conformance inspection. Each unit offered for delivery on the contract or order shall be subjected to the examination and tests specified in 4.5, 4.6.1, 4.6.5 and 4.6.9.

4.5 Visual examination. The completed equipment shall be given a thorough visual examination to determine that it conforms to the applicable specifications and approved working drawings with respect to material, finish, workmanship, construction, assembly, dimensions, weight and marking of identification and information plates. The examination shall be limited to those tests that may be performed without disassembling the component in such a manner that its performance, durability or appearance would be affected. The visual examination shall include a check of all operating controls, circuit functions, adjustments, and an operating test of the complete equipment (see 4.6.8).

4.6 Test methods.

4.6.1 Creepage and clearance distance. Creepage and clearance distances shall be demonstrated by actual measurement and shall conform to the requirements of 3.7.

4.6.2 Enclosure. The component enclosures shall be tested for water-tightness (3-foot). The test for waterproof enclosures shall be as specified in 4.6.2.1 through 4.6.2.4.

4.6.2.1 The enclosure shall be submerged under a 3-foot head of standard sea water, specific gravity 1.025, at approximately 15 degrees Celsius for 1 hour.

4.6.2.2 After immersion for 1 hour, the equipment shall be removed from the water and shall drain for 1 hour while being held in the position in which it would normally be mounted on board ship.

4.6.2.3 The equipment shall then be energized in the normal manner for 1 hour.



Source: https://assist.dla.mil -- Downloaded: 2026-10-19T10:12Z
Check the source to verify that this is the current version before use.

4.6.2.4 Four hours after the equipment has been removed from the water it shall be disassembled and inspected. There shall be no evidence of water pockets and no evidence of corrosion.

4.6.3 Temperature and humidity. The equipment shall be operated in the ambient temperatures and humidity as specified in 3.11 to determine any deleterious effect therefrom. The test unit shall be subjected to a series of 15 temperature cycles within the range of temperatures specified in 3.11. Temperature tests shall be conducted in accordance with methods 501.2 and 502.2 of MIL-STD-810. Humidity test shall be conducted in accordance with method 507.2 of MIL-STD-810.

4.6.4 Salt spray. A salt spray test shall be conducted in accordance with method 101D of MIL-STD-202, test-condition letter B.

4.6.5 Dielectric strength. A dielectric strength test shall be conducted in accordance with method 301 of MIL-STD-202. The test shall be performed by applying a test voltage of 1500 volts root mean square between the electrical circuits and the enclosure.

4.6.6 Vibration. Vibration tests shall be performed on the completed assembly in accordance with the type I environmental test of MIL-STD-167-1. After completion of tests the assembly shall be examined for evidence of leakage or physical damage.

4.6.7 Shock. Shock tests shall be conducted on a shock-testing machine for lightweight equipment in accordance with grade A, class 1, type A of MIL-S-901 (see 3.15). Failure to perform principal functions shall result in rejection. Failure to perform principal functions is defined as follows:

(a) Breakage of any parts, including mounting bolts. Minor chipping or distortion of parts will be accepted when such chipping or distortion cannot in any way impair the operation or performance requirements of the equipment.
(b) Appreciable distortion of any parts including the case and mounting appendages.
(c) Insulation resistance values lower than those permitted by this specification.
(d) Failure to pass the dielectric strength test.
(e) Failure to pass the operating test.

4.6.8 Operating test. The unit shall be given an operating test as follows: A 6-ohm load resistor shall be connected across each of the three pairs of output terminals and the unit then connected to a 12-volt direct current power source. Each of the three individual circuits in the unit shall then be adjusted to simultaneously supply a 1.0 ampere output current to the 6-ohm load resistor. The unit shall then be operated in this condition, with the cover closed, for 2 hours. The unit shall be observed during this test for any evidence of hot spots or other indication of unsatisfactory operation.



Source: https://assist.dla.mil -- Downloaded: 2026-10-19T10:12Z
Check the source to verify that this is the current version before use.

4.6.9 Electrical tests. With each 6-ohm load resistor connected at a time in accordance with the connection set up of 4.6.8, the voltage measured at the load shall be adjustable from plus 0.01, minus 0 to plus 0, minus 0.01 volts using a 12-volt power source.

4.7 Inspection of packaging. Sample packages and packs, and the inspection of the preservation-packaging, packing and marking for shipment and storage shall be in accordance with the requirements of section 5 and the documents specified therein.

5. PACKAGING

(The packaging requirements specified herein apply only for direct Government acquisition. For the extent of applicability of the packaging requirements of referenced documents listed in section 2, see 6.5.)

5.1 Preservation, packing and marking. The equipment and accessories shall be preserved level A or C; packed by level A, B or C and marked as specified in the contract or order (see 6.2.1) in accordance with MIL-E-17555. Method II shall apply for level A preservation of the equipment.

5.2 Use of polystyrene (loose-fill) material.

5.2.1 For domestic shipment and early equipment installation and level C preservation and packing. Unless otherwise specified in the contract or order (see 6.2.1), use of polystyrene (loose-fill) material for domestic shipment and early equipment installation and level C preservation and packing applications such as cushioning, filler and dunnage is prohibited. When specified, unit packages and containers (interior and exterior) shall be marked and labeled as follows:

"CAUTION

Contents cushioned, etc., with polystyrene (loose-fill) material.
Not to be taken aboard ship.
Remove and discard loose-fill material before shipboard storage.
If required, recushion with cellulosic material bound fiber,
fiberboard, or transparent flexible cellular material."

5.2.2 For level A preservation and level A and B packing. Use of polystyrene (loose-fill) material is prohibited for level A preservation and level A and B packing applications such as cushioning, filler and dunnage.

6. NOTES

6.1 Intended use. These control assemblies control the coil assemblies used on Naval vessels to produce a magnetic field at the magnetic compass which is equal and opposite to that produced at the same position by the degaussing coils.



Source: https://assist.dla.mil -- Downloaded: 2026-10-19T10:12Z
Check the source to verify that this is the current version before use.

6.2 Ordering data.

6.2.1 Acquisition requirements. Acquisition documents should specify the following:

(a) Title, number, and date of this specification.
(b) When first article inspection is required (see 3.1).
(c) Level of preservation, packing and marking (see 5.1).
(d) When polystyrene (loose-fill) material is approved (see 5.2.1).

6.2.2 Data requirements. When this specification is used in an acquisition and data are required to be delivered, the data requirements identified below shall be developed as specified by an approved Data Item Description (DD Form 1664) and delivered in accordance with the approved Contract Data Requirements List (CDRL), incorporated into the contract. When the provisions of DoD FAR Supplement, Part 27, Sub-Part 27.475-1 (DD Form 1423) are invoked and the DD Form 1423 is not used, the data specified below shall be delivered by the contractor in accordance with the contract or purchase order requirements. Deliverable data required by this specification are cited in the following paragraphs.

| Paragraph no. | Data requirement title | Applicable DID no. | Option |
|---|---|---|---|
| 4.1.2 | Inspection system program plan | DI-R-4803 | ---- |
| 4.3 | First article inspection procedure | DI-T-4901 | ---- |
| 4.3 | First article inspection report | DI-T-4902 | ---- |

(Data item descriptions related to this specification, and identified in section 6 will be approved and listed as such in DoD 5010.12-L., AMSDL. Copies of data item descriptions required by the contractors in connection with specific acquisition functions should be obtained from the Naval Publications and Forms Center or as directed by the contracting officer.)

6.2.2.1 The data requirements of 6.2.2 and any task in sections 3, 4, or 5 of this specification required to be performed to meet a data requirement may be waived by the contracting/acquisition activity upon certification by the offeror that identical data were submitted by the offeror and accepted by the Government under a previous contract for identical item acquired to this specification. This does not apply to specific data which may be required for each contract regardless of whether an identical item has been supplied previously (for example, test reports).

6.3 First article. When a first article inspection is required, the item should be a first article sample. The first article should consist of one unit. The contracting officer should include specific instructions in acquisition documents regarding arrangements for examinations, approval of first article test results and disposition of first articles. Invitations for bids should provide that the Government reserves the right to waive the requirement for samples for


Source: https://assist.dla.mil -- Downloaded: 2026-10-19T10:12Z
Check the source to verify that this is the current version before use.

first article inspection to those bidders offering a product which has been previously acquired or tested by the Government, and that bidders offering such products, who wish to rely on such production or test, must furnish evidence with the bid that prior Government approval is presently appropriate for the pending contract.

6.4 Provisioning. Provisioning Technical Documentation (PDT), spare parts, and repair parts should be furnished as specified in the contract.

6.4.1 When ordering spare parts or repair parts for the equipment covered by this specification, the contract should state that such spare parts and repair parts should meet the same requirements and quality assurance provisions as the parts used in the manufacture of the equipment. Packaging for such parts should also be specified.

6.5 Sub-contracted material and parts. The packaging requirements of referenced documents listed in section 2 do not apply when material and parts are acquired by the contractor for incorporation into the equipment and lose their separate identity when the equipment is shipped.

6.6 Subject term (key word) listing.

Heat dissipation
Nonmagnetic material
Resistor assemblies

6.7 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Preparing activity:
Navy - SH
(Project 1075-N055)



Source: https://assist.dla.mil -- Downloaded: 2026-10-19T10:12Z
Check the source to verify that this is the current version before use.

☆ U.S. GOVERNMENT PRINTING OFFICE: 1988 - 604-033/92855

# STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

*(See Instructions – Reverse Side)*

| 1. DOCUMENT NUMBER | 2. DOCUMENT TITLE |
|---|---|
| MIL-C-21640B(SH) | CONTROL, DEGAUSSING COMPASS COMPENSATING TYPE A-1 |

**3a. NAME OF SUBMITTING ORGANIZATION**

**b. ADDRESS** *(Street, City, State, ZIP Code)*

**4. TYPE OF ORGANIZATION** *(Mark one)*

- ☐ VENDOR
- ☐ USER
- ☐ MANUFACTURER
- ☐ OTHER *(Specify)*: _____

**5. PROBLEM AREAS**

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

**6. REMARKS**

| 7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional | b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional |
|---|---|
| c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional | 8. DATE OF SUBMISSION *(YYMMDD)* |

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

*(TO DETACH THIS FORM, CUT ALONG THIS LINE.)*

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T10:12Z
Check the source to verify that this is the current version before use.

**INSTRUCTIONS:** In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

*NOTE:* This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

*(Fold along this line)*

*(Fold along this line)*

DEPARTMENT OF THE NAVY

COMMANDER
NAVAL SEA SYSTEMS COMMAND (SEA 55Z3)
DEPARTMENT OF THE NAVY
WASHINGTON, DC 20362-5101

**OFFICIAL BUSINESS**
**PENALTY FOR PRIVATE USE $300**

**BUSINESS REPLY MAIL**
FIRST CLASS PERMIT NO. 12503 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE NAVY

COMMANDER
NAVAL SEA SYSTEMS COMMAND (SEA 55Z3)
DEPARTMENT OF THE NAVY
WASHINGTON, DC 20362-5101

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T10:12Z
Check the source to verify that this is the current version before use.