[INCH-POUND]
A-A-52195
30 December 1994

COMMERCIAL ITEM DESCRIPTION

BRACE, ANKLE, PARACHUTISTS

The General Services Administration has authorized the use of this commercial item description, for all federal agencies.

1. SCOPE

1.1 This commercial item description describes an ankle brace system used by parachutists (see 2.1 and 7.1).

1.2 The ankle braces are intended for use by military personnel for the prevention of ankle injuries when performing parachutist training or in actual airborne exercises and operations. It is intended that the braces would be used repeatedly as required.

2. CLASSIFICATION

2.1 The ankle brace systems shall conform to the following sizes (see 3.1.4 and 7.1).

Size I - Small
Size II - Medium
Size III - Large

Beneficial comments, recommendations, additions, deletions, clarifications,etc. and any other data which may improve this document should be sent to: Commander, U.S. Army Natick Research, Development, and Engineering Center, ATTN: SATNC-UC, Natick, MA 01760-5014.

AMSC N/A FSC 1670

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:07Z
Check the source to verify that this is the current version before use.

3. SALIENT CHARACTERISTICS

3.1 Operational characteristics (see 5.1). The ankle brace system shall fit on the outside and be compatible with the standard military combat boot. It shall be capable of being quickly and easily adjusted.

3.1.1 Vertical height adjustment. The brace shall be capable of being adjusted to the vertical height of the boot by means of a bottom fastening strap. Once adjusted it will not need to be undone for either removal or reapplication to the same size boot.

3.1.2 Ankle support adjustment. Each brace will be capable of fitting and supporting the vertical part of the boot and ankle when fastened around the ankle of the individual.

3.1.3 Mounting and removal. The braces must be able to be quickly and easily mounted and removed by the individual with a minimum of effort.

3.1.4 Size. The braces shall come in three sizes. The range of sizes for the brace shall be such that they fit the 5th through the 95th percentile of soldiers (see 2.1 and 7.1).

3.2 System configuration. Each size of the ankle brace system shall come in pairs complete with a positively marked right and left brace.

3.3 Design and construction. The design and construction of the ankle braces shall conform in all respects to the requirements specified herein. (see 5.1).

3.3.1 Brace shell design. The brace shell shall be of one-piece construction of molded impact resistant material and anatomically shaped to accommodate the ankle. It shall have two upright sides which are connected at the bottom by a horizontal strip which fits around the heel of the boot.

3.3.2 Straps and buckles. The straps and buckles shall be of nylon. All straps shall be constructed with positive locking hook and loop fastening tape closures. The straps and buckles shall be the same color as the brace shell (see 7.1).

3.3.2.1 Vertical adjustment straps. The vertical adjustment strap will have a buckle adjustment with a hook and loop fastening tape locking end on the strap. The buckle will be securely bolted and/or riveted to the brace. The strap will be bolted to the brace and be able to be replaced.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:07Z
Check the source to verify that this is the current version before use.

3.3.2.2 Ankle adjustment straps. There will be two ankle adjustment straps, one upper and one lower. Each strap will have an adjusting buckle and a hook and loop fastening tape locking end on the strap. Each strap will be securely rived to the brace.

3.3.3 Air bladders. There will be an air bladder permanently attached to the inside of each side of the shell to provide the maximum amount of support and comfort.

3.4 Mounting and adjusting instructions. A single sheet providing mounting and adjusting instructions will be provided with each system.

3.5 Workmanship. The finished braces shall conform to the quality of product established by this document. The occurrence of defects shall not exceed the contractor's own quality assurance standards defined by the technical data in the bid package.

3.6 Bid samples. When required, offerors shall submit samples of their intended production. The bid sample will consist of units independently developed. The bid samples will be analyzed and evaluated by the Government. Evaluation criteria and basis of award are contained in the solicitation. The bid samples will be retained by the Government. One (1) bid sample approved by the contracting agency will serve as a manufactured standard for the corresponding production items delivered under the contract. Offerors are advised that the bid sample does not relieve the successful offeror of his responsibility to perform in accordance with the commercial item description specified above.

4. REGULATORY REQUIREMENTS

4.1 The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR).

5. QUALITY ASSURANCE PROVISIONS

5.1 Certification. The contractor shall certify and maintain substantiating evidence that the product offered meets the salient characteristics and requirements of this Commercial Item Description, and that the product conforms to the producer's own drawings, specifications, standards, and quality assurance practices, and is the same product offered for sale in the commercial marketplace. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

Source: https://assist.dla.mil -- Downloaded: 202610-26T09:07Z
Check the source to verify that this is the current version before use.

5.2 Metric product. Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch-pound units, provided they fall within specified tolerances using conversion tables contained in the latest revision of Federal Standard No. 376, and all other requirements of this CID are met. If a product is manufactured to metric dimensions and those dimensions exceed the tolerances specified in the inch-pound units, a request should be made to the contracting officer to determine if the product is acceptable. The contracting officer has the option of accepting or rejecting the product.

5.3 Market acceptability criteria. The item offered must have been sold to the commercial market or to the Government, and the contractor shall certify and provide supporting documentation as to the serviceability and the long term (one year) availability of all necessary maintenance and logistics support parts and materials.

5.4 Warranty. The item offered shall include the standard warranty given to the commercial market.

6. PACKAGING

6.1 Preservation and packing. Preservation and packing shall be commercial preservation and packing in accordance with ASTM D 3951 or as specified in the contract or purchase order.

6.2 Palletization. When specified (see 7.1) the brace systems shall be palletized in accordance with ASTM D 4649 and ASTM D 4675.

6.3 Marking. In addition to any special marking required by the contract or order, unit packs, shipping containers and palletized unit loads shall be marked in accordance with ASTM D 3951.

7. NOTES

7.1 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this document.
b. Size required (see 2.1).
c. Colors of ankle brace systems
d. Selection of applicable packaging and packing (see 6.1).
e. Palletization when required (see 6.2).

Source: https://assist.dla.mil -- Downloaded: 202610-26T09:07Z
Check the source to verify that this is the current version before use.

7.2 Sources of documents.

7.2.1 Sources for nongovernment association documents.

ASTM D 3951 - Standard Practice for Commercial Packaging

ASTM D 4649 - Standard Guide for Selection of Stretch, Shrink, and Net Wrap Materials

ASTM D 4675 - Standard Guide for Selection and Use of Flat Strapping Materials

The above are available from:
The American Society for Testing and Materials (ASTM)
1916 Race Street
Philadelphia, PA 19103-1187

7.2.2 Sources of governmental documents. Copies of Military and Federal documents are available from:

Standardization Documents Order Desk
Bldg. 4D
700 Robbins Avenue
Philadelphia, PA 19111-5094

7.3 Known sources for the item(s) described:

Aircast, Inc.
P.O. Box 709
92 River Road
Summit, NJ 07902-0709

7.4 Part identification number (PIN). The following part identification numbering procedure is for government purposes and does not constitute a requirement for the offeror/contractor.

This example describes a part numbering system for CID A-A-52195.

AA 52195 - I
- I: Size
- AA 52195: CID Number

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:07Z
Check the source to verify that this is the current version before use.

MILITARY INTERESTS:

Custodian

Army - GL
Navy - AS
Air Force - 99

Review activities

Army - AV
Navy - MC
Air Force - 82

CIVIL AGENCY COORDINATING ACTIVITY:

GSA - FSS

PREPARING ACTIVITY:

Army - GL

Project 1670-0833

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:07Z
Check the source to verify that this is the current version before use.