A-A-52206B
April 10, 2002
SUPERSEDING
A-A-52206A
September 28, 2001

COMMERCIAL ITEM DESCRIPTION

OPENERS, CAN, HAND AND MOUNTED

The General Services Administration has authorized the use of this commercial item description for all federal agencies.

1. SCOPE.

1.1 Scope. This commercial item description (CID) covers hand-held, wall-mounted, and table- mounted manually operated can openers.

1.2 Intended use. The can openers are intended to open round and oblong standard food cans, and square food cans with corner radii over 1½ inches. The type I, classes 1 and 2 openers and type II openers are used for opening all round cans up to and including No. 10 cans. The type III and type IV openers are used to open all round cans up to and including No. 12 cans. The grade A openers are for general use. The grade B openers are used on ships and in areas where severe corrosive conditions prevail.

2. CLASSIFICATION.

2.1 Classification. The can openers shall conform to the following types, classes and grades as specified (see 7.1).

Type I - Hand operated, household, portable
Class 1 - Lever-operated, with bottle opener
Class 2 - Wing-operated feed wheel

Grade A - Standard commercial quality
Grade B - Corrosion-resisting steel

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, U.S. Army Soldier and Biological Chemical Command, ATTN: AMSSB-RCF-S(N), Natick, MA 01760-5018 by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:08Z
Check the source to verify that this is the current version before use.

Type II - Wall-mounted with magnetic lid lifter
Grade A - Standard commercial quality
Grade B - Corrosion-resisting steel

Type III - Table mounted heavy duty, with cutting wheel
Grade A – Standard commercial quality

Type IV - Table-mounted, heavy duty, with cutting blade
Grade B - Corrosion-resisting steel
(a) – with bolt-on base
(b) – with clamp-on base
(c) – with no base

3. SALIENT CHARACTERISTICS

3.1 Design. The openers shall be of the types, classes, and grades as specified in 3.1.1 through 3.1.5. All parts that come in contact with, or may be contaminated by food, shall be easily cleaned.

3.1.1 Type I, class 1 opener. The type I, class 1 opener shall be grade A or grade B and shall be hand-operated by leverage. The opener shall have a blade, a cap opener, a handle, and a can bead guide. The handle shall have rounded surfaces to provide comfortable operation. The type I, class 1 openers shall open all size cans up to and including No. 10 round. The opener shall show no evidence of breaking, parts separation, or permanent deformation when load and performance are tested as specified in 5.3.1.

3.1.2 Type I, class 2 opener. The type I, class 2 opener shall be grade A or grade B and shall be hand-operated by turning a wing-operated feed wheel to force the can top against the cutting wheel. The feed and cutting wheels shall each have an interlocking gear which together functions to turn the cutting wheel whenever the feed wheel turns. The gears shall provide a positive rotation of the cutting wheel upon operations of the wing crank. The feed wheel shall be case hardened to a depth of 0.008 inch or greater to a Rockwell 15-N hardness of 89 to 90. The cutting wheel shall be case hardened to a depth of 0.006 inch or greater to Knoop hardness ranges as follows: 0.002 inch = 600-700, 0.004 inch = 500-700, 0.006 inch = 500-700. The opener shall consist of a body with a can guide, a wing-operated feed wheel, a cutting wheel, and a plier-type pressure device to force the cutting wheel through the can top and hold the can in the cutting position while pressure is applied. The opener shall have an integral bottle cap opener. The handle width shall be a minimum of 0.4 inches. The handles shall have rounded surfaces to provide comfortable operation. The handle padding material shall be fully enclosed around the opener and have no open gaps which allow food accumulation. The type I, class 2 openers shall remove the tops from all size cans up to and including No. 10 round, and shall support cans which weigh up to 8 pounds in the cutting position. The opener shall operate freely without binding and shall show no evidence of parts separation, breaking, or permanent deformation and shall remove the tops from cans without producing metal slivers, chips, jagged or irregular edges when tested as specified in 5.3.2.

3.1.3 Type II opener. The type II opener shall be grade A or grade B and shall be wall-mounted and operated by a hand crank. The opener shall consist of a wall-mounting bracket, an extension arm, a geared cutting wheel, a geared feed wheel, a crank, a cutting wheel lever, and a magnetic lid lifter. The feed and cutting wheels shall each have an interlocking gear which together function to turn the cutting wheel whenever the feed wheel turns. The gears shall provide a positive rotation of the cutting wheel

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:08Z
Check the source to verify that this is the current version before use.

upon operation of the wing crank. The feed wheel shall be case hardened to a depth of 0.008 inch or greater to a Rockwell 15-N hardness of 89 to 90. The cutting wheel shall be case hardened to a depth of 0.006 inch or greater to Knoop hardness ranges as follows: 0.002 inch = 600-700, 0.004 inch = 550-700, 0.006 inch = 500-700. The type II opener shall remove the tops from all size cans up to and including No.10 round, and shall support cans which weigh up to 8 pounds, in the cutting position. The opener shall operate freely without binding and shall show no evidence of parts separation, breaking, or permanent deformation and shall remove the tops from cans without producing metal slivers, chips, jagged or irregular edges when tested as specified in 5.3.3.

3.1.4 Type III opener. The type III opener shall be grade A and shall be table-mounted and operated by a hand crank. The opener shall consist of a body, a feed wheel, a cutting wheel, a can holder, a crank and knob, a can guide, a vertical shaft, a table clamping bracket, and when required, a magnetic lid lifter (see 7.1). The feed and cutting wheels may be geared or without gears at the option of the manufacturer. The feed and cutting wheels shall be hardened to a Rockwell C hardness of 53 to 58. The feed and cutting wheel gears (if present) shall be hardened to a Rockwell C hardness of 45 to 50. The type III opener shall remove the tops from all size cans up to and including No. 12 round having weights up to 25 pounds. The opener shall operate freely without binding and shall show no evidence of parts separation, breaking, or permanent deformation and shall remove the tops from cans without producing metal slivers, chips, jagged or irregular edges, when tested as specified in 5.3.4.

3.1.5 Type IV opener. The type IV opener shall be grade B, table-mounted with no base, or with a bolt-on base or clamp-on base (see 7.1), and operated by a hand crank. The opener shall consist of a body, a feed wheel, a reversible cutting blade, a can holder, a can guide, a crank and knob, a vertical shaft, and a table-mounting bracket. The type IV opener shall remove the tops from all size cans up to and including No. 12 round, 9½ inches square with corner radii over 1¼ inches, and 9½ inches oblong or pear-shaped cans, having weights of up to 25 pounds. The opener shall operate freely without binding and shall show no evidence of parts separation, breaking, or permanent deformation, and shall remove the tops from cans without producing metal slivers, chips, jagged or irregular edges, when tested as specified in 5.3.4.

3.1.5.1 Can opener adapter. A can opener adapter (see 7.1) shall be required when the type IV openers are to be used in the old type III table or counter mountings.

3.2 Materials. Materials used shall be of the quality normally used by the manufacturer in manufacturing his standard commercial can openers. When grade B is specified for types I, II, or IV openers, the components listed below shall be made of corrosion-resisting steel:

Type I, class 1	- Blade and handle
Type I, class 2	- Body and can guide
Type II	- Wall-mounting bracket, extension arm, crank, and cutting wheel lever
Type III	- Body, vertical shaft, table-clamping bracket, and can holder eccentric bushing (when used).
Type IV	- Body, feed wheel, reversible cutting blade, can holder, can guide, crank, vertical shaft and table-mounting bracket.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:08Z
Check the source to verify that this is the current version before use.

3.3 Finish. All carbon steel components, except the feed wheels, cutting wheels, blades and gears, shall be chromium plated, nickel plated, or nickel and chromium plated in accordance with the manufacturer's standard commercial practice. All exposed surfaces of corrosion-resisting steel components shall have a 2B (100 grit) finish or better. All other metal parts shall be finished in accordance with the manufacturer's commercial practice.

3.4 Lubrication. All points of can openers requiring lubrication shall be lubricated with the manufacturer's recommended food service equipment grade lubricant. The lubricant shall not cause food contamination.

3.5 Workmanship. The finished openers shall be clean and free of rust, slivers, die marks, deformities, and fractures. All sharp edges and corners, except cutting edges and feed wheel serrations shall be removed. The cutting wheels and blades shall be sharp and free of burrs and slivers. The cutting wheels and blades may have a radii on the cutting edge so that the blade will shear, instead of cutting the metal to avoid slivers. Sharp edges on the gear teeth shall be removed. Feed wheel serrations, or teeth, shall be sharp, uniform in shape, and equally spaced, and burrs and slivers shall be removed.

3.5.1 Plating. Plating shall be free of blisters, peeling, chipping, areas of no coverage, and imbedded foreign matter.

3.5.2 Castings. Castings shall be complete and free of porosity, cracks, blow holes, and deformities.

3.5.3 Welds. Welds shall be sound, smooth, and free from pits, fractures, burn through, or fissures. All scale or flux shall be removed. Spot welds shall be free of flashes.

3.5.4 Rivets. All burrs shall be removed from rivet holes. Rivet heads and peened ends shall be round and in full contact with the joined metal. There shall be no missing rivets.

3.5.5 Threaded fasteners. Threaded fasteners shall be drawn tight and shall not be stripped or cross-threaded. Washers, lockwashers, and bushings shall be provided where required in accordance with standard commercial practice.

3.6 Metric products. Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch-pound units, provided they fall within the tolerances specified using conversion tables contained in the latest revision of IEEE/ASTM SI 10, and all other requirements of this document are met. If a product is manufactured to metric dimensions and those dimensions exceed the tolerances specified in the inch-pound units, a request should be made to the contracting officer to determine if the product is acceptable. The contracting officer has the option of accepting or rejecting the product.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:08Z
Check the source to verify that this is the current version before use.

4. REGULATORY REQUIREMENTS

4.1 Contractor recovered materials. The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR).

5. PRODUCT CONFORMANCE PROVISIONS

5.1 Product conformance. The products provided shall meet the salient characteristics of this Commercial Item Description, shall conform to the producer's own drawings, specifications, standards and quality assurance practices, and be the same product offered for sale in the commercial marketplace for over one year, or is the same product that has successfully been delivered to the Government on a previous contract or purchase order. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

5.1.1 Market acceptability criteria. The following market acceptability criteria are necessary to document the quality of the product to be provided under this CID.

a. The company producing the item must have been producing a product meeting the requirements of this CID for at least 2 years.
b. The company must have sold at least1000 units of the product meeting the requirements of this CID, in the commercial or government marketplace over the past 2 years.

5.2 NSF International standard compliance. (For type IV, grade B only). Prior to the approval of the first shipment, the contractor shall submit satisfactory evidence to the contracting officer or his authorized representative that the items conform to the applicable requirements of NSF International Standard No. 2 or NSF International Standard Criteria C-2. Acceptable evidence of meeting the requirements of NSF International Standard No. 2 or NSF International Standard Criteria C-2 shall be a listing in the current edition of the NSF International "Listing of Food Service Equipment" and display of the NSF International mark on the finished can opener, or certified test report from a recognized independent testing laboratory acceptable to the medical authority of the service for which the items are being procured stating that the items have been tested and conform to NSF International Standard No. 2 or Criteria C-2. Acceptance of the independent testing laboratory to the medical authority shall be based on the laboratory submitting to the contracting officer a written letter from either the American Association for Laboratory Accreditation (A^2LA), Gaithersburg, MD, or the American National Institute (ANSI), Washington, DC, stating that the independent testing laboratory has been evaluated and is accredited for testing and evaluating food service equipment for conformance with applicable NSF International standards and criteria. Accreditation of the independent testing laboratory must be completed prior to the item testing.

5.3 Load and performance test. All cans specified in the following paragraphs shall comply with PPP-C-96.

5.3.1 Type I, class 1 opener. The opener handle shall be clamped in a holding device at a 45-degree angle from the horizontal. The opener shall be used to open nine No. 10 round cans. The opener shall then be examined to determine compliance with the parts separation, breaking, and permanent deformation requirements of 3.1.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:08Z
Check the source to verify that this is the current version before use.

5.3.2 Type I, class 2 opener. The opener shall be placed in the cutting position on an open can and the wing clamped in a holding device. A weight or a force of not less than 8 pounds shall then be applied to the bottom inside of the can in a vertical downward direction for not less than one minute. The opener shall then be removed from the can and the holding device and the opener used to open nine No. 10 round cans. The can opener shall open at least six of the nine cans in one motion without slipping off or requiring an additional attempt. If any of the remaining three cans requires more than two attempts by the can opener to completely open it, the can opener shall be considered deficient. During the openings, the opener shall be observed to determine compliance with the operational requirements of 3.1.2 (i.e., operate freely without binding). After all cans have been opened, they shall be examined to determine compliance with the metal sliver or chip, and jagged or irregular edge requirements of 3.1.2. The opener shall then be examined to determine compliance with the parts separation, breaking, and permanent deformation requirements of 3.1.2.

5.3.3 Type II opener. The opener shall be secured to a wall or holding device by the wall-mounting bracket and an open No. 10 round can placed in the cutting position. The opener shall then be tested as specified in 5.3.2 to determine conformance with 3.1.3.

5.3.4 Types III and IV openers. The opener shall be placed in an operating position on a table or bench and an open No. 12 round can placed in the cutting position. A weight or a force of not less than 25 pounds shall then be applied to the inside bottom of the can in a vertical downward direction for not less than 1 minute. The can shall then be removed from the opener and three No. 12 round cans, and three 4½ by 4½ inch square cans shall be opened. In addition, four No. 10 round cans, commercially packed four to a case, weighing not less than 6 pounds each, shall be dented by dropping the case from a height of not less than 2 feet onto a flat concrete surface. The case shall be dropped once on each of the six sides and once on each of the four diagonal corners. The dented cans shall also be opened. The opener shall be observed while opening the cans to determine compliance with the operation and binding requirements of 3.1.4 and 3.1.5. The opened cans shall be examined to determine compliance with the metal slivers or chips, and the jagged or irregular edge requirements of 3.1.4 and 3.1.5. The opener shall then be examined to determine compliance with the parts separation, breaking, and permanent deformation requirements of 3.1.4 and 3.1.5.

6. PACKAGING

6.1 Packaging. Preservation, packing and marking requirements shall be as specified in the contract or purchase order (see 7.1).

7. NOTES

7.1 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in procurement documents (if applicable).

a. Title, number and date of this document.
b. Type, class, and grade required (see 2.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:08Z
Check the source to verify that this is the current version before use.

c. Type of base (bolt-on, clamp-on, or no base) required for type IV opener (see 2.1 and 3.1.5).
d. When a can opener adapter is required (see 3.1.5.1).
e. Packaging requirements (see 6.1).

7.2 Sources for documents.

7.2.1 Sources of government documents.

FEDERAL SPECIFICATION

PPP-C-96 - Cans, Metal, 28 Gage and Lighter

Copies of the above document are available from:

Document Automation and Production Service
Building 4D (DPM-DODSSP)
700 Robbins Avenue
Philadelphia, PA 19111-5094

7.2.2 Sources for non-government association documents. Copies of referenced non-government documents may be obtained from the following organizations:

IEEE/ASTM STANDARD:

SI 10 – Standard for Use of the International System of Units (SI): The Modern Metric System

(Application for copies of IEEE/ASTM standards should be addressed to the Institute of Electrical and Electronics Engineers, Inc., 445 Hoes Lanes, P.O. Box 1331, Piscataway, NJ 08855-1331, or the American Society for Testing and Materials, 100 Barr Harbor Drive, West Conshohocken, PA 19428-2959).

NSF INTERNATIONAL

NSF International Standard No. 2 - Food Equipment.
NSF International Standard Criteria C-2 - Special Equipment and/or Devices.

(Application for copies of NSF International Standards should be addressed to NSF International, 3475 Plymouth Road, P. O. Box 130140, Ann Arbor, MI 48113-0140).

7.3 National Stock Number (NSN). The following is a list of NSNs assigned which correspond to this document. The list may not be indicative of all possible NSNs associated with the document.

NSN	TYPE	CLASS	GRADE
7330-00-224-8081	I	1	A
7330-00-272-2591	I	2	A
7330-00-251-1515	II		A
7330-00-205-3151	III		A

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:08Z
Check the source to verify that this is the current version before use.

7330-01-411-9788	IV (Bolt-on base)	B
7330-01-411-9789	IV (Clamp-on base)	B
7330-01-476-6657	Can opener adapter	

7.4 Sources of supply. Manufacturers whose products are known to meet the requirements of this document are listed below; however, competition is not limited to these companies.

Anchor Equipment
21 Washington Avenue
Carteret, NJ 07008

Edlund Co.
159 Industrial Parkway
Burlington, VT 05401

CRC Products
1703 N. 13th Street
Terre Haute, IN 47808

Turner & Seymour Mfg
100 Lawton Street
P.O. Box 358
Torrington, CT 06790

7.5 Part Identification Number (PIN). The PINs to be used for items required by this CID are created as follows:

AA 52206 1 2 A (Example of a PIN: AA52206-12A)

- A: Grade A – Standard commercial quality; Grade B – Corrosion-resisting steel
- 2: Class: 1 – Lever-operated, with bottle opener; 2 – Wing-operated feed wheel
- 1: Type: 1 – I – Hand operated household portable; 2– II- Wall-mounted with magnetic lid lifter–III – Table mounted, heavy duty, with cutting wheel; 3- III Table mounted heavy duty, with cutting wheel; 4 – IV-Table mounted, heavy duty with cutting blade (a) bolt-on base (b) clamp-on base (c) no base
- 52206: CID number
- AA: Designates a Commercial Item Description

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:08Z
Check the source to verify that this is the current version before use.

MILITARY INTERESTS:

Custodians:
Army - GL
Navy - SA
Air Force - 99

Review Activities
Army - MD1, QM1
Air Force - 35, 84
Navy - MC, CG
DLA-SS

CIVIL AGENCY COORDINATING ACTIVITY:

GSA - FSS

PREPARING ACTIVITY:

ARMY - GL

Project 7330-0793

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:08Z
Check the source to verify that this is the current version before use.