A-A-52286
10 Jul 90

COMMERCIAL ITEM DESCRIPTION

Sprayer, Pesticide, Pushcart Mounted

The General Services Administration has authorized the use of this commercial item description.

Abstract. This commercial item description describes a cart mounted electric motor driven sprayer for applying ultra-low volume (ULV) insecticide formulations for food warehouses and other indoor storage areas.

Salient characteristics.

Electrical. The sprayer shall operate from a 115 volt, 60 hertz, with a maximum current draw of 20 amps. The power cord shall not be less than 25 feet in length and shall be of 3 wire grounded construction. The wiring to the main on-off control shall be a minimum of 12 American Wire Gage (AWG) with slow blow fusing at 25 amperes. Intermediate wiring from time controls to motorized components shall be a minimum of 16 AWG. Fuses, reset circuits (line filters), and input power cable shall be wired to an intermediate junction box.

Beneficial comments, recommendations, additions, deletions, clarifications, etc., and any data which may improve this document should be sent to: U.S. Army Biomedical Research and Development Laboratory, ATTN: SGRD-UBE-D, Fort Detrick, Frederick, MD 21701-5010.

AMSC N/A FSC 3740

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:08Z
Check the source to verify that this is the current version before use.

Construction. The sprayer shall be made of aluminum or steel, which is is pesticide corrosion resistant, and mounted on a rectangular frame. The overall dimensions shall be no less than 2.5 feet wide, 4 feet long, and 4 feet high. A ULV nozzle and a blower fan shall be mounted inside a cylindrical drum no less than 2 feet in diameter and 3.5 feet long. The drum shall be capable of adjustment, from a horizonal position to a 30 degree tilt. The nozzle and a blower fan shall be mounted internally in the drum. The frame shall have two straight bicycle-type handles with hand grips, two 20 inch bicycle type wheels, a 6 inch front center swivel wheel, mounting brackets for the compressor and motor, insecticide pump electric timers, and insecticide tank. There shall be two 24-hour electric timers (one for the fan motor and one for the compressor) and a stop/start motor control. The pump shall be a reciprocating piston metering type and must be capable of accurately dispersing 1-4 ounces/minute of insecticide with an accuracy of ± 5 percent. The insecticide tank capacity shall be at least one gallon.

Preformance. The sprayer must be capable of an adequate overnight treatment of a warehouse that has at least 500,000 cubic feet with a ULV formulation of insecticide.

Weight. The sprayer shall weigh no more than 200 pounds,

Conformance. The sprayer shall conform to the requirements of Underwriters Laboratories (UL), Inc., Standard 1559.

Workmanship The sprayer shall be free from burrs and sharp edges or projections or other defects which detract from its appearance, impair its performance or serviceability, and which may create an electrical or safety hazard.

Warranty. The sprayer shall have as a minimum requirement, a 3-year manufacturer's warranty; covering all of the sprayer's parts.

Contractor certification. The contractor shall certify and maintain substantiating evidence that the product offered meets the salient characteristics of this Commercial Item Description and that the product conforms to the producer's own drawings, specifications, standards, and quality assurance practices. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

Metric products. Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch/pound units, provided they fall within specified tolerances using conversion tables contained in the latest revision of Federal Standard No. 376, and all other requirements of this Commercial Item Description are met.

Source: https://assist.dla.mil -- Downloaded: 202610-26T09:08Z
Check the source to verify that this is the current version before use.

If a product is manufactured to metric dimensions and those dimensions exceed the tolerances specified in the inch/pound units, a request should be made to the contracting officer to determine if the product is acceptable.

The contracting officer has the option of accepting or rejecting the product.

Regulatory requirements. The offeror/contractor is encouraged to use recovered materials in accordance with Public Law 94-580 to the extent practicable, so long as the requirements of this description are met.

The offeror/contractor shall comply, and be responsible for compliance by their subcontractors/suppliers, with the requirements of the Federal Food, Drug and Cosmetic Act; Occupational Safety and Health Act; and all other applicable Federal, State, and local statutes, ordinances, and regulations.

Preservation, packaging, packing, labeling, and marking. Unless otherwise specified, one each sprayer shall be packaged into a single wooden box with adequate cushioning, blocking, and bracing. Preservation, packaging, and packing shall afford protection to preclude damage to containers and or contents under normal shipping, handling, and storage, and shall conform to applicable carrier's rules and regulations. Intermediate and exterior containers shall be labeled and marked as specified in the contract or purchase order.

NOTES.

Purchaser should obtain Major Command pest management professional consultant approval before purchase.

Purchaser should specify if optional power source is required.

Purchaser should specify intermediate and exterior labeling and marking requirements.

Purchaser should specify the requirement for a commercial off-the-shelf manual with parts list.

The UL Standard 1559 is available from Underwriters Laboratories, Inc., 333 Pfingsten Road, Northbrook, Illinois 60062.

Source: https://assist.dla.mil -- Downloaded: 202610-26T09:08Z
Check the source to verify that this is the current version before use.