INCH-POUND

A-A-52297
February 3, 1992

COMMERCIAL ITEM DESCRIPTION

TABLE, PHOTOINTERPRETER AND ANALYST, ILLUMINATED, SPLIT STAGE

The General Services Administration has authorized the use of this commercial item description in preference to Military specification MIL-T-52993(ME).

This description covers an illuminated table for viewing and annotating photographic film for photointerpreting and analysis purposes.

Salient characteristics.

Design. The table shall have a two-section illuminated viewing surface which shall accommodate one strand of 9.5-inch wide aerial roll film or two strands of film with a combined width of up to 10.5 inches. It shall be equipped with a film transport system which shall facilitate manual transport of the film in both directions. The table shall be provided with an optics carriage equipped for mounting and movement of a Bausch & Lomb Zoom 240 optical system or equal over the viewing surface. It shall be provided with controllable light masks for use in blocking extraneous light at the front and back of the illuminated surface. The table shall be mounted on a base which can adjust the viewing surface to a comfortable working height for the operator. Each part of the table shall be of sufficient strength and rigidity to maintain smooth operation and proper alinement under normal conditions. The table shall withstand shock, vibration and inclination incident to handling and transport.

Weight. The table shall not weigh more than 400 pounds.

Dimensions. The dimensions of the table, without film spools, shall not exceed 62 inches wide, 31 inches deep, and 70 inches high.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and other data which may improve this document should be sent by letter to: Commander, US Army Belvoir Research, Development and Engineering Center, ATTN: STRBE-TSE, Fort Belvoir, VA 22060-5606.

AMSC N/A FSC 6675

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:08Z
Check the source to verify that this is the current version before use.

Viewing surface. The viewing surface of the table shall be split into two viewing stages of approximately 11 inches by 18 inches each. The viewing surface shall be free of any obstruction except for the slot between the stages for the split vertical and the variable length film takeup threading configurations. The viewing surface shall be capable of supporting a weight of 20 pounds with a base approximately 7 inches in diameter without damage.

Illumination. The light intensity at the viewing surface shall be infinitely adjustable from a maximum of 3,500 foot lamberts down to a minimum of approximately 700 foot lamberts. The color temperature of the light produced shall be approximately 5,000 degrees Kelvin at maximum intensity.

Masks. Each viewing stage shall be provided with masking devices for blocking extraneous light. Convenient manual controls shall be provided at the front of the table for positioning and retracting the light masks.

Film transport system. The table shall be equipped with a manually operable film transport system capable of transporting one or two strands of film simultaneously in both directions across the viewing stages. The transport system shall provide for split-vertical viewing of films. The transport system also shall be equipped with a manually controlled variable length film accumulation capability which will provide for viewing of widely separated targets (up to 75 inches apart) on one strand of film. Reel brackets at each end of the table shall be capable of handling single film spools in widths up to 9.5 inches, or dual film spools with combined widths of up to 10.5 inches, and film lengths up to 1,000 feet. Film rollers shall be mounted at each end of the viewing surface to support the film slightly above the viewing stage surface. The rollers shall be constructed in segments so as to allow transport of a second strand of film at a different speed or in the opposite direction from the first.

Elevating base. The table shall have an elevating base equipped for manual adjustment of the viewing surface to any height between 29 inches and 42.5 inches above the floor where most comfortable for the operator. The base shall be mounted on four rubber-tired casters for ease of movement. The front casters shall include locking mechanisms to prevent movement of the table when in use.

Optics carriage. The table shall be equipped with an optics carriage which provides for precise three-axis movement of a mounted optical device over the viewing surface. Magnetic clutches shall be provided to permit the carriage to be locked into place and to allow manual fine feed control along the X and Y axes. The clutches shall be capable of being decoupled to allow rapid manual operation of the carriage by the operator. The carriage shall maintain parallelism of the optics to the viewing surface throughout the full range of movement along the X and Y axes of each

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:08Z
Check the source to verify that this is the current version before use.

viewing stage. Provisions shall be made for both coarse and fine movement of the optical device along the Z axis for manually focusing the optics.

Electrical requirements. The table shall operate from a 120 volt, 60 hertz, single phase, alternating current electrical power source and shall draw not more than 9 amperes. A 10-foot long, rubber-covered, 3-wire, grounding type electrical power cord terminated with a 3-prong male rubber plug shall be provided for connecting the table to the electrical power source. The table shall be provided with one main power on/off switch for control of all table electrical circuits. The lamps serving as light sources shall be ruggedized and mounted in a manner to withstand handling and transport of the table. The light sources shall be controlled by a single on/off switch and a single potentiometer for control of the viewing surface illumination level. All switches and controls shall be located so as to be readily accessible to the operator.

Finish. The interior of the lamp housing shall be given a durable white finish. The frame and other untreated exposed metal surfaces shall be given a durable light green finish.

Workmanship. The external surfaces of the table shall be free of burrs, sharp edges and corners except where sharp edges or corners are essential or where they will not cause injury to operating or maintenance personnel.

Certification of commercial item. The contractor shall certify that the product offered to the Government meets the salient characteristics of this description and that the product conforms to the producer's own drawings, specifications, standards, and quality assurance practices and is the same product as the manufacturer's current product offered by the contractor in the commercial marketplace for at least one year preceding the solicitation. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

Metric products. Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch-pound units, provided they fall within specified tolerances using conversion tables contained in the latest revision of FED-STD-376, and all other requirements of this Commercial Item Description are met.

If a product is manufactured to metric dimensions and those dimensions exceed the tolerances specified in the inch-pound units, a request should be made to the contracting officer to determine if the product is acceptable.

The contracting officer has the option of accepting or rejecting the product.

Source: https://assist.dla.mil -- Downloaded: 202640-26T09:08Z
Check the source to verify that this is the current version before use.

Regulatory requirements. In accordance with Federal Acquisition Regulation, section 23.403, the Government's policy is to acquire items composed of the highest percentage of recovered materials practicable, consistent with maintaining a satisfactory level of competition without adversely affecting performance requirements or exposing the contractor's employees to undue hazards from the recovered materials.

Preservation, packaging, packing, labeling and marking. Preservation, packaging, packing, labeling and marking shall be as specified in the contract or order.

Quality assurance. The table photointerpreter and analyst shall be examined for the following defects. Presence of one or more defects shall be cause for rejection.

1. Design not as specified.
2. Weight not as specified.
3. Dimensions not as specified.
4. Viewing surface not as specified.
5. Illumination not as specified.
6. Masks not provided as specified.
7. Film transport system not as specified.
8. Elevating base not as specified.
9. Optics carriage not as specified.
10. Electrical requirements not as specified.
11. Finish not as specified.
12. Workmanship not as specified.

Notes. The procuring agency should specify the preferred options permitted herein and include the following information in procurement documents:

1. Title, number, and date of this item description.
2. When this commercial item description is used for procurement, the commercial item certification clause must appear in the solicitation.

FED-STD-376 can be obtained from the Standardization Documents Order Desk, Building 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

The following is a suggested source of supply for this item description (Competition is not limited to this source):

1. The Richards Corporation, 44931 Falcon Place, Sterling, VA 22170-9510.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:08Z
Check the source to verify that this is the current version before use.

The preparing activity for this item description is the US Army Belvoir Research, Development, and Engineering Center, ATTN: STRBE-TSE, Fort Belvoir, VA 22060-5606.

MILITARY INTERESTS:

Custodian:
Army - ME

CIVIL AGENCY COORDINATING ACTIVITY:

GSA - FSS

PREPARING ACTIVITY

Army - ME

Project 6675-0966

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:08Z
Check the source to verify that this is the current version before use.