INCH-POUND

A-A-52299A
20 September 1999
SUPERSEDING
A-A-52299
29 January 1992

COMMERICAL ITEM DESCRIPTION

LEVEL, SURVEYING: LOCATOR'S, HAND-TYPE

The General Services Administration has authorized the use of this Commercial Item Description (CID) for all federal agencies.

1. SCOPE.

1.1 Abstract. This commercial item description covers hand held, surveying levels used for line of sight determination of relative elevation.

2. CLASSIFICATION:

2.1 Type. The hand levels shall be classified as follows:

Type I – Non-telescoping, no magnification of the field of view, and 4X magnification of level bubble.

Type II – Telescoping (draw tube), 2X magnification of the field of view, and 4X magnification of level bubble.

3. SALIENT CHARACTERISTICS.

3.1 Construction. The hand level, regardless of type, shall have the following characteristics:

a. A tubular body with an objective lens at one end and at the other, a removable eyepiece suitably sealed to preclude the entry of dust into the instrument.

b. Horizontal and vertical cross hairs for use in determining the exact target intercept and vertical orientation of the level.

c. An integral focusing arrangement to accommodate the individual eye.

d. A permanently mounted instrument level to indicate when the line of sight is horizontal.

e. A mechanism that shall project the image or readout of the level indicator magnified 4x to one side of the field of view.

f. A lanyard to suspend the instrument from the user's neck.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data which may improve this document should be sent to: U.S. Army Topographic Engineering Center, ATTN: CETEC-TD-T, 7701 Telegraph Road, Alexandria, VA 22315-3864.

FSC 6675

Distribution Statement A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:08Z
Check the source to verify that this is the current version before use.

3.2 Configuration. The levels shall be constructed in accordance with the following:

a. Type I. The tubular body shall be non-telescoping, with no magnification of the field of view and 4X magnification of level bubble. The overall length of the level shall not be greater than 6.5 inches.

b. Type II. The tubular body shall telescope, to afford a 2X magnification of the field of view and 4X magnification of level bubble. With the telescoping portion fully retracted, the overall length of the level shall not be greater than 6.5 inches.

3.3 Level indicator. The instrument level indicator shall be accurate to within a ± 0.25 percent gradient from horizontal and shall maintain this accuracy in normal use, handling, and storage for the life of the instrument.

3.4 Carrying case. A carrying case, to fit and protect the instrument, shall be provided with each level. The case shall have a securable closure and a loop(s) compatible with a belt 3.00 inches wide. The carrying case shall be fungus resistant and withstand use, handling, and storage normal to battlefield conditions without malfunction or damage.

4. REGULATORY REQUIREMENTS.

4.1 Recycled, recovered, or environmentally preferable materials. The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR).

5. QUALITY ASSURANCE PROVISIONS.

5.1 Market acceptability. The levels offered shall be the latest version of the standard product of the supplier, that has been used in the field for at least one year by commercial organizations.

5.2 Product conformance. The levels offered shall meet the salient characteristics of this CID, conform to the manufacture’s drawings, specifications, standards, and quality assurance practices, and be the same product offered for sale in the commercial market. The government reserves the right to require proof of such conformance.

6. PACKAGING.

6.1 Packaging. Preservation, packing, and marking shall be as specified in the contract or order (see 7.2)

7. NOTES

7.1 Intended use. The levels are intended to be used to determine approximate differences in elevation, between points a short distance apart.

7.2 Ordering data. Acquisition documents must specify the following:

a. Title, number, and date of this document.

b. Type of level required (see 2.1).

c. Level of preservation and packing required (se 6.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:08Z
Check the source to verify that this is the current version before use.

7.3 Part identification number (PIN). The following part identification numbering procedure is for government purposes and does not constitute a requirement for the contractor.

This example describes a part numbering system for CID A-A-52299A

AA52299I

Level type I = Non-telescoping
II = Telescoping, 2X magnification

Document identifier

7.4 Source of government documents: Defense Automated Printing Service, Building 4D, NPM-DoDSSP, 700 Robbins Avenue, Philadelphia, PA 19111-5094.

7.5 Procurement History. Type I was previously procured in accordance with Federal Specification GG-L-261 (Replaced by CID A-A-52299), NSN 6675-01-880-1820.

7.6 Subject term (key word) listing.

Measure, plane
Optics
Telescoping
Transit

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:08Z
Check the source to verify that this is the current version before use.

Custodian:
Army - CE3
Air force - 99
Navy – YD2
DLA-GS

Review activities:
Army-CR
Navy-MC
Air Force-82

Civil Review Agency:
GSA - FCGC

Preparing activity:
Army - CE3
(Project 6675-0131)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:08Z
Check the source to verify that this is the current version before use.