INCH-POUND
MIL-DTL-32059 (OS)
24 February 2000

DETAIL SPECIFICATION

INITIATOR, ARM FIRE, JAU-54A/A

This specification is approved for use by the Naval Sea Systems Command, Department of the Navy, and is available for use by all Department and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the requirements for the manufacture and acceptance of the JAU-54A/A Arm Fire Initiator (3W84) (see 6.1).

2. APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are specified in sections 3 and 4 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements documents specified in sections 3 and 4 of this specification, whether or not they are listed.

2.2 Government documents.

2.2.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplements thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS

DEPARTMENT OF DEFENSE

MIL-L-46225	Lead Azide RD-1333 (For Use in Ammunition)
MIL-C-83124	Cartridge Actuated Devices/Propellant Actuated Devices, General Design Specification for

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to the Commander, Indian Head Division, Naval Surface Warfare Center, Standardization Team (Code 840M), 101 Strauss Avenue, Indian Head, MD 20640-5035, by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by sending a letter.

AMSC N/A FSC 1377
DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T04:32Z
Check the source to verify that this is the current version before use.

STANDARDS

DEPARTMENT OF DEFENSE

MIL-STD-1168	Ammunition Lot Numbering and Ammunition Data Card

(Unless otherwise indicated, copies of Federal and Military specifications and standards are available from: Standardization Documents Order Desk, Bldg. 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094)

2.2.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation (see 6.2).

SPECIFICATIONS

NAVAL SEA SYSTEMS COMMAND (CAGE Code 53711)

WS 5003	HNS Explosive

DRAWINGS

NAVAL SEA SYSTEMS COMMAND (CAGE Code 53711)

DL6106319	Initiator, Arm Fire, JAU-54A/A

NAVAL AIR SYSTEMS COMMAND (CAGE Code 30003)

857AS800	Test Fixture Assembly
841AS450	Test Tip, Shielded Mild Detonating Cord

(Application for copies should be addressed to the Commander, Indian Head Division, Naval Surface Warfare Center, Documentation Branch (Code 8410), 101 Strauss Avenue, Indian Head, MD 20640-5035.)

2.3 Non-Government publications and drawings. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted are those listed in the issue of the DODISS cited in solicitation. Unless otherwise specified, the issues of documents not listed in DODISS are the issues of the documents cited in the solicitation (see 6.2).

AMERICAN NATIONAL STANDARD INSTITUTE/AMERICAN SOCIETY FOR QUALITY CONTROL

ANSI/ASQC Z1.4	Sampling Procedures and Tables for Inspection by Attributes

(Application for copies should be addressed to the American Society for Quality Control, PO Box 3005, 611 E. Wisconsin Ave., Milwaukee, WI 53201-4606.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T04:32Z
Check the source to verify that this is the current version before use.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

ASTM E 1742	Standard Practice for Radiographic Examination
ASTM E 545	Standard Method for Determining Image Quality in Direct Thermal Neutron Radiographic Examination

(Application for copies of ASTMs should be sent to the American Society for Testing and Materials, 100 Barr Harbor Drive, West Conshohocken, PA 19428-2959)

2.4 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified (see 6.2), a sample shall be subjected to the first article inspection in accordance with 4.3.

3.2 Conformance to documents. The JAU-54A/A initiator covered by this specification shall be manufactured in accordance with DL6106319 and all documents listed thereon.

3.3 Materials. All materials used in the manufacture of the initiators shall conform to the specifications referred to on the respective drawings unless specific approval in writing covering a departure therefrom has been obtained from the cognizant design activity prior to manufacture. When alternate materials or methods of manufacture are specified on the drawings, the bidder's selections shall be clearly stated in the proposal.

3.4 Primary components. For the purposes of this specification, the primers, lead azide, and the hexanitrostilbene are considered primary components.

3.4.1 Percussion primers. Only percussion primers from lots manufactured within the last 24 months or recertified within the last 12 months shall be used in these units.

3.4.2 Lead Azide. Only lead azide conforming to MIL-L-46225, RD-1333, manufactured within the last 24 months or recertified within the last 12 months shall be used. Only lead azide from one (1) lot will be used in a single lot of transfer charges.

3.4.3 Hexanitrostilbene (HNS II). Only HNS II, Grade A, manufactured in accordance with WS 5003 shall be used in the transfer charge. The purity level of the HNS II batch being used shall be certified by the manufacturer. A copy of the certification shall be furnished with the contract data. Only HNS II, Grade A, from one (1) lot shall be used in a single lot of transfer charges.

3.5 Transfer Charge. All transfer charges shall be manufactured with primary components which meet the requirements of 3.4.

3.5.1 Radiographic Examination. Each transfer charge shall be X-rayed and N-rayed and shall be free of the following defects when examined by in accordance with 4.5.6: missing, defective or improperly assembled components; foreign matter; cracks, abnormal voids or other abnormalities which

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T04:32Z
Check the source to verify that this is the current version before use.

could adversely affect the form, fit or function of the transfer charge. During radiographic examination each transfer charge shall be positioned so that the center plane through the primers is perpendicular to the radiographic beam.

3.5.2 Leak Test. Each transfer charge when leak tested in accordance with 4.5.3 shall not have a leak rate greater than 1 X 10E-5 cc/sec of air (2.4 X 10E-5 cc/sec of helium).

3.5.3 Visual inspection. Each transfer charge shall be subjected to visual inspection. Any transfer charge exhibiting cracks, dents, damaged closure disk, defective or incomplete weldments, or any other defect which could adversely affect form, fit, or function shall be rejected.

3.6 Initiator assembly.

3.6.1 Transfer Charge. Only Transfer Charges meeting the requirements of the applicable drawings and manufactured in accordance with 3.5 shall be used in initiators. Each transfer charge shall be permanently marked with a serial number. A marriage log shall be kept which records which transfer charge is installed in each initiator.

3.6.2 Arming torque test. The initiator handle shall rotate from the safe position to the armed position when 6 to12 inch-pounds of torque is applied to the handle. Verification shall consist of two turns of the handle from the safe position to the armed position. This torque requirement does not apply to the torque required to rotate the handle from the armed position back to the safe position. Testing shall be performed in accordance with 4.5.1.

3.6.3 Initiator Actuation. The initiator assemblies shall actuate when armed as described in 3.6.2 and a 20 to 35 pound force is applied axially to the shaft assembly in the direction to pull the shaft assembly out of the initiator body. Testing shall be performed in accordance with 4.5.1.

3.6.4 Mechanical force test. Any assembly that actuates or causes permanent deformation to the safety pin or the initiator body when tested in accordance with 4.5.2 shall be rejected.

3.6.5 Residual magnetism. Each initiator shall be subject to the residual magnetism test as specified in 4.5.4. Any initiator that deflects the compass point more than 5° in any direction shall be subjected to degaussing and retested until it passes or it shall be rejected.

3.6.6 Visual inspection. Each initiator shall be subjected to visual inspection. Any initiator exhibiting the types of defects noted in 4.5.5 or any other defect which could adversely affect form, fit, or function shall be rejected.

3.6.7 Radiographic inspection. Each initiator shall be X-rayed in accordance with 4.5.6. Any initiator that does not conform to the data package as detailed on DL6106319 shall be rejected.

3.7 Ballistic requirements. Completely assembled initiators from each lot, selected in accordance with 4.4.2, shall meet the requirements of 3.7.1 through 3.7.3 when tested in accordance with 4.5.7.

3.7.1 Actuation. Each initiator tested shall be mounted in the test fixture described in drawing 857AS800 in such a manner that the pull force required to pull the Shaft Assembly from the initiator body can be measured. The initiator shall meet the torque and force requirements of 3.6.2 and 3.6.3. Failure to meet these requirements shall result in rejection of the lot represented.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T04:32Z
Check the source to verify that this is the current version before use.

3.7.2 Ballistic output. A 0.062 thick witness plate manufactured of aluminum alloy 6061-T6 shall be taped securely to the exposed mild detonating cord of the test tip (841AS450-1). The explosive output of each tested initiator shall meet the requirements of 4.5.7.2. Failure to meet this requirement shall result in rejection of the lot represented.

3.7.3 Mechanical Failure. The initiator shall function in accordance with the performance requirements specified herein without mechanical failure (see 6.4.2). Failure to meet this requirement shall result in rejection of the lot.

3.8 Workmanship. Initiators shall be constructed and finished in a manner to assure compliance with all the provisions of this specification and the applicable drawings. Special attention shall be directed to dimensions, finishes, coatings and cleanliness.

4. VERIFICATION

4.1 Classification of inspections.

a. First article inspection (see 4.3)
b. Quality conformance inspection (see 4.4)

4.2 Inspection conditions. Unless otherwise specified, all inspections shall be performed in accordance with the test conditions specified in 4.5.

4.3 First article inspections and tests. First article inspection shall be performed prior to production of the fleet delivery lot. First article inspection shall be performed on units which have been manufactured in the same manner and using the same materials, equipment, processes, and procedures as to be used in the regular production. All parts and materials including packaging and packing shall be the same as used for regular production and shall be obtained from the same source of supply. The first article shall be selected in accordance with 4.3.1 and with the requirements of 4.3.2.1. Any production prior to notification by the contracting agency of the first article sample acceptability shall be at the contractor's risk.

4.3.1 Sample size. Unless otherwise specified (see 6.2) the first article sample shall consist of 38 assembled initiators and 10 complete unassembled sets of components for dimensional and visual inspection and testing.

4.3.2 Inspection routine.

4.3.2.1 Initiators. Thirty-six (36) initiators shall be sequentially tested in the order listed in Table I. Two (2) additional initiators shall be retained for investigative purposes. The 36 initiators shall be randomly divided into 4 groups (A through D) of 9 initiators each. In addition, ten (10) sets of initiator components (designated group E) shall be inspected per Table I to verify conformance with applicable drawing requirements. All radiographic requirements listed in Table I except the post-environmental initiator x-ray are the responsibility of the contractor. The radiographs shall be delivered to the procuring activity with the first article. A first article sample acceptable for functional and sequential testing is defined as a sample that has met the requirements of 3.2 through 3.5.7 of this specification. The environmental tests specified in Table I shall be performed in accordance with MIL-C-83124. The ballistic tests shall be performed using the test device of 3.7.1. Acceptance shall be based on integrity of the parts and legibility of markings after environmental treatment and ballistic performance in accordance with the limits prescribed in 3.7.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T04:32Z
Check the source to verify that this is the current version before use.

TABLE I. First Article Tests

Test/Inspection	Item	Req'm't para.	Test para.	Group A	Group B	Group C	Group D	Group E
Visual/Dimensional	Component set	3.1	Dimensional req'm'ts					10
Leak Test	Transfer Charge	3.5.2	4.5.3					10
Radiographic Inspection	Transfer Charge	3.5.1	4.5.6	9	9	9	9	10
Visual Inspection	Initiator	3.6.6	4.5.5	9	9	9	9	
Mechanical Force Test	Initiator	3.6.4	4.5.2	9	9	9	9	
Magnetism	Initiator	3.6.5	4.5.4	9	9	9	9	
X-ray	Initiator	3.6.7	4.5.6	9	9	9	9	
Shock (20 g)	Initiator	3.1	4.3.2.1	9				
Temp. Shock/Hum./Alt.	Initiator	3.1	4.3.2.1		9			
Low temperature	Initiator	3.1	4.3.2.1			9		
Vibration	Initiator	3.1	4.3.2.1				9	
X-ray	Initiator	3.6.7	4.5.6	9	9	9	9	
Ballistic test (-65°F)	Initiator	3.7	4.3.2.1 and 4.5.7	3	3	3	3	
Ballistic test (70°F)	Initiator	3.7	4.3.2.1 and 4.5.7	3	3	3	3	
Ballistic test (200°F)	Initiator	3.7	4.3.2.1 and 4.5.7	3	3	3	3	

4.3.2.2 Failure. Failure of any initiator or percussion primer to meet the requirements of DL6106319 or this specification shall be cause for first article rejection. The Government reserves the right to terminate its inspection upon any failure of an assembly or component in the sample to comply with any or all of the stated requirements. In the event of failure of any sample, the Government reserves the right to require the contractor to take corrective action and submit a new sample or portion thereof. Until a first article inspection sample is accepted, the contractor is in no way authorized by the Government to initiate regular production unless otherwise directed in writing by the procuring activity.

4.4 Quality conformance inspection. Quality conformance inspection shall consist of the characteristics classified on the applicable data list and the tests and examinations of table II.

TABLE II. Quality Conformance Tests And Examinations.

Item	Nature of test	Requirement	Test
Primary Component	Single Lot Verification	3.4	-
Transfer Charge	Lot Acceptance Verification	3.6.1	-
Primer	Age and Inspection	3.4.1	-
Initiator	Mechanical Force Test	3.6.4	4.5.2
Transfer Charge	Leakage	3.5.2	4.5.3
Initiator	Magnetism	3.6.5	4.5.4
Initiator	Visual Inspection	3.6.6	4.5.5
Initiator	X-ray	3.6.7	4.5.6
Initiator	Ballistic	3.7	4.5.7
Initiator	Preservation-packaging, packing and marking	Section 5	-

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T04:32Z
Check the source to verify that this is the current version before use.

4.4.1 Lot size. The lot size shall be 9 minimum and 1200 maximum. The lot shall include 2 units which will be retained for investigative purposes and the test sample units as specified in 4.4.2. Initiators required for all test purposes are selected from the production lot and will not be applied as a part of the quantity specified for delivery by the contract. Only primary components (see 3.4) from a single lot shall be used in a production lot of initiators. One primary component production lot may be used in more than one initiator production lot.

4.4.2 Sampling. The test sample size shall be as specified in Table III. The test sample units shall be randomly selected in accordance with ANSI/ASQC Z1.4. Unless otherwise specified in the contract, all samples for test purposes shall be provided at the contractors' expense.

TABLE III. Production Lot Test Sample Size

Lot size	9-25	26-50	51-90	91-150	151-280	281-500	501-1200
Sample size	6	9	15	21	33	51	81

4.5 Tests.

4.5.1 Actuation. The initiator assembly shall be secured and instrumentation provided to measure the arming torque and pull force. Failure to function and meet the requirements of 3.6.2 and 3.6.3 will be cause to reject the initiator assembly.

4.5.2 Mechanical Force Test. The initiator assembly shall be secured. An axial load of 200 to 220 pounds shall be applied so as to pull the handle away from the body. Failure to meet the requirements of 3.6.4 will be cause to reject the initiator assembly.

4.5.3 Leak Test. Each transfer charge of the first article lot and each transfer charge in the production lot(s) shall be tested in a helium dry gas leak detector at a pressure differential of 1.0 ± 0.1 atmosphere for 1 hour minimum. Use of any other type of detector must be approved by the Government prior to use. Failure to meet the requirements of 3.5.2 will result in the rejection of the item tested.

4.5.4 Residual magnetism. The assembly shall be tested for excessive residual magnetism in an area free of local magnetic effects by placing the test initiator six inches from the end and at the same height as the compass in a north-south horizontal position with the compass set in an east-west heading. The initiator shall be moved at a speed no greater than 10 feet per minute past the compass in a longitudinal direction for its entire length, rotated 90 degrees in the horizontal position about its longitudinal axis and moved slowly past the compass. This procedure shall be repeated for 90 degree rotation of the initiator. Failure to meet the requirement of 3.6.5 will result in the rejection of the initiator.

4.5.5 Visual inspection. Examine each initiator produced under a contract and reject for cracks, splits, incomplete or damaged threads, orientation of safety pin, missing safety pin, inadequate marking or other defects which might prevent proper mating with connecting parts or proper functioning of the device.

4.5.6 Radiographic Examination. Radiographically examine in accordance with ASTM E1742 (X-ray) and ASTM E545 (N-ray) as applicable. One (1) unit may be used as the penetrometer. Any observable imperfection in components or assembly shall be cause for rejection. The subject items shall be positioned for the most revealing exposure with the long axis perpendicular to the radiographic beam. All items shall be identified with serial numbers in consecutive numerical order beginning with 001 in each production lot prior to exposure. The items shall be arranged on boards or trays in consecutive order with any missing serial numbers identified on the radiographic plate. Each radiograph shall carry a permanent identification of the items displayed thereon. The radiographic identification shall include

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T04:32Z
Check the source to verify that this is the current version before use.

item nomenclature, the complete lot number assigned to that lot, and the span of serial numbers displayed. Defective items found during radiographic review are to be marked on the radiograph and, prior to shipment, all defective items shall be removed from the production lot. Radiographs of the entire production lot and a description of the defects of removed items shall accompany the ballistic sample to the activity conducting the production lot acceptance tests.

4.5.7 Ballistic tests.

4.5.7.1 Tests. Sample initiators shall be randomly selected to be representative of the complete lot. One third of samples shall be temperature conditioned at each of the following temperatures for 4 hours minimum but not to exceed 24 hours maximum: –65 ± 5°F, 70 ± 5°F and 200 ± 5°F. The 24 hour maximum does not apply to the 70°F conditioning. Each sample shall be fired in the test fixture (see 6.4.1) within 5 minutes after removal from conditioning. If the 5 minute limit is exceeded the unit shall be returned to a 70 ± 5°F environment for 4 hours minimum and then reconditioned in the intended environment for the designated time. The initiators shall be actuated and meet the requirements of 3.6.2, 3.6.3 and 3.7.

4.5.7.2 Ballistic Output. The dent produced by the SMDC test tip in the witness plate when tested in accordance with 3.7.2 shall be a minimum of 0.001 inch deep.

4.5.7.3 Test failure. Any failures or defects found during lot acceptance testing may cause the lot to be rejected. If test failure is not attributed to the initiator, the data may be disregarded for that firing and a retest permitted with a new initiator.

4.6 Retest. There shall be no retest, except as defined and allowed in 4.5.7.3. Any defects or failures during lot acceptance testing may be cause for rejection.

5. PACKAGING

5.1 Packaging. For acquisition purposes, the packaging requirements shall be specified in the contract or purchase order (see 6.2 and 6.5). When actual packaging of material is to be performed by DOD personnel, these personnel need to contact the responsible packaging activity to ascertain requisite packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activity within the Military Department or Defense Agency, or within the Military's Department's System Command. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

6. NOTES

(This section contains information of a general or explanatory nature that maybe helpful but is not mandatory.)

6.1 Intended Use. The JAU-54A/A is a cockpit mounted tee handle initiator used in the canopy removal system of the AH-1 G/J/S/T helicopters. The canopy removal system is only used in military aircraft, therefore the initiator has no commercial application. This specification replaces WS32889 for the JAU-54A/A only.

6.2 Acquisition Requirements. Acquisition documents must specify the following:

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T04:32Z
Check the source to verify that this is the current version before use.

a. Title, number, and date of this specification.

b. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.2.1, 2.2.2 and 2.3).

c. Inspection conditions if other than specified in 4.2.

d. First article sample size, if other than as specified (see 4.3.1)

e. Whether first article inspection is required and, if so, specify the test activity (see 3.1 and 4.3).

f. Lot size, if other than as specified (see 4.4.1).

g. Packaging (see 5.1 and 6.5).

h. Sampling, if other than as specified (see 4.4.2, and 6.6)

i. Date and place of delivery

j. That the safety precaution requirements of the "Contractors' Safety Manual for Ammunition, Explosives and Related Dangerous Material," DOD 4145.26M are applicable. NOTE: When this specification is used as a part of the description of work to be accomplished by a Government activity the safety precautions requirements of "Ammunition and Explosives," OP 5, are applicable.

6.3 First Article. When a first article inspection is required, the items should be a first article sample. The first article should consist of 38 assembled initiators and 10 complete sets of components. The contracting officer should include specific instructions in acquisition documents regarding arrangements for examinations, approval of first article test results, and disposition of first articles. Invitation(s) for bid(s) should provide that the U.S. Government reserves the right to waive the requirements for samples for first article inspection to those bidders offering a product which has been previously acquired or tested by the U. S. Government, and that bidders offering such products, who wish to rely on such production or test, must furnish evidence with the bid that prior U.S. Government approval is presently appropriate for the pending contract.

6.4 Definitions. For the purpose of this specification, the following definitions apply.

6.4.1 Test fixtures. The ballistic testing is to be conducted in a test fixture that conforms to Drawing 857AS800.

6.4.2 Mechanical failure. Any deformation or breakage of a part or separation of parts which is other than a design function.

6.4.3 Primary component. Components from a single lot.

6.5 Packaging. The inner and intermediate packing and packaging should be in accordance with SPI (AM) P1377-13.

6.6 Subject term (keyword) listing.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T04:32Z
Check the source to verify that this is the current version before use.

Propellant
Canopy removal
AH-1 G/J/S/T helicopter

Preparing Activity:
Navy - OS
(Project 1377-0125)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T04:32Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.

2. The submitter of this form must complete blocks 4, 5, 6, and 7, and send to preparing activity.

3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:

1. DOCUMENT NUMBER	2. DOCUMENT DATE (YYYYMMDD)
MIL-DTL-32059	20000224

3. DOCUMENT TITLE INITIATOR, ARM FIRE, JAU-54A/A

4. NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)*

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME *(Last, First, Middle Initial)*	b. ORGANIZATION

c. ADDRESS *(Include Zip Code)*	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON *(if applicable)*	**7.DATE SUBMITTED** (YYYYMMDD)

8. PREPARING ACTIVITY

a. NAME	b. TELEPHONE *Include Area Code)* (1) Commercial	(2) AUTOVON
Commander, Indian Head Division	(301)-744-4700	354-4700

c. ADDRESS *(Include Zip Code)*	**IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT:**
Naval Surface Warfare Center Standardization Team (Code 840M2) 101 Strauss Ave	Defense Standardization Program Office (DLSC-LM) 8725 John J. Kingman road, Suite 2533 Ft. Belvoir, VA 22060-2533 Telephone (703) 767-6888 AUTOVON 427-6888

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T04:32Z
Check the source to verify that this is the current version before use.