INCH-POUND

MIL-DTL-32059C(OS)
16 July 2024
SUPERSEDING
MIL-DTL-32059B(OS)
12 August 2003

DETAIL SPECIFICATION

INITIATOR, ARM FIRE, JAU-54/A

This specification is approved for use by the Naval Surface Warfare Center Indian Head Division (NSWCIHD) and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the JAU-54/A Arm Fire Initiator (3W84).

2. APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are specified in sections 3 and 4 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements documents specified in sections 3 and 4 of this specification, whether or not they are listed.

2.2 Government documents.

2.2.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

DEPARTMENT OF DEFENSE SPECIFICATIONS

MIL-DTL-46225	-	Lead Azide RD-1333
MIL-C-83124	-	Cartridge Actuated Devices/Propellant Actuated Devices, General Design Specification for

DEPARTMENT OF DEFENSE STANDARDS

MIL-STD-331	-	Fuzes, Ignition Safety Devices and Other Related Components, Environmental and Performance Tests for
MIL-STD-810	-	Environmental Engineering Considerations and Laboratory Tests

(Copies of these documents are available online at https://quicksearch.dla.mil.)

2.2.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

Comments, suggestions, or questions on this document should be addressed to Commander, Naval Sea Systems Command, ATTN: SEA 05S, 1333 Isaac Hull Avenue, SE, Stop 5160, Washington Navy Yard, DC 20376-5160 or emailed to CommandStandards@navy.mil, with the subject line "Document Comment". Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at https://assist.dla.mil.

AMSC N/A FSC 1377

DISTRIBUTION STATEMENT A. Approved for public release: distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T04:32Z
Check the source to verify that this is the current version before use.

NAVAL SEA SYSTEMS COMMAND (NAVSEA) PUBLICATIONS

WS 5003 - HNS Explosive

(Copies of this document are available from Commander, Indian Head Division, Naval Surface Warfare Center, CAD/PAD Data Management Branch (Code E26), 4393 Benson Road, BLDG 1557, Indian Head, MD 20640-5092. Refer questions, inquires, or problems to nswc_iheodtd_dmo@navy.mil.)

NAVSEA DRAWINGS

6106319 - Initiator, Arm Fire, JAU-54/A

(Copies of this drawing are available from Commander, Indian Head Division, Naval Surface Warfare Center, CAD/PAD Data Management Branch (Code E26), 4393 Benson Road, BLDG 1557, Indian Head, MD 20640-5092. Refer questions, inquires, or problems to nswc_iheodtd_dmo@navy.mil.)

NAVAL AIR SYSTEMS COMMAND (NAVAIR) DRAWINGS

841AS450 - Test Tip, Shielded Mild Detonating Cord

857AS800 - Test Fixture Assembly

(Copies of these documents are available via Joint Engineering Data Management Information and Control System (JEDMICS) at https://webjedmics.navair.navy.mil/webjedmics/index.jsp. Refer questions, inquiries, or problems to: nani_customerservice@navy.mil.)

2.3 Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents are those cited in the solicitation or contract.

ASTM INTERNATIONAL

ASTM E545	-	Standard Test Method for Determining Image Quality in Direct Thermal Neutron Radiographic Examination
ASTM E748	-	Standard Guide for Thermal Neutron Radiography of Materials
ASTM E1742/E1742M	-	Standard Practice for Radiographic Examination

(Copies of these documents are available online at www.astm.org.)

2.4 Order of precedence. Unless otherwise noted herein or in the contract, in the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified (see 6.2), a sample shall be subjected to first article inspection in accordance with 4.2. First article testing is for the purpose of determining that the contractor, prior to starting production, is capable of producing items that comply with the technical requirements of the contract. A first article inspection-shall be required if 2 or more years have passed since the items were manufactured, if there has been major turnover in personnel, if there have been major changes to the production facility, or if there has been transfer of production to a new facility or site.

3.2 Design and construction. The JAU-54/A Initiator and all its components shall be manufactured in accordance with NAVSEA Drawing 6106319 and all documents listed thereon.

3.3 Materials. All materials used in the manufacture of the initiators shall conform to the standards established at technical service release. When specified (see 6.2), any divergence will require technical evaluation and potential design certification testing.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T04:32Z
Check the source to verify that this is the current version before use.

3.4 Primary components. For the purposes of this specification, the primers, lead azide, and the hexanitrostilbene are considered primary components (see 6.4.2). Only primary components from a single lot shall be used in a production lot of initiators. One primary component production lot may be used in more than one initiator production lot.

3.4.1 Percussion primers. Only percussion primers manufactured within the last 24 months or recertified within the last 12 months shall be used in these units.

3.4.2 Lead azide. Only lead azide in accordance with MIL-DTL-46225, RD-1333, manufactured within the last 24 months or recertified within the last 12 months shall be used.

3.4.3 Hexanitrostilbene (HNS II). Only HNS II, grade A, manufactured in accordance with WS 5003 shall be used in the transfer charge. The purity level of the HNS II batch being used shall be certified by the manufacturer as specified (see 6.2).

3.5 Transfer charge. All transfer charges shall be manufactured with primary components that meet the requirements of 3.4. When specified (see 6.2), individual transfer charges shall be permanently marked with a unique serial number.

3.5.1 Visual inspection requirements. All transfer charges exhibiting cracks, dents, damaged closure disk, defective or incomplete weldments, missing serial number or any other defect which could adversely affect form, fit, or function shall be rejected. Examination shall be performed in accordance with 4.5.1.1.

3.5.2 Radiographic inspection requirements. All transfer charges shall be free of the following defects when examined in accordance with 4.5.2.1: missing, defective, or improperly assembled components; foreign matter; cracks; abnormal voids or other abnormalities which could adversely affect the form, fit, or function of the transfer charge.

3.5.3 Leakage. Transfer charges that exhibit a leak rate greater than 1.0 E-5 standard cubic centimeters per second of air at a pressure differential of 1.0±0.1 atmosphere when tested in accordance with 4.5.3 shall be rejected.

3.6 Initiator assembly.

3.6.1 Transfer charge. Only transfer charges meeting the requirements of the applicable drawings and manufactured in accordance with 3.5 shall be used in initiators. A marriage log shall be kept as specified (see 6.2).

3.6.2 Visual inspection requirements. All initiators shall be free of the following defects when examined in accordance with 4.5.1.2: cracks, splits, missing safety pin, incomplete or unclear markings or other defects which might prevent proper mating with connecting parts or proper functioning of the device.

3.6.3 Radiographic inspection requirements. All initiators shall be free of missing, defective, or improperly assembled components, foreign matter, cracks, abnormal voids, or other abnormalities which could adversely affect the form, fit, or function when inspected in accordance with 4.5.2 and 4.5.2.2. Initiators shall be positioned so that the axis of the quick release pin is perpendicular to the x-ray beam. X-rays shall be identified by date, contract number, part number, lot number, and serial number.

3.6.4 Residual magnetism. Initiators shall not deflect a compass point more than 5 degrees in any direction. Any initiator that deflects the compass point more than 5 degrees in any direction when tested in accordance with 4.5.4 shall be degaussed and retested until it passes or it shall be rejected.

3.7 Environmental conditions. Only initiators meeting the requirements of 3.6 shall be subjected to environmental conditions.

3.7.1 Forty-foot drop. To ensure safety of handling, the initiator shall not fire when dropped from a height of 40 feet in accordance with 4.6.1. Initiators subjected to the 40-foot drop test shall not be ballistically tested.

3.7.2 Six-foot drop. Initiators shall not fire or incur any internal or external defect when dropped from a height of 6 feet when tested in accordance with 4.6.2. After being subjected to the 6-foot drop test, the initiators shall meet the requirements of 3.8 when ballistically tested.

3.7.3 Temperature/humidity cycling. The initiators shall not fire or suffer damage which could adversely affect the form, fit, or function of the initiator when subjected to the temperature/humidity environment in accordance with 4.6.3. After being subjected to the temperature/humidity environment, the initiators shall meet the requirements of 3.8 when ballistically tested.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T04:32Z
Check the source to verify that this is the current version before use.

3.7.4 Shock. The initiators shall not fire or suffer damage which could adversely affect the form, fit, or function of the initiator when subjected to the shock environments in accordance with 4.6.4. After being subjected to the shock environment, the initiators shall meet the requirements of 3.8 when ballistically tested.

3.7.5 Vibration. The initiators shall not fire or suffer damage which could adversely affect the form, fit, or function of the initiator when subjected to the vibration environment in accordance with 4.6.5. After being subjected to the vibration environment, the initiators shall meet the requirements of 3.8 when ballistically tested.

3.7.6 Dust. The initiators shall not fire or suffer damage which could adversely affect the form, fit, or function of the initiator when subjected to the dust environment in accordance with 4.6.6. After being subjected to the dust environment, the initiators shall meet the requirements of 3.8 when ballistically tested.

3.7.7 Salt fog. The test initiators shall be capable of withstanding exposure to salt fog as specified in 4.6.7 and shall meet the requirements of 3.8 when ballistically tested.

3.8 Ballistic requirements.

3.8.1 Arming torque. The torque required to rotate the shaft assembly 90 degrees from the safe position to the armed position with the quick release pin (safety pin) removed shall be 6 to 36 inch-pounds. Failure to meet this requirement shall result in rejection of the lot represented. Testing shall be performed in accordance with 4.7.2.

3.8.2 Actuation force. The force required to pull the shaft assembly from the initiator body when the shaft assembly is in the armed position shall be 20 to 40 pounds. Failure to meet this requirement shall result in rejection of the lot represented. Testing shall be performed in accordance with 4.7.3.

3.8.3 Ballistic output. The output of each initiator tested shall be verified by confirming that the dent produced in the witness plate is 0.001 inch deep, minimum. Failure to meet this requirement shall result in rejection of the lot represented. Testing shall be performed in accordance with 4.7.4.

3.8.4 Mechanical failure. The initiator shall function in accordance with the performance requirements specified herein without mechanical failure, such as cracking, breaking, deforming, etc. (see 6.4.1). Failure to meet this requirement shall result in rejection of the lot.

3.9 Workmanship. Initiators shall be constructed and finished in a manner to assure compliance with all the provisions of this specification and the applicable drawings. Special attention shall be directed to dimensions, finishes, coatings, and cleanliness.

4. VERIFICATION

4.1 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.2).

b. Production conformance inspection (see 4.3).

c. Lot acceptance conformance inspection (see 4.4).

4.2 First article inspection. Unless otherwise specified (see 6.2), a first article sample of 35 assembled initiators and 10 unassembled sets of components shall be manufactured using the same methods and procedures proposed for the production lot. First article inspection shall include the examinations and tests specified in 4.2.1 and 4.2.2. Any production prior to written notification of acceptability of the first article sample by the contracting agency is at the contractor’s risk.

4.2.1 Component inspection. Ten sets of initiator components shall be inspected to verify conformance with the requirements of 3.3. Failure to meet these requirements shall result in rejection of the first article sample.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T04:32Z
Check the source to verify that this is the current version before use.

4.2.2 Initiators. Thirty-two initiators shall be tested as described in table I. The 32 initiators shall be randomly divided into 7 groups, A through G. The quantity of initiators in each group shall be as specified in table I. Three additional initiators shall be retained for investigative purposes. A first article sample acceptable for functional and environmental testing is defined as a sample that has met the requirements of 3.2 through 3.5 of this specification. First article sample acceptance shall consist of the tests shown in table I. Failure of any initiator shall be cause for rejection of the first article sample. Unless otherwise specified (see 6.2), the environmental tests specified in table I shall be performed in accordance with MIL-C-83124. The ballistic tests shall be performed using the test fixture specified in 4.7.1. Acceptance shall be based on integrity of the parts and legibility of markings after environmental exposures and acceptable ballistic performance in accordance with the requirements of 3.8.

TABLE I. First article tests.

Test/inspection	Requirement paragraph	Test paragraph	Test group and quantity						
			A 4	B 3	C 9	D 4	E 4	F 4	G 4
Visual inspection	3.6.2	4.5.1.2	4	3	9	4	4	4	4
Radiographic	3.6.3	4.5.2.2	4	3	9	4	4	4	4
Residual magnetism	3.6.4	4.5.4	4	3	9	4	4	4	4
Forty-foot drop	3.7.1	4.6.1	4	--	--	--	--	--	--
Six-foot drop	3.7.2	4.6.2	--	3	--	--	--	--	--
Temp/humidity	3.7.3	4.6.3	--	--	9	--	--	--	--
Shock	3.7.4	4.6.4	--	--	--	4	--	--	--
Vibration	3.7.5	4.6.5	--	--	--	--	4	--	--
Dust	3.7.6	4.6.6	--	--	--	--	--	4	--
Salt fog	3.7.7	4.6.7	--	--	--	--	--	--	4
Ballistic test (-65 °F)	3.8	4.7	--	--	3	1	1	1	1
Ballistic test (70 °F)	3.8	4.7	--	3	3	2	2	2	2
Ballistic test (200 °F)	3.8	4.7	--	--	3	1	1	1	1

4.3 Production conformance inspection. Production conformance inspection shall include the examination and tests of items as listed in table II. Any unit failing to meet these requirements shall be rejected and removed from the lot.

TABLE II. Production tests and examinations.

Item	Nature of test	Requirement	Test
Primary component	Single lot verification	3.4	--
Primer	Age and inspection	3.4.1	--
Transfer charge	Visual inspection	3.5.1	4.5.1.1
Transfer charge	Leakage	3.5.3	4.5.3
Transfer charge	Radiographic inspection	3.5.2	4.5.2.1
Initiator	Visual inspection	3.6.2	4.5.1.2
Initiator	Radiographic inspection	3.6.3	4.5.2.2
Initiator	Residual magnetism	3.6.4	4.5.4

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T04:32Z
Check the source to verify that this is the current version before use.

4.4 Lot acceptance conformance inspection. Lot acceptance inspection shall consist of verification of the characteristics classified on NAVSEA Drawing 6106319 and verification of the requirements and tests specified in table III. Unless otherwise specified (see 6.2), the lot acceptance test sample shall be determined as specified in 4.4.1. Failure of one or more initiators from the sample shall be cause for rejection of the lot represented.

TABLE III. Lot acceptance tests.

Test/Inspection	Requirement paragraph	Test paragraph	Quantity
Visual inspection	3.6.2	4.5.1.2	all
Radiographic	3.6.3	4.5.2.2	all
Residual magnetism	3.6.4	4.5.4	all
Ballistic test (-65 °F)	3.8	4.7	⅓ sample
Ballistic test (70 °F)	3.8	4.7	⅓ sample
Ballistic test (200 °F)	3.8	4.7	⅓ sample

4.4.1 Lot sample. A random sample from each production lot shall be selected in accordance with table IV. In addition to the sample required for lot acceptance, three additional initiators shall be furnished for investigative purposes. The production lot shall contain both the test and retained sample quantity.

TABLE IV. Production lot test sample size.

Lot size	Sample size
1-50	9
51-90	15
91-150	21
151-280	33
281-500	51
501-1200	81

4.5 Inspections and tests.

4.5.1 Visual inspection.

4.5.1.1 Transfer charge visual inspection. All transfer charges produced under contract shall be visually examined. Any transfer charges produced under contract may be rejected for any of the defects specified in 3.5.1. Failure to meet the requirement of 3.5.1 shall result in the rejection of the transfer charge.

4.5.1.2 Initiator assembly visual inspection. All initiator assemblies produced under contract shall be visually examined. Any initiator assembly may be rejected for any of the defects specified in 3.6.2. Failure to meet the requirement of 3.6.2 shall result in the rejection of the initiator.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T04:32Z
Check the source to verify that this is the current version before use.

4.5.2 Radiographic inspection. All specified items shall be radiographically examined in accordance with ASTM E1742/E1742M (x-ray), ASTM E748, or ASTM E545 (n-ray) as applicable. One unit may be used as the penetrometer. Any observable imperfection in components or assembly shall be cause for rejection. All items shall be identified with serial numbers in consecutive numerical order beginning with 00001. The items shall be arranged on boards or trays in consecutive order with any missing serial numbers identified on the radiographic plate. Each radiograph shall carry a permanent identification of the items displayed thereon. The radiographic identification shall include item nomenclature, the contract number, the complete lot number assigned to that lot, and the span of serial numbers displayed. Defective items found during radiographic review are to be marked on the radiograph and, prior to shipment, all defective items shall be removed from the production lot. Radiographs of the entire production lot and a description of the defects of removed items shall accompany the ballistic sample to the activity conducting the production lot acceptance tests. Failure to meet the requirement of 3.5.2 or 3.6.3, as applicable, shall result in the rejection of that item.

4.5.2.1 Transfer charge radiographic inspection. Each transfer charge shall be positioned such that its center plane passing through both primers is perpendicular to the radiographic beam. Radiographs shall be identified by date, contract number, part number, lot number, and serial number.

4.5.2.2 Initiator radiographic inspection. Each initiator shall be positioned such that the centerline of the initiator and the centerline of the safety pin are both perpendicular to the radiographic beam.

4.5.3 Leak test. All transfer charges shall be tested with a dry gas leak detector of sufficient sensitivity to ascertain whether the cartridges meet the requirement of 3.5.3. Documentation of this test will be as specified (see 6.2).

4.5.4 Residual magnetism. All initiators shall be subjected to the residual magnetism test. The assembly shall be tested for excessive residual magnetism in an area free of local magnetic effects by placing the test initiator 6 inches from the end and at the same height as the compass in a north-south horizontal position with the compass set in an east-west heading. The initiator shall be moved at a speed no greater than 10 feet per minute past the compass in a longitudinal direction for its entire length, rotated 90 degrees in the horizontal position about its longitudinal axis and moved slowly past the compass. This procedure shall be repeated for 90-degree rotation of the initiator. Failure to meet the requirement of 3.6.4 shall result in the rejection of the initiator.

4.6 Environmental tests.

4.6.1 Forty-foot drop test. Test initiators shall be dropped from a height of 40 to 41 feet in accordance with test 103.2 of MIL-STD-331. The impact surface shall be a 2-inch minimum thick steel plate embedded in concrete. The shipping caps/plugs and the quick release safety pin shall be removed and the handle shall be in the unarmed position. The drop orientation shall be equally divided between handle-up and handle-down. If any initiator fails to meet the requirements of 3.7.1, the first article sample shall be rejected.

4.6.2 Six-foot drop test. Test initiators shall be dropped from a height of 6 feet + 2 inches – 0 inches onto a 2-inch minimum thick steel plate embedded in concrete with the shipping caps/plugs and the quick release safety pin removed. The handle shall be in the unarmed position. The drop orientation shall be equally divided between handle-up, handle-down, and horizontal orientation. If any initiator fails to meet the requirements of 3.7.2, the first article sample shall be rejected.

4.6.3 Temperature/humidity cycling test. Test initiators shall be subjected to temperature/humidity environments in accordance with MIL-C-83124, except that the altitude shall be 0 feet (14.7 pounds per square inch absolute). If any initiator fails to meet the requirements of 3.7.3, the first article sample shall be rejected.

4.6.4 Shock test. Test initiators shall be subjected to shock tests in accordance with method 516, procedure I of MIL-STD-810 with the safety pin removed. The shock pulse wave shall be a terminal peak sawtooth. The peak amplitude shall be 20g and the duration shall be 11 milliseconds. If any initiator fails to meet the requirements of 3.7.4, the first article sample shall be rejected.

4.6.5 Vibration test. Test initiators shall be subjected to the vibration test in accordance with method 514, procedure I, parts 1, 2, and 3 of MIL-STD-810 using curve Z up to 2000 cycles per second. The tee-handle shall be in the safe position, but the safety pin shall be removed. Test units shall be vibrated at the temperatures specified in table I. If any initiator fails to meet the requirements of 3.7.5, the first article sample shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T04:32Z
Check the source to verify that this is the current version before use.

4.6.6 Dust test. Test initiators shall be subjected to the dust test in accordance with method 510 of MIL-STD-810. If any initiator fails to meet the requirements of 3.7.6, the first article sample shall be rejected.

4.6.7 Salt fog test. Test initiators shall be subjected to a salt fog in accordance with method 509 of MIL-STD-810. If any initiator fails to meet the requirements of 3.7.7, the first article sample shall be rejected.

4.7 Ballistic tests.

4.7.1 Tests. Sample initiators shall be randomly selected to be representative of the complete lot. One third of samples shall be temperature conditioned at each of the following temperatures for 4 hours minimum but not to exceed 24 hours maximum: –65±5 °F, 70±5 °F, and 200±5 °F. The 24-hour maximum does not apply to the 70 °F conditioning. Each sample shall be fired in the test fixture described in NAVAIR Drawing 857AS800 within 5 minutes after removal from conditioning. If the 5-minute limit is exceeded, the sample shall be reconditioned for twice the time out of conditioning. The initiators shall then be actuated and shall meet the requirements of 3.8.

4.7.2 Arming torque. Test initiators shall be mounted in the test fixture described in NAVAIR Drawing 857AS800 with the quick release pin (safety pin) removed and instrumentation shall be provided to measure the arming torque required to rotate the shaft assembly 90 degrees from the safe position to the armed position. This torque requirement does not apply to the torque required to rotate the handle from the armed position back to the safe position. Failure to function and meet the requirements of 3.8.1 shall result in the rejection of the lot.

4.7.3 Actuation force. Test initiators shall be mounted in the test fixture described in NAVAIR Drawing 857AS800 with the quick release pin (safety pin) removed and instrumentation shall be provided to measure the force required to pull the shaft assembly out of the initiator. Failure to function and meet the requirements of 3.8.2 shall result in the rejection of the lot.

4.7.4 Ballistic output. A 0.062-inch thick witness plate of aluminum alloy 6061-T6 shall be secured to the exposed mild detonating cord (MDC) of the output test tip, in accordance with NAVAIR Drawing 841AS450-1. Failure to function and meet the requirements of 3.8.3 shall result in the rejection of the lot.

4.7.5 Test failure. Any failures or defects found during lot acceptance testing shall cause the lot to be rejected. If test failure is not attributed to the initiator, the data may be disregarded for that firing and a retest permitted with a new initiator.

4.7.6 Retest. There shall be no retest, except as defined and allowed in 4.7.5. Any defects or failures during lot acceptance testing may be cause for rejection.

5. PACKAGING

5.1 Packaging. For acquisition purposes, the packaging requirements shall be specified in the contract or order (see 6.2). When packaging of materiel is to be performed by DoD or in-house contractor personnel, these personnel need to contact the responsible packaging activity to ascertain packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activities within the Military Service or Defense Agency, or within the military service's system commands. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The JAU-54/A is a cockpit mounted tee handle initiator used in the canopy removal system of AH-1 helicopters. The canopy removal system is only used in military aircraft; therefore, the initiator has no commercial application.

6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of this specification.

b. When first article inspection is required (see 3.1).

c. When any divergence will require technical evaluation and potential design certification testing (see 3.3).

d. When a copy of the purity certification is required to be furnished with the contract data (see 3.4.3).

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T04:32Z
Check the source to verify that this is the current version before use.

e. When each transfer charge is required to have a unique serial number permanently marked on it (see 3.5).

f. When the serial number of the transfer charge installed in each initiator assembly is required to be recorded in a marriage log to be furnished with the contract data (see 3.6.1).

g. First article sample size, if other than as specified (see 4.2).

h. When environmental tests do not need to be performed in accordance with MIL-C-83124 (see 4.2.2).

i. Determination of lot acceptance test sample, if other than as specified (see 4.4).

j. When documentation certifying that all transfer charges successfully passed the leak test is required (see 4.5.3).

k. Packaging requirements (see 5.1).

l. Date and place of delivery.

m. That the safety precaution requirements of the "Contractors' Safety Manual for Ammunition, Explosives and Related Dangerous Material," DOD 4145.26M are applicable. NOTE: When this specification is used as a part of the description of work to be accomplished by a Government activity, the safety precautions requirements of "Ammunition and Explosives," OP 5, are applicable.

6.3 First article. When a first article inspection is required (see 3.1), the items should be a first article sample. The first article should consist of 35 assembled initiators and 10 complete sets of components. The contracting officer should include specific instructions in acquisition documents regarding arrangements for examinations, approval of first article test results, and disposition of first articles. Invitation(s) for bid(s) should provide that the U.S. Government reserves the right to waive the requirements for samples for first article inspection to those bidders offering a product that has been previously acquired or tested by the U.S. Government, and that bidders offering such products who wish to rely on such production or test must furnish evidence with the bid that prior U.S. Government approval is presently appropriate for the pending contract.

6.3.1 First article sample. A first article sample may be required at the contracting agency's discretion or if:

a. 2 or more years have passed since the manufacturer last produced the JAU-54/A,

b. there has been significant turnover in personnel,

c. there have been major changes to the production facility, or

d. there has been transfer of production to a new facility.

6.4 Definitions. For the purpose of this specification, the following definitions apply.

6.4.1 Mechanical failure. Any deformation or breakage of a part or separation of parts that is other than a design function.

6.4.2 Primary components. Components from a single lot.

6.4.3 Test fixtures. A test fixture is the apparatus used to ballistically test the units.

6.5 Packaging. The inner and intermediate packing and packaging should be in accordance with SPI (AM) P1377-13.

6.6 Subject term (keyword) listing.

AH-1 helicopter
Canopy removal
Propellant

6.7 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T04:32Z
Check the source to verify that this is the current version before use.

CONCLUDING MATERIAL

Preparing activity:
Navy – OS
(Project 1377-2023-002)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T04:32Z
Check the source to verify that this is the current version before use.