INCH-POUND
MIL-PRF-32052/6(CR)
AMENDMENT 1
6 October 2000

PERFORMANCE SPECIFICATION SHEET

BATTERY, RECHARGEABLE, SEALED, BB-XX16/U

This amendment forms a part of MIL-PRF-32052/6(CR), dated 7 December 1999, and is approved for the Communications-Electronics Command, Department of the Army and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

Delete in its entirety and substitute the attached page.

Custodian:
Army – CR

Preparing Activity:
Army - CR

(Project 6140-A923-005)

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T04:29Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Rated capacity (C/5): 0.22 AH.
Voltage (nominal): 24 volts.
Weight (maximum): 0.27 kg (0.59 lbs).
Terminals: 2 each nickel, flat surface.
Charge rate for testing and on battery (C/2 for 2-3 hrs): 0.22 amps.

Discharge Rates	5 Second Voltage(V)	Final Voltage(V)	Current (Amps)
C/5	-	20.0	0.045
$0.5C_5$	-	20.0	0.20
$2C_5$	22.0	20.0	0.80
$4C_5$	-	20.0	1.60

Test	Discharge Current (amps)	Capacity Requirement (AH)
Full Capacity Discharge	0.20	0.20
Cycle Life, 224 cycles	0.20	0.15
Overcharge, 24 hours	0.20	0.20
High Rate Discharge	0.80	0.13
Low Temperature Discharge at -30°C (-22°F)	0.20	0.07
Retention of Charge 7 days at 50°C (122°F)	0.20	0.12
Pulse Discharge 1.6 amps, 5 seconds on, 25 seconds off, continuously to 20 volts	1.60	0.13
Vibration	0.045	0.22

Mounting screws for connector: Not applicable.

Terminal markings: The positive terminal marking may be painted red. The negative terminal may be painted black.

Terminal: The two terminals shall be low resistance flat contacts of nickel.

Electrical leakage: Not applicable.

Immersion: Not applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T04:29Z
Check the source to verify that this is the current version before use.