INCH-POUND

MIL-DTL-3943/21F
10 September 2007
SUPERSEDING
MIL-DTL-3943/21E
31 July 2006

DETAIL SPECIFICATION SHEET

DECORATION, SILVER LIFE-SAVING MEDAL AND BAR, COAST GUARD

This specification is approved for use by all Departments and Agencies of the Department of Defense.


The requirements for acquiring the product described herein shall consist of this specification sheet and the latest issue of MIL-DTL-3943.



OBVERSE -1, -3



OBVERSE -2, -4



REVERSE



REVERSE

DASH NO.
- -1: Silver Life-Saving Medal, Regular Size
- -2: Silver Life-Saving Bar, Regular Size
- -3: Silver Life-Saving Medal, Miniature Size
- -4: Silver Life-Saving Bar, Miniature Size

FINISH: Oxidized, Buffed Relieved and shall match The Institute of Heraldry (TIOH) Metal Finish Chip Number 14.

MATERIAL:

-1, -3:
PENDANT AND SUSPENSION BAR: 99 Percent Pure Silver
PENDANT SWIVEL, SWIVEL EYE, ATTACHMENT RING AND PENDANT RIBBON ATTACHMENT BAR: Sterling Silver
PIN, HINGE AND CATCH (ON ATTACHMENT BAR): Nickel Silver

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:51Z
Check the source to verify that this is the current version before use.

-2, -4:
PENDANT AND SUSPENSION BAR: 99 Percent Pure Silver
PIN, HINGE AND CATCH (ON ATTACHMENT BAR): Nickel Silver

DIMENSIONS:

DASH NO. -1, -3:
PENDANT:
DIAMETER:
-1: 1-15/32 inches (REF)
-3: 3/4 inch (REF)
THICKNESS (at rim):
-1: 0.120 inch ± 0.010 inch
-3: 0.080 inch ± 0.010 inch
SUSPENSION BAR:
HEIGHT (overall):
-1: 15/16 inch (REF)
-3: 1/2 inch (REF)
WIDTH (overall):
-1: 1-9/16 inches (REF)
-3: 25/32 inch (REF)
THICKNESS (at thickest point):
-1, -3: 0.095 inch ± 0.010 inch

DASH NO. -2, -4:
HEIGHT (overall):
-2: 9/16 inch (REF)
-4: 9/32 inch (REF)
WIDTH (overall):
-2: 1-21/32 inches (REF)
-4: 53/64 inch (REF)
THICKNESS (at thickest point):
-2, -4: 0.095 inch ± 0.010 inch

WEIGHT (minimum):

-1 (PENDANT AND SUSPENSION BAR ONLY, ASSEMBLED):	560 Grains
-2 (INCLUDING ATTACHING DEVICE):	144 Grains
-3 (PENDANT AND SUSPENSION BAR ONLY, ASSEMBLED):	270 Grains
-4 (INCLUDING ATTACHING DEVICE):	80 Grains

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. Thickness is given for information only. Weight governs.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:51Z
Check the source to verify that this is the current version before use.

3. The suspension bar ring shall be fabricated from 0.050 inch ± 0.002 inch nominal diameter wire for Dash No. -1 and 0.032 inch ± 0.002 inch nominal diameter wire for Dash No. -3. The rings shall be soldered to the vertical center line of the suspension bar 5/32 inch ± 1/64 inch above the tip of the eagle's beak for Dash No. -1 and 5/64 inch ± 1/64 inch for Dash No. -3.

4. The swivel eye ring shall be fabricated from 0.044 inch ± 0.002 inch nominal diameter wire for Dash No. -1 and 0.030 inch ± 0.002 inch nominal diameter wire for Dash No. -3. The rings shall be swaged in the swivel device.

5. The swivel device shall be hard soldered to the top of the pendant.

6. The ribbon attachment bar shall conform to Type III Ribbon Bar as shown on TIOH Drawing 4-4-86.

7. The pin and catch attaching device for Dash Nos. -2 and -4 shall be located on and soldered to the horizontal center line equidistant from each side. The attaching device shall be 1-5/8 inch ± 1/64 inch for Dash No. -2 and 13/16 inch ± 1/64 inch for Dash No. -4.

8. Decoration set shall consist of a regular size medal and bar, a service ribbon and a lapel button all packaged in a presentation case conforming to MIL-C-14633, Type VIII, Style 6 with a Class 1, 1A or 3 pad.

9. The ribbon for the pendant drape and service ribbon shall conform to MIL-DTL-11589/135.

10. The lapel button shall conform to MIL-DTL-11484/8.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodians:
Army - IH
Navy – NU

Preparing activity:
Army - IH
(Project No. 8455-2007-161)

Review activities:
Coast Guard - CG
DLA - CT

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:51Z
Check the source to verify that this is the current version before use.