NOT MEASUREMENT SENSITIVE

MIL-DTL-3943/24G
11 May 1999
SUPERSEDING
MIL-DTL-3943/24F
1 May 1997

DETAIL SPECIFICATION SHEET

DECORATION, PURPLE HEART

Inactive for new design after 14 January 1999.

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-3943 listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation.



MATERIAL:

BASE: Gilding Metal
DEVICE (Shield): Gilding Metal
DEVICE (Profile): Red Brass
HEART INSERT: Purple Plastic

DASH NO:
-1: Regular Size
-2: Miniature Size

FINISH:

BASE: Hard Enameled, Gold Plated, Matte Finish and shall match TIOH Metal Finish Chip Number 7.
DEVICE (profile): Gold Plated, Matte Finish and shall match TIOH Metal Finish Chip Number 7.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:53Z
Check the source to verify that this is the current version before use.

DEVICE (shield): Hard Enameled, Gold Plated, Matte Finish and shall match TIOH Metal Finish Chip Number 7.
HEART INSERT: Mirror-like Polished.

DIMENSIONS:

BASE:
HEIGHT:
-1 (including lug): 1-7/8 inches (REF)
-2 (including lug and pendant ribbon ring): 29/32 inch (REF)
WIDTH (overall):
-1: 1-3/8 inches (REF)
-2: 3/4 inch (REF)
THICKNESS:
-1: (on profile platform): 0.160 inch ± 0.005 inch
-2: (on shield): 0.110 inch ± 0.005 inch

DEVICE (profile):
HEIGHT (overall):
-1: 13/16 inch (REF)
-2: 11/32 inch (REF)
WIDTH (overall):
-1: 9/16 inch (REF)
-2: 1/4 inch (REF)
THICKNESS (at thickest point)
-1: 0.070 inch ± 0.005 inch
-2: 0.055 inch ± 0.005 inch

PLASTIC INSERT:
HEIGHT:
-1: 1-3/32 inches (REF)
-2: 9/16 inch (REF)
THICKNESS (minimum at center):
-1: 0.055 inch ± 0.005 inch tapering at edge to 0.020 inch maximum
-2: 0.055 inch ± 0.005 inch
WIDTH (overall):
-1: 1 inch (REF)
-2: 1/2 inch (REF)

DEVICE (shield):
HEIGHT (overall)
-1: 3/8 inch (REF)
WIDTH (overall):
-1: 5/32 inch (REF)
THICKNESS (at thickest point):
-1: 0.031 inch ± 0.005 inch

ASSEMBLED THICKNESS:
-1: 0.230 inch ± 0.010 inch
-2: 0.225 inch ± 0.010 inch

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:53Z
Check the source to verify that this is the current version before use.

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. Profile device on decorations shall be attached to the base by means of two drive pins having a minimum length of 1/8 inch. Drive pins shall be located on the vertical center line of the device, equidistant from each end and shall be soldered, swaged or extruded as an integral part of the profile. Drive pins shall not protrude or be noticeable on reverse of medal.

3. The shield device shall be attached to the base using soft solder.

4. Enamel colors shall be as indicated. The colors shall conform to TIOH Hard Enamel Color Chip Numbers listed below.

COLOR	CHIP NO.
Red	4
Green	11
Purple	22
White	28

5. Epoxy resin (stoning epoxy) may be used in lieu of hard enamel at the option of the manufacturer. When epoxy resin is used in lieu of hard enamel, the material requirement shall be gilding metal or red brass.

6. Pendant ribbon ring for Dash No. -1 shall be formed from 0.57 inch ± .002 inch diameter brass wire and shall have a rectangular design and an outside dimension of 15/32 inch ± 1/32 inch in width and 11/32 inch ± 1/32 inch in height.

7. Lug for Dash No. -1 shall not be completely drilled through but shall be drilled in a minimum of 1/16 inch from each side. The hole shall be 1/16 inch + 1/32 inch -0 inch, in diameter.

8. When glued in place, the color of the plastic insert shall match Purple, Cable No. HP 67115 from the Department of Defense Standard Shades of Heraldic Yarns for Embroidery and Ribbons (1993 Edition).

9. Plastic insert shall be glued in place using cellulose ester cement.

10. Enamel may be used in place of plastic insert for Dash No. -2.

11. Decoration set shall consist of a regular size medal, a service ribbon, and a lapel button all packaged in a presentation case conforming to MIL-DTL-14633, Type VIII, Style 6 with a Class 1, 1A or 3 pad.

12. The ribbon for the pendant drape and service ribbon shall conform to MIL-DTL-11589/126.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:53Z
Check the source to verify that this is the current version before use.

13. The lapel button shall conform to MIL-DTL-11484/18.

14. The shield device for Dash No. -2 is an integral part of the base.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodians:
Army - IH
Air Force - 45
Navy - NU

Preparing activity:
Army - IH

Review activities:
Air Force - 32, 82, 99
Navy - MC
Coast Guard - CG
DLA - CT

(Project No. 8455-0978)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:53Z
Check the source to verify that this is the current version before use.