MILITARY SPECIFICATION

HYDRAULIC FLUID, ARRESTING GEAR

* This amendment forms a part of Military Specification MIL-H-5559A(WEP) dated 22 April 1964.

By this amendment, basic Specification MIL-H-5559A(WEP) is changed to read MIL-H-5559A(AS).

PAGE 2

2.1 Standards: Delete "MIL-STD-129 Marking for Shipment and Storage" and substitute "MIL-STD-290 Packaging, Packing and Marking of Petroleum and Related Products."

3.2.1 Delete and substitute:

"3.2.1 Triethanolamine phosphate - The triethanolamine phosphate shall be a mixture of commercially pure triethanolamine and commercially pure phosphoric acid. Any water present in the mixture shall be included in the total percent of water of the hydraulic fluid."

PAGE 4

* 4.1 Delete and substitute:

"4.1 Responsibility for inspection - Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements."

Source: https://assist.dla.mil -- Downloaded: 202640-17T05:12Z
Check the source to verify that this is the currentversion before use.

Add new paragraph:

* "4.1.1 Quality conformance inspection - Quality conformance inspection shall consist of all the examinations and tests of this specification."

* 4.2 Delete and substitute:

"4.2 Quality conformance inspection samples - The quality conformance inspection samples shall consist of samples for tests (4.2.3), sample of NaMBT inhibitor (4.2.4), and samples for examination of filled containers (4.2.5). Samples shall be labeled completely with information identifying the purpose of the sample, name of product, specification number, lot number and container number (5.3), date of sampling and contract number."

* 4.2.1 Delete and substitute:

"4.2.1 Lot - A lot is an indefinite number of containers (55 gallon drums or 5 gallon cans) of identical size and type, offered for acceptance, and filled with a homogeneous mixture of material from one isolated container and manufactured in a single plant run (not exceeding 24 hours) through the same processing equipment, with no change in ingredient material."

PAGE 5

* 4.2.2 Delete and substitute:

"4.2.2 Samples for tests - A one gallon sample of finished hydraulic fluid shall be taken from the first and last container in each lot. In addition, a one gallon sample shall be selected at random from containers in each lot in accordance with Method 8001 of Standard Federal Test Method Standard No. 791 (ASTM-D270). All samples shall be subjected to all the applicable tests of this specification (4.3). A copy of the test report shall be forwarded to the Commanding Officer, Naval Air Engineering Center, Attn: Code 9151, Lakehurst, N.J. 08733. Test report shall contain numerical test values. Statements such as "passed" or "failed" are not acceptable. If any of the samples fail any of the requirements of this specification (Section 3), the lot represented by the sample shall be rejected.

PAGE 10

*5.2 Delete and substitute:

"5.2 Packing - Packing of the hydraulic fluid shall be in accordance with MIL-STD-290 Level A or C as specified (6.2). Containers shall be inspected for cleanliness and dryness prior to filling."

Source: https://assist.dla.mil -- Downloaded: 202640-17T05:12Z
Check the source to verify that this is the currentversion before use.

* 5.3 Delete and substitute:

"5.3 Marking - In addition to any special marking required by the contract or order, each container shall be marked in accordance with the requirements of Standard MIL-STD-290 and shall include the container number which shall reflect the order of filling."

* Add new paragraph:

"5.3.2 Instruction marking - The following instruction marking shall appear on each container:

> Instructions: Obliterate all markings when empty. This fluid is not interchangeable with any other type or grade of hydraulic fluid."

The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Preparing activity:
Navy - AS
(Project No. 9150-N452)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T05:12Z
Check the source to verify that this is the current version before use.