NOT MEASUREMENT SENSITIVE


MIL-B-41809/44A
21 September 1994
SUPERSEDING
MIL-B-41809/44
14 June 1991

MILITARY SPECIFICATION SHEET

BADGE, IDENTIFICATION, RECRUITER, MEDICAL DEPARTMENT, ARMY

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-B-41809.



MATERIAL: Gilding Metal

FINISH: Hard Enameled, Nickel Plated, Silver Plated, Oxidized, Relieved, Matte Finish and shall match TIOH Metal Finish Chip Number 14.

DIMENSIONS:
HEIGHT: 2 inches (5.08 cm) (REF)
WIDTH: 2 inches (5.08 cm) (REF)
THICKNESS (At edge): 0.060 inch ± 0.010 inch (0.152 cm ± 0.025 cm)

AMSC N/A FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:42Z
Check the source to verify that this is the current version before use.

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. Enameled area shall be Maroon as indicated. The color shall conform to the TIOH color chip Number 6 or the standard sample:

3. Epoxy resin (stoning epoxy) may be used in lieu of hard enamel at the option of the manufacturer.

4. The attaching device shall be prong with clutch type. Three prongs shall be located on a circle 1-11/16 inch (4.29 cm) in diameter. Each prong shall be 120 degrees apart with one prong located on the vertical center line at the top of the badge.

5. A full forcer shall be used to bring up the details of the design and reduce the overall weight.

Custodian:
Army - IH

Preparing Activity:
Army - IH

Review Activity:
DLA - CT

(Projected No. 8455-0766)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:42Z
Check the source to verify that this is the current version before use.