NOT MEASUREMENT SENSITIVE


MIL-B-41809/45
22 December 1992

MILITARY SPECIFICATION SHEET

BADGE, IDENTIFICATION, UNITED STATES STRATEGIC COMMAND

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-B-41809.



MATERIAL:
RED BRASS - Base with rope design, disk with clouds and gauntlet device
GILDING METAL - Disk with lettering

DIMENSIONS:
BASE PLATE -
DIAMETER: 1-5/8 inches (4.13 cm) REF
THICKNESS (Without Rope): 0.040 inch ± 0.005 inch (0.101 cm ± 0.012 cm)
ROPE (Without Base Plate Thickness)
THICKNESS (Overall): 0.080 inch ± 0.005 inch (0.203 cm ± 0.012 cm)
DISK WITH LETTERING -
DIAMETER: Outside - 1-1/2 inch (3.81 cm) (REF)
Recessed Center - 15/16 inch (2.38 cm) (REF)
THICKNESS: Outer Circle - 0.085 inch ± 0.005 inch (0.215 cm ± 0.012 cm)
Recessed Center - 0.050 inch ± 0.005 inch (0.127 cm ± 0.012 cm
DISK WITH CLOUD DESIGN -
DIAMETER: 15/16 inch (2.38 cm) (REF)
THICKNESS (At Thickest Point): 0.065 inch ± 0.005 inch (0.165 cm ± 0.012 cm)
DEVICE (Gauntlet) -
HEIGHT (Overall): 7/8 inch (2.22 cm) (REF)
WIDTH (Overall): 3/4 inch (1.91 cm) (REF)
THICKNESS (At Thickest Point): 0.060 inch ± 0.005 inch (0.152 cm ± 0.012 cm)

AMSC N/A FSC 8455
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:42Z
Check the source to verify that this is the current version before use.

FINISH:
BASE AND ROPE: Gold Plated, Bright Polished
DISK WITH LETTERING: Hard Enameled, Nickel Plated, Gold Plated, Mirror-like Polished; Stars Shall be Nickel Plated , Mirror-like Polished
DISK WITH CLOUD DESIGN: Nickel Plated, Silver Plated, Oxidized, Relieved
DEVICE (GAUNTLET): Nickel Plated, Mirror-like Polished

NOTES:
1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. The rope shall be fabricated from three pieces of brass wire 0.035 inch + 0.005 inch - 0 (0.088 cm + 0.012 cm - 0) twisted approximately 14 turns per inch. This rope shall be hard soldered to the base as shown.

3. The attaching device shall be prong and clutch type. Three prongs shall be located on a 1-1/4 inch (3.18 cm) diameter circle. Each prong shall be spaced 120 degrees apart with the bottom prong located on the vertical center line at the bottom of the badge. Prong length shall be 9/32 inch (0.71 cm).

4. Enameled area shall be as indicated. The blue color used on the disk with lettering shall conform to the TIOH chip number 20 or the standard sample.

5. Epoxy resin may be used in lieu of hard enamel at the option of the manufacturer. The epoxy resin shall be a stoning epoxy, have a shore D hardness of no less than 85 and incorporate an ultraviolet inhibitor.

6. The gauntlet shall have a screw post attached to the reverse side and be made from any type brass. The back screw plate shall be made from any type 1/4 hard brass. The screw post shall be 3/16 inch $\pm$ 1/64 inch (0.48 cm $\pm$ 0.04 cm) long and shall be hard soldered or fused to the gauntlet device in a location to correctly position the gauntlet device to the base. The base plate and disk with lettering shall have a 1/8 inch (0.32 cm) hole centered through each piece. The base plate with rope, disk with lettering, disk with cloud design and gauntlet device shall be assembled as shown. The four pieces shall be secured by a Type A back plate without the post as shown on TIOH drawing 4-4-89.

7. The disk with cloud design shall be lacquered prior to assembly.

Custodian:
Army - IH
Air Force - 11
Navy - NU

Preparing activity:
Army - IH

Review activities:
Air Force - 82,99
Navy - MC
DLA - CT

(Project No. 8455-0697)

User activities:
Air Force - 45

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:42Z
Check the source to verify that this is the current version before use.