NOT MEASUREMENT SENSITIVE


MIL-B-41809/46A
21 September 1994
SUPERSEDING
MIL-B-41809/46
15 July 1993

MILITARY SPECIFICATION SHEET

BADGE, IDENTIFICATION, COMMANDANT'S STAFF, COAST GUARD

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-B-41809.



MATERIAL:
BASE: Red Brass
DEVICE: Gilding Metal

DASH NO.
-1: Regular Size
-2: Miniature Size

FINISH:
BASE: Gold Plated, Matte Finish, Polished Highlights and shall match TIOH Metal Finish Chip Number 8.
DEVICE: Hard Enameled, Nickel Plated, Mirror-like Polished and shall match TIOH Metal Finish Chip Number 16.

AMSC N/A FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:42Z
Check the source to verify that this is the current version before use.

DIMENSIONS:

WIDTH (Point to Point):

BASE:

-1: 2-1/4 inches (5.72 cm) REF

-2: 1-1/2 inches (3.81 cm) REF

DEVICE:

-1: 7/8 inch (2.22 cm) REF

-2: 9/16 inch (1.43 cm) REF

THICKNESS:

BASE (Rope Edge):

-1: 0.085 inch ± 0.010 inch (0.216 cm ± 0.025 cm)

-2: 0.070 inch ± 0.010 inch (0.178 cm ± 0.025 cm)

DEVICE:

-1: 0.060 inch ± 0.010 inch (0.152 cm ± 0.025 cm)

-2: 0.050 inch ± 0.010 inch (0.127 cm ± 0.025 cm)

OVERALL THICKNESS (At Thickest Point):

-1: 0.150 inch ± 0.010 inch (0.381 cm ± 0.025 cm)

-2: 0.120 inch ± 0.010 inch (0.305 cm ± 0.025 cm)

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. Enameled areas shall be as indicated. The blue color used in the lettering, inner and outer circles on the device and the top of the shield shall confor to the TIOH chip number 18 or the standard sample. The red color used in t vertical bars and outline of the shield shall conform to the TIOH chip number 1 or the standard sample.

3. Epoxy resin (stoning epoxy) may be used in lieu of hard enamel at the option of the manufacturer.

4. The device shall be superimposed and secured to the base by rivets or soft solder as shown. When hard enamel is used on the device, the device shall be soft soldered or riveted to the center platform of the base. When epoxy resin is used on the device, the device shall be attached by using rivets. Two rivets shall be soldered or electronically fused on the vertical center line and 5/16 inch (0.79 cm) on centers for Dash -1 and one rivet shall be soldered or electronically fused in the center of the device for Dash -2.

5. The attaching device shall be prong and clutch type. Three prongs shall be located on a 1-3/4 inch (4.45 cm) diameter circle for Dash No. -1 and 1-1/8 inch (2.86 cm) diameter circle for Dash No. -2. Each prong shall be spaced 120 degrees apart with the top prong located on the vertical center line at the top of the badge.

Custodian:
Army - IH
Coast Guard - CG

Preparing activity:
Army - IH

Review activities:
DLA - CT

(Project No. 8455-0766)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:42Z
Check the source to verify that this is the current version before use.