NOT MEASUREMENT SENSITIVE

MIL-B-41809/47
30 September 1994

MILITARY SPECIFICATION SHEET

BADGE, IDENTIFICATION, RECRUITING, COAST GUARD

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-B-41809.



MATERIAL: Red Brass

DIMENSIONS:
DIAMETER: 1-31/32 inches (5.00 cm) (REF)
THICKNESS (Edge): 0.080 inch ± 0.010 inch (0.203 cm ± 0.025 cm)

FINISH: Gold Plated, Mirror-like Polished and shall match TIOH Metal Finish Number 6.

AMSC N/A FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:42Z
Check the source to verify that this is the current version before use.

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. Enameled areas shall be as indicated. The color shall conform to the TIOH chip numbers listed below or the standard sample.

COLOR	CHIP NUMBER
Red	1
Blue	18
White	28

3. Epoxy resin (stoning epoxy) may be used in lieu of hard enamel at the option of the manufacturer.

4. The badge shall be spherically dapped 3/32 inch ± 1/16 inch (0.24 cm ± 0.16 cm) when measured on the reverse side.

5. Attaching device shall be prong and clutch type. Three prongs shall be located on a 1-1/2 inch (3.81 cm) diameter circle. Each prong shall be 120 degrees apart with one prong located on the vertical center line at the top of the badge.

Custodian:
Army - IH
Coast Guard - CG

Review activities:
DLA - CT

Preparing activity:
Army - IH

(Project No. 8455-0771)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:42Z
Check the source to verify that this is the current version before use.