MIL-R-41819C
30 MAY 1986
SUPERSEDING
MIL-R-41819B
31 DECEMBER 1969

MILITARY SPECIFICATION

RIBBON ATTACHMENTS, DECORATION AND MEDAL GENERAL SPECIFICATION FOR

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers ribbon attachments for decorations, medals and service ribbons.

1.2 Classification. Ribbon attachments covered by this specification shall be as specified on the applicable specification sheet (see 2.1 and 6.2).

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be used in improving this document should be addressed to: Director, The Institute of Heraldry, US Army, Cameron Station, Alexandria, VA 22304-5050, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 8455

AMSC N/A
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:44Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

FEDERAL

PPP-B-636 - Boxes, Shipping Fiberboard
PPP-B-676 - Boxes, Set-up

STANDARDS

FEDERAL

FED-STD-151 - Metals; Test Methods

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-147 - Palletized Unit Loads
MIL-STD-794 - Parts and Equipment, Procedures for Packaging of

SPECIFICATION SHEETS

MIL-R-41819/ - For applicable Specification Sheet see Supplement 1

(Copies of specifications, standards, and other Governments documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.2 Other publications. The following document forms a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted shall be those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS shall be the issue of the nongovernment documents which is current on the date of the solicitation.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

ASTM-D-3951 - Standard Practice for Commercial Packaging.

(Application for copies of ASTM publications should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, Pennsylvania 19103.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:44Z
Check the source to verify that this is the current version before use.

(Nongovernment standards and other publications are normally available from the organizations which prepare or which distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, (except for associated detail specifications, specification sheets or MS standards) the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Specification sheets. The individual item requirements shall be as specified herein and in accordance with the applicable specification sheets. In the event of any conflict between requirements of this specification and the specification sheets, the latter shall govern.

3.2 Detail requirements for the individual ribbon attachments. Detail requirements or exceptions applicable to a particular ribbon attachment shall be as specified on the applicable specification sheet. In the event of any conflict between the requirements of this specification and the applicable specification sheet the latter shall govern (see 6.2), except the design as shown on the specification sheet is intended for illustrative purposes only (see 3.5).

3.3 Standard sample. Unless otherwise specified (see 6.2), the contracting officer will furnish a standard sample to be used for matching color and finish only.

3.4 First article. When specified in the contract or purchase order, a sample shall be subjected to first article inspection (see 4.4 and 6.4).

3.5 Materials. Materials shall conform to the referenced specifications sheets and to the requirements specified herein.

3.5.1 Copper base alloys. Copper base alloys shall be roll polished, free from pits, scale (including red oxide), dents, cracks, nicks, deep scratches, segregations and foreign matter that will not be removed by later processing. The chemical composition of the applicable copper base alloys shall be as shown in Table I, when tested as specified in 4.6.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:44Z
Check the source to verify that this is the current version before use.

TABLE I. Chemical composition of copper base alloy.

Alloy	Copper	Nickel 1/	Lead (max)	Iron (max)	Manganese (max)	Zinc	Others (max)
Yellow brass	64.0 to 68.5	-	.15	.05	-	remainder	.15
Red brass	84.0 to 86.0	-	.05	.05	-	remainder	.15
Gilding metal	94.0 to 96.0	-	.03	.05	-	remainder	.13
Bronze	89.0 to 91.0	-	.05	.05	-	remainder	.13
Nickel silver	63.0 to 66.5	16.5 to 19.5	.10	.25	.50	remainder	-

1/ Cobalt counting as nickel.

3.5.2 Silver for plating. Silver for plating shall be not less than 99.5 percent pure silver.

3.5.3 Gold for plating. Gold for plating shall be 24 karat.

3.5.4 Lacquer. Lacquer shall be a pale, clear, synthetic lacquer. The use of pigmented lacquer shall not be permitted.

3.5.5 Solder. All solder shall be hard solder having a melting point of not less than 1075 degrees F.

3.6 Design. The embossed design of the ribbon attachment covered by this specification shall be exact replicas of the designs on the Government loaned hubs (see 3.9) from which the contractor's working dies shall be extracted. Dies shall be tooled and polished to remove any dents, nicks, scratches or other imperfections. Unornamented areas shall be smooth.

3.7 Construction.

3.7.1 Stamping, trimming and piercing. Ribbon attachments shall be struck in such a manner so as to assure a well defined die struck edge. The attachments shall be trimmed and when applicable, pierced to the die struck outline of the area specified. All edges shall be clean, smooth, free from burrs,

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:44Z
Check the source to verify that this is the current version before use.

drag, step and rough edges. The piercing or trimming operation shall not distort the design or alter the shape of the ribbon attachment.

3.7.2 Soldering. Unless otherwise specified on the applicable specification sheet, all solder shall be hard solder specified in 3.5.5. Soldered connections shall be completely joined without excess solder and all excess flux shall be removed. Joints shall be clean, smooth, strong and free from burned or reduced areas. When tested as specified in 4.6.3, the soldered connection shall not separate.

3.7.3 Attaching device. The attaching devices for the ribbon attachments shall be specified on the applicable specification sheet. When prongs are specified, the point of the prongs may be either cone pointed or bias cut. The use of either post type or staple type prongs shall be permitted on all ribbon attachments which have an overall width dimension of 1/2 inch or more. For all ribbon attachments having a width dimension under 1/2 inch, only staple type prongs shall be permitted. Unless otherwise specified on the applicable specification sheet, prongs shall be fabricated from annealed nickel silver or yellow brass wire .025 plus or minus .003 inch in diameter and shall be (3/8 plus or minus 1/32) inch in length. When tested as specified in 4.6.2, the prongs shall not break off nor shall the swaged joint be lifted away from the back. Unless otherwise specified on the applicable specification sheet the staple type prongs shall be soldered or swaged not more than 1/16 inch off-center. Unless otherwise specified the post type prong shall be located not more than 1/16 inch on centers from each other in the vertical plane and not more than 1/32 inch from the applicable center. At the option of the manufacturer, the attaching device for the good conduct clasp may be long staple type prong swaged or soldered in the location specified on the apli-cable specification sheet. The prong shall not lift from the clasp when tested as specified in 4.6.3.

3.7.4 Dimensions. Dimensions indicated as reference dimensions are given for bidding information purposes only. The actual dimensions are controlled by the Government furnished hub.

3.8 Finish. The finish of the face and edges (surfaces visible from the front) of the ribbon attachments shall be as specified on the applicable specification sheet and shall match the finish of the standard sample (see 3.3). Unless otherwise specified the back of the ribbon attachments shall be clean.

3.8.1 Plating. All plating required shall be accomplish by electroplating. Prior to plating, surfaces to be plated shall be cleaned of all matters that may affect the plating. The plating shall be nonporous and continuous over the entire surface. There shall be no cut-through, peeled or blistered plating.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:44Z
Check the source to verify that this is the current version before use.

3.8.1.1 Gold plating. Gold specified in 3.5.3, shall be used for all gold plating. The use of white metal as an undercoating shall not be permitted. When tested as specified in 4.6.4, there shall be no visible chemical reaction, such as evolution of gases.

3.8.1.2 Silver plating. Silver specified in 3.5.2 shall be used for plating. The use of a white metal as an undercoating shall be permitted. When silver plating is required the plating shall have a minimum thickness of 0.0003 inches after finishing. When red brass is used as a base material for ribbon attachments which require a silver plated finish, the complete ribbon attachment must be nickel underplated. The nickel underplating shall be a minimum thickness of 0.00025 inch. When nickel silver is used as a base material, the ribbon attachment may be nickel underplated at the option of the manufacturer.

3.8.1.3 Rhodium plating. When tested as specified in paragraph 4.6.4, no visible chemical reaction shall occur. All brass attachments which are to be rhodium plated shall have a flash of nickel as an underplating.

3.8.2 Lacquering. All metal surfaces (obverse and reverse) except gold plated or rhodium plated attachments and attaching devices shall be thoroughly coated with lacquer specified in 3.5.4. The dry lacquer film shall be hard, continuous, level, adherent and free from lint, dust or other foreign inclusions. At the manufacturer's option, gold plated attachments may also be lacquered. When tested as specified in 4.6.5.1, there shall be no change in the appearance of the lacquered items, except a slight yellowing around the highlights. When tested as specified in 4.6.5.2, the tissue shall not adhere to the lacquered items.

3.8.3 Marking. Quality marks for precious metal ribbon attachments shall be legibly and inconspicuously stamped on the reverse side of the ribbon attachment whenever practical.

3.9 Government loaned property. Hubs will be loaned by the Government and shall be used for making the contractor's working dies necessary for any one contract or order.

3.10 Workmanship. The ribbon attachments shall be clean, well made and shall meet the acceptable quality levels (AQL's) established by this specification.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:44Z
Check the source to verify that this is the current version before use.

any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.4).

b. Quality conformance inspection (see 4.5).

4.3 Sampling for inspection and acceptance. Sampling for inspection and acceptance shall be in accordance with MIL-STD-105 except where otherwise indicated.

4.3.1 Inspection conditions. Unless otherwise specified, all inspections shall be performed in accordance with the test conditions specified in (applicable test method document or applicable paragraph(s) in the specification).

4.4 First article inspection. When a first article is required, inspection of the first article shall be conducted for all provisions applicable for end item examination and tests.

4.5 Quality conformance inspection. Inspection shall be in accordance with the provisions set forth in MIL-STD-105, except where otherwise indicated.

4.5.1 Inspection of component.

4.5.1.1 Testing of component. In addition to the quality assurance provisions of the subsidiary specifications and drawings, testing shall be performed on components and materials listed in Table II for the test characteristic shown. The inspection level shall be S-1. Requirements are applicable to the lot average.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:44Z
Check the source to verify that this is the current version before use.

TABLE II. Testing of components.

Components and lot expressed in terms of	Characteristics	Rqm't ref	Test method	#determ per s/u	Results reported as	Sample unit
Copper base alloy (as applicable) (1 lb)	Chemical composition	3.5.1 and Table I	4.6.1	2 for each element (composite)	Nearest Ø.1% each element	4 oz. of material for each alloy or 1Ø prongs

4.5.1.2 Certification of compliance. Components and materials listed below may be accepted on the basis of a contractor's certification of compliance for characteristics indicated.

Component	Characteristic	Rqm't ref
Silver for plating	Fineness	3.5.2
Gold for plating	Karat and no white metal as an undercoating	3.5.3 and 3.8.1.1
Lacquer	Material identification	3.5.4
Solder	Material identification	3.5.5

4.5.2 Examination for acceptance.

4.5.2.1 End item examination. The defects found during examination shall be classified in accordance with 4.5.2.1.1 and 4.5.2.1.2. The lots shall be inspected in accordance with 4.5.2.1.3. The sample unit for these examinations shall be one ribbon attachment of each type and finish.

4.5.2.1.1 Examination of ribbon attachment for visual characteristics. All ribbon attachments shall be viewed from a distance of 16 to 18 inches under normal daylight conditions. Defects designated by an asterisk shall be classified as major when seriously affecting appearance or serviceability and minor when affecting appearance or serviceability but not seriously.

Examine	Defect	Classification Major	*	Minor
Color and finish	Poor match to approved guide samples; e.g., not highlighted to the same extent as the approved or excessively highlighted	-	*	-
	Discolored; i.e., spot, stain or speck	-	*	-

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:44Z
Check the source to verify that this is the current version before use.

Examine	Defect	Classification Major	*	Minor
	Pit, dent, nick, scratch, pinhole, crack, rupture, segregation, foreign matter or other blemish	-	*	-
	Buff, drag, blushed or cloudy finish	-	*	-
	Any solder spatter or flux on front or edges exposed or concealed by plating	x	-	-
	Not lacquered when required	-	-	x
	Lacquer not set to touch	-	-	x
	Lacquer forms noticeable runs or sags on the front or edges	x	-	-
	Lacquer coating is not continuous, level, smooth or adherent; e.g., is flaking, blistering or peeling	x	-	-
	Lacquer coating has lint, dust or other foreign inclusion	-	*	-
Design	Any detail altered or obscured; i.e., does not conform to Government hub	x	-	-
	Warp, twist or distortion producing irregular surface contour or outline	x	-	-
	Any significant detail not clear, missing or obliterated	x	-	-
	Detail struck over, resulting in a double impression	x	-	-
	Any area not pierced as indicated by the specification sheet	x	-	-
Quality of plating	Surface spotted or open grained; i.e., appearing as pitted, porous or crystalized	x	-	-
	Any plated or gold filled area cut-through, broken, peeling, blistered or otherwise impaired	-	*	-
	Not plated when required or plating is not specified type	x	-	-
Workmanship and construction	Surface or edge not clean, not smooth and not free from burrs, roughness, drag, step or tool marks	-	*	-
	Die struck edge, rim or outline is not well defined	-	*	-
	Not trimmed to die struck edge	-	*	-
	Pierced edge not clean and smooth; e.g., any burr, drag, cutter or file mark	-	-	x
Soldering	Solder does not completely unite component part to base metal; i.e., any perceptible opening between component parts	-	*	-

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:44Z
Check the source to verify that this is the current version before use.

Examine	Defect	Classification Major	*	Minor
	Joints not clean and smooth; e.g., flux or excess solder not removed	-	*	-
	Metal burned or reduced in soldering	-	*	-
	Solder spatter exceeding 3/16 inch in maximum direction	-	-	x
Attaching device	Prongs hooked, blunted or not pointed as required.	-	*	-
	Prong is loose	x	-	-
	Prong missing.	x	-	-
	Not type or size specified	-	-	x
	Not positioned as specified; i.e., not conforming to specification sheet	-	*	-
	Twisted, damaged, deformed or otherwise impaired.	-	*	-
	Staple prongs positioned more than 1/16 inch off center	-	*	-
	Post type prong positioned more than 1/16 inch off center from each other	x	-	-
	Center of both post type prongs located more than 1/32 inch from applicable centerline	x	-	-
Quality marking	Missing, incorrect, illegible not placed as required.	-	-	x

4.5.2.1.2 Examination of ribbon attachments for dimensions. Any dimension that is not within the specified tolerances shall be classified as a defect.

4.5.2.1.3 AQL's and inspection levels. The inspection levels and the acceptable quality levels (AQL's) expressed in defects per hundred units shall be as follows:

	Inspection level	AQL Major	AQL Total
For defects applicable to 4.5.2.1.1	II	2.5	10
For defects applicable to 4.5.2.1.2	S-3	(One class)	4.0

4.5.2.2 End item testing. Testing of the completely fabricated ribbon attachment shall be performed for the characteristics shown herein. The sample unit for end item testing shall be three ribbon attachments. The requirements are applicable to the individual unit with one determination per sample unit. The results shall be reported as pass or fail. The inspection level shall be S-1 and acceptable quality levels (AQL's) shall be 6.5 defects per hundred units.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:44Z
Check the source to verify that this is the current version before use.

TABLE III. End item testing.

Characteristic	Rqm't para	Test method	#determ per s/u	Results reported as
Bending test for prongs	3.7.3	4.6.2	1	Pass or fail
Test for soldered joints	3.7.2	4.6.3	1	Pass or fail
Tests for lacquer:				
Liver of sulphur test	3.8.2	4.6.5.1	1	Pass or fail
Tackiness test	3.8.2	4.6.5.2	1	Pass or fail
Acid test for gold and rhodium electroplating	3.8.1.1., 3.8.1.3	4.6.4	1	Pass or fail
Thickiness test for:				
Silver electro-plating	3.8.1.2	Std. commercial	1	Pass or fail
Nickel electro-plating	3.8.1.2	Std. commercial	1	Pass or fail

4.5.3 Examination for count of ribbon attachments in intermediate containers. Ribbon attachments packaged for shipment shall be examined to determine conformance with package markings and specified quantity. The sample unit for this examination shall be one box (interior package). Any box containing less than the specified or marked quantity of ribbon attachments shall be classified as a defect. The inspection level shall be S-2 and the AQL shall be 4.0 defects per hundred units. The lot size shall be the number of intermediate containers.

4.5.3.1 Examination of preparation for delivery requirements. An examination shall be made to determine that packaging, packing and marking requirements are complied with. Defects shall be scored in accordance with the list below. The sample unit shall be one shipping container fully prepared for delivery with the exception that it need not be sealed. Defects of closure listed below shall be examined on shipping containers fully prepared for delivery. The lot size shall be the number of shipping containers in the end item inspection lot. The inspection level shall be S-2 and the acceptable quality levels (AQL's) shall be 2.5 defects per hundred units.

Examine	Defects
Marking (exterior and interior)	Omitted, incorrect, illegible, of improper size, location, sequence or method of application.
Materials	Any component missing or damaged.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:44Z
Check the source to verify that this is the current version before use.

Examine	Defects
Workmanship	Inadequate application of components, such as, incomplete sealing or closure of container flaps, inadequate stapling. Bulging or distortion of containers.
Weight or content (exterior and interior)	Number of intermediate packages is more or less than required, weight of contents per shipping container exceeds requirements.

4.5.4 Palletization examination. An examination shall be made to determine that the palletization is in compliance with the section 5 requirements. Defects shall be scored in accordance with the list below. The sample unit shall be one palletized unit load fully packaged. The lot size shall be the number of palletized unit loads in the inspection lot. The inspection level shall be S-1 and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 6.5.

Examine	Defect
Finished dimensions	Length, width, or height exceeds specified maximum requirements.
Palletization	Pallet pattern not as specified. Interlocking of loads not as specified. Load not bonded with required straps as specified.
Weight	Exceeds maximum load limits.
Marking	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application

4.6 Tests.

4.6.1 Chemical composition test. Chemical composition shall be determined in accordance with test #111 of Fed-Std-151. Results shall be evaluated to determine compliance with the requirements specified in 3.5.1.

4.6.2 Bending test for prongs. Wire prongs shall be bent three times back and forth through an angle of 90 degrees, after which the prongs and the soldered or swaged connections shall be examined to determine compliance with the requirements specified in 3.7.3.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:44Z
Check the source to verify that this is the current version before use.

4.6.3 Test for hard soldered joints. Hard soldered ribbon attachments shall be placed in an oven maintained at 1065 degrees F., plus or minus 5 degrees F., for 15 minutes. While at this temperature the ribbon attachments shall be lifted by the attaching device and shall be inspected to determine compliance with the requirements specified in 3.7.2. A 15 pound pull test shall be applied to the prongs of the Good Conduct clasp. The pull shall be in the direction of the vertical axis of the prong. The attaching device shall then be examined to determine compliance with paragraph 3.7.3.

4.6.4 Acid test for gold or rhodium plating. Ribbon attachments to be tested for compliance with 3.8.1.1 and 3.8.1.3 may be unlacquered or have the lacquer completely removed with an organic solvent. The acid test shall be conducted as follows: Using a test acid consisting of a solution containing 50 percent by volume nitric acid (specific gravity 1.42) and equal volume of distilled water. At room temperature place a drop of test acid on face of ribbon attachment. The drop shall remain on the ribbon attachment for not less than one minute.

4.6.5 Test for lacquer.

4.6.5.1 Liver of sulphur test. Ribbon attachments to be tested shall be immersed in 2 percent by weight CP liver of sulphur (sulphated potash) water solution, at a temperature of 100 degrees F., plus or minus 10 degrees F., for a period of 3 minutes. The ribbon attachment shall be wiped gently with an absorbent cellulose material or whirled to remove residual moisture and shall be air dried at room temperature (60 to 80 degrees F.) for 1 hour. The ribbon attachment shall then be inspected to determine compliance with the requirements specified in 3.8.2.

4.6.5.2 Tackiness test. At room temperature (60 to 80 degrees F.) press a piece of tissue paper against the lacquered surface for 15 seconds, using any pressure capable of being exerted between thumb and two fingers, after which, the pressure shall be released and the ribbon attachment inspected to determine compliance with the requirement specified in 3.8.2.

5. PACKAGING

5.1 Preservation. Preservation shall be levels A, C or Commercial as specified (see 6.2).

5.1.1 Level A.

5.1.1.1 Unit packaging. Ribbon attachments of one type and dash number only in the quantities specified in Table IV shall be placed in an open style envelope made from not less than 28 substance kraft paper. Each envelope shall be securely sealed to prevent the loss of the contents. The contents of

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:44Z
Check the source to verify that this is the current version before use.

individual envelopes may contain plus or minus 2 percent of the quantities specified in Table IV; however, the intermediate packages shall be contain at least the minimum number specified.

TABLE IV. Unit package.

Sheet No.	Quantity per envelope	Sheet No.	Quantity per envelope
1	25	18	100
2	25	19	50
3	100	20	25
4	100	21	100
5	50	22	50
6	50	23	50
7	100	24	25
8	50	25	50
9	50	26	50
10	50	27	25
11	50	28	50
12	100	29	25
13	25	30	100
14	100	31	100
15	100	32	50
16	100	33	50
17	50	34	50

5.1.1.2 Intermediate packaging. Five hundred ribbon attachments of one type and dash number only shall be preserved in a snug-fitting, set-up paperboard box conforming to type I, variety 1, class A, style 3 or 4 of PPP-B-676. Box closure shall be in accordance with the appendix of the box specification.

5.1.2 Level C. Ribbon attachment shall be packaged to the MIL-STD-794 requirements for this level.

5.1.3 Commercial. Ribbon attachments shall be preserved in accordance with the applicable requirements of ASTM-D-3951.

5.2 Packing. Packing shall be level A, B, C or commercial, as specified (see 6.2).

5.2.1 Level A. Ribbon attachments of one type only, packaged as specified in 5.1 shall be packed in a snug-fitting fiberboard shipping container conforming to V3s or V3c of PPP-B-636. Closure shall be in accordance with the appendix of the container specification. The weight of the contents of each shipping container shall not exceed the size and weight limitations of the container specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:44Z
Check the source to verify that this is the current version before use.

5.2.2 Level B. Ribbon attachments, of one type and dash number only, packaged as specified in 5.1, shall be packed in a snug-fitting, fiberboard box conforming to type CF or SF, class domestic grade 200 of PPP-B-636. Closure shall be in accordance with the appendix of the container specification. The weight of the contents of each shipping container shall not exceed the size and weight limitations of the container specification.

5.2.3 Level C. Ribbon attachment shall be preserved to the MIL-STD-794 requirements for this level.

5.2.4 Commercial. Ribbon attachments shall be preserved in accordance with the applicable requirements of ASTM-D-3951.

5.2.5 Palletization. Items packed as specified shall be palletized on a 4-way entry pallet in accordance with load type 1A of MIL-STD-147. Each prepared load shall be bonded with primary and secondary straps in accordance bonding means C,K and L, O or P. Pallet pattern shall be in accordance with the appendix of MIL-STD-147. The pallet shall be 4-wy, type I, class 1, style 1, size A, wood group I, II, III, or IV of MIL-P-15011, or 4-way, type IV, V or VIII, class 1, style A, size 2, wood group I, II, III or IV, grade A of NN-P-71. Interlocking of loads shall be effected by reversing the pattern of each course. If the container is of a size which does not conform to any of the patterns specified in MIL-STD-147, the pallet pattern used shall be approved by the contracting officer.

5.3 Marking. In addition to any special marking required by the contract or order, unit and intermediate packages and shipping containers shall be marked in accordance with MIL-STD-129 or ASTM-D-3951 or applicable.

6. NOTES

6.1 Intended use. The ribbon attachments covered by this specification are used to denote that the recipient has either performed duty in designated wars, campaigns, expedition or performed designated services as indicated by the applicable ribbon attachment.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number and date of this specification.
(b) Title, number, date and dash number required of the applicable specification sheet (see 3.1).
(c) When a standard sample will not be furnished (see 3.2).
(d) When first article is not required (see 3.3).
(e) Selection of applicable levels of packaging and packing (see 5.1 and 5.2).
(f) Palletization when required.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:44Z
Check the source to verify that this is the current version before use.

6.3 Samples. For access to samples, address the contracting activity issuing the invitation for bids.

6.4 First article. When a first article inspection is required, the item should be a first article sample or it may be a standard production item from the contractor's current inventory as specified in 4.4. The first article should consist of one completed ribbon attachment. The contracting officer should include specific instructions in acquisition documents regarding arrangements for examinations, approval of first article test results and disposition of first articles. Invitations for bids should provide that the Government reserves the right to waive the requirement for samples for first article inspection to those bidders offering a product which has been previously acquired or tested by the Government, and that bidders offering such products, who wish to rely on such production or test, must furnish evidence with the bid that prior Government approval is presently appropriate for the pending contract.

6.5 Changes from previous issue. Asterisks or vertical lines are not used in this revision to identify changes with respect to previous issue due to the extensiveness of the changes.

Custodians:
Army - IH
Air Force - 11
Navy - NU

Review activities:
Air Force - 82,99
Navy - MC
Other - CT

User activities:
Air Force - 45
Navy - CG

Preparing activity:
Army - IH

(Project No. 8455 - 0250)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:44Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-R-41819C	Ribbon Attachments, Decoration and Medal General Specification for

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:44Z
Check the source to verify that this is the current version before use.