NOT MEASUREMENT SENSITIVE

MIL-DTL-41819D
2 April 2025
SUPERSEDING
MIL-R-41819C
30 May 1986

DETAIL SPECIFICATION

RIBBON, ATTACHMENTS,DECORATION AND MEDAL, GENERAL SPECIFICATION FOR

This specification is approved for use by all Departments and agencies of the Department of Defense

1. SCOPE

1.1 Scope. This specification covers ribbon attachments for decorations, medals and service ribbons.

1.2 Classification. Decorations and medals covered by this specification will be as specified on the applicable military specification sheet (See 2.2.1 and 6.2).

2. APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are specified in section 3, and 4 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements of documents cited in sections 3, and 4 of this specification, whether or not they are listed.

2.2 Government documents.

2.2.1 Specification, standard and handbooks. The following specifications, standards and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents cited in the solicitation or contract.

Comments, suggestions, or questions on this document should be addressed to The Institute of Heraldry, ATTN: Technical and Production Division, 9325 Gunston Road, Room S-108, Fort Belvoir, VA 22060-5579 or email to usarmy.belvoir.hqda.mil.tioh-webmaster@mail.mil. You may verify the currency of this specification using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:44Z
Check the source to verify that this is the current version before use.

SPECIFICATION FEDERAL
PPP-B676 Boxes Setup

DEPARTMENT OF DEFENSE SPECIFICATIONS
MIL-STD-1916 – DOD Preferred Methods for Acceptance of Product
MIL-STD-129 - Marking of Shipment and Storage
MIL-STD -147 - Palletized Unit Loads
MIL-STD-2073-1E – Standard Practice for military Packaging

SPECIFICATION SHEETS

(See Supplement 1 for list of specification sheets.)

(Copies of these documents are available online at https://quicksearch.dla.mil).

2.3 Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents are those cited in the solicitation or contract.

ASTM INTERNATIONAL
ASTM-B568 - Standard Test Method for Measurement of Coating Thickness by X-Ray Spectrometry
ASTM-D2240 - Standard Test Method for Rubber Property – Durometer Hardness
ASTM-D5118/D5118M - Boxes, Fiberboard Shipping Fabrication of
ASTM- D3951 - Packaging Commercial

(Copies for these documents are available online at https://www.astm.org)

AMERICAN NATIONAL STANDARDS INSTITUTE (ANSI) ANSI/ASQ Z1.4

(Copies of ANSI/ASQ Z1.4 are available online at www.asq.org or ASQ Distribution Center, 5131 S. Third Street, Milwaukee, Wisconsin 53207-6028.)

2.4 Order of precedence. Unless otherwise noted herein or in the contract. In the event of a conflict between the text of this document and the references cited herein (except for related specification sheets), the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Specification sheets. The individua litem requirements shall be as specified herein and in accordance with the applicable specification sheet. In the event of any conflict between requirements of this specification and the specification sheets, the latter shall govern.

3.2 Detail requirements for the individual ribbon attachments. Detail requirements or exceptions applicable to a particular ribbon attachment shall be as specified on the applicable specification sheet. In the event of any conflict between the requirements of this specification

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:44Z
Check the source to verify that this is the current version before use.

and the applicable specification sheet the latter shall govern (see 6.2),except the design as shown on the specification sheet is intended for illustrative purposes only (see 3.5).

3.3 Standard sample. Unless otherwise specified(see 6.2), the contracting officer will furnish a standard sample to be used for matching color and finish only.

3.4 First article. When specified in the contract or purchase order, a sample shall be subjected to first article inspection (see 4.4 and 6.4)

3.5 Materials. Materials shall conform to the referenced specifications sheet and to the requirements specified herein.

3.5.1 Copper base alloy. The copper base alloy shall be roll polished, free from pits, scale (including red oxide), dents, nicks, cracks, scratches, segregation, and foreign inclusions that cannot be removed in later processing. When tested as specified in 4.5.1, the chemical composition of the copper content of the copper base alloy shall be as specified in Table I.

TABLE I. Unified Numbering System and Copper content of copper base alloys.

UNS ALLOY NUMBER	ALLOY NAME	COPPER
C210	Gilding Metal	94.0%-96.0%
C220	Bronze	89.0%-91.0%
C230	Red Brass	84.0%-86.0%
C240	Low Brass	78.5%-81.5%
C268	Yellow Brass	64.0%-68.5%
C280	Free Cutting Brass	59.0%-63.0%
C745	Nickel Brass	63.0%-66.5%
C752	Nickel Silver (65-18)	63.0%-66.5% 2/
C770	Nickel Silver (55-18)	53.5%-56.5% 1/

1/ Copper content for the nickel silver pin only may be 53.5% to 56.5% (C770).

2/ When nickel silver is used as a base material, the nickel content shall be not less than 18% (C752).

3.5.2 Silver for plating. Silver for plating shall be not less than 99.5 percent pure silver.

3.5.3 Gold for plating. Gold plating shall be 24 karat.

3.5.4 Lacquer. Lacquer shall be a pale, clear, synthetic lacquer. The use of pigmented lacquer shall be not permitted.

3.5.5 Solder. All solder shall be hard solder having a malting point of not less than 1075 degrees F.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:44Z
Check the source to verify that this is the current version before use.

3.6 Design. The embossed design of the ribbon attachment covered by this specification shall be exact replicas of the designs on the Government loaned hubs (see 3.9) from which the contractor's working dies shall be extracted. Dies shall be tooled and polished to remove any dents, nicks, scratches or other imperfections. Unornamented areas shall be smooth.

3.7 Construction.

3.7.1 Stamping, trimming, and piercing. Ribbon attachments shall be struck in such a manner so as to assure a well-defined die struck edge. The attachments shall be trimmed and when applicable, pierced to the die struck outline of the area specified. All edges shall be clean, smooth, free from burrs, drag, step and rough edges. The piercing or trimming operation shall not distort the design or alter the shape of the ribbon attachment.

3.7.2 Soldering. Unless otherwise specified on the applicable specification sheet, all solder shall be hard solder specified in 3.5.5. Soldered connections shall be completely joined without excess solder and all excess flux shall be removed. Joints shall be clean, smooth, strong and free from burned or reduced areas. When tested as specified in 4.6.3, the Soldered connection shall not separate.

3.7.3 Attaching device. The attaching devices for the ribbon attachment shall be specified on the applicable specification sheet. When prongs are specified, the point of the prongs may be either cone pointed or bias cut. The use of either post type or staple type prongs shall be permitted on all ribbon attachments which have an overall width dimension of 1/2 inch or. more. For all ribbon attachment having a width dimensionunder1/2 inch, only staple type prongs shall be permitted. Unless otherwise specified on the applicable specification sheet, prongs shall be fabricated from annealed nickel silver or yellow brass wire .025 plus or minus .003 inch in diameter and shall be (3/8 plus or minus 1/32) inch in length. When test+ as specified in 4.6.2,the prongs shall not break off nor shall the swaged joint be lifted away from the back. Unless otherwise specified" on the applicable specification sheet the staple type prongs shall be soldered or swaged not more than l/16 inch off-center. Unless otherwise specified the post type prong shall be located not more than l/16 inch off centers from each other in the vertical plane and not more than 1/32 inch from the applicable center. At the option of the manufacturer, the attaching device for the good conduct clasp may be long staple type prong swaged or soldered in the location specified on the applicable specification sheet. The prong shall not lift from the clasp when tested as specified in 4.6.3.

3.7.4 Dimensions. Dimensions indicated as reference dimensions are given for bidding information purposes only. The actual dimensions are controlled by the Government furnished hub.

3.8 Finish. The finish of the face and edges (surfaces visible from the front) of the ribbon attachments shall be as specified on the applicable specification sheet and shall match the finish of the standard sample (sea 3.3). Unless otherwise specified the back of the ribbon attachment- shall be clean.

3.8.1 Plating. All plating required shall be accomplish by electroplating. Prior to plating surfaces to be plated shall be cleaned of all matters that may affect the plating. The plating shall be nonporous and continuous over the entire surface. There shall be no cut-through, peeled, or blistered plating.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:44Z
Check the source to verify that this is the current version before use.

3.8.1.1 Gold plating. Gold specified in 3.5.3,shall be used for all gold plating. The use of white metal as an under coating shall not be permitted. When tested as specified in 4.6.4,there shall be no visible chemical reaction, such as evolution of gases.

3.8.1.2 Silverplating. Silver specified in 3.5.2 shall be used fox plating. The use of a white metal as an under coating shall be permitted. When silver plating is required, the plating shall have a minimum thickness of 0.0003 inches after finishing. When red brass is used as a base material for ribbon attachments which require a silverplated finish, the complete ribbon attachment must be nickel under plated. The nickel under plating shall be a minimum thickness of 0.00025 inch. When nickel silver is used as a base material, the ribbon attachment may be nickel under plated at the option of the manufacturer.

3.8.1.3 Rhodium plating. When tested as specified in paragraph4.6.4, no visible chemical reaction shall occur. All brass attachments which are to be rhodium plated shall have a flash of nickel as an underplating.

3.8.2 Lacquering. All metal surfaces(obverse and reverse) except gold plated or rhodium plated attachments and attaching devices shall be thoroughly coated with lacquer specified in 3.5.4. The dry lacquer film shall be hard, continuous ,level ,
Adherent and free from lint, dust or other foreign inclusions. At the manufacturer's option, gold plated attachments may also be lacquered. When tested as specified in 4.6.5.1,there shall be no change in the appearance of the lacquered items, except a slight yellowing around the highlights. When tested as specified in 4.6.5.2,the tissue shall not adhere to the lacquered items.

3.8.3 Marking. Quality marks for precious metal ribbon attachments shall be legibly and inconspicuously stamped on the reverse side of the ribbon attachment whenever practical.

3.9 Government loaned property. Hubs will be loaned by the Government and shall be used for making the contractor's working die a necessary for any one contractor order.

3.10 Workmanship. The ribbon attachments shall be clean, well made and shall meet the acceptable quality levels (AQL's) established by this specification.

4. VERIFICATION

4.1 Responsibility for inspection. Unless otherwise specified in the contractor purchase order, the contractor is responsible for the performance of all inspection reequipments as specified herein. Except as otherwise specified in the contractor purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The 'Government reserve a the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification. shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the Specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:44Z
Check the source to verify that this is the current version before use.

submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.4).
b. Quality conformance inspection (see 4.5).

4.3 Sampling for inspection and acceptance. Sampling for inspection and acceptance shall be in accordance with MIL-STD-105 except where otherwise indicated.

4.3.1 Inspection conditions. Unless otherwise specified, all inspections shall be performed in accordance with the test conditions specified in (applicable test method document or applicable paragraph(s) in the specification).

4.4 First article inspection. When a first article is required ,inspection of the first article shall be conducted for all provisions applicable for end item examination and tests.

4.5 Quality conformance inspection. Inspection shall be in accordance with the provisions set forth in MIL-STD-105, except where otherwise indicated.

4.5.1 Inspection of component.

4.5.1. Testing of components. Inspection shall be performed on components and materials listed in Table II for the test characteristics shown therein. Material listed in Table II may be accepted on a contractor's certificate of compliance for requirements specified in applicable paragraphs of this specification. The government reserves the right to test samples of the gold and silver (without additional charge) to verify the contractor's certification.

TABLE II. Testing of components.

Components and lots express in terms of	Characteristic	Rqm't ref	Test Method	#determpers/u	Results reported as	Sample unit
Copper base alloy (as applicable) (1 lb)	Chemical	3.5.1 and Table I	4.6.1	2 for each element (component site)	Nearest o.1 each element	4 oz of material for each alloy or 10 prongs

4.5.1.2 Certification of compliance. Components and materials listed below may be accepted based on a contractor' certification compliance for Characteristics indicated.

COMPONENT	CHARACTERISTIC	REQUIREMENT REF
Silver for plating	Fineness	3.5.2

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:44Z
Check the source to verify that this is the current version before use.

Gold for plating	Karat and no white metal as an undercoating	3.5.3 and 3.8.1.1
Lacquer	Material identification	3.5.4
Solder	Material identification	3.5.5

4.5.2 Examination for acceptance.

4.5.2.1 End item inspection. The defects found during examination shall be classified in accordance with 4.5.2.1.1 and 4.5.2.1.2. The lots shall be inspected in accordance with 4.5.2.1.3. The sample unit for these examinations shall be one ribbon attachment of each type and finish.

4.5.2.1.1 Examination of ribbon attachment for visual characteristics. All ribbon Attachments shall be viewed from a distance of 16 to 18 inches under normal daylight conditions. Defects designated by an asterisk (*) shall be classified as major when seriously affecting appearance or serviceability but not seriously.

EXAMINE	DEFECT	CLASSIFICATION		
		MAJOR	□ □ □	MINOR
Color & Finish	Poor match to approved guide samples, e.g., not highlighted to the same extent as the approved or excessive highlighted……...	-	*	-
	Discolored, i.e., spot, stain, or speck……	-	*	-
	Pit, dent, nick, scratch, pinhole, crack, rupture, segregation, foreign matter or other blemish….	-	*	-
	Buff, drag, blushed or cloudy finish……	-	*	-
	Any solder spatter or flux on front or edges exposed or concealed by plating……	X	-	-
	Not lacquer when required……..	-	-	X
	Lacquer not set to touch……..	-	-	X
	Lacquer forms noticeable runs or sags on the front or edges……...	X	-	-
	Lacquer coating is not continuous, level, smooth or adherent: e.g., is flaking, blistering, or peeling……	X	-	-
	Lacquer coating has lint, dust, or other foreign inclusion……	-	*	-
Design	Any detail altered or obscured: i.e., does not conform to Government hub……	X	-	-
	Warp, twist or distortion producing irregular surface contour or outline……..	X	-	-
	Any significant detail not clear, missing or obliterated……	X	-	-
	Detail struck over, resulting in double impression……	X	-	-
	Any area not pierced as indicated by the specification sheet……..	X	-	-

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:44Z
Check the source to verify that this is the current version before use.

Quality of plating	Surface spotted or open grained: i.e., appearing as pitted, porous, or crystalized……	X	-	-
	Any plated or gold-filled area cut-through, broken, peeling, blistered or otherwise impaired……	-	*	-
	Examination of ribbon attachment continued	X	-	-
Workmanship and construction	Not plated when required or plating is not specified type……	-	*	-
	Surface or edge not clean, not smooth, and not free from burrs, roughness, drug, step or tool marks……			
	Die struck edge, rim or outline is not well defined……	-	*	-
	Not trimmed to die struck edge……	-	-	-
	Pierced edge not clean and smooth, e.g., any burr, drag, cutter or file mark……	-	*	-
Soldering	Solder does not completely unite component part to base metal, i.e., any perceptible opening between component parts……	-	*	-
	Joints not clean and smooth, e.g., flux or excess solder not removed……	-	*	-
	Metal burned or reduced in soldering……	-	*	-
	Solder spatter exceeding 3/16 inch in maximum direction……	-	-	X
Attaching device	Prong hooked, blunted or not pointed as required……	-	*	-
	Prong is loose……	X	-	-
	Prong missing……	X	-	-
	Not type or size specified……	-	-	X
	Not position as specified, i.e., not conforming to specification sheet……	-	*	-
	Twisted, damaged, deformed or otherwise impaired……	-	*	-
	Staple prongs position more than 1/16 inch off center……	-	*	-
	Post type prong position more than 1/16 inch off center form each other……	X	-	-
	Center of both post type prongs located more than 1/32 inch from applicable centerline……	X	-	-
Quality marking	Missing, incorrect, illegible not placed as required……	-	-	X

4.5.2.1.2 Examination of ribbon attachments for dimension Any dimension that is not within the specified tolerances shall be classified as defect.

4.5.2.1.3 AQL's and inspection levels The inspection levels and the acceptable quality levels (AQL's) expressed in defects per hundred units shall be as follows:

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:44Z
Check the source to verify that this is the current version before use.

	Inspection level	AQL Major	AQL Total
For defects applicable to 4.5.2.1.1	II	2.5	10
For defects applicable to 4.5.2.1.2	S-3	(one class)	4.0

4.5.2.2 End item testing. Testing of the completely fabricated ribbon attachment shall be performed for the characteristics shown herein. The sample unit for end item testing shall be three ribbon attachments. The requirements are applicable to the individual unit with one determination per sample unit. Results shall be reported as pass or fail. The inspection level shall be S-1 and acceptable quality levels (AQL's) shall be 6.5 defects per hundred units.

TABLE III. Testing of end item.

CHARACTERISTIC	RQM'T	TEST METHOD	#DETERM PER S/U	RESULTS REPORTED AS
Bending test for prongs	3..7.3	4.6.2	1	Pass or fail
Test for soldered joints	3.7.2	4.6.3	1	Pass or fail
Test for lacquer:				
Liver of Sulphur test	3.8.2	4.6.5.1	1	Pass or fail
Tackiness test	3.8.2	4.6.5.2		Pass or fail
Acid test for gold and rhodium	3.8.1.1	4.6.4	1	Pass or fail
Electroplating	3.8.1.3			
Thickness test for:				
Silver electroplating	3.8.1.2	Std. commercial	1	Pass or fail
Nickel electroplating	3.8.1.2	Std. commercial	1	Pass or fail

4.5.3 Examination for count of ribbon attachments in intermediate containers. Ribbon attachments packaged for shipment shall be examined to determine conformance with package markings and specified quantity. The sample unit for this examination shall be one box (interior package). Any box containing ess than the specified or marked quantity of ribbon attachment shall be classified as a defect. The inspection level shall be S-2 and the AQL shall be 4.0 defects per hundred units. The lot size shall be the number of intermediate containers.

4.5.3.1 Examination of preparation for delivery requirements. An examination shall be made to determine that packaging, packing and marking requirements are complied with. Defects shall be scored in accordance with the list below. .The sample unit shall be one shipping container fully prepared for delivery with the exception that it need not be sealed. Defects of closure listed below shall be examined on shipping containers fully prepared for delivery. The lot size shall be the number of shipping containers in the end item inspection lot. The inspection level shall be S-2 and the acceptable ,quality levels(AQL's)shall be 2.5 defects per hundred units.

Examine	Defects
Marking (exterior and interior)	Omitted, incorrect, illegible, of improper size,

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:44Z
Check the source to verify that this is the current version before use.

	location, sequence or method of application.
Materials	Any component missing or damaged.
Workmanship	Inadequate application of components, such as incomplete sealing or closure of container flaps, inadequate stapling.
	Bulging or distortion of containers.
Weight or content (exterior and interior)	Number of intermediate packages is more or less than required, weight of contents per shipping container exceeds requirements.

4.5.4 Palletization examination. An examination shall be made to determined that the palletization is in compliance with the section 5 requirements. Defects shall be scored in accordance with the list below. The sample unit shall be one palletizes unit load fully Package. The lot size shall be the number of palletized units loads in the inspection lot. The inspection level shall be S-1 and the acceptable quality level (AQL],expressed in terms of defects per hundred units, shall be 6.5.

Examine	Defects
Finished dimensions	Length, width, or height exceeds specified. maximum requirements.
Palletization	Pallet pattern not as specified.
	Interlocking of load not specified.
	Load not bonded with required straps as specified.
Weight	Exceeds maximum load limits.
Marking	Omitted, incorrect, illegible, of improper size, location, sequence, or method of application.

4.6 Test

4.6.1 Chemical composition test. Shall be evaluated to determine compliance with the requirements specified in 3.5.1.

4.6.2 Bending test for prongs. Wire prongs shall be bent three times back and forth through an angle of 90 degrees, after which the prongs and the soldered or swaged connections shall be examined to determine compliance with the requirement specified in 3.7.3.

4.6.3 Test for hard soldered joints. Hard soldered ribbon attachments shall be placed in an oven maintained at 1065 degrees F., plus or minus 5 degrees F., for 15 minutes. While at this temperature the ribbon attachments shall be lifted by the attaching device and shall be inspected to determine compliance with the requirements specified in 3.7.2. A 15-pound pull test shall be applied to the prongs of the Good Conduct clasp. The pull shall be in the direction of the vertical axis of the prong. The attaching devices hall then be examined to determine compliance with paragraph 3.7.3.

4.6.4 Acid test for gold or rhodium plating. Ribbon attachments to be tested or compliance with 3.8.1.1 and 3.8.1.3 may be unlacquered or have the lacquer completely removed with an organic solvent. The acid test shall be conducted as follows: Using a test acid consisting of a solution containing 50 percent by volume nitric acid (specific gravity

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:44Z
Check the source to verify that this is the current version before use.

1.42) and equal volume of distilled water. At room temperature place a drop of test acid on face of ribbon attachment. The drop shall remain on the ribbon attachment for not less than one minute.

4.6.5 Test for lacquer.

4.6.5.1 Liver of Sulphur test. Ribbon attachments to be tested shall be immersed in 2 percent by weight CP liver of Sulphur (sulphated potash) water solution, at a temperature of 100 degrees F., plus or minus 19 degrees F., for a period of 3 minutes. The ribbon attachment shall be wiped gently with an absorbent cellulose material or whirled o remove residual moisture and shall be air dried at room temperature(60 to 80 degrees F.) for 1 hour. The ribbon attachment shall then be inspected to determine compliance with the requirements specified in 3.8.2.

4.6.5.2 Tackiness test. At room temperature (60 to 80 degrees F.) press a piece of tissue paper against the lacquered surface for 15 seconds, using any pressure capable of being exerted between thumb and two fingers, after which, the pressure shall be released and the ribbon attachment inspected to determine compliance with the requirement specified 3.8.2.

5. PACKAGING

5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When actual packaging of materiel is to be performed by DoD or in- house contractor personnel these personnel need to contact the responsible packaging activity to ascertain requisite packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activities within the Military Service or Defense Agency, or within the military service's system commands. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful but is not mandatory.)

6.1 Intended use. The ribbon attachments covered by this specification are used to denote that the recipient has either performed duty in designated wars, campaigns, expedition or performed designated services as indicated by the applicable ribbon attachment.

6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of this specification.
b. The title, number, and date of the applicable specification sheet (See 3.1).
c. When a standard sample will not be furnished (see 3.2).
d. When first article is not required (see 3.3).
e. Selection of applicable levels of packaging and packing (see 5.1).
f. Palletization when required.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:44Z
Check the source to verify that this is the current version before use.

g. When special marking is required (see 3.11.1).
h. Packaging requirements (See 5.1)

6.3 Samples. For access to samples, address the contracting activity issuing the invitation for bids.

6.4 First article. When a first article inspection is required, the item should be a first article sample, or it may be a standard production item from the contractor's current inventory specified in.4.4. The first article should consist of one completed ribbon attachment. The contracting officer should include specific instructions in acquisition documents regarding arrangement for examinations, approval of first article test results and disposition of first articles. Invitations for bids should provide that the Government reserves the right to waive the requirement for sample for first article inspection to those bidders offering a product which has been previously acquired or tested by the Government, and that bidders offering such products, who wish to rely on such production or test, must furnish evidence with the bid that prior Government approval is presently appropriate for the pending contract.

6.5 Subject term (Key word) listing.

Acetone	Lead
Acquisition	Plating
Epoxy	Silver

6.6 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodians:
Army - IH
Navy - NU
Air Force - 11

Preparing activity:
Army - IH

Review activities:
Navy - MC, CG1
DLA - CT

(Project No. 8455-2025-068)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:44Z
Check the source to verify that this is the current version before use.