NOT MEASUREMENT SENSITIVE

MIL-DTL-41819/4E
30 September 1996
SUPERSEDING
MIL-R-41819/4D
1 November 1994

DETAIL SPECIFICATION SHEET

RIBBON ATTACHMENT, OAK LEAF CLUSTER

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-41819 listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation.

DASH NO.
- -1: BRONZE (5/16 INCH) SINGLE
- -2: SILVER (5/16 INCH) SINGLE
- -3: BRONZE (13/32 INCH) SINGLE
- -4: SILVER (13/32 INCH) SINGLE
- -5: BRONZE (5/16 INCH) DOUBLE
- -6: BRONZE (5/16 INCH) TRIPLE
- -7: BRONZE (5/16 INCH) QUADRUPLE

MATERIAL:
-1, -3, -5, -6, -7: Red Brass or Gilding Metal
-2, -4: Red Brass or Nickel Silver

FINISH:
-1, -3, -5, -6, -7: Copper Flash, (Red Brass Only), Oxidized, Relieved
-2, -4: Nickel Plated (Red Brass Only), Silver Plated, Oxidized, Relieved, Matte Finish and shall match TIOH Metal Finish Chip Number 14.

AMSC N/A FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:46Z
Check the source to verify that this is the current version before use.

DIMENSIONS:

HEIGHT (Overall):		
-1, -2, -5, -6, -7:	1/4 inch (0.64 cm) (REF)	
-3, -4:	3/16 inch (0.48 cm) (REF)	
WIDTH (Overall):		
-1, -2:	5/16 inch (0.79 cm) (REF)	
-3, -4:	13/32 inch (1.03 cm) (REF)	
-5:	1/2 inch (1.27 cm) (REF)	
-6:	21/32 inch (1.67 cm) (REF)	
-7:	7/8 inch (2.22 cm) (REF)	
THICKNESS (At Thickest Point):		
-1, -2, -5, -6, -7:	0.045 inch $\pm$ 0.005 inch (0.114 cm $\pm$ 0.012 cm)	
-3, -4:	0.065 inch $\pm$ 0.005 inch (0.165 cm $\pm$ 0.012 cm)	

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. The attaching device shall be located as follows:

-1 thru -4:	The staple type prong shall be centered on the back of the oak leaf.
-5:	One prong shall be centered on the back of each oak leaf.
-6:	One prong shall be centered on the back of the first and second leaf beginning from the right when viewed from the reverse with the leaf sloping up.
-7:	One prong shall be centered on the back of the first and third leaf beginning from the right when viewed from the reverse with the leaf sloping up.

3. Dash No. -5 through -7 are optional items available for commercial sale only.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodian:
Army - IH
Air Force - 45
Navy - NU

Preparing activity:
Army - IH

Review activities:
Air Force - 32, 82, 99
Navy - MC
Coast Guard - CG
DLA - CT

(Project No. 8455-0863)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:46Z
Check the source to verify that this is the current version before use.