INCH-POUND

MIL-DTL-41819/7M
18 May 2016
SUPERSEDING
MIL-DTL-41819/7L
20 May 2005

DETAIL SPECIFICATION SHEET

RIBBON ATTACHMENT, STAR

This specification is approved for use by all
Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-41819.



The various stars and star configurations addressed by this specification sheet are listed in the table below:

DASH NO.	TYPE STAR	CONFIGURATION	HEIGHT	OVERALL WIDTH (STAR POINT TO STAR POINT)	USER
-1	Bronze	Single	3/16"	3/16"	A, N, AF, MC, CG
-2	Silver (polished)	Single	3/16"	3/16"	A, N, AF, MC, CG
-3	Silver (polished)	Single	5/16"	5/16"	A, N, AF, MC, CG
-4	Gold (polished)	Single	5/16"	5/16"	N, AF, MC, CG
-5	Bronze	Double	3/16"	13/32"	A, N, AF, MC, CG
-6	Bronze	Triple	3/16"	5/8"	A, N, AF, MC, CG
-7	Bronze	Quadruple	3/16"	13/16"	A, N, AF, MC, CG
-8	Silver (polished)	Double	3/16"	13/32"	A, N, AF, MC, CG
-9	Silver (polished)	Triple	3/16"	5/8"	A, N, AF, MC, CG
-10	Silver (polished)	Quadruple	3/16"	13/16"	A, N, AF, MC, CG
-11	Gold (polished)	Double	5/16"	19/32"	N, MC, CG
-12	Gold (polished)	Triple	5/16"	29/32"	N, MC, CG
-13	Gold (polished)	Quadruple	5/16"	1-3/16"	N, MC, CG
-14	Bronze	Single	5/16"	5/16"	AF
-15	Silver (matte)	Single	5/16"	5/16"	A, N, AF, MC, CG
-16	Silver (matte)	Double	5/16"	19/32"	A, N, AF, MC, CG
-17	Silver (matte)	Triple	5/16	29/32"	A, N, AF, MC, CG

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:47Z
Check the source to verify that this is the current version before use.

DASH NO.	TYPE STAR	CONFIGURATION	HEIGHT	OVERALL WIDTH (STAR POINT TO STAR POINT)	USER
-18	Silver (matte)	Quadruple	5/16"	1-3/16"	A, N, AF, MC, CG
-19	Gold (matte)	Single	5/16"	5/16"	A, N, AF, MC, CG
-20	Gold (matte)	Double	5/16"	19/32"	A, N, AF, MC, CG
-21	Gold (matte)	Triple	5/16"	29/32"	A, N, AF, MC, CG
-22	Gold (matte)	Quadruple	5/16"	1-3/16"	A, N, AF, MC, CG

MATERIAL: 85/15 Rich-Low Brass or 95/5 Gilding Metal

FINISH:

-1, -5, -6, -7, -14: Copper Flashed (Rich-Low Brass only), Oxidized, Relieved

-2, -3, -8, -9, -10: Nickel Plated, Mirror-like Polished, and shall match The Institute of Heraldry Metal Finish Chip Number 16

-4, -11, -12, -13: 24K Gold Plated, Mirror-like Polished, and shall match TIOH Metal Finish Chip Number 6.

-15 thru -18: Nickel Plated, Matte Finished, and shall match TIOH Metal Finish Chip Number 17.

-16 thru -22: 24K Gold Plated, Matte Finished, and shall match TIOH Metal Finish Chip Number 7.

THICKNESS:

-1, -2, -5 thru -10 (3/16 inch stars): 1/16 inch ± 1/64 inch

-3, -4, -11 thru -22 (5/16 inch stars): 5/64 inch ± 1/64 inch

NOTES:

1. The height and width measurements (shown on the table on page 1) are REF and refer to measurements taken from the Government furnished hub or die.

2. Attaching device for all configurations shall be staple type prong or U-wire centered on the back of the star or star grouping.

3. -5 thru -13, -16 thru -18, and -20 thru -22 are optional items and were developed for commercial sale.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:47Z
Check the source to verify that this is the current version before use.

Custodians:
Army - IH
Air Force - 11
Navy - NU

Preparing activity:
Army - IH

Review activities:
Navy - MC, CG1
DLA - CT

(Project No. 8455-2016-454)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:47Z
Check the source to verify that this is the current version before use.