MIL-T-41813F
20 August 1987
SUPERSEDING
MIL-T-41813E
15 June 1984

MILITARY SPECIFICATION

TENT SECTIONS, FRAME TYPE, MAINTENANCE, MEDIUM

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This document covers tent sections with covers for one type of frame-supported raised hemicylindrical tent fabricated of fire, water, weather, and mildew-resistant (FWWMR) treated cotton duck. Each intermediate section is provided with a window and window screen, and each end section has a chain hoisted vehicle door, a personnel door, and a double heater duct. Covers are provided for protection of each section during transport.

1.2 Classification. Tent sections shall be of the following types, as specified (see 6.2):

Type I - End section
Type II - Intermediate section

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: U.S. Army Natick Research, Development, and Engineering Center, Natick, MA 01760-5014, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 8340

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:43Z
Check the source to verify that this is the current version before use.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

* 2.1.1 Documents. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

FEDERAL

L-P-378	- Plastic Sheet and Strip, Thin Gauge, Polyolefin
L-S-125	- Screening, Insect, Nonmetallic
T-C-571	- Cords, Cotton; General and Special Purpose, Sash and Venetian Blind
T-T-871	- Twine, Cotton, Wrapping
T-T-911	- Twine, Fibrous, Jute
V-F-106	- Fasteners, Slide, Interlocking
V-T-285	- Thread, Polyester
FF-R-556	- Rivet, Solid, Small; Rivet, Split, Small; [illegible]t, Tubular, Small; Flat Washer (Burr); and Cap, Rivet; General Purpose
FF-T-276	- Thimbles, Rope
QQ-B-613	- Brass, Leaded and Nonleaded: Flat Products (Plate, Bar, Sheet and Strip)
QQ-W-423	- Wire, Steel, Corrosion-Resisting
QQ-W-428	- Wire, Steel, Carbon (High Carbon, Round, for Mechanical Springs, General Purpose)
TT-E-529	- Enamel, Alkyd, Semigloss
TT-P-595	- Preservative Coating, Canvas
CCC-C-429	- Cloth, Osnaburg, Cotton
CCC-C-467	- Cloth, Burlap, Jute (or Kenaf)
DDD-L-20	- Label: For Clothing, Equipage, and Tentage, (General Use)
PPP-B-601	- Boxes, Wood, Cleated-Plywood

MILITARY

MIL-C-496	- Clips, End, Strap
MIL-W-530	- Webbing, Textile, Cotton, General Purpose, Natural or in Colors

Source: https://assist.dla.mil -- Downloaded: 202640-21T19:43Z
Check the source to verify that this is the current version before use.

MIL-B-543	- Buckles, Tongueless and Web Strap
MIL-R-1670	- Rope, Tent-Lay
MIL-L-1709	- Lines, Tent
MIL-R-2327	- Rings, Connecting, Round
MIL-C-2399	- Cement, Liquid, Tent Patching
MIL-R-3390	- Rings, Dee
MIL-F-10884	- Fasteners, Snap
MIL-L-11075	- Loops, Strap Fastener
MIL-G-16491	- Grommet, Metallic
MIL-R-30500	- Rope, Polyester
MIL-L-40069	- Leather, Cattlehide, Chrome Tanned, Cold-Climate
MIL-T-43566	- Tape, Textile, Cotton or Polyester, General Purpose, Natural or in Colors
MIL-C-43627	- Cloth, Duck, Cotton, Plied Yarns, Fire, Water, Weather and Mildew Resistant Treated, Lightdry Finish

STANDARDS

FEDERAL

FED-STD-751	- Stitches, Seams, and Stitchings

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	- Marking for Shipment and Storage

* 2.1.2 Other Government documents. The following other Government documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

DRAWINGS

U.S. ARMY NATICK RESEARCH, DEVELOPMENT, AND ENGINEERING CENTER

5-4-691	- Tent, Frame-Type, Maintenance, Medium; Erection Instructions
5-4-935	- Tent Sections, Frame-Type, Maintenance, Medium; Assembly
5-4-936	- End Section Assembly

Source: https://assist.dla.mil -- Downloaded: 202610-21T19:43Z
Check the source to verify that this is the current version before use.

5-4-937	- End Section Blanket Details
5-4-938	- End Section - Details "A"
5-4-939	- End Section - Details "B"
5-4-940	- End Section - Details "C"
5-4-941	- End Section - Details "D"
5-4-942	- End Section - Detail and Sections
5-4-943	- Intermediate Section Assembly
5-4-944	- Intermediate Section - Window Assembly
5-4-945	- Intermediate Section - Window Details
5-4-946	- End and Intermediate Details
5-4-947	- End and Intermediate Sections
5-4-948	- Cover

PUBLICATION

Department of the Army Field Manual FM 10-16 - General Repair of Tents, Canvas and Webbing

(Copies of documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

* 2.2 Other publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted shall be those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS shall be the issues of the nongovernment documents which are current on the date of the solicitation.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

A 167 - Stainless and Heat-Resisting Chromium-Nickel Steel Plate, Sheet and Strip

D 2016 - Standard Test Methods for Moisture Content of Wood

D 3951 - Standard Practice for Commercial Packaging

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, Pennsylvania 19103.)

(Technical society and technical association documents are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:43Z
Check the source to verify that this is the current version before use.

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document shall take precedence. Nothing in this document, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified in the contract or purchase order, a sample shall be subjected to first article inspection (see 4.3, 6.2, and 6.3).

3.2 Materials and components. (See 6.4)

3.2.1 Cloth, cotton duck. The cloth shall conform to MIL-C-43627 color Olive Drab 7.

* 3.2.2 Tape, textile, cotton. The tape shall conform to type I, class 4, 3/4-inch, 1-inch, and 2-inch widths, Olive Drab 7 of MIL-T-43566.

* 3.2.3 Webbing, textile, cotton. The webbing shall conform to type IIb, class 4, 1-inch width, and type III, class 4, 1-inch width, Olive Drab 7 of MIL-W-530.

3.2.4 Screening, nonmetallic. The screening shall conform to type III, class 1, size 18 by 18, color green, of L-S-125.

3.2.5 Thread, polyester. The thread shall conform to type I, class 1, subclass B of V-T-285 as follows:

a. For all stitching except zig-zag stitching and stitching indicated by "Z" on drawings, use size FF for needle and bobbin.

b. For stitching indicated by "Z" on drawings, use size FF for needle and size F for looper.

c. For zig-zag stitching, use size E.

3.2.5.1 Color. The thread for all stitching shall match Olive Drab S-1 (CA 66022). The dyed thread shall show fastness to weathering equal to or better than the standard shade sample. If no standard shade sample is available, the thread shall show good fastness to weathering.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:43Z
Check the source to verify that this is the current version before use.

3.2.6 Twine, cotton. The twine shall conform to type II, class 1, 5 ply c T-T-871.

3.2.7 Cord, cotton, braided. The cord shall conform to type I, class 3, size number 4 of T-C-571. The color shall be Olive Drab prior to mildew-resistant treatment and the shade imparted by the treatment will be acceptabl

3.2.8 Rope, tent-lay. The manila rope used for stiffeners shall conform t type I, class 2, 1 1/8 inch circumference of MIL-R-1670.

3.2.9 Rope, polyester. The polyester rope shall conform to 3/4 inch circumference (1/4 inch approximate diameter) of MIL-R-30500, and shall be natural in color or as specified on applicable drawings.

3.2.10 Lines, tent. The cover tie lines shall conform to type XXI, class A, and the tent guy lines shall conform to type XLIII, class A (except that the guy lines shall be finished in accordance with figure 1) of MIL-L-1709 (see 6.6).

3.2.11 Film, plastic. Plastic film shall conform to the requirements for 0.0060-inch thick film, type I, class 1, grade A, B, or C, finish 1 of L-P-37 except that the film thickness shall be 0.020 ± 0.004 inch. The requirements for slip, ink adhesion, water vapor permeability, impact resistance, and heat-seal strength shall not be applicable.

3.2.12 Leather. The leather shall conform to type I, II, III, or IV, clas 1, 6 ounces of MIL-L-40069. The color shall be that imparted by chrome-tannage, and the crocking requirement shall not apply.

3.2.13 Grommets, metallic. The grommets shall conform to type III, class 3, size Nos. 2, 3, and 4 (as specified on applicable drawings) of MIL-C-16491

* 3.2.14 Fasteners, slide, interlocking. The slide fasteners shall conform to size H, brass chain and slider of V-F-106. Alternatively, the slide fastener chain shall be polyester continuous monofilament in a ladder or coil type configuration. Color of the chain, slider, pull, and stops shall approximately match the tape color.

3.2.14.1 Window fastener. The window fasteners shall be type I, style 2, wire stirrup pull.

3.2.14.2 Personnel door fastener. The personnel door fasteners shall be type III, style 1, wire stirrup pull.

Source: https://assist.dla.mil -- Downloaded: 20261O-21T19:43Z
Check the source to verify that this is the current version before use.

3.2.14.3 Tape. The slide-fastener tape shall be dyed to match Olive Drab S (CA 66519) and water-repellent and mildew-resistant treated. The color of the tape after treatment will be considered acceptable. The tape shall show good fastness to weathering.

3.2.15 Fasteners, snap. The snap fasteners shall conform to style 1, finish 2, stud-eyelet size 1 with washer of MIL-F-10884.

3.2.16 Buckle, tongueless, 2-bar. The buckles shall conform to type II, style 1, class 1 and 1-inch size of MIL-B-543.

3.2.17 Rings, dee. The dee rings shall conform to class 1, configurations A and K of MIL-R-3390.

* 3.2.18 Snap, loop eye. The snap shall be 5/8-inch commercial loop eye snap fabricated of die cast zinc (see 6.5). The snap shall have a black enamel finish in accordance with the manufacturer's standard practice.

3.2.19 Toggles, wood. The wood toggles shall conform to the design and dimensions shown on Drawing 5-4-941. The wood for the toggles shall be straight-grained, sound and smooth lumber, kiln dried to not more than 15 percent moisture content when tested as specified in 4.4.1.1. The toggles shall be free from knots, shakes, checks, splits or splintery surfaces. Any of the following woods may be used:

Beech	Pecan	Rock Elm	Hickory
Birch	Hard Maple	Ash	Red or White Oak

3.2.20 Hook, "J". The "J" hooks as shown on Drawing 5-4-946 shall be fabricated from corrosion-resisting steel wire conforming to type I, composition 302 or 304, condition A of QQ-W-423. The finished "J" hook shall withstand a load of at least 500 pounds for not less than 1 minute without any evidence of failure when tested as specified in 4.4.1.2.

3.2.21 Hook, arch. The arch hooks as shown on Drawing 5-4-941 shall be fabricated from corrosion-resisting steel sheet or strip, 300 series conforming to ASTM A 167 (see 2.2).

3.2.22 Spring assembly. The spring assembly as shown on Drawing 5-4-941 shall be fabricated from hard drawn, high carbon steel wire conforming to type II, 0.062-inch diameter of QQ-W-428.

* 3.2.23 Thimble, rope. The thimbles shall conform to type II, thimble size 1/4-inch of FF-T-276 and shall be coated with black enamel conforming to type I or II of TT-E-529.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:43Z
Check the source to verify that this is the current version before use.

3.2.24 Rings, round. The round connecting ring shall conform to class 2 or 5, size 4 of MIL-R-2327.

3.2.25 Loop, strap. The strap loops shall conform to type I, II, or III, style A or B of MIL-L-11075.

3.2.26 Rivets and burrs. The rivets with burrs shall conform to type I, class 2, grade A or F, size No. 7 of FF-R-556. The rivets shall be of sufficient length to assure a secure clinch.

3.2.27 Clamp, rope, brass. The clamps used to serve the ends of the polyester rope shall conform to copper alloy No. 260, sheet or strip of QQ-B-613 in the design and dimensions as shown on Drawing 5-4-946 (see 6.5).

3.2.28 Clip, end, strap. The end clip shall conform to type I, class 1 or 2, size 1 inch of MIL-C-496.

3.3 Construction. Construction shall conform to the drawings listed in section 2 and as specified herein.

3.3.1 Stitching, machine.

3.3.1.1 Types of stitching. All stitch types shall conform to FED-STD-751 as follows:

a. For all stitching except zig-zag stitching and stitching indicated by "Z" on drawings, use type 301, 5 to 7 stitches per inch.

b. For zig-zag stitching, use type 304, 1/8 to 1/2 inch wide (bight), 14 to 16 stitches per inch.

c. For stitching indicated by "Z" on drawings, use type 401, 5 to 7 stitches per inch. The chain portion of stitching shall not appear on outside of tent section or cover.

3.3.1.2 Thread breaks. Thread breaks in stitching shall be overstitched not less than 1 inch at each break on stitch type 301, not less than 3/4 inch at each break on stitch type 304, and not less than 1 1/2 inches at each break on stitch type 401. Thread breaks in type 401 stitching may be overstitched with stitch type 301.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:43Z
Check the source to verify that this is the current version before use.

3.3.1.3 Stitching ends. The ends of 301 stitching shall be overstitched not less than 1 inch, except where ends are turned under in a hem or held down by other stitching. Where stitching is performed automatically on stitch patterns such as box, box with cross-stitch, "W" stitching or straight line tacking, at least, 3 or more tying, overlapping, or back stitches shall be used to secure the ends. The ends of type 304 stitching shall be firmly secured by back stitching or overstitching or by increasing the number of stitches per inch at the ends for a minimum 1/4 inch.

3.3.1.4 Skipped stitches. Two or more skipped stitches occurring consecutively in stitch type 301 or 304 shall be overstitched not less than 1 inch on each side of a skip. Any skipped stitch in stitch type 401 shall be overstitched not less than 1 1/2 inches on each side of a skip. Skipped stitches in stitch type 401 may be overstitched with stitch type 301.

3.3.1.5 Lubrication of thread. The addition of any lubricant to the polyester thread prior to or during the sewing operation is prohibited.

3.3.2 Setting of grommets. Holes punched to receive the grommets shall be smaller than the outside diameter of the grommet barrel so that the barrel must be forced through the hole. The grommets shall be securely clinched without cutting the materials. Roll of the clinched grommet shall not contain more than three scores (splits).

3.3.3 Setting of snap fasteners. If a hole is punched before inserting the male or female part of the fastener, it shall be smaller than the outside diameter of the fastener tube so that the tube must be forced through the hole. The fasteners shall be securely clinched. Roll of the clinched eyelet of the assembled fastener component shall not contain more than three scores (splits).

3.3.4 Setting of end clips. The webbing shall be inserted the full depth of the clip. The clips shall be securely attached without cutting the webbing and the webbing shall lie flat at the point of entry.

3.3.5 Setting of rivets. The rivets shall be securely set and neatly headed.

3.3.6 Attachment of slide fasteners. Care shall be taken to trim all thread ends and maintain specified distances between the edges of fabric attached to slide fastener tape so that there will be no interference with the operation of the slider.

3.3.7 Repairs. All necessary repairs shall be effected in accordance with Department of the Army Field Manual FM 10-16, except that hand sewn patches or cemented patches other than as specified herein will not be acceptable.

Source: https://assist.dla.mil -- Downloaded: 202610-21T19:43Z
Check the source to verify that this is the current version before use.

Cemented patches on holes, cuts, or tears not more than 1 inch in diameter or length, using cement specified in MIL-C-2399, shall be permitted. A maximum of two cemented patches per section shall be allowed without prior authorization by the contracting officer. All other repairs shall require authorization by the contracting officer. Repairs required as a result of failure of the cup test shall be performed by treating with a compound conforming to type I, class 1 of TT-P-595 prior to retesting (see 6.8).

3.3.8 Wicking of sewing thread (cup test). There shall be no wicking of water through the tent stitching when the tent sections are tested as specified in 4.5.1. The cup test is intended to ensure that non-wicking thread has been utilized and that no lubrication has been added to the polyester thread prior to or during the sewing operation.

3.4 Marking. All marking shall conform to DDD-L-20.

3.4.1 Special marking. The letters "US" and the item nomenclature on the end sections, intermediate sections, and covers shall conform to type IV, class 9 in the size characters and locations shown on the drawings. Class 9 markings shall be clearly legible after subjection to accelerated weathering.

3.4.2 Identification labels. Identification labels shall conform to type VI, class 6, and shall be 3 1/2 inches by 5 1/2 inches minimum and a blank space of at least 1 1/4 inches shall be provided on the bottom of the label for the Department of Defense inspector's stamp. Identification labels shall be stitched to the end sections, intermediate sections, and covers in the locations shown on the drawings.

3.4.3 Label of erection instructions. Labels of erection instructions shall conform to type VI, class 7 and shall be stitched to the end sections, intermediate sections and covers in the locations shown on the drawings. The label shall be a proportionate copy of Drawing 5-4-691 as reproduced from a glossy print of this drawing furnished by the contracting officer. The size of the label shall be 15 ± 1/4 inches in the longer dimension with a minimum 1/2-inch margin outside of the borderline on all sides.

3.4.4 Label of warning instructions. Warning instruction labels shall conform to type VI, class 9 and shall be stitched to the end sections and intermediate sections in the locations shown on the drawings. The warning label shall read as follows:

WARNING

WHEN TENT IS CLOSED, EXHAUST
OF INTERNAL COMBUSTION ENGINES
MUST BE VENTED TO THE OUTSIDE

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:43Z
Check the source to verify that this is the current version before use.

The word "WARNING" shall be in red letters at least 2 inches high and the remainder of the label shall be black letters at least 1/2 inch high. Fastness of the class 9 labels shall be as specified for the class 7 labels.

3.5 Workmanship. Cloth components shall be clean and free of holes, cuts, tears, or cloth defects such as multiple floats or broken or missing yarns. Webbing and tapes shall have no frayed or scalloped edges and rope components shall be free of cuts or breaks. Thread tension shall be maintained so that there will be no loose stitching and seam allowances shall be maintained so that no runoffs, twists, pleats, or open seams shall result. All thread ends shall be trimmed to 1/2 inch or less. Care shall be taken in sewing to see that no needle chews occur. Metal components shall be free of burrs, sharp edges, or corroded areas and shall not be broken or malformed.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this document where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this document shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirement in the document shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.1.2 Certificates of compliance. When certificates of compliance are submitted, the Government reserves the right to inspect such items to determine the validity of the certification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:43Z
Check the source to verify that this is the current version before use.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).

4.3 First article inspection. When a first article is required (see 6.2), it shall be examined for the defects specified in tables I through IV and tested as specified in 4.4.7. The presence of any defect or failure of any test shall be cause for rejection of the first article.

4.4 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.4.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this document or applicable purchase document.

* 4.4.1.1 Wood toggle moisture content testing. In addition to the quality assurance provisions of the subsidiary documents, the wood toggles shall be tested for conformance to the moisture content requirements of 3.2.19. The moisture content shall be determined in accordance with the oven-drying or the electrical meter method referenced in ASTM D 2016. The results shall reported to the nearest 0.1 percent for each toggle tested. The lot size shall be expressed in toggles. The sample unit shall be one toggle. The inspection level shall be S-1 and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 4.0.

4.4.1.2 "J" hook breaking strength testing. In addition to the quality assurance provisions of the subsidiary documents, the "J" hooks shall be tested for conformance to the static load resistance requirements of 3.2.20. The strength shall be determined by mounting a sample in such a manner that when a 500-pound static load is applied to the hook, the weld area will be placed in tension. Any evidence of separation at the weld will constitute a failure. The lot size shall be expressed in "J" hooks. The sample unit shall be one "J" hook. The inspection level shall be S-4 and the AQL, expressed in terms of defects per hundred units, shall be 4.0.

4.4.2 In-process inspection. Inspection shall be made to determine that the following are as specified:

a. There shall be no lubrication of polyester thread prior to or during sewing operations for compliance with 3.3.1.5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:43Z
Check the source to verify that this is the current version before use.

b. Holes punched to receive grommets are in compliance with 3.3.2.

c. Holes punched to receive male or female parts of snap-fasteners are in compliance with 3.3.3.

d. The 8-inch hem on inner edge of right and left end walls contains a double-ply reinforcement; the rope stiffener is flush with the folded edge of the 2-ply reinforcement and is kept in place by a row of stitching through both plies of the reinforcement for compliance with section A-A on Drawing 5-4-942.

e. Line "B" is spliced into line "A" as specified for compliance with Drawing 5-4-946.

Whenever nonconformance is noted, correction shall be made to the item affected and to the process.

* 4.4.3 End item general visual examination. The completely fabricated tent cover, end section, or intermediate section shall be examined for listed defects as follows:

Cover	Table I only
End section	Table I and table II
Intermediate section	Table I and table III

The lot size shall be expressed in units of tent covers, end sections, or intermediate sections as applicable. The sample unit shall be one tent cover, end section, or intermediate section, as applicable. The inspection level shall be I. The AQL, expressed in terms of defects per hundred units shall be:

For covers	6.5 for major defects 15.0 for major and minor A defects combined 40.0 for total (major, minor A and minor B) defects combined
For end sections	10.0 for major defects 25.0 for major and minor A defects combined 100.0 for total (major, minor A and minor B) defects combined
For intermediate sections	6.5 for major defects 15.0 for major and minor A defects combined 65.0 for total (major, minor A and minor B) defects combined

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:43Z
Check the source to verify that this is the current version before use.

TABLE I. End item general visual defects

Examine	Defect	Classification		
		Major	Minor A	Minor B
Fabric	Cut, tear, or hole (including exposed drill hole) greater than 1/8 inch in length or diameter:			
	- on tent section	X		
	- on cover or sod cloth		X	
	Cut, tear, or hole (including exposed drill hole) 1/8 inch or less in length or diameter:			
	- more than 20 holes:			
	- on tent section	X		
	- on cover or sod cloth		X	
	- more than 10 but not more than 20 holes:			
	- on tent section		X	
	- on cover or sod cloth			X
	- more than 5 but not more than 10 holes:			
	- on tent section			X
	Broken or missing yarn, multiple floats clearly visible at normal inspection distance (approximately 3 feet)		X	
Screening	Cut or tear:			
	- more than 2 inches in length	X		
	- more than 1/4 inch but not more than 2 inches in length		X	
	- not more than 1/4 inch in length:			
	- at more than 10 locations per square foot	X		
	- at more than 5 but not more than 10 locations per square foot		X	
	- at not more than 5 locations per square foot			X
Tape and webbing	Edge frayed or scalloped			X

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:43Z
Check the source to verify that this is the current version before use.

TABLE I. End item general visual defects - Continued

Examine	Defect	Classification		
		Major	Minor	
			A	B
Rope components	Any cut, any break:			
	- on guy line		X	
	Eye splice omitted		X	
	Eye splice not as specified			X
	Any free end not finished as specified			X
Hardware	Broken	X		
	Malformed:			
	- fails to perform intended function	X		
	- but will perform intended function		X	
	Corroded area			X
	Burr or sharp edge that may cause injury in handling or damage to fabric	X		
Grommets	Improperly set: two or more teeth exposed (except where grommet is set as specified but is in an area of unequal thickness that prevents uniform clinching)			X
	Clinched loosely allowing grommet to rotate in hole			X
	Clinched excessively tight, cutting fabric:			
	- on tent section	X		
	- on cover		X	
	Insecurely clinched (i.e., grommet or washer may become disengaged):			
	- on tent section	X		
	- on cover		X	
	Roll of grommet contains more than three scores (splits)			X
Wood toggles	Any knots, shakes, or checks			X
	Any splits or splintery surfaces		X	
"J" hook	Not inserted in leather hook retainer as specified	X		

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:43Z
Check the source to verify that this is the current version before use.

TABLE I. End item general visual defects - Continued

Examine	Defect	Classification		
		Major	Minor A	Minor B
Seams and stitching	Open seam on stitch type 301:			
	- for more than 1/4 inch but not more than 1 inch			X
	- for more than 1 inch		X	
	Open seam on stitch type 401:			
	- one row of stitching open for 1 inch or less on tent section or cover			X
	- one row of stitching open for more than 1 inch on tent section or cover		X	
	- both rows of stitching open (not necessarily at same location) on tent section or cover	X		
	NOTE: A seam shall be classified as open when one or more stitches joining a seam are broken or when one or more skipped or run-off stitches occur. On double stitched seams, a seam shall be classified as open when either one or both sides of seam are open.			
	Raw edges caught in stitching:			
	- more than 1 inch but not more than 3 inches			X
	- more than 3 inches		X	
	Thread breaks:			
	- overstitched less than 1 1/2 inches on stitch type 401			X
	- overstitched less than 1 inch on stitch type 301			X
	- overstitched less than 3/4 inch on stitch type 304			X
	NOTE: Thread breaks not overstitched shall be classified as open seams.			

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:43Z
Check the source to verify that this is the current version before use.

TABLE I. End item general visual defects - Continued

Examine	Defect	Classification		
		Major	Minor A	Minor B
Seams and stitching - continued	Skipped stitches:			
	- overstitched less than 1 1/2 inches on stitch type 401			X
	- overstitched less than 1 inch on stitch type 301 or 304 (when two or more skipped stitches occur consecutively)			X
NOTE:	Skipped stitches not overstitched shall be classified as open seams.			
	Needle chews resulting in cut, tear, or hole (see fabric cut, tear, or hole for classification)			
	One or more required rows of stitching omitted (except on boxstitching and "W" stitching)	X		
Boxstitching	Incomplete:			
	- one row of stitching omitted			X
	- two or more rows of stitching omitted		X	
	Any boxstitching less than specified length by more than 1/8 inch			X
"W" stitching	Incomplete:			
	- one row of stitching omitted		X	
	- two or more rows of stitching omitted	X		
	Any "W" stitching less than specified length by more than 1 inch			X

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:43Z
Check the source to verify that this is the current version before use.

TABLE I. End item general visual defects - Continued

Examine	Defect	Classification		
		Major	Minor A	Minor B
Seams and stitching - continued				
Stitching ends	Overstitched less than 1 inch on stitch type 301 (except where ends are held down by other stitching, turned under in a hem, or where stitching is performed automatically)		X	
	Secured with less than three tying, overlapping, or back stitches when automatic stitching is performed		X	
	Secured with less than 1/4 inch of back stitching, overstitching, or an increased number of stitches per inch at the end of stitch type 304			X
Seams	Seam pleated			
Seam type	Wrong seam type	X		
Stitch type	Wrong stitch type	X		
Stitch tension	Loose resulting in an exposed bobbin or top thread for more than 6 inches		X	
	Tight as evidenced by puckering on fabric for more than 6 inches		X	
Stitches per inch	Less than minimum specified (except panel joining seams):			
	- one stitch			X
	- two or more stitches		X	
	Less than minimum specified on panel joining seams		X	
	More than maximum specified:			
	- one stitch			X
	- two or more stitches		X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:43Z
Check the source to verify that this is the current version before use.

TABLE I. End item general visual defects - Continued

Examine	Defect	Classification		
		Major	Minor A	Minor B
Seams and stitching - continued				
	NOTE: Variation in the number of stitches per inch, caused by the operator speeding up the machine and pulling the fabric in order to sew over heavy places or heavy seams or in turning corners, shall be classified as follows: a. Within the minor "B" defect classification - no defect b. Within the minor "A" defect classification - minor "B" defect			
Stitching gage	Not as specified		X	
Stitching margin	Larger than specified by more than 3/16 inch			
	- for more than 2 inches but not more than 4 inches in length			X
	- for more than 4 inches in length		X	
	Less than specified			
	- for more than 2 inches but not more than 4 inches in length			X
	- for more than 4 inches in length		X	
Stitching indicated by "Z" on drawings	Chain portion of stitching shows on outside of tent cover		X	
Mends, darns, or patches	Repairs not in accordance with Department of the Army Field Manual FM 10-16 or not authorized by the contracting officer (see 3.3.7)	X		
Components and assembly	Any component part not fabricated of applicable referenced material	X		
	Any component omitted	X		

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:43Z
Check the source to verify that this is the current version before use.

TABLE I. End item general visual defects - Continued

Examine	Defect	Classification		
		Major	Minor A	Minor B
Component and assembly - continued	Any operation not performed as specified (unless otherwise classified herein)	X		
Hems	Constructed with partial turnunder when double turnunder is required		X	
	Twisted or pleated (except on semi-circular hem of ends)			X
Reinforcements	Improperly applied causing excessive fullness on reinforcement or reinforced part			X
Slide fastener	Slider jams or fails to interlock chain	X		
	Any tape improperly assembled, causing failure of chain to effect a smooth and secure closure	X		
	Thong omitted			X
Construction details defects				
Openings on sod cloth	Openings not fully reinforced; ends of reinforcement not overlapped or overlapped less than 1/2 inch		X	
Guy line sleeves	Not stitched through body of section, arch reinforcement and 1-inch webbing reinforcement; attached to the inside of end section or intermediate section in lieu of outside; misplaced, failing to cover fully the guy line opening; sleeve opening obstructed or caught in unrelated stitching, failing to provide clearance for guy lines.	X		
Transverse line	Line "B" misplaced, failing to extend from No. 3 grommet on hem	X		

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:43Z
Check the source to verify that this is the current version before use.

TABLE I. End item general visual defects - Continued

Examine	Defect	Classification		
		Major	Minor A	Minor B
Construction details defects - continued				
Buckles	Not attached to securing strap "C" assembly as specified (i.e., reversed, failing to effect a secure fastening of straps)	X		
Markings and labels	Omitted, incorrect, illegible, misplaced, or not type specified			X
Cleanness	Grease or oil stains			X
	Thread ends not trimmed to 1/2 inch or less (except in slide fastener area)			X
	Thread ends not trimmed to 1/2 inch or less in slide fastener area		X	

* 4.4.4 Tent end section general visual defects. In addition to the defects listed in table I, the tent end section shall be examined for the defects listed in table II.

TABLE II. End section general visual defects

Examine	Defect	Classification		
		Major	Minor A	Minor B
Vehicle door flaps	Constructed with less than two plies of material	X		
"J" hook and hook retainers	Misplaced, failing to effect a smooth and secure closure of door flaps when laced in a closed position	X		
	Any "J" hook reversed (i.e., set with hook portion facing edge of end wall flap or edge of vehicle door)	X		

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:43Z
Check the source to verify that this is the current version before use.

TABLE II. End section general visual defects - Continued

Examine	Defect	Classification		
		Major	Minor A	Minor B
Spar pockets (A, B, C, & D)	Not formed and stitched to door as specified	X		
Dee ring chape "A"	Not stitched through both the vehicle door and the 2-inch tape	X		
Dee rings	One ring missing		X	
	Two or more rings missing	X		
Ventilator screen	Edges of screen not fully caught in stitching of facing			X
Snap hook with spring	Type not as specified; spring tongue on snap jams or fails to function properly	X		
Snap fasteners	Misplaced, failing to effect a smooth and secure closure; female components used on location where male components are required	X		
	Fasteners fail to snap in a closed position or to remain firmly closed	X		
	Roll of clinched eyelet fastener assembly contains more than three scores (splits)			X
Rivets	Not securely set and neatly headed	X		
Ventilator flap	Misplaced, failing to cover ventilator opening fully when in a closed position or attached to outside of end assembly	X		
Ventilator hood	Not constructed as specified; not attached to door as specified; spring assembly in hem fails to hold ventilator open	X		

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:43Z
Check the source to verify that this is the current version before use.

TABLE II. End section general visual defects - Continued

Examine	Defect	Classification		
		Major	Minor	
			A	B
Heater duct opening	Cut out on lower left wall in lieu of lower right (facing door from inside)	X		
Heater duct sleeve	Stitched to duct opening on inside of tent section		X	
Personnel door flap	Not formed or attached to left end wall as specified, failing to cover opening and slide fastener fully when in a closed position	X		
Toggle and loops	Out of alignment with one another failing to effect a smooth and secure closure		X	
Securing strap "A"	Not stitched through 2-inch tape, 6-inch reinforcement, and vehicle door	X		
Markings and labels	Omitted, incorrect, illegible, misplaced, or not type specified			X

* 4.4.5 Intermediate section visual defects. In addition to the defects listed in table I, the tent intermediate section shall be examined for the defects listed in table III.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:43Z
Check the source to verify that this is the current version before use.

TABLE III. Intermediate section visual defects

Examine	Defect	Classificatio	
		Major	Mino A
Window pane and screen	Any puncture, deep creases, or cracks on pane	X	
	Film not securely caught in frame stitching all around		X
	Edges of screen not securely caught in stitching attaching window reinforcement tape to opening		X
Window blackout flap	Misplaced, failing to cover window opening fully when in a closed position	X	
Purlin reinforcements	Ends not securely caught in hem stitching		
Arch reinforcements	Inner edge not flush with fold line of hem		

4.4.6 End item dimensional examination. The end item shall be examined for the applicable defects listed in table IV. The lot size shall be expressed in units of end sections and cover or intermediate sections and cover, as applicable. The sample unit shall be one end section with cover or one intermediate section with cover, as applicable. The inspection level shall be S-4. For end sections and intermediate sections the AQL, expressed in terms of defects per hundred units, shall be 4.0 for major defects, 25.0 for combined major and minor A defects, and 65.0 for total combined (major, minor A, and minor B) defects. For the covers (both for end sections and for intermediate sections, the AQL shall be 4.0 for major defects, 10.0 for combined major and minor A defects, and 40.0 for total combined (major, minor A, and minor B) defects.

Source: https://assist.dla.mil -- Downloaded: 202640-21T19:43Z
Check the source to verify that this is the currentversion before use.

TABLE IV. End item dimensional defects

Examine	Defect	Classification		
		Major	Minor A	Minor B
Overall dimensions of end section and intermediate sections	Smaller than nominal dimensions less applicable minus tolerance indicated on drawings	X		
	Larger than nominal dimensions and applicable plus tolerance indicated on drawings			X
Cover	Smaller than nominal dimensions less applicable minus tolerance indicated on drawings but not smaller than nominal dimensions less twice the applicable minus tolerance			X
	Smaller than nominal dimensions less twice the applicable minus tolerance indicated on drawings		X	
	Larger than nominal dimensions and applicable plus tolerance indicated on drawings			X
Tent openings	Under or over specified dimensions by more than 1/2 inch (unless otherwise specified)			X
Tape and webbing; tie tapes	Finished length less than specified by more than 1/2 inch			X
Rope components	Line "A" less than specified length by more than 2 inches; line "B" less than specified length by more than 1 inch		X	
Leather strap (hook retainer)	Length and width less than specified by more than 1/8 inch; thickness less than specified by more than 1/64 inch		X	
Hems	Required to finish less than 3/4 inch in width, less than specified, hems required to finish 3/4 inch or more in width, less than specified by more than 1/4 inch			X

Source: https://assist.dla.mil -- Downloaded: 202610-21T19:43Z
Check the source to verify that this is the current version before use.

TABLE IV. End item dimensional defects - Continued

Examine	Defect	Classification		
		Major	Minor A	Minor B
Guy line opening	Less than 2 inches wide; less than 10 inches long			X
Location dimensions	Components set beyond specified tolerances		X	
Grommets	Door grommets set beyond specified location by more than 3/8 inch; cover grommets set beyond specified location by more than 1/2 inch			X
Windows	Vertical center line of opening out of alignment with center line of intermediate section: - by more than 1/2 inch, but not more than 1 inch			X
	- by more than 1 inch			
Purlin reinforcements	Out of specified location by more than 1 inch		X	
Openings on sod cloth	Out of specified location by more than 1/2 inch		X	
Guy line opening	Out of specified location: - by 1 inch or more, but less than 1 1/2 inches			X
	- by 1 1/2 inches or more		X	

4.4.7 End item testing. The end item shall be tested for wicking as specified in 4.5.1 for compliance with the requirements in 3.3.8. The lot size shall be expressed in units of end sections or intermediate sections, as applicable. The sample unit shall be one end section or intermediate section, as applicable. The inspection level shall be S-3. Any test failure shall be cause for rejection of the lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:43Z
Check the source to verify that this is the current version before use.

4.4.8 Packaging examination. The fully packaged end items shall be examined for the defects listed below. The lot size shall be expressed in units of shipping containers. The sample unit shall be one shipping container fully packaged. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

Examine	Defect
Marking (exterior and interior)	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application
Materials	Any component missing, damaged, or not as specified
Workmanship	Inadequate application of components, such as incomplete closure of cloth covered bundles or bundles insecurely sewn

4.5 Methods of inspection.

4.5.1 Seam leakage test. The tent section shall be tested in two areas as follows: At a panel lap seam and on a purlin reinforcement seam. Suspend the seamed section of the test fabric in the center of a 6 inch ± 1/8-inch diameter hoop and form a depression with the seamed fabric in the hoop to a depth of 1 inch ± 1/4 inch. Slowly pour 500 mL of water at a temperature of 77° ± 4°F into the cupped area (depression) and observe the under surface of the test areas for water penetration. Any wicking of water along the sewing thread, identified by a discoloring or darkening of the thread, within 5 minutes after the water is poured shall be considered a test failure. Water leakage through the needle holes or between the plies of the lapped seamed fabric shall not be considered a failure.

5. PACKAGING

5.1 Preservation. Preservation shall be level A or Commercial, as specified (see 6.2).

5.1.1 Level A. Each tent end section and intermediate section shall be neatly folded. All windows, doors, window blackout flaps, and heater duct openings shall be closed and secured before folding operation. Care shall be exercised to avoid folding the windows. Each completely folded end or intermediate tent section shall be placed within the cover provided. Two tent lines shall be included with each intermediate section.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:43Z
Check the source to verify that this is the current version before use.

5.1.2 Commercial. Tent sections shall be preserved in accordance with ASTM D 3951.

5.2 Packing. Packing shall be level A, B, or Commercial, as specified (see 6.2).

5.2.1 Level A packing. Each tent section, preserved as specified in 5.1, shall be packed within a close-fitting wood-cleated plywood shipping container conforming to overseas type, style A of PPP-B-601. Each shipping container shall be closed and strapped with flat steel strapping in accordance with the container specification.

5.2.2 Level B packing. Each tent section, preserved as specified in 5.1, shall be wrapped and sewn in cotton onsaburg cloth conforming to class 2 of CCC-C-429; or burlap cloth conforming to class 3 of CCC-C-467. The wrapping shall be securely hand sewn with type I or II, 16-ply cotton twine conforming to T-T-871, or type I, size No. 2 jute twine conforming to T-T-911, with approximately one stitch to the inch and every third stitch knotted, or alternatively, the bottom and side may be machine sewn. A minimum of five inches of wrapping material shall be gathered together on each of the four corners and securely hand-sewn into ears for handles. However, the polyester thread used in manufacturing the end item may be used for effecting the machine sewn closure of the wrapping or tubing.

5.2.3 Commercial packing. Tent sections, preserved as specified in 5.1, shall be packed in accordance with ASTM D 3951.

5.3 Marking. In addition to any special marking required by the contract or purchase order, shipments shall be marked in accordance with MIL-STD-129 or ASTM D 3951, as applicable.

5.3.1 Additional marking. The following shall be stenciled or imprinted on each shipping container and cloth covered bundle in characters not less than three-fourths of an inch high:

"SEE ERECTION INSTRUCTIONS SEWED
TO INSIDE OF TENT COVER"

6. NOTES

6.1 Intended use. The tent sections are designed to be used in forming a medium size tent for repair of wheeled and track vehicles in cold climates. The tent is procurable in varied lengths depending on the number of intermediate sections required. Each increase or reduction in the required number changes the length by 8 feet.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:43Z
Check the source to verify that this is the current version before use.

6.2 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this document.
b. Type required (see 1.2).
c. When a first article is required (see 3.1, 4.3, and 6.3).
d. Selection of applicable levels of preservation and packing (see 5.1 and 5.2).

6.3 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of FAR 52.209. The first article should be a preproduction sample. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should include specific instructions in all acquisition instruments regarding arrangements for selection, inspection, and approval of the first article.

6.4 Recycled material. It is encouraged that recycled material be used when practical as long as it meets the requirements of this document (see 3.2).

6.5 Commercial products. The North and Judd Manufacturing Company's zinc die cast 5/8-inch loop eye snap has been found to meet the requirements of paragraph 3.2.18. The Astrup Company, Cleveland, Ohio, brass rope clamp No. 877 has been found to meet the requirements of 3.2.27.

6.6 Tent lines. The tent lines (type XLIII) as required in 3.2.10 are to be used as guy lines when erecting the frame.

6.7 Other components. The components required for erection of the tent sections covered by this document are as follows:

Frame sections conforming to MIL-F-40132
Pins, tent, steel, 12-inch
Anchors, ground, 4-inch, arrowhead, malleable iron, with guy lines

The numbers of components required is dependent upon the number of tent sections utilized in forming a maintenance tent.

6.8 Seam retreatment. A satisfactory method of applying the textile retreatment compound for the repair of leaking seams is as follows:

a. A suitable volume of compound conforming to type I, class 1 of TT-T-595, shall be thoroughly stirred and diluted with an equal volume of petroleum solvent (Stoddard solvent or equivalent).

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:43Z
Check the source to verify that this is the current version before use.

b. Prior to application of the compound, the tents must be dry. Special attention must be taken to insure adequate ventilation and that pro fire preventive measures are taken since the compound is flammable.

c. Two coats of the compound shall then be applied to the seams (or the outside of the tent only). A four-inch wide stiff brush is recommended for use. The first coat shall be air dried for a minimum of four hours pri to application of the second coat. Elapsed time between coats may be reduc by providing a supply of hot air to evaporate the solvent more quickly. In this manner, a second coat may be applied as soon as the first coat is dry the touch. After the application of the second coat, the treated tent shal be allowed to air dry for a period of at least 24 hours.

6.8.1 Seams to be treated. Seams that have failed the test specified in 4.5.1 shall be treated as follows:

a. Failure at panel lap seams. Treat all panel lap seams.
b. Failure at purlin reinforcement seams. Treat all purlin reinforcement seams.

6.9 International standardization agreements. Certain provisions of thi document are the subject of international standardization agreement as cite in NATO, STANAG No. 2882, relative to camouflage requirements for ten shelters and subsidiary components. When amendment, revision, or canc at of this document is proposed that will affect or violate the international agreement concerned, the preparing activity will take appropriate reconciliation action through international standardization channels includ departmental standardization offices, if required.

* 6.10 Subject term (key word) listing.

Tent, maintenance
Tent sections

6.11 Changes from previous issue. The margins of this document have bee marked with an asterisk (*) to indicate where changes (additions, modificat corrections, deletions) from the previous issue were made. This was done a convenience only, and the Government assumes no liability whatsoever for an inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content, as written, irrespective of the marginal notations and relationship to the las previous issue.

Source: https://assist.dla.mil -- Downloaded: 202610-21T19:43Z
Check the source to verify that this is the current version before use.

Custodians:

Army - GL
Navy - NU
Air Force - 99

Review activities:

Army - MD
Air Force - 82
DLA - CT

User activities:

Navy - YD, MC
Air Force - 45

Preparing activity:

Army - GL

Project No. 8340-0502

Source: https://assist.dla.mil -- Downloaded: 202610-21T19:43Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this fo submitting comments and suggestions for improvements. All users of military standardization documents are invit suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT S* mailed. In block 5, be as specific as possible about particular problem areas such as wording which required inter too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alle problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled acknowledgement will be mailed to you within 30 days to let you know that your comments were received and a considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarific specification requirements on current contracts. Comments submitted on this form do not constitute or imply au to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

US Army Natick Research, Development, and
Engineering Center
Natick, MA 01760-5014

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300
STRNC-ES

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Natick Research, Development,
and Engineering Center
ATTN: STRNC-ES
Box 14A
Natick, MA 01760-5014

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:43Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions - Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-T-41313F	Tent Sections, Frame Type, Maintenance, Medium

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION (Mark o
	☐ VENDOR
	☐ USER
b. ADDRESS (Street, City, State, ZIP Code)	☐ MANUFACTURER
	☐ OTHER (Specify)

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation

6. REMARKS

7a. NAME OF SUBMITTER (Last, First, MI) - Optional	b. WORK TELEPHONE NUMB Code) - Optional
c. MAILING ADDRESS (Street, City, State, ZIP Code) - Optional	8. DATE OF SUBMISSION (YYMMDD)

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-01-21 16:44:42
Check the source to verify that this is the current version before use.