INCH-POUND

MIL-DTL-83796/3B
w/AMENDMENT 1
24 May 2012
SUPERSEDING
MIL-DTL-83796/3B
11 August 2008

DETAIL SPECIFICATION SHEET

HOSE ASSEMBLY, RUBBER, LIGHTWEIGHT, MEDIUM PRESSURE, FIELD ATTACHABLE END FITTINGS, FLARELESS TO FLARELESS

This specification is approved for use by all
Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-83796.




FIGURE 1. Hose assembly styles, field attachable fittings, flareless-to-flareless.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:41Z
Check the source to verify that this is the current version before use.

Hose assembly elbow fitting drop height. Elbow fitting drop height, A and B as shown on figure 2, are as specified in the applicable fitting specification sheet (see table I).

TABLE I. Hose assembly, field attachable fittings, HCOF, styles A thru M.


Style	Fitting ends MIL-DTL-83798		MIL-DTL-83797 hose cut off factor (HCOF) 1/ inches verses hose dash size number										
	Fitting 1	Fitting 2	-03	-04	-05	-06	-08	-10	-12	-16	-20	-24	-32
A and B	M83798/4	M83798/4	1.88	1.78	1.84	2.08	2.38	2.56	2.74	3.20	3.60	4.14	4.92
C and D	M83798/4	M83798/5	2.03	2.06	2.17	2.40	2.66	2.91	3.27	3.82	4.30	4.89	5.71
E and F	M83798/4	M83798/6	1.73	1.83	1.90	2.11	2.34	2.55	2.96	3.53	4.03	4.64	5.32
G and H	M83798/5	M83798/5	2.18	2.34	2.50	2.72	2.94	3.26	3.80	4.44	5.00	5.64	6.50
J and K	M83798/5	M83798/6	1.88	2.11	2.23	2.43	2.62	2.90	3.49	4.15	4.73	5.29	6.11
L and M	M83798/6	M83798/6	1.58	1.88	1.96	2.14	2.30	2.54	3.18	3.86	4.46	4.94	5.72

1/ Example of hose cut-off factor: for a -04, 1/4 hose OD, 18-1/2 assembly length, style D, the bulk hose length = 18.50 - the HCOF = 18.50 -2.03 = 16.47. Bulk hose length required is 16.47.

Hose assembly length. The hose assembly length is calculated as shown on figure 2.

Angular displacement. Angular displacement shall be as shown on figure 3.


Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:41Z
Check the source to verify that this is the current version before use.



NOTES:
1. Drop height B and C can be found in the applicable MIL-DTL-83798 slash sheet as specified in table I herein.
2. Hose length “L” is measured from one fitting end to another fitting end.

FIGURE 2. Hose assembly dimensions and elbow drop heights.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:41Z
Check the source to verify that this is the current version before use.



NOTES:

1. Angular displacement for hose assemblies with elbow fittings on both ends shall have the angular displacement between elbows, measured counter-clockwise from the centerline of the nearest fitting, positioned at six-o' clock, to the centerline of the other fitting (see SAE-J517).
2. The near end of the connector shall be put in numerical order relative to the far end (see table I). Example: Near end adapter 45°, far end 90°.
3. Angular displacement shall be measured in degrees with a tolerance of ± 3° for lengths up to 2 feet (61 cm) and ± 5° for all lengths over 2 feet (61 cm).
4. The angular displacement shall be expressed in two digits number of degrees divided.
5. Making the angular determination in the wrong direction will result in an unacceptable part.

FIGURE 3. Elbow fitting drop height and angular alignment.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:41Z
Check the source to verify that this is the current version before use.

REQUIREMENTS

Hose assemblies shall be specified on figures 1, 2, and 3.

Fittings shall mate with parts in accordance with SAE-AS33514.

Hose assembly length tolerance shall be in accordance with MIL-DTL-83796.

Size codes shall be as specified in table II.

TABLE II. Size code. 1/ 2/

Dash number		-03	-04	-05	-06	-08	-10	-12	-16
Size code		B	E	F	G	H	J	K	M
Hose OD reference	Inches fraction	3/16	1/4	5/16	3/8	1/2	5/8	3/4	1
	Inches decimal	.188	.250	.313	.375	.500	.625	.750	1.000
	mm	4.78	6.35	7.95	9.53	12.70	15.88	19.05	25.40

Dash number		-20	-24	-32
Size code		N	P	R
Hose OD reference	Inches fraction	1 1/4	1 1/2	2
	Inches decimal	1.250	1.500	2.000
	mm	31.75	38.10	50.80

1/ Dimensions are in inches.
2/ Metric equivalents are given for information only.

Materials and finishes shall be in accordance with MIL-DTL-83796 and in table III.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:41Z
Check the source to verify that this is the current version before use.


TABLE III. Nut and nipple material and finish code. 1/

PIN code dash letter 2/	Material	Plating Finish
Blank	Steel (sizes -3, -4, and -5)	Cadmium plating in accordance with SAE-AMS-C-81562, type II, class 3 or SAE-AMS-QQ-P-416, type II, class 2.
	Aluminum (sizes -6 and above)	Anodize in accordance with MIL-A-8625, type II
-A	Steel (sizes -3, -4, and -5)	Aluminum-nickel in accordance with ASTM F1136/F1136M, grade 3, NC
-B	Aluminum (sizes -6 and above)	Anodize above with NAVAIR trivalent chromium pretreatment (TCP) in accordance with MIL-DTL-81706, type 2, class 1A.
-CN	Steel (sizes -3, -4, and -5)	Cadmium plating in accordance with SAE-AMS-C-81562, type II, class 3 or SAE-AMS-QQ-P-416, type II, class 2 with NAVAIR TCP in accordance with MIL-DTL-81706, type 2, class 1A.
-H	Steel (sizes -3, -4, and -5)	Zinc phosphate finish in accordance MIL-DTL-16232 type Z, class1 3/
-J	Steel (sizes -3, -4, and -5)	Zinc plating in accordance with ASTM B633; type II or III, Fe/Zn 5, or ASTM B695, type II, class 5
N	Steel (sizes -3, -4, and -5)	NAVAIR TCP above.
-R	Steel (sizes -3, -4, and -5)	Zinc plating in accordance with ASTM B633; type VI, Fe/Zn 5.
-S	Corrosion resistant steel	No additional finish. Passivation in accordance with SAE-AMS2700, method 2
-T	Titanium (all sizes) 4/	Annealed
-V	Steel (sizes -3, -4, and -5)	Zinc-nickel in accordance with SAE-AMS2417, type 1
-Z	Zinc any type above	PIN code F, G, H, J, R, V
-ZN	Zinc any type above	PIN code F, G, H, J, R, V with NAVAIR TCP in accordance with MIL-DTL-81706, type 2, class 1A.

1/ Shall be capable of withstanding minimum of 96 hours salt spray.
2/ Part or Identifying Number (PIN).
3/ Hexavalent chromium free.
4/ Not for use in oxygen systems.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:41Z
Check the source to verify that this is the current version before use.

PIN example:



M83796/3H082F06T indicates - Hose assembly for 1/2 hose OD, 8 1/4 inches in length, style F, 30° between elbows, titanium alloy.

Amendment notations. The margins of this specification are marked with vertical lines to indicate modifications generated by this amendment. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations.

Referenced documents. In addition to MIL-DTL-83796, this document references the following:

MIL-A-8625	ASTM F1136/F1136M
MIL-DTL-16232	SAE-AMS2417
MIL-DTL-81706	SAE-J517
MIL-DTL-83797	SAE-AMS-C-81562
MIL-DTL-83798	SAE-AMS-QQ-P-416
ASTM B633	SAE-AMS2700
ASTM B695	SAE-AS33514

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:41Z
Check the source to verify that this is the current version before use.

CONCLUDING MATERIAL

Custodians:
Army - AV
Navy - AS
Air Force - 99
DLA - CC

Preparing activity:
DLA - CC

(Project 4720-2012-002)

Review activities:
Army - AT
Navy - MC, SA
Air Force 71, 85

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:41Z
Check the source to verify that this is the current version before use.