DATA ITEM DESCRIPTION
Title: PAINT PRESERVATION APPENDICES REPORT

Number: DI-MISC-82120
AMSC Number: N9794
DTIC Applicable: No
Preparing Activity: SH
Applicable Forms: N/A

Approval Date: 20170410
Limitation: N/A
GIDEP Applicable: No
Project Number: MISC-2017-006

Use/Relationship: The Preservation Appendices Report will provide the Government with evidence of completed preservation operations.

This DID contains the format and content preparation instructions for the data product generated by the specific and discrete task requirements as delineated in the contract.

Requirements:

Format. The Paint Preservation Appendices Report shall be in contractor's format.

Content. The Paint Preservation Appendices Report shall contain all the information contained in Sample Figures 1 through 9.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:59Z
Check the source to verify that this is the current version before use.

SAMPLE FIGURE-1

APPENDIX 1
QA INSPECTION FORM - ENVIRONMENTAL READINGS & PAINT/NONSKID STORAGE

SHIP NAME & HULL #: _____ **CONTRACT/TASK ORDER/CLIN/TWD:** _____ **DATE/TIME:** _____

LOCATION: _____ **WORK ITEM:** _____ **PARA. NO.:** _____

(I) ___ **(V)** ___ **(G)** ___ **PRODUCT BEING APPLIED:** _____

REQ'T DOCUMENT: _____ **/FY:** _____ **TABLE:** _____ **LINE:** _____ **COLUMN:** _____
(NSTM 631, 634, PPI, NSI 009-32 FY)

MAINTAIN SEPARATE LOG FOR EACH AREA/LOCATION, PREPARED OR COATED SURFACE. WHEN AN AREA IS DIVIDED INTO SEPARATE SECTIONS, MAINTAIN A SEPARATE LOG FOR EACH SECTION.

NOTE #1 FOR ANY UNSAT CONDITION FOUND, PROVIDE THE TECHNICAL ADJUDICATION AND CORRECTIVE ACTION TAKEN IN THE COMMENTS BLOCK.
NOTE #2 UNLESS OTHERWISE STATED IN SPECIFICATION, SURFACE TEMPERATURE MUST BE A MINIMUM OF 50 DEG F AND AT LEAST 5 DEG F ABOVE DEW POINT.
NOTE #3 IF SPACES ARE NOT APPLICABLE, INSERT N/A. UNUSED SECTIONS SHALL BE CROSSED OUT AND MARKED N/A.

ACCEPT CRITERIA: **ENV: MAX %RH:** ____ **SURFACE TEMP:** MIN: ____ MAX: ____ **STORAGE TEMP:** MIN: ____ MAX: ____

Check for Ventilation Running (PW, RFW, & FWDC Tanks): ☐ | Data Logger Used? (Yes/No) ☐

Date	Time	Enter Activity/Process: Cleanliness Check, Surface Preparation, Prime Application, Prime Cure, Stripe Application, Stripe Cure, Intermediate Application, Intermediate Cure, Tack Application, Top Coat Application, Top Coat Cure, etc.	Substrate Surface Temp. (°F)	Dew Point (°F)	% RH	Dry Bulb (Ambient Temp) (°F)	Wet Bulb (°F)

Gage # _____ Gage Cal Due Date: _____ Condition of Reading SAT: ☐ UNSAT: ☐

Gage # _____ Gage Cal Due Date: _____

Contractor (Print): _____ Contractor (Signature): _____

COMMENTS: _____

Date	Time	Enter Activity/Process: Cleanliness Check, Surface Preparation, Prime Application, Prime Cure, Stripe Application, Stripe Cure, Intermediate Application, Intermediate Cure, Tack Application, Top Coat Application, Top Coat Cure, etc.	Substrate Surface Temp. (°F)	Dew Point (°F)	% RH	Dry Bulb (Ambient Temp) (°F)	Wet Bulb (°F)

Gage # _____ Gage Cal Due Date: _____ Condition of Reading SAT: ☐ UNSAT: ☐

Gage # _____ Gage Cal Due Date: _____

Contractor (Print): _____ Contractor (Signature): _____

COMMENTS: _____

Date	Time	Enter Activity/Process: Cleanliness Check, Surface Preparation, Prime Application, Prime Cure, Stripe Application, Stripe Cure, Intermediate Application, Intermediate Cure, Tack Application, Top Coat Application, Top Coat Cure, etc.	Substrate Surface Temp. (°F)	Dew Point (°F)	% RH	Dry Bulb (Ambient Temp) (°F)	Wet Bulb (°F)

Gage # _____ Gage Cal Due Date: _____ Condition of Reading SAT: ☐ UNSAT: ☐

Gage # _____ Gage Cal Due Date: _____

Contractor (Print): _____ Contractor (Signature): _____

COMMENTS: _____

Paint/Nonskid Storage

Date	Time/ Time Range	Enter Product/Component & Prime, Stripe, Intermediate, Tack, Top Coat	Min. & Max. Temp. for 24hr Period Prior to Initiation of Application	–OR– Storage Temp. Manually Measured	–OR– Core Temp. After Each Component Separately Mixed Part A / Part B		Method of Measurement
			Min.: /Max.:				

Contractor (Print): _____ Contractor (Signature): _____

COMMENTS: _____

FY17 Change 1 version

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:59Z
Check the source to verify that this is the current version before use.

SAMPLE FIGURE-2

APPENDIX 2
QA INSPECTION FORM - SSPC-SP 1 CLEANLINESS CHECKPOINT

SHIP NAME & HULL #: _____ **CONTRACT/TASK ORDER/CLIN/TWD:** _____ **DATE/TIME:** _____

LOCATION: _____ **WORK ITEM:** _____ **PARA. NO.:** _____

(I) ___ **(V)** ___ **(G)** ___ **PRODUCT BEING APPLIED:** _____

REQ'T DOCUMENT: _____ **/FY:** _____ **SQFT OF AREA PRESERVED:** _____ **PARTIAL AREA:** _____ **/FINAL:** ___
(NSTM 631, 634, PPI, NSI 009-32 FY)

Accomplish SSPC-SP-1 degreasing/cleaning to ensure the removal of surface contaminants.	Date/Time: _____	SAT: ☐ UNSAT: ☐
Accomplish degreasing/cleaning a maximum of 4 hours prior to surface preparation, ensuring the adequate removal of surface contaminants.	Date/Time: _____	SAT: ☐ UNSAT: ☐
Start of Surface Preparation Coating Removal:	Date/Time: _____	
If evidence of contamination exists, accomplish degreasing/cleaning a maximum of 4 hours prior to the application of each coat of paint to ensure removal of surface contaminants.	Date/Time: _____	SAT: ☐ UNSAT: ☐

COMMENTS: _____

Contractor (Print): _____	Contractor (Signature): _____	Date/Time: _____
Subcontractor (Print): _____	Subcontractor (Signature): _____	Date/Time: _____
Govt. Insp. (Print): _____	Govt. Insp. (Signature): _____	Date/Time: _____

FY17 Change 1 version

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:59Z
Check the source to verify that this is the current version before use.

SAMPLE FIGURE-3

APPENDIX 3
QA INSPECTION FORM - SURFACE PROFILE / PREPARATION & CLEANLINESS LOG

SHIP NAME & HULL #: _____ **CONTRACT/TASK ORDER/CLIN/TWD:** _____ **DATE/TIME:** _____

LOCATION: _____ **WORK ITEM:** _____ **PARA. NO.:** _____

(I) ___ **(V)** ___ **(G)** ___ **PRODUCT BEING APPLIED:** _____

REQ'T DOCUMENT: _____ **/FY:** _____ **SQFT OF AREA PRESERVED:** _____ **PARTIAL AREA:** _____ **/FINAL:** ___
(NSTM 631, 634, PPI, NSI 009-32 FY)

MAINTAIN SEPARATE LOG FOR EACH AREA/LOCATION, PREPARED OR PAINTED SURFACE. WHEN AN AREA IS DIVIDED INTO SEPARATE SECTIONS, MAINTAIN A SEPARATE LOG FOR EACH SECTION.

NOTE #1 FOR PAINTS & SUBMARINE NONSKID: 1 PROFILE MEASUREMENT REQUIRED FOR EVERY 200 SQFT (10 INDIVIDUAL READINGS FOR METHOD B; 2 INDIVIDUAL TAPE READINGS FOR METHOD C) FOR THE FIRST 1000 SQFT AREA (50/10 INDIVIDUAL READINGS TOTAL FOR METHOD B/C); 1 PROFILE MEASUREMENT REQUIRED FOR EACH ADDITIONAL 500 SQFT OR LESS AREA (10/2 INDIVIDUAL READINGS FOR METHOD B/C).

NOTE #2 FOR SURFACE SHIP NONSKID: 1 PROFILE MEASUREMENT REQUIRED EVERY 100 SQFT (10 INDIVIDUAL READINGS FOR METHOD B; 2 INDIVIDUAL TAPES FOR METHOD C) FOR THE FIRST 500 SQFT AREA (50 INDIVIDUAL READINGS TOTAL FOR METHOD B; 10 INDIVIDUAL TAPES TOTAL FOR METHOD C); 1 PROFILE MEASUREMENT PER 1000 SQFT REMAINING (10 INDIVIDUAL READINGS FOR METHOD B; 2 INDIVIDUAL TAPES FOR METHOD C).

NOTE #3 FOR ANY UNSAT CONDITION FOUND, PROVIDE THE TECHNICAL ADJUDICATION AND CORRECTIVE ACTION TAKEN IN THE COMMENTS BLOCK.

NOTE #4 IF SPACES ARE NOT APPLICABLE, INSERT N/A. UNUSED SECTIONS SHALL BE CROSSED OUT AND MARKED N/A.

ACCEPTANCE CRITERIA: **PROFILE RANGE** _____ **MILS** **TO** _____ **MILS**

Method B: ☐ **Method C:** ☐		**Profile Measurement (Average Mils)**			**Profile Measurement (Average Mils)**
Reading: _____ mils	Reading: _____ mils		Reading: _____ mils	Reading: _____ mils	
Reading: _____ mils	Reading: _____ mils		Reading: _____ mils	Reading: _____ mils	
Reading: _____ mils	Reading: _____ mils		Reading: _____ mils	Reading: _____ mils	
Reading: _____ mils	Reading: _____ mils		Reading: _____ mils	Reading: _____ mils	
Reading: _____ mils	Reading: _____ mils		Reading: _____ mils	Reading: _____ mils	

COMMENTS: _____

Abrasive Manufacturer: (If Applicable) _____ Type: (If Applicable) _____ Mesh Size: (If Applicable) _____

TYPE OF SURFACE PREPARATION: _____

GAGE # _____ GAGE CAL DUE DATE: _____	(Base Metal Reading) (Type 1 gage) BMR _____	SURFACE PROFILE INSP: SAT: ☐ UNSAT: ☐	SURFACE PREP. INSP: SAT: ☐ UNSAT: ☐	CLEANLINESS INSP: SAT: ☐ UNSAT: ☐

Contractor (Print): _____ Contractor (Signature): _____ Date/Time: _____

Subcontractor (Print): _____ Subcontractor (Signature): _____ Date/Time: _____

Govt. Insp. (Print): _____ Govt. Insp. (Signature): _____ Date/Time: _____

FY17 Change 1 version

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:59Z
Check the source to verify that this is the current version before use.

SAMPLE FIGURE-4

APPENDIX 4
QA INSPECTION FORM - SURFACE CONDUCTIVITY / CHLORIDE LOG

SHIP NAME & HULL #: _____ **CONTRACT/TASK ORDER/CLIN/TWD:** _____ **DATE/TIME:** _____

LOCATION: _____ **WORK ITEM:** _____ **PARA. NO.:** _____

(I) ___ **(V)** ___ **(G)** ___ **PRODUCT BEING APPLIED:** _____

REQ'T DOCUMENT: _____ **/FY:** _____ **SQFT OF AREA PRESERVED:** _____ **PARTIAL AREA:** _____ **/FINAL:** ___
(NSTM 631, 634, PPI, NSI 009-32 FY)

MAINTAIN SEPARATE LOG FOR EACH AREA/LOCATION, PREPARED OR PAINTED SURFACE. WHEN AN AREA IS DIVIDED INTO SEPARATE SECTIONS, MAINTAIN A SEPARATE LOG FOR EACH SECTION.

MAXIMUM READING (IMMERSED SURFACES): CONDUCTIVITY (30) µS/cm CHLORIDE (3) µg/cm^2
MAXIMUM READING (NON-IMMERSED SURFACES): CONDUCTIVITY (70) µS/cm CHLORIDE (5) µg/cm^2

1 READING REQUIRED FOR EVERY 200 SQFT FOR FIRST 1000 SQFT, THEN 1 READING FOR EACH ADDITIONAL 500 SQFT OR LESS

NOTE #1 FOR ANY UNSAT CONDITION FOUND, PROVIDE THE TECHNICAL ADJUDICATION AND CORRECTIVE ACTION TAKEN IN THE COMMENTS BLOCK.
NOTE #2 IF SPACES ARE NOT APPLICABLE, INSERT N/A. UNUSED SECTIONS SHALL BE CROSSED OUT AND MARKED N/A.

Test Kit Batch No.: _____ **Expiration Date:** _____

TEST LOCATIONS	CHLORIDE (µg/cm^2)	CONDUCTIVITY (µS/cm)	SAT	UNSAT

COMMENTS: _____

GAGE # _____ GAGE CAL DUE DATE: _____ CONDITION OF CHECKPOINT: SAT: ☐ UNSAT: ☐

Contractor (Print): _____ Contractor (Signature): _____ Date/Time: _____

Subcontractor (Print): _____ Subcontractor (Signature): _____ Date/Time: _____

Govt. Insp. (Print): _____ Govt. Insp. (Signature): _____ Date/Time: _____

FY17 Change 1 version

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:59Z
Check the source to verify that this is the current version before use.

SAMPLE FIGURE-5

APPENDIX 5
QA INSPECTION FORM - SURFACE CLEANLINESS (DUST) TAPE

SHIP NAME & HULL #: _____ **CONTRACT/TASK ORDER/CLIN/TWD:** _____ **DATE/TIME:** _____

LOCATION: _____ **WORK ITEM:** _____ **PARA. NO.:** _____

(I) ____ **(V)** ____ **(G)** ____ **PRODUCT BEING APPLIED:** _____

REQ'T DOCUMENT: _____ **/FY:** _____ **SPECIFIC FEATURES OF AREA TO BE TESTED:** _____
(NSTM 631, 634, PPI, NSI 009-32 FY)

ADHESIVE TAPE TYPE(S) FOR DUST MEASUREMENT: _____

MAINTAIN SEPARATE LOG FOR EACH AREA/LOCATION, PREPARED OR PAINTED SURFACE. WHEN AN AREA IS DIVIDED INTO SEPARATE SECTIONS, MAINTAIN A SEPARATE LOG FOR EACH SECTION.

NOTE #1 FOR UNDERWATER HULL, 1 INDIVIDUAL READING REQUIRED FOR EVERY 200 SQFT FOR THE FIRST 1000 SQFT AREA; IF READINGS ARE SATISFACTORY, 1 INDIVIDUAL READING REQUIRED FOR EACH ADDITIONAL 500 SQFT OR LESS AREA.
NOTE #2 FOR FLIGHT DECK NONSKID, 3 INDIVIDUAL READINGS REQUIRED EVERY 100 SQFT FOR THE FIRST 500 SQFT; IF READINGS ARE SATISFACTORY, 1 INDIVIDUAL READING PER 1000 SQFT REMAINING.
NOTE #3 FOR ANY UNSAT CONDITION FOUND, PROVIDE THE TECHNICAL ADJUDICATION AND CORRECTIVE ACTION TAKEN IN THE COMMENTS BLOCK.
NOTE #4 IF SPACES ARE NOT APPLICABLE, INSERT N/A. UNUSED SECTIONS SHALL BE CROSSED OUT AND MARKED N/A.

Spot Measurement	Dust Quantity Rating	Dust Size Class	Approximate Location

Spot Measurement	Dust Quantity Rating	Dust Size Class	Approximate Location

Spot Measurement	Dust Quantity Rating	Dust Size Class	Approximate Location

Spot Measurement	Dust Quantity Rating	Dust Size Class	Approximate Location

Spot Measurement	Dust Quantity Rating	Dust Size Class	Approximate Location

CONDITION OF CHECKPOINT

SAT: ☐ UNSAT: ☐

COMMENTS: _____

Contractor (Print): _____ Contractor (Signature): _____ Date/Time: _____

Subcontractor (Print): _____ Subcontractor (Signature): _____ Date/Time: _____

Govt. Insp. (Print): _____ Govt. Insp. (Signature): _____ Date/Time: _____

FY17 Change 1 version

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:59Z
Check the source to verify that this is the current version before use.

SAMPLE FIGURE-6

APPENDIX 6
QA INSPECTION FORM - PAINT/NONSKID APPLICATION AND CONSUMPTION LOG

SHIP NAME & HULL #: _____ **CONTRACT/TASK ORDER/CLIN/TWD:** _____ **DATE/TIME:** _____

LOCATION: _____ **WORK ITEM:** _____ **PARA. NO.:** _____

(I) ___ **(V)** ___ **(G)** ___ **PRODUCT BEING APPLIED:** _____

REQ'T DOCUMENT: _____ **/FY:** _____ **TABLE:** _____ **LINE:** _____ **COLUMN:** _____
(NSTM 631, 634, PPI, NSI 009-32 FY)

MAINTAIN SEPARATE LOG FOR EACH AREA/LOCATION, PREPARED OR PAINTED SURFACE. WHEN AN AREA IS DIVIDED INTO SEPARATE SECTIONS, MAINTAIN A SEPARATE LOG FOR EACH SECTION.

In first row, indicate which coat: e.g. Prime, Stripe, Intermediate, Tack, Top Coat, 1st AF coat, 2nd AF coat		_____ Coat	_____ Coat	_____ Coat	_____ Coat	_____ Coat	_____ Coat
Application Method: *Plural Airless, Conventional Airless, Brush, Roller, Conventional Spray*							
Airless Pump Ratio (*if Plural Component*): Fixed: ☐ Variable: ☐							
If Using Inline Heater, Temp. in °F (Fahrenheit)	Temp. Setting At Heater						
	Temp. At Tip						
Product Applied							
Product Manufacturer							
Color Applied							
Base Portion Batch No # (Part A)							
Expiration Date (Part A)							
Hardener Portion Batch No # (Part B)							
Expiration Date (Part B)							
Gallons Used Per Coat							
Square Feet Coated							
Start (Date/Time)							
Stop (Date/Time)							

COMMENTS: _____

FY17 Change 1 version

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:59Z
Check the source to verify that this is the current version before use.

SAMPLE FIGURE-7

APPENDIX 7
QA INSPECTION FORM - DRY FILM THICKNESS MEASUREMENTS

SHIP NAME & HULL #: _____ **CONTRACT/TASK ORDER/CLIN/TWD:** _____ **DATE/TIME:** _____

LOCATION: _____ **WORK ITEM:** _____ **PARA. NO.:** _____

(I) ___ **(V)** ___ **(G)** ___ **PRODUCT BEING APPLIED:** _____

REQ'T DOCUMENT: _____ **/FY:** _____ **SQFT OF AREA PRESERVED:** _____ **PARTIAL AREA:** _____ **/FINAL:** ___
(NSTM 631, 634, PPI, NSI 009-32 FY)

MAINTAIN SEPARATE LOG FOR EACH AREA/LOCATION, PREPARED OR PAINTED SURFACE. WHEN AN AREA IS DIVIDED INTO SEPARATE SECTIONS, MAINTAIN A SEPARATE LOG FOR EACH SECTION.

NOTE #1 FOR ANY UNSAT CONDITION FOUND, PROVIDE THE TECHNICAL ADJUDICATION AND CORRECTIVE ACTION TAKEN IN COMMENTS BLOCK.
NOTE #2 IF SPACES ARE NOT APPLICABLE, INSERT N/A. UNUSED SECTIONS SHALL BE CROSSED OUT AND MARKED N/A.

Select Type of Gage being used: Type 1 ☐ Type 2 ☐ Base Metal Reading (Type 1 gage): _____
Gage # _____ Current Calibration Due Date: _____ Accuracy Adjustment (Type 1 gage): _____

ACCEPTANCE CRITERIA

☐ **PRIMER COAT DFT** _____ **TO** _____ **MILS** ☐ **TOPCOAT DFT** _____ **TO** _____ **MILS**

☐ **INTERMEDIATE COAT DFT** _____ **TO** _____ **MILS** ☐ **TOTAL SYSTEM DFT** _____ **TO** _____ **MILS**

☐ **STRIPE COAT (for Cleanliness & Holiday QA)**

SPREAD RATE: ☐

Note: Each Spot Measurement = The AVG of Three Gage Readings.

SPOT MEASUREMENT	DFT (Mils) AVG of 3 Gage Readings	Approximate Location
1		
2		
3		
4		
5		
Average:		

Note: Each Spot Measurement = The AVG of Three Gage Readings.

SPOT MEASUREMENT	DFT (Mils) AVG of 3 Gage Readings	Approximate Location
1		
2		
3		
4		
5		
Average:		

Note: Each Spot Measurement = The AVG of Three Gage Readings.

SPOT MEASUREMENT	DFT (Mils) AVG of 3 Gage Readings	Approximate Location
1		
2		
3		
4		
5		
Average:		

Note: Each Spot Measurement = The AVG of Three Gage Readings.

SPOT MEASUREMENT	DFT (Mils) AVG of 3 Gage Readings	Approximate Location
1		
2		
3		
4		
5		
Average:		

Note: Each Spot Measurement = The AVG of Three Gage Readings.

SPOT MEASUREMENT	DFT (Mils) AVG of 3 Gage Readings	Approximate Location
1		
2		
3		
4		
5		
Average:		

Note: Each Spot Measurement = The AVG of Three Gage Readings.

SPOT MEASUREMENT	DFT (Mils) AVG of 3 Gage Readings	Approximate Location
1		
2		
3		
4		
5		
Average:		

HOLIDAY INSP.: SAT ☐ UNSAT ☐ DFT INSP.: SAT ☐ UNSAT ☐ N/A (for stripe coat) ☐

CLEANLINESS INSP.: SAT ☐ UNSAT ☐ CHLORIDE/CONDUCTIVITY INSP.: SAT ☐ UNSAT ☐

COMMENTS: _____

Contractor (Print): _____ Contractor (Signature): _____ Date/Time: _____

Subcontractor (Print): _____ Subcontractor (Signature): _____ Date/Time: _____

Govt. Insp. (Print): _____ Govt. Insp. (Signature): _____ Date/Time: _____

FY17 Change 1 version

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:59Z
Check the source to verify that this is the current version before use.

SAMPLE FIGURE-8

APPENDIX 7A
QA INSPECTION FORM - WET FILM THICKNESS MEASUREMENTS

SHIP NAME & HULL #: _____ **CONTRACT/TASK ORDER/CLIN/TWD:** _____ **DATE/TIME:** _____

LOCATION: _____ **WORK ITEM:** _____ **PARA. NO.:** _____

(I) ___ **(V)** ___ **(G)** ___ **PRODUCT BEING APPLIED:** _____

REQ'T DOCUMENT: _____ **/FY:** _____ **SQFT OF AREA PRESERVED:** _____ **PARTIAL AREA:** _____ **/ FINAL:** ___
(NSTM 631, 634, PPI, NSI 005-32 FY)

MAINTAIN SEPARATE LOG FOR EACH AREA/LOCATION, PREPARED OR PAINTED SURFACE. WHEN AN AREA IS DIVIDED INTO SEPARATE SECTIONS, MAINTAIN A SEPARATE LOG FOR EACH SECTION.

NOTE #1 FOR ANY UNSAT CONDITION FOUND, PROVIDE THE TECHNICAL ADJUDICATION AND CORRECTIVE ACTION TAKEN IN THE COMMENTS BLOCK WHERE REQUIRED IN LIEU OF DFT.
NOTE #2 IF SPACES ARE NOT APPLICABLE, INSERT N/A. UNUSED SECTIONS SHALL BE CROSSED OUT AND MARKED N/A.

Indicate Coating System Sequence

_____Prime Coat _____Intermediate Coat (if applicable) _____Topcoat
_____Stripe Coat (if applicable) _____Stripe Coat (if applicable) _____Other Coat (specify) (_____)

METALLIC SURFACES
2 SPOT READINGS PER 1000 SQFT:
0 - 1000 SQFT = 2 SPOTS REQUIRED
1001 - 2000 SQFT = 4 SPOTS REQUIRED

NON - METALLIC SURFACES
0 - 100 SQFT = 5 SPOTS REQUIRED
101 - 200 SQFT = 10 SPOTS REQUIRED
201 - 1000 SQFT = 15 SPOTS REQUIRED
> 1000 SQFT = 5 SPOTS REQUIRED PER 1000 SQFT AREA

WFT Measurement #	Location of Readings	WFT Measurement Reading
1		
2		
3		
4		
5		
6		
7		
8		
9		
10		
11		
12		
13		
14		
15		
16		
17		
18		
19		
20		

COMMENTS: _____

Contractor (Print): _____ Contractor (Signature): _____ Date/Time: _____

Subcontractor (Print): _____ Subcontractor (Signature): _____ Date/Time: _____

Govt. Insp. (Print): _____ Govt. Insp. (Signature): _____ Date/Time: _____

FY17 Change 1 version

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:59Z
Check the source to verify that this is the current version before use.

SAMPLE FIGURE 9

APPENDIX 8
COATINGS APPLICATION PRODUCT SUMMARY (CAPS) SHEET

I. **GENERAL:** **DATE:**

SHIP	Contract/Task Order/CLIN/TWD	Work Item	Surface to be coated:

TECHNICAL STANDARDS **SURFACE PREPARATION**

Standard Item 009-32 ☐		FY:	SSPC-SP-10/NACE NO. 2 ☐	Profile Min ____	Max ____
	Table and Line(s):	Column:	SSPC-SP-12/NACE NO. 5 ☐	Profile Min ____	Max ____
Surface Prep -		A	SSPC-SP-11 ☐	Profile Min ____	Max ____
	Table and Line(s):	Column(s):	SSPC-SP-11 (inaccessible area) ☐	Profile Min ____	Max ____
Coating -			Other (specify) ☐	Profile Min ____	Max ____

SCOPE OF PRESERVATION: **COATINGS CONTRACTOR:**

Standard Preservation ☐
Touch up ☐
☐
Other (address below) ☐

Prime Contractor: _____
_____
Subcontractor/Applicator: _____
_____
Contractor (Name / Phone #)
_____/_____

II. **PROPERTIES:**

Coating Mfr.	Generic Description	Product Designation	Curing Agent	Mix Ratio	Pot Life @ °F	Induct Time	% Vol Solids	VOC's IAW F-718	Flash Point	Shelf Life

III. **APPLICATION:**

Product Designation / Coating Step	*	Color	Application Method	Wet Film Thickness Mils		Dry Film Thickness Mils		Environmental Limitations: Surface Temp (°F)		Ambient Temp (°F)		% Rel Humidity		For Recoat/Handle/Immersion times, temperatures and %RH see ASTM F-718 sheet
			**	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	SUBMIT ASTM F-718 SHEETS WITH CAP SHEET SUBMITTAL
														NOTE: Refer to 009-32 para 3.1.13 if ASTM F-718 sheet data and 009-32 data conflict.

* P= Prime coat, S= Stripe coat, I= Intermediate coat, T= Top coat, N= Nonskid, TA= Tack coat, C= Color topping coat.
** Denote method used to apply product to MAJORITY of the area (airless spray, plural spray, roller, all brush, etc.).

COMMENTS:

FY17 Change 1 version

End of DI-MISC-82120

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:59Z
Check the source to verify that this is the current version before use.