PPP-T-360a

August 1, 1962

SUPERSEDING
Int. Fed Spec. PPP-T-00360 (Army-Ord)
January 11, 1962

FEDERAL SPECIFICATION

TIME MEASURING INSTRUMENTS: PACKAGING OF

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE

1.1 This specification covers the packaging, packing, and marking of time measuring instruments for each level of protection

2. APPLICABLE SPECIFICATIONS AND STANDARDS

2.1 The following specifications and standards, of the issues in effect on date of invitation for bids, form a part of this specification to the extent specified herein.

Federal Specifications:

UU-P-558—Paper, Wrapping, Tissue.
PPP-B-566—Boxes, Folding, Paperboard.
PPP-B-576—Box, Wood, Cleated, Veneer, Paper Overlaid
PPP-B-585—Boxes, Wood, Wirebound.
PPP-B-591—Boxes, Fiberboard, Wood-Cleated.
PPP-B-601—Boxes, Wood, Cleated-Plywood.
PPP-B-621—Boxes, Wood, Nailed and Lock-Corner
PPP-B-636—Box, Fiberboard
PPP-B-640—Boxes, Fiberboard, Corrugated, Triple Wall.
PPP-B-676—Boxes, Set-Up Paperboard.
PPP-C-843—Cushioning Material, Cellulosic.
PPP-P-291 — Paperboard, Wrapping, Cushioning.
PPP-T-45—Tape, Gummed, Paper, Reinforced
PPP-T-76 — Tape, Pressure - Sensitive Adhesive, Paper, Water Resistant, (for Carton Sealing)
PPP-T-97 — Tape, Pressure - Sensitive Adhesive, Filament Reinforced.

Federal Standards:

Fed Std No 102—Preservation, Packaging and Packing Levels
Fed Std No 123—Marking for Domestic Shipment (Civilian Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications, Standards, and Handbooks and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U. S Government Printing Office, Washington 25, D C

(Single copies of this specification and other product specifications required by activities outside the Federal Government for bidding purposes are available without charge at the General Services Administration Regional Offices in Boston, New York, Washington, D C Atlanta, Chicago, Kansas City, Mo., Dallas, Denver, San Francisco, and Auburn, Wash.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications, Standards, and Handbooks from established distribution points in their agencies.)

Military Specifications:

MIL-P-116—Preservation, Methods Of.

FSC PACK

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:50Z
Check the source to verify that this is the current version before use.

MIL-B-117—Bags, Interior Packaging.
MIL-B-3106 Board, Composition, Water-Resistant, Solid (for Filler and Cushioning Pads)
MIL-R-5001—Rubber Latex Foam Sponge.
MIL-R-6130—Rubber, Cellular, Chemically Blown
MIL-C-7769 — Cushioning Material, Bound Fiber.

MIL-P-13988—Paper, Lens, Tissue, Antitarnish, Wrapping
MIL-M-19590—Marking of Commodities and Containers to Indicate Radioactive Material
MIL-R-20092—Rubber Sheets and Molded Shapes, Cellular, Synthetic, Exploded Cell (Foamed Latex)

Military Standards

MIL-STD-105 — Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129—Marking for Shipment and Storage.

(Copies of Military Specifications and Standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Time measuring instrument groupings Time measuring instruments have been segregated into groups according to the packaging and packing required, as specified in table I Items marked Group Z shall be packaged and packed as specified in the applicable commodity specification, drawing or purchase document.

3.2 Materials and methods. The materials, methods and procedures used in the packaging of time measuring instruments shall be in accordance with this specification.

3.2.1 *Preproduction pack.* When specified, prior to quantity production, a preproduction sample packaged and packed as for shipment shall be subjected to the examinations and tests of section 4 and shall be approved by the Government (see 6.2)

3.3 Size of containers. Interior packages and exterior containers shall be of minimum size that will provide adequate protection to the contents

3.4 Cleaning. The exterior surfaces of all time measuring instruments shall be cleaned so as to be free from dirt, smudges, fingerprints and other foreign substances in accordance with Process C-1 of MIL-P-116.

3.5 Drying. Immediately after cleaning, time measuring instruments shall be dried thoroughly in accordance with any procedure specified in MIL-P-116 that will not damage the items

3.6 Cushioning and cushioning materials. Time measuring instruments shall be cushioned, as required, to prevent damage to the instruments as determined by the criteria of MIL-P-116, and to prevent puncture or tearing of the barrier materials utilized in packaging Excessive use of cushioning within the unit package shall be avoided since an unnecessary increase in tare weight and cube will otherwise result The performance requirements of MIL-P-116 shall govern the amount of cushioning material used Excelsior, shredded newspaper and similar material which have not been chemically refined for noncorrosiveness are unacceptable for interior packaging Cushioning material used within the unit package shall conform to PPP-C-843, PPP-P-291, MIL-B-3106, MIL-R-5001, MIL-R-6130, MIL-C-7769 or MIL-R-20092, except that additional types of cushioning materials may be used within the unit package provided they meet the neutrality requirements of packaging and cushioning material specified in MIL-P-116

3.7 Radioactive treated items. WARNING —The packaged or packed quantity of time measuring instruments containing radioactive material shall be limited to the safe level

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:50Z
Check the source to verify that this is the current version before use.

of radiation applicable to the mode of transportation.

3.8 **Package groupings.** Time measuring instruments shall be packaged and packed in accordance with the requirements of the packaging group applicable Unless otherwise specified, paragraphs 3.2 through 3.7 are applicable for the packaging required for each group.

TABLE I

Nomenclature	Packaging group
Chronometer, Make Break Circuit	Z*
Chronometer, Break Circuit, M-1	Z*
Chronometer, Ships	Z*
Chronometer Watches, Gimbaled	Z*
Clock, Alarm (General Purpose)	3
Clock, Aircraft	3
Clocks, Boat and Deck	4
Clocks, Floor, Shelf and Wall (Synchronous Motor)	4
Clocks, Interval Timer	Z*
Clock, Message Center	Z*
Clocks, Pendulum	Z*
Clocks, Portable, Watchmen's	Z*
Clock-System, Electric, Equipment For	Z*
Clocks, Small with Second Hand	2
Clocks Wall, Mechanical	4
Counter Assembly, Hour Meter	3
Elapsed Time Indicator	3
Hour Meter	3
Meter, Time	3
Meter, Time Space Totalizing	3
Meter, Time Totalizing	3
Meter, Time Totalizing Operational Use, Electric	Z*
Meter, Time Totalizing (Indicator, Elapsed Time)	3
Meters, Time Totalizing 380 to 420 Cycle	3
Repeat Cycle Timer	3
Time Recorders	Z*
Time Stamps	Z*
Timer, Bombing	Z*
Timer, Engine Overtemperature	3
Timer Interval	3
Timer, Interval, Electric, FN-4	3
Timer, Interval, Electric, Automatic, Photographic, C-1B	Z*
Timer, Interval, Spring Driven, Photographic	Z*
Timer, Sequential	3
Timer, Shutter, Speed	Z*
Timer, Stop Watch, Automatic Astronomic Observation	Z*
Timer-Tone, Generator	Z*
Timing Unit, ML 390	Z*
Watches, Chronometer	Z*
Watches, Navigation, Pocket and Stop	2
Watches, Wrist (except Submersible)	1
Watches, Wrist, Submersible, Non-Magnetic	Z*
Watchmen's Report Systems	Z*

*See paragraph 3.1

3.9 **Group I packaging and packing.**

3.9.1 *Level A packaging.*

3.9.1.1 *Unit packaging.* Each wristwatch shall be packaged as specified herein. Preservation shall be in accordance with MIL-P-116, method III.

3.9.1.1.1 *Wrapping.* The watch shall be wrapped with two thicknesses of tissue paper conforming to MIL-P-13988 or UU-P-553, type II The wrist strap shall be wrapped around the watch and the watch cushioned as specified in 3.6.

3.9.1.1.2 *Paperboard box.* Each watch, wrapped as specified in 3.9.1.1.1 and cushioned as specified in 3.6, shall be packaged in a paperboard box conforming to type I or IV of PPP-B-676 or style III or VIII of PPP-B-566 The box shall be closed as specified in the appendix to the applicable box specification.

3.9.1.1.3 *Documents.* Operating instructions, publications, or manuals, if required by the commodity specification, contract, or order, shall be placed in the paperboard box with the cushioned watch.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:50Z
Check the source to verify that this is the current version before use.

3.9.1.1.4 *Intermediate packaging* Unless otherwise specified, 10 unit packaged watches containing the same stock number shall be further packaged in a fiberboard box conforming to class 2 compliance symbol W5c, any style of PPP-B-636 Each fiberboard box shall be closed with pressure sensitive tape as specified in the appendix to the box specification, except that the tape shall conform to PPP-T-76 The intermediate package may be used as the domestic shipping container when the total quantity to be shipped to one destination is equal to or less than the specified intermediate quantity

3.9.2 *Level B packaging (civil agency procurement).* Level B packaging shall be accomplished in accordance with 3 9 1

3.9.3 *Level C packaging* Preservation and packaging shall be such as to afford protection against corrosion, deterioration and damage during direct shipment from the supply source to the first receiving activity for immediate use or for controlled humidity storage

3.9.4 *Level A packing* Intermediate packages containing watches of the same stock number shall be packed in a shipping container conforming to one of the following specifications at the option of the contractor

PPP-B-636	Class 2 V3c any style
PPP-B-640	Class 2
PPP-B-576	Class 2
PPP-B-591	Overseas type
PPP-B-585	Class 3
PPP-B-601	Overseas type
PPP-B-621	Class 2

Selection shall be made, when practicable, from the upper part of the containers listed above Heavier containers are listed in the lower part of the column and shall be selected only when the lighter weight container is not available for use

3.9.4 1 *Closure and strapping.* Closure and strapping shall be in accordance with the appendix of the applicable specification, except that a fiberboard shipping container shall be reinforced with filament tape conforming to type IV of PPP-T-97 The tape shall be applied as specified in the tape specification

3.9.4.2 *Gross weight and quantity limitation* Except for watches containing radioactive material the gross weight of shipping containers, other than fiberboard boxes conforming to PPP-B-636, snall not exceed 200 pounds The gross weight of fiberboard boxes conforming to PPP-B-636 shall not exceed 70 pounds The quantity of unit packaged watches per shipping container shall not exceed 500

3.9.5 *Level B packing* Intermediate packages containing watches of the same stock number shall be packed in a fiberboard box conforming to class 1, type I any style of PPP-B-636 Closure of the fiberboard box shall be as specified in the appendix to the box specification Alternatively, closure of fiberboard boxes may be by 3-inch tape conforming to PPP-T-45 applied to the top and bottom seams The tape shall extend over the ends not less than 2-1/2 inches If the end panel is less than 2-1 2 inches in depth the tape shall extend the full depth of the end panel If the bottom of the fiberboard box is closed with staples or adhesive (or a style OPF fiberboard box is used) only a single piece of tape on the seam is required

3.9.6 *Level C packing* Packing shall be such as to afford protection against damage during direct shipment from the supply source to the first receiving activity in a manner to insure carrier acceptance Containers shall be in accordance with carrier rules or regulations applicable to the mode of transportation.

3.10 Group 2 packaging and packing.

3.10.1 *Level A packaging.*

3.10.1.1 *Unit packaging* Each item shall

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:50Z
Check the source to verify that this is the current version before use.

be packaged as specified herein Preservation shall be in accordance with MIL-P-116, method 1A-8

3.10.1.2 *Wrapping* The item shall be wrapped with two thicknesses of tissue paper conforming to MIL-P-13988 or UU-P-553, type II The item shall be cushioned as specified in 3 6

3.10.1.3 *Water-vaporproof bag* The cushioned item shall be placed in a water-vaporproof bag conforming to type II, class e of MIL-B-117 The bag shall be heat sealed in such a manner as to pass the heat seal and quick leak tests of MIL-P-116 Air shall be extracted from the bag prior to final closure.

3.10.1.4 *Paperboard box* Each item, bagged as specified in 3 10 1 3, shall be packaged in a paperboard box conforming to type I or IV of PPP-B-676 or style II or VIII of PPP-B-566 The box shall be closed as specified in the appendix to the applicable box specification

(a) When a shock absorber and leather chain accompany an item, the shock absorber shall be positioned on the item prior to unit packaging and the leather chain shall be inserted in the paperboard box with the water-vaporproof bag

3.10.1.5 *Documents* Operating instructions, publications, or manuals, if required by the commodity specification, contract, or order, shall be placed in the paperboard box with the bagged item

3.10.1.6 *Intermediate packaging* Intermediate packaging shall be as specified in 3 9 1 1 4

3.10.2 *Level B packaging (civil agency procurement).* Level B packaging shall be accomplished in accordance with 3 10 1.

3.10.3 *Level C packaging.* Preservation and packaging shall be such as to afford protection against corrosion, deterioration, and damage during direct shipment from the supply source to the first receiving activity for immediate use or for controlled humidity storage

3.10 1 *Packing* Packing for each level of protection shall be as specified in 3 9 4 to 3 9 6 inclusive The use of the intermediate container as a shipping container shall be as specified in 3 9 1.1 4

3.11 Group 3 packaging and packing.

3.11.1 *Unit packaging* Packaging for each level of protection shall be as specified in 3 10 1 to 3 10.3 inclusive, except as follows:

(a) The water-vaporproof bag shall conform to type I, class e of MIL-B-117.

(b) Cushioned items that still contain projections and sharp corners that may damage the water-vaporproof bag shall be completely wrapped with single face corrugated paperboard conforming to PPP-P-291, class I, type I The wrap shall be secured with pressure-sensitive tape conforming to PPP-T-76

(c) The required mounting hardware, keys or similar items shall be placed in an envelope of minimum size. The envelope shall be placed in the paperboard box with the bagged item

3.11.2 *Packing.* Packing for each level of protection shall be as specified in 3.9 4 to 3 9 6 inclusive The use of the intermediate container as a shipping container shall be as specified in 3.9 1.1 4

3 12 Group 4 packaging and packing

3.12.1 *Level A packaging.*

3.12.1.1 *Unit packaging* Each item shall be packaged as specified herein. Preservation shall be in accordance with MIL-P-116, method IA-8.

3.12.1.2 *Securing cords.* When a cord ac-

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:50Z
Check the source to verify that this is the current version before use.

companies an item, the cord shall be coiled and secured to the back of the item with pressure-sensitive tape conforming to PPP-T-76

3.12.1.3 *Wrapping* The item shall be wrapped with two thicknesses of tissue paper conforming to MIL-P-13988 or UU-P-553, type II The item shall be cushioned, as specified in 3 6

3.12.1.4 *Water-vaporproof bag* The cushioned item shall be placed in a water-vaporproof bag conforming to type I, class e of MIL-B-117 The bag shall be heat sealed in such a manner as to pass the heat seal and quick leak tests of MIL-P-116 Air shall be extracted from the bag prior to final closure

3.12.1.5 *Fiberboard box.* Each bagged item shall be packaged in a fiberboard box conforming to PPP-B-636, class 2, W5c Internal cushioning or die cut inner forms shall be provided within the fiberboard box to prevent excessive movement and to prevent the possibility of damage during transportation handling or storage Closure of the fiberboard box shall be as specified in the appendix to the box specification

3.12.2 *Level B packaging (civil agency procurement)*

3.12.2.1 *Unit packaging.* Packaging shall be as specified in 3 12.1, except as specified herein Preservation shall be in accordance with MIL-P-116, Method IC-5

(a) The water-vaporproof bag is not required

3.12.3 *Level C packaging* Preservation and packaging shall be such as to afford protection against corrosion, deterioration, and damage during direct shipment from the supply source to the first receiving activity for immediate use or for controlled humidity storage

3.12.4 *Packing.* Packing for each level of protection shall be as specified in 3 9 4 to 3 9 6 inclusive except as follows·

(a.) Intermediate packaging is not required

3.13 Marking

3.13.1 *Military shipments* In addition to any special marking required by the contract or order, interior packages and exterior shipping containers shall be marked in accordance with MIL-STD-129, and 3 13 3 and 3 13 1 except that·

(a) When the unit package consists of bag and container, the identification data shall be applied to each bag and container

(b) On the shipping container the nomenclature and manfacturer's name shall be omitted

3.12.2 *Civil agency shipments.* Marking of interior packages and exterior shipping containers shall be in accordance with Fed Std No 123 and 3 13 3 and 3 13 3 1

3.13.3 *Radioactive material* Time measuring instruments which contain radioactive luminous compounds other than radium shall be marked in accordance with MIL-STD-129 and MIL-M-19590

3.13.3.1 *Special marking* Unit packages, intermediate packages and shipping containers shall be marked as follows

"Radioactive materials fogs film DO NOT STORE WITHIN 25 FEET OF FILM"

4. SAMPLING, INSPECTION, AND TEST PROCEDURES

4.1 The supplier is responsible for the performance of all inspection requirements as specified herein Except as otherwise specified, the supplier may utilize his own or any other inspection facilities and services acceptable to the Government. Inspection records of the examinations and tests shall be kept complete and available to the Govern-

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:50Z
Check the source to verify that this is the current version before use.

ment as specified in the contract or order. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements

4.1.1 *Contractor's written description.* The contractor shall provide and maintain an effective packaging and packing inspection system acceptable to the Government A current written description of the system shall be submitted to the contracting officer prior to initiation of production packaging and packing The written description shall be considered acceptable when, as a minimum it provides the quality assurance required in this specification and other applicable documents The contractor's written system shall include, as a minimum the proposed system of inspection for the following

(a) Cleaning — process, materials and equipment

(b) Drying—procedure and equipment

(c) Packaging — method sizes of all wraps, bags, containers, etc., and equipment

(d) Packing—materials, procedure and equipment

The contractor shall notify the Government of and obtain approval for any change to his written inspection procedure that affects the degree of assurance required by this specification and documents referenced herein.

4.2 **Government verification.** All quality assurance operations performed by the contractor will be subject to Government verification at unscheduled intervals Verification shall consist of (a) surveillance of the operations to determine whether the practices, methods, and procedures of the written plan are being properly applied, and (b) Government packaging and packing inspection to measure quality of the packs offered for acceptance Deviations from the prescribed or agreed-upon procedures, or instances of poor practices, shall be immediately called to the attention of the contractor Failure of the contractor to promptly correct deficiencies discovered shall be cause for suspension of acceptance until corrections have been made. To avoid interference with operations, the contractor shall designate a responsible official or officials to whom the Government inspector will report such instances.

4.3 **Preproduction sample** When specified (see 3.2.1 and 6.2), the contractor shall conduct inspection on one completed package, packed for shipment to ascertain that the cleaning, drying, preservation, packaging, packing, and marking conforms to this specification The preproduction sample will not be required when such a pack has previously been inspected and accepted for the same method for a similar item by the same contractor, and satisfactory evidence can be furnished to the Government that the items have been prepared identically with the previously approved pack Preproduction inspection shall be repeated when changes in preservation and packing materials, processes, or designs are made

4.3.1 *Preproduction sample inspection.* When specified (see 3.2.1 and 6.2) a complete pack of the item shall be subjected to the examinations and tests herein Upon completion of the rough handling tests, the item shall be inspected, as applicable, in accordance with the initial acceptance limits of the item specification to determine freedom from operational malfunction.

4.3.1.1 A preproduction test will not be required when level C packaging and packing protection is specified.

4.3.2 *Preproduction pack rejection* Should the preproduction pack fail to pass the test for Government approval, the contractor shall make the necessary corrections and resubmit a sample for Government approval

4.4. **Inspection lot.** All times measuring instruments of the same packaging group

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:50Z
Check the source to verify that this is the current version before use.

(see 3 6) offered for delivery at one time shall be considered a lot for purposes of sampling and inspection

4.4.1 Defective units and lots shall be processed as specified in MIL-STD-105

4.5 Sampling

4.5.1 *Sampling for visual examination.* Unit packages, intermediate packages and shipping containers shall be selected in accordance with MIL-STD-105 at inspection level I The following AQL's shall apply: Major 1.5 percent, Minor 4 0 percent

4.5.2 *Sampling for tests* Unit packages shall be selected in accordance with MIL-STD-105 at inspection level L-7 for the tests of 4 7.2 The AQL shall be 4 0 defective for combined test failures

4.5.3 *Examination and tests for radiation* The radiation level at any surface of all shipping containers packed with time measuring instruments containing radioactive material shall not exceed the radioactive limits as specified in the applicable commodity specification and the regulations applicable to the mode of transportation

(a) Any shipping container which exceeds the permitted radiation limit shall be rejected

(b) Any shipping container which does not display appropriate radiation warning labels shall be rejected

(c) Any unit or intermediate package which does not display appropriate radiation warning labels shall be rejected.

4.6 Inspection

4.6.1 *Classification of defects. Visual* examination for defects established in Table II shall apply to samples of interior packages or exterior containers

TABLE II *Classification of defects*

Categories	Defects
Critical	
1	See paragraph 4 5 3
Major	
101	Exterior surfaces of time measuring instruments not clean
102	Exterior surfaces of time measuring instruments not dry
103	Non-neutral material used as cushioning
104	Incorrect method of unit packaging
105	Unit packages of different stock numbers in intermediate package
106	Cushioning inadequate to prevent excessive movement of item within carton
107	Closure, strapping, or banding of containers not as specified
108	Required operating instructions, publications or manuals missing
109	Water-vaporproof bag damaged, air not extracted before final clearance
110	Required hardware missing
111	Markings illegible, incorrect missing not conforming to requirements specified herein
Minor	
201	Gross weight and quantity limitations exceeded
202	Wrist strap not wrapped around watch
203	Cords not coiled or secured to back of item
204	Shock absorber and leather chain not positioned as specified
205	Containers not conforming to applicable specification requirements
206	Required hardware not packaged as specified
207	Not wrapped as specified

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:50Z
Check the source to verify that this is the current version before use.

4.7 **Test procedures.**

4.7.1 *Rough handling test* The preproduction pack only shall be subjected to the rough handling test in accordance with MIL-P-116

4.7.2 *Unit packaging tests* Each sample unit package shall be subjected to the tests as applicable to the methods of preservation specified herein

5 PREPARATION FOR DELIVERY

There are no applicable requirements

6 NOTES

6.1 **Intended use** It is intended that this specification be used for reference in section 5 of commodity specifications or direct reference in contracts or orders Those items marked group Z in table I will be included within this specification by revision to the specification at a later date (See 3.1)

6.2 Ordering data Procurement documents should specify the following

(a) Title number, and date of this specification

(b) Selections of applicable levels of packaging and packing or marking requirements if other than those required by 3.6

(c) Intermediate package quantity and exterior pack quantity when applicable

(1) Level B preservation and packing is intended to provide economical but limited protection and should be specified only when it is determined the time measuring instrument will be held in covered storage aproximately 6 months from date of initial packaging (See 3.9.2, 3.10.2 and 3.12.2)

(d) Applicable stock number.

(e) Preproduction pack, when required (see 3.2.1)

6.3 **Levels of protection** For civil agency procurements the levels of protection (packaging and packing classification) shall be as defined in Fed Std No 102

6.4 **Supersession data** This specification includes the requirements of MIL-W-11446 dated 29 November 1957 and the section 5 of the following specifications

GG-C-447	MIL-C-856	MIL-W-3818
GG-C-466	MIL-C-1194	MIL-C-3956
GG-S-761	MIL-C-2512	MIL-W-5492
MIL-W-5605	MIL-C-7939	MIL-C-25917
MIL-C-6499	MIL-W-13725	MIL-C-25942
MIL-W-6510	MIL-W-13741	MIL-C-26349
MIL-C-7047	MIL-T-25445	MIL-T-26791
MIL-M-7793	MIL-C-25885	MIL-C-27298

Notice—When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever and the fact that the Government may have formulated furnished, or in any way supplied the said drawings specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation or conveying any rights or permission to manufacture use or sell any patented invention that may in any way be related thereto

MILITARY INTERESTS

Army—O Sig Q

Navy—Sh

Air Force—MAAMA.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:50Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE NAVY

POSTAGE AND FEES PAID
NAVY DEPARTMENT

OFFICIAL BUSINESS

Commanding Officer
Frankford Arsenal
Attn: SMUFA-N1100
Philadelphia, Pa. 19137

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:50Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor involved in the use of the specification in procurement of products for ultimate use by the Department of Defense This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost Comments and the return of this form will be appreciated Fold on lines on reverse side staple in corner and send to preparing activity (as indicated on reverse hereof)

SPECIFICATION

ORGANIZATION (Of submitter) | CITY AND STATE

CONTRACT NO | QUANTITY OF ITEM PROCURED | DOLLAR AMOUNT
$

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1 HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A GIVE PARAGRAPH NUMBER AND WORDING

B RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2 COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3 IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4 REMARKS (Attach any pertinent data which may be of use in improving this specification If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)

SUBMITTED BY (Printed or typed name and activity) | DATE

DD, FORM 1 APR 63 1426 REPLACES NAVSHIPS FORM 4863, WHICH IS OBSOLETE PLATE NO 15419

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:50Z
Check the source to verify that this is the current version before use.