MIL-B-63299A(AR)
AMENDMENT 4
17 September 1985
SUPERSEDING
AMENDMENT 3
24 January 1985

MILITARY SPECIFICATION

BODY ASSEMBLY
MINE, ANTI-PERSONNEL: HE, M74

This Amendment forms a part of Military Specification MIL-B-63299A(AR), dated 15 December 1983, and is approved for use by the US Army Armament, Munitions and Chemical Command is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

2.1.2, Drawings: Delete "(See 6.7)" and substitute "(See 6.8)".

PRODUCT AND PACKAGING DRAWING: Delete "... DRAWING" and substitute "...DRAWINGS".

PAGE 4

* 3.5.2: Delete "...a torque of 35 inch pounds (in-lbs) min. without ..." and substitute "...a torque of 18 ± 2 inch pounds (in-lbs) min. without ..."

3.6d: Delete "Presence of shorting eyelet." and substitute "Presence of detonator and micropiston actuator flex cable shunts."

PAGE 8

Delete "Insert (Dwg. 9292629)" and substitute "Insert, Bushing (Dwg. 9381375)".

PAGE 18

4.4.2.4: Delete present Page 18 and substitute included Page 18.

PAGE 53

4.4.2.34, Critical 4: Delete "Shorting eyelet missing" and substitute "Flex cable shunts missing or improper".

FSC 1345

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:35Z
Check the source to verify that this is the current version before use.

PAGE 54

4.4.2.34: Delete Major 109 in its entirety.

PAGE 56

4.4.2.35 Cont'd: Add "Major 110, Shim missing or incorrect, 0.40%, 3.2, Visual".

PAGE 62

4.4.2.40:

Criticals 1 thru 4: Delete "0-1".

Critical 2: Delete "(See Note c)" and substitute "(See Note b)".

Critical 4: Delete "(b)".

Major: Delete "RESISTANCE OF EED's AFTER T-V, (a)" and substitute "RESISTANCE AFTER T-V".

PERFORMANCE/FUNCTION: Delete "(b)".

NOTES: Delete (a), (b) and (c) in their entirety and substitute "(a) See sheet 2; (b) Acoustic sensor or adequate alternate shall be used for monitoring".

PAGE 63

Add Page 63A, 4.4.2.41 included herein.

PAGE 65

4.5.1, line 30: Delete "DRSMC-QAT-I(D)" and substitute "AMSMC-QAT-I(D)".

PAGE 66

4.5.1 CONT., line 3: Delete "DRSMC-QAT-M(D)" and substitute "AMSMC-QAT-M(D)".

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:35Z
Check the source to verify that this is the current version before use.

PAGE 73

6.3, line 3: Delete "DRSMC-QAT-I(D)" and substitute "AMSMC-QAT-I(D)".

6.4, line 3: Delete "DRSMC-QAT-M(D)" and substitute "AMSMC-QAT-M(D)".

6.6, line 4: Delete "DRSMC-QAT-M(D)" and substitute "AMSMC-QAT-M(D)".

The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:35Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-B-63299A(AR)
AMENDMENT 4

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.4	Insert, Bushing	1 OF 1	9381375
			NEXT HIGHER ASSEMBLY: 9292680

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Length		0.65%	3.2	Gage
202	Outside diameter		0.65%	3.2	Gage
203	Diameter of hole		0.65%	3.2	Gage
204	Location of hole		0.65%	3.2	Gage
205	Evidence of poor workmanship		0.65%	3.11	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:35Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.41	Shim, Shorting Bar				9381374
					NEXT HIGHER ASSEMBLY 9292680
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Length		0.65%	3.2	Gage
202	Length of legs, 2 places		0.65%	3.2	Gage
203	Width		0.65%	3.2	Gage
204	Diameter of hole		0.65%	3.2	Gage
205	Evidence of poor workmanship		0.65%	3.11	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:35Z
Check the source to verify that this is the current version before use.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1345-A352)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:35Z
Check the source to verify that this is the current version before use.