INCH-POUND

MIL-C-70628 (AR)
AMENDMENT 1

23 FEBRUARY 1990

MILITARY SPECIFICATION

CONTAINER, AMMUNITION, PA108 ASSEMBLY

This amendment forms a part of Military Specification MIL-C-70628(AR), dated 9 March 1987, and is approved for use by the U.S. Army Armament, Munitions and Chemical Command and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 14

4.5.4.1, Delete in its entirety and substitute:

"4.5.4.1 Vacuum method. The assembled container shall be tested for leakage by immersing the closed container, in a vacuum vessel, to a depth of at least one inch below the surface of the water. The air pressure in the vessel shall be lowered such that it is between 3 and 4 psi below ambient pressure and maintained at this point for the duration of the test. Observation for leakage of air from the interior of the container assembly shall be made during the period of lowering pressure and for a minimum of 15 seconds after the 3 psi pressure differential has been reached."

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1305-AC73)

AMSC N/A

FSC 1305

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:49Z
Check the source to verify that this is the current version before use.