MILITARY SPECIFICATION

TEST FACILITIES KIT MK-980( )/PPS-5

This amendment forms a part of Military Specification MIL-T-55655A(EL), 24 January 1972, and is approved for use by all Departments and Agencies of the Department of Defense

PAGE 6

3.7 Service Conditions. - In Table I, delete "Air Seal Test."

3.7.1 Temperature/Altitude. - Delete

3.7.2 Vibration. -

Line 5 - Delete "Double amplitude" and substitute "Total excursion of the applied vibration should not be less than."

PAGE 9

4.3 First Article Inspection. -

Delete Table II and substitute the following table:

Source: https://assist.dla.mil -- Downloaded: 202610-22T23:49Z
Check the source to verify that this is the current version before use.

TABLE II- FIRST ARTICLE/GROUP C INSPECTION, ORDER OF TESTING

Inspection (Note 1)	Test Para.	Number of samples					
		One	Two		Three		
			Unit 1	Unit 2	Unit 1	Unit 2	Unit 3
Non-damaging (Note 2)							
Preconditioning Bounce	4.6	1	1	1	1	1	1
Temperature	4.9	3	2		2		
Low							
High							
Altitude (elevation)	4.9	4	3		3		
Leakage (immersion)	4.9	2 & 12		2 &6		2 & 5	
Electromagnetic Compatability	4.10	5	4				2
Potentially Damaging							
Humidity (Moisture-Resistance) (Note 3)	4.9	6	6			3	
Shock (Ballistic) (Panel Assembly only)	4.9	7	5		5		
Shock (Ballistic) Case only, with dummy load)	4.9	8		3		4	
Shock, Drop (Case only, with dummy load)	4.9	9		4			3
Fungus (Note 3)	4.9	10		5	4		
Vibration	4.9.2	11	7				4

NOTE 1: Other First Article inpsection may precede, follow, or be interspersed between the non-damaging tests.

NOTE 2: Except for Preconditioning Bounce, the order of non-damaging tests and the choice of which units are subjected to the non-damaging tests may be varied if convenient.

NOTE 3: The equipment shall be thoroughly washed, cleaned, dried, and refurbished, if necessary, before proceeding with subsequent tests.

Source: https://assist.dla.mil -- Downloaded: 202610-22T23:49Z
Check the source to verify that this is the current version before use.

PAGE 10

4.5.1 Group A inspection. -

Line 13 - Delete "....except that the air-seal test shall be last."

Table IIIA - Delete "Lot Information" and substitute "Lot Formation."

PAGE 14

4.9.1 Temperature/Altitude tests. - Delete.

PAGE 15

4.9.1 Temperature/Altitude tests. - Delete Table V.

Custodian:
ARMY-EL

Preparing Activity
ARMY-EL

Project Number 6625-A566

Source: https://assist.dla.mil -- Downloaded: 202610-22T23:49Z
Check the source to verify that this is the current version before use.