INCH - POUND

A-A-59682
November 28, 2000

COMMERCIAL ITEM DESCRIPTION

VALVE, INFLATION, 25-PERSON LIFERAFT

The General Services Administration has authorized the use of this commercial item description for all federal agencies.

1. SCOPE. This commercial item description identifies the requirements of the inflation valve for 25-person life rafts.

2. SALIENT CHARACTERISTICS

2.1 Design and construction.

2.1.1 Design: The operation of the valve shall not be dependent on springs.

2.1.2 Operation Gas: Breathable air.

2.1.3 Operation Pressure: 5000 psi (nominal) at 72 degrees Fahrenheit.

2.1.4 Operational Temperature Range: minus 20°F to 160°F.

2.1.5 Required Operational Service Time: Minimum four years before overhaul.

2.1.6 Material: Corrosion resistant characteristics equivalent or better than those offered by Class 316 stainless steel.
2.1.7 Leakage Rate (Maximum): Equivalent to 2.25x10-5 cc/sec when pressurized at 5000 psi using Helium gas without the use of caps or plugs.

2.1.8 Discharge Rate: 99 percent of the cylinder charge in less than 45 seconds, when installed on a 455 cubic inch air cylinder charged to a nominal pressure of 5000 psi.

2.1.9 Safety Relief Device: Actuate at a pressure range between 6225 psi and 7500 psi.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data that may improve this document should be sent to: Commander, Naval Sea Systems Command, SEA 05Q, 2531 Jefferson Davis Hwy., Arlington, VA 22242-5160.

AMSC N/A FSC 4220

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:23Z
Check the source to verify that this is the current version before use.

2.1.10 Actuation Mechanism: Operate with a force of 10 to 40 pounds with a maximum of one inch travel and have an integral safety pin to prevent accidental inflation prior to final installation.

2.1.11 Cylinder Interface: Externally threaded 1 1/16-12UN 2A with one inch total full thread length.

2.1.12 Discharge Port: Externally threaded, .375-18 NPS and configured with a removable anti-recoil fitting which disperses the discharge gas perpendicular to the centerline axis of the fitting in four directions (90 degrees apart). Discharge port shall be equipped with a swivel-type fitting to accommodate the inflation hose.

2.1.13 Adaptability: The valve body is of sufficient material strength and thickness at the cylinder connection to permit machining to modify the 1 1/16-12UN 2A valve thread to fit an air cylinder having a 7/8 inch diameter internally threaded port.

2.1.14 Water-tightness: No evidence of moisture present internally after submergence in a seawater bath to a depth of one (1) foot for a period of 48 hours.

2.1.15 Serviceability: The valve must be serviceable by shop personnel utilizing normal shop tools except for any special bleed-down tools or special disassembly tools required to restore the valve to as new condition.

2.2 Physical characteristics. The required physical characteristics of the valve are:

2.2.1 Weight: Less than 2 lbs.

2.2.2 Volume: Less than 3 cubic inches, not including the lanyard.

2.2.3 Lanyard: Plastic/nylon coated, ten (10) inches in length with an open/close end fitting.

2.2.4 Label: Permanent and indelible manufacturer label which includes contract number and valve serial number.

2.2.5 Serial number: Five (5) digit sequential and non-repeating number beginning at 30000.

3. REGULATORY REQUIREMENTS. The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR).

4. PRODUCT CONFORMANCE PROVISIONS

4.1 Product conformance. The products provided shall meet the salient characteristics of this Commercial Item Description, conform to the producer's own drawings, specifications, standards, and quality assurance practices, and be the same product offered for sale in the commercial marketplace. The Government reserves the right to require proof of such conformance.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:23Z
Check the source to verify that this is the current version before use.

4.2 Market availability. The contractor shall provide evidence that the item has been available commercially for at least five years and is currently being provided on 25-person life rafts manufactured by at least two manufacturers. Commercial items having a failure rate greater than 0.03 percent shall not be considered for purchase. Test methods used for compliance to these requirements where necessary shall be approved commercial standards.

4.3 Documentation. Prospective offerors shall provide a representative valve for submittal along with documentation of conformance to the requirements of this commercial item description.

5. PACKAGING. Preservation, packing and marking shall be as specified in the contract or order.

6. NOTES

6.1 Intended use. This valve is used in conjunction with a 5000 psi (nominal) air charged cylinder as the primary device for automatically inflating the Navy 25-Person Mark 6 Life Raft.

6.2 Ordering data. Acquisition documents specify the following:

a. Title, number, and date of this document.

MILITARY INTERESTS: CIVIL AGENCY COORDINATING ACTIVITIES:
GSA-FSS

CUSTODIANS:
Navy – SH
Army – AV
Air Force - 99

Preparing activity:
NAVY - SH
(Project 4220-0449)

REVIEW ACTIVITIES:
DLA - IS



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:23Z
Check the source to verify that this is the current version before use.