INCH-POUND

A-A-59687
04 June 2001

COMMERCIAL ITEM DESCRIPTION

ROBOT, EXPLOSIVE ORDNANCE DISPOSAL (EOD)

The General Services Administration has authorized the use of this commercial item description for all federal agencies.

1. SCOPE. This commercial item description covers one type of EOD robot for detecting, handling and exploding of surface demolition.

2. SALIENT CHARACTERISTICS.

2.1 Remote Transport System. Must provide a remotely controlled, mobile, all-terrain platform capable of delivering a suite of current EOD special series tools and attachments.

2.2 Operation. Must be operable by no more than two EOD task-qualified personnel of any skill level.

2.3 System control. Must provide operator full control of all system functions at distances up to 100 meters and when inside other structures.

2.4 Imaging capability. Must have an imaging capability that enables the operator to perform reconnaissance and identify devices as far as 10 meters from the platform and use on-board lighting to ensure visibility in all lighting conditions.

2.5 Mobility. Must be air deployable and all required equipment fit within a 17.25 cubic feet space in Internal Slingable Unit (ISU) mobility containers.

2.6 Weight. Total weight must not exceed 375 pounds.

2.7 Electrical firing of explosive devices. Must be capable of meeting the DoD Non-Nuclear Munitions Safety Board standards for electrical firing of explosive devices.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any other data that may improve this document should be sent to: OO-ALC/WM, 6033 Elm Lane, Hill AFB, UT 84056-5819.

FSC 1385

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:23Z
Check the source to verify that this is the current version before use.

2.8 Temperature and weather conditions. Able to operate in all temperature and weather conditions. Temperatures from –15 to 130 degree F.

2.9 Remote control. Must provide a primary and backup remote control capability. Must employ battery-powered platform, batteries should be rechargeable and provide full operation for a period of 1 hour between charges. Must be modular and self-contained, two-man portable, and have capability to use external 120 VAC, 60Hz electricity. Battery chargers for vehicle and command control unit shall be included.

2.10 Firing capability. Must fire one series EOD special tool and five 12-guage shotgun blasts on the same approach without human entry.

2.11 Manuals. Must include complete and accurate operations and repair manual.

2.12 Repair tool kit. Must include repair tool kit that contains all unique tools necessary for repairs of the remote transport system.

2.13 Vehicle. All terrain capability with manipulator arm and gripper shall include crossing 24 inch high grass and/or weeds, loose sand 6 inches deep, mud, gravel/rocks up to 4 inches in diameter, and be able to negotiate the following from a head on position; traverse railroad tracks, 18 inch wide ditches, 12 inch high obstacles (i.e. logs, curbs), climb and descend a flight of stairs with minimum 7 inch risers and 8 inch treads, negotiate (at a minimum) a 35 degree up or down slope, negotiate (at a minimum) a 15 degree side slope.

2.14 Width. Must be able to negotiate aircraft aisles no more than 18 inches wide.

2.15 Turning radius. Must be able to perform 180 degree turn in an aisle no more than 40 inches wide

2.16 Speed. Must have a variable speed with a minimum range of 1 to 12 inches per second.

2.17 Audio. Must have at least a 1-way audio capability.

2.18 Battery. Must have rechargeable battery(s) with capability of 1 hour minimum of full operation between charges.

2.19 Color camera. Must have a minimum of 1 color pan/tilt camera with remote focus, zoom, and iris control.

2.19.1 Black/white camera. Must have a minimum of one (1) black/white camera with wide angle lens, automatic iris, positioned on the manipulator arm to allow operator full view of the gripper when performing tasks.

2.20 Manipulator Arm. The manipulator arm must be able to rotate/pivot shoulder and/or elbow to allow for work 90 degrees to either side of the vehicle platform.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:23Z
Check the source to verify that this is the current version before use.

2.20.1 Reach and lift capability. Must have sufficient reach and lift capability to grip and move (at a minimum) a 15 pound object located up to 2 feet off either side and in front of the vehicle and 12 inches below the ground (in a hole) to 6 feet above the ground.

2.20.2 Gripper. The manipulator arm with the gripper must be able to operate various types of doorknobs, open suitcases, toolboxes, etc., place a minimum of a 15-pound object into a bomb containment vessel

2.21 Shotgun. Must be able to aim and fire the shotgun and other current EOD tools either straight ahead or at 90 degrees to the side of the vehicle platform and from ground level up to 3 feet above the ground without immobilizing or damaging the manipulator arm and/or the vehicle.

2.22 EOD tools. Must be able to use existing EOD tools with minor modifications.

2.23Operational Control Units.

2.23.1 Power supply. Must be operable from rechargeable battery(s) and from a 120 VAC power supply.

2.23.2 Audio/video connectors. Must have audio/video output connectors to allow recording capability.

2.23.3 Audio. Must have at least a 1-way audio from the vehicle capability.

2.23.4 Unit. The unit must be modular and self-contained and be 2-man portable.

2.23.5 Chemical protective equipment. Must be operable while wearing chemical protective equipment.

3. REGULATORY REQUIREMENTS

3.1 Recovered materials. The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR).

4. QUALITY ASSURANCE PROVISIONS

4.1 Quality Conformance. The products provided shall meet the salient characteristics of this Commercial Item Description, conform to the producer’s own drawings, specifications, standards, and quality assurance practices, and be the same product offered for sale in the commercial market. The government reserves the right to require proof of such conformance.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:23Z
Check the source to verify that this is the current version before use.

4.2 Market Acceptability. The following market acceptability criteria are necessary to document the quality of the product to be provided under this CID:

a. The manufacturer of the item must have been producing a product meeting the requirements of this CID for at least 2 years.

5. PACKAGING

5.1 Packaging. Preservation, packing, and marking shall be as specified in the contract or order.

6. NOTES

6.1 Source of Documents.

a. The Code of Federal Regulations (CFR) may be obtained from the Superintendent of Documents, U.S. Government Printing Office, Washington, DC, 20402.

b. TAPPI Standards are available from the Technical Association of the Pulp and Paper Industry, PO box 105113, Atlanta, GA, 30348.

c. ASTM Standards are available from the American Society for Testing and Materials, 100 Barr Harbor Dr., Conshohocken, PA, 19428-2959.

6.2 National Stock Numbers (NSNs). The following is a list of NSNs assigned that correspond to this CID. The list may not be indicative of all possible NSNs associated with the CID.

1385-01-439-0799
1385-01-456-9129

6.3 Ordering data. The contract or order should specify the following:

a. CID document number and revision.

b. Quality conformance provisions.

c. Packaging requirements.

6.4 Key words.

RCT
Remote Controlled Transporter
Bomb Disposal Robot

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:23Z
Check the source to verify that this is the current version before use.

MILITARY INTERESTS:

Custodian:
Air Force – 99

Preparing activity:
Air Force – 70

(Project 1385-0001)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:23Z
Check the source to verify that this is the current version before use.