INCH-POUND

A-A-59695
13 SEPTEMBER 2001

COMMERCIAL ITEM DESCRIPTION

# POWER SUPPLY

The General Services Administration has authorized the use of this commercial item description (CID) for all federal agencies.

1. SCOPE. This CID defines the minimum technical and performance requirements for a power supply used on the AN/FYQ-93 Operational Control Central.

2. SALIENT CHARACTERISTICS.

2.1 Performance Requirements.

2.1.1 Input Voltage. The power supply shall accept an AC input voltage of 85-132VAC/170-265VAC auto-selectable, 47Hz-440Hz.

2.1.2 Efficiency. The power supply shall operate with a minimum efficiency of 70%.

2.1.3 DC Output Controls. The power supply shall include a multi-turn potentiometer for voltage adjustment (4.5-6.3Vdc adj).

2.1.3 Regulated Voltage Output. Line regulation shall be 0.1% for variations from low line to high line and high line to low line. Load regulation shall be 0.1% for load variations from no load to full load and full load to no load. Ripple and noise shall be 10mVRMS, 35 MV peak to peak.

2.1.5 Overshoot. There shall be no overshoot under conditions of power turn-on, turn-off or input power failure.

2.1.6. Overvoltage Protection. The power supply shall include an inverter shutdown type overvoltage protection device.

2.1.6 Overload Protection. An internal current limiting circuit which resets automatically shall be included for overload protection.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data that may improve this document should be sent to: OC-ALC/PK-3, 6038 Aspen Ave. Bldg 1289 SE, Hill AFB, UT 84056-5805

AMSC N/A FSC 6130

DISTRIBUTION STATEMENT A. Approved for public release: distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:24Z
Check the source to verify that this is the current version before use.

2.1.7 Operating Temperature. The power supply shall have an operating temperature range of -40°C to 71°C, with a maximum of 20 minute warm-up for below -30°C.

2.1.8 Storage Temperature. The power supply shall have a storage temperature range from -40°C to 85°C.

2.1.9 Temperature Coefficient. The temperature coefficient shall be 0.025% per degree Celsius.

2.1.10 Cooling. The power supply shall be cooled by forced air via an internal fan.

2.1.11 Humidity. The power supply shall operate in an environment with 5%-95% humidity (non-condensing).

2.1.12. Isolation. Input to output shall be 3000 VRMS, output to chassis shall be 500 VRMS, input to chassis shall be 1500 VRMS.

2.1.12 Output Voltage. The power supply shall have an output voltage of 5VDC and 6VDC (4.5-6.3VDC adjustable).

2.1.13 Output Current. The output current shall be 90A at 71°C, 120A at 60°C, 135A at 50°C, and 150A at 40°C.

2.1.13 Power Rating. The power supply shall be rated for 750 watts of power.

2.1.14 Remote On/Off. Remote on-off shall be TTL compatible (active high).

2.1.15 Remote Sensing. Remote sensing internal circuitry shall allow for 1.2V drop in output leads.

2.1.16 Programmed Voltage. Resistive programming at 1000 ohms/volt ratio. Voltage programming shall be volt per volt.

2.1.17 Thermal Protection. The power supply shall contain an internal thermostat to protect the power supply from overheating. Cycle input power to restore operation.

2.2 Physical Requirements.

2.2.1 Dimensions. The power supply dimensions shall be as follows: Height: 4.75 inches, Width: 5 inches, Depth: 10.37 inches.

2.2.2 Weight. The unpacked weight of the power supply, including all accessories shall not exceed 11 pounds.

2.2.3 Mounting. The power supply shall have one mounting surface with multiple mounting positions.

2.2.4 DC Output Connection Type. The dc output connection shall be bussbar type.

2.3 Safety Agency Approval. The power supply must have the approval of UL1950, CSA950, EN60950, and CE Mark.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:24Z
Check the source to verify that this is the current version before use.

3. REGULATORY PROVISIONS.

3.1 Recoverable materials. In accordance with Section 23.403 of the Federal Acquisition Regulation (FAR), the Federal Government's policy is to acquire items composed of the highest percentage of recoverable materials practicable consistent with maintaining a satisfactory level of competition and without adversely affecting performance requirements or exposing the supplier's employees to undue hazards from the recovered materials.

4. PRODUCT CONFORMANCE:

4.1 Product conformance. The products provided shall meet the salient characteristics of this commercial item description, conform to the producer's own drawings, specifications, standards, and quality assurance practices, and be the same product offered for sale in the commercial market. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter, as may be otherwise provided under the provisions of the contract.

5. PACKAGING.

5.1 Packaging. Preservation, packing, labeling , and marking shall be as specified in the contract or order and shall meet accepted standards for the protection of power supply devices.

6. NOTES.

6.1 Warranty. Required item should include a warranty to cover parts and labor for a minimum of 5 years from the date of delivery.

6.1 Ordering data. The following information should be provided at the time of contract award:

a. CID Number and revision
b. Packaging requirements

6.3. Suggested sources of supply.

a. Lambda, 3055 Del Sol Boulevard, San Diego, CA 92154, Phone (619) 575-4400.

MILITARY INTEREST:

Custodian:
Navy - SH
Army-CR
DLA – GS

CIVIL AGENCY
COORDINATING ACTIVITY:

GSA – FSS

Preparing Activity:
Air Force – 70

Agent:
Air Force – 99

(Project Number 6130-0416)



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:24Z
Check the source to verify that this is the current version before use.