MIL-C-81730 (AS)
7 July 1969
Superseding AS 1646
5 April 1968

MILITARY SPECIFICATION

CARTRIDGE, DELAY, MARK 136 MOD 0

This specification has been approved by the Naval Air Systems Command, Department of the Navy.

1. SCOPE

1.1 This document governs the manufacture, assembly and preparation for delivery of the MARK 136 MOD 0 delay cartridge and the methods of inspection and tests upon which product acceptance will be based.

2. APPLICABLE DOCUMENTS

2.1 The following specifications, standards, drawings and publications, of the issue in effect on date of invitation for bids, form a part of this document to the extent specified herein.

SPECIFICATIONS

Military

MIL-D-21625	Design and Evaluation of Cartridges for Cartridge Actuated Devices
MIL-M-21383	Manganese Delay Composition
MIL-P-116	Preservation, Methods of

FSC 1377

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:01Z
Check the source to verify that this is the current version before use.

MIL-P-20444	Primer, Percussion, M42 Loading, Assembling and Packing
MIL-P-22264	Powders, Ignition, Gasless

STANDARDS

Military

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	Marking for Shipment and Storage

DRAWINGS

Naval Air Systems Command

DL 2519923	Cartridge, Delay, MARK 136 MOD 0, List of Drawings and Specifications
DL 2838169	Test Fixture, Cartridge, Delay, MARK 136 MOD 0

Bureau of Naval Weapons

PL 2518489	Cartridge, Delay Type, Packaging Equipment

Ordnance Corps of the Army

Ordnance Dwg. 8799925	Primer, M42, Assembly and Details

PUBLICATIONS

BUSANDA Instruction 4030.17	Preservation, Packaging, Packing and Marking; Navy Policy for

Bureau of Naval Weapons

WR-43	Preparation of Quality Assurance Provisions

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:01Z
Check the source to verify that this is the current version before use.

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the Contracting Officer.)

2.2 Other publications. The following document forms a part of this specification. Unless otherwise indicated, the issue in effect on date of invitation for bids shall apply.

CODE OF FEDERAL REGULATIONS

49 CFR 71-78	Transportation, Interstate Commerce Commission, Explosives and Other Dangerous Articles

(Application for copies should be addressed to the Superintendent of Documents, Government Printing Office, Washington, D. C. 20402. Orders for the above publication should cite the latest edition and supplements thereto.)

3. REQUIREMENTS

3.1 General.

3.1.1 The MARK 136 MOD 0 delay cartridge covered by this specification shall be manufactured in accordance with DL 2519923 and all documents listed thereon.

3.2 Materials. All materials used in the manufacture of the cartridges shall conform strictly with the specifications referred to on the respective Naval Air Systems Command drawings unless specific approval in writing covering a departure therefrom has been obtained from the cognizant Navy design activity prior to manufacture. When alternate materials or methods of manufacture are specified on the drawings, the bidder's selections shall be clearly stated in the proposal.

3.2.1 Preproduction sample. Unless otherwise specified by the procuring activity, a preproduction sample of 70 MARK 136 MOD 0 delay cartridges shall be manufactured using the same methods and procedures proposed for the production lot. The sample shall be tested as specified in 4.3.2 and is for the purpose of determining that the contractor, prior to starting production, is capable of producing items which comply with the technical requirements of the contract.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:01Z
Check the source to verify that this is the current version before use.

3.3 Primary components. For the purposes of this specification the primer, M42, Army Ordnance Drawing 8799925, the gasless ignition powder and delay composition, Naval Air Systems Command Drawing 2519925 of DL 2519923, are defined as primary components. See 4.3.3.

3.3.1 Primer. The M42 percussion primer used in the MARK 136 MOD 0 delay cartridge shall be manufactured in accordance with Army Ordnance Drawing 8799925, loaded with primer mixture number 793, and accepted in accordance with the requirements of MIL-P-20444. The primers shall be from lots manufactured within a year past. See 4.7.1.

3.3.1.1 X-ray. Primers shall be free from defects that are questionable from any standpoint, especially cracked or off-center anvils; anvil abnormally close to primer cap dome; charge missing or abnormally thin; charge broken, cracked or porous.

3.3.2 Propellant charge.

3.3.2.1 Quantity. All propellant charges shall be as specified on Naval Air Systems Command Drawings 2299582 and 2519923 of DL 2519923. Charges shall be determined by weight rather than by volume measurements.

3.3.3 Gasless ignition powder. The A-1A gasless ignition powder shall be accepted in accordance with the provisions of MIL-P-22264 and loaded into the cartridge as specified on Naval Air Systems Command Drawing 2519925 of DL 2519923.

3.3.4 Manganese delay composition. The manganese delay composition shall be accepted in accordance with the requirements of MIL-M-21383 and loaded into the cartridge as specified on Naval Air Systems Command Drawing 2519925 of DL 2519923.

3.4 Cartridge inspection.

3.4.1 Visual inspection. The complete cartridge shall be free from dents, deep scratches, split or cracked edges, chipping or flaking of the anodized finish, sharp edges, absence of sealant around crimped areas, or other defects which could conceivably prevent entry into the firing chamber or adversely affect ballistic performance.

3.4.2 Leakage. The rate of air leakage into the completed cartridge shall not exceed 10^{-5} cc/sec at a pressure differential of one atmosphere.

3.4.3 X-ray. Each cartridge shall not contain any observable imperfections in components or assembly when subjected to a radiographic examination.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:01Z
Check the source to verify that this is the current version before use.

3.5 Ballistic requirements. Cartridges from each production lot, selected in accordance with 4.7.6.1, shall meet the requirements listed below when subjected to the test prescribed in 4.7.6.1.

3.5.1 Delay time. The upper and lower limits of delay time shall be 0.30 second and 0.15 second, respectively.

3.5.2 Maximum pressure. The lower limit of maximum pressure shall be 380 psi.

3.5.3 Misfire. There shall be no misfires. See 4.7.6.2.2.

3.6 Workmanship. Cartridges shall be constructed and finished in a manner to assure compliance with all requirements of this specification. Particular attention should be directed to dimensions, finishes, coatings and quality of crimping and staking operations.

4. QUALITY ASSURANCE PROVISIONS

4.1 Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may utilize his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Sampling. Unless otherwise specified, and when applicable, the sampling plans and procedures used in the determination of the acceptability of products submitted by a supplier shall be in accordance with the provisions of MIL-STD-105.

4.3 Lots.

4.3.1 Inspection lots. Inspection lot definition, formation, and size shall be in accordance with paragraph 5 of MIL-STD-105.

4.3.2 Preproduction sample. Before entering into quantity production, an acceptable preproduction sample of 70 MARK 136 MOD 0 delay cartridges shall be prepared. Of these cartridges 60 shall be expended in the tests listed below and ten shall be retained for investigative purposes. A preproduction sample acceptable for environmental and functional testing shall be defined as a sample which has met the requirements of paragraphs 3.1 through 3.4 of this specification. The contractor shall deliver the

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:01Z
Check the source to verify that this is the current version before use.

cartridges to the activity designated by the contracting agency for test. Preproduction sample acceptance shall consist of the following tests as prescribed in MIL-D-21625: 40-foot drop test (6); 14-day temperature and humidity cycling (18); vibration (12); low temperature (12); and high temperature (12). The number in parentheses denotes the number of cartridges allocated for test. With the exception of the 40-foot drop test sample, each cartridge shall be fired in the test device of 4.7.6.1. The preproduction sample shall be accepted if the sample fulfills the requirements of 3.5.1, 3.5.2 and 3.5.3. Any quantity production prior to notification by the contracting agency of preproduction sample acceptability shall be at the contractor's risk. The preproduction cartridges will not be applied as a part of the quantity specified for delivery by the contract.

4.3.3 Production lot. The minimum production lot size shall be 151 cartridges. Cartridges required for all test purposes are selected from the production lot and will not be applied as a part of the quantity specified for delivery by the contract. Only primary components from a single lot shall be used in a production lot of cartridges. One primary component production lot may be used in more than one cartridge production lot. Cartridges selected for the ballistic test shall be delivered to the activity designated by the contracting agency.

4.4 Gages. The contractor shall provide himself with gages as necessary to insure that the material to which this specification applies will meet the dimensional requirements shown on the applicable drawings.

4.5 Classification of characteristics. The characteristics verified by the tests and examinations herein are classified as Critical, Major or Minor in accordance with WR-43. Tests and examinations that verify critical characteristics are identified by the symbol (C) and major characteristics by the symbol (M). The number following the classification symbol indicates the serial number of test or examination. Tests and examinations which are not annotated with a classification code are classified minor.

4.6 Quality conformance inspection. Quality conformance inspection shall consist of verification of the characteristics classified on the drawings of DL 2519923 and the following tests and examinations.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:01Z
Check the source to verify that this is the current version before use.

Item	Nature of Test	Requirement	Test	Classification (WR-43)
Primary Component	Single lot verification	3.3	4.3.3	(M101)
Primer	Age, primer mixture, and acceptance verification	3.3.1	4.7.1	(C1)
Primer	X-ray	3.3.1.1	4.7.2	(C2)
Propellant	Type and weight verification	3.3.2.1	-----	(C3)
Ignition Powder	Acceptance and loading verification	3.3.3	------	(C4)
Delay Composition	Acceptance and loading verification	3.3.4	------	(C5)
Cartridge	Visual inspection	3.4.1	4.7.3	(M102)
Cartridge	Leakage	3.4.2	4.7.4	(C6)
Cartridge	X-ray	3.4.3	4.7.5	(C7)
Cartridge	Ballistic requirements	3.5	4.7.6	(C8)

4.6.1 Packing, packaging, and marking. (M103) The inspector shall ascertain that the packing and packaging and the container markings conform to Section 5 of this specification.

4.7 Tests.

4.7.1 Primer verification. Verification shall be obtained that the primers to be used were manufactured within a year past and were furnished from lots certified by the supplier to have been loaded in accordance with 3.3.1 and accepted in accordance with the provisions of MIL-P-20444.

4.7.2 Primer X-ray. Examine all primers by X-ray. Primers should be mounted in suitable grooved racks. For the most revealing exposure, the primers are laid on their side with the anvil cutouts vertical. Pressure-sensitive tape may be used as an aid in positioning the primers. Reject any primers that fail to meet the requirements of 3.3.1.1.

4.7.3 Visual inspection. Examine all cartridges visually and reject any that fail to meet the requirements of 3.4.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:01Z
Check the source to verify that this is the current version before use.

4.7.4 Leakage. Each cartridge in the preproduction and production samples will be tested in a dry gas leak tester. If one or more cartridges of the applicable sample fail to meet the leakage rate requirement of 3.4.2, then a leak test of each cartridge in the lot shall be required. Cartridges which exhibit a leakage rate in excess of that specified in 3.4.2 shall be rejected and shall not be a part of the quantity specified for delivery in the contract or order.

4.7.5 X-ray examination. Examine all cartridges by X-ray to determine conformance to 3.4.3, and reject defective cartridges. X-ray plates may be destroyed after ballistic acceptance of the cartridges.

4.7.6 Functional test. The number of cartridges selected from each production lot for the functional test shall be in accordance with the requirements of MIL-STD-105, Inspection Level II, AQL 0.15. The cartridges shall be conditioned at + 70°F for a minimum of six hours and fired in a closed bomb test fixture, Naval Air Systems Command DL 2838169. Instrumentation shall be provided to measure the maximum pressure and the time from sear removal from the firing mechanism to first indication of pressure. In addition to the sample of cartridges for the above test, ten additional cartridges shall be furnished from the production lot for investigative purposes.

4.7.6.1 Criteria of acceptability. The total number of defective units in the production sample shall not exceed the acceptance number specified in the single sampling plan table of MIL-STD-105 for normal inspection at an AQL of 0.15. Any cartridge containing one or more of the following defects shall be classified as a defective unit.

4.7.6.1.1. Defects.

4.7.6.1.1.1 Delay time. Delay time is defined at the time interval from sear removal to the first indication of pressure rise in the bomb chamber. Failure to meet the requirements of 3.5.1 shall constitute a defect.

4.7.6.1.1.2 Maximum pressure. Failure to meet the requirement of 3.5.2 shall constitute a defect.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:01Z
Check the source to verify that this is the current version before use.

4.7.6.2 Misfire. The failure of any cartridge to fire shall result in rejection of the lot represented, unless such failure is plainly attributable to faulty test equipment or procedure.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging. For definitions of packaging levels, see 6.4.

5.1.1 Level A. Level A packaging shall be used for packaging of all production lots for service use. Two cartridges shall be packaged in an inner container in accordance with Bureau of Naval Weapons Drawing 2518488 of PL 2518489.

5.1.2 Level B. Not applicable.

5.1.3 Level C. When directed by the procuring activity, those cartridges which are intended for expenditure in preproduction sample testing and for production lot acceptance tests shall be packaged in accordance with Method III of MIL-P-116 and with the Code of Federal Regulations 49 CFR 71-78.

5.2 Packing. For definitions of packing levels, see 6.4.

5.2.1 Level A. Level A packing shall be used for packing of all production lots for service use. Six inner containers as described in 5.1.1 shall be packed in accordance with Bureau of Naval Weapons Drawing 2518489 of PL 2518489.

5.2.2 Level B. Not applicable.

5.2.3 Level C. When directed by the procuring activity, cartridges intended for expenditure in preproduction sample testing and for production lot acceptance tests and are packaged in accordance with 5.1.3 shall be packed to afford protection against damage during direct shipment from the supply source to the first receiving activity for immediate use. Shipping containers shall be in accordance with the Code of Federal Regulations 49 CFR 71-78.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:01Z
Check the source to verify that this is the current version before use.

5.3 Markings.

5.3.1 Special markings. Marking of exterior containers shall be in accordance with the Code of Federal Regulations 49 CFR 71-78.

5.3.2 Normal markings. In addition to the markings required by contract or order, and as specified on Bureau of Naval Weapons Drawings 2518488 and 2518489 of PL 2518489, unit packages and shipping containers shall be marked in accordance with the requirements of MIL-STD-129.

6. NOTES

6.1 Intended use. The MARK 136 MOD 0 delay cartridge was orignially designed to actuate the parachute static line cutter, Propellex P/N 52-3, for the OV-10A aircraft.

6.2 Ordering information. Procurement documents should specify the following:

a. title, number and date of this specification

b. whether preproduction inspection is required, and if so, specify the test activity;

c. production lot size and test activity (see 4.3.3);

d. items of data required for each production and production lot (see 6.3).

6.3 Data. For the information of Contractors and Contracting Officers, any of the data specified in (a) subparagraphs below, (b) applicable documents listed in Section 2 of this specification or (c) referenced lower-tier documents need not be prepared for the Government unless specified in the contract or order. The data to be furnished shall be listed on DD Form 1423 (Contractor Data Requirements List) which shall be attached to and made a part of the contract or order. NAVWEPS Form 4200/15 (Drawings, Lists and Specifications Required) shall be attached where applicable.

6.3.1 Test report. Results of ballistic tests shall be forwarded to the Naval Air Systems Command and the procuring activity.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:01Z
Check the source to verify that this is the current version before use.

6.3.2 Data cards. The contract or order should state the format, quantity and destination of data cards.

6.4 Definitions. The definitions of Levels A and C packaging and packing given below were extracted from BUSANDA Instruction 4030.17.

6.4.1 Level A packaging. The degree of preservation and packaging which will afford adequate protection against corrosion, deterioration and physical damage during handling, shipment, indeterminate storage and world-wide redistribution.

6.4.1.1 Level C packaging. The degree of preservation and packaging which will afford adequate protection against corrosion, deterioration and physical damage during shipment from supply source to the first receiving activity for immediate use. This level may conform to supplier's commercial practice when such meets the requirements of this level.

6.4.2 Level A packing. The degree of packing which will afford adequate protection during shipment, handling, indeterminate storage and world-wide redistribution.

6.4.2.1 Level C packing. The degree of packing which will afford protection against damage during direct domestic shipment from the supply source to the first receiving activity for immediate use. This level in general will conform to applicable carrier rules and regulations and may be the supplier's commercial practice when such meets the requirement of this level.

6.5 Explosives safety precautions.

6.5.1 Applicability. The loading, assembly and handling of the explosives, subassemblies and the finished items covered by this specification involve hazardous operations and therefore require suitable explosive safety precautions. At plants of the Naval Air Systems Command, Department of the Navy, and other Government plants where the Government is responsible for safety, the precautions listed below are mandatory. These same minimum provisions are recommended for observance by a contractor or manufacturer that explosively loads the item covered in this specification in order to fulfill his own safety responsibility. Other warnings and precautions, pertaining to the operational effectiveness or safety of the specified item during its use (for example, during its handling, launching or firing), are included in the detailed technical requirements of the specification. Use of this specification shall not be construed to replace other safety regulations of governmental agencies or to

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:01Z
Check the source to verify that this is the current version before use.

relieve the contractor or manufacturer of responsibility for the safety of his operations.

6.5.2 Personnel and equipment. Proper care must be exercised at all times to protect personnel from accidents, fires or explosions and to limit damage to equipment and loading areas. In connection with the above, the precautionary measures in the following paragraphs should be observed. (See also paragraph 6.5.4, Static and electrical and other applicable parts of these safety precautions.)

6.5.2.1 Explosives operations shall be kept under strict supervision. Periodic inspections shall be employed to assure compliance with established safety regulations.

6.5.2.2 Safe equipment and methods should be utilized for handling and transporting explosives and loaded parts.

6.5.2.3 Where required, remote control-barricaded-handling equipment shall be used for explosives operations such as mixing, pouring, weighing, charging, sifting, drying, pressing, casting, crimping, etc.

6.5.2.4 Employ properly proportioned and properly located protective barricades, screens or shields at all required points.

6.5.2.5 Maintain equipment such as presses, dies, crimpers, blenders, mixers, sifters, conveyors, and the like in safe operating condition.

6.5.2.6 Enforce, where necessary, the wearing of suitable safety footwear, gloves, goggles, respirators, and impregnated garments to protect personnel against burns, poisioning and associated industrial hazards.

6.5.2.7 During static tests, propulsion units such as rocket motors shall be restrained aginst full thrust to prevent flight if ignited, for example, during test of igniter circuit. Also, means shall be provided to harmlessly vent flames and exhaust gases.

6.5.3 Operating procedures. All loading operations shall be conducted in full accordance with a formalized operating procedure which shall include the following:

6.5.3.1 Keep only minimum, limited quantities of explosives and completed or partially loaded parts present at each stage of operation.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:01Z
Check the source to verify that this is the current version before use.

6.5.3.2 Allow no fires, exposed electrical or other sparking equipment, and little or no flammable material to be present in loading, handling and storage spaces. Enforce proper "Match" and "No Smoking" rules where necessary.

6.5.3.3 Appropriate safety instructions for specific operations shall be posted and personnel instructed as to the hazards present and precautions involved.

6.5.3.4 The number of working personnel and transients permitted in each work space shall be established and posted in such areas. The numbers shall be the minimum number required to accomplish necessary operations.

6.5.3.5 All loading operations should be conducted in a neat and orderly manner.

6.5.3.6 Enforce good housekeeping and maintain effective policing, inspection and supervisory methods throughout the loading area and surroundings.

6.5.3.7 Employ effective cleaning methods periodically to minimize the accumulation of explosives or explosive dust and other contamination upon, and assure its removal from, floors, walls, ceiling, ledges, tables, benches, piping, and equipment or the items loaded. Clean up any spilled material immediately.

6.5.3.8 The exposure of explosive materials and related parts should be so controlled as to minimize the absorption of moisture from the atmosphere or other sources during loading and handling operations.

6.5.3.9 Personnel handling detonators, primers, delay elements, lead-ins, boosters, and related parts which affect functioning should, insofar as practicable, avoid using bare fingers or improper equipment in order to prevent damage, corrosion, or deterioration from perspiration or other contaminating deposits.

6.5.3.10 Keep explosives and explosive parts in approved covered receptacles with covers in place when material is not being taken out or put into the receptacles. Where necessary, receptacles should be conductive to ground electrostatic charges. (See paragraphs 6.5.4.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:01Z
Check the source to verify that this is the current version before use.

6.5.4 Static and electrical.

6.5.4.1 Protect operations from electrostatic charges by effectively grounding all machinery, equipment, and fixtures; and where necessary, employ suitable grounded conductive coverings for floors, work benches and tables, and worker's conductive shoes. Workers' clothing of a type to minimize the accumulation of static charges shall be employed. Fabrics, such as silk and nylon, which generate static electricity shall be avoided. Additional grounding devices, such as grounded bracelets for workers, should be employed where operations are conducted with items which are unusually sensitive to initiation by static electricity. Such items include initiating explosives, tracer mixtures, and low energy type of electric primers, detonators and squibs. The latter types of items shall have the free ends of lead wires bared and twisted together and be packed in relatively small groups wrapped in bare non-insulated aluminum foil or other uncoated metal foil. During assembly and processing operations, such sensitive electric items should be short circuited by clips or other devices until installed with safety shunt in the final device. Additional precautions for these items should include mechanical shielding to contain or deflect fragments and blast; also electrical shielding from induced electric currents originated by sources such as lightning, static, electromagnetic radiations, etc. Where necessary for safety, humidity of work rooms should be appropriately increased, as required to lessen electrostatic effects, but without inducing excessive moisture absorption by and of the components of the item being processed.

6.5.4.2 Protect all explosive operations from the effects of electric currents originating in equipment (such as soldering irons or guns, heaters, switches, wiring, motors, lights, test instruments, etc.) by suitable insulation, grounding, separation or shielding. Such electric sources may initiate explosives by heat, sparks, arcs, or by completing an electric circuit through an electric primer, detonator or squib. For example, circuits may be inadvertently completed from a defective electric soldering iron through a grounded contact. All electric types of primers, detonators or squibs provided with wire leads shall have the free ends of the wires bared and twisted together to short circuit each unit, except when in process or assembly into a finished item. Removable short circuiting clips or other devices should be employed during manufacturing operations involving items such as electric primers, detonators or squibs.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:01Z
Check the source to verify that this is the current version before use.

6.5.4.3 Where necessary, protect personnel and operations from electromagnetic energy. In certain work with very sensitive explosives or items, a shielded environment free from significant electromagnetic energy should be provided.

6.5.5 Operating facility and storage regulations.

6.5.5.1 All explosives including partially loaded items should be stored in suitable storage magazines located in accordance with the minimum distances prescribed in the American Table of Distances (ATD). While the explosive or loaded items are in process, stored in loading rooms, or in ready or servicesmagazines, they would be located in accordance with Intraplant Distances set forth in the ATD. For Navy managed or contractor managed-Navy owned-explosives loading plants, the Armed Services Explosives Safety Board standards approved by the Department of Defense, the Secretary of the Navy and the Naval Air Systems Command covering quantity-distance regulations for explosives apply.

PROJECT NO. 1377-N351

☆U.S. GOVERNMENT PRINTING OFFICE: 1969-393-088/S222

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:01Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity *(as indicated on reverse hereof)*.

SPECIFICATION
MIL-C-81730(AS) CARTRIDGE, DELAY, MARK 136 MOD 0

ORGANIZATION *(Of submitter)* | CITY AND STATE

CONTRACT NO. | QUANTITY OF ITEMS PROCURED | DOLLAR AMOUNT
$

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES.

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)* | DATE

DD, FORM 1 APR 63 1426

C-8378

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:01Z
Check the source to verify that this is the current version before use.